US Patent & Trademark Office Patent Public Search | Text View

United States Patent

Kind Code

Date of Patent

Inventor(s)

12388198

B2

August 12, 2025

Gebhardt; Martin et al.

Connection arrangement employing a clamping spring and actuator

Abstract

A connection arrangement for connecting an electrical conductor includes: a housing; a busbar; a clamping spring including a clamping leg transferrable into a clamping position and into a release position; an actuator by which a compressive force is applicable to the clamping leg for transferring the clamping leg from the clamping position into the release position; a conductor connection space formed between a section of the busbar and of the clamping leg of the clamping spring; a displaceably arranged guide element in operative connection with the clamping leg of the clamping spring, the clamping leg being holdable in the release position by the guide element; and a release element, which in the release position of the clamping leg of the clamping spring is in engagement with the guide element. The release element, during insertion of the conductor to be connected into the conductor connection space, actuates by the insertion.

Inventors: Gebhardt; Martin (Lage, DE), Hoppmann; Ralph (Bad Oeynhausen,

DE)

Applicant: Phoenix Contact GmbH & Co. KG (Blomberg, DE)

Family ID: 1000008748029

Assignee: PHOENIX CONTACT GMBH & CO. KG (Blomberg, DE)

Appl. No.: 17/799937

Filed (or PCT

February 16, 2021

Filed):

PCT No.: PCT/EP2021/053698

PCT Pub. No.: WO2021/165220

PCT Pub. Date: August 26, 2021

Prior Publication Data

Document Identifier Publication Date

US 20230064800 A1 Mar. 02, 2023

Foreign Application Priority Data

DE 10 2020 104 138.1 Feb. 18, 2020

Publication Classification

Int. Cl.: H01R4/48 (20060101)

U.S. Cl.:

CPC **H01R4/4833** (20230801); **H01R4/484** (20230801); H01R4/4821 (20230801)

Field of Classification Search

CPC: H01R (4/4833); H01R (4/484); H01R (4/4821)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7115001	12/2005	Brockman et al.	N/A	N/A
9614301	12/2016	Ludewig	N/A	H01R 4/4833
10658766	12/2019	Herrmann	N/A	H01R 4/4833
2007/0099479	12/2006	Holterhoff et al.	N/A	N/A
2018/0331449	12/2017	Juelich et al.	N/A	N/A
2019/0190168	12/2018	Witte et al.	N/A	N/A
2022/0209435	12/2021	Fehling et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1213024	12/1965	DE	N/A
202006009460	12/2006	DE	N/A
202013100740	12/2012	DE	N/A
202014103797	12/2013	DE	N/A
102015118574	12/2016	DE	N/A
202017103185	12/2016	DE	N/A
202016104971	12/2016	DE	N/A
102016115601	12/2017	DE	N/A
202019101246	12/2018	DE	N/A
H05135809	12/1992	JP	N/A

Primary Examiner: Girardi; Vanessa

Attorney, Agent or Firm: LEYDIG, VOIT & MAYER, LTD.

Background/Summary

CROSS-REFERENCE TO PRIOR APPLICATIONS

- (1) This application is a U.S. National Phase application under 35 U.S.C. § 371 of International Application No. PCT/EP2021/053698, filed on Feb. 16, 2021, and claims benefit to German Patent Application No. DE 10 2020 104 138.1, filed on Feb. 18, 2020. The International Application was published in German on Aug. 26, 2021 as WO/2021/165220 under PCT Article 21(2). FIELD
- (2) The invention relates to a connection arrangement for connecting an electrical conductor. The invention further relates to an electronic device.

BACKGROUND

(3) Such connection arrangements usually have a clamping spring designed as a leg spring, which clamping spring has a retaining leg and a clamping leg, wherein a conductor inserted into the connection arrangement can be clamped against the busbar by means of the clamping leg of the clamping spring. If, in particular, flexible conductors are being clamped, the clamping spring must have already been moved, before insertion of the conductor, into a release position by means of an actuating means and thus be actuated in order to pivot the clamping spring or the clamping leg away from the busbar, so that the conductor can be inserted into the intermediate space between the busbar and the clamping spring. Only in the case of rigid and thus robust conductors can the conductor apply sufficient force to the clamping spring or the clamping leg of the clamping spring, in order to be able to pivot the clamping leg away from the busbar, without the actuating means having to be actuated for this purpose by a user. With flexible conductors, the user must first pivot the clamping spring away from the busbar by actuating the actuating means, so that the flexible conductor can be inserted. In order to clamp the inserted conductor, the actuating means must be manually actuated once more by the user in order to transfer the clamping spring from the release position into the clamping position. Actuating the actuating means by the user makes mounting or connecting the conductor more difficult for the user, since the handling is inconvenient and the time required increases as well.

SUMMARY

(4) In an embodiment, the present invention provides a connection arrangement for connecting an electrical conductor, comprising: a housing; a busbar; a clamping spring comprising a clamping leg transferrable into a clamping position and into a release position; an actuator by which a compressive force is applicable to the clamping leg for transferring the clamping leg from the clamping position into the release position; a conductor connection space formed between a section of the busbar and of the clamping leg of the clamping spring; a displaceably arranged guide element in operative connection with the clamping leg of the clamping spring, the clamping leg being holdable in the release position by the guide element; and a release element, which in the release position of the clamping leg of the clamping spring is in engagement with the guide element, wherein the release element, during insertion of the conductor to be connected into the conductor connection space, is actuatable by the insertion such that the release element comes out of engagement with the guide element, and wherein the guide element is displaceable by a spring force of the clamping leg such that the clamping leg is transferrable into the clamping position to clamp the conductor against the busbar.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present invention will be described in even greater detail below based on the exemplary figures. The invention is not limited to the exemplary embodiments. Other features and advantages of various embodiments of the present invention will become apparent by reading the following

- detailed description with reference to the attached drawings which illustrate the following:
- (2) FIG. **1** is a schematic representation of a connection arrangement according to the invention with the clamping leg of the clamping spring in a clamping position,
- (3) FIG. **2** is a schematic representation of the connection arrangement shown in FIG. **1** with the clamping leg of the clamping spring in a release position,
- (4) FIG. **3** is a schematic representation of a further connection arrangement according to the invention with the clamping leg of the clamping spring in a clamping position,
- (5) FIG. 4 is a schematic sectional representation of the connection arrangement shown in FIG. 3,
- (6) FIG. **5** is a schematic representation of the connection arrangement shown in FIG. **3** with the clamping leg of the clamping spring in a release position, and
- (7) FIG. **6** is a schematic sectional representation of the connection arrangement shown in FIG. **5**. DETAILED DESCRIPTION
- (8) In an embodiment, the present invention provides a connection arrangement and an electronic device with which connecting, in particular, of flexible conductors can be simplified.
- (9) The connection arrangement according to the invention has a housing, a busbar, a clamping spring, which has a clamping leg that can be transferred into a clamping position and into a release position, an actuating means by means of which a pressure force can be applied to the clamping leg in order to transfer the clamping leg from the clamping position into the release position, a conductor connection space formed between a section of the busbar and of the clamping leg of the clamping spring, a displaceably arranged guide element, which is in operative connection with the clamping leg of the clamping spring, wherein the clamping leg can be held in the release position by means of the guide element, and a release element that in the release position of the clamping spring is in engagement with the guide element. When the conductor to be connected is being inserted into the conductor connection space, the release element can be actuated by the said conductor in such a way that the release element comes out of engagement with the guide element and the guide element can be displaced by a spring force of the clamping leg in such a way that the clamping leg is transferred into the clamping position in order to clamp the conductor against the busbar.
- (10) By means of the connection arrangement according to the invention, even a flexible conductor can now be connected in a directly pluggable manner and can be clamped against the busbar. The clamping spring is preferably designed as a leg spring, which has a retaining leg and a clamping leg designed to be pivotable relative to the retaining leg. By means of a pivoting movement of the clamping leg, the clamping leg can be transferred into a release position, in which the clamping leg is arranged at a distance from the busbar and a conductor that is to be connected can be guided into or out of a conductor connection space formed thereby between the busbar and the clamping leg, and into a clamping position, in which the clamping leg can rest against the busbar or against the connected conductor in order to clamp the conductor against the busbar. The connection arrangement has a guide element that is mounted in particular horizontally displaceably and that is in particular operatively connected to the clamping spring in the release position of the clamping leg of the clamping spring, which means that the clamping leg, due to the operative connection with the guide element, follows the displacement movement and thus the position of the guide element. The guide element holds the clamping leg in the release position against its spring force in that the guide element presses against the clamping leg. To be able to hold the guide element in this position, the guide element is in engagement with the release element in the release position of the clamping leg of the clamping spring. When the release element is in engagement with the guide element, a displacement movement of the guide element is not possible or is stopped. Via an operative connection or coupling of the release element to the guide element and of the guide element to the clamping leg of the clamping spring in the release position of the clamping leg, the clamping leg can be held in this release position without additional manual actuation, so that in particular a flexible conductor can be inserted into the conductor connection space thereby free

between the busbar and the clamping spring. The release element can have a pressure surface pointing in the direction of the conductor connection space, which is arranged flush with a conductor insertion opening for insertion of the conductor into the connection arrangement or flush with the conductor connection space, so that the conductor strikes the pressure surface of the release element during its insertion into the connection arrangement, as a result of which a compressive force can be applied by the conductor to the release element. By applying a compressive force to the pressure surface by means of the conductor and thus to the release element, the release element can, for example, be brought into a pivoting movement or tilting movement in the direction of the insertion direction of the conductor, so that the release element can be pivoted or tilted away from the guide element in the insertion direction of the conductor. As a result of the pivoting movement of the release element, the release element can be brought out of engagement with the guide element so that the guide element is freely displaceable again and the guide element can thereby be displaced solely by the spring force of the clamping leg, without manual assistance, in such a way that the clamping leg can be transferred from the release position into the clamping position. By means of this special mechanism, a flexible conductor can be connected in a particularly simple manner solely by the insertion movement of the conductor, without a user needing to actuate further elements, such as an actuating means, in order to release the clamping spring and transfer it from the release position into the clamping position. This facilitates the handling of the connection arrangement and saves time when connecting a conductor. The release element is preferably an element formed separately from the clamping spring, the busbar and the guide element. The release element preferably extends over the region between the clamping spring and the section of the busbar against which a conductor can be clamped, so that the release element can delimit the conductor connection space to one side. The guide element can take the form of a slide element. The transfer of the clamping leg of the clamping spring from the clamping position into the release position takes place by means of an actuating means in that a pressure force is applied to the clamping leg by means of the actuating means, whereby the clamping leg can be pivoted away from the busbar. For actuation of the clamping spring, the actuating means thus acts directly on the clamping leg of the clamping spring. However, the actuating means is preferably only used for the transfer of the clamping leg from the clamping position into the release position, but not for the transfer of the clamping leg from the release position into the clamping position.

- (11) In order to be able to form an operative connection between the guide element and the clamping leg of the clamping spring, it can be provided that the guide element has at least one spring contact edge against which the clamping leg can rest. The spring contact edge can be designed in such a way that both in the release position and in the clamping position, the clamping leg or at least a part of the clamping leg can rest against the spring contact edge. The spring contact edge preferably extends in the insertion direction of the conductor into the connection arrangement. The spring contact edge thus extends preferably transversely to the direction of displacement of the guide element. Depending on the size of the diameter of the inserted and clamped conductor, at least a part of the clamping leg can rest against the spring contact edge even in the clamping position.
- (12) In order to be able to achieve a uniform guidance of the guide element and of the clamping leg of the clamping spring, two such spring contact edges can be formed on the guide element so that the clamping leg can be guided on the guide element via two such spring contact edges. The two spring contact edges preferably extend in parallel to one another on the guide element.

 (13) With such a design, it is possible for the clamping leg to have two slide sections each arranged
- laterally in relation to a main section having a clamping leg to have two slide sections each arranged two spring contact edges arranged at a distance from one another, wherein a first slide section can rest against a first spring contact edge and a second slide section can rest against a second spring contact edge. The two slide sections preferably each have a shorter length than the main section of

the clamping leg. The main section and the two slide sections preferably extend in parallel to one another. The two slide sections are preferably each curved so that they can each form a skid, which can slide along a respective spring contact edge. However, the main section is preferably straight. (14) If, in order to transfer the clamping leg from the clamping position to the release position by means of the actuating means, a compressive force on the clamping leg is carried out, the compressive force will preferably be transmitted from the clamping leg of the clamping spring to the guide element, so that the guide element will also be displaced away from the busbar by a pivoting movement of the clamping leg until the guide element is able to engage with the release element. For this purpose, the guide element can have a counter-contact edge, onto which the clamping leg can apply a force to the guide element during the transfer from the clamping position into the release position. During the transfer from the clamping position into the release position, the clamping leg can thus press against the counter-contact edge in order to move the guide element. The guide element can thus follow the movement of the clamping leg during transfer of the clamping leg from the clamping position into the release position. The clamping leg can preferably apply a force to the guide element via its slide section.

- (15) The guide element preferably has two counter-contact edges arranged at a distance from one another and even the clamping leg preferably has two slide sections, so that the two slide sections of the clamping leg can be pressed simultaneously against the two counter-contact edges of the guide element in order to move the guide element from the clamping position into the release position during the movement of the clamping leg.
- (16) The at least one counter-contact edge is preferably arranged opposite the at least one spring contact edge. Depending on the movement of the clamping leg, the clamping leg or a slide section of the clamping leg can thus rest alternately against the spring contact edge and against the countercontact edge of the guide element.
- (17) The at least one guide element can have a slot-shaped recess, wherein the at least one spring contact edge and the at least one counter-contact edge can be formed in the region of the at least one slot-shaped recess. The slot-shaped recess preferably extends into the guide element. A part of the clamping leg, in particular a slide section of the clamping leg, can be immersed in and guided within the slot-shaped recess. The guide element preferably has two slot-shaped recesses arranged opposite each other, on each of which a spring contact edge and a counter-contact edge are formed, so that the two slide sections of the clamping leg can be symmetrical to one another in engagement with the guide element via the two slot-shaped recesses. Both the spring contact edge and the counter-contact edge can each form a partial section of a boundary wall of the slot-shaped recess. (18) The guide element is preferably displaceable in such a way that a displacement movement of the guide element into the conductor connection space can take place, said movement being transverse to an insertion direction of the conductor to be connected. In this way, a particularly compact design is possible, as a result of which the connection arrangement can be characterized by a reduced installation space.
- (19) In order to release the release element from the guide element by means of the conductor inserted into the conductor connection space and to thus be able to bring it out of engagement with the guide element, the release element can be mounted so as to be tiltable relative to the guide element. The release element can thus be designed like a rocker. If the conductor to be connected is pressed against the release element, the release element can tilt in the insertion direction of the conductor in order to come out of engagement with the guide element and thus release the guide element so that the latter is again freely displaceable.
- (20) In order to be able to form an engagement of the release element with the guide element in the release position of the clamping leg of the clamping spring, the release element can have at least one undercut with which at least one latching lug of the guide element can latch when the clamping leg of the clamping spring is in the release position. As a result, a latching connection can be formed between the guide element and the release element when the clamping leg of the clamping

spring is in the release position. The release element preferably has two undercuts and the guide element preferably has two latching lugs so that a double-acting latching can be formed between the guide element and the release element. If two undercuts are provided, they are preferably formed on two side faces of the release element running in parallel to one another. The release element can have a T-shape in the region of the two undercuts.

- (21) It can preferably also be provided that the guide element has two longitudinal side walls arranged parallel to each other, which can delimit the conductor connection space on a first side and on a second side opposite the first side. The guide element can thus also form a guide for the conductor to be connected when the latter is being inserted into the conductor connection space. The two longitudinal side walls can prevent incorrect insertion of the conductor. The conductor connection space can thus be delimited on two of its sides by the guide element and on its other two sides by the busbar and by the clamping leg of the clamping spring. The spring contact edge and/or the counter-contact edge can be formed on the two longitudinal side walls.
- (22) The actuating means can be, for example, a tool, such as a screwdriver, which, if necessary, can be inserted into the housing of the connection arrangement in order to transfer the clamping leg of the clamping spring from the clamping position into the release position. For this purpose, the housing can have an opening via which the actuating means can be inserted into the housing in order to actuate the clamping leg of the clamping spring.
- (23) The opening for inserting the actuating means is preferably arranged between a conductor insertion opening formed on the housing and a bearing point of the clamping spring in the housing. In the inserted state, the actuating means is then preferably positioned between the section of the busbar against which the conductor is clamped and the clamping spring. The bearing point can be a receptacle for the arcuate section of the clamping spring between the clamping leg and the retaining leg of the clamping spring.
- (24) Furthermore, it is possible for the actuating means to be integrated into the housing and not to be a tool that is additionally to be inserted. The actuating means can then be mounted in the housing and can be linearly guided in a guide opening formed in the housing in order to pivot the clamping leg from the clamping position into the release position.
- (25) The actuating means can be designed such that it surrounds the clamping spring in a U-shape. In particular in the region of the arcuate section of the clamping spring, the actuating means can surround or overlap the clamping spring. The actuating means can thus surround the clamping spring in the form of a hood.
- (26) The actuating means can have a first actuating finger and a second actuating finger opposite the first actuating finger, wherein a side wall of the actuating means can extend between the first actuating finger and the second actuating finger, which side wall can laterally cover the clamping spring at least in regions. If the housing is designed to be open on one side, the clamping spring can be held in its position at the bearing point via the actuating means or the side wall of the actuating means, so that the clamping spring can be prevented from slipping out of the housing. The first actuating finger preferably serves to actuate the clamping leg of the clamping spring. The second actuating finger preferably covers a partial section of the retaining leg of the clamping spring. When the clamping spring is actuated by means of the actuating means, the actuating means can exert a force on the clamping leg via its first actuating finger and the second actuating finger can be guided simultaneously along the retaining leg.
- (27) The connection arrangement can form, for example, a connection terminal in the form of a terminal block that can be snapped onto a mounting rail, for example. Furthermore, the connection arrangement can also form a connection terminal that can be arranged, for example, on a printed circuit board.
- (28) It is also possible for a connection terminal arrangement to be provided, which can have a plurality of connection terminals arranged in a row, each of which can have at least one connection arrangement formed and developed as described above.

- (29) In an embodiment the present invention also provides an electronic device that can have at least one connection arrangement formed and further developed as described above.
- (30) FIGS. **1** to **6** show two different connection arrangements **100**. The two connection arrangements **100** have a housing **140** that can be made of an insulating material. Except for the actuating means **129**, the two connection arrangements shown in FIGS. **1** to **6** are of identical design.
- (31) A busbar **110** and a clamping spring **111** designed as a leg spring are arranged In the housing **140**. The clamping spring **111** has a retaining leg **112** and a clamping leg **113**. The retaining leg **112** is connected to the clamping leg **113** via an arcuate section **141**. The retaining leg **112** is held in a fixed position, whereas the clamping leg **113** is pivotable relative to the retaining leg **112**. By a pivoting movement of the clamping leg **113**, the latter can be transferred into a clamping position, as shown in FIGS. **1**, **3** and **4**, and into a release position, as shown in FIGS. **2**, **5** and **6**. (32) In the clamping position, the clamping leg **113** presses against a section **114** of the busbar **110** or against a conductor inserted into the connection arrangement **100**, in order to clamp said conductor against the section **114** of the busbar **110** and connect the same. In the release position, the clamping leg **113** is positioned at a distance from the section **114** of the busbar **110**, so that a conductor can be inserted into the free space thus formed that forms the conductor connection
- (33) The connection arrangement **100** furthermore has a guide element **115**. The guide element **115** is mounted displaceably in particular with respect to the busbar **110** so that the guide element **115** can perform a horizontal displacement movement V.

space **124** and lies between the section **114** of the busbar **110** and the clamping leg **113**.

- (34) The clamping leg **113** of the clamping spring **111** can be held in the release position by means of the guide element **115**. For this purpose, the guide element **115** is operatively connected to the clamping leg **113** of the clamping spring **111**.
- (35) In the developments shown here, the guide element **115** has two spring contact edges **116***a*, **116***b*, which are arranged parallel to one another and against which the clamping leg **113** rests. (36) The clamping leg **113** has a main section **117**, on the free end of which a clamping edge **118** is formed, as can be seen in the sectional views of FIGS. **4** and **6**, in which a connection arrangement **100** is shown, which is identical to the embodiment shown in FIGS. **1** and **2** as regards the clamping spring **111** and the guide element **115**. Two slide sections **119***a*, **119***b* are formed laterally in relation to the main section **117** so that the main section **117** is arranged between the two slide sections **119***a*, **119***b*. The two slide sections **119***a*, **119***b* rest against the two spring contact edges **116***a*, **116***b* of the guide element **115** at least in the release position and during the transfer from the release position into the clamping position, wherein the slide section **119***a* rests against the spring contact edge **116***b*.
- (37) The slide sections **119***a*, **119***b* have a shorter length than the main section **117**. The slide sections **119***a*, **119***b* are curved so that they form a skid shape, by means of which the slide sections **119***a*, **119***b* can slide along the spring contact edges **116***a*, **116***b* when the clamping leg **113** is being transferred into the clamping position.
- (38) The two spring contact edges **116***a*, **116***b* are formed on opposite longitudinal side walls **120***a*, **120***b* of the guide element **115**. The two longitudinal side walls **120***a*, **120***b* are arranged in parallel to one another. The two longitudinal side walls **120***a*, **120***b* each have an upper edge **121***a*, **121***b* and an opposite lower edge **122***a*, **122***b*. The spring contact edges **116***a*, **116***b* each extend essentially perpendicular to the upper edge **121***a*, **121***b*. Starting from the horizontally extending upper edge **121***a*, **121***b*, the spring contact edges **116***a*, **116***b* extend downward in the direction of the horizontally extending lower edge **122***a*, **122***b* of the guide element **115**.
- (39) The busbar **110** and the clamping spring **111** are arranged between the two longitudinal side walls **120***a*, **120***b* of the guide element **115**. The busbar **110** and the clamping spring **111** are enclosed by the guide element **115**.
- (40) The guide element **115** furthermore has two end walls **123***a*, **123***b*, which are aligned parallel

to one another. The two end walls **123***a*, **123***b* are arranged transversely to the two longitudinal side walls **120***a*, **120***b* of the guide element **115**.

- (41) A conductor connection space **124**, into which a conductor to be connected can be inserted, is formed between the section **114** of the busbar **110** and the clamping leg **113**. The conductor connection space **124** is laterally covered or delimited by the two longitudinal side walls **120***a*, **120***b* of the guide element **115** so that the guide element **115** also forms a guide for the conductor to be connected.
- (42) The conductor connection space **124** is designed to align with a conductor insertion opening **143** formed in the housing **140**, via which the conductor to be connected can be inserted into the housing **140** of the connection arrangement **100** in the insertion direction E.
- (43) The connection arrangement **100** also has a release element **125**. The release element **125** is arranged flush with the conductor insertion opening **143** and the conductor connection space **124**. The release element **125** delimits the conductor connection space **124** downwardly.
- (44) In the release position of the clamping leg **113** of the clamping spring **111**, the release element **125** is in engagement with the guide element **115**, as can be seen in FIGS. **2**, **5** and **6**, as a result of which the guide element **115** is held in its position and is thus also held in its position via the spring contact edges **116***a*, **116***b* and the slide sections **119***a*, **119***b* of the clamping legs **113**, so that an undesired pivoting back of the clamping leg **113** from the release position into the clamping position can be prevented.
- (45) The release element **125** has two laterally arranged undercuts **126** that, in the release position of the clamping leg **113** of the clamping spring **111**, are in engagement with a respective latching lug **127***a*, **127***b* of the guide element **115** in order to form a latching between the guide element **115** and the release element **125**. The latching lug **127***a* is formed on the lower edge **122***a* of the longitudinal side wall **120***a*, and the latching lug **127***b* is formed on the lower edge **122***b* of the longitudinal side wall **120***b*.
- (46) In the clamping position, the release element **125** is out of engagement with the guide element **115**, as can be seen in FIGS. **1**, **3** and **4**, so that the guide element **115** is freely displaceable.
- (47) The release element **125** is mounted so as to be tiltable relative to the guide element **115**.
- (48) When a conductor to be connected is being inserted along the insertion direction E via the conductor insertion opening **143** into the conductor connection space **124**, the conductor bumps against the release element **125**, as a result of which the release element **125** is tilted relative to the guide element **115** and thereby comes out of engagement with the guide element **115**, so that the guide element **115** can be freely displaced again, and the guide element **115** can thereby be displaced by the spring force of the clamping leg **113** alone, without manual assistance, in such a way that the clamping leg **113** can be transferred from the release position into the clamping position.
- (49) The release element **125** has a pressure surface **128** that points in the direction of the conductor connection space **124** and is arranged flush with the conductor insertion opening **143** or flush with the conductor connection space **124**, so that the conductor bumps against the pressure surface **128** of the release element **125** when it is being inserted into the connection arrangement **100**, as a result of which a compressive force is applied by the conductor to the release element **125**. By applying a compressive force by means of the conductor to the pressure surface **128** and thus to the release element **125**, the release element **125** can be brought into a pivoting movement or tilting movement in the direction of the insertion direction E of the conductor so that the release element **125** can be pivoted or tilted away from the guide element **115** in the insertion direction E of the conductor.
- (50) When the guide element **115** is out of engagement with the release element **125**, the displacement movement V of said guide element takes place in a direction that is oriented transversely to the insertion direction E of the conductor to be connected into the conductor connection space **124**.

- (51) Furthermore, a counter-contact edge **142***a*, **142***b* is formed on each of the two longitudinal side walls **120***a*, **120***b*. When the clamping leg **113** is being transferred from the clamping position to the release position, the clamping leg **113** presses with its two slide sections **119***a*, **119***b* against the two counter-contact edges **142***a*, **142***b*, as can be seen in FIGS. **2**, **5** and **6**, as a result of which the guide element **115** follows the pivoting movement of the clamping leg **113** and is shifted to such an extent by a displacement movement V until the guide element **115** with its latching lugs **127***a*, **127***b* comes into engagement with the release element **125** and latches there.
- (52) The two counter-contact edges **142***a*, **142***b* are arranged on the respective longitudinal side wall **120***a*, **120***b* of the guide element **115** opposite the spring contact edges **116***a*, **116***b*.
- (53) The longitudinal side walls **120***a*, **120***b* each have a slot-shaped recess **154***a*, **154***b*, in which the clamping leg **113** is immersed with its two slide sections **119***a*, **119***b*. The spring contact edge **116***a*, **116***b* and the counter-contact edge **142**, **142***b* of a longitudinal side wall **120***a*, **120***b* each form a part of a boundary wall of the slot-shaped recess **154***a*, **154***b* of the respective longitudinal side wall **120***a*, **120***b*. The two slot-shaped recesses **154***a*, **154***b* are formed symmetrical or parallel to one another on the two longitudinal side walls **120***a*, **120***b*.
- (54) In the embodiments shown in FIGS. **1** to **6**, the clamping leg **113** is transferred from the clamping position into the release position by means of an actuating means **129**. The connection arrangements **100** shown in FIGS. **1** to **6** are identical to one another except for the type and guidance of the actuating means **129**.
- (55) In the embodiment shown in FIGS. 1 and 2, the actuating means 129 is a tool that is to be inserted separately into the housing 140 and that is shown here in the form of a screwdriver. The housing 140 has an opening 144 via which the actuating means 129 can be inserted into the housing 140 in order to actuate the clamping leg 113 of the clamping spring 111.
- (56) The opening **144** for the insertion of the actuating means **129** is arranged between the conductor insertion opening **143** and a bearing position **145** of the clamping spring **111** in the housing **140**. The bearing point **145** is in the form of a pin that projects from a rear wall **146** of the housing **140**. Via its arcuate section **141**, the clamping spring **111** is attached to the bearing point **145**.
- (57) In the embodiment shown in FIGS. 3 to 6, the actuating means 129 is integrated into the housing 140 by the actuating means 129 being mounted in the housing 140 and being linearly guidable in a guide opening 147 formed in the housing 140. The guide opening 147 extends parallel to the conductor insertion opening 143, so that the actuation direction B of the actuating means 129 is directed parallel to the insertion direction E of the conductor into the housing 140. (58) As can be seen in the sectional view of FIGS. 4 and 6, the actuating means 129 surrounds the clamping spring 111 in a U-shape. The actuating means 129 has a recess 148 into which the clamping spring 111 is immersed in particular in the region of its arcuate section 141, so that the actuating means 129 surrounds around or overlaps the clamping spring 111. The actuating means 129 can thus surround the clamping spring 111 in the form of a hood. The recess 148 is formed in the middle of the actuating means 129. Starting from a lower side 149 of the actuating means 129 directed in the direction of the clamping spring 111, the recess 148 extends in the direction of an upper side 150 of the actuating means 129. The upper side 150 forms an actuating surface for actuating the actuating means 129.
- (59) The actuating means **129** is designed in such a way that it has a first actuating finger **151** and a second actuating finger **152** opposite the first actuating finger **151**, a side wall **152** of the actuating means **129** extending between the first actuating finger **151** and the second actuating finger **152**, said side wall laterally covering the clamping spring **111** at least in regions. However, the housing **140** has only a rear wall **146** but no opposite front wall, and the housing **140** is thus designed to be open on one side here, so that the clamping spring **111** is held in its position at the bearing point **145** via the actuating means **129** or the side wall **152** of the actuating means **129**, so that the clamping spring **111** is prevented from slipping out of the housing **140** in the region of the front

- side where the housing **140** does not have a wall.
- (60) The underside **149** of the actuating means **129** is formed by the two free ends of the actuating fingers **151**, **152**.
- (61) The first actuating finger **151** serves to actuate the clamping leg **113** of the clamping spring **111** in that the first actuating finger **151** rests directly against the clamping leg **113** and can slide along it. The second actuating finger **152** is guided essentially parallel to the retaining leg **112** of the clamping spring **111**. The arcuate section **141** of the clamping spring **111** is arranged between the two actuating fingers **151**, **152**.
- (62) In the two embodiments shown in FIGS. **1** to **6**, a test opening **155** is further formed on the housing **140**, via which a test plug can be inserted into the connection arrangement **100**. The test opening **155** is arranged directly next to the conductor insertion opening **143**.
- (63) While the invention has been illustrated and described in detail in the drawings and foregoing description, such illustration and description are to be considered illustrative or exemplary and not restrictive. It will be understood that changes and modifications may be made by those of ordinary skill within the scope of the following claims. In particular, the present invention covers further embodiments with any combination of features from different embodiments described above and below. Additionally, statements made herein characterizing the invention refer to an embodiment of the invention and not necessarily all embodiments.
- (64) The terms used in the claims should be construed to have the broadest reasonable interpretation consistent with the foregoing description. For example, the use of the article "a" or "the" in introducing an element should not be interpreted as being exclusive of a plurality of elements. Likewise, the recitation of "or" should be interpreted as being inclusive, such that the recitation of "A or B" is not exclusive of "A and B," unless it is clear from the context or the foregoing description that only one of A and B is intended. Further, the recitation of "at least one of A, B and C" should be interpreted as one or more of a group of elements consisting of A, B and C, and should not be interpreted as requiring at least one of each of the listed elements A, B and C, regardless of whether A, B and C are related as categories or otherwise. Moreover, the recitation of "A, B and/or C" or "at least one of A, B or C" should be interpreted as including any singular entity from the listed elements, e.g., A, any subset from the listed elements, e.g., A and B, or the entire list of elements A, B and C.

LIST OF REFERENCE SIGNS

(65) **100** Connection arrangement **110** Busbar **111** Clamping spring **112** Retaining leg **113** Clamping leg **114** Section of the current bar **115** Guide element **116***a*, **116***b* Spring contact edge **117** Main section **118** Clamping edge **119***a*, **119***b* Slide section **120***a*, **120***a* Longitudinal side wall **121***a*, **121***b* Upper edge **122***a*, **122***b* Lower edge **123***a*, **123***b* End wall **124** Conductor connection space **125** Release element **126** Undercut **127***a*, **127***b* Latching lug **128** Pressure surface **129** Actuating means **140** Housing **141** Arcuate section **142***a*, **142***b* Counter-contact edge **143** Conductor insertion opening **144** Opening **145** Bearing point **146** Rear wall **147** Guide opening **148** Recess **149** Underside **150** Upper side **151** First actuating finger **152** Second actuating finger **153** Side wall **154***a*, **154***b* Slot-shaped recess **155** Test opening V Displacement movement E Insertion direction B Actuation direction

Claims

1. A connection arrangement for connecting an electrical conductor, comprising: a housing; a busbar; a clamping spring comprising a clamping leg transferrable into a clamping position and into a release position; an actuator by which a compressive force is applicable to the clamping leg for transferring the clamping leg from the clamping position into the release position; a conductor connection space formed between a section of the busbar and of the clamping leg of the clamping spring; a displaceably arranged guide element in operative connection with the clamping leg of the

clamping spring, the clamping leg being holdable in the release position by the guide element; and a release element, which in the release position of the clamping leg of the clamping spring is in engagement with the guide element, wherein the release element, during insertion of the conductor to be connected into the conductor connection space, is actuatable by the insertion such that the release element comes out of engagement with the guide element, wherein the guide element is displaceable by a spring force of the clamping leg such that the clamping leg is transferrable into the clamping position to clamp the conductor against the busbar, wherein the actuator is mounted in the housing and is linearly guidable in a guide opening formed in the housing, and wherein the actuator surrounds the clamping spring in a U-shape.

- 2. A connection arrangement for connecting an electrical conductor, comprising: a housing; a busbar; a clamping spring comprising a clamping leg transferrable into a clamping position and into a release position; an actuator by which a compressive force is applicable to the clamping leg for transferring the clamping leg from the clamping position into the release position; a conductor connection space formed between a section of the busbar and of the clamping leg of the clamping spring; a displaceably arranged guide element in operative connection with the clamping leg of the clamping spring, the clamping leg being holdable in the release position by the guide element; and a release element, which in the release position of the clamping leg of the clamping spring is in engagement with the guide element, wherein the release element, during insertion of the conductor to be connected into the conductor connection space, is actuatable by the insertion such that the release element comes out of engagement with the guide element, wherein the guide element is displaceable by a spring force of the clamping leg such that the clamping leg is transferrable into the clamping position to clamp the conductor against the busbar, and wherein the guide element has two longitudinal side walls arranged parallel to each other, which delimit the conductor connection space on a first side and on a second side opposite the first side.
- 3. A connection arrangement for connecting an electrical conductor, comprising: a housing; a busbar; a clamping spring comprising a clamping leg transferrable into a clamping position and into a release position; an actuator by which a compressive force is applicable to the clamping leg for transferring the clamping leg from the clamping position into the release position; a conductor connection space formed between a section of the busbar and of the clamping leg of the clamping spring; a displaceably arranged guide element in operative connection with the clamping leg of the clamping spring, the clamping leg being holdable in the release position by the guide element; and a release element, which in the release position of the clamping leg of the clamping spring is in engagement with the guide element, wherein the release element, during insertion of the conductor to be connected into the conductor connection space, is actuatable by the insertion such that the release element comes out of engagement with the guide element, wherein the guide element is displaceable by a spring force of the clamping leg such that the clamping leg is transferrable into the clamping position to clamp the conductor against the busbar, wherein the guide element is displaceable such that a displacement movement of the guide element takes place transversely to an insertion direction of the conductor to be connected into the conductor connection space, and wherein the guide element and the actuator are separate elements.
- 4. The connection arrangement of claim 3, wherein the release element is mounted tiltably relative to the guide element.
- 5. The connection arrangement of claim 3, wherein the release element has at least one undercut, which in the release position of the clamping leg of the clamping spring, is latched with at least one latching lug of the guide element.
- 6. The connection arrangement of claim 3, wherein the guide element has two longitudinal side walls arranged parallel to each other, which delimit the conductor connection space on a first side and on a second side opposite the first side.
- 7. The connection arrangement of claim 3, wherein the guide element has at least one spring contact edge against which the clamping leg rests.

- 8. The connection arrangement of claim 7, wherein the clamping leg has two slide sections each arranged laterally in relation to a main section having a clamping edge, wherein the guide element has two spring contact edges arranged at a distance from one another, and wherein a first slide section rests against a first spring contact edge and a second slide section rests against a second spring contact edge.
- 9. The Connection arrangement of claim 3, wherein the housing has an opening via which the actuator is guidable to the clamping leg of the clamping spring.
- 10. The connection arrangement of claim 9, wherein the opening for inserting the actuator is arranged between a conductor insertion opening formed on the housing and a bearing point of the clamping spring in the housing.
- 11. The connection arrangement of claim 3, wherein the guide element has at least one countercontact edge on which the clamping leg is configured to apply a force on the guide element during transfer from the clamping position into the release position.
- 12. The connection arrangement of claim 11, wherein the at least counter-contact edge is arranged opposite the at least one spring contact edge.
- 13. The connection arrangement of claim 11, wherein the at least one guide element has a slot-shaped recess, and wherein the at least one spring contact edge and the at least one counter-contact edge are formed in a region of the at least one slot-shaped recess.
- 14. The connection arrangement of claim 3, wherein the actuator is mounted in the housing and is linearly guidable in a guide opening formed in the housing.
- 15. The connection arrangement of claim 14, wherein the actuator surrounds the clamping spring in a U-shape.
- 16. The connection arrangement of claim 14, wherein the actuator has a first actuating finger and a second actuating finger opposite the first actuating finger, and wherein a side wall of the actuator extends between the first actuating finger and the second actuating finger, the side wall laterally covering the clamping spring at least in regions.