

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250248815

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Navia; Jose Luis et al.

BIOPROSTHETIC HEART VALVE

Abstract

A sterile, packaged bioprosthetic heart valve includes an expandable support member, a bioprosthetic valve attached to the expandable support member, a layer of biocompatible material covering at least a portion of the expandable support member, and a microorganism-resistant container in which the bioprosthetic valve is sealed. The bioprosthetic valve includes a tissue component comprising glutaraldehyde-fixed bovine pericardium including interstices containing a dimensional stabilizer comprising an aqueous solution of propylene glycol.

Inventors: Navia; Jose Luis (Shaker Heights, OH), Chen; Ji-Feng (Lakewood, OH)

Applicant: EDWARDS LIFESCIENCES CORPORATION (Irvine, CA)

Family ID: 39321510

Appl. No.: 19/191190

Filed: April 28, 2025

Related U.S. Application Data

parent US continuation 18078769 20221209 parent-grant-document US 12318291 child US 19191190

parent US continuation 15478210 20170403 parent-grant-document US 11547560 child US 18078769

parent US continuation 13868892 20130423 parent-grant-document US 9610160 child US 15478210

parent US continuation 13336974 20111223 ABANDONED child US 13868892

parent US continuation 12016168 20080117 parent-grant-document US 8105375 child US 13336974

us-provisional-application US 60881244 20070119

Publication Classification

Int. Cl.: A61F2/24 (20060101); A61F2/00 (20060101); A61F2/95 (20130101); A61L27/36 (20060101)

U.S. Cl.:

CPC A61F2/2433 (20130101); A61F2/2418 (20130101); A61F2/243 (20130101); A61F2/2436 (20130101); A61F2/0095 (20130101); A61F2/2415 (20130101); A61F2/9522 (20200501); A61F2220/0008 (20130101); A61F2230/0078 (20130101); A61F2250/0092 (20130101); A61L27/3625 (20130101); A61L27/3629 (20130101); A61L27/3687 (20130101); A61L27/3691 (20130101); Y10T29/49925 (20150115)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/078,769, filed Dec. 9, 2022, which is a continuation of U.S. patent application Ser. No. 15/478,210, filed Apr. 3, 2017, now U.S. Pat. No. 11,547,560, which is a continuation of U.S. patent application Ser. No. 13/868,892, filed Apr. 23, 2013, now U.S. Pat. No. 9,610,160, which is a continuation of U.S. patent application Ser. No. 13/336,974, filed Dec. 23, 2011, which is a continuation of U.S. patent application Ser. No. 12/016,168, filed Jan. 17, 2008, now U.S. Pat. No. 8,105,375, which claims the benefit of U.S. Patent Application No. 60/881,244, filed Jan. 19, 2007, the entire disclosures all of which are incorporated by reference for all purposes.

TECHNICAL FIELD

[0002] The present invention relates generally to a method for treating and improving the function of cardiovascular valves, and more particularly to a method for implanting a cardiovascular valve within the cardiovascular system of a subject.

BACKGROUND OF THE INVENTION

[0003] A number of implantable bioprosthetic devices are currently being used for treating patients with cardiovascular diseases and defects. Such implantable devices are useful for replacing diseased, damaged, or congenitally malformed components of a patient's cardiovascular system. Thus, damaged or diseased heart valves have been replaced with chemically-fixed, bioprosthetic heart valves prepared from tissues of porcine or bovine origin. Similarly, regions of damaged or diseased blood vessels may also be replaced with bioprosthetic vessels prepared from bovine tissues.

[0004] Typically, the animal tissues used to form implantable devices are chemically cross-linked with agents, especially those animal tissue components that come into direct contact with the blood of a patient, and then chemically sterilized and preserved in a chemical solution. Such treatment is necessary to prevent rejection of the implanted bioprosthetic device by the recipient. Such treatment also stabilizes the protein components of the animal tissue, thus making them more resistant to degradation by proteolytic enzymes.

[0005] The use of chemically-treated implantable bioprosthetic devices presents several drawbacks, however. For example, the presence of chemically cross-linked/preserved agents, such as glutaraldehyde, presents an environmental hazard to the operating room personnel who are exposed to these chemicals as well as personnel involved in transporting such tissues. Consequently, preparation of chemically-treated devices in the operating room is a cumbersome and time consuming process as the chemical agents must be rinsed thoroughly off of the devices and then

carefully crimped and loaded into a delivery catheter.

SUMMARY OF THE INVENTION

[0006] In one aspect of the present invention, a method is provided for implanting a valve having at least one valve leaflet within the cardiovascular system of a subject. One step of the method comprises preparing a substantially dehydrated bioprosthetic valve and providing an expandable support member having oppositely disposed first and second ends and a main body portion extending between the ends. The substantially dehydrated bioprosthetic valve is attached to the expandable support member so that the substantially dehydrated bioprosthetic valve is operably secured within the main body portion of the expandable support member. The expandable support member is then crimped into a compressed configuration and placed at a desired location within the cardiovascular system of the subject.

[0007] In another aspect of the present invention, a method is provided for implanting a valve having at least one valve leaflet within the cardiovascular system of a subject. One step of the method comprises preparing a substantially dehydrated bioprosthetic valve and providing an expandable support member having oppositely disposed first and second ends and a main body portion extending between the ends. The substantially dehydrated bioprosthetic valve is attached to the expandable support member so that the substantially dehydrated bioprosthetic valve is operably secured within the main body portion of the expandable support member. The expandable support member is next crimped into a compressed configuration and exposed to a re-hydrating fluid. The substantially dehydrated bioprosthetic valve is then placed at a desired location within the cardiovascular system of the subject.

[0008] In another aspect of the present invention, a method is provided for implanting a valve having at least one valve leaflet within the cardiovascular system of a subject. One step of the method comprises preparing a substantially dehydrated bioprosthetic valve and providing an expandable support member having oppositely disposed first and second ends and a main body portion extending between the ends. The substantially dehydrated bioprosthetic valve is attached to the expandable support member so that the substantially dehydrated bioprosthetic valve is operably secured within the main body portion of the expandable support member. The substantially dehydrated bioprosthetic valve is next exposed to a re-hydrating fluid. The expandable support member is then crimped into a compressed configuration and placed at a desired location within the cardiovascular system of the subject.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The foregoing and other features of the present invention will become apparent to those skilled in the art to which the present invention relates upon reading the following description with reference to the accompanying drawings, in which:

[0010] FIG. 1 is a flow diagram illustrating a method for implanting a valve having at least one leaflet within the cardiovascular system of the subject in accordance with the present invention;

[0011] FIG. 2 is a cross-sectional schematic view of a human heart;

[0012] FIG. 3 is a perspective view of a substantially dehydrated bioprosthetic valve securely attached to an expandable support member in an expanded configuration;

[0013] FIG. 4 is a perspective view showing a process for forming the valve shown in FIG. 3;

[0014] FIG. 5A is a perspective view showing an alternative embodiment of the valve in FIG. 3;

[0015] FIG. 5B is a perspective view showing another alternative embodiment of the valve in FIG. 5A;

[0016] FIG. 6 is a perspective view showing a process for collapsing the expandable support member shown in FIG. 3 into a compressed configuration;

[0017] FIG. 7 is a cross-sectional view showing a guidewire extending trans-septally through a human heart;

[0018] FIG. 8 is a cross-sectional view showing the guidewire extending through the mitral valve into the left ventricle;

[0019] FIG. 9 is a cross-sectional view showing a delivery catheter advanced over the guidewire;

[0020] FIG. 10A is a perspective view showing the valve of FIG. 6 attached to the guidewire;

[0021] FIG. 10B is a perspective view showing the valve of FIG. 10A loaded into the delivery catheter;

[0022] FIG. 11 is a cross-sectional view showing the valve of FIG. 10B positioned at a distal end of the delivery catheter;

[0023] FIG. 12 is a cross-sectional view of a magnified mitral valve showing the valve of FIG. 6 being delivered to the mitral valve;

[0024] FIG. 13 is a cross-sectional view of a magnified mitral valve showing the valve of FIG. 3 securely positioned in place of the mitral valve;

[0025] FIG. 14 is a flow diagram illustrating an alternative embodiment of the present invention;

[0026] FIG. 15A is a perspective view showing the valve of FIG. 6 being exposed to a re-hydrating fluid;

[0027] FIG. 15B is a perspective view showing the valve of FIG. 15A immersed in the re-hydrating fluid;

[0028] FIG. 16 is a perspective view showing the valve of FIG. 5A contained in a delivery catheter and being delivered to a mitral valve via a port at the left ventricular apex;

[0029] FIG. 17 is a perspective view showing the valve of FIG. 16 in an expanded configuration in place of the mitral valve;

[0030] FIG. 18 is a perspective view showing the valve of FIG. 5A contained in a delivery catheter and being delivered to a mitral valve via a port at the left atrial appendage;

[0031] FIG. 19 is a perspective view showing the valve of FIG. 18 in an expanded configuration in place of the mitral valve;

[0032] FIG. 20 is a flow diagram illustrating another alternative embodiment of the present invention;

[0033] FIG. 21 is a graph depicting the flow performance of a valve comprised of bovine pericardium constructed in accordance with the present invention;

[0034] FIG. 22 is a graph comparing the flow performance of a valve and a control valve, each comprised of porcine pericardium. In accordance with the methods of the present invention, the control valve was dehydrated, crimped, sterilized, stored in a fluid-free container for 53 days, and then re-hydrated in water prior to testing;

[0035] FIG. 23 is a graph comparing the flow performance of a valve and a control valve, each comprised of bovine pericardium. In accordance with the methods of the present invention, the control valve was dehydrated, crimped, sterilized, stored in a fluid-free container for 53 days, and then re-hydrated in water prior to testing;

[0036] FIG. 24 is a graph depicting the flow performance of a control valve comprised of bovine pericardium; and

[0037] FIG. 25 is a graph comparing the flow performance of a valve and a control valve, each comprised of porcine pericardium. In accordance with the methods of the present invention, the control valve was dehydrated, crimped, sterilized, stored in a fluid-free container for 53 days, and then re-hydrated in water prior to testing.

DETAILED DESCRIPTION

[0038] The present invention relates generally to a method for treating and improving the function of cardiovascular valves, and more particularly to a method for implanting a cardiovascular valve within the cardiovascular system of a subject. As used herein, the term “cardiovascular system” refers to a bodily system consisting of the heart, blood vessels, and blood that circulates blood

throughout the body, delivers nutrients and other essential materials to cells, and removes waste products. As representative of the present invention, FIG. 1 illustrates a method **10** for implanting a valve **30** (FIG. 3) having at least one valve leaflet **36** within the cardiovascular system of a subject, wherein the valve comprises a substantially dehydrated bioprosthetic valve **32** securely attached to an expandable support member **34**. Advantageously, the method **10** (FIG. 1) of the present invention minimizes, if not eliminates, the possibility of introducing aldehydes into the blood stream of the subject while also preserving the functional properties of the valve **30** (FIG. 3). The present method **10** also avoids the problems associated with exposing manufacturing or operating room personnel to the fumes given off by aldehyde-containing solutions, in turn reducing the risk of damaging the valve **30** and the amount of time spent in the operating room preparing the valve for implantation.

[0039] FIG. 2 schematically illustrates a human heart **50**. The human heart **50** includes four chambers: the right and left atria **52** and **54** and the right and left ventricles **56** and **58**. The right and left atria **52** and **54** are divided by the interatrial septum **60**. The thin-walled right atrium **52** receives deoxygenated blood from the superior vena cava **62**, the inferior vena cava **64**, and from the coronary sinus (not shown). The thin-walled left atrium **54** receives oxygenated blood from pulmonary veins **66**. The right and left ventricles **56** and **58** pump oxygenated and deoxygenated blood, respectively, throughout the body, and the pocket-like semilunar pulmonary valve (not shown) and the aortic valve (not shown) prevent reflux into the ventricles. Atrial blood is pumped through the atrioventricular orifices, guarded by the tri-leaflet tricuspid valve **68** on the right side of the heart **50** and the bi-leaflet mitral valve **70** on the left side of the heart. The leaflets **72** of the mitral valve **70** are attached to the papillary muscles **74** in the right and left ventricles **56** and **58** by chordae tendineae **76**. Similarly, the leaflets **78** of the tricuspid valve **68** are attached to the papillary muscles **74** in the right and left ventricles **56** and **58** by chordae tendineae **76**.

[0040] In one embodiment of the present invention, a method **10** (FIG. 1) is provided for implanting a valve **30** having at least one valve leaflet **36** within the cardiovascular system of a subject. As used herein, the term “subject” refers to any mammal including, for example, human beings, dogs, cats, horses, and non-human primates. At **12**, one step of the method **10** comprises preparing a substantially dehydrated bioprosthetic valve **32** (FIG. 3). The substantially dehydrated bioprosthetic valve **32** is prepared according to the teachings of U.S. Pat. No. 6,534,004, the subject matter of which is hereby incorporated by reference.

[0041] Briefly, a tissue component **38** (FIG. 4) is fixed by treating the tissue component with an aqueous solution comprising at least one non-volatile, biocompatible dimensional stabilizer at a concentration, temperature, and for a time sufficient to allow an equilibrium to be reached between the fluids in the interstices of the tissue component and the aqueous solution. As used herein, the term “tissue component” refers to tissue that is dissected from an animal including, for example, muscular tissues, connective tissues, epithelial tissues, or combinations thereof, and tissues or tissue precursors that are formed in animal cell cultures. The tissue component **38** can include, but is not limited to, a heart valve (e.g., a bi- or tri-leaflet valve), peritoneum, pleura, submucosal tissue, dura mater and/or pericardium obtained from non-human animals, such as porcine, equine and/or bovine animals, in addition to human donors (e.g., cadaveric tissue).

[0042] As used herein, the term “fixed” when used with reference to the tissue component **38** refers to a tissue component in which the proteins thereof have reduced solubility, antigenicity, and biodegrading properties as compared to the proteins in a native tissue component. The tissue component **38** may be fixed by cross-linking the amine groups of the proteins of the tissue component with an aldehyde, such as glutaraldehyde or formaldehyde, for example.

[0043] Dimensional stabilizers include organic molecules that are hydrophilic and that comprise a plurality of carbon atoms attached to a plurality of hydroxyl groups. Examples of dimensional stabilizers include, but are not limited to, water soluble polyhydric alcohols such as glycerol, ethylene glycol, polyethylene glycols, propylene glycol, butylene glycol, sorbitol, mannitol, and

pentaerythritol; water soluble carbohydrates such as ribose, maltose, sucrose, fructose, dextrose, dextran, cellulose, and methyl cellulose; pectin; derivatives of glycerol including, for example, glycerol bori-borate and glycerol borate akerite glycerin alternative; and water soluble gums.

[0044] At **12**, the tissue component **38** is contacted with the aqueous treatment solution for a time and at a temperature sufficient to permit the treatment solution to penetrate into the interstices of the tissue component and achieve an equilibrium between the treatment solution and the fluids in the interstices of the tissue component. The time needed to achieve such equilibrium is directly related to the thickness of the tissue component **38** and to the concentration of the dimensional stabilizer in the solution. Additionally, the time needed to achieve equilibrium is inversely related to the ratio between the volumes of the treatment solution and the tissue component **38** to the rate of mixing of the treatment solution.

[0045] After the tissue component **38** has been treated, the tissue component is formed into a substantially dehydrated bioprosthetic valve **32** (FIG. **3**) or, alternatively, exposed to ambient air at standard room temperature and humidity. Where the tissue component **38** is exposed to air following treatment, the tissue component may be air dried for a time sufficient to increase the viscosity of the dimensional stabilizer in the solution entrapped within the interstices of the tissue component such that the treated tissue component is essentially free from excess aqueous treatment solution.

[0046] After preparing the tissue component **38**, the substantially dehydrated bioprosthetic valve **32** is formed. As illustrated in FIG. **4**, the tissue component **38** is first securely attached to a root component **40**. The root component **40** provides both structural support and a substrate for attachment of the tissue component **38**. The root component **40** may be made of a scaffolding material, such as a harvested aortic root, for example, or any other suitable scaffolding material, such as biological tissue (e.g., pericardium, peritoneal tissue, submucosal tissue, dura mater, and the like), polytetrafluoroethylene (ePTFE), polyester or polyurethane. The root component **40** may be fixed in an identical or similar manner as the tissue component **38**. The root component **40** is securely attached to the tissue component **38** using, for example, sutures or any other known attachment means (e.g., pins, clips, staples, adhesives, and the like). It will be appreciated that the tissue component **38** may be treated with the aqueous treatment solution prior to the time it is fashioned into the substantially dehydrated bioprosthetic valve **32**, after it is fashioned into the substantially dehydrated bioprosthetic valve, or at both stages in the manufacture of the substantially dehydrated bioprosthetic valve.

[0047] After the tissue component **38** is securely attached to the root component **40**, an expandable support member **34** is then provided at **14**. As shown in FIG. **3**, the expandable support member **34** comprises oppositely disposed first and second ends **42** and **44** and a main body portion **46** extending between the ends. The expandable support member **34** has a known stent configuration that allows it to be expanded and compressed (FIG. **6**). The flexible and expandable properties of the expandable support member **34** facilitate percutaneous delivery of the valve **30**.

[0048] The expandable support member **34** may be made from any suitable medical grade metal or plastic, including shape memory materials such as Nitinol, stainless steel, and/or titanium. Additionally, at least a portion of the expandable support member **34** may be made from a bioabsorbable material including, for example, magnesium alloy, dendrimers, biopolymers such as thermoplastic starch, polylactides, cellulose, and aliphatic aromatic copolyesters.

[0049] The expandable support member **34** is generally annular in shape and may be comprised of a continuous series of W-shaped segments **48** collectively forming a mesh-like configuration. It is contemplated, however, that other geometries may be used. As shown in FIG. **3**, the W-shaped segments **48** comprising the first and second ends **42** and **44** extend radially from the main body portion **46** of the expandable support member **34**. As described in more detail below, the radial configuration of the first and second ends **42** and **44** facilitates implantation of the valve **30**. It should be appreciated that the substantially dehydrated bioprosthetic valve **32** may be formed (i.e.,

treated) after attachment to the expandable support member **34**.

[0050] It should also be appreciated that the valve **30** may include other bioprosthetic valves known in the art. For example, the valve **30** may be constructed in an identical or similar fashion as the bioprosthetic valves illustrated in FIGS. **5A** and **5B** and disclosed in U.S. Patent Pub. Nos. 2006/0195183 A1 and 2006/0259135 A1, the entireties of which are hereby incorporated by reference.

[0051] As illustrated in FIGS. **5A** and **5B**, a valve **30'** can comprise an expandable support member **34'** having oppositely disposed first and second ends **42'** and **44'** and a main body portion **46'** extending between the ends. The first and second ends **42'** and **44'** of the expandable support member **34'** can respectively include a plurality of upper and lower wing members **94** and **96** that extend from the main body portion **46'** and are spaced circumferentially apart about the main body portion. Each of the upper and lower wing members **94** and **96** can include at least one attachment mechanism **98**. As shown in FIG. **5A**, for example, the at least one attachment mechanism **98** can comprise a barb **100** or hook capable of embedding into cardiovascular tissue.

[0052] Alternatively, each of the upper and lower wing members **94** and **96** can respectively include first and second magnetic components **102** and **104** as shown in FIG. **5B**. The first and second magnetic components **102** and **104** may be magnetically attracted to one another so that, when the valve **30'** is placed in the annulus **90** (FIG. **12**) of a mitral valve **70**, for example, the upper and lower wing members **94** and **96** (FIGS. **5A** and **5B**) are pulled toward one another to secure the valve in the mitral annulus. The second end **44'** of the expandable support member **34'** may also include at least two strut members **106** that are spaced apart from each other.

[0053] A tissue component **38'**, such as a substantially dehydrated bioprosthetic valve **32'**, may be secured within the main body portion **46'** of the expandable support member **34'** as shown in FIGS. **5A** and **5B**. For example, the substantially dehydrated bioprosthetic valve **32'** can comprise a valve having at least two valve leaflets that are coaptable to permit unidirectional blood flow. It should be appreciated that the tissue component **38'** may alternatively have a tri-leaflet configuration (not shown). Each of the at least two valve leaflets may be joined together at least two commissural sections **112** that are spaced apart from each other. Each of the at least two commissural sections **112** may be attached to a respective one of the strut members **106** to prevent prolapse of the valve leaflets.

[0054] Referring again to FIG. **3**, the expandable support member **34** may further include a layer **80** of biocompatible material covering at least a portion of the expandable support member **34**. The layer **80** of biocompatible material may be synthetic, such as polyester (e.g., Dacron®) (Invista, Wichita, Kans.), woven velour, polyurethane, PTFE, ePTFE, Gore-Tex® (W. L. Gore & Associates, Flagstaff, Ariz.), or heparin-coated fabric. Alternatively, the layer **80** may be a biological material such as bovine, equine, and/or porcine pericardium, peritoneal tissue, pleura, submucosal tissue, dura mater, an allograft, a homograft, a patient graft, or a cell-seeded tissue.

[0055] The layer **80** can cover either the inside surface of the expandable support member **34**, the outside surface of the expandable support member, or can be wrapped around both the inside and outside surfaces. The layer **80** may be attached around the entire circumference of the expandable support member **34** or, alternatively, may be attached in pieces or interrupted sections to allow the expandable support member to more easily expand and contract. As shown in FIG. **3**, for example, only the main body portion **46** of the expandable support member **34** may be covered with the layer **80** of biocompatible material. The entire expandable support member **34** may be entirely covered with the layer **80** of biocompatible material or, alternatively, not covered at all.

[0056] To facilitate positioning of the valve **30** in the cardiovascular system of a subject, the expandable support member **34** may include at least one radiographically opaque marking (not shown). The radiographically opaque marking may be located at any other portion of the expandable support member **34**. The radiographically opaque marking can be any one or combination of materials or devices with significant opacity. Examples of such radiographically

opaque markings include, but are not limited to, a steel mandrel sufficiently thick to be visible on fluoroscopy, a tantalum/polyurethane tip, a gold-plated tip, bands of platinum, stainless steel or gold, soldered spots of gold, and polymeric materials with a radiographically opaque filler such as barium sulfate.

[0057] The expandable support member **34** may also include at least one therapeutic agent for eluting into the cardiovascular tissue and/or blood stream. The therapeutic agent may be capable of preventing a variety of pathological conditions including, but not limited to, hypertension, hypotension, arrhythmias, thrombosis, stenosis and inflammation. Accordingly, the therapeutic agent may include at least one of an anti-arrhythmic agent, an anti-hypertensive, an anti-hypotensive agent, an anticoagulant, an antioxidant, a fibrinolytic, a steroid, an anti-apoptotic agent, an anti-mineralization agent, an anti-calcification agent, and/or an anti-inflammatory agent.

[0058] Optionally or additionally, the therapeutic agent may be capable of treating or preventing other diseases or disease processes such as microbial infections and heart failure. In these instances, the therapeutic agent may include an inotropic agent, a chronotropic agent, an anti-microbial agent, and/or a biological agent such as a cell, peptide, or nucleic acid. The therapeutic agent can be linked to a surface of the expandable support member **34**, embedded and released from within polymer materials, such as a polymer matrix, or surrounded by and released through a carrier.

[0059] After the substantially dehydrated bioprosthetic valve **32** is securely attached to the expandable support member **34**, the expandable support member is crimped into a compressed configuration at **18** (FIG. **6**). The expandable support member **34** may be crimped using tactile means, for example, or by any other method, including various mechanical-based devices, such as the device **116** illustrated in FIG. **6**, known in the art. Crimping the expandable support member **34** into a compressed configuration facilitates percutaneous delivery of the valve **30** at **132**. The crimped valve **30** is then stored in an environment (not shown) essentially free of liquid for later processing or implantation. It will be appreciated that the valve **30** may also be stored in the expanded configuration.

[0060] An environment, container (not shown), or package (not shown) that is “essentially free of liquid” as described herein refers to a non-fluid environment in which the presence of water or other liquids is limited to the content of such liquids in the ambient air (as more precisely defined by the relative humidity), and the content of liquid contained within the substantially dehydrated bioprosthetic valve **32** disposed within a container or package. For example, the valve **30** may be placed into the chamber of a microorganism-resistant container. After the valve **30** is placed in the chamber at **132**, the chamber is sealed and sterilized at **134** by, for example, exposure to ionizing radiation or a sterilizing gas (e.g., ethylene oxide). Alternatively, the valve **30** may be placed in a delivery catheter **86** and the delivery catheter then stored in a container essentially free of liquid.

[0061] At **20**, the valve **30** is placed at a desired location within the cardiovascular system of a subject. As illustrated in FIGS. **7-13**, for example, the valve **30** may be placed within the cardiovascular system of a subject to replace a diseased mitral valve **70**. It should be appreciated, however, that the valve **30** may be implanted at any desired location within the cardiovascular system of subject, including, for example, in place of a tricuspid valve **68**, an aortic valve, a pulmonary valve, a pulmonary artery (not shown) or vein **66**, a venous valve, an inferior vena cava **64**, a superior vena cava **62**, or any other peripheral artery or venous valve.

[0062] Prior to placement of the valve **30** at the desired location, the dimensions of the diseased mitral valve **70** are determined using known imaging techniques including, for example, magnetic resonance imaging (MRI), fluoroscopy, computed tomography (CT), angiography, ultrasound, and combinations thereof. After determining the dimensions of the diseased mitral valve **70**, an appropriately-sized valve **30** having dimensions that correspond to the dimensions of the diseased mitral valve is selected.

[0063] Next, a guidewire **82** is inserted into the vasculature of the subject via a femoral vein (not

or jugular vein (not shown) and, under image guidance (e.g., fluoroscopy, ultrasound, MRI, CT, or combinations thereof), respectively steered through the vasculature of the subject into the inferior vena cava **64** or superior vena cava **62**. The guidewire **82** is then passed across the right atrium **52** so that the distal end **84** of the guidewire pierces the interatrial septum **60** as shown in FIG. 7. The guidewire **82** is extended across the left atrium **54** and then downward through the diseased mitral valve **70** so that the distal end **84** of the guidewire is securely positioned in the left ventricle **58** (FIG. 8).

[0064] After the guidewire **82** is appropriately positioned in the heart **50**, a delivery catheter **86** is passed over the guidewire as shown in FIG. 9. The delivery catheter **86** may be comprised of a flexible, resiliently yieldable material such as silicone, PTFE, ePTFE, plastic polymer, or the like. After the delivery catheter **86** is positioned as shown in FIG. 9, the appropriately-sized valve **30** is removed from the sterile container, attached to the proximal end **114** of the guidewire **82** (FIG. 10A), and loaded into the delivery catheter (FIG. 10B). If needed, the valve **30** may be rinsed with a sterile solution or liquid, such as sterile saline or water, just prior to loading the valve into the delivery catheter **86**. A positioning wire (not shown) or other similar device useful for advancing the valve **30** over the guidewire **82** is then attached to the valve. An axial force is then applied to the positioning wire so that the valve **30** is passed over the guidewire **82** and positioned at the distal end **88** of the delivery catheter **86** (FIG. 11).

[0065] Upon reaching the distal end **88** of the delivery catheter **86**, the valve **30** is progressively freed from the delivery catheter and positioned in the mitral annulus **90** as shown in FIG. 12. As the valve **30** is progressively freed from the delivery catheter **86**, the position of the valve in the left atrium **54** can be monitored, controlled, and/or quality assured by imaging systems of various kinds. For example, X-ray machines, fluoroscopic machines, ultrasound, CT, MRI, positron emission tomography (PET), and other imaging devices may be used.

[0066] As shown in FIG. 13, the expandable support member **34** obtains an expanded configuration at **22** as the expandable support member is progressively freed from the delivery catheter **86**. In the expanded configuration, the first end **42** of the expandable support member **34** engages the superior aspect **92** of the mitral valve annulus **90**, and the second end **44** displaces the mitral leaflets **72** so that the leaflets are pinned back against the annulus of the mitral valve. With the valve **30** securely positioned in the mitral annulus **90**, blood flows through the expandable support member **34** and contacts the substantially dehydrated bioprosthetic valve **32**. As the blood contacts the substantially dehydrated bioprosthetic valve **32**, the interstices of the substantially dehydrated bioprosthetic valve are re-hydrated, causing the substantially dehydrated bioprosthetic valve to obtain its original (or substantially original) properties and assume normal (or substantially normal) blood flow performance (FIGS. 21-25). Because the valve **30** has been prepared and conditioned prior to delivery, the time needed to prepare the valve for delivery in the operating room is significantly reduced. Additionally, comparable devices prepared in the operating room do not provide such a consistent quality of manufacture as does the valve **30** of the present invention.

[0067] Another embodiment of the present invention is illustrated in FIG. 14. In FIG. 14, a method **10a** is provided for implanting a valve **30'** having at least one valve leaflet **36'** within the cardiovascular system of a subject. The method **10a** is identical to the method **10** illustrated in FIG. 1, except where as described below. According to the method **10a**, a substantially dehydrated bioprosthetic valve **32'** may be prepared at **12a** and securely attached at **16a** to an expandable support member **34'** to form the valve **30'** shown in FIG. 5A (as described above). As also described above, the expandable support member **34'** may then be crimped into a compressed configuration at **18a**, stored at **132a**, and then sterilized at **134a**.

[0068] In the compressed configuration, the substantially dehydrated bioprosthetic valve **32'** may be exposed to a re-hydrating fluid at **118** (FIG. 15A). The re-hydrating fluid can comprise saline or sterile water, for example, and may be contained in a suitable container **120**. As shown in FIG. 15B, the valve **30'** may be immersed in the re-hydrating fluid for a time appropriate so that the

substantially dehydrated bioprosthetic valve **32'** is re-hydrated and obtains (or substantially obtains) its original properties.

[0069] As described above, the valve **30'** may be loaded into a delivery catheter **86** as shown in FIG. **16**. The valve **30'** may be operably disposed about an inflatable balloon **122** which may be selectively inflated to expand the valve. It should be appreciated, however, that an inflatable balloon **122** may not be included where the valve **30'** is self-expanding. After loading the valve **30'** into the delivery catheter **86**, access to a desired location within the cardiovascular system of a subject may then be obtained. As shown in FIG. **16**, for example, access to a diseased mitral valve **70** of a subject may be obtained via a minimally invasive, open surgical approach whereby a port **124** is created at the left ventricular apex **126**. After the port **124** is created, the delivery catheter **86** may be inserted through the port and the distal end **88** of the catheter positioned in the diseased mitral valve **70** as shown in FIG. **16**.

[0070] The valve **30'** may next be advanced to the distal end **88** of the delivery catheter **86**. The delivery catheter **86** may then be progressively withdrawn so that the valve **30'** is positioned in the diseased mitral valve **70**. Next, the valve **30'** may be expanded by inflating the inflatable balloon **122** as shown in FIG. **17**. As the valve **30'** is expanded, the barbs **100** of the upper and lower wing members **94** and **96** respectively engage the superior and inferior aspects **92** and **128** of the mitral valve annulus **90**. In doing so, the lower wing members **96** pin the mitral leaflets **72** against the annular wall and secure the valve **30'** in place of the diseased mitral valve **70**.

[0071] As illustrated in FIGS. **18** and **19**, percutaneous access to a desired location within the cardiovascular system of a subject may be obtained via a left atrial appendage **130**. Using an open surgical approach, for example, a port **124** or puncture may be made at the left atrial appendage **130** so that a guidewire **82** may be inserted into the port and then threaded through the left atrium **54**, across the diseased mitral valve **70**, and into the left ventricle **58**. Next, a delivery catheter **86** may be advanced over the guidewire **82** so that the distal end **88** of the catheter is positioned in the diseased mitral valve **70** (FIG. **18**).

[0072] Although not illustrated herein, it should be appreciated that access to other desired locations within the cardiovascular system of a subject may also be obtained using known approaches. For example, access to the tricuspid valve **68**, may be obtained via right atrial appendage (not shown). Additionally, for replacement of the aortic valve, access may be obtained through the ascending aorta (not shown) or left ventricular apex **126** (FIG. **16**). Alternatively, for replacement of the pulmonary valve (not shown in detail), access may be obtained via the pulmonary artery (not shown), the right ventricle **56**, and/or right ventricular outflow track.

[0073] The valve **30'** may be loaded into the delivery catheter **86** as described above. The valve **30'** may then be advanced to the distal end **88** of the delivery catheter **86** as shown in FIG. **18**, and then progressively withdrawn from the subject. The inflatable balloon **122** may next be inflated to expand the valve **30'** (FIG. **19**). Expanding the valve **30'** allows the barbs **100** of the upper and lower wing members **94** and **96** to respectively engage the superior and inferior aspects **92** and **128** of the diseased mitral valve **70**. In doing so, the lower wing members **96** pin the mitral leaflets **72** against the annular wall and secure the valve **30'** in place of the diseased mitral valve **70**.

[0074] Another embodiment of the present invention is illustrated in FIG. **20**. In FIG. **20**, a method **10**; is provided for implanting a valve **30** having at least one valve leaflet **36** within the cardiovascular system of a subject. The method **10b** is identical to the method **10** illustrated in FIG. **1**, except where as described below. As described above, a substantially dehydrated bioprosthetic valve **32** may be prepared at **12b** and securely attached to an expandable support member **34** at **16b**. After forming the substantially dehydrated bioprosthetic valve **32**, the substantially dehydrated bioprosthetic valve may be attached to an expandable support member **34** at **16**; to form a valve **30**, and then exposed to a re-hydrating fluid at **118**. The valve **30** may be immersed in the re-hydrating fluid for a time appropriate so that the substantially dehydrated bioprosthetic valve **32** is re-hydrated and obtains (or substantially obtains) its original properties.

[0075] As described above, the valve **30** may next be loaded into a delivery catheter **86** as described above. Access to a desired location within the cardiovascular system of a subject may then be obtained. As described above, for example, access to a femoral vein may be obtained so that the valve **30** may be implanted in place of a diseased mitral valve **70**. After obtaining access to the cardiovascular system of the subject, the valve **30** may be appropriately placed and expanded at **20**; and **22b**, respectively (as described above). Because the substantially dehydrated bioprosthetic valve **32** is re-hydrated prior to implantation, the substantially dehydrated bioprosthetic valve can function normally immediately upon introduction to the cardiovascular system of the subject.

[0076] It should be appreciated that the valve **30** may be rinsed prior to implantation. For example, where the valve **30** is disposed in a delivery catheter **86** and stored in a container essentially free of liquid prior to delivery, the delivery catheter may be rinsed or flushed with a sterile fluid, such as sterile saline or water, before insertion into a subject. Alternatively, the valve **30** may be rinsed while in an expanded configuration in a suitable container **120**, for example, crimped into the compressed configuration, and delivered to a subject as described above.

[0077] From the above description of the invention, those skilled in the art will perceive improvements, changes and modifications. For example, the substantially dehydrated bioprosthetic valve **32** may be exposed to a re-hydrating or rinsing solution while the valve **30** is disposed within a delivery catheter **86** prior to delivery. Such improvements, changes and modifications within the skill of the art are intended to be covered by the appended claims.

Claims

1. A sterile, packaged bioprosthetic heart valve comprising: an expandable support member made from metal, the expandable support member having oppositely disposed first and second ends, and a main body portion extending between the ends, the expandable support member crimpable into a compressed configuration for delivery within a cardiovascular system, the expandable support member having an annular shape comprised of a continuous series of W-shaped segments collectively forming a mesh-like configuration; a bioprosthetic valve attached to the expandable support member, the bioprosthetic valve operably secured within the main body portion of the expandable support member, the bioprosthetic valve comprising a tissue component having a tri-leaflet configuration, the tissue component comprising glutaraldehyde-fixed bovine pericardium, the pericardium comprising interstices including a dimensional stabilizer comprising an aqueous solution of propylene glycol; a layer of biocompatible material covering at least a portion of the expandable support member, the layer of biocompatible material covering a portion of both the inside and outside surfaces of the expandable support member, the layer of biocompatible material comprising a synthetic fabric; and a microorganism-resistant container in which the bioprosthetic valve is sealed.
2. The packaged bioprosthetic heart valve of claim 1, wherein the layer of biocompatible material comprises polyester.
3. The packaged bioprosthetic heart valve of claim 1, wherein the microorganism-resistant container is essentially free of liquid.
4. A system comprising the sterile, packaged bioprosthetic heart valve of claim 1 and a delivery catheter.
5. The system of claim 4, wherein the delivery catheter comprises an inflatable balloon.
6. The system of claim 4, further comprising a crimping device.
7. A sterile, packaged bioprosthetic heart valve comprising: an expandable support member made from metal, the expandable support member having oppositely disposed first and second ends, and a main body portion extending between the ends, the expandable support member crimpable into a compressed configuration for delivery within a cardiovascular system, the expandable support member having an annular shape comprised of a continuous series of W-shaped segments

collectively forming a mesh-like configuration; a bioprosthetic valve attached to the expandable support member, the bioprosthetic valve operably secured within the main body portion of the expandable support member, the bioprosthetic valve comprising a tissue component having at least one valve leaflet, the tissue component comprising glutaraldehyde-fixed bovine pericardium, the pericardium comprising interstices including a dimensional stabilizer comprising an aqueous solution of propylene glycol; a layer of biocompatible material covering at least a portion of the expandable support member, the layer of biocompatible material comprising a synthetic fabric; and a microorganism-resistant container in which the bioprosthetic valve is sealed.

8. The sterile, packaged bioprosthetic heart valve of claim 7, wherein the tissue component has a tri-leaflet configuration.
 9. The sterile, packaged bioprosthetic heart valve of claim 7, wherein the layer of biocompatible material covers a portion of an inside surface of the expandable support member.
 10. The sterile, packaged bioprosthetic heart valve of claim 7, wherein the layer of biocompatible material covers a portion of an outside surface of the expandable support member.
 11. The sterile, packaged bioprosthetic heart valve of claim 7, wherein the layer of biocompatible material covers a portion of both the inside and outside surfaces of the expandable support member.
 12. The sterile, packaged bioprosthetic heart valve of claim 7, wherein the layer of biocompatible material comprises polyester.
 13. The packaged bioprosthetic heart valve of claim 7, wherein the microorganism-resistant container is essentially free of liquid.
 14. A system comprising the sterile, packaged bioprosthetic heart valve of claim 7 and a delivery catheter.
 15. The system of claim 14, further comprising a crimping device.
 16. A sterile, packaged bioprosthetic heart valve comprising: an expandable support member made from nitinol, the expandable support member having oppositely disposed first and second ends, and a main body portion extending between the ends, the expandable support member crimpable into a compressed configuration for delivery within a cardiovascular system, the expandable support member having an annular shape comprised of a continuous series of W-shaped segments collectively forming a mesh-like configuration; a bioprosthetic valve attached to the expandable support member, the bioprosthetic valve operably secured within the main body portion of the expandable support member, the bioprosthetic valve comprising a tissue component having a tri-leaflet configuration, the tissue component comprising glutaraldehyde-fixed bovine pericardium, the pericardium comprising interstices including a dimensional stabilizer comprising an aqueous solution of propylene glycol; a layer of biocompatible material covering at least a portion of the expandable support member, the layer of biocompatible material covering a portion of both the inside and outside surfaces of the expandable support member, the layer of biocompatible material comprising a synthetic fabric; and a microorganism-resistant container in which the bioprosthetic valve is sealed.
 17. The packaged bioprosthetic heart valve of claim 16, wherein the layer of biocompatible material comprises polyester.
 18. The packaged bioprosthetic heart valve of claim 16, wherein the microorganism-resistant container is essentially free of liquid.
 19. A system comprising the sterile, packaged bioprosthetic heart valve of claim 16 and a delivery catheter.
 20. The system of claim 19, further comprising a crimping device.
-