

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent  
Kind Code  
Date of Patent  
Inventor(s)

12388919  
B2  
August 12, 2025  
Jung; Minsu et al.

### Camera structure and electronic device comprising camera structure

#### Abstract

An example electronic device may include a first camera including a first camera barrel accommodating a first lens assembly; a second camera including a second camera barrel accommodating a second lens assembly; a cover housing arranged to substantially cover the first camera and the second camera and including a first opening corresponding to the first camera barrel of the first camera and a second opening corresponding to the second camera barrel of the second camera; a camera window including a first transparent region formed in a portion thereof corresponding to the first opening and a second transparent region formed in a portion thereof corresponding to the second opening; a first decoration part disposed at the inner circumference of the first opening of the cover housing and having an inclination formed at the inner circumferential portion thereof; and a second decoration part disposed at the inner circumference of the second opening of the cover housing and having an inclination formed at the inner circumferential portion thereof, wherein the first transparent region and the second transparent region of the camera window may have the same diameter, and the first decoration part and the second decoration part may have the same diameter.

**Inventors:** Jung; Minsu (Suwon-si, KR), Hwang; Yoonyoung (Suwon-si, KR), Kim; Gyeongtae (Suwon-si, KR), Choi; Jongchul (Suwon-si, KR)

**Applicant:** SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

**Family ID:** 1000008751723

**Assignee:** SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

**Appl. No.:** 18/095168

**Filed:** January 10, 2023

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230164251 A1	May. 25, 2023

## Foreign Application Priority Data

KR

10-2020-0090154

Jul. 21, 2020

## Related U.S. Application Data

continuation parent-doc WO PCT/KR2021/009116 20210715 PENDING child-doc US 18095168

---

## Publication Classification

**Int. Cl.:** **H04M1/20** (20060101); **H04M1/02** (20060101); **H04N23/57** (20230101); **H04N23/68** (20230101); **H04N23/90** (20230101)

### U.S. Cl.:

**CPC** **H04M1/0264** (20130101); **H04N23/57** (20230101); **H04N23/685** (20230101); **H04N23/90** (20230101);

## Field of Classification Search

**CPC:** H04M (1/0264); H04M (1/0283); H04N (23/57); H04N (23/685); H04N (23/90); H04N (23/45); H04N (23/51); G03B (5/00); G03B (11/00); G03B (17/02); G03B (17/56); G03B (30/00); G03B (2205/0007)

**USPC:** 455/556.1

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8610822	12/2012	Weber et al.	N/A	N/A
9726847	12/2016	An	N/A	G02B 7/02
10131292	12/2017	Oh	N/A	B60R 11/04
10425561	12/2018	Jarvis et al.	N/A	N/A
10635137	12/2019	Park	N/A	G06F 1/1641
11153503	12/2020	Ebrahimi Afrouzi	N/A	H04N 23/74
11178320	12/2020	Noh	N/A	H04M 1/0266
11323554	12/2021	Ha	N/A	H04M 1/0264
11528399	12/2021	Queeney	N/A	H04N 23/54
2007/0193901	12/2006	Cohen	206/316.2	A45C 11/38
2010/0328219	12/2009	Lombardi	345/169	H04N 7/142
2011/0255000	12/2010	Weber	219/121.72	B23K 26/351
2013/0259461	12/2012	Yoon	396/165	G03B 15/05

2013/0313672	12/2012	Min	N/A	N/A
2014/0063265	12/2013	Shukla	348/374	H04N 23/57
2014/0253799	12/2013	Moon	348/376	H04N 23/57
2016/0119520	12/2015	Park	348/373	H04N 23/57
2016/0309069	12/2015	Steinberg	N/A	G03B 15/05
2017/0104901	12/2016	Sanford	N/A	H04N 23/56
2018/0024419	12/2017	Sheridan	N/A	N/A
2018/0196219	12/2017	O et al.	N/A	N/A
2018/0241861	12/2017	Kim et al.	N/A	N/A
2019/0052785	12/2018	Ai	N/A	H04N 23/58
2019/0082083	12/2018	Jarvis	N/A	H04N 23/51
2019/0369678	12/2018	Park et al.	N/A	N/A
2020/0150387	12/2019	Kim	N/A	G06T 7/586
2020/0348480	12/2019	Kim	N/A	G02B 7/04
2021/0021801	12/2020	Lee et al.	N/A	N/A
2021/0136187	12/2020	Jeon	N/A	H04M 1/0264
2021/0405508	12/2020	Kim et al.	N/A	N/A
2022/0078317	12/2021	Wang et al.	N/A	N/A

## FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107241466	12/2016	CN	N/A
209105310	12/2018	CN	N/A
3168682	12/2016	EP	G02B 27/646
2000250111	12/1999	JP	N/A
2007-181045	12/2006	JP	N/A
10-2015-0026419	12/2014	KR	N/A
10-2019-0020474	12/2018	KR	N/A
10-2019-0028284	12/2018	KR	N/A
10-2019-0119856	12/2018	KR	N/A
10-2031654	12/2018	KR	N/A
10-2172637	12/2019	KR	N/A
10-2306912	12/2020	KR	N/A
10-2377985	12/2021	KR	N/A
WO-2015058153	12/2014	WO	G02B 13/001
WO-2016168838	12/2015	WO	G03B 13/06

## OTHER PUBLICATIONS

International Search Report for PCT/KR2021/009116 mailed Oct. 25, 2021, 4 pages. cited by applicant

Written Opinion of the ISA for PCT/KR2021/009116 mailed Oct. 25, 2021, 3 pages. cited by applicant

---

*Primary Examiner:* Patel; Mahendra R

*Attorney, Agent or Firm:* Nixon & Vanderhye, P.C.

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2021/009116, designating the United States, filed on Jul. 15, 2021, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2020-0090154, filed on Jul. 21, 2020, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

## BACKGROUND

### Field

(1) The disclosure relates to a camera structure and an electronic device including the camera structure.

### Description of Related Art

(2) Various types of cameras may be mounted on an electronic device. A plurality of cameras may be included in an electronic device to enable photographing in various photographing conditions (e.g., focal length, angle of view). A standard camera, a wide-angle camera, and a telephoto camera may be included in an electronic device, according to angle of view.

(3) Such a plurality of cameras may be arranged to share one camera window. The camera window may be configured of a transparent material so that external light can be incident to the plurality of cameras.

## SUMMARY

(4) Various cameras may include different lens assemblies having different optical specifications. In a case in which the sizes of the lens assemblies are different from each other, the sizes of the barrels for accommodating the lens assemblies and the sizes of the bodies of the cameras may be different from each other.

(5) When the sizes of a plurality of cameras are different from each other, the cameras may be viewed as having different shapes through a camera window shared by the plurality of cameras. Accordingly, the unity between the cameras may be reduced, thereby reducing external elegance and aesthetics of the electronic device.

(6) In addition, if housings covering the cameras are machined into different sizes, machining cost and machining difficulties may increase.

(7) Various embodiments disclosed herein may provide a camera structure in which cameras viewed through a camera window shared by the cameras have a sense of unity and aesthetics with each other and an electronic device including the camera structure.

(8) An electronic device according to various example embodiments of the disclosure may include a first camera including a first camera barrel in which a first lens assembly is accommodated, a second camera including a second camera barrel in which a second lens assembly is accommodated, a cover housing including a first opening corresponding to the first camera barrel of the first camera and a second opening corresponding to the second camera barrel of the second camera and disposed to substantially cover the first camera and the second camera, a camera window including a first transparent area at a portion corresponding to the first opening and a second transparent area at a portion corresponding to the second opening and disposed on the cover housing, a first decoration unit disposed on an inner circumference of the first opening of the cover housing and having an inclination formed on the inner circumference thereof, and a second decoration unit disposed on an inner circumference of the second opening of the cover housing and having an inclination formed on the inner circumference thereof, wherein the diameters of the first transparent area and the second transparent area of the camera window may be the same with each other, and the diameters of the first decoration unit and the second decoration unit may be the same with each other.

(9) A camera structure according to various example embodiments disclosed herein may include a first camera including a first camera barrel in which a first lens assembly is accommodated, a second camera including a second camera barrel in which a second lens assembly is

accommodated, a cover housing including a first opening corresponding to the first camera barrel of the first camera and a second opening corresponding to the second camera barrel of the second camera and disposed to substantially cover the first camera and the second camera, a camera window including a first transparent area at a portion corresponding to the first opening and a second transparent area at a portion corresponding to the second opening and disposed on the cover housing, a first decoration unit configured to have a diameter decreasing away from the camera window and disposed on the inner circumference of the first opening of the cover housing, and a second decoration unit configured to have a diameter decreasing away from the camera window and disposed on the inner circumference of the second opening of the cover housing, wherein the diameters of the first transparent area and the second transparent area of the camera window may be the same with each other, and the diameters of the first decoration unit and the second decoration unit may be the same with each other.

(10) According to various embodiments disclosed herein, a plurality of cameras included in the camera structure may be exposed to the outside in a unified shape to improve the external aesthetics of the camera structure. In addition, a three-dimensional effect of the outer appearances of cameras may be improved by including a configuration capable of providing a three-dimensional effect to a housing configured to cover the cameras.

(11) In addition, by unifying the sizes of the portions where the cameras are viewed, the processing cost and difficulty may be reduced.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) In relation to the description of drawings, the same or similar reference numerals may be used for the same or similar components.

(2) The above and other aspects, features and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:

(3) FIG. 1 is a block diagram illustrating an example electronic device in a network environment according to various embodiments;

(4) FIG. 2A is a perspective view illustrating a front surface of an example electronic device according to various embodiments;

(5) FIG. 2B is a perspective view illustrating a rear surface of the example electronic device illustrated in FIG. 2A;

(6) FIG. 3A is an exploded perspective view of an example camera structure according to various embodiments;

(7) FIG. 3B is a plan view of the camera window illustrated in FIG. 3A;

(8) FIG. 3C is a plan view of the cover housing illustrated in FIG. 3A;

(9) FIG. 3D is a plan view of the camera structure illustrated in FIG. 3A;

(10) FIG. 4A is a cross-sectional view of the example camera structure taken along line D1-D1 of FIG. 3D;

(11) FIG. 4B is a cross-sectional view of the example camera structure taken along line D2-D2 of FIG. 3D;

(12) FIG. 5 is a side view of an example first camera and an example second camera according to various embodiments;

(13) FIG. 6 is a cross-sectional view of an example camera structure according to various embodiments; and

(14) FIG. 7 is a view for explaining an example machining method of a decoration unit and a covering unit according to various embodiments.

#### DETAILED DESCRIPTION

(15) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment.

(16) With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the item, unless the relevant context clearly indicates otherwise.

(17) As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish components from another, and do not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(18) FIG. 1 is a block diagram illustrating an example electronic device **101** in a network environment **100** according to various embodiments. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connection terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In various embodiments, at least one of the components (e.g., the connection terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In various embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(19) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to an embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(20) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof, but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(21) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(22) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(23) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(24) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(25) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(26) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(27) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip

sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(28) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(29) A connection terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connection terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(30) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(31) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(32) The power management module **188** may manage power supplied to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(33) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(34) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(35) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type



communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1ms or less) for implementing URLLC.

(36) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of or including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(37) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(38) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(39) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing,

mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In an embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(40) FIG. 2A is a perspective view showing a front surface of an example electronic device according to various embodiments. FIG. 2B is a perspective view showing a rear surface of the example electronic device illustrated in FIG. 2A.

(41) Referring to FIG. 2A and FIG. 2B, an electronic device **200** according to an embodiment may include a housing **210** including a first surface (or a front surface) **210A**, a second surface (or a rear surface) **210B**, and a side surface **210C** configured to surround a space between the first surface **210A** and the second surface **210B**. In an embodiment (not shown), a housing may refer to a structure configuring the first surface **210A** of FIG. 2A, the second surface **210B** of FIG. 2B, and a portion of the side surface **210C**. According to an embodiment, the first surface **210A** may be configured by a front plate **202** of which at least a portion is substantially transparent. In an embodiment, the front plate **202** may be coupled to the housing **210** to configure an inner space together with the housing **210**. In various embodiments, the inner space may refer to a space configured to accommodate at least a portion of a display **201** as an inner space of the housing **210**.

(42) According to various embodiments, the second surface **210B** may be configured by a rear plate **211** which is substantially opaque. The rear plate **211** may be configured by, for example, coated or tinted glass, ceramic, polymer, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two of the above materials. The side surface **210C** may be coupled to the front plate **202** and the rear plate **211** and be configured by a side bezel structure (or “side member”) **218** including a metal and/or a polymer. In various embodiments, the rear plate **211** and the side bezel structure **218** may be integrally configured and may include the same material (e.g., a metal material such as aluminum).

(43) In an embodiment, the front plate **202** may include, at opposite ends of long edges of the front plate **202**, two first areas **210D** (e.g., curved areas) bended from the first surface **210A** toward the rear plate **211** to extend seamlessly. In an embodiment, the rear plate **211** may include, at opposite ends of long edges thereof, two second areas **210E** (e.g., curved areas) bended from the second surface **210B** toward the front plate **202** to extend seamlessly. In various embodiments, the front plate **202** (or the rear plate **211**) may include only one among the first areas **210D** (or the second areas **210E**). In an embodiment, a portion among the first areas **210D** or the second areas **210E** may not be included. In an embodiment, when viewed from the side surface of the electronic device **200**, the side bezel structure **218** may have a first thickness (or width) at the side of a side surface (e.g., the side surface through which a connector hole **208** extends) which does not include the first areas **210D** or the second areas **210E**, and may have a second thickness smaller than the first thickness at the side of a side surface (e.g., the side surface on which a key input device **217** is disposed) including the first areas **210D** or the second areas **210E**.

(44) According to an embodiment, the electronic device **200** may include at least one among a display **201**, audio modules **203**, **207**, and **214**, a sensor module **204**, camera modules **205** and **230**, a key input device **217**, a light emitting element **206**, and connector holes **208** and **209**. In various embodiments, the electronic device **200** may omit at least one (e.g., a key input device **217** or a light emitting element **206**) among components or additionally include other components.

(45) The display **201** may be exposed, for example, through a considerable portion of the front plate **202**. In various embodiments, at least a portion of the display **201** may be exposed through the front plate **202** configuring the first areas **210D** of the first surface **210A** and the side surface

**210C.** In various embodiments, the rim of the display **201** may be configured to be substantially the same as the shape of an adjacent outer periphery of the front plate **202**. In an embodiment (not shown), the gap between the outer periphery of the display **201** and the outer periphery of the front plate **202** may be configured to be substantially the same, so as to expand the area to which the display **201** is exposed.

(46) In an embodiment (not shown), a recess or an opening is disposed at a portion of a screen display area (e.g., an active area) or an area outside the screen display area (e.g., an inactive area) of the display **201**, and at least one among an audio module **214**, a sensor module **204**, camera modules **205** and **230**, and a light emitting element **206** aligned with the recess or the opening may be included. In an embodiment (not shown), at least one among an audio module **214**, a sensor module **204**, camera modules **205** and **230**, and a light emitting element **206** may be included in the rear surface of the screen display area of the display **201**. In an embodiment (not shown), the display **201** may be disposed to be coupled or adjacent to a touch detection circuit, a pressure sensor capable of measuring strength (pressure) of touch, and/or a digitizer configured to detect a magnetic stylus pen. In an embodiment, at least a portion of the sensor module **204** and/or at least a portion of the key input device **217** may be arranged at the first areas **210D** and/or the second areas **210E**.

(47) The audio modules **203**, **207**, and **214** may include a microphone hole **203** and speaker holes **207** and **214**. In the microphone hole **203**, a microphone configured to acquire external sound may be disposed, and in various embodiments, a plurality of microphones may be arranged so as to detect the direction of sound. The speaker holes **207** and **214** may include an external speaker hole **207** and a receiver hole **214** for a call. In various embodiments, the speaker holes **207** and **214** and the microphone hole **203** may be implemented as one hole, or a speaker may be included without the speaker holes **207** and **214** (e.g., a piezo speaker).

(48) The sensor module **204** may produce an electric signal or data value corresponding to an internal operating state of the electronic device **200** or an external environmental state. The sensor module **204** may include, for example, a first sensor module **204** (e.g., a proximity sensor) and/or a second sensor module (not shown) (e.g., a fingerprint sensor) arranged on the first surface **210A** of the housing **210**, and/or another sensor module (not shown) (e.g., a heart rate monitor (HRM) sensor or a fingerprint sensor) disposed on the second surface **210B** of the housing **210**. The fingerprint sensor may be disposed not only on the first surface **210A** (e.g., a display **201**) but also on the second surface **210B** of the housing **210**. The electronic device **200** may further include a sensor module not shown, for example, at least one among a gesture sensor, a gyro sensor, a barometric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor **204**.

(49) The camera modules **205** and **230** may include a first camera device **205** disposed on the first surface **210A** and a second camera device **230** disposed on the second surface **210B** of the electronic device **200**. The camera modules **205** and **230** may include one or more lenses, image sensors, and/or image signal processors. In various embodiments, two or more lenses (infrared cameras, wide-angle and telephoto lenses) and image sensors may be arranged on one surface of the electronic device **200**.

(50) The key input device **217** may be disposed on a side surface **210C** of the housing **210**. In an embodiment, the electronic device **200** may not include some or all of the above-described key input devices **217**, and the key input devices **217** not included may be implemented in other forms, such as soft keys, on the display **201**.

(51) The light emitting element **206**, for example, may be disposed on the first surface **210A** of the housing **210**. The light emitting element **206** may provide, for example, state information of the electronic device **200** in the form of light. In an embodiment, the light emitting element **206** may provide, for example, a light source interlocked with the operation of the camera module **205**. The

light emitting element **206** may include, for example, an LED, an IR LED, and/or a xenon lamp. (52) The connector holes **208** and **209** may include a first connector hole **208** capable of receiving a connector (for example, a USB connector) configured to transmit and receive power and/or data to and from an external electronic device and/or a second connector hole (for example, an earphone jack) **209** capable of receiving a connector configured to transmit and receive an audio signal to and from an external electronic device.

(53) FIG. **3A** is an exploded perspective view of an example camera structure according to various embodiments disclosed herein. FIG. **3B** is a plan view of a camera window illustrated in FIG. **3A**. FIG. **3C** is a plan view of a cover housing illustrated in FIG. **3A**. FIG. **3D** is a plan view of the example camera structure illustrated in FIG. **3A**.

(54) According to various embodiments, a camera structure **300** (e.g., the second camera device **230** of FIG. **2B**) may include a camera module **301**, a light emitting unit **391**, a cover housing **340**, and a camera window **350**. At least one of the components of the above-described camera structure **300** may be omitted, and the shape of the camera structure **300** is not limited to that shown in the drawings. According to an embodiment, the camera structure **300** may include two or four or more cameras. In the following description, it is assumed that the camera structure **300** includes three cameras (a first camera **310**, a second camera **320**, and a third camera **330**).

(55) According to various embodiments, the camera module **301** may include a first camera **310**, a second camera **320**, and a third camera **330**. Each of the first camera **310**, the second camera **320**, and the third camera **330** may include an image sensor configured to convert light reflected from an object into an electrical signal. The image sensor may be, for example, a sensor such as a charge coupled device (CCD) and a complementary metal oxide semiconductor (CMOS). The first camera **310**, the second camera **320**, and the third camera **330** included in the camera module **301** may be cameras having different types or performing different functions. In an embodiment, the first camera **310**, the second camera **320**, and the third camera **330** may include different types of lens assemblies. For example, the first camera **310** may include a first lens assembly **311**, the second camera **320** may include a second lens assembly **321**, and the third camera **330** may include a third lens assembly **331**. The lens assembly may refer, for example, to at least one optically disposed lens. The first lens assembly **311**, the second lens assembly **321**, and the third lens assembly **331** may be assemblies including lenses having different optical properties (e.g., angle of view, focal length, autofocus, f-number, and/or optical zoom). For example, the first lens assembly **311** of the first camera **310** may be a lens assembly capable of photographing an image with a first angle of view, the second lens assembly **321** of the second camera **320** may be a lens assembly capable of photographing an image with a second angle of view, and the third lens assembly **331** of the third camera **330** may be a lens assembly capable of photographing an image with a third angle of view. The first angle of view may be an angle of view generally classified as a wide angle in the field of cameras, the second angle of view may be an angle of view classified as a standard angle, and the third angle of view may be an angle of view classified as a zoom angle.

(56) According to various embodiments, at least one camera among the first camera **310**, the second camera **320**, and the third camera **330** may include an optical image stabilizer (OIS) unit (not shown) configured to drive an OIS. The OIS unit may, for example, be a device configured to compensate shake of the electronic device (e.g., the electronic device **200** of FIG. **2A**) in a photographing situation. The OIS unit can compensate the shake of the electronic device by moving an instrument (e.g., a camera barrel, a camera body) in which the lens assembly is accommodated. The OIS unit may be driven by various kinds of forces. For example, the OIS unit may be driven by electromagnetic force or magnetic force between a coil and a magnet, and may be driven by the driving force of an electric motor.

(57) According to various embodiments, the first camera **310** may include a first camera body **313** configured to accommodate a printed circuit board on which an image sensor is disposed and accommodate other instruments of the first camera **310** and a first camera barrel **312** in which the

first lens assembly **311** is accommodated. At least a portion of the first camera barrel **312** may be inserted into the first opening **341** of the cover housing **340**.

(58) According to various embodiments, the second camera **320** may include a second camera body **323** configured to accommodate a printed circuit board on which an image sensor is disposed and accommodate other instruments of the second camera **320** and a second camera barrel **322** in which the second lens assembly **321** is accommodated. At least a portion of the second camera barrel **322** may be inserted into the second opening **342** of the cover housing **340**.

(59) According to various embodiments, the third camera **330** may include a third camera body **333** configured to accommodate a printed circuit board on which an image sensor is disposed and accommodate other instruments of the third camera **330** and a third camera barrel **332** in which the third lens assembly **331** is accommodated.

(60) According to various embodiments, the sizes of the first lens assembly **311**, the second lens assembly **321**, and the third lens assembly **331** may be different from one another, and thus the sizes of the first camera barrel **312**, the second camera barrel **322**, and the third camera barrel **332** may be different from one another. Therefore, a space between the first camera barrel **312** and the first decoration unit **361**, a space between the second camera barrel **322** and the second decoration unit **362**, and a space between the third camera barrel **332** and the third decoration unit **363** may all have different sizes. A first covering unit **371** may be disposed to fill at least a portion of the space between the first camera barrel **312** and the first decoration unit **361**, and a third covering unit **373** may be disposed to fill at least a portion of the space between the third camera barrel **332** and the third decoration unit **363**. In an embodiment, the size of the second camera barrel **322** may be substantially identical to that of the diameter of the inner circumference of the second decoration unit **362**. Therefore, no covering unit may be disposed between the second camera barrel **322** and the second decoration unit **362**. Details of the first covering unit **371** and the third covering unit **373** will be described later.

(61) According to various embodiments, the first camera body **313** of the first camera **310**, the second camera body **323** of the second camera **320**, and the third camera body **333** of the third camera **330** may be at least partially integrated with or coupled to each other to configure the camera module **301**.

(62) According to various embodiments, the light emitting unit **391** (e.g., a light emitter) may produce light. The light emitting unit **391** may include an element (e.g., a light emitting element) capable of producing light. For example, the light emitting unit **391** may include an element such as a light emitting diode (LED), an injection laser diode (ILD), or a xenon lamp. In an embodiment, the light emitting unit **391** may operate in a photographing situation to add light in a dark photographing environment, thereby making it possible to take a picture with an appropriate shutter speed and sensitivity (e.g., international standard organization (ISO) value). In an embodiment, the light emitting unit **391** may operate alone to allow a user to use same as a flash.

(63) According to various embodiments, a sensor unit **392** may be a sensor configured to measure a user's biometric information. For example, the sensor unit **392** may be a sensor (e.g., a photoplethysmography (PPG) sensor) configured to measure information related to a user's heartbeat. The sensor unit **392** may include a light emitting element **392-1** and a light receiving element **392-2**. The sensor unit **392** may receive, through the light receiving element **392-2**, light produced from the light emitting element **392-1** and reflected from the skin to measure information related to the heartbeat.

(64) According to various embodiments, the cover housing **340** may be disposed to substantially cover the first camera **310**, the second camera **320**, and the third camera **330** included in the camera structure **300**. At least a portion of the cover housing **340** may be supported by the first camera body **313** of the first camera **310**, the second camera body **323** of the second camera **320**, and the third camera body **333** of the third camera **330**.

(65) According to various embodiments, the cover housing **340** may include a first opening **341**, a

second opening **342**, and a third opening **343**. In an embodiment, the first opening **341** may correspond to the first camera barrel **312**, the second opening **342** may correspond to the second camera barrel **322**, and the third opening **343** may correspond to the third camera barrel **332**. The size of the first opening **341** may be the same as or greater than the size of the first camera barrel **312**, the size of the second opening **342** may be the same as or greater than the size of the second camera barrel **322**, and the size of the third opening **343** may be the same as or greater than the size of the third camera barrel **332**. For example, a portion of the first camera barrel **312** may be inserted into the first opening **341**, and a portion of the second camera barrel **322** may be inserted into the second opening **342**. External light may be incident on the first lens assembly **311** accommodated in the first camera barrel **312** through the first opening **341**, external light may be incident on the second lens assembly **321** accommodated in the second camera barrel **322** through the second opening **342**, and external light may be incident on the third lens assembly **331** accommodated in the third camera barrel **332** through the third opening **343**.

(66) According to various embodiments, the camera window **350** may be disposed in a partial area of the camera structure **300**. According to an embodiment, the camera window **350** may be disposed at a portion where the camera structure **300** is exposed to the outside of the electronic device. At least partial area of the camera window **350** may be configured of a material having high light transmittance. For example, the camera window **350** may be configured of substantially transparent glass or synthetic resin. The camera window **350** may block external foreign substances from being introduced into the camera structure **300**. The camera window **350** may be exposed to the external environment, and thus be formed of a material having good durability (e.g., hardness, strength, corrosion resistance). According to an embodiment, the camera window **350** may include a material capable of improving optical properties of the first camera **310**, the second camera **320**, and the third camera **330**. This material may be disposed on the surface of the camera window **350** in a manner such as coating or printing.

(67) According to various embodiments, the camera window **350** may be divided into a plurality of areas. For example, the camera window **350** may include a first transparent area **351** corresponding to the first opening **341** of the cover housing **340**, a second transparent area **352** corresponding to the second opening **342** of the cover housing **340**, a third transparent area **353** corresponding to the third opening **343** of the cover housing **340**, a fourth transparent area **354** corresponding to the light emitting unit, a fifth transparent area **355** corresponding to the sensor unit, and an opaque area **356** excluding the first transparent area **351** to the fifth transparent area **355**. In an embodiment, the camera window **350** is configured of a material having high transmittance such as glass, and a material having low transmittance may be disposed on the opaque area **356** excluding the first transparent area **351**, the second transparent area **352**, the third transparent area **353**, the fourth transparent area, and the fifth transparent area **355** in a manner such as coating or printing. For example, a material having a high light absorption rate and thus having a black color may be disposed in the opaque area **356**. In an embodiment, the camera window **350** may be configured of a composite material. For example, the opaque area **356** may be configured of a material having low transmittance, and the first transparent area **351**, the second transparent area **352**, the third transparent area **353**, the fourth transparent area **354**, and the fifth transparent area **355** may be configured of a material having high transmittance.

(68) According to various embodiments, as illustrated in FIG. 3B, the sizes of the first transparent area **351**, the second transparent area **352**, and the third transparent area **353** may be the same. For example, as illustrated in FIG. 3B, in a case in which the first transparent area **351**, the second transparent area **352**, and the third transparent area **353** are substantially circular, the diameter A of the first transparent area **351**, the diameter A of the second transparent area **352**, and the diameter A of the third transparent area **353** may all be the same. For example, the diameter A of the first transparent area **351**, the diameter A of the second transparent area **352**, and the diameter A of the third transparent area **353** may be about 12.3 mm. In an embodiment, the diameter A of the first

transparent area **351** may be the same as the diameter of the outer circumference of the first decoration unit **361** (the diameter B of the outer circumference of the first decoration unit **361** in FIG. 3C), the diameter A of the second transparent area **352** may be the same as the diameter of the outer circumference of the second decoration unit **362** (the diameter B of the outer circumference of the second decoration unit **362** in FIG. 3C), and the diameter A of the third transparent area **353** may be the same as the diameter of the outer circumference of the third decoration unit **363** (the diameter B of the outer circumference of the third decoration unit **363** in FIG. 3C). Due to the unity of the size, a plurality of cameras viewed through the camera window **350** may have aesthetic unity.

(69) According to various embodiments, the camera structure **300** may include a first decoration unit **361**, a second decoration unit **362**, and a third decoration unit **363**. The first decoration unit **361** may be disposed on the inner circumference of the first opening **341**, the second decoration unit **362** may be disposed on the inner circumference of the second opening **342**, and the third decoration unit **363** may be disposed on the inner circumference of the third opening **343**. Referring to the cross-section (e.g., FIG. 4A) of the camera structure **300**, side surfaces of the first decoration unit **361**, the second decoration unit **362**, and the third decoration unit **363** may have inclinations (e.g., may be sloped).

(70) According to various embodiments, as illustrated in FIG. 3C, the first decoration unit **361**, the second decoration unit **362**, and the third decoration unit **363** may be configured in a ring shape. The sizes of the first decoration unit **361**, the second decoration unit **362**, and the third decoration unit **363** may be the same. For example, the diameter B of the outer circumference of the first decoration unit **361**, the diameter B of the outer circumference of the second decoration unit **362**, and the diameter B of the outer circumference of the third decoration unit **363** may be the same with one another, and the diameter C of the inner circumference of the first decoration unit **361**, the diameter C of the inner circumference of the second decoration unit **362**, and the diameter C of the inner circumference of the third decoration unit **363** may be the same with one another. The width W of the first decoration unit **361**, the width W of the second decoration unit **362**, and the width W of the third decoration unit **363** may also be the same. The width W may refer to the distance between the outer circumferential surface and the inner circumferential surface of the decoration unit. For example, the diameter B of the outer circumference of the decoration unit may be 12.3 mm, the diameter C of the inner circumference of the decoration unit may be 11 mm, and the width W of the decoration unit may be about 1.3 mm. The first decoration unit **361**, the second decoration unit **362**, and the third decoration unit **363** may be machined in the same way by a machining body of the same size, and thus external shapes of the decoration units may be the same.

(71) According to various embodiments, the first decoration unit **361**, the second decoration unit **362**, and the third decoration unit **363** may be configured by machining the cover housing **340**. For example, the first decoration unit **361**, the second decoration unit **362**, and the third decoration unit **363** may be configured by machining a portion of the cover housing **340** using a computerized numerical control (CNC) method. In an embodiment, the first decoration unit **361**, the second decoration unit **362**, and the third decoration unit **363** may be separately machined to be arranged on the cover housing **340**.

(72) According to various embodiments, the first covering unit **371** may be disposed on the inner circumference of the first decoration unit **361** such that at least a portion between the first camera barrel **312** and the first decoration unit **361** is filled. The third covering unit **373** may be disposed on the inner circumference of the third decoration unit **363** such that at least a portion between the third camera barrel **332** and the third decoration unit **363** is filled. The surface of the first covering unit **371** and the surface of the third covering unit **373** may be anodized. For example, the surface of the first covering unit **371** and the surface of the third covering unit **373** may be anodized with a material having low light transmittance. The first covering unit **371** and the third covering unit **373** may be omitted as necessary. For example, in a case in which the first camera **310** and the third

camera **330** include an OIS unit, the first covering unit **371** and the third covering unit **373** may be omitted or the sizes thereof may be adjusted in consideration of driving of the OIS unit.

(73) According to various embodiments, covering plates **381** and **382** (e.g., cover plate) may be fitted around at least one among the first camera barrel **312** of the first camera **310**, the second camera barrel **322** of the second camera **320**, and the third camera barrel **332** of the third camera **330**. The covering plates **381** and **382** may be configured in a shape which may be fitted around the camera barrels. For example, as illustrated in FIG. **3A**, in a case in which the covering plates are fitted around the first camera barrel **312** and the second camera barrel **322** configured in a cylindrical shape, the covering plates **381** and **382** are configured in a ring shape to be fitted around the first camera barrel **312** and the second camera barrel **322**. The covering plates **381** and **382** may be configured of a material having low transmittance. In an embodiment, the width of the first covering plate **381** fitted around the first camera barrel **312** may be smaller than the width of the second covering plate **382** fitted around the second camera barrel **322**.

(74) FIG. **4A** is a cross-sectional view of the camera structure taken along line D1-D1 of FIG. **3D**.

(75) According to various embodiments, the first camera barrel **312** of the first camera **310** may be disposed to allow at least a portion thereof to be inserted into the first opening **341** of the cover housing **340**.

(76) According to various embodiments, the first decoration unit **361** and the first covering unit **371** may be arranged at the first opening **341** of the cover housing **340**. The inner circumference of the first decoration unit **361** may have an inclination (e.g., be sloped). The first decoration unit **361** may be configured to have a decreasing diameter. The first decoration unit **361** may be configured to have a diameter decreasing away from the camera window **350**.

(77) As illustrated in FIG. **4A**, a first inclined surface **361A** may be configured on the first decoration unit **361**. For example, the first decoration unit **361** may include the first inclined surface **361A** having an inclination of 17 degrees to 20 degrees. In an embodiment, the surface (a first inclined surface **361A**) of the first decoration unit **361** may be anodized. The surface **361A** of the first decoration unit **361**, configured to have a gradually decreasing diameter, may provide a three-dimensional effect to a user. In an embodiment, a hair line may be formed on the surface **361A** of the first decoration unit **361**.

(78) According to various embodiments, the first covering unit **371** may be disposed on the inner circumference of the first decoration unit **361**. The first covering unit **371** may be configured to fill at least a portion of the space between the first decoration unit **361** and the first camera barrel **312**. The first covering unit **371** may fill at least a portion of the section between the first decoration unit **361** and the first camera barrel **312** such that the space between the first decoration unit **361** and the first camera barrel **312** is not viewed through the first transparent area **351** of the camera window **350**. A material (e.g., a black material) having low transmittance may be disposed on the surface **371A** of the first covering unit **371**. The surface **371A** of the first covering unit **371** may be configured to have low transmittance by anodizing.

(79) According to various embodiments, the first transparent area **351** of the camera window **350** may be disposed at a portion corresponding to the first camera **310**. According to an embodiment, the diameter of the first transparent area **351** may be the same as the diameter of the outer circumference of the first decoration unit **361**.

(80) According to various embodiments, the first covering plate **381** may be fitted around the first camera barrel **312**. The first covering plate **381** may fill at least a portion of the section between the first decoration unit **361** and the first camera barrel **312** such that the space between the first decoration unit **361** and the first camera barrel **312** is not viewed through the first transparent area **351** of the camera window **350**.

(81) According to various embodiments, a portion excluding the first lens assembly **311** of the first camera **310** may be shielded by the first covering unit **371** and the first covering plate **381**.

(82) FIG. **4B** is a cross-sectional view of the camera structure taken along line D2-D2 of FIG. **3D**.



(83) According to various embodiments, the second camera barrel **322** of the second camera **320** may be disposed to allow at least a portion thereof to be inserted into the second opening **342** of the cover housing **340**.

(84) According to various embodiments, the second decoration unit **362** may be disposed on the second opening **342** of the cover housing **340**. The inner circumference of the second decoration unit **362** may have an inclination (e.g., be sloped). The second decoration unit **362** may be configured to have a gradually decreasing diameter. The second decoration unit **362** may be configured to have a diameter decreasing away from the camera window **350**.

(85) As illustrated in FIG. 4B, a second inclined surface **362A** may be configured on the second decoration unit **362**. For example, the second decoration unit **362** may include the second inclined surface **362A** having an inclination of about 15 degrees to 20 degrees. In an embodiment, the surface (the second inclined surface **362A**) of the second decoration unit **362** may be anodized. The surface **362A** of the second decoration unit **362**, configured to have a gradually decreasing diameter, may provide a three-dimensional effect to a user. In an embodiment, a hair line may be formed on the surface **362A** of the second decoration unit **362**.

(86) According to various embodiments, the second transparent area **352** of the camera window **350** may be disposed at a portion corresponding to the second camera **320**. In an embodiment, the diameter of the second transparent area **352** may be the same as the diameter of the outer circumference of the second decoration unit **362**.

(87) According to an embodiment, the second camera barrel **322** of the second camera **320** may be disposed to be spaced a predetermined gap **G** apart from the second decoration unit **362**. This may be in consideration of the movement of the second camera barrel **322** by the OIS driving of the second camera **320**. For example, the gap **G** may be about 0.9 mm. The separation distance (gap **G**) between the second camera barrel **322** and the second decoration unit **362** may be at least greater than the operation range of the second camera barrel **322** by the OIS driving. In an embodiment, the second covering unit (not shown) may be disposed between the second camera barrel **322** and the second decoration unit **362**. For example, in a case in which the second camera **320** does not include the OIS unit, the second covering unit may be disposed on the inner circumference of the second decoration unit **362** to fill the space between the second camera barrel **322** and the second decoration unit **362**. In an embodiment, the second covering unit, of which the size has been adjusted to fill at least a portion of the section between the second camera barrel **322** and the second decoration unit **362**, may be disposed on the inner circumference of the second decoration unit **362**.

(88) According to various embodiments, the second covering plate **382** may be fitted around the second camera barrel **322**. The second covering plate **382** may fill at least a portion of the section between the second decoration unit **362** and the second camera barrel **322** such that the space between the second decoration unit **362** and the second camera barrel **322** is not viewed through the second transparent area **352** of the camera window **350**. As illustrated in FIG. 4B, the second covering plate **382** may be configured to extend, so as to overlap the second decoration unit **362** in at least a partial section. Even though the second camera barrel **322** is moved by the OIS driving, the second covering plate **382** overlapping the second decoration unit **362** may block the space between the second decoration unit **362** and the second camera barrel **322** from being viewed to the outside through the second transparent area **352**.

(89) According to various embodiments, a portion excluding the second lens assembly **312** of the second camera **320** may be shielded by the second covering plate **382**.

(90) According to various embodiments, an inclination (e.g., slope) may be configured on the inner circumference of the third decoration unit **363** (see FIG. 3A) disposed on the third opening **343** (see FIG. 3A) of the cover housing **340** (see FIG. 3A). The third decoration unit may be configured to have a decreasing diameter. The third decoration unit may include a third inclined surface **361A**, like the first inclined surface **361A** of the first decoration unit **361** and the second inclined surface

**362A** of the second decoration unit **362**. The third decoration unit **363** may be configured to have a diameter decreasing away from the camera window **350**, similar to the first decoration unit **361** and the second decoration unit **362**.

(91) FIG. 5 is a side view of an example first camera and an example second camera according to various embodiments disclosed herein.

(92) Reference numerals and descriptions of the same components as those described above among the components shown in FIG. 5 will not be repeated.

(93) According to various embodiments, grooves **510** and **520** may be configured on the outer circumferences of the camera barrels (e.g., the first camera barrel **312** and the second camera barrel **322**) around which the covering plates are fitted, to allow the covering plates to be fitted thereinto. The first covering plate **381** may be fitted into a first groove **510** disposed on the first camera barrel **312** to be fixed in position, and the second covering plate **382** may be fitted into a second groove **520** configured on the second camera barrel **322** to be fixed in position.

(94) According to various embodiments, the surfaces of the first covering plate **381** and the second covering plate **382** may be configured to be identical or similar to the surfaces of the first camera barrel **312** and the second camera barrel **322** so that the first camera barrel **312** and the second camera barrel **322** and the first covering plate **381** and the second covering plate **382** viewed through the camera window **350** have a sense of aesthetic unity.

(95) FIG. 6 is a cross-sectional view of an example camera structure according to various embodiments.

(96) Detailed descriptions of the same components as those described above among the components shown in FIG. 6 will not be repeated.

(97) According to various embodiments, a shielding unit **610** (e.g., shield) configured of a material capable of shielding light may be disposed on at least a portion of the surface (hereinafter, referred to as “the first surface **352A**”) facing the second camera **320** in the second transparent area **352** of the camera window **350**. The shielding unit **610** may reduce a phenomenon in which light reflected from the second decoration unit **362** is partially reflected from the first surface **352A** of the second transparent area **352** to be incident on the second lens assembly **321** of the second camera **320**. The shielding unit **610** may shield light reflected from the second decoration unit **362** to reduce a phenomenon in which light is reflected from the first surface **352A** of the second transparent area **352**. The area in which the shielding unit **610** is disposed may be determined by a portion in which light reflected from the second decoration unit **362** reaches the first surface **352A** of the second transparent area **352**. According to the inclination of the second inclined surface **362A** of the second decoration unit **362**, the reflection angle of light reflected from the second decoration unit **362** may vary, and a portion at which the reflected light reaches the first surface **352A** of the second transparent area **352** may vary. An area in which the shielding unit **610** is disposed may be adjusted according to the inclination (or the inclination angle) of the second inclined surface **362A** of the second decorating unit **362**. For example, in a case in which the inclination of the second decoration unit **362** is about 15 degrees to 20 degrees, the length of the shielding unit **610** may be about 0.5 mm.

(98) In the above description, the shielding unit **610** has been described to be disposed in the second transparent area **352** for convenience of description, but the shielding unit **610** may also be disposed in the first transparent area **351** (see FIG. 3A) and the third transparent area **353** (see FIG. 3A).

(99) FIG. 7 is a view for explaining a machining method of a decoration unit and a covering unit (e.g., cover) according to various embodiments disclosed herein. Hereinafter, descriptions will be made, with reference to the first decoration unit **361** and the first shielding unit **371**. The second decoration unit **362**, the third decoration unit **363**, and the third covering unit **373** may be machined in the same manner as the first decoration unit **361** and the first covering unit **371**.

(100) According to various embodiments, the first decoration unit **361**, the second decoration unit

**362**, and the third decoration unit **363** may be processed and configured by a first machining body **710** of the same size. For example, the diameter of the first machining body **710** may be greater than the diameters of the outer circumferences of the first decoration unit **361**, the second decoration unit **362**, and the third decoration unit **363**. The first machining body **710** may include an inclined surface **710A** such that the first inclined surface **361A** of the first decoration part **361** is configured. The first machining body **710** may machine the cover housing **340** by rotation to configure the first decoration unit **361**. The first decoration unit **361**, the second decoration unit, and the third decoration unit **363** may be configured by using one machining body, and thus machining costs may be reduced. In addition, machining may be performed at once using the machining body greater than the first decoration unit **361**, the second decoration unit **362**, and the third decoration unit **363**, and thus the first inclined surface **361A** may be more uniformly configured. Since machining may be performed at once by using the machining body, the first inclined surface **361A** may have a higher luminance than the surrounding instruments. Anodizing may be performed on the first inclined surface **361A** of which the inclination is uniformly configured. By performing anodizing, the first decoration unit **361**, the second decoration unit **362**, and the third decoration unit **363** may have high reflectance (luminance).

(101) According to various embodiments, the first covering unit **371** and the third covering unit **373** may be machined by a second machining body **720** having a diameter of which the size is the same as those of the diameters of the inner circumferences of the decoration units **361**, **362**, and **363**. Surfaces of the first covering unit **371** and the third covering unit **373** may be configured to have low light transmittance via anodizing. The surfaces of the first covering unit **371** and the third covering unit **373** may be machined to configure inclinations.

(102) An electronic device according to various embodiments disclosed herein may include a first camera including a first camera barrel in which a first lens assembly is accommodated, a second camera including a second camera barrel in which a second lens assembly is accommodated, a cover housing including a first opening corresponding to the first camera barrel of the first camera and a second opening corresponding to the second camera barrel of the second camera and disposed to substantially cover the first camera and the second camera, a camera window including a first transparent area at a portion corresponding to the first opening and a second transparent area at a portion corresponding to the second opening and disposed on the cover housing, a first decoration unit disposed on an inner circumference of the first opening of the cover housing and having an inclination formed on the inner circumference thereof, and a second decoration unit disposed on an inner circumference of the second opening of the cover housing and having an inclination formed on the inner circumference thereof, wherein the diameters of the first transparent area and the second transparent area of the camera window may be the same with each other, and the diameters of the first decoration unit and the second decoration unit may be the same with each other.

(103) In addition, the first decoration unit, and the second decoration unit may be ring-shaped, the diameter of the outer circumference of the first decoration unit may be the same as the diameter of the first transparent area of the camera window, and the diameter of the outer circumference of the second decoration unit may be the same as the diameter of the second transparent area of the camera window.

(104) In addition, the electronic device may further include a first cover disposed on the inner circumference of the first decoration unit to fill at least a portion of the section between the first camera barrel and the first decoration unit.

(105) In addition, a surface of the first cover may be anodized to be configured to have low light transmittance.

(106) In addition, the second camera may further include an optical image stabilizer (OIS) configured to move the second camera barrel, and may further include a cover plate fitted around the second camera barrel.

(107) In addition, in the first transparent area of the camera window, a shield may be disposed in at least a partial area of the surface facing the first camera.

(108) In addition, in the second transparent area of the camera window, a shield may be disposed in at least a partial area of the surface facing the second camera.

(109) In addition, the first decoration unit and the second decoration unit may be configured such that a partial area of the cover housing is machined by a machining body having a diameter greater than the diameters of the first decoration unit and the second decoration unit.

(110) In addition, the electronic device may further include a third camera including a third camera barrel in which a third lens assembly is accommodated, the cover housing may further include a third opening corresponding to the third camera barrel of the third camera, the camera window may further include a third transparent area at a portion corresponding to the third opening and may further include a third decoration unit disposed on the inner circumference of the third opening of the cover housing and having an inclination formed on the inner circumference thereof, the diameters of the first transparent area, the second transparent area, and the third transparent area of the camera window may be the same with each other, and the diameters of the first decoration unit, the second decoration unit, and the third decoration unit may be the same with each other.

(111) In addition, the third decoration unit may be ring-shaped, and the diameter of the outer circumference of the third decoration unit may be the same as the diameter of the third transparent area.

(112) In addition, the electronic device may further include a third cover disposed on the inner circumference of the third decoration unit to fill at least a portion of the section between the third camera barrel and the third decoration unit, and a surface of the third cover may be anodized to be configured to have low light transmittance.

(113) In addition, the first decoration unit, the second decoration unit, and the third decoration unit may be configured such that a partial area of the cover housing is machined by a machining body have a diameter greater than the diameters of the first decoration unit, the second decoration unit, and the third decoration unit.

(114) A camera structure according to various embodiments disclosed herein may include a first camera including a first camera barrel in which a first lens assembly is accommodated, a second camera including a second camera barrel in which a second lens assembly is accommodated, a cover housing including a first opening corresponding to the first camera barrel of the first camera and a second opening corresponding to the second camera barrel of the second camera and disposed to substantially cover the first camera and the second camera, a camera window including a first transparent area at a portion corresponding to the first opening and a second transparent area at a portion corresponding to the second opening and disposed on the cover housing, a first decoration unit configured to have a diameter decreasing away from the camera window and disposed on the inner circumference of the first opening of the cover housing, and a second decoration unit configured to have a diameter decreasing away from the camera window and disposed on the inner circumference of the second opening of the cover housing, wherein the diameters of the first transparent area and the second transparent area of the camera window may be the same with each other, and the diameters of the first decoration unit and the second decoration unit may be the same with each other.

(115) In addition, the first decoration unit and the second decoration unit may be ring-shaped, the diameter of the outer circumference of the first decoration unit may be the same as the diameter of the first transparent area of the camera window, and the diameter of the outer circumference of the second decoration unit may be the same as the diameter of the second transparent area of the camera window.

(116) In addition, the camera structure may further include a first cover disposed on the inner circumference of the first decoration unit to fill at least a portion of the section between the first camera barrel and the first decoration unit.

(117) In addition, the surface of the first cover may be anodized to be configured to have low light transmittance.

(118) In addition, the second camera may further include an optical image stabilizer (OIS) configured to move the second camera barrel, and may further include a cover plate fitted around the second camera barrel.

(119) In addition, in the second transparent area of the camera window, a shield may be disposed in at least a partial area of the surface facing the second camera.

(120) In addition, the camera structure may further include a third camera including a third camera barrel in which a third lens assembly is accommodated, the cover housing may further include a third opening corresponding to the third camera barrel of the third camera, the camera window may further include a third transparent area at a portion corresponding to the third opening and may further include a third decoration unit configured to have a diameter decreasing away from the camera window to be disposed on the inner circumference of the third opening of the cover housing and a third cover disposed on the inner circumference of the third decoration unit so as to fill the space between the third camera barrel and the third decoration unit, the diameters of the first transparent area, the second transparent area, and the third transparent area of the camera window may be the same with each other, the diameters of the first decoration unit, the second decoration unit, and the third decoration unit may be the same with each other, and the surface of the third covering unit may be anodized to be configured to have low light transmittance.

(121) In addition, the first decoration unit, the second decoration unit, and the third decoration unit may be configured such that a partial area of the cover housing is machined by a machining body having a diameter greater than the diameters of the first decoration unit, the second decoration unit, and the third decoration unit.

(122) The embodiments disclosed in the specification and drawings in the disclosure are merely presented as specific examples to easily describe the technical contents according to the embodiments disclosed herein and to help understanding of the embodiments disclosed herein, and are not intended to limit the scope of the embodiments disclosed herein. Therefore, the scope of various embodiments disclosed herein should be construed to include, in addition to the embodiments disclosed herein, all changes or modifications derived based on the technical ideas of various embodiments disclosed herein.

(123) While the disclosure has been illustrated and described with reference to various example embodiments, it will be understood that the various example embodiments are intended to be illustrative, not limiting. It will be further understood by those skilled in the art that various changes in form and detail may be made without departing from the true spirit and full scope of the disclosure, including the appended claims and their equivalents. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

## Claims

1. An electronic device comprising: a first camera comprising a first camera barrel accommodating a first lens assembly; a second camera comprising a second camera barrel accommodating a second lens assembly; a cover housing disposed to substantially cover the first camera and the second camera and comprising a first opening corresponding to the first camera barrel of the first camera and a second opening corresponding to the second camera barrel of the second camera; a camera window disposed on the cover housing and comprising a first transparent area at a portion corresponding to the first opening and a second transparent area at a portion corresponding to the second opening; a first decoration unit disposed on an inner circumference of the first opening of the cover housing and having an inclination formed on the inner circumference thereof; and a second decoration unit disposed on an inner circumference of the second opening of the cover

housing and having an inclination formed on the inner circumference thereof, wherein diameters of the first transparent area and the second transparent area of the camera window are the same with each other, and wherein diameters of the first decoration unit and the second decoration unit are the same with each other.

2. The electronic device of claim 1, wherein the first decoration unit and the second decoration unit are ring-shaped, wherein a diameter of an outer circumference of the first decoration unit is the same as a diameter of the first transparent area of the camera window, and wherein a diameter of an outer circumference of the second decoration unit is the same as a diameter of the second transparent area of the camera window.

3. The electronic device of claim 2, further comprising a first cover disposed on the inner circumference of the first decoration unit to fill at least a portion of a section between the first camera barrel and the first decoration unit.

4. The electronic device of claim 3, wherein a surface of the first cover is anodized to have low light transmittance.

5. The electronic device of claim 1, wherein the second camera further comprises an optical image stabilizer (OIS) configured to move the second camera barrel and further comprises a cover plate fitted around the second camera barrel.

6. The electronic device of claim 1, wherein, in the first transparent area of the camera window, a shield is disposed in at least a partial area of a surface facing the first camera.

7. The electronic device of claim 1, wherein, in the second transparent area of the camera window, a shield is disposed in at least a partial area of a surface facing the second camera.

8. The electronic device of claim 1, wherein the first decoration unit and the second decoration unit are configured such that a partial area of the cover housing is machinable by a machining body having a diameter greater than the diameters of the first decoration unit and the second decoration unit.

9. The electronic device of claim 1, further comprising a third camera comprising a third camera barrel accommodating a third lens assembly, wherein the cover housing further comprises a third opening corresponding to the third camera barrel of the third camera, wherein the camera window further comprises: a third transparent area at a portion corresponding to the third opening; and a third decoration unit disposed on an inner circumference of the third opening of the cover housing and having an inclination formed on the inner circumference thereof, wherein diameters of the first transparent area, the second transparent area, and the third transparent area are the same with each other, and wherein diameters of the first decoration unit, the second decoration unit, and the third decoration unit are the same with each other.

10. The electronic device of claim 9, wherein the third decoration unit is ring-shaped, and wherein a diameter of an outer circumference of the third decoration unit is the same as a diameter of the third transparent area.

11. The electronic device of claim 10, further comprising a third cover disposed on an inner circumference of the third decoration unit to fill at least a portion of a section between the third camera barrel and the third decoration unit, wherein a surface of the third cover is anodized to have low light transmittance.

12. The electronic device of claim 9, wherein the first decoration unit, the second decoration unit, and the third decoration unit are configured such that a partial area of the cover housing is machinable by a machining body having a diameter greater than the diameters of the first decoration unit, the second decoration unit, and the third decoration unit.

13. A camera structure comprising: a first camera comprising a first camera barrel accommodating a first lens assembly; a second camera comprising a second camera barrel accommodating a second lens assembly accommodated; a cover housing disposed to substantially cover the first camera and the second camera and comprising a first opening corresponding to the first camera barrel of the first camera and a second opening corresponding to the second camera barrel of the second camera;

a camera window disposed on the cover housing and comprising a first transparent area at a portion corresponding to the first opening and a second transparent area at a portion corresponding to the second opening; a first decoration unit configured to have a diameter decreasing away from the camera window and disposed on an inner circumference of the first opening of the cover housing; and a second decoration unit configured to have a diameter decreasing away from the camera window and disposed on an inner circumference of the second opening of the cover housing, wherein diameters of the first transparent area and the second transparent area of the camera window are the same with each other, and wherein diameters of the first decoration unit and the second decoration unit are the same with each other.

14. The camera structure of claim 13, further comprising a first cover disposed on the inner circumference of the first decoration unit to fill at least a portion of a section between the first camera barrel and the first decoration unit.

15. The camera structure of claim 13, wherein the second camera further comprises an optical image stabilizer (OIS) configured to move the second camera barrel, and further comprises a cover plate fitted around the second camera barrel.

---