US Patent & Trademark Office
Patent Public Search | Text View

Electroadhesion device

Abstract

Disclosed embodiments include a selfie camera system for capturing selfie content and sharing captured content on a social media and/or a video streaming platform. In various embodiments, selfie camera makes capturing higher quality selfie content more efficient by providing a preview of the selfie content before and after capture. One or more aspects of previews may be modified to simulate content displayed on a social media and/or video streaming platform. The selfie camera may be easily attached to any surface using one or more mounting mechanisms to allow the selfie camera for function as a personal, private photographer than can capture any scene from a variety of perspectives using a variety of capture sequences.

Inventors:	**Koci; Denis (Woodland Hills, CA)**
Applicant:	**SELFIE SNAPPER, INC.** (Sherman Oaks, CA)
Family ID:	**1000008749546**
Assignee:	**SELFIE SNAPPER, INC. (Sherman Oaks, CA)**
Appl. No.:	**18/235770**
Filed:	**August 18, 2023**

Prior Publication Data

Document Identifier	Publication Date
US 20230403461 A1	Dec. 14, 2023

Related U.S. Application Data

continuation parent-doc US 17671498 20220214 US 11770607 child-doc US 18235770
continuation parent-doc US 16922979 20200707 US 11283982 20220322 child-doc US 17671498
us-provisional-application US 62956054 20191231
us-provisional-application US 62871158 20190707

Publication Classification

Int. Cl.: H04N23/661 (20230101); **G02B7/36** (20210101); **H04N23/67** (20230101)

U.S. Cl.:

CPC **H04N23/661** (20230101); **H04N23/67** (20230101); G02B7/36 (20130101)

Field of Classification Search

CPC: H04N (23/661); H04N (23/67); H04N (23/60); H04N (23/65); G02B (7/36); G03B (15/10); G03B (2206/00); G03B (2217/002); G03B (2217/007); G03B (17/02); G03B (17/56); H04M (2250/52); H04M (1/72412)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7328119	12/2007	Pryor et al.	N/A	N/A

7551419	12/2008	Pelrine et al.	N/A	N/A
7554787	12/2008	Pelrine et al.	N/A	N/A
7684694	12/2009	Fromm	N/A	N/A
7773363	12/2009	Pelrine et al.	N/A	N/A
7872850	12/2010	Pelrine et al.	N/A	N/A
8111500	12/2011	Pelrine et al.	N/A	N/A
8125758	12/2011	Pelrine et al.	N/A	N/A
8325458	12/2011	Prahlad et al.	N/A	N/A
D692473	12/2012	Kawaguchi et al.	N/A	N/A
8564926	12/2012	Prahlad et al.	N/A	N/A
D697122	12/2013	Ikegame	N/A	N/A
8665578	12/2013	Pelrine et al.	N/A	N/A
8861171	12/2013	Prahlad et al.	N/A	N/A
8982531	12/2014	Prahlad et al.	N/A	N/A
9401668	12/2015	Prahlad et al.	N/A	N/A
D779577	12/2016	Ikegame	N/A	N/A
D781363	12/2016	Ikegame	N/A	N/A
D797836	12/2016	Li	N/A	N/A
9769332	12/2016	Delaunay et al.	N/A	N/A
D848512	12/2018	Kamei	N/A	N/A
D849077	12/2018	Tian	N/A	N/A
10452146	12/2018	Khoshkava	N/A	G06F 3/016
D876518	12/2019	Tran et al.	N/A	N/A
D887478	12/2019	Brickner et al.	N/A	N/A
D894994	12/2019	Yu	N/A	N/A
D906399	12/2019	Wang	N/A	N/A
D908765	12/2020	Wang	N/A	N/A
D916166	12/2020	Li	N/A	N/A
D939607	12/2020	Koci	N/A	N/A
2003/0067734	12/2002	Nakano	N/A	N/A
2006/0010454	12/2005	Napoli et al.	N/A	N/A
2006/0244620	12/2005	Sotiriou	N/A	N/A
2007/0074115	12/2006	Patten et al.	N/A	N/A
2007/0081094	12/2006	Ciudad et al.	N/A	N/A
2007/0254640	12/2006	Bliss	N/A	N/A
2008/0037971	12/2007	Takami et al.	N/A	N/A
2008/0089002	12/2007	Pelrine et al.	N/A	N/A
2008/0211341	12/2007	Pelrine et al.	N/A	N/A
2009/0065348	12/2008	Fujii	N/A	N/A
2010/0249553	12/2009	MacLaughlin	600/324	A61B 5/257
2011/0193362	12/2010	Prahlad et al.	N/A	N/A
2012/0062691	12/2011	Fowler et al.	N/A	N/A
2012/0120544	12/2011	Pelrine et al.	N/A	N/A
2013/0242455	12/2012	Prahlad et al.	N/A	N/A
2013/0292303	12/2012	Prahlad et al.	N/A	N/A
2013/0294875	12/2012	Prahlad et al.	N/A	N/A
2014/0009861	12/2013	Tatsumi et al.	N/A	N/A
2014/0036404	12/2013	Prahlad et al.	N/A	N/A
2014/0085460	12/2013	Park et al.	N/A	N/A
2014/0108552	12/2013	Singh et al.	N/A	N/A
2014/0133062	12/2013	Prahlad et al.	N/A	N/A
2015/0138595	12/2014	Sugimoto	N/A	N/A
2016/0041628	12/2015	Verma	N/A	N/A
2016/0094078	12/2015	Graham et al.	N/A	N/A
2016/0100034	12/2015	Miller	N/A	N/A
2016/0318190	12/2015	Prahlad	N/A	H01L 21/6833
2016/0350953	12/2015	Mittelstaedt et al.	N/A	N/A
2017/0031235	12/2016	Kubotera et al.	N/A	N/A
2017/0068149	12/2016	Fromm	N/A	N/A
2017/0072407	12/2016	Prahlad et al.	N/A	N/A
2017/0291806	12/2016	Lessing et al.	N/A	N/A
2017/0331952	12/2016	Rogers et al.	N/A	N/A
2017/0372525	12/2016	Rosenthal et al.	N/A	N/A
2018/0054595	12/2017	Odamaki et al.	N/A	N/A
2018/0137523	12/2017	Kim et al.	N/A	N/A
2018/0350148	12/2017	George	N/A	N/A
2018/0356711	12/2017	Otsuka et al.	N/A	N/A
2019/0047157	12/2018	Shintake et al.	N/A	N/A

2019/0075922	12/2018	Rivera et al.	N/A	N/A
2019/0098190	12/2018	Hosoe	N/A	N/A
2019/0158136	12/2018	DiLella	N/A	N/A
2019/0172743	12/2018	McIntyre et al.	N/A	N/A
2019/0263595	12/2018	Prahlad	N/A	B65G 54/02
2020/0338731	12/2019	Lynders et al.	N/A	N/A
2021/0006181	12/2020	Koci	N/A	N/A
2021/0006706	12/2020	Koci	N/A	N/A
2021/0008416	12/2020	DeCarlo	N/A	N/A
2021/0203245	12/2020	Koci	N/A	N/A
2021/0386219	12/2020	Koci	N/A	N/A
2021/0387347	12/2020	Koci	N/A	N/A
2022/0009086	12/2021	Verma	N/A	N/A
2022/0174205	12/2021	Koci	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103597519	12/2013	CN	N/A
203889500	12/2013	CN	N/A
2033216	12/2008	EP	N/A
2041784	12/2008	EP	N/A
2533951	12/2011	EP	N/A
2548299	12/2012	EP	N/A
2844592	12/2014	EP	N/A
3056016	12/2015	EP	N/A
3086016	12/2015	EP	N/A
2041784	12/2016	EP	N/A
3343507	12/2017	EP	N/A
2033216	12/2019	EP	N/A
H07210104	12/1994	JP	N/A
H08191098	12/1995	JP	N/A
2006500894	12/2005	JP	N/A
2007251083	12/2006	JP	N/A
2008282118	12/2007	JP	N/A
2009262860	12/2008	JP	N/A
2009539684	12/2008	JP	N/A
5038405	12/2011	JP	N/A
2012243991	12/2011	JP	N/A
2013519532	12/2012	JP	N/A
5329398	12/2012	JP	N/A
2014236544	12/2013	JP	N/A
5832386	12/2014	JP	N/A
5883430	12/2015	JP	N/A
5940028	12/2015	JP	N/A
2017511262	12/2016	JP	N/A
2017199179	12/2016	JP	N/A
6423200	12/2017	JP	N/A
20080106270	12/2007	KR	N/A
20160131821	12/2015	KR	N/A
20220043574	12/2021	KR	N/A
2007143662	12/2006	WO	N/A
2008070201	12/2007	WO	N/A
2011100028	12/2010	WO	N/A
2011116357	12/2010	WO	N/A
2012150028	12/2011	WO	N/A
2013166329	12/2012	WO	N/A

OTHER PUBLICATIONS

Guo J., et al., "Electroadhesion Technologies for Robotics: A Comprehensive Review," IEEE Transactions on Robotics, Apr. 2020, vol. 36, No. 2, DOI:10.1109/TRO.2019.2956869, XP011781873, [Retrieved on Aug. 21, 2021] Retrieved from URL: https://ieeexplore.ieee.org/document/8946902. cited by applicant

Savioli et al., "Morphing Electroadhesive Interface to Manipulate Uncooperative Objects," Proceedings of the SPIE, vol. 9061, id. 906129, Publication date Mar. 2014, 14 pages. cited by applicant

Extended European Search Report for Application No. 20837304.3, dated Oct. 4, 2023, 13 Pages. cited by applicant

Extended European Search Report for Application No. 20908755.0, dated Feb. 16, 2024, (13 Pages). cited by applicant

First Examination Report for Indian Patent Application No. 202247006152, dated Dec. 28. 2023 (6 pages). cited by applicant

Office Action for Canadian Patent Application No. 3163370, mailed Mar. 19, 2024, 4 pages. cited by applicant

Office Action for Japanese Patent Application No. 2022501135, mailed Jun. 13, 2024, 13 pages. cited by applicant

Yuan M., et al., "A Mixed Reality Virtual Clothes Try-on System," IEEE Transaction on Multimedia, Dec. 2013, vol. 15, No. 8, 11 pages. cited

Amazon, What is an API (Application Programming Interface), downloaded on Oct. 15, 2024, 6 pages, Retrieved from the Internet URL: https://aws.amazon.com/whatis/api/#:~:text=APIs%20are%20mechanisms%20that%20enable,use%20Simple%20Object%20Access%20Protoco
cited by applicant
Examination Report No. 1 for Australian Patent Application No. 2020309528 dated Jan. 14, 2025, 4 pages. cited by applicant
Office Action for Japanese Patent Application No. 2022-540681, mailed Dec. 2, 2024, 13 pages. cited by applicant
Office Action for Korean Patent Application No. 10-2022-7004022 mailed Nov. 25, 2024, 24 pages. cited by applicant
Office Action for Japanese Patent Application No. 2022-540681, mailed Jun. 19, 2025, 09 pages. cited by applicant
Office Action for Korean Patent Application No. 10-2022-7026452, mailed May 13, 2025, 19 pages. cited by applicant

Primary Examiner: Selby; Gevell V

Attorney, Agent or Firm: DLA PIPER LLP (US)

Background/Summary

PRIORITY CLAIM (1) This application is a Continuation of and claims priority to Ser. No. 17/671,498 filed 14 Feb. 2022 which is a continuation of and in turn claims priority to U.S. non-provisional Ser. No. 16/922,979 filed 7 Jul. 2020 which in turn claims priority from U.S. Provisional 62/956,054 filed 31 Dec. 2019 and U.S. Provisional 62/871,158 filed 7 Jul. 2019, the entirety of which are hereby incorporated by reference.

FIELD
(1) The present disclosure relates generally to cameras and image processing, in particular, systems and methods for capturing and sharing selfie content.
BACKGROUND
(2) Every day people take millions of self-portrait or "selfie" photos. Many of these photos are uploaded to social media platforms and shared as posts that provide updates about the selfie subject to a network of followers. Taking a good selfie is hard and a lot of time is wasted in re-taking photos to get the pose, angle, lighting, background, and other characteristics just right. There is therefore a need to develop a camera system that reduces the number of takes and overall amount of time required to produce a good selfie.
(3) Taking a group selfie is also difficult and one or more people posing for a group photo are frequently cut off or left out of the shot. It would be desirable to have a camera system that allows for easy capture of group selfies that included everyone in a group.
(4) Post capture, uploading selfies to social media platforms is frustrating and time consuming. Manually transferring photos from one device to another and, once on the proper device, from one platform to another adds time and complexity to social media posting. Transfers between devices and platforms and also introduce additional editing time and result in data loss (e.g., accidentally deleted phots, resolution loss, etc.). There is therefore a need to develop a camera system that reduces the overall time needed to post selfies and other items of content to social media platforms.
(5) Previous attempts have been made to solve problems with capturing selfie content, but the arm capture method (i.e., pointing a smartphone camera at one's self and extending the camera away from the face/body to increase the field of view) is still the most commonly used technique. Although highly visible, selfie sticks provide only a marginally longer arm, therefore, maintain the limited capture angle and restricted field of view problems associated with arm capture. Remote timer and tripod systems have also been adapted to smartphones to take selfies but they take a long time to setup and do not provide an efficient way to preview photos before capture. Behavioral adaptions including mirror selfies and asking strangers to take photos have also been adopted but these solutions restrict the conditions in which selfies can be captured. No selfie specific camera solutions have been explored.

Description

BRIEF DESCRIPTION OF THE DRAWINGS
(1) Various objectives, features, and advantages of the disclosed subject matter can be more fully appreciated with reference to the following detailed description of the disclosed subject matter when considered in connection with the following drawings, in which like reference numerals identify like elements.
(2) FIG. **1** depicts an exemplary system for capturing and sharing selfie content including selfie images;
(3) FIG. **2** depicts an exemplary system for capturing and sharing selfie content including selfie videos;
(4) FIG. **3** illustrate more details of portions of the systems shown in FIGS. **1-2**;
(5) FIG. **4** illustrates an exemplary camera device used to capture selfie content;
(6) FIG. **5**A-M illustrate exemplary preview screens for previewing selfie content;
(7) FIG. **6** illustrates an exemplary electro adhesion system for mounting a camera device shown in FIG. **4**;
(8) FIGS. **7**A-B illustrate a selfie camera mounted to a foreign object using the exemplary electro adhesion system shown in FIG. **6**;
(9) FIG. **8**A-D illustrates an example mechanical mounting system for mounting a camera device shown in FIG. **4**;
(10) FIG. **9** is a flow diagram illustrating an exemplary process for capturing selfie content using the system shown in FIG. **1**;
(11) FIG. **10** is a flow diagram showing an exemplary process for streaming selfie content using the system shown in FIG. **2**;
(12) FIG. **11** is a block diagram of an illustrative user device that may be used to implement the system of FIG. **3**.
(13) FIG. **12** is a block diagram of an illustrative server device that may be used to implement the system of FIG. **3**.
(14) FIG. **13** is a block diagram of the camera device shown in FIG. **4**; and
(15) FIG. **14** is a block diagram illustrating more details of portions of the camera device shown in FIG. **13**.
DETAILED DESCRIPTION OF ONE OR MORE EMBODIMENTS
(16) As used herein, the terms "share", "shared", and "sharing" refer to the digital distribution of selfie content including images,

recorded video, and live video. Selfie content may be shared using a user device (e.g., personal computer, laptop, camera, smart phone, tablet, etc.) directly to another user device. Additionally, selfie content may be shared with an online community (e.g., social media network, public online audience, group of online friends, etc.) by uploading to a host website or posting to a social media platform.

(17) As used herein, the terms "subject" and "subjects" refer to the people, objects, landscapes, and/or background elements included in a photo or video. Human subjects may include a single person, multiple people, a group of people, multiple groups of people, and/or one or more crowds of people. Object subjects may include one or more pets, items and/or plates of food, one or more items of clothing, and/or any number of things or other objects.

(18) As used herein, the terms "user device" and "user devices" refer to any computer device having a processor, memory, and a display. Exemplary user devices can include a communications component for connecting to a selfie camera and may include smartphones, tablet computers, laptops, mobile computers, hand held computers, personal computers, and the like.

(19) As used herein, the terms "selfie image" and "selfie images" refer to images and videos of a person taken by that person. Portrait and/or self-portrait type images of objects (e.g., food, clothing, tools, jewelry, vehicles, memorabilia, personal items, and the like) and/or groups of people are also included in the terms "selfie image" and "selfie images" as disclosed herein.

(20) As used herein the terms "piece of content" and "pieces of content" refer to images, video, and other content capable of capture by a selfie camera of the disclosure. Selfie images are exemplary pieces of content. Pieces of content may be transferred as data files including image data, audiovisual data, and the like using file/data lossless transfer protocols such as HTTP, HTTPS or FTP.

EXEMPLARY EMBODIMENTS OF THE SYSTEM

(21) FIGS. **1**-**2** illustrate exemplary systems for capturing and sharing pieces of content including selfie images and videos. These systems may, for example, reduce the number of re-takes and overall time required to capture and share pieces of content including selfie images and videos. FIG. **1** illustrates an example embodiment of a selfie image system **100** that may capture and share pieces of content including selfie images. The selfie image system **100** may include a selfie camera **102** that captures pieces of content including a subject **110**. The selfie camera **102** may be communicatively coupled to a user device **104** using one or more connections **114** (e.g., a Bluetooth, Wifi, or other wireless or wired connection). The selfie camera **102** may stream a preview **108** of the area within the field of the view of the selfie camera **102** to a user device **104**. Using the user device **104** as a remote control, a user may capture a piece of content using the selfie camera **102**. In various embodiments, the preview **108** may include a live video showing the subject **110** and surrounding area captured by the image sensor of the selfie camera **102**. A user may view the preview **108** to assist the capture process by verifying the subject **110** appears as the user would like before deciding to initiate capture. When the subject **110** appears exactly how the user would like in the preview **108**, the user may capture a selfie image or other piece of content using the selfie camera **102** by remotely activating the selfie camera **102** using the user device **104**. The preview **108** of the captured image is then sent by the selfie camera **102** to a user device **104** and displayed on a user device display. If the user is happy with how the selfie image or other piece of content turned out, the user may share the selfie image or other piece of content to a social media platform **112**. If the user desires to capture another piece of content including the subject **110**, the first piece of content may be saved on the user device **104** or discarded and the preview **108** changed from displaying a captured piece of content back to displaying a live video of the subject **110** and surrounding area.

(22) The user device **104** may be a processor based device with memory, a display, and wired or wireless connectivity circuits that allow a user device **104** to communicate with the selfie camera **102** and/or the social media platform **112** and interact/exchange data with the selfie camera **102** and/or the social media platform **112** using a communications path **116**. For example, the user device **104** may communicate a message to selfie camera **102** to capture a piece of content and receive a data file including the piece of content in response from the selfie camera **102**. The image file may be displayed on a user device display as a preview **108**. The user device may be a smartphone device, such as an Apple iPhone product or an Android OS based system, a personal computer, a laptop computer, a tablet computer, a terminal device, and the like. The user device **104** may have an application (e.g., a web app or a mobile app) that is executed by the processor of the user device **104** that may display visual information to a user including the preview **108** before and/or after image capture and a user interface for editing and/or sharing selfie content. One example user interface is shown below in FIGS. **5A-5M**. The communications path **116** may include one or more wired or wireless networks/systems that allow the user device **104** to communicate with a social media platform **112** using a known data and transfer protocol. The social media platform may be any known social media application including Twitter, Facebook, Snapchat, Instagram, Wechat, Line, and the like.

(23) FIG. **2** illustrates an example embodiment of a selfie video **200** system that may capture and share pieces of content including videos. To capture selfie videos and other pieces of content the selfie camera **102** connects to a user device **104** using one or more connections **114** (e.g., a Bluetooth, Wifi, or other wireless or wired connection). Once connected to the selfie camera **102** a user device **104** may receive a live video preview **108** of a subject **110** from the selfie camera and display the preview **108** on a user device display. The preview **108** may show the subject **110** and the area surrounding the subject **110** as captured by the image sensor in the selfie camera **102**. Once the subject **110** appears as desired in the preview **108**, videos and other pieces of content captured by the selfie camera **102** may be streamed to a video streaming platform **202**. Remote control functionality included in an application (e.g., mobile app or web app) executed by the processor of the user device **104**, may cause a selfie camera **102** to record and/or share selfie videos and other pieces of content on a video streaming platform **202**. To share a piece of content on a video streaming platform, the selfie camera **102** may connect to a video streaming platform **202** using a communications path **116**. User account information, including account name and login information, may be received from a user device **104** as part of the connection process. A user device connected to the selfie camera **102** may simultaneously connect to a video steaming platform **202** using a communications path **116**. A direct communications path **116** between a user device **104** and a video streaming platform **202** and/or a selfie camera **102** and a video streaming platform **202** gives users full control over their user device **104** when live streaming video and other pieces of content (i.e., "going live") to a video streaming platform **202** because, in the selfie video system **200**, the selfie camera **102** is the device streaming video and other pieces of content not the user device **104**. Therefore, functionality of a user device **104** is not inhibited when a user live streams pieces of content to a video streaming platform **202** using the selfie video **200** system.

(24) A user device **104** may communicate with the selfie camera **102** and/or video streaming platform **202** and interact and/or exchange data with the selfie camera **102** and/or the video streaming platform **202**. For example, the user device **104** may communicate one or more messages to a selfie camera **102** to record and/or stream video and other pieces of content to a video streaming platform **202**. In response, the selfie camera **102** may send a message (e.g., a push notification) to the user device **104** indicating a live video stream has started. A user device **104** connected to the video streaming platform **202** will then be able to view the live video stream provided by

the selfie camera **102** on a user device display. The user device **104** may have an application (e.g., a web app or a mobile app) that is executed by the processor of the user device **104** that may display visual information to a user including a preview **108** before and/or after video recording and a user interface for streaming, editing, and/or sharing selfie content. The communications path **116** may include one or more wired or wireless networks/systems that allow a user device **104** and/or a selfie camera **102** to communicate with a video streaming platform **202** using a known data and transfer protocol. The video streaming platform **202** may include one or more video streaming servers for receiving videos and other pieces of content from a selfie camera **102** and a plurality video streaming clients for distributing videos and other pieces of content from the video streaming server. To facilitate sharing live video content, one or more communications paths **116** and/or video streaming platforms **202** may include a content distribution network for distributing video content from one or more video streaming servers to a plurality of video streaming clients. The video streaming platform **202** may be any known video streaming application including Twitch, TikTok, Houseparty, Youtube, Facebook, Snapchat, Instagram, Wechat, Line, and the like.

(25) FIG. **3** illustrates more details of the systems shown in FIGS. **1-2** and specifically more details of the user device **104** and a server device **320** that may be incorporated into at least one of the social media platform **112** and/or the video streaming platform **202**. The components shown in FIG. **3** provide the functionality delivered by the hardware devices shown in FIGS. **1-2**. As used herein, the term "component" may be understood to refer to computer executable software, firmware, hardware, and/or various combinations thereof. It is noted that where a component is a software and/or firmware component, the component is configured to affect the hardware elements of an associated system. It is further noted that the components shown and described herein are intended as examples. The components may be combined, integrated, separated, or duplicated to support various applications. Also, a function described herein as being performed at a particular component may be performed at one or more other components and by one or more other devices instead of or in addition to the function performed at the particular component. Further, the components may be implemented across multiple devices or other components local or remote to one another. Additionally, the components may be moved from one device and added to another device or may be included in both devices.

(26) As shown in FIG. **3**, a user device **104** may be communicatively coupled to a selfie camera and specifically receive pieces of content (e.g., data files including image data, audiovisual data, and the like) and send and receive messages. Pieces of content received from the selfie camera **102** may be stored in an image data store **306** included in a user device **104**. The image data store **306** may store data files including pieces of content in various ways including, for example, as a flat file, indexed file, hierarchical database, relational database, unstructured database, graph database, object database, and/or any other storage mechanism. The image data store **306** may be implemented as a portion of the user device **104** hard drive or flash memory (e.g., NAND flash memory in the form of eMMCs, universal flash storage (UFS), SSDs etc.). To capture and process pieces of content, a user device **104** may include a selfie generator **308**. In various embodiments, the selfie generator **308** may be implemented as a stand-alone mobile app installed on a user device, a stand-alone web app accessible by a web browser application, and/or as a plug-in or other extension of another mobile app installed on a user device (e.g., a naïve camera app, photo app, photo editing app, and the like) or web app accessible through a web browser. The selfie generator **308** may be communicatively coupled to a selfie camera **102** and a plurality of other apps (**316***a*, **316***b*, **316***c*, etc.) that are executed by a processor of a user device **104**.

(27) In various embodiments, the selfie generator **308** includes a selfie camera controller **310**, preview logic **312**, and a streaming engine **314**. The selfie camera controller **310** may send and receive messages and other data from the selfie camera to control camera functionality. For example, the selfie camera controller **310** may receive a message from a selfie camera **102** indicating with selfie camera **102** is powered on and located close enough to the user device **104** to establish a connection. In response, the settle camera controller **310** may send a message containing a connection request to establish a communication path with a selfie camera **102**. The selfie camera controller **310** may send messages including commands for adjusting one or more camera settings (e.g., zoom, flash, aperture, aspect ratio, contrast, etc.) of the selfie camera **102**. The selfie camera controller **310** may send messages including commands causing the selfie camera **102** to record video, stream video, and/or capture images. The selfie camera **102** executes the commands and then distributes captured pieces of content to an image data store **306**. In various embodiments, the settle camera controller **310** by execute one or more capture routines for controlling capture of selfie images, selfie videos, and other pieces of content by the selfie camera **102**. Capture routines may cause the selfie camera **102** and/or user device **104** to provide a visual or auditory countdown signaling when capture is about to take place. For example, a capture routine may include a 3 to 10 second countdown that incorporates displaying a countdown sequence of numbers number per second) on a user device display. The countdown may also include an audio component that audibly counts backward from, for example, 10 to 1. The audio component may be in sync with the user device display so that when the number displayed on the user device display is counted in the audio component. At the conclusion of the countdown, the selfie camera controller **310** may initiate capture of one or more pieces of content. One or more delays can be included in a capture routine to provide additional time to between competing the countdown and initiating capture of one or more pieces of content. Capture routines executed by the selfie camera controller **310** may capture a sequence of, for example, 2 to 5 photos with each captured photo displayed in a preview shown on a user device display.

(28) In various embodiments, when executing a command to stream video and/or other pieces of content, the selfie camera **102** may initiate a connection with a sever device **320** (e.g., a streaming platform server) of a video streaming platform. Once connected to a server device **320** the selfie camera **102** may stream selfie videos and other pieces of content to the server device **320**) for distribution to a plurality of streaming platform clients. In various embodiments, the selfie camera **102** may also provide video and other pieces of content for streaming to an image data store **306**. The streaming engine **314** may retrieve video and other pieces of content for streaming from the image data store **306** and transfer the video and other pieces of content for streaming to a content API **322** using file/data lossless transfer protocols such as HTTP, HTTPS or FTP. Video and other pieces of content for streaming may then be provided to a content distribution module **326** for distribution to a plurality of clients through a livestream API **328** and/or stored a selfie content database **324**. In various embodiments a content distribution module **326** and/or a livestream API **328** may include a media codec (e.g., audio and/or video codec) having functionality for encoding video and audio and other pieces of content received from a selfie camera **102** and or user device **104** into a format for streaming (e.g., an audio coding format including MP3, Vorbis, AAC, Opus, and the like and/or a video coding format including 11.264, HEVC, VP8 or VP9) using a known streaming protocol (e.g., real time streaming protocol (WISP), real-time transport protocol (RIP), real-time transport control protocol (RTCP), and the like) The content distribution module **326** and/or livestream API **328** may then assemble encoded video streams in a container bitstream (e.g., MP4, WebM, ASF ISMA, and the like) that is provided by the livestream API **328** to a plurality of streaming clients using a known

transport protocol (e.g., RTP, RTMP, IRS by Apple, Smooth Streaming by Microsoft, MPEG-DASH by Adobe, and the like) that supports adaptive bitrate streaming over HTTP or other k web data transfer protocol.

(29) The selfie generator **308** may connect to one or more mobile or web apps **316***b*, **316***a* executed by a processor of the user device. In various embodiments, preview logic **312** may parse one or more GUIs included in a mobile app and or web app to capture the size, resolution and other characteristics of pieces of content displayed on a social media platform and/or video streaming platform. For example, preview logic **312** may parse HTML, CSS, XML, JavaScript, and the like elements rendered as web app GUIs to extract characteristics (e.g., size, resolution, aspect ratio, and the like) of pieces of content displayed in web app implementations of social media platforms and/or video streaming platforms. Preview logic **312** may extract characteristics of pieces of content displayed in mobile app implementations of social media platforms and/or video streaming platforms by parsing Swift, Objective C, and the like elements (for iOS apps) and/or Java, C, C++, and the like elements (for Android apps). To create a realistic preview of how a piece of content will look on a social media platform and/or video streaming platform, preview logic **312** may include instructions for modifying images, videos, and other pieces of content received from the selfie camera to mirror the characteristics of images, videos, and other pieces of content displayed on one or more social media platforms and/or video streaming platforms. For example, preview logic **312** may crop a piece of content to a size and/or aspect ratio that matches the size and/or aspect ratio of pieces of content displayed in a particular GUI (e.g., post GUI, content feed GUI, live stream GUI, and the like) included in a web app and/or mobile app implementation of a social media and/or video streaming platform. Preview logic **312** may also change the resolution of one or more pieces of content received from a selfie camera to match the resolution of pieces of content displayed in a particular GUI included in a web app and/or mobile app implementation of a social media and/or video streaming platform.

(30) Preview logic **312** can include functionality for configuring previews projected on a user device display to match the orientation of the user device display. For example, preview logic **312** may access a motion sensor (e.g., gyroscope, accelerometer, and the like) included in a user device **104** to determine the orientation of a user device display. Preview logic **312** may then crop the live video feed preview and/or captured piece of content received from the selfie camera **102** to fit the aspect ratio of the user device display at its current orientation. Preview logic **312** may dynamically crop the previews and/or captured piece of content from the selfie camera **102** to match the orientation of the user device display to dynamically change the aspect ratio of the previews and/or captured pieces of content, for example, from portrait to landscape when the user device display rotates from a portrait orientation to a landscape orientation. Post capture, preview logic **312** may display pieces of content as full view content with no cropping, portrait content cropped to a portrait aspect ratio, landscape content cropped to a landscape aspect ratio, and shared content cropped to match one or more GUIs for sharing pieces of content included in a social media and/or video streaming platform. In various embodiments, preview logic **312** may incorporate one or more characteristics of pieces of content extracted from a social media and/or video streaming platform into portrait and/or landscape content. For example, preview logic **312** may modify portrait content to simulate cropping that occurs when sharing one or more pieces of content on a content streaming GUI (e.g., Snapchat snaps, Instagram stories, Facebook stories, and the like) included in a social media and/or video streaming platform. Preview logic **312** may modify landscape content to simulate cropping that occurs when sharing one or more wide angle pieces of content (e.g., a group photo/video captured in a landscape orientation) to a social media and/or video streaming platform. Full view content and/or pieces of content modified by preview logic **312** into portrait content and/or landscape content may be saved to the image data store **306** and/or provided to a content API **322** of a server device **320** using as file/data lossless transfer protocols such as HTTP, HTTPS or FTP. Pieces of content received by a content API **322** may be shared to a social media and/or video streaming platform through a posting API **330**.

(31) In various embodiments, preview logic **312** may include one or more routines for editing previews and captured pieces of content. Preview logic **312** may edit captured video by segmenting recorded video and other pieces of content into clips (i.e., 1 to 30 second segments). One or more routines for editing video clips and other pieces of content may also be included in preview logic **312**. In various embodiments, preview logic **312** may edit video clips and other pieces of content using one or more video editing filters. For example, preview logic **312** can include editing filters that pan within a scene in any direction (e.g., horizontal, vertical, diagonal, and the like); zoom in to and/or zoom out from one more areas of a scene; show movement within a scene in slow motion; and sync one or more audio clips with playback of a video clip. Preview logic **312** may combine one or more editing filters to enable more advanced editing functionality. For example, preview logic **312** may combine a slow motion editing filter with an audio sync editing filter to sync one or more audio clips with playback of a video clip having a slow motion effect to mask the ambient sound distortion that may occur when a slow motion editing filter is applied to a video clip having audio. In various embodiments, preview logic **312** may apply one or more editing filters post capture by first defining a portion of a scene included in a captured video or other piece of content to manipulate with a editing filter. For example, defining a rectangle at the center of the captured video. One or more editing filters may then be applied to manipulate the aspects of a scene within the rectangle (e.g., zoom in on an object within the rectangle, pan from left to right across the objects within the rectangle, and the like). In various embodiments, preview logic **312** may apply one or more stabilization and/or sharpening functions to livestream video, recorded video, recorded video clips, and other pieces of content. For example, a stabilization function may smooth out vibrations and other undesired movement included in recorded scenes and other pieces of content. A sharpening function may reduce blurring of moving objects captured in record scenes and other pieces of content. In various embodiments, preview logic **312** can include one or more background filters that may be applied to change the background of previews or captured pieces of content. To change the background of a piece of content to one or more background filters, preview logic **312** may include instructions for segmenting the background and foreground aspects of a preview and/or captured piece of content. The background elements of one or more captured pieces of content and/or live video previews may then by extracted and replaced with one or more background filters. Background filters may be actual photographs to simulate real like settings and/or virtual scenes simulating virtual reality or mixed reality environments. Pieces of content modified according to one or more editing functionalities of the preview logic **312** may be saved in the image date store **306** and/or provided to a content API **322** of a server device **320** using as file/data lossless transfer protocols such as HTTP, HTTPS or FTP. Pieces of content received by a content API **322** may be shared to a social media and/or video streaming platform using a posting API **330**.

(32) FIG. **4** illustrates one example embodiment of a selfie camera **102**. The selfie camera **102** may include a housing **400** disposing a circuit board including the electrical components (e.g., processor, control circuits, power source, image sensor, and the like) of the selfie camera **102**. The housing **400** may be include an eye portion **402** extending laterally out from the surface of the housing. The eye portion **402** may dispose one or more camera components (e.g., lens, image sensor, and the like). At one end the eye portion **402** includes an opening **404** to allow light to pass through the lens and reach the image sensor disposed inside the housing **400** and/or eye

portion **402**. An LED light **406** may be embedded in an exterior surface of the housing **400** to provide additional light (i.e., flash) to enable capture of selfie content in low light conditions. More details about the components of the selfie camera **102** are described in FIGS. **13-14**. One or more mounting systems may be attached to the backside of the housing **400** opposite the eye portion **402**. The mounting systems may fix the selfie camera **102** to one or more foreign surfaces to position the selfie camera **102** for capturing selfie content. Specific exemplary mounting systems are described below in FIGS. **6-8D**.

(33) FIGS. **5**A-M illustrate exemplary preview GUIs rendered by the selfie generator. The preview GUIs display previews of selfie content before and after capture. Selfie content displayed in preview GUIs is provided to a user device from a selfie camera connected to the user device. Selfie content displayed in preview GUIs may be modified to simulate one or more characteristics of selfie content shared on one or more social medial platforms and/or video streaming platforms. FIGS. **5**A-B illustrate exemplary image preview GUIs for previewing image selfie content provided by a selfie camera. FIG. **5**A illustrates an exemplary live image preview GUI displaying a live video of a scene provided by a selfie camera. The photo preview mode is clearly shown in the bottom portion of the image preview GUI. Inputting a capture command to the selfie camera controller that results in a captured image will render the exemplary captured image preview GUI shown in FIG. **5**B on a user device display. From the captured image preview GUI, image selfie content received from the selfie camera may be deleted, saved to a user device image data store, shared to a social media platform, shared through a messaging platform, saved to a cloud storage instance, set as a wallpaper, and/or copied to a user device clipboard. Any action taken on the image preview GUI may result in rendering the live image preview GUI on a user device display.

(34) FIGS. **5**C-E illustrate exemplary video preview GUIs for previewing video selfie content provided by a selfie camera. FIG. **5**C illustrates a live video preview GUI displaying live video of a scene provided by a selfie camera. The video preview mode is clearly shown in the bottom portion of the video preview GUI. Inputting a record video and/or live stream video command to the selfie camera controller that results in a recorded and/or live streamed video will render the exemplary video recording preview GUI shown in FIG. **5**D on a user device display. For live streamed video, the video recording preview GUI may show selfie video content exactly it is shown on a live stream shared over a social media and/or video streaming platform. Inputting a stop recording command into the video recording preview GUI will display the exemplary captured video preview GUI shown in FIG. **5**E. From the captured video preview GUI, video selfie content received from the selfie camera may be deleted, saved to a user device image data store, saved to a cloud storage device or other remote data store, set as a wallpaper, shared to a social medial and/or video streaming platform, shared through a messaging platform, and/or coped to a user device clipboard. Any action taken on the captured video preview GUI may result in rendering the live video preview GUI on a user device display.

(35) FIGS. **5**F-G illustrate exemplary image sequence preview GUIs for previewing image selfie content provided by a selfie camera before and after performing a capture sequence generated by the selfie camera controller. FIG. **5**F illustrates an exemplary live image sequence preview GUI displaying a live video of a scene provide by a selfie camera. The live image sequence preview GUI shows the scene as it will be captured by the selfie camera during execution of a capture sequence. Inputting a capture command to the selfie camera controller that results in performance of a capture sequence will render the exemplary captured image sequence preview GUI shown in FIG. **5**G. In various embodiments, the captured image sequence preview GUI may show the first image captured in the capture sequence as a large preview taking up most of the GUI with all the images, in this example 5, captured in the image sequence shown as smaller previews in a bottom portion of the GUI. Selecting one of the smaller previews may display the selected image in the large preview portion of the GUI. More than one photo may be selected in the smaller previews to enable users to take action on more than one photo captured in the capture sequence. Confirming selection of one or more photos will render a captured image sequence action GUI shown in FIG. **5**H for each confirmed selected image. In various embodiments, the functionality of the captured image sequence action GUI is the same as the captured image preview GUI in FIG. **5**B. When two or more images captured in the image sequence are selected and confirmed taking action on the first photo in the captured image preview GUI may render a captured image preview GUI for the second photo and so on. If only one image captured in the image sequence is selected and confirmed, taking action on the photo may render the live image sequence preview GUI.

(36) FIGS. **5**I-M illustrate exemplary content editing preview GUIs for previewing and editing captured selfie content. FIG. **5**I illustrates an exemplary content editing live preview GUI displaying live video of a scene provided by a selfie camera. The content editing live preview GUI shows the scene as it will be captured by the selfie camera during execution of a capture command. Inputting a capture and/or video edit command to the selfie camera controller resulting in capture of selfie content will render a define edit area GUI shown in FIG. **5**J. In various embodiments, the define edit area preview GUI may include a box defining an area within which one or more effects (e.g., zoom, pan, slow motion, and the like) may be added to edit selfie content. Inputting a capture and/or audio edit command into the selfie camera controller resulting in capture of selfie content will render a record audio edit GUI shown in FIG. **5**K. In various embodiments, the record audio edit GUI may record an audio clip that may be synced with selfie content. Recording an audio clip may result in rendering a recorded audio edit preview GUI shown in FIG. **5**L. A preview of the recorded audio clip played over the audio of captured selfie content may be displayed in the audio edit preview GUI as well as options for confirming the recorded audio clip for use in content editing and/or recording a new audio clip. Selecting a record new audio clip may transition back to a record audio edit GUI. Confirming use of the record audio clip may transition to an edited captured content preview GUI shown in FIG. **5**M. Selfie content including video effects edits added in the define edit area GUI and/or audio edits added in the record audio edit GUI may be previewed in the edited captured content preview GUI. From the edited captured content GUI, selfie content received from the selfie camera and/or edited by the selfie generator may be deleted, saved to a user device image data store, saved to a cloud storage device or other remote data store, set as a wallpaper, shared to a social medial and/or video streaming platform, shared through a messaging platform, and/or coped to a user device clipboard. Any action taken on the edited capture content GUI may result in rendering the content editing live preview GUI on a user device display.

(37) FIGS. **6-8D** illustrate exemplary mounting systems that, may be used to fix a selfie camera to a foreign object. Mounting systems may be removably attached and/or built into the back of the settle camera to enable quick and secure attachment to a variety of surfaces. Attaching a selfie camera using a mounting system improves the perspective of scenes captured by the selfie camera. FIGS. **6-7**B pertain to electroadhesion mounting systems and FIGS. **8**A-D illustrate exemplary mechanical mounting systems.

(38) FIG. **6** illustrates and electroadhesion device **600** that may be integrated with and or otherwise attached to the selfie camera. In various embodiments, the electroadhesion device **600** can be implemented as a compliant film comprising one or more electrodes **604** and an insulating material **602** between the electrodes **604** and a case and/or device (i.e., the selfie camera). The electroadhesive film may include a chemical adhesive applied to the insulating material **602** and/or electrodes **604** to allow the electroadhesion device **600**

to be attached to a case and/or device. Additional attachment mechanisms used to secure the electroadhesion device **600** to a case and/or device can include a mechanical fastener, a heat fastener (e.g., welded, spot welded, or spot-melted location); dry adhesion; Velcro; suction/vacuum adhesion; magnetic or electromagnetic attachment or tape (e.g.: single- or double-sided). Depending on the degree or device portability desired or needed for a given situation and the size of the electroadhesion device, the attachment mechanism may create a permanent, temporary, or even removable form of attachment.

(39) The insulating material **602** may be comprised of several different layers of insulators. For purposes of illustration, the electroadhesion device **600** is shown as having four electrodes in two pairs, although it will be readily appreciated that more or fewer electrodes can be used in a given electroadhesion device **600**. Where only a single electrode is used in a given electroadhesion device **600**, a complimentary electroadhesion device **600** having at least one electrode of the opposite polarity is preferably used therewith. With respect to size, electroadhesion device **600** is substantially scale invariant. That is, electroadhesion device **600** sizes may range from less than 1 square centimeter to greater than several meters in surface area. Even larger and smaller surface areas are also possible and may be sized to the needs of a given device.

(40) In various embodiments, the electroadhesion device **600** may cover the entire rear surface of a device. One or more electrodes **604** may be connected to a power supply **612** (e.g., battery, AC power supply, DC, power supply and the like) using one or more known electrical connections **606**. A power management integrated circuit **610** may manage power supply **612** output, regulate voltage, and control power supply **612** changing functions. To create an electroadhesive force that provides sufficient electroadhesive attraction to support a device, low voltage power from a power supply **612** must be converted into high voltage charges at the one or more electrodes **604** using a voltage converter **608**. The high voltages on the one or more electrodes **604** form an electric field that interacts with a foreign object and or other target surface in contact with- and/or proximate to-the electroadhesion device **600**. The electric field may locally polarize the target surface and/or induce electric charges on the target surface that are opposite to the charge on the one or more electrodes **604**. The opposite charges on the one or more electrodes **604** and the target surface attract to cause electroadhesion between the electrodes **604** and the target surface. The induced charges may be the result of a dielectric polarization or from weakly conductive materials and electrostatic induction of charge. In the event that the target surface comprises a material that is a strong conductor, such as copper for example, the induced charges may completely cancel the electric field. In this case, the internal electric field is zero, but the induced charges nonetheless still form and provide electroadhesive force (i.e., Lorentz forces) to the electroadhesion device **600**.

(41) Thus, the adjustable voltage applied to the one or more electrodes **604** provides an overall electroadhesive force between the electroadhesion device **600** and the material of the foreign object and/or other target surface. The electroadhesive force holds the electroadhesion device **600** on the target surface. The overall electroadhesive force may be sufficient to overcome the gravitational pull on the electroadhesion device **600** and a consumer device or other object attached to the electroadhesion device **600**. Therefore, the electroadhesive force may be used to hold a consumer device mounted with the electroadhesion device **600** aloft on the target surface. In various embodiments, a plurality of electroadhesion devices may be placed against target surface, such that additional electroadhesive forces against the target surface can be provided. The combination of electroadhesive forces may be sufficient to lift, move, pick and place, mount, or secure a large object on the target surface.

(42) Removal of the adjustable voltages from the one or more electrodes **604** ceases the electroadhesive force between electroadhesion device **600** and the target surface. Thus, when there is no adjustable voltage between the one or more electrodes **104**, the electroadhesion device **600** can move more readily relative to the target surface. This condition allows the electroadhesion device **600** to move before and after an adjustable voltage is applied. Well controlled electrical activation and de-activation enables fast adhesion and detachment, such as response times less than about 50 milliseconds, for example, while consuming relatively small amounts of power.

(43) Applying too much voltage to certain materials (e.g., metals and other conductors) can cause sparks, fires, electric shocks, and other hazards. Applying too little voltage generates a weak electroadhesive force that is not strong enough to securely attach the electroadhesion device **600** to the target surface. To ensure the proper adjustable voltage is generated and applied to the electrodes **604** to generate a sufficient electroadhesive force, a digital switch **616** may autonomously control the voltage converter **608**. The digital switch **616** may control the voltage output of the voltage converter **608** based on sensor data collected by one or more sensors **614** included in the electroadhesion device **600**. The digital switch **616** may be a microcontroller or other integrated circuit including programmable logic for receiving sensor data, determining one or more characteristics based on the sensor data, and controlling the voltage converter based on the one or more characteristics. The digital switch **616** may operate the voltage converter **608** to generate, modify, set, and/or maintain an adjustable output voltage used to attach the electroadhesion device **600** to a target surface.

(44) For example, in response to detecting a conductive target surface (e.g., metal) by the sensor **614**, the digital switch **616** may cause the voltage convener **608** to generate an adjustable voltage sufficient to attach and secure the electroadhesion device **600** to the conductive target surface. The adjustable voltage output may also be safe to apply to conductive surfaces and may eliminate sparks, fires, or other hazards that are created when an electroadhesion device **600** that is generating a high voltage contacts and/or is placed close to a conductive target surface. Similarly, when the sensor **614** detects a different surface with different characteristics, the digital switch **616** controls the voltage converter **608** to generate a different adjustable voltage that is sufficient to attach and secure the electroadhesion device **600** to that different surface. For example, in response to detecting an organic target surface (e.g., wood, drywall, fabric, and the like) by the sensor **614**, the digital switch **616** may cause the voltage converter **608** to generate an adjustable voltage that may be sufficient to attach and secure the electroadhesion device to the organic target surface without creating hazards. The adjustable voltage may also minimize the voltage output to avoid hazards that may be created when the electroadhesion device **600** is accidently moved. In response to detecting a smooth target surface (e.g., glass) or an insulating target surface (e.g., plastic, stone, sheetrock, ceramics, and the like) by the sensor **614**, the digital switch **616** may cause the voltage convener **608** to generate an adjustable voltage sufficient to attach and secure the electroadhesion device **600** to the smooth and/or insulating target surface without creating hazards. Thus, the electroadhesion device **600** has an adjustable voltage level that is adjusted based on a characteristic of the target surface determined by the sensor **614** resulting in an electroadhesion device **600** that can be safely used to attach to various target surfaces without safety hazards.

(45) The strength (i.e., amount of voltage) of the adjustable voltage may vary depending on the material of the target surface. For example, the strength of the adjustable voltage required to attach the electroadhesion device **600** to a conductive target surface (e.g., metal) may be less than the adjustable voltage required to attach the electroadhesion device **600** to an insulating target surface, a

smooth target surface, and/or an organic target surface. The strength of the adjustable voltage required to attach the electroadhesion device **600** to an organic target surface may be greater than the adjustable voltage required to attach the electroadhesion device **600** to a conductive target surface and less than the adjustable voltage require to attach the electroadhesion device **600** to an insulating target surface. The strength of the adjustable voltage required to attach the electroadhesion device **600** to an insulating target surface may be higher than the adjustable voltage required to attach the electroadhesion device **600** to an organic target surface or a conductive target surface. The electroadhesion device **600** may be configured to attach to any type of surface (e.g., metallic, organic, rough, smooth, undulating, insulating, conductive, and like). In some embodiments, it may be preferable to attach the electroadhesion device **100** to a smooth, flat surface.

(46) Attaching the electroadhesion device **600** to some target surfaces requires a very high voltage. For example, a very high voltage output may be required to attach the electroadhesion device **600** to a rough target surface, a very smooth target surface (e.g., glass), and/or an insulating target surface. An electroadhesion device **600** generating a high voltage output may generate sparks, fires, electric shock, and other safety hazards when placed into contract with- and/or in close proximity to- conductive surfaces. To avoid safety hazards, some embodiments of the electroadhesion device **600** may not generate a high voltage and may only generate an output adjustable voltage sufficient to attach the electroadhesion device **600** to conductive target surfaces, organic target surfaces, and the like.

(47) When the electroadhesion device **600** is moved to a new target surface, the sensor **614** may automatically detect one or more characteristics of the new target surface and/or determine the material type, surface texture, surface morphology, or other characteristic for the new target surface. The digital switch **616** may then modify and/or maintain the adjustable voltage output generated by the voltage converter **608** based on the material type and/or characteristics for the new target surface. To determine the adjustable voltage to generate using the voltage converter **608**, the digital switch **616** may include logic for determining the adjustable voltage based on sensor data received from the sensor **614**. For example, the digital switch **616** may include logic for using a look up table to determine the proper adjustable voltage based on the sensor data. The logic incorporated into the digital switch **616** may also include one or more algorithms for calculating the proper adjustable voltage based on the sensor data. Additionally, if the sensor **614** detects the electroadhesion device **600** is moved away from a target surface, the digital switch **616** may power down the voltage converter **608** and/or otherwise terminate the adjustable voltage output from the voltage converter **608** until a new target surface is detected by the sensor **614**.

(48) The one or more sensors **614** can include a wide variety of sensors **614** for measuring characteristics of the target surface. Each sensor **614** may be operated by a sensor control circuit **618**. The sensor control circuit **618** may be included in the sensor **614** or may be a distinct component. The sensor control circuit **618** can be a microcontroller or other integrated circuit having programmable logic for controlling the sensor **614**. For example, the sensor control circuit **618** may initiate capture of sensor data, cease capture of sensor data, set the sample rate for the sensor, control transmission of sensor data measured by the sensor **614**, and the like. Sensors **614** can include conductivity sensors (e.g., electrode conductivity sensors, induction conductivity sensors, and the like); Hall effect sensors and other magnetic field sensors; porosity sensors (e.g., time domain reflectometry (TDR) porosity sensors); wave form sensors (e.g., ultrasound sensors, radar sensors, infrared sensors, dot field projection depth sensors, time of flight depth sensors); motion sensors; surface texture sensors; surface profile sensors, surface morphology sensors, and the like. Sensor data measured by the one or more sensors **614** may be used to determine one or more characteristics of the target surface. For example, sensor data may be used to determine the target surface's conductivity and other electrical or magnetic characteristics; the material's porosity, permeability, and surface morphology; the materials hardness, smoothness, surface profile, and other surface characteristics; the distance the target surface is from the sensor; and the like. One or more characteristics determined from sensor data may be used to control the digital switch **616** directly. Sensor data may also be sent to a data analysis module. The data analysis module may refine the sensor data and use it to determine a characteristic and/or material type (e.g., metal, wood, plastic, ceramic, concreate, drywall, glass, stone and the like) for the target surface. The digital switch **616** may then control the voltage output from the voltage converter **608** based on the characteristic and/or material type for the target surface determined by the data analysis module.

(49) The digital switch **616** may function as an essential safety feature of the electroadhesion device **100**. The digital switch **616** may reduce the risk of sparks, fires, electric shock, and other safety hazards that may result from applying a high voltage to a conductive target surface. By autonomously controlling the voltage generated by the electroadhesion device **600**, the digital switch **616** may also minimize human error that may result when a user manually sets the voltage output of the electroadhesion device **600**. For example, human errors may include a user forgetting to change the voltage setting, a child playing with the electroadhesion device and not paying attention to the voltage setting, a user mistaking a conductive surface for an insulating surface, and the like. These errors may be eliminated by using digital switch **616** to automatically adjust the voltage generated by the voltage converter **608** based on sensor data received from the one or more sensors **614** and/or material classifications made by the data analysis module.

(50) As shown in FIG. **7**A, to promote safely and improve user experience, the selfie camera **102** and or electroadhesion device **600** may include a mechanism (e.g., button, mechanical switch, element, and the like) **716** for actuating the sensor **614** and/or digital switch **616**. The sensor **614** and digital switch **616** may also be automatically turned on when the electroadhesion device **600** and/or the selfie camera **102** is powered on. The electroadhesion device **600** and/or selfie camera **102** may also include a signaling mechanism (e.g., status light, UI element, mechanical switch, and the like) for communicating the status of the sensor **614** and/or digital switch **616** to a user of the electroadhesion device **600**. The signaling mechanism may be used to communicate that the proper adjustable voltage for a particular target surface has been determined.

(51) In various embodiments, the signaling mechanism may be a status light that is red when the sensor **614** and/or digital switch **616** is powered on and sensing the target surface material or other characteristics but has not determined the proper adjustable voltage for the target surface. The status light may turn green when the digital switch **616** has received the sensor data, determined the appropriate adjustable voltage for the particular target surface, and generated the proper adjustable voltage output and the electroadhesion device **600** is ready to attach to the target surface. The status light may also turn blinking red and/or yellow if there is some problem with determining the adjustable voltage for the particular target surface and/or generating the adjustable voltage output for the particular target surface. For example, the status light may blink red and/or turn yellow when the sensor **614** is unable to collect sensor data, the data analysis module is unable to determine a material type or other characteristic for the target surface material, the digital switch **616** is unable to operate the voltage converter **608**, the voltage converter **608** is unable to generate the correct adjustable voltage, and the like.

(52) As described herein, voltage generated by the voltage converter **608** is defined as a range of DC voltage of any one or more of the

following from 250 V to 10,000 V; from 500 V to 10,000 V; from 1,000 V to 10,000 V; from 1,500 V to 10,000 V; from 2,000 V to 10,000 V; from 3,000 V to 10,000 V; from 4,000 V to 10,000 V; from 5,000 V to 10,000 V; from 6,000 V to 10,000 V; from 7,000 V to 10,000 V; from 250 V to 1,000 V; from 250 V to 2,000 V; from 250 V to 4,000 V; from 500 V to 1,000 V; from 500 V to 2,000 V; from 500 V to 4,000 V; from 1,000 V to 2,000 V; from 1,000 V to 4,000 V; from 1,000 V to 6,000 V; from 2,000 V to 4,000 V; from 2,000 V to 6,000 V; from 4,000 V to 6,000 V; from 4,000 V to 10,000 V; from 6,000 V to 8,000 V; and from 8,000 V to 10,000 V.

(53) As described herein, voltage generated by the voltage converter **608** is defined as a range of AC voltage of any one or more of the following from 250 V.sub.rms to 10,000 V.sub.rms; from 500 V.sub.rms to 10,000 V.sub.rms; from 1,000 V.sub.rms to 10,000 V.sub.rms; from 1,500 V.sub.rms to 10,000 V.sub.rms; from 2,000 V.sub.rms to 10,000 V.sub.rms; from 3,000 V.sub.rms to 10,000 V.sub.rms; from 4,000 V.sub.rms to 10,000 V.sub.rms; from 5,000 V.sub.rms to 10,000 V.sub.rms; from 6,000 V.sub.rms to 8,000 V.sub.rms; from 7,000 V.sub.rms to 8,000 V.sub.rms; from 8,000 V.sub.rms to 10,000 V.sub.rms; from 9,000 V.sub.rms to 10,000 V.sub.rms; from 250 V.sub.rms to 1,000 V.sub.rms; from 250 V.sub.rms to 2,000 V.sub.rms; from 250 V.sub.rms to 4,000 V.sub.rms; from 500 V.sub.rms to 1,000 V.sub.rms; from 500 V.sub.rms to 2,000 V.sub.rms; from 500 V.sub.rms to 4,000 V.sub.rms; from 1,000 V.sub.rms to 2,000 V.sub.rms; from 1,000 V.sub.rms to 4,000 V.sub.rms; from 1,000 V.sub.rms to 6,000 V.sub.rms; from 2,000 V.sub.rms to 4,000 V.sub.rms; from 2,000 V.sub.rms to 6,000 V.sub.rms; from 4,000 V.sub.rms to 6,000 V.sub.rms; from 4,000 V.sub.rms to 8,000 V.sub.rms; and from 6,000 V.sub.rms to 8,000 V.sub.rms.

(54) As described herein, voltage generated by the voltage converter **608** is defined as a range of DC voltage of any one or more of the following from about 250 V to about 10,000 V; from about 500 V to about 10,000 V; from about 1,000 V to about 10,000 V; from about 1,500 V to about 10,000 V; from about 2,000 V to about 10,000 V; from about 3,000 V to about 10,000 V; from about 4,000 V to about 10,000 V; from about 5,000 V to about 10,000 V; from about 6,000 V to about 8,000 V; from about 7,000 V to about 8,000 V; from about 250 V to about 1,000 V; from about 250 V to about 2,000 V; from about 250 V to about 4,000 V; from about 500 V to about 1,000 V; from about 500 V to about 2,000 V; from about 500 V to about 4,000 V; from about 1,000 V to about 2,000 V; from about 1,000 V to about 4,000 V; from about 1,000 V to about 6,000 V; from about 2,000 V to about 4,000 V; from about 2,000 V to about 6,000 V; from about 4,000 V to about 6,000 V; from about 4,000 V to about 8,000 V; from about 6,000 V to about 8,000 V; from about 8,000 V to about 10,000 V; and from about 9,000 V to about 10,000 V.

(55) As described herein, voltage generated by the voltage converter **608** is defined as a range of AC voltage of any one or more of the following from about 250 V.sub.rms to about 10,000 V.sub.rms; from about 500 V.sub.rms to about 10,000 V.sub.rms; from about 1,000 V.sub.rms to about 10,000 V.sub.rms; from about 1,500 V.sub.rms to about 10,000 V.sub.rms; from about 2,000 V.sub.rms to about 10,000 V.sub.rms; from about 3,000 V.sub.rms to about 10,000 V.sub.rms; from about 4,000 V.sub.rms to about 10,000 V.sub.rms; from about 5,000 V.sub.rms to about V.sub.rms; from about 6,000 V.sub.rms to about 8,000 V.sub.rms; from about 7,000 V.sub.rms to about 8,000 V.sub.rms; from about 250 V.sub.rms to about 1,000 V.sub.rms; from about 250 V.sub.rms to about 2,000 V.sub.rms; from about 250 V.sub.rms to about 4,000 V.sub.rms; from about 500 V.sub.rms to about 1,000 V.sub.rms; from about 500 V.sub.rms to about 2,000 V.sub.rms; from about 500 V.sub.rms to about 4,000 V.sub.rms; from about 1,000 V.sub.rms to about 2,000 V.sub.rms; from about 1,000 V.sub.rms to about 4,000 V.sub.rms; from about 1,000 V.sub.rms to about 6,000 V.sub.rms; from about 2,000 V.sub.rms to about 4,000 V.sub.rms; from about 2,000 V.sub.rms to about 6,000 V.sub.rms; from about 4,000 V.sub.rms to about 6,000 V.sub.rms; from about 4,000 V.sub.rms to about 8,000 V.sub.rms; from about 6,000 V.sub.rms to about 8,000 V.sub.rms; from about 8,000 V.sub.rms to about 10,000 V.sub.rms; and from about 9,000 V.sub.rms to about 10,000 V.sub.rms.

(56) As described herein, voltage output from the power supply **612** is defined as a range of DC voltage of any one or more of the following from 2.0 V.sub.rms to 249.99 V.sub.rms; from 2.0 V.sub.rms to 150.0 V.sub.rms; from 2.0 V.sub.rms to 100.0 V.sub.rms; from 2.0 V.sub.rms to 50.0 V.sub.rms; from 5.0 V.sub.rms to 249.99 V.sub.rms; from 5.0 V.sub.rms to 150.0 V.sub.rms; from 5.0 V.sub.rms to 100.0 V.sub.rms; from 5.0 V.sub.rms to 50.0 V.sub.rms; from 50.0 V.sub.rms to 150.0 V.sub.rms; from 100.0 V.sub.rms to 249.99 V.sub.rms; from 100.0 V.sub.rms to 130.0 V.sub.rms; and from 10.0 V.sub.rms and 30.0 V.sub.rms.

(57) As described herein, voltage output from the power supply **612** is defined as a range of AC voltage of any one or more of the following from 2.0 V.sub.rms to 249.99 V.sub.rms; from 2.0 V.sub.rms to 150.0 V.sub.rms; from 2.0 V.sub.rms to 100.0 V.sub.rms; from 2.0 V.sub.rms to 50.0 V.sub.rms; from 5.0 V.sub.rms to 249.99 V.sub.rms; from 5.0 V.sub.rms to 150.0 V.sub.rms; from 5.0 V.sub.rms to 100.0 V.sub.rms; from 5.0 V.sub.rms to 50.0 V.sub.rms; from 50.0 V.sub.rms to 150.0 V.sub.rms; from 100.0 V.sub.rms to 249.99 V.sub.rms; from 100.0 V.sub.rms to 130.0 V.sub.rms; and from 10.0 V.sub.rms and 30.0 V.sub.rms.

(58) As described herein, voltage output from the power supply **612** is defined as a range of DC voltage of any one or more of the following from about 2.0 V to about 249.99 V; from about 2.0 V to about 150.0 V; from about 2.0 V to about 100.0 V; from about 2.0 V to about 50.0 V; from about 5.0 V to about 249.99 V; from about 5.0 V to about 150.0 V; from about 5.0 V to about 100.0 V; from about 5.0 V to about 50.0 V; from about 50.0 V to about 150.0 V; from about 100.0 V to about 249.99 V; from about 100.0 V to about 130.0 V; and from about 10.0 V and 30.0 V.

(59) As described herein, voltage output from the power supply **612** is defined as a range of AC voltage of any one or more of the following from about 2.0 V.sub.rms to about 249.99 V.sub.rms; from about 2.0 V.sub.rms to about 150.0 V.sub.rms; from about 2.0 V.sub.rms to about 100.0 V.sub.rms; from about 2.0 V.sub.rms to about 50.0 V.sub.rms; from about 5.0 V.sub.rms to about 249.99 V.sub.rms; from about 5.0 V.sub.rms to about 150.0 V.sub.rms; from about 5.0 V.sub.rms to about 100.0 V.sub.rms; from about 5.0 V.sub.rms to about 50.0 V.sub.rms; from about 50.0 V.sub.rms to about 150.0 V.sub.rms; from about 100.0 V.sub.rms to about 249.99 V.sub.rms; from about 100.0 V.sub.rms to about 130.0 V.sub.rms; and from about 10.0 V.sub.rms and 30.0 V.sub.rms.

(60) FIGS. **7A-B** illustrate a selfie camera **102** having an electroadhesion device **600** mounting system. In various embodiments, the electroadhesion device **600** may be used to mount the selfie camera to the target surface **714** of any foreign object **712** including walls, mirrors, trees, furniture, and the like. FIG. **7A** illustrates a back surface **700** of a selfie camera **102** having an electroadhesion device **600**, for example, a compliant electroadhesive film fixed to the back surface **700**. FIG. **7B** illustrates a side view of a selfie camera **102** mounted to a foreign object **710** using the electroadhesion device **600**. The electroadhesion device **600** may include one or more sensors **614** for measuring one or more characteristics of the foreign object **710**.

(61) To attach the selfie camera **102** to the foreign object **710**, the one or more sensors **614** determine a characteristic of the foreign object **710**. Based on the sensor data, the electroadhesion device **600** applies an adjustable voltage to one or more electrodes **604**, the adjustable voltage induces a local electric field **720** around the one or more electrodes **604** wherein opposite charges from the inner portion **712** of the foreign object **710** build up around the surface of the electrodes **604**. The build-up of opposing charges creates an electroadhesive force between the electroadhesion device **600** attached to the selfie camera **102** and the foreign object **710**. The

electroadhesive force is sufficient to fix the selfie camera **102** to the target surface **714** of the foreign object **710** while the adjustable voltage is applied. It should be understood that the electroadhesion device **600** does not have to be in direct content with the target surface **714** of the foreign object **710** to produce the electroadhesive force. Instead, the target surface **714** of the foreign object **710** must be proximate to the electroadhesion device **600** to interact with the adjustable voltage on the one or more electrodes **604**. The electroadhesion device **600** may, therefore, secure the selfie camera **102** to smooth, even surfaces as well as rough, uneven surfaces. Additionally, the portion of the electroadhesion device **600** including the one or more electrodes **604** may be curved, flat, and or have an adjustable surface to facilitate better contact with the target surface **714**.

(62) FIGS. **8**A-D illustrate mechanical mounting systems that may be used with the selfie camera. Mechanical mounting systems that may secure the selfie camera **102** to one or more foreign objects include suction cups, mini suction cups, disposable sticky pads, magnets, and the like. Mechanical and/or electroadhesion mounting systems may be removably attached and/or permanently fixed to the selfie camera **102** using one or more hooks **800** included in a rear surface of the selfie camera **102**. FIGS. **8**B-D illustrate an exemplary suction cup mounting system including a suction cup **810** and a mounting plate **812** for securing the suction cup **810** to the selfie camera **102**. The mounting plate may also include a pivot for changing the position (i.e., orientation, direction, perspective, and the like) of the selfie camera **102**. In various embodiments the position of the selfie camera **102** may be changed when the selfie camera **102** is mounted to a foreign object my moving the selfie camera **102** about the pivot **814**. FIG. **8**B illustrates a perspective view of an exemplary suction cup **810** mounting system fixed to a selfie camera **102** using a mounting plate **812**. FIG. **8**C illustrates a flat top view of an exemplary suction cup **810** mounting system fixed to a selfie camera **102** using a mounting plate **812** having a pivot **814** at the base of the suction cup **810**. FIG. **8**D illustrates a flat front view of an exemplary suction cup **810** mounting system fixed to a selfie camera using a mounting plate **812**.

(63) FIG. **9** illustrates and exemplary process **900** for capturing and sharing a selfie image using the selfie camera system shown in FIG. **1**. At step **902**, a selfie camera connects to a user device to establish a communication pathway for transferring messages and data. Once a connection is established, a selfie image preview may be provided to a user device, in step **904**. The selfie image preview may be a live video stream of a scene as viewed by the selfie camera device. One or more aspects to the selfie image preview may be modified to simulate the appearance so selfie content on a social media and/or video streaming platform. At step **906**, a selfie camera receives a capture command from a connected user device and captures a selfie image. The captured selfie image is sent to the connected user device using the connection pathway. At decision point **908**, the quality of the selfie image is evaluated by viewing the preview of the selfie image provided by the selfie camera. If the selfie image shown in the preview is acceptable, the selfie image may be saved on a user device and/or shared on a social media platform by connecting to a social media platform using the user device and transferring the selfie image to the social media platform, at step **910**. In various embodiments, the selfie generator providing the selfie image preview may automatically connect to a social media platform when a connection is established with the selfie camera device. Once the selfie generator is connected to a social media platform, selfie image previews may be shared on a social media platform directly from a selfie image preview GUI. If a selfie image shown in a selfie image preview is not acceptable, a selfie image may be discarded. To expediting retaking a selfie image, discarding a selfie image may automatically restarts the selfie capture process by generating a live selfie image preview, at step **904**. Steps **904** through **908** may be repeated as many times as necessary to generate an acceptable selfie image.

(64) FIG. **10** illustrates an exemplary process **1000** for live streaming selfie content. At step **1002**, a selfie camera connects to a user device to establish a communication pathway for transferring messages and data. Once a connection is established, a selfie video preview may be provided to a user device, in step **1004**. The video image preview may be a live video stream of a scene as viewed by the selfie camera device. One or more aspects to the selfie video preview may be modified to simulate the appearance of selfie content on a social media and/or video streaming platform. At step **906**, a selfie camera receives a live stream command from a connected user device and connects to a social media and/or streaming video platform. The selfie camera may provide streamed video content to a connected user device in step **1008** and simultaneously share streamed video on a video streaming platform at step **1010**.

(65) FIG. **11** shows a user device **1100**, according to an embodiment of the present disclosure. The illustrative user device **1100** may include a memory interface **1102**, one or more data processors, image processors, central processing units **1104**, and/or secure processing units **1105**, and a peripherals interface **1106**. The memory interface **1102**, the one or more processors **1104** and/or secure processors **1105**, and/or the peripherals interface **1106** may be separate components or may be integrated into one or more integrated circuits. The various components in the user device **1100** may be coupled by one or more communication buses or signal lines.

(66) Sensors, devices, and subsystems may be coupled to the peripherals interface **1106** to facilitate multiple functionalities. For example, a motion sensor **1110**, a light sensor **1112**, and a proximity sensor **1114** may be coupled to the peripherals interface **1106** to facilitate orientation, lighting, and proximity functions. Other sensors **1116** may also be connected to the peripherals interface **1106**, such as a global navigation satellite system (GNSS) (e.g., GPS receiver), a temperature sensor, a biometric sensor, depth sensor, magnetometer, or another sensing device, to facilitate related functionalities.

(67) A camera subsystem **1120** and an optical sensor **1122**, e.g., a charged coupled device (CCD) or a complementary metal-oxide semiconductor (CMOS) optical sensor, may be utilized to facilitate camera functions, such as recording photographs and video clips. The camera subsystem **1120** and the optical sensor **1122** may be used to collect images of a user to be used during authentication of a user, e.g., by performing facial recognition analysis.

(68) Communication functions may be facilitated through one or more wired and/or wireless communication subsystems **1124**, which can include radio frequency receivers and transmitters and/or optical (e.g., infrared) receivers and transmitters. For example, the Bluetooth (e.g., Bluetooth low energy (BILE)) and/or WiFi communications described herein may be handled by wireless communication subsystems **1124**. The specific design and implementation of the communication subsystems **1124** may depend on the communication network(s) over which the user device **1100** is intended to operate. For example, the user device **1100** may include communication subsystems **1124** designed to operate over a GSM network, a GPRS network, an EDGE network, a WiFi or WiMax network, and a Bluetooth™ network. For example, the wireless communication subsystems **1124** may include hosting protocols such that the device **1100** can be configured as a base station for other wireless devices and/or to provide a WiFi service.

(69) An audio subsystem **1126** may be coupled to a speaker **1128** and a microphone **1130** to facilitate voice-enabled functions, such as speaker recognition, voice replication, digital recording, and telephony functions. The audio subsystem **1126** may be configured to facilitate processing voice commands, voiceprinting, and voice authentication, for example.

(70) The I/O subsystem **1140** may include a touch-surface controller **1142** and/or another input controller(s) **1144**. The touch-surface

controller **1142** may be coupled to a touch surface **1146**. The touch surface **1146** and touch-surface controller **1142** may, for example, detect contact and movement or break thereof using any of a plurality of touch sensitivity technologies, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with the touch surface **1146**.

(71) The other input controller(s) **1144** may be coupled to other input/control devices **1148**, such as one or more buttons, rocker switches, thumb-wheel, infrared port, USB port, and/or a pointer device such as a stylus. The one or more buttons (not shown) may include an up/down button for volume control of the speaker **1128** and/or the microphone **1130**.

(72) In some implementations, a pressing of the button for a first duration may disengage a lock of the touch surface **1146**; and a pressing of the button for a second duration that is longer than the first duration may turn power to the user device **1100** on or off. Pressing the button for a third duration may activate a voice control, or voice command, a module that enables the user to speak commands into the microphone **1130** to cause the device to execute the spoken command. The user may customize a functionality of one or more of the buttons. The touch surface **1146** can, for example, also be used to implement virtual or soft buttons and/or a keyboard.

(73) In some implementations, the user device **1100** may present recorded audio and/or video files, such as MP3, AAC, and MPEG files. In some implementations, the user device **1100** may include the functionality of an MP3 player, such as an iPod™. The user device **1100** may, therefore, include a 36-pin connector and/or 8-pin connector that is compatible with the iPod. Other input/output and control devices may also be used.

(74) The memory interface **1102** may be coupled to memory **1150**. The memory **1150** may include high-speed random access memory and/or non-volatile memory, such as one or more magnetic disk storage devices, one or more optical storage devices, and/or flash memory (e.g., NAND, NOR). The memory **1150** may store an operating system **1152**, such as Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks.

(75) The operating system **1152** may include instructions for handling basic system services and for performing hardware dependent tasks. In some implementations, the operating system **1152** may be a kernel (e.g., UNIX kernel). In some implementations, the operating system **1152** may include instructions for performing voice authentication.

(76) The memory **1150** may also store communication instructions **1154** to facilitate communicating with one or more additional devices, one or more computers and/or one or more servers. The memory **1150** may include graphical user interface (GUI) instructions **1156** to facilitate graphic user interface processing; sensor processing instructions **1158** to facilitate sensor-related processing and functions; phone instructions **1160** to facilitate phone-related processes and functions; electronic messaging instructions **1162** to facilitate electronic-messaging related processes and functions; web browsing instructions **1164** to facilitate web browsing-related processes and functions; media processing instructions **1166** to facilitate media processing-related processes and functions; GNSS/Navigation instructions **1168** to facilitate GNSS and navigation-related processes and instructions; and/or camera instructions **1170** to facilitate camera-related processes and functions.

(77) The memory **1150** may store application instructions and data **1172** for recognizing GUIs displaying content on a specific social media and/or video streaming platform; capturing characteristics of content displayed in relevant GUIs; generating selfie content previews using captured characteristics; sending settle content to a server device; communicating with a selfie camera; and editing captured selfie content. In various implementations, application data may include social media and/or video streaming platform content characteristics, selfie camera control commands, instructions for sharing selfie content, and other information used or generated by other applications persisted on a user device.

(78) The memory **1150** may also store other software instructions **1174**, such as web video instructions to facilitate web video-related processes and functions; and/or web instructions to facilitate content sharing-related processes and functions. In some implementations, the media processing instructions **1166** may be divided into audio processing instructions and video processing instructions to facilitate audio processing-related processes and functions and video processing-related processes and functions, respectively.

(79) Each of the above-identified instructions and applications may correspond to a set of instructions for performing one or more functions described herein. These instructions need not be implemented as separate software programs, procedures, or modules. The memory **1150** may include additional instructions or fewer instructions. Furthermore, various functions of the user device **1100** may be implemented in hardware and/or in software, including in one or more signal processing and/or application specific integrated circuits.

(80) In some embodiments, processor **1104** may perform processing including executing instructions stored in memory **1150**, and secure processor **1105** may perform some processing in a secure environment that may be inaccessible to other components of user device **1100**. For example, secure processor **1105** may include cryptographic algorithms on board, hardware encryption, and physical tamper proofing. Secure processor **1105** may be manufactured in secure facilities. Secure processor **1105** may encrypt data/challenges from external devices. Secure processor **1105** may encrypt entire data packages that may be sent from user device **1100** to the network. Secure processor **1105** may separate a valid user/external device from a spoofed one, since a hacked or spoofed device may not have the private keys necessary to encrypt-′decrypt, hash, or digitally sign data, as described herein.

(81) FIG. **12** shows an illustrative computer **1200** that may implement the archiving system and various features and processes as described herein. The computer **1200** may be any electronic device that runs software applications derived from compiled instructions, including without limitation personal computers, servers, smart phones, media players, electronic tablets, game consoles, email devices, etc. In some implementations, the computer **1200** may include one or more processors **1202**, volatile memory **1204**, non-volatile memory **1206**, and one or more peripherals **1208**. These components may be interconnected by one or more computer buses **1210**.

(82) Processor(s) **1202** may use any known processor technology, including but not limited to graphics processors and multi-core processors. Suitable processors for the execution of a program of instructions may include, by way of example, both general and special purpose microprocessors, and the sole processor or one of multiple processors or cores, of any kind of computer. Bus **1210** may be any known internal or external bus technology, including but not limited to ISA, EISA, PCI, PCI Express, NuBus, USB, Serial ATA or fireWire. Volatile memory **1204** may include, for example, SDRAM. Processor **1202** may receive instructions and data from a read-only memory or a random access memory or both. The essential elements of a computer may include a processor for executing instructions and one or more memories for storing instructions and data.

(83) Non-volatile memory **1206** may include, by way of example, semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and

DVD-ROM disks. Non-volatile memory **1206** may store various computer instructions including operating system instructions **1212**, communication instructions **1214**, application instructions **1216**, and application data **1217**. Operating system instructions **1212** may include instructions for implementing an operating system (e.g., Mac OS®, Windows®, or Linux).

(84) The operating system may be multi-user, multiprocessing, multitasking, multithreading, real-time, and the like. Communication instructions **1214** may include network communications instructions, for example, software for implementing communication protocols, such as TCP/IP, HTTP, Ethernet, telephony, etc. Application instructions **1216** can include social media and/or video streaming platform content characteristics, selfie camera control commands, instructions for sharing selfie content, and other information used or generated by other applications persisted on a user device. For example, application instructions **1216** may include instructions for modifying settle content previews, editing captured selfie content, and/or capturing and sharing selfie content using the system shown in FIG. **1**. Application data **1217** may correspond to data stored by the applications running on the computer **1200**. For example, application data **1217** may include selfie content, commands for controlling a selfie camera, image data received from a selfie camera, content characteristics retrieved from a social media and/or content video streaming platform, and/or instructions for sharing selfie content.

(85) Peripherals **1208** may be included within the computer **1200** or operatively coupled to communicate with the computer **1200**. Peripherals **1208** may include, for example, network interfaces **1218**, input devices **1220**, and storage devices **1222**. Network interfaces **1218** may include, for example, an Ethernet or WiFi adapter for communicating over one or more wired or wireless networks. Input devices **1220** may be any known input device technology, including but not limited to a keyboard (including a virtual keyboard), mouse, trackball, and touch-sensitive pad or display. Storage devices **1222** may include one or more mass storage devices for storing data files; such devices include magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and optical disks.

(86) As shown in FIG. **13**, the camera device **1300** includes one or more image sensors **1304** fitted with one lens **1302** per sensor. The lens **1302** and image sensor **1304** can capture images or video content. Each image sensors **1304** and lens **1302** may have associated parameters, such as the sensor size, resolution, and interocular distance, the lens focal lengths, lens distortion centers, lens skew coefficient, and lens distortion coefficients. The parameters of each image sensor and lens may be unique for each image sensor or lens, and are often determined through a stereoscopic camera calibration process. The camera device **1300** can further include a processor **1306** for executing commands and instructions to provide communications, capture, data transfer, and other functions of the camera device as well as memory **1308** for storing digital data and streaming video. For example, the storage device can be, e.g., a flash memory, a solid-state drive (SSD) or a magnetic storage device. The camera device may include a communications interface **1310** for communicating with external devices. For example, the stereoscopic device can include a wireless communications module for connecting to an external device (e.g., a laptop, an external hard drive, a tablet, a smart phone) for transmitting the data and/or messages to the external device. The camera device **1300** may also include an audio component **1312** (e.g., a microphone or other known audio sensor) for capturing audio content. A bus **1314**, for example, a high-bandwidth bus, such as an Advanced High-performance Bus (AHB) matrix interconnects the electrical components of the camera device **1300**.

(87) FIG. **14** show more details of the processor **1306** of the camera device shown in FIG. **13**. A video processor controls a camera **1412** (e.g., a selfie camera) using a camera control circuit **1410** according to commands received from a selfie camera controller. A power management integrated circuit (PMIC) **1420** is responsible for controlling a battery charging circuit **1422** to charge a battery **1424**. The battery **1424** supplies electrical energy for running the camera device **1300**. The PMIC **1420** may also control a electro adhesion control circuit **1490** that supplies power to an electroadhesion device **600**. The processor **1306** can be connected to an external device via a USB controller **1426**. In some embodiments, the battery charging circuit **1422** receives external electrical energy via the USB controller **1426** for charging the battery **1424**.

(88) The camera device **1300** may include a volatile memory **1430** (e.g., double data rate memory or 4R memory) and a non-volatile memory **1432** (e.g., embedded MMC or eMMC, solid-state drive or SSD, etc.). The processor **1306** can also control an audio codec circuit **1440**, which collects audio signals from microphone **1312** and microphone **1312** for stereo sound recording. The camera device **1300** can include additional components to communicate with external devices. For example, the processor **1306** can be connected to a video interface **1350** (e.g., Wifi connection, UDP interface, TCP link, high-definition multimedia interface or HDMI, and the like) for sending video signals to an external device. The camera device **1300** can further include an interface conforming to Joint Test Action Group (JTAG) standard and Universal Asynchronous Receiver/Transmitter (UART) standard. The camera device **1300** can include a slide switch **1460** and a push button **1462** for operating the camera device **1300**. For example, a user may turn on or off the camera device **1300** by pressing the push button **1462**. The user may switch on or off the electroadhesion device **600** using the slide switch **1460**. The camera device **1300** can include an inertial measurement unit (IMU) **1470** for detecting orientation and/or motion of the camera device **1300**. The processor **1310** can further control a light control circuit **1480** for controlling the status lights **1482**. The status lights **1482** can include, e.g., multiple light-emitting diodes (LEDs) in different colors for showing various status of the camera device **1300**.

(89) The foregoing description is intended to convey a thorough understanding of the embodiments described by providing a number of specific exemplary embodiments and details involving previewing, capturing, editing, and sharing pieces of content to improve the efficiency of capturing selfie content and the quality of captured selfie content. It should be appreciated, however, that the present disclosure is not limited to these specific embodiments and details, which are examples only. It is further understood that one possessing ordinary skill in the art, in light of known systems and methods, would appreciate the use of the invention for its intended purposes and benefits in any number of alternative embodiments, depending on specific design and other needs. A user device and server device are used as examples for the disclosure. The disclosure is not intended to be limited GUI display screens, image capture systems, data extraction processors, and client devices only. For example, many other electronic devices may utilize a system to preview, capture, and share piece of content including selfie images and videos.

(90) Methods described herein may represent processing that occurs within a system (e.g., system **100** of FIG. **1**). The subject matter described herein can be implemented in digital electronic circuitry, or in computer software, firmware, or hardware, including the structural means disclosed in this specification and structural equivalents thereof, or in combinations of them. The subject matter described herein can be implemented as one or more computer program products, such as one or more computer programs tangibly embodied in an information carrier (e.g., in a machine-readable storage device), or embodied in a propagated signal, for execution by, or to control the operation of, data processing apparatus (e.g., a programmable processor, a computer, or multiple computers). A

computer program (also known as a program, software, software application, or code) be written in any form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, or another unit suitable for use in a computing environment. A computer program does not necessarily correspond to a file. A program can be stored in a portion of a file that holds other programs or data, in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub programs, or portions of code). A computer program can be deployed to be executed on one computer or on multiple computers at one site or distributed across multiple sites and interconnected by a communication network.

(91) The processes and logic flows described in this specification, including the method steps of the subject matter described herein, can be performed by one or more programmable processors executing one or more computer programs to perform functions of the subject matter described herein by operating on input data and generating output. The processes and logic flows can also be performed by, and apparatus of the subject matter described herein can be implemented as, special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit).

(92) Processors suitable for the execution of a computer program include, by way of example, both general and special purpose microprocessors, and any one or more processor of any kind of digital computer. Generally, a processor will receive instructions and data from a read-only memory or a random access memory or both. The essential elements of a computer are a processor for executing instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic, magneto-optical disks, or optical disks. Information carriers suitable for embodying computer program instructions and data include all forms of nonvolatile memory, including, by ways of example, semiconductor memory devices, such as EPROM, EEPROM, flash memory device, or magnetic disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

(93) It is to be understood that the disclosed subject matter is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The disclosed subject matter is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting. As such, those skilled in the art will appreciate that the conception, upon which this disclosure is based, may readily be utilized as a basis for the designing of other structures, methods, and systems for carrying out the several purposes of the disclosed subject matter. Therefore, the claims should be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the disclosed subject matter.

(94) As used herein, the singular forms "a", "an", and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "includes" and/or "including", when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(95) As used herein, the terms "and/or" and "at least one of" include any and all combinations of one or more of the associated listed items.

(96) Certain details are set forth in the foregoing description and in FIGS. **1-14** to provide a thorough understanding of various embodiments of the present invention. Other details describing well-known structures and systems often associated with image processing, camera systems, user devices, and server devices, etc., however, are not set forth below to avoid unnecessarily obscuring the description of the various embodiments of the present invention.

(97) Although the disclosed subject matter has been described and illustrated in the foregoing exemplary embodiments, it is understood that the present disclosure has been made only by way of example, and that numerous changes in the details of implementation of the disclosed subject matter may be made without departing from the spirit and scope of the disclosed subject matter.

Claims

1. An electroadhesion device, comprising: a case including a removable attachment, the removable attachment including, a compliant thin film including a plurality of electrodes and insulating material formed between the plurality of electrodes, wherein the insulating material including a plurality of layers, and wherein the plurality of electrodes are arranged in pairs where each pair includes one each of negative and positive polarity, and wherein the electrodes include voltage converters configured to convert low voltage power to high voltage charges; a battery included in the case wherein the battery is configured to power the plurality of electrodes; a power management integrated circuit included in the case, in communication with the plurality of electrodes, the power management integrated circuit configured to activate and deactivate the plurality of electrodes with a response time less than about **50** milliseconds; wherein at least one sensor included the case, the sensor configured to determine conductivity of a surface placed in close proximity to the sensor; and wherein the case includes a selfie camera device.

2. The electroadhesion device of claim 1 further comprising, a digital switch in communication with the voltage converters and the at least one sensor, the digital switch configured to control the voltage converters voltage output based on conductivity data received from the at least one sensor.

3. The electroadhesion device of claim 2 wherein the digital switch further configured to use a look up table to determine adjustable voltage based on the sensor data.

4. The electroadhesion device of claim 2 wherein the digital switch further configured to use a predetermined algorithm to determine adjustable voltage based on the sensor data.

5. The electroadhesion device of claim 2 wherein the sensor includes at least one of: a Hall effect sensor, a magnetic field sensor, a time domain reflectometry (TDR) porosity sensor, a wave form sensor, a motion sensor; a surface texture sensor; a surface profile sensor, or a surface morphology sensor.

6. The electroadhesion device of claim 5 wherein the a wave form sensor is at least one of an ultrasound sensor, a radar sensor, an infrared sensor, a dot field projection depth sensor, or a time of flight depth sensor.

7. The electroadhesion device of claim 1 wherein the sensor is in communication with a status light configured to indicate a safe voltage.

8. The electroadhesion device of claim 1 wherein voltage generated by the voltage converter is a range of DC voltage from 250 V to 10,000 V.

9. The electroadhesion device of claim 1 wherein voltage generated by the voltage converter is a range of DC voltage from 500 V to 2,000 V.

10. The electroadhesion device of claim 1 wherein voltage generated by the voltage converter is a range of DC voltage from 6,000 V to 8,000 V.

11. The electroadhesion device of claim 1 wherein voltage generated by the voltage converter is a range of AC voltage from 250 Vrms to 10,000 Vrms.

12. The electroadhesion device of claim 1 wherein voltage generated by the voltage converter is a range of DC voltage from 500 Vrms to 2,000 Vrms.

13. The electroadhesion device of claim 1 wherein voltage generated by the voltage converter is a range of DC voltage from 6,000 Vrms to 8,000 Vrms.

14. An electroadhesion device, comprising: a case including a removable attachment, the removable attachment including, a compliant thin film including a plurality of electrodes and insulating material formed between the plurality of electrodes, wherein the insulating material including a plurality of layers, and wherein the plurality of electrodes are arranged in pairs where each pair includes one each of negative and positive polarity, and wherein the electrodes include voltage converters configured to convert low voltage power to high voltage charges; a battery included in the case wherein the battery is configured to power the plurality of electrodes; a power management integrated circuit included in the case, in communication with the plurality of electrodes, the power management integrated circuit configured to activate and deactivate the plurality of electrodes with a response time less than about **50** milliseconds; wherein at least one sensor included the case, the sensor configured to determine conductivity of a surface placed in close proximity to the sensor; wherein the sensor is one of an electromagnetic conductivity sensor, Hall effect sensor, magnetic field sensor, porosity sensor, wave form sensor, or motion sensor.

15. The electroadhesion device of claim 14 further comprising, a digital switch in communication with the voltage converters and the at least one sensor, the digital switch configured to control the voltage converters voltage output based on conductivity data received from the at least one sensor.

16. The electroadhesion device of claim 15 wherein the digital switch further configured to use a look up table to determine adjustable voltage based on the sensor data.

17. The electroadhesion device of claim 15 wherein the digital switch further configured to use a predetermined algorithm to determine adjustable voltage based on the sensor data.

18. The electroadhesion device of claim 14 wherein the case includes a selfie camera device.

19. The electroadhesion device of claim 14 wherein the sensor is in communication with a status light configured to indicate a safe voltage.

20. The electroadhesion device of claim 14 wherein voltage generated by the voltage converter is a range of DC voltage from 250 V to 10,000 V.