

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12385463
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Steiner; John

---

### Articulated-wing power generation

---

#### Abstract

An energy generation system to generate energy from a fluid flow, the energy generation system including an extendable arm that extends into a fluid flow, a fin connected to one end of the extendable arm and causing, due to the fluid flow, the extendable arm to move from a first orientation within the fluid flow to a second orientation within the fluid flow, and a joint connected to a second end of the extendable arm that couples the extendable arm to an energy generator.

---

<b>Inventors:</b>	<b>Steiner; John (Boise, ID)</b>
<b>Applicant:</b>	<b>Steiner; John (Boise, ID)</b>
<b>Family ID:</b>	<b>1000008750676</b>
<b>Appl. No.:</b>	<b>17/663905</b>
<b>Filed:</b>	<b>May 18, 2022</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20220372949 A1	Nov. 24, 2022

#### Related U.S. Application Data

us-provisional-application US 63190339 20210519

---

#### Publication Classification

**Int. Cl.:** F03B17/06 (20060101)

**U.S. Cl.:**

**CPC** F03B17/065 (20130101); F05B2220/706 (20130101); F05B2240/40 (20130101)

## Field of Classification Search

**CPC:** F03B (17/065); F05B (2220/706); F05B (2240/40)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5324169	12/1993	Brown	416/17	F03B 17/06
5708305	12/1997	Wolfe	60/497	F03B 13/1815
5899664	12/1998	Lawrence	417/334	F03B 17/06
6323563	12/2000	Kallenberg, Jr.	N/A	N/A
6652232	12/2002	Bolduc	N/A	N/A
6726440	12/2003	Pollard, V	N/A	N/A
7989973	12/2010	Birkestrand	N/A	N/A
8049357	12/2010	Saavedra	N/A	N/A
8288883	12/2011	Finnigan	N/A	N/A
8657575	12/2013	Morris	N/A	N/A
9291147	12/2015	Jones	N/A	N/A
10590907	12/2019	Chen et al.	N/A	N/A
10711761	12/2019	Mckinley	N/A	N/A
10968884	12/2020	English	N/A	N/A
2009/0056327	12/2008	Raikamo et al.	N/A	N/A
2011/0254276	12/2010	Anderson, Jr.	416/176	F03B 17/061
2015/0054287	12/2014	Jones	290/55	F03D 9/008
2017/0167467	12/2016	Toran et al.	N/A	N/A
2017/0175701	12/2016	Barrett	N/A	N/A
2020/0232442	12/2019	Bird	N/A	F03B 17/061

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2469073	12/2011	EP	N/A
6550569	12/2018	JP	N/A

### OTHER PUBLICATIONS

International Searching Authority; International Search Report and Written Opinion for Application No. PCT/US2022/72431 Aug. 9, 2022. cited by applicant

---

*Primary Examiner:* Nguyen; Viet P

*Attorney, Agent or Firm:* Parsons Behle & Latimer

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application, under 35 U.S.C. § 119, claims the benefit of U.S. Provisional Patent Application Ser. No. 63/190,339 filed on May 19, 2021, and entitled “Articulated-Wing Power Generation,” the contents of which are hereby incorporated by reference herein.

## FIELD OF THE DISCLOSURE

(1) This disclosure relates generally to fluid-flow energy generation. In particular, this disclosure relates to articulated wing energy generation systems and methods.

## BACKGROUND

(2) Hydroelectric and wind-power generators are generally known. Typically, hydroelectric systems require a dam or the like to store sufficient water to turn the turbines and associated generators used to generate electricity. Dams can be costly, can interfere with natural habitats and fish migration, and typically require extensive upkeep and maintenance.

(3) Wind based turbines may allow for more flexible placement and location. However, wind turbines can only generate electricity when sufficient wind is blowing. Other drawbacks, inefficiencies, and issues are also present in current systems and methods.

## SUMMARY

(4) Accordingly, disclosed embodiments address the above-noted, and other, drawbacks, inefficiencies, and issues with existing systems and methods. Disclosed embodiments include articulated wing-based energy generation systems that operate in a flowing fluid. As used herein, “fluid” means any liquid or gas that flows. As also used herein, “energy” means any potential to do work and includes, but is not limited to, electricity generation, hydraulic power, pneumatic power, mechanical power, and the like.

(5) Disclosed embodiments include an extendable arm that can be positioned in a fluid flow. A fin or wing on one end of the extendable arm is impacted by at least a portion of the fluid flow and causes the extendable arm to move. In some embodiments, the fin or wing is coupled to the extendable arm through a pivot joint that changes the orientation of the fin or wing upon reaching a set point or set time and causes the extendable arm to move in the opposite direction. The other end of the extendable arm is coupled to an energy generator that creates energy due to the motion of the extendable arm.

(6) Other embodiments also exist.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates an embodiment of an articulated wing energy generator sited along an irrigation canal in accordance with disclosed embodiments.

(2) FIG. 2 shows an exemplary embodiment where several articulated wing energy generator systems are located along the bank of a fluid flow in accordance with disclosed embodiments.

(3) FIGS. 3A-3C illustrate some hydrodynamic cross-sections usable with the extendable arm, the fin or wing, and other fluid-impinged components of disclosed embodiments.

(4) FIGS. 4A-4B illustrate a schematic view of articulating wing energy generator systems in accordance with disclosed embodiments.

(5) FIG. 5 illustrates a number of fin or wing embodiments in accordance with this disclosure.

(6) FIG. 6 is a schematic illustration of a mid-fluid flow mounting of articulating wing energy generator systems in accordance with disclosed embodiments.

(7) FIG. 7 is a schematic illustration of a pivotable mounting of articulating wing energy generator systems in accordance with disclosed embodiments.

(8) FIG. 8 is a side view schematic illustration of an articulating wing energy generator system in accordance with disclosed embodiments.

(9) FIG. 9 is a schematic illustration of an energy generator **106** in accordance with disclosed embodiments.

(10) While the disclosure is susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and will be described in detail

herein. However, it should be understood that the disclosure is not intended to be limited to the particular forms disclosed. Rather, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

#### DETAILED DESCRIPTION

(11) FIG. 1 illustrates an embodiment of an articulated wing energy generator sited along an irrigation canal **102** in accordance with disclosed embodiments. As shown a base **104** and an energy generator **106** may be positioned near a fluid flow **108**, in this embodiment an irrigation canal **100** containing flowing water. An extendable arm **110** is coupled to the energy generator **106** through a suitable joint **112**, shown in this embodiment as a rotating gimbal joint **112**. The other end of the extendable arm **110** includes a fin or wing **114** that is coupled to the extendable arm through a pivot joint **116** and is positionable in the fluid flow **108**. Embodiments of the pivot joint **116** may include a ratcheting mechanism, a hinge, an electronically controlled joint, or the like, that positions the fin or wing **114** in a first orientation causing the extendable arm **110** to move due to the fluid flow **108** moving over the fin or wing **114**. As indicated by the dotted arrow, when the extendable arm **110** moves to a set point **118A**, the pivot joint **116** changes the orientation of the fin or wing **114** and causes the extendable arm **110** to move back to an opposite set point **118B** and then changes the orientation of the fin or wing **114** back and repeats the cycle.

(12) The motion of the extendable arm **110** provides the energy to move the energy generator **106** (e.g., electric generator, hydraulic generator, pneumatic generator, mechanical generator, or the like) and generate energy. As also illustrated the energy generated may be fed into an electrical power grid **120** through a meter **122** and other power conditioning devices (not shown) as would be apparent to those of ordinary skill in the art having the benefit of this disclosure.

(13) As also shown in FIG. 1, the energy generator **106** may be positioned next to the fluid flow **108** and requires a relatively small footprint. Likewise, the amount of impingement into, and motion within, the fluid flow **108** can be set by appropriate stops or set points (e.g., **118A**, **118B**) on the extendable arm **110**, the gimbal joint **112**, the pivot joint **116**, and the like. In some embodiments, it is possible to remove the extendable arm **110** from the fluid flow **108** altogether to, for example, allow a boat to pass through, or the like.

(14) In other embodiments, it may be desirable to submerge the energy generator **106** and extendable arm **110** within the fluid flow **108**. For example, to be at a sufficient depth to allow boat and ship traffic to pass above.

(15) FIG. 2 shows an exemplary embodiment where several articulated wing energy generator systems **100A**, **100B**, **100C** are located along the bank of a fluid flow **108**, in this embodiment an irrigation canal **102** containing water. As would be apparent to those of ordinary skill in the art having the benefit of this disclosure, among other things, the relatively small footprint and freedom from significant obstruction or interference with the fluid flow, enable multiple systems **100A-C** to be installed and, potentially, generate significant amounts of energy.

(16) FIGS. 3A-3C illustrate some hydrodynamic cross-sections usable with the extendable arm, the fin or wing, and other fluid-impinged components of disclosed embodiments. For example, FIG. 3A illustrates an oblate circle cross-section that is a stable hydrodynamic shape. Narrower cross-sections can collapse vertically under the pressure. FIG. 3B illustrates a trimmed oblate circle cross-section that, for the same dimensions as the cross-section in FIG. 3A, has less hydrodynamic resistance due to the flat rear side and creates a minimal wake. FIG. 3C illustrates a Kamm Tail that has even less hydrodynamic resistance than either the FIG. 3A-3B cross-sections. Other cross-sections may also be used.

(17) FIGS. 4A-4B illustrate a schematic view of articulating wing energy generator systems **100** in accordance with disclosed embodiments. As also shown in FIG. 5, various fin or wing **114A-E** shapes, sizes, constructions, and the like may be used as would be apparent to those of ordinary skill in the art having the benefit of this disclosure. For example, a multi-piece construction may be used (e.g., **114C-D**) or a foldable or otherwise extendible wing (e.g., **114E**) may be used. Other

configurations are also possible. Likewise, multiple extendable arms **110**, bent arms, telescoping arms, and the like, may be used to take advantage of different fluid flows **108**, different locations for the energy generator **106**, different motions of the arm, and the like.

(18) FIG. **6** is a schematic illustration of a mid-fluid flow mounting of articulating wing energy generator systems **100** in accordance with disclosed embodiments. As shown, articulated wing generator **100** may be mounted on platform **124** that extends over the fluid flow **108** (in this example, irrigation canal **102**) so that extendable arm **110** and wings **114**, **114'** may be positioned to articulate near the middle of fluid flow **108** where, potentially, the fluid is deeper, swifter, or otherwise more advantageous to use. As also shown, extendable arm **110** may incorporate multiple wings **114**, **114'** on the same arm **110**. Wings **114**, **114'** may have the same, or differing, fluid flow characteristics depending on the fluid flow **108** and intended motion of extendable arm **110**.

(19) FIG. **7** is a schematic illustration of a pivotable mounting of articulating wing energy generator systems **100** in accordance with disclosed embodiments. As shown, articulating wing generator **100** may be mounted on a floating platform **126** connected to a stationary pivot point **128**. When fluid flow **108** changes direction, platform **126** may rotate, as indicated schematically by arrow **130**, about the pivot point **128**. As would be understood by those of skill in the art having the benefit of this disclosure, rotation **130** may be in either direction, may be partially limited or restrained, may be accomplished by powered motors, engines, or the like, may be accomplished by rudders or fins on the platform **126**, as applicable to the particular fluid flow being exploited. In some embodiments, a platform **126** may be located on an ocean or seaside where tidal changes cause a “reversal” of the fluid flow **108**.

(20) FIG. **8** is a side view schematic illustration of an articulating wing energy generator system **100** in accordance with disclosed embodiments. As shown in this exemplary embodiment, a dual fin **114**, **114'** extendable arm **110** is positioned in a fluid flow **108** (e.g., in an irrigation canal **102**). Bridge or platform **125** spans the canal **102** and allows the extendable arm **110** to be positioned advantageously in the fluid flow **108**. In some embodiments, extendable arm **110** may be mounted on a armature pivot **132** or the like and a desired depth maintained through a level adjuster **134** or the like. As also shown, some embodiments may have an energy generator **106** that comprises one or more hydraulic pumps **136** that convert and store the energy from the motion of the arm **110** due to the fluid flow **108** as disclosed herein.

(21) FIG. **9** is a schematic illustration of an energy generator **106** in accordance with disclosed embodiments. As shown, the motion of extendable arm **110** due to fluid flow **108** operates hydraulic pumps **136** which pump hydraulic fluid to a reservoir **138** and associated accumulators **140** for storage. In some embodiments, the hydraulic fluid can be controllably released, using the exemplary hydraulic circuit shown, to power a hydraulic motor/pump **142** which, in turn, may power an electric generator **144** or the like. Other embodiments and configurations are also possible.

(22) Although various embodiments have been shown and described, the present disclosure is not so limited and will be understood to include all such modifications and variations would be apparent to one skilled in the art.

## Claims

1. An energy generation system to generate energy from a fluid flow in an irrigation canal, the energy generation system comprising: an extendable arm that extends into a fluid flow in an irrigation canal; a fin, having an oblate circular cross section, connected to one end of the extendable arm and causing, due to the fluid flow, the extendable arm to move from a first orientation within the fluid flow to a second orientation within the fluid flow; a rotating gimbal joint connected to a second end of the extendable arm that couples the extendable arm to an energy generator, the energy generator comprising: at least one hydraulic pump that pumps a hydraulic

- fluid in a fluid circuit due to the motion of the extendable arm from the first orientation to the second orientation; a hydraulic motor in the fluid circuit and that operates due to the hydraulic fluid; and an electric generator operated by the hydraulic motor to generate electrical energy.
2. The energy generation system of claim 1 wherein the energy generator is mounted on a base that is located adjacent to the irrigation canal.
  3. The energy generation system of claim 1 wherein the energy generator is mounted on a base that is located within the irrigation canal.
  4. The energy generation system of claim 1 wherein the energy generator is mounted on a base that extends over the fluid flow.
  5. The energy generation system of claim 1 wherein the fluid flow can change direction and the energy generator is mounted on a base that rotates with the change in direction of the fluid flow.
  6. The energy generation system of claim 1 further comprising a second fin attached to extendable arm and in contact with the fluid flow.
  7. The energy generation system of claim 1 further comprising: a hydraulic accumulator in the fluid circuit that stores hydraulic fluid under pressure for selective release to the hydraulic motor.
  8. The energy generation system of claim 1 further comprising: a hydraulic reservoir in the fluid circuit that stores hydraulic fluid.
  9. An energy generation system to generate energy from a fluid flow, the energy generation system comprising: a first generation unit comprising: a first extendable arm that extends into a fluid flow; a first fin, having an oblate circular cross section, connected to one end of the first extendable arm and causing, due to the fluid flow, the first extendable arm to move from a first orientation within the fluid flow to a second orientation within the fluid flow; and a first rotating gimbal joint connected to a second end of the first extendable arm that couples the first extendable arm to a first energy generator, the first energy generator comprising: at least one first hydraulic pump that pumps a hydraulic fluid in a first fluid circuit due to the motion of the first extendable arm from the first orientation to the second orientation; a first hydraulic motor in the fluid circuit and that operates due to the hydraulic fluid; and a first electric generator operated by the first hydraulic motor to generate electrical energy; and a second generation unit comprising: a second extendable arm that extends into the fluid flow; a second fin, having an oblate circular cross section, connected to one end of the second extendable arm and causing, due to the fluid flow, the second extendable arm to move from a first orientation within the fluid flow to a second orientation within the fluid flow; and a second rotating gimbal joint connected to a second end of the second extendable arm that couples the second extendable arm to a second energy generator, the second energy generator comprising: at least one second hydraulic pump that pumps a hydraulic fluid in a second fluid circuit due to the motion of the second extendable arm from the first orientation to the second orientation; a second hydraulic motor in the second circuit and that operates due to the hydraulic fluid; and a second electric generator operated by the second hydraulic motor to generate electrical energy.
  10. The energy generation system of claim 9 wherein the fluid flow comprises water flow in an irrigation canal and the first and second energy generators are mounted on a base that is located adjacent to the irrigation canal.
  11. The energy generation system of claim 9 wherein the fluid flow comprises water flow in an irrigation canal and at least one of the first or second energy generators is mounted on a base that is located within the irrigation canal.
  12. The energy generation system of claim 9 wherein the fluid flow comprises water flow in an irrigation canal and at least one of the first or second energy generators is mounted on a base that extends over the fluid flow.
  13. The energy generation system of claim 9 further comprising: a hydraulic accumulator in at least one of the first or second fluid circuits that stores hydraulic fluid under pressure for selective release to the respective first or second hydraulic motors.

14. The energy generation system of claim 9 further comprising: a hydraulic reservoir in at least one of the first or second fluid circuits that stores hydraulic fluid.
  15. The energy generation system of claim 9 further comprising an additional fin attached to at least one of the first or second extendable arms and in contact with the fluid flow.
-