

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12382921
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kim; Tae-Hyun et al.

Toilet training device for a pet

Abstract

The present invention relates to a toilet training device for a pet. More specifically, the present invention relates to the toilet training device for the pet, which allows the pet to receive the automatic toilet training to save an owner's time for training the pet in connection with the defecation, wherein it enables the more correct determination about the pet's defecation state, while simplifying a sensor plate configuration for detecting the pet's defecation state, so that it is possible to reduce manufacturing cost thereof. The present invention for obtaining the above goals comprises a defecation unit which receives pet's excrement; and a feeding unit for supplying snack in case that the pet defecates on the defecation unit, wherein the defecation unit comprises a sensor plate for sensing the defecation state of the pet and a collecting member located below the sensor plate.

Inventors:	Kim; Tae-Hyun (Incheon, KR), Kim; Dong-Hyun (Goyang-si, KR)
Applicant:	Kim; Tae-Hyun (Incheon, KR); Kim; Dong-Hyun (Goyang-si, KR)
Family ID:	1000008748741
Appl. No.:	17/623243
Filed (or PCT Filed):	June 17, 2020
PCT No.:	PCT/KR2020/007817
PCT Pub. No.:	WO2021/002612
PCT Pub. Date:	January 07, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220361438 A1	Nov. 17, 2022

Foreign Application Priority Data

Publication Classification**Int. Cl.:** A01K1/01 (20060101)**U.S. Cl.:**

CPC A01K1/011 (20130101);

Field of Classification Search**CPC:** A01K (5/0114); A01K (5/0233); A01K (15/02); A01K (15/021); A01K (1/0107); C25D (5/14); H05K (3/467); H05K (3/4661); H05K (1/036); H05K (1/0298)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4837050	12/1988	Iwasa	427/96	B05D 5/12
10412933	12/2018	Eom	N/A	N/A
2006/0141763	12/2005	Brody	438/622	H01L 21/67173
2007/0252712	12/2006	Allen et al.	N/A	N/A
2012/0299731	12/2011	Triener	702/19	G16Z 99/00
2013/0105806	12/2012	Liu	257/E21.318	H10F 77/122
2014/0033989	12/2013	Ault	119/712	A01K 15/021

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1899002	12/2006	CN	C25D 7/00
417946	12/1990	EP	C08J 7/047
2519772	12/2014	GB	A01K 13/006
59-42440	12/1983	JP	N/A
2003163442	12/2002	JP	H05K 1/02
2004-507257	12/2003	JP	N/A
2017-020817	12/2016	JP	N/A
2019-110796	12/2018	JP	N/A
10-2004-0027806	12/2003	KR	N/A
20040027806	12/2003	KR	E04B 1/80
10-0609506	12/2005	KR	N/A
10-2008-0109506	12/2007	KR	N/A
20080109506	12/2007	KR	A01K 1/0107
10-2014-0108837	12/2013	KR	N/A
10-2014-0114420	12/2013	KR	N/A
20140114420	12/2013	KR	B32B 27/08
10-2017-0040032	12/2016	KR	N/A

20170040032	12/2016	KR	A01K 1/0107
10-2019-0019271	12/2018	KR	N/A
20190019271	12/2018	KR	A01K 1/0107

OTHER PUBLICATIONS

International Search Report for PCT/KR2020/007817 mailed Oct. 12, 2020 from Korean Intellectual Property Office. cited by applicant

Primary Examiner: Poon; Peter M

Assistant Examiner: Lynch; Carly W.

Attorney, Agent or Firm: Revolution IP, PLLC

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a toilet training device for a pet. More specifically, the present invention relates to the toilet training device for the pet, which allows the pet to receive the automatic toilet training to save an owner's time for training the pet in connection with the defecation. Also, it relates to the toilet training device enabling the more correct determination about the pet's defecation state, while simplifying a sensor plate configuration for detecting the pet's defecation state, so that it is possible to reduce manufacturing cost thereof.

TECHNICAL BACKGROUND

(2) Generally, a pet dog pees or poops on anywhere as well as on a blanket and a bed, if it is not well trained in connection with defecation. In such a case, an owner of a pet dog has difficulties for keeping the pet dog and may abandon his/her dog. Thus, the toilet training for the pet dog is very important, when keeping the pet dog indoors.

(3) Normally, it takes about two months for toilet-training a young pet dog so as to keep it indoors, although it depends on the dog's intelligence. The owner of the pet dog should spend a lot of hard work and dedication in order to let the dog complete the toilet training.

(4) In a conventional toilet training for the pet dog, 3-4 sheets of newspaper staked on top of each other is used. If the pet dog shows a sign of defecation while being observed, it is brought to a place where the stack of newspaper is laid. Then, it is necessary to wait until the pet dog finishes the defecation. By doing so, the pet dog will get into the habit of defecating on the newspaper. Instead of the newspaper, a defecation plate or a defecation pad may be used.

(5) On the other hand, stacking several sheets of the newspaper is to wet the newspaper below with the dog's urine and to soak the smell of urine on the newspaper. Also, it is to induce the dog to come to the previous defecation place by smelling its own urine on the newspaper when defecating later. However, such a toilet training requires a lot of time and effort from the owner, and thus, it is difficult to carry out the toilet training smoothly.

(6) Accordingly, KR 10-2019-0019271 discloses a toilet training device for a pet in order to solve these problems. Referring to FIGS. 1 and 2, it comprises: a body **110** having shielding walls installed at side and rear surfaces; a mesh plate **120** with a sensor unit located on a bottom side of the body, which includes a light sensor **122**, a humidity sensor **123** and an ammonia sensor **124**; a removable defecation member **130** located under the mesh plate **120** for receiving pet's excrements; a weight sensor located under the defecation member **130** for measuring weight of urine or stool; a defecation plate **100** comprising a transmitter (not shown) for transmitting sensed information from

the sensor unit; a feeding module **210** for supplying a snack or foodstuff to the pet when the pet poops on the defecation plate **100**; a sound recording module **220** enabling sound recording; a speaker module **230** outputting the sound recorded in the sound recording module **220** when the pet poops; a control module **240** for determining whether or not the pet poops on the defecation plate **100** and for operating the feeding module **210** when the pet poops thereon; and a feeder **200** comprising a receiver (not shown) for receiving sensed information of the sensor unit from the transmitter.

(7) The disclosure in KR 10-2019-0019271 is advantageous because the toilet training for the pet is automatically carried out and an owner of the pet does not have to spend a long time for training. However, a number of sensors are necessary for sensing and analyzing the pet's defecation. Thus, it has problems, such as complex configuration, high manufacturing cost and frequent breakdown.

SUMMARY OF THE INVENTION

(8) The present invention is to solve the above-described problems. The object of the present invention is to provide a toilet training device for a pet, which allows the pet to receive the automatic toilet training to save an owner's time for training the pet in connection with the defecation, wherein it enables the more correct determination about the pet's defecation state, while simplifying a sensor plate configuration for detecting the pet's defecation state.

(9) The other object of the present invention is to provide a toilet training device for a pet, which allows defecation situation to be monitored by sensing the pet's defecation state and sending defecation information to an owner's mobile terminal at a remote location in real time, wherein if more than a certain amount of excrement is collected in a defecation unit, the information thereof is sent to the mobile terminal so as to prevent excessive accumulation of excrement and to maintain pleasant environments.

(10) In order to the above-described objects, the present invention provides a toilet training device for a pet comprising: a defecation unit which is place where the pet defecates; and a feeding unit for supplying snack in case that the pet defecates on the defecation unit.

(11) The defecation unit comprises: a sensor plate for sensing the defecation state of the pet; and a collecting member located below the sensor plate.

(12) The sensor plate comprises: a body in a mesh shape; and a conductive circuit formed on an upper surface of the body for sensing the defecation state.

(13) The conductive circuit is formed to have a circuit part for + electricity and a circuit part for - electricity spaced apart from each other.

(14) The upper surface of the body is formed to have installation grooves into which the conductive circuit is installed and the conductive circuit has plating layers, which are formed by plating in the order of a nickel layer, a copper layer and a nickel layer.

(15) The conductive circuit further comprises a coating layer formed over the upper surface of the conductive circuit, which comprises cellulose derivatives.

(16) The collecting member is formed with a receiving part for receiving the pet's excrement, wherein the collecting member is formed with hooking grooves at both sides of its upper end and wherein the sensor plate is formed with handles at both sides to be inserted in the hooking grooves so that the sensor plate is spaced apart from a bottom of the receiving part.

(17) A disposable pad is further included within the receiving part.

(18) The feeding unit further comprises a remote mobile terminal and a communication module, wherein the defecation state sensed from the sensor plate is transmitted to the mobile terminal through the communication module.

(19) The mobile terminal calculates current amount of excrements received in the defecation unit based on the defecation state received and the warning that the defecation unit needs cleaning is given if the amount of excrements exceeds a predetermined value.

(20) The conductive circuit is formed by fusing conductive metal and the upper surface of the body with the use of a heat-bonding method or a high-frequency fusion method.

(21) The conductive circuit is directly formed on the upper surface of the body by a silk screen method or a pad printing method and a conductive paste and an adhesive is used as main materials.

(22) After printing on a film a conductive paste and an adhesive, which are used as main materials, the conductive circuit is formed by bonding the film to the upper surface of the body.

Effect of the Invention

(23) The present invention allows the pet to receive the automatic toilet training to thereby save an owner's time for training the pet in connection with the defecation. Also, it enables the more correct monitoring of the pet's defecation state, while simplifying a sensor plate configuration for detecting the pet's defecation state.

(24) Also, the present invention allows defecation situation to be monitored by sensing the pet's defecation state and sending defecation information to an owner's mobile terminal at a remote location in real time. Also, if more than a certain amount of excrement is collected in a defecation unit, it is sent to the mobile terminal so as to prevent excessive accumulation of excrements. Thus, it is possible to maintain pleasant environments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of a conventional toilet training device for a pet.
- (2) FIG. 2 is a detailed view of a mesh plate of the conventional toilet training device for the pet.
- (3) FIG. 3 shows a schematic configuration of the toilet training device for the pet according to the present invention.
- (4) FIG. 4 is an exploded perspective view of a defecation unit of the toilet training device for the pet according to the present invention.
- (5) FIG. 5 is a block diagram of the toilet training device for the pet according to the present invention.
- (6) FIG. 6 is an enlarged view of a sensor plate in the defecation unit of the toilet training device for the pet according to the present invention.
- (7) FIG. 7 is a sectional view of the sensor plate in the toilet training device for the pet according to the present invention.
- (8) FIG. 8 is a plan view showing embodiments of various patterns of the conductive circuits in the toilet training device for the pet according to the present invention

DETAILED DESCRIPTION OF THE INVENTION

(9) Hereinafter, preferred embodiments of the present invention will be described in more detail with reference to the accompanying drawings. The same reference numerals are used for the same components in the drawings, and repeated descriptions of the same components are omitted. Also, it should be understood that the present invention may be implemented in many different ways and is not limited to the described embodiments.

(10) FIG. 3 shows a configuration of the toilet training device for the pet according to the present invention; FIG. 4 is an exploded perspective view of a defecation unit of the toilet training device for the pet according to the present invention; FIG. 5 is a block diagram of the toilet training device for the pet according to the present invention; FIG. 6 is an enlarged view of a sensor plate in the defecation unit of the toilet training device for the pet according to the present invention; FIG. 7 is a sectional view of the sensor plate in the toilet training device for the pet according to the present invention; and FIG. 8 is a plan view showing embodiments of various patterns of the conductive circuits in the toilet training device for the pet according to the present invention

(11) The present invention relates to a toilet training device for pet. As shown in FIGS. 3 to 8, the toilet training device for the pet comprises: a defecation unit **300**, which is a place where the pet defecates, and a feeding unit **400**, which provides a snack when the pet defecates on the defecation

unit **300**.

(12) Here, when the pet defecates, it is sensed in the defecation unit **300**, and the feeding unit **400** receives a signal sensed by the defecation unit **300**. If the defecation is in a normal state, the snacks stored within the feeding unit **400** are supplied.

(13) Therefore, in the prior art, the owner had to train for a long time for the toilet training of the pet. However, the present invention enables automatic toilet-training through the toilet training device for the pet, and thus, the time that the owner should spend for the toilet training may be saved.

(14) The defecation unit **300** comprises: a sensor plate **310** for sensing the defecation state of the pet; and a collecting member **330** located under the sensor plate **310** so as to receive the pet's excrements.

(15) Here, the sensor plate **310** comprises: a body **311** in the form of a mesh, which enables the penetration; and a conductive circuit **320** formed on the upper surface of the body **311** for sensing the defecation state.

(16) Here, a connection terminal **314** for providing electricity to the conductive circuit **320** is provided on a side of the sensor plate **310**, and the conductive circuit **320** comprises a circuit part **320a** for + electricity and a circuit part **320b** for – electricity serving as a switch. The circuit part **320a** for + electricity and the circuit part **320b** for – electricity are positioned adjacent to each other, but they are formed to be spaced apart from each other.

(17) Therefore, when the pet defecates on the upper part of the sensor plate **310**, urine or feces is disposed to span the circuit part **320a** for + electricity and the circuit part **320b** for – electricity. Then, water component included in urine and feces allows the circuit parts **320a** and **320b** to be electrically connected, so that it is possible to monitor whether or not the pet defecates by sensing the electric connection.

(18) Of course, when urine or stool dries over time, the electrical connection between the circuit part **320a** for + electricity and the circuit part **320b** for – electricity is terminated.

(19) On the other hand, an installation groove **316** for installing the conductive circuit **320** is formed on the upper surface of the body **311**, wherein the body **311** is made from synthetic resin (e.g., polycarbonate, etc.) that is easily softened by heat, and wherein the installation groove **316** is formed to have a groove shape on the upper surface of the body **311** using a Laser Direct Structuring (LDS) technique.

(20) Here, the conductive circuit **320** is formed in the installation groove **316** by a plating method. In other words, the conductive circuit is formed by plating in the order of the nickel layer **322**, the copper layer **324**, and the nickel layer **326** from a bottom.

(21) The copper layer **324** increases electrical conductivity, and the nickel layers **322** and **326** respectively formed on upper and lower surfaces of the copper layer **324** increases corrosion resistance. Thus, the phenomenon that the conductive circuit **320** is damaged from urine or stool is stably prevented.

(22) The inner and lower surface of the installation groove **316** is formed to have a concave-convex shape, and the conductive circuit **320** is formed by plating, so that the bonding force increases. The installation groove **316** is formed to have a depth of about 5 to 6 μm , and the conductive circuit **320** is formed to have a thickness of 13 μm in total by forming the nickel layers **322** and **326** to have 3 μm , and forming the copper layer **324** to have 7 μm .

(23) Accordingly, the conductive circuit **320** protrudes beyond the upper surface of the installation groove **316**, so that the conductive circuit is in more stable contact with the pet's excrement. As a result, it is possible to detect the occurrence of the pet's defecation more accurately.

(24) In addition, a coating layer **328** may be further formed over the conductive circuit **320**, wherein the coating layer **328** is formed from a cellulose derivative. Thus, it is possible to maintain electrical conductivity, while stably preventing corrosion that may occur in a washing process, etc.

(25) Here, the pattern of the conductive circuit **320** may be formed in various patterns as shown in

FIG. 8 as well as the patterns shown in FIGS. 6 and 7. Also, various patterns not shown in the drawings are available.

(26) In the other embodiment of the present invention, when forming the conductive circuit **320** on the upper surface of the body **311**, the conductive circuit **320** may be formed by fusing conductive metal and the upper surface of the body **311** with the use of a heat-bonding method or a high-frequency fusion method, other than the above-described LDS technique.

(27) In addition, the conductive circuit **320** may be directly formed on the upper surface of the body **311** by silk screen or pad printing, wherein a conductive paste such as silver paste and an adhesive is used as main materials. Otherwise, after printing on a separate film (not shown) a conductive paste and an adhesive which is used as main materials, the conductive circuit **320** may be formed by bonding the printed film to the upper surface of the body **311**.

(28) Here, additional plating may be performed over the conductive circuit **320** in order to prevent damage such as corrosion, while increasing electrical conductivity.

(29) The collecting member **330** is located under the sensor plate **310**. The collecting member **330** is formed with a receiving part **332** therein. The collecting member **330** has an opening on its upper part so as to make it possible to collect the pet's excrements.

(30) Here, the collecting member **330** is formed with hooking grooves **334** positioned at both sides of its upper end. Also, the sensor plate **310** is formed with handles **312** at both sides, which protrude outward. The handles **312** are inserted into the hooking grooves **334**, so that the sensor plate **310** is securely supported on the collecting member **330** without swaying.

(31) Since the handles **312** project beyond the hooking grooves **334**, the sensor plate **310** may be readily removed when the pet owner tries to remove the excrements collected in the collecting member **330**.

(32) On the other hand, the receiving part **332** further comprises a disposable pad (not shown). The disposable pad may absorb a certain amount of the pet's urine, and thus, the absorption of the pet's urine is possible, even if the pet urinates several times. Accordingly, it is possible to minimize bad smell.

(33) The feeding unit **400** is provided at a side of the defecation unit **300**. The defecation unit **300** is electrically connected to the feeding unit **300** through an electric wire connected to a connection terminal **314** formed at a side of the sensor plate **310**.

(34) The feeding unit **400** comprises a snack receiver **410** for receiving the snack, which will be supplied to the pet as a compensation, and an automatic snack feeder **420** for providing the snack into the snack receiver **410**. The automatic snack feeder **420** includes a controller **430** for controlling the snack supply in accordance with a signal received from the defecation unit **300**.

(35) Various techniques are well known in connection with the automatic snack feeder **420**, and thus, further description will not be given with respect thereto.

(36) Additionally, a communication module **432** is further included in the automatic snack feeder **420** of the feeder unit **400**. The communication module **432** transmits the defecation state, which is received from the defecation unit **300**, to the mobile terminal **500** positioned at a remote location in real time through a wire or wireless communication network.

(37) Accordingly, the owner who is positioned at a remote location can monitor the pet's defecation state in a real time with the use of the mobile terminal **500**. Further, the mobile terminal **500** may calculate (presume) an amount of the pet's excrement currently received in the defecation unit **300** based on the defecation situation (the number of defecation). If the amount of the excrement exceeds a predetermined value, the warning that the defecation unit **300** needs cleaning is given.

(38) Here, the capacity that a disposable pad can absorb is set by the owner, and the mobile terminal **500** determines the amount of urine that the pet excretes at one time based on the pet's age, weight, breed etc. On the basis thereof, the number of pees that the disposable pad can absorb is counted. When the received number of pees is coincident with the counted number, a warning will be given to the owner (the user), to thereby let the owner handle the situation quickly.

(39) If the user (owner) finishes cleaning the defecation unit **300**, the cleaning state may be uploaded in the mobile terminal **500** and the number of the defecation may be re-counted.

(40) The body **311** further comprises a heater (not shown) made of heating wires, in addition to the conductive circuit **320**. When the controller **430** senses the defecation state through the conductive circuit **320**, it can cause the heater to operate for rapidly drying excrements on the sensor plate **320**. Thus, it is possible to prevent odor of excrements from being spread.

(41) Under the circumstance that continuous defecation signals from the conductive circuit **320** are sensed owing to undried excrements, a correct sensing may be impossible, if the pet additionally poops or fees. Thus, the correct sensing is available by rapidly drying the excrement, even if the pet additionally defecates.

(42) Although preferred embodiments of the present invention have been described above, the scope of the present invention is not limited thereto. The scope of the rights of the present invention extends to those that are substantially equivalent to the embodiments of the present invention. Various modifications can be made by those of ordinary skill in the art to which the invention pertains without departing from the spirit of the invention.

INDUSTRIAL APPLICABILITY

(43) The present invention relates to a toilet training device for pet. More specifically, the present invention relates to the toilet training device for pet, which allows the pet to receive the automatic toilet training to save an owner's time for training the pet in connection with the defecation, wherein it enables the more correct monitoring of the pet's defecation state, while simplifying a sensor plate configuration for detecting the pet's defecation state, so that it is possible to reduce manufacturing cost thereof.

Claims

1. A toilet training device for a pet consisting of: a defecation unit which is a place where the pet defecates; and a feeding unit for supplying a snack when the pet defecates on the defecation unit, wherein the defecation unit consists of: a sensor plate for sensing the defecation state of the pet; and a collecting member located below the sensor plate, wherein the sensor plate consists of: a body in a mesh shape; and a conductive circuit formed on an upper surface of the body for sensing the defecation state, wherein the upper surface of the body is formed to have installation grooves having a depth of 5 to 6 μm into which the conductive circuit is installed and a coating layer directly covering the conductive circuit and a part of the upper surface of the body, wherein the conductive circuit has only three plating layers, which are formed by plating in the order of a first nickel layer having a thickness of 3 μm , a copper layer having a thickness of 7 μm , and a second nickel layer having a thickness of 3 μm so that the second nickel layer directly contacts with the copper layer without contacting the first nickel layer, wherein each of the first nickel layer, the copper layer, and the second nickel layer has a same width throughout a length of the conductive circuit, wherein the width of the conductive circuit is equal to a width of the installation groove so that the first nickel layer and a portion of the copper layer completely fill in the installation groove, wherein the coating layer is made of a cellulose derivative to prevent from corrosion, wherein the conductive circuit protrudes beyond the upper surface surrounding the installation groove, wherein the conductive circuit is formed in a grid pattern consisting of a plurality of horizontal lines and vertical lines intersecting perpendicular to each other.
2. The toilet training device as claimed in claim 1, wherein the conductive circuit is formed to have a circuit part for + electricity and a circuit part for - electricity spaced apart from each other.
3. The toilet training device as claimed in claim 1, wherein the collecting member is formed with a receiving part for receiving the pet's excrement, wherein the collecting member is formed with hooking grooves at both sides of its upper end and wherein the sensor plate is formed with handles at both sides to be inserted in the hooking grooves so that the sensor plate is spaced apart from a

bottom of the receiving part.

4. The toilet training device as claimed in claim 1, wherein a disposable pad is further included within the receiving part.

5. The toilet training device as claimed in claim 1, wherein the conductive circuit is formed by fusing conductive metal and the upper surface of the body with the use of a heat-bonding method or a high-frequency fusion method.

6. The toilet training device as claimed in claim 1, wherein the conductive circuit is directly formed on the upper surface of the body by a silk screen method or a pad printing method and wherein a conductive paste and an adhesive is used as main materials.

7. The toilet training device as claimed in claim 1, wherein after printing on a film a conductive paste and an adhesive, which are used as main materials, the conductive circuit is formed by bonding the film to the upper surface of the body.

8. A toilet training device for a pet comprising consisting of: a defecation unit which is a place where the pet defecates; and a feeding unit for supplying a snack when the pet defecates on the defecation unit, the feeding unit consists of: a remote mobile terminal; and a communication module wherein the defecation unit consists of: a sensor plate for sensing the defecation state of the pet; and a collecting member located below the sensor plate, wherein the sensor plate consists of: a body in a mesh shape; and a conductive circuit formed on an upper surface of the body for sensing the defecation state, wherein the upper surface of the body is formed to have installation grooves having a depth of 5 to 6 μm into which the conductive circuit is installed and a coating layer directly covering the conductive circuit and a part of the upper surface of the body, wherein the conductive circuit has only three plating layers, which are formed by plating in the order of a first nickel layer having a thickness of 3 μm , a copper layer having a thickness of 7 μm , and a second nickel layer having a thickness of 3 μm so that the second nickel layer directly contacts with the copper layer without contacting the first nickel layer, wherein each of the first nickel layer, the copper layer, and the second nickel layer has a same width throughout a length of the conductive circuit, wherein the width of the conductive circuit is equal to a width of the installation groove so that the first nickel layer and a portion of the copper layer completely fill in the installation groove, wherein the coating layer is made of a cellulose derivative to prevent from corrosion, wherein the conductive circuit protrudes beyond the upper surface surrounding the installation groove, wherein the conductive circuit is formed in a grid pattern consisting of a plurality of horizontal lines and vertical lines intersecting perpendicular to each other, wherein the defecation state sensed from the sensor plate is transmitted to the mobile terminal through the communication module.

9. The toilet training device as claimed in claim 8, wherein the mobile terminal calculates current amounts of excrements received in the defecation unit based on the defecation state received and wherein a warning that the defecation unit needs cleaning is given if the amount of excrements exceeds a predetermined value.
