



US012383784B2

(12) **United States Patent**  
**McLaughlin**

(10) **Patent No.:** **US 12,383,784 B2**  
(45) **Date of Patent:** **Aug. 12, 2025**

(54) **MAGNETICALLY COUPLED BARBELL PAD AND RELATED METHODS**

(71) Applicant: **LiftMo LLC**, Orlando, FL (US)

(72) Inventor: **Haley McLaughlin**, Oviedo, FL (US)

(73) Assignee: **LIFTMO LLC**, Orlando, FL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 108 days.

4,588,191 A \* 5/1986 Stewart ..... A63B 69/3638  
273/DIG. 30  
5,415,607 A \* 5/1995 Carpenter ..... A63B 21/4001  
482/106  
5,460,378 A \* 10/1995 Getts ..... A63B 69/3638  
473/238  
6,083,116 A \* 7/2000 Loreda ..... A63B 69/3638  
473/256  
6,224,518 B1 \* 5/2001 Weiss ..... A63B 21/078  
482/106  
6,604,789 B1 \* 8/2003 Downing ..... A47C 31/11  
5/663

(Continued)

(21) Appl. No.: **18/502,222**

**FOREIGN PATENT DOCUMENTS**

(22) Filed: **Nov. 6, 2023**

GB 2504722 2/2014

(65) **Prior Publication Data**

US 2024/0149099 A1 May 9, 2024

**Related U.S. Application Data**

(60) Provisional application No. 63/422,673, filed on Nov. 4, 2022.

**OTHER PUBLICATIONS**

Gopher Sport "Gopher Magnetic Barbell Pad" <https://www.gophersport.com/product-and-service-delay>: Retrieved from internet May 1, 2022; pp. 4.

(51) **Int. Cl.**

**A63B 21/078** (2006.01)

**A63B 21/072** (2006.01)

*Primary Examiner* — Garrett K Atkinson

(74) *Attorney, Agent, or Firm* — Allen, Dyer, Doppelt + Gilchrist, PA

(52) **U.S. Cl.**

CPC ..... **A63B 21/0783** (2015.10); **A63B 21/0724** (2013.01); **A63B 2209/08** (2013.01)

(57)

**ABSTRACT**

(58) **Field of Classification Search**

CPC ..... **A63B 21/0783**; **A63B 21/0724**; **A63B 2209/08**; **A63B 2209/00**; **A63B 2209/10**  
See application file for complete search history.


A barbell pad includes a base having first and second arms, and a curved channel between the first and second arms. The first and second arms extend laterally away from the curved channel, and the first and second arms extend in opposite directions. The barbell pad also includes magnets carried by the base within the curved channel and to be magnetically coupled to a barbell, and a flexible pad coupled to the base opposite to the magnets to distribute weight load from the barbell.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,984,486 A \* 5/1961 Jones ..... A63B 60/08  
473/568  
4,017,070 A \* 4/1977 Hilton ..... A63B 69/00  
434/247

**20 Claims, 6 Drawing Sheets**




(56)

**References Cited**


## U.S. PATENT DOCUMENTS

6,676,575 B1 *	1/2004	Mayo .....	A63B 23/0211	2001/0052710 A1 *	12/2001	Witherell .....	A63B 21/4035
			482/148				294/137
7,175,572 B2 *	2/2007	Stonecipher .....	A63B 21/072	2008/0040891 A1 *	2/2008	Tyler .....	A63B 21/4017
			482/106				16/421
7,490,361 B1 *	2/2009	Floyd .....	A63B 21/4005	2009/0258765 A1 *	10/2009	Panicali .....	A63B 21/4035
			2/94				482/106
7,494,451 B1 *	2/2009	Ramos .....	A63B 21/0728	2009/0275447 A1 *	11/2009	Fishman .....	A63B 21/072
			482/148				482/139
7,588,500 B2 *	9/2009	Hoeckl .....	A63B 69/3638	2012/0129664 A1 *	5/2012	Perry .....	A63B 71/14
			473/226				482/139
8,128,541 B2 *	3/2012	Hartman .....	A63B 21/4017	2013/0196824 A1 *	8/2013	Ross .....	A63B 1/005
			482/122				482/40
D688,338 S *	8/2013	Bisson .....	D21/694	2014/0274614 A1 *	9/2014	Newman .....	A63B 21/4035
8,500,609 B1 *	8/2013	Williams .....	A63B 21/0726				482/139
			135/65	2015/0065315 A1 *	3/2015	Ferrell .....	A63B 21/078
9,138,613 B2 *	9/2015	Ferrell .....	A63B 21/078				482/104
9,656,120 B1 *	5/2017	Franco .....	A63B 24/0062	2016/0045809 A1 *	2/2016	Jones .....	A63B 71/0054
9,839,806 B2 *	12/2017	Slaughter .....	A63B 21/0728				428/100
9,907,993 B2 *	3/2018	Penney .....	A63B 21/4035	2016/0332022 A1 *	11/2016	Mathews .....	A63B 21/4035
10,806,987 B2 *	10/2020	Burns .....	A63B 21/4035	2018/0021662 A1 *	1/2018	Carpinelli .....	A63B 21/0726
D945,108 S *	3/2022	Walker .....	D34/27				482/104
11,266,870 B2 *	3/2022	Leadbetter .....	A63B 21/0724	2018/0264313 A1 *	9/2018	Boysen .....	A63B 21/0724
D980,928 S *	3/2023	Hetrick .....	D21/694	2019/0001211 A1 *	1/2019	Burns .....	A63B 21/0724
D985,697 S *	5/2023	Hetrick .....	D21/694	2019/0059568 A1 *	2/2019	Orlando .....	A46B 5/0041
11,896,889 B2 *	2/2024	Stubbers .....	A63B 71/1225	2022/0047910 A1 *	2/2022	Beck .....	A63B 21/0442
2001/0024999 A1 *	9/2001	Pappert .....	A63B 23/00	2022/0161122 A1 *	5/2022	Stubbers .....	A63B 23/0222
			482/93	2022/0273978 A1 *	9/2022	Malave .....	A63B 21/00189
				2022/0314060 A1 *	10/2022	Fogle .....	A63B 21/0728
				2023/0123935 A1 *	4/2023	Staken .....	A63B 21/4035
							482/139

\* cited by examiner



**FIG. 1**

**FIG. 2**






FIG. 3



**FIG. 4A**



**FIG. 4B**





FIG. 5A



**FIG. 5B**



1

# MAGNETICALLY COUPLED BARBELL PAD AND RELATED METHODS

## RELATED APPLICATION

This application is based upon prior filed Application No. 63/422,673 filed Nov. 4, 2022, the entire subject matter of which is incorporated herein by reference in its entirety.

## TECHNICAL FIELD

The present disclosure relates to the field of exercise equipment, and, more particularly, to a weight lifting accessory device and related methods.

## BACKGROUND

Exercise is widely accepted as a means of promoting and maintaining good health and wellbeing. Many forms of exercise equipment are used. In particular, barbells are widely used for many exercise movements. Barbells consist of a long bar ranging in length from 2 to 8 feet, often with disc shaped weights attached on each end. The barbell is used for free weight training and competitive sports to perform dynamic movements, such as the bench press, back squat, front squat, and hip thrusters. During these movements (especially squats and hip thrusters), heavy weights may be used, which may cause significant pressure on the contact points between the barbell and the user's body.

## SUMMARY

Generally, a barbell pad comprises a base comprising first and second arms, and a curved channel between the first and second arms. The first and second arms extend laterally away from the curved channel, and the first and second arms extend in opposite directions. The barbell pad also includes a plurality of magnets carried by the base within the curved channel and to be magnetically coupled to a barbell, and a flexible pad coupled to the base opposite to the plurality of magnets to distribute weight load from the barbell.

In particular, each of the plurality of magnets may comprise a curve-shaped magnet, and each of the plurality of magnets may be recessed within the curved channel. The first and second arms may be substantially parallel to each other. The curved channel may comprise a semi-circle shaped channel, and the first and second arms may extend perpendicularly from ends of the semi-circle shaped channel. The flexible pad may comprise a first end coupled to the base, and a second end opposite to the first end, the second end being curve-shaped.

In some embodiments, the plurality of magnets may comprise first and second pairs of aligned magnets, and each of the first and second pairs of aligned magnets may comprise a first magnet within the curved channel adjacent to the first arm, and a second magnet within the curved channel adjacent to the second arm and aligned with the first magnet.

Also, the barbell pad may further comprise an adhesive layer between the base and the flexible pad. For example, the flexible pad may comprise a foam pad; and the base may comprise a polymer plastic material.

Another aspect is directed to a method for making a barbell pad. The method includes forming a base comprising first and second arms, and a curved channel between the first and second arms. The first and second arms extend laterally away from the curved channel, and the first and second arms extend in opposite directions. The method also includes

2

positioning a plurality of magnets carried by the base within the curved channel and to be magnetically coupled to a barbell, and coupling a flexible pad to the base opposite to the plurality of magnets to distribute weight load from the barbell.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a barbell pad, according to the present disclosure.

FIG. 2 is a side view of the barbell pad of FIG. 1.

FIG. 3 is a top plan view of the barbell pad of FIG. 1.

FIGS. 4A and 4B are perspective and side views of the magnet from the barbell pad of FIG. 1, respectively.

FIG. 5A is a cross-section view of the barbell pad of FIG. 1 along line 5-5 of FIG. 3 without the magnets.

FIG. 5B is an enlarged cross-section view from FIG. 5A without the flexible pad.

## DETAILED DESCRIPTION

The present disclosure will now be described more fully hereinafter with reference to the accompanying drawings, in which several embodiments of the invention are shown. This present disclosure may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the present disclosure to those skilled in the art. Like numbers refer to like elements throughout.

Referring initially to FIGS. 1-3, a barbell pad 100 according to the present invention is now described. The barbell pad 100 comprises a base 101 comprising first and second arms 102a-102b, and a curved channel 103 between the first and second arms. In the illustrated embodiment, the curved channel 103 comprises a semi-circle shaped channel (i.e., an arc of  $180^\circ \pm 10^\circ$ ). Of course, in other embodiments, the curved channel 103 may comprise other oblong shapes.

The first and second arms 102a-102b extend laterally away from the curved channel 103, and the first and second arms extend in opposite lateral directions. As perhaps best seen in FIG. 2, the first and second arms 102a-102b may be substantially parallel to each other (i.e.,  $\pm 10^\circ$  of parallel), and the curved channel 103 is centrally placed between the first and second arms 102a-102b. The first and second arms 102a-102b extend perpendicularly from ends of the semi-circle shaped channel. As shown in FIG. 3, the barbell pad 100 also includes a plurality of magnets 104a-104d carried by the base 101 within the curved channel 103 and to be magnetically and releasably coupled to a barbell 105.

Referring now additionally to FIGS. 4A-4B & 5A-5B, each of the plurality of magnets 104a-104d illustratively comprises a curve-shaped magnet, and each of the plurality of magnets may be partially or fully recessed within the curved channel 103. Here, the plurality of magnets 104a-104d comprises first and second pairs 104a-104b, 104c-104d of aligned magnets. As perhaps best seen in FIG. 5A, each of the first and second pairs 104a-104b, 104c-104d of aligned magnets comprises a first magnet within the curved channel 103 adjacent to the first arm 102a, and a second magnet within the curved channel adjacent to the second arm 102b and aligned with the first magnet. Helpfully, in combination with the recessed first and second pairs 104a-104b, 104c-104d of aligned magnets, this maintains a tight magnetic coupling to the barbell 105.

3

As perhaps best seen in FIGS. 4A-4B, each of the plurality of magnets **104a-104d** illustratively has a curved rectangular box shape. Also, each of the plurality of magnets **104a-104d** comprises a first convex side **111a**, and a second concave side **111b** opposite to the first convex side. The second concave side **111b** is to be positioned within matching recesses **112a-112b** within the curved channel **103**.

The barbell pad **100** also includes a flexible pad **106** coupled to the base **101** opposite to the plurality of magnets **104a-104d**. The flexible pad **106** cooperates with the base **101** to distribute weight load from the barbell **105**. The flexible pad **106** comprises a first end **107a** coupled to the base **101**, and a second end **107b** opposite to the first end. The second end **107b** is illustratively curve-shaped to better cushion the associated weight carried by the barbell **105** for the user. As perhaps best seen in FIGS. 2 & 5A, the flexible pad **106** is illustratively substantially semi-cylinder shaped.

Also, the barbell pad **100** further comprises an adhesive layer **110** between the base **101** and the flexible pad **106**. For example, the flexible pad **106** may comprise a foam pad. The base **101** may comprise a rigid material with sufficient mechanical strength to not deform under typical barbell weights. For example, the base **101** may comprise a polymer plastic material, or a metallic compound.

Another aspect is directed to a method for making a barbell pad **100**. The method includes forming a base **101** comprising first and second arms **102a-102b**, and a curved channel **103** between the first and second arms. The first and second arms **102a-102b** extend laterally away from the curved channel **103**, and the first and second arms extend in opposite directions. The method also includes positioning a plurality of magnets **104a-104d** carried by the base **101** within the curved channel **103** and to be magnetically coupled to a barbell **105**, and coupling a flexible pad **106** to the base opposite to the plurality of magnets.

Yet another aspect is directed to a method for using a barbell pad **100** with a barbell **105** and associated desired weight. The barbell pad **100** includes a base **101** comprising first and second arms **102a-102b**, and a curved channel **103** between the first and second arms. The first and second arms **102a-102b** extend laterally away from the curved channel **103**, and the first and second arms extend in opposite directions. The barbell pad **100** also includes a plurality of magnets **104a-104d** carried by the base **101** within the curved channel **103**, and a flexible pad **106** coupled to the base opposite to the plurality of magnets to distribute weight load from the barbell. The method comprises releasably and magnetically coupling the barbell pad **100** to the barbell **105**, and performing at least weight training exercise with the barbell pad and the barbell.

Advantageously, the barbell pad **100** is easily magnetically and releasably coupled to the barbell **105**. In a typical application, the user would releasably couple the barbell pad **100** to the barbell **105**, which is carrying a desired amount of weight. During one or more weight training exercises (e.g., a hip thrust exercise, a squat exercise, or other lift exercise using a barbell), the barbell pad **100** provides a cushion/distribution device to the user from the pressure from desired amount of weight.

Further, the magnetic coupling is secure and strong so as not to disrupt weight training exercises from the user. As will be appreciated, one common reason for users to avoid using typical barbell pads is the extra step of fitting the pad onto the barbell. The barbell pad **100** provides an approach to this issue with quick magnetic coupling. Another common reason for users to avoid using typical barbell pads is dislodging of the pad during exercises (e.g., shifting forward/backward/

4

diagonally or longitudinal sliding). The barbell pad **100** provides an approach to this issue with reliable magnetic coupling. Further, the central placement of the curved channel **103** naturally balances the weight on the barbell pad **100**.

Many modifications and other embodiments of the present disclosure will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is understood that the present disclosure is not to be limited to the specific embodiments disclosed, and that modifications and embodiments are intended to be included within the scope of the appended claims.

The invention claimed is:

1. A barbell pad comprising:

a base comprising first and second arms, and a curved channel between the first and second arms, the first and second arms extending laterally away from the curved channel, the first and second arms extending in opposite directions;

a plurality of magnets carried by the base within the curved channel and configured to be magnetically coupled to a barbell; and

a flexible pad coupled to the base opposite to the plurality of magnets to distribute weight load from the barbell.

2. The barbell pad of claim 1 wherein each of the plurality of magnets comprises a curve-shaped magnet; and wherein each of the plurality of magnets is recessed within the curved channel.

3. The barbell pad of claim 1 wherein the first and second arms are substantially parallel to each other.

4. The barbell pad of claim 1 wherein the curved channel comprises a semi-circle shaped channel; and wherein the first and second arms extend perpendicularly from ends of the semi-circle shaped channel.

5. The barbell pad of claim 1 wherein the flexible pad comprises a first end coupled to the base, and a second end opposite to the first end, the second end being curve-shaped.

6. The barbell pad of claim 1 wherein the plurality of magnets comprises first and second pairs of aligned magnets, each of the first and second pairs of aligned magnets comprises a first magnet within the curved channel adjacent to the first arm, and a second magnet within the curved channel adjacent to the second arm and aligned with the first magnet.

7. The barbell pad of claim 1 further comprising an adhesive layer between the base and the flexible pad.

8. The barbell pad of claim 1 wherein the flexible pad comprises a foam pad.

9. The barbell pad of claim 1 wherein the base comprises a polymer plastic material.

10. A barbell pad comprising:

a base comprising first and second arms, and a semi-circle shaped channel between the first and second arms, the first and second arms extending laterally away from the semi-circle shaped channel, the first and second arms extending in opposite directions and being substantially parallel to each other;

a plurality of curve-shaped magnets carried by the base within the semi-circle shaped channel and configured to be magnetically coupled to a barbell, each of the plurality of curve-shaped magnets being recessed within the semi-circle shaped channel; and

a flexible pad coupled to the base opposite to the plurality of curve-shaped magnets to distribute weight load from the barbell.

## 5

11. The barbell pad of claim 10 wherein the first and second arms extend perpendicularly from ends of the semi-circle shaped channel.

12. The barbell pad of claim 10 wherein the flexible pad comprises a first end coupled to the base, and a second end opposite to the first end, the second end being curve-shaped.

13. The barbell pad of claim 10 wherein the plurality of magnets comprises first and second pairs of aligned magnets, each of the first and second pairs of aligned magnets comprises a first magnet within the semi-circle shaped channel adjacent to the first arm, and a second magnet within the semi-circle shaped channel adjacent to the second arm and aligned with the first magnet.

14. The barbell pad of claim 10 further comprising an adhesive layer between the base and the flexible pad.

15. The barbell pad of claim 10 wherein the flexible pad comprises a foam pad; and wherein the base comprises a polymer plastic material.

16. A method for making a barbell pad comprising:  
Forming a base comprising first and second arms, and a curved channel between the first and second arms, the first and second arms extending laterally away from the curved channel, the first and second arms extending in opposite directions;

## 6

positioning a plurality of magnets carried by the base within the curved channel and configured to be magnetically coupled to a barbell; and

coupling a flexible pad to the base opposite to the plurality of magnets to distribute weight load from the barbell.

17. The method of claim 16 wherein each of the plurality of magnets comprises a curve-shaped magnet; and wherein each of the plurality of magnets is recessed within the curved channel.

18. The method of claim 16 wherein the first and second arms are substantially parallel to each other.

19. The method of claim 16 wherein the curved channel comprises a semi-circle shaped channel; and wherein the first and second arms extend perpendicularly from ends of the semi-circle shaped channel.

20. The method of claim 16 wherein the flexible pad comprises a first end coupled to the base, and a second end opposite to the first end, the second end being curve-shaped; and wherein the plurality of magnets comprises first and second pairs of aligned magnets, each of the first and second pairs of aligned magnets comprises a first magnet within the curved channel adjacent to the first arm, and a second magnet within the curved channel adjacent to the second arm and aligned with the first magnet.

\* \* \* \* \*