

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261039

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

PURNHAGEN; Heiko et al.

METHOD AND APPARATUS FOR AUDIO DECODING BASED ON DEQUANTIZATION OF QUANTIZED PARAMETERS

Abstract

The present disclosure provides methods, devices and computer program products for non-uniform quantization of parameters. The disclosure further relates to a method and apparatus for reconstructing an audio object in an audio decoding system taking the non-uniformly quantized parameters into account. According to the disclosure, such an approach renders it possible to reduce bit consumption without substantially reducing the quality of the reconstructed audio object.

Inventors: PURNHAGEN; Heiko (Sundbyberg, SE), EKSTRAND; Per (Saltsjobaden, SE)

Applicant: Dolby International AB (Dublin, IE)

Family ID: 1000008563586

Assignee: DOLBY INTERNATIONAL AB (Dublin, IE)

Appl. No.: 19/023373

Filed: January 16, 2025

Related U.S. Application Data

parent US continuation 18503083 20231106 parent-grant-document US 12213004 child US 19023373

parent US continuation 17711191 20220401 parent-grant-document US 11838798 child US 18503083

parent US continuation 16905920 20200619 parent-grant-document US 11297533 child US 17711191

parent US continuation 14916534 20160303 parent-grant-document US 9672837 WO continuation PCT/EP2014/069040 20140908 child US 15584534

parent US division 16454649 20190627 parent-grant-document US 10694424 child US 16905920

parent US division 16101220 20180810 parent-grant-document US 10383003 child US 16454649

Publication Classification

Int. Cl.: **H04W28/06** (20090101); **G10L19/008** (20130101); **G10L19/035** (20130101);
G10L19/038 (20130101); **H04S1/00** (20060101); **H04W28/02** (20090101)

U.S. Cl.:

CPC **H04W28/065** (20130101); **G10L19/008** (20130101); **G10L19/035** (20130101);
H04S1/007 (20130101); **H04W28/0215** (20130101); **G10L19/038** (20130101);
H04S2420/03 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/503,083, filed on Nov. 6, 2023, which is a continuation of U.S. patent application Ser. No. 17/711,191, filed on Apr. 1, 2022, now U.S. Pat. No. 11,838,798, which is a continuation of U.S. patent application Ser. No. 16/905,920, filed on Jun. 19, 2020, now U.S. Pat. No. 11,297,533, which is a divisional of U.S. patent application Ser. No. 16/454,649, filed Jun. 27, 2019, now U.S. Pat. No. 10,694,424, which is a divisional of U.S. patent application Ser. No. 16/101,220, filed Aug. 10, 2018, now U.S. Pat. No. 10,383,003, which is a divisional of U.S. patent application Ser. No. 15/584,534, filed May 2, 2017, now U.S. Pat. No. 10,057,808, which is a continuation of U.S. patent application Ser. No. 14/916,534, filed Mar. 3, 2016, now U.S. Pat. No. 9,672,837, which is the United States National Stage Entry of PCT/EP2014/069040, filed Sep. 8, 2014, which claim the benefit of U.S. Provisional Application No. 61/877,166, filed Sep. 12, 2013, each of which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

[0002] The disclosure herein generally relates to audio coding. In particular, it relates to perceptually optimized quantization of parameters used in a system for parametric spatial coding of audio signals.

BACKGROUND

[0003] The performance of low bit audio coding systems can be significantly improved for stereo signals when a parametric stereo (PS) coding tool is employed. In such a system, a mono signal is typically quantized and conveyed using a State-of-the-Art audio coder and stereo parameters are estimated and quantized in the encoder and added as side information to the bit stream. In the decoder, the stereo signal is reconstructed from the decoded mono signal with help of stereo parameters.

[0004] There are several possible parametric stereo coding variants. Accordingly, there are several encoder types and, in addition to a mono downmix, they generate different stereo parameters that are embedded in the generated bit stream. Tools for such coding have also been standardized. An example of such a standard is MPEG-4 Audio (ISO/IEC 14496-3).

[0005] The main idea behind audio coding systems in general and parametric stereo coding in particular, and one of the several challenges of this technical field is to minimize the amount of information that has to be transferred in the bit stream from an encoder to a decoder while still obtaining a good audio quality. A high level of compression of the bit stream information may lead to unacceptable sound quality either because of complex and insufficient calculation processes or

because information has been lost in the compression process. A low level of compression of the bit stream information may on the other hand lead to capacity problems which also may result in unacceptable sound quality.

[0006] Accordingly, there is a need for improved parametric stereo coding methods.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] In what follows, example embodiments will be described in greater detail and with reference to the accompanying drawings, in which:

[0008] FIG. 1 discloses a block diagram of a parametric stereo encoding and decoding system in accordance with an example embodiment;

[0009] FIG. 2 shows a block diagram relating to processing of stereo parameters in encoding part of the parametric stereo encoding system of FIG. 1;

[0010] FIG. 3 presents a block diagram relating to processing of stereo parameters in the decoding part of the parametric stereo encoding system of FIG. 1;

[0011] FIG. 4 shows the value of a scaling factor s as a function of one of the stereo parameters;

[0012] FIG. 5 discloses non-uniform and uniform quantizers (fine and coarse) in the (a, b)-plane, where a and b are stereo parameters; and

[0013] FIG. 6 presents a diagram showing average parametric stereo bit consumption for examples of uniform fine, and uniform coarse quantization, compared with non-uniform fine and non-uniform coarse quantization in accordance with an example embodiment.

[0014] FIG. 7 discloses a block diagram of a parametric multichannel encoding and decoding system in accordance with another example embodiment.

[0015] All the figures are schematic and generally only show parts which are necessary in order to elucidate the disclosure, whereas other parts may be omitted or merely suggested. Unless otherwise indicated, like reference numerals refer to like parts in different figures.

DETAILED DESCRIPTION

[0016] In view of the above it is an object to provide encoders, decoders, systems comprising encoders and decoders, and associated methods which provide an increased efficiency and quality of the coded audio signal.

I. Overview—Encoder

[0017] According to a first aspect, example embodiments propose encoding methods, encoders, and computer products for encoding. The proposed methods, encoders and computer program products may generally have the same features and advantages.

[0018] According to example embodiments, there is provided a method in an audio encoder for quantization of parameters relating to parametric spatial coding of audio signals, comprising: receiving at least a first parameter and a second parameter to be quantized; quantizing the first parameter based on a first scalar quantization scheme having non-uniform step-sizes to obtain a quantized first parameter, wherein the non-uniform step-sizes are selected such that smaller step-sizes are used for ranges of the first parameter where the human sound perception is most sensitive, and larger step-sizes are used for ranges of the first parameter where the human sound perception is less sensitive; dequantizing the quantized first parameter using the first scalar quantization scheme to obtain a dequantized first parameter being an approximation of the first parameter; accessing a scaling function which maps values of the dequantized first parameter on scaling factors which increase with the step-sizes corresponding to the values of the dequantized first parameter, and determining a scaling factor by subjecting the dequantized first parameter to the scaling function; and quantizing the second parameter based on the scaling factor and a second scalar quantization scheme having non-uniform step-sizes to obtain a quantized second parameter.

[0019] The method is based on the understanding that human sound perception is not homogenous. Instead, it turns out that human sound perception is higher regarding some sound characteristics and lower for other sound characteristics. This implies that human sound perception is more sensitive for some values of parameters relating to parametric spatial coding of audio signals than for other such values. According to the provided method, a first such parameter is quantized in non-uniform step-sizes such that smaller step-sizes are used where human sound perception is most sensitive and larger step-sizes are used where the human sound perception is less sensitive. By quantizing using such non-uniform step-size schemes it is possible to reduce average parametric stereo bit consumption without reducing the perceptible sound quality.

[0020] According to embodiments, the scaling function of the method is a piecewise linear function.

[0021] According to embodiments, the method step of quantizing the second parameter is based on the scaling factor and the second scalar quantization scheme comprises dividing the second parameter by the scaling factor prior to subjecting the second parameter to quantization in accordance with the second scalar quantization scheme.

[0022] According to an alternative embodiment of the method, the non-uniform step-sizes of the second scalar quantization scheme are scaled by the scaling factor prior to quantization of the second parameter.

[0023] According to embodiments of the method, the non-uniform step-sizes of the second scalar quantization scheme increase with the value of the second parameter.

[0024] According to embodiments of the method, the first scalar quantization scheme comprises more quantization steps than the second scalar quantization scheme.

[0025] According to embodiments of the method, the first scalar quantization scheme is constructed by offsetting, mirroring and concatenating the second scalar quantization scheme.

[0026] According to embodiments of the method, the largest step-size of the first and/or second scalar quantization scheme is approximately four times larger than the smallest step-size of the first and/or second scalar quantization scheme.

[0027] According to example embodiments, there is provided a computer-readable medium comprising computer code instructions adapted to carry out any method of the first aspect when executed on a device having processing capability.

[0028] According to example embodiments there is provided an audio encoder for quantization of parameters relating to parametric spatial coding of audio signals, comprising: a receiving component arranged to receive at least a first parameter and a second parameter to be quantized; a first quantizing component arranged downstreams of the receiving component configured to quantize the first parameter based on a first scalar quantization scheme having non-uniform step-sizes to obtain a quantized first parameter, wherein the non-uniform step-sizes are selected such that smaller step-sizes are used for ranges of the first parameter where the human sound perception is most sensitive, and larger step-sizes are used for ranges of the first parameter where the human sound perception is less sensitive; a dequantizing component configured to receive the first quantized parameter from the first quantizing component, and to dequantize the quantized first parameter using the first scalar quantization scheme to obtain a dequantized first parameter being an approximation of the first parameter; a scaling factor determining component configured to receive the dequantized first parameter, access a scaling function which maps values of the dequantized first parameter on scaling factors which increase with the step-sizes corresponding to the values of the dequantized first parameter, and determine a scaling factor by subjecting the dequantized first parameter to the scaling function; and a second quantizing component configured to receive the second parameter and the scaling factor, and quantize the second parameter based on the scaling factor and a second scalar quantization scheme having non-uniform step-sizes to obtain a quantized second parameter.

II. Overview—Decoder

[0029] According to a second aspect, example embodiments propose decoding methods, decoders, and computer program products for decoding. The proposed methods, decoders and computer program products may generally have the same features and advantages.

[0030] Advantages regarding features and setups as presented in the overview of the encoder above may generally be valid for the corresponding features and setups for the decoder.

[0031] According to example embodiments there is provided a method in an audio decoder for dequantization of quantized parameters relating to parametric spatial coding of audio signals, comprising: receiving at least a first quantized parameter and a second quantized parameter; dequantizing the quantized first parameter according to a first scalar quantization scheme having non-uniform step-sizes to obtain a dequantized first parameter, wherein the non-uniform step-sizes are selected such that smaller step-sizes are used for ranges of the first parameter where the human sound perception is most sensitive, and larger step-sizes are used for ranges of the first parameter where the human sound perception is less sensitive; [0032] accessing a scaling function which maps values of the dequantized first parameter on scaling factors which increase with the step-sizes corresponding to the values of the dequantized first parameter, and determining a scaling factor by subjecting the dequantized first parameter to the scaling function; and dequantizing the second quantized parameter based on the scaling function and a second scalar quantization scheme having non-uniform step-sizes to obtain a dequantized second parameter.

[0033] According to example embodiments of the method, the scaling function is a piecewise linear function.

[0034] According to an embodiment, the step of dequantizing the second parameter based on the scaling factor and the second scalar quantization scheme comprises dequantizing the second quantized parameter in accordance with the second scalar quantization scheme and multiplying the result thereof by the scaling factor.

[0035] According to an alternative embodiment, the non-uniform step-sizes of the second scalar quantization scheme are scaled by the scaling factor prior to dequantization of the second quantized parameter.

[0036] According to further embodiments, the non-uniform step-size of the second scalar quantization scheme increases with the value of the second parameter.

[0037] According to an embodiment, the first scalar quantization scheme comprises more quantization steps than the second scalar quantization scheme.

[0038] According to an embodiment, the first scalar quantization scheme is constructed by offsetting, mirroring and concatenating the second scalar quantization scheme.

[0039] According to an embodiment, the largest step-size of the first and/or second scalar quantization scheme is approximately four times larger than the smallest step-size of the first and/or second scalar quantization scheme.

[0040] According to example embodiments, there is provided a computer-readable medium comprising computer code instructions adapted to carry out the method of any method of the second aspect when executed by a device having processing capability.

[0041] According to example embodiments, there is provided an audio decoder for dequantization of quantized parameters relating to parametric spatial coding of audio signals, comprising: a receiving component configured to receive at least a first quantized parameter and a second quantized parameter; a first dequantizing component arranged downstreams of the receiving component and configured to dequantize the quantized first parameter according to a first scalar quantization scheme having non-uniform step-sizes to obtain a dequantized first parameter, wherein the non-uniform step-sizes are selected such that smaller step-sizes are used for ranges of the first parameter where the human sound perception is most sensitive, and larger step-sizes are used for ranges of the first parameter where the human sound perception is less sensitive; a scaling factor determining component configured to receive the dequantized first parameter from the first dequantizing component, access a scaling function which maps values of the dequantized first

parameter on scaling factors which increase with the step-sizes corresponding to the values of the dequantized first parameter, and determine a scaling factor by subjecting the dequantized first parameter to the scaling function; and a second dequantizing component configured to receive the scaling factor and the second quantized parameter, and dequantize the second quantized parameter based on the scaling factor and a second scalar quantization scheme having non-uniform step-sizes to obtain a dequantized second parameter.

[0042] According to example embodiments, there is provided methods, apparatus and systems for dequantization of quantized parameters relating to decoding of audio signals. At least a first quantized parameter and a second quantized parameter are received. The quantized first parameter is dequantized according to a first scalar quantization scheme having first non-uniform step-sizes to obtain a dequantized first parameter. The first non-uniform step-sizes are selected such that smaller step-sizes are used for ranges of the first parameter where the human sound perception is most sensitive, and larger step-sizes are used for ranges of the first parameter where the human sound perception is less sensitive. A scaling factor is determined based on the dequantized first parameter. The second quantized parameter is dequantized based on a second quantization scheme having second non-uniform step-sizes to obtain a dequantized second parameter. The second quantization scheme is one of a scalar quantization scheme or a vector quantization scheme.

III. Overview—an Audio Encoding/Decoding System

[0043] According to a third aspect, example embodiments propose decoding/encoding systems comprising an encoder according to the first aspect and a decoder according to the second aspect.

[0044] Advantages regarding features and setups as presented in the overview of the encoder and decoder above may generally be valid for the corresponding features and setups for the system.

[0045] According to example embodiments there is provided such a system wherein the audio encoder is arranged to transmit the first and second quantized parameters to the audio decoder.

IV. Example Embodiments

[0046] The disclosure herein discusses perceptually optimized quantization of parameters used in a system for parametric spatial coding of audio signals. In the examples considered below, the special case of parametric stereo coding for 2-channel signals is discussed. The same technique can also be used in parametric multichannel coding, e.g. in a system operating in 5-3-5 mode. An example embodiment of such a system is outlined in FIG. 7 and will be briefly discussed below. The example embodiments presented here relate to simple non-uniform quantization allowing reduction of the bit rate needed for conveying these parameters without affecting the perceived audio quality, and further allowing continued use of established entropy coding techniques for scalar parameters (like time- or frequency-differential coding followed by Huffman coding).

[0047] FIG. 1 shows a block diagram of an embodiment of a parametric stereo encoding and decoding system **100** discussed here. A stereo signal comprising a left channel **101** (L) and a right channel **102** (R) is received by the encoder part **110** of the system **100**. The stereo signal is sent as input to an “Advanced Coupling” (ACPL) encoder **112** generating a mono down mix **103** (M) and stereo parameters a (referred to in FIG. 1 as **104a**) and b (referred to in FIG. 1 as **104b**).

Furthermore, the encoder part **110** comprises a downmix encoder **114** (DMX Enc) transforming the mono down mix **103** to a bit stream **105**, a stereo parameter quantization means **116** (Q) generating a stream of quantized stereo parameters **106**, and a multiplexer **118** (MUX) that generates the final bit stream **108** that also comprises the quantized stereo parameters that is conveyed to the decoder part **120**. The decoder part **120** comprises a de-multiplexer **122** (DE-MUX) which receives the incoming final bit stream **108** and regenerates the bit stream **105** and the stream of quantized stereo parameters **106**, a downmix decoder **124** (DMX Dec) which receives the bit stream **105** and outputs a decoded mono downmix **103'** (M'), a stereo parameter dequantization means **126** (Q') which receives a stream of quantized stereo parameters **106** and outputs dequantized stereo parameters a' **104a'** and b' **104b'**, and finally the ACPL decoder **128** that receives the decoded mono downmix **103'** and the dequantized stereo parameters **104a'**, **104b'** and transforms these incoming signals into

reconstructed stereo signals **101'** (L') and **102'** (R').

[0048] Starting from incoming stereo signals **101** (L) and **102** (R) the ACPL encoder **112** computes a mono downmix **103** (M) and a side signal(S) according to following equations:

[00001] $M = (L + R) / 2$ (equation1) $S = (L - R) / 2$ (equation2)

[0049] Stereo parameters a and b are computed in a time- and frequency-selective manner, i.e. for each time/frequency tile, typically with help of a filterbank like a QMF bank and using a non-uniform grouping of QMF bands to form a set of parameter bands according to a perceptual frequency scale.

[0050] In the ACPL decoder, the decoded mono downmix M' together with stereo parameters a', b' and a decorrelated version of M' (decorr(M')) are used as input to reconstruct an approximation of the side signal in accordance with the following equation:

[00002] $S' = a' * M' + b' * \text{decorr}(M')$ (equation3)

[0051] L' and R' are then computed as:

[00003] $L' = M' + S'$ (equation4) $R' = M' - S'$ (equation5)

[0052] The parameter pair (a, b) can be considered as a point in a two-dimensional (a, b)-plane.

The parameters a, b are related to the perceived stereo image, where parameter a is primarily related to the position of the perceived sound source (e.g. left or right), and where parameter b is primarily related to the size or width of the perceived sound source (small and well localized or wide and ambient). Table 1 lists a few typical examples of perceived stereo images and the corresponding values of the parameters a, b.

TABLE-US-00001 TABLE 1 Parameter Point values Signal description
Left a = 1, b = 0 Signal fully panned to the left side, i.e. R = 0. Center a = 0, b = 0 Signal in phantom center, i.e. L = R. Right a = -1, b = 0 Signal fully panned to the right side, i.e. L = 0. Wide a = 0, b = 1 Wide signal, L and R are uncorrelated and have same level.

[0053] Note that b is never negative. It should also be noted that even though b and the absolute value of a often are within the range of 0 to 1, they can also have absolute values larger than 1, for example in case of strong out-of-phase components in L and R, i.e. when the correlation between L and R is negative.

[0054] The problem at hand is now to design a technique to quantize parameters a, b for transmission as side information in a parametric stereo/spatial coding system. A simple and straight-forward approach of prior art is to use uniform quantization and quantize a and b independently, i.e. to use two scalar quantizers. A typical quantization step size is delta=0.1 for fine or delta=0.2 for coarse quantization. The bottom left and right panel of FIG. 5 show the points in the (a, b) plane that can be represented by such a quantization scheme for fine and coarse quantization. Typically, the quantized parameters a and b are entropy-coded independently, using time-differential or frequency-differential coding in combination with Huffman coding.

[0055] However, the present inventors have now realized that the performance (in a rate-distortion sense) of the parameter quantization can be improved over such scalar quantization by taking perceptual aspects into account. In particular, the sensitivity of the human auditory system to small changes in the parameter values (like the error introduced by quantization) depends on the position in the (a, b) plane. Perceptual experiments investigating the audibility of such small changes or "just-noticeable differences" (JND) indicate that JNDs for a and b are substantially smaller for sound sources with a perceived stereo image that is represented by the points (1, 0) and (-1, 0) in the (a, b)-plane. Hence, a uniform quantization of a and b can be too coarse (with audible artifacts) for the regions close to (1, 0) and (-1, 0) and unnecessary fine (causing an unnecessarily high side information bit rate) in other regions, such as around (0, 0) and (0, 1). It would of course be possible to consider a vector quantizer for (a, b) to achieve joint and non-uniform quantization of the stereo parameters a and b. However, a vector quantizer is computationally more complex, and also the entropy coding (time- or frequency-differential) would have to be adapted and would

become more complex as well.

[0056] Accordingly, a novel non-uniform quantization scheme for the parameters a and b is introduced in this application. The non-uniform quantization scheme for a and b exploits position-dependent JNDs (like a vector quantizer could do) but it can be implemented as a small modification to the prior art uniform and independent quantization of a and b. Furthermore, also the prior art time- or frequency-differential entropy coding can remain basically unchanged. Only Huffman code books need to be updated to reflect changes in index ranges and symbol probabilities.

[0057] The resulting quantization scheme is shown in FIGS. 2 and 3, where FIG. 2 relates to the stereo parameter quantization means **116** of the encoder part **110** and FIG. 3 relates to the stereo parameter dequantization means **126** of the decoder part **120**. The stereo parameter quantization scheme starts by applying a non-uniform scalar quantization to parameter a (referred to as **104a** in FIG. 2) in quantizing means Q.sub.a (referred to as **202** in FIG. 2). The quantized parameter **106a** is forwarded to the multiplexer **118**. The quantized parameter is also dequantized directly in dequantization means Q.sub.a.sup.-1 (referred to as **204** in FIG. 2) to parameter a'. As quantized parameter **106a** is dequantized to a' (referred to as **104a'** in FIG. 3) in the decoder part **120** too, a' will be identical in both the encoder part **110** and the decoder part **120** of the system **100**. Then, a' is used to compute a scaling factor s (carried out by scaling means **206**) that is used to make the quantization of b dependent on the actual value of a. The parameter b (referred to as **104b** in FIG. 2) is divided by this scaling factor s (carried out by inversion means **208** and multiplying means **210**) and then sent to another non-uniform scalar quantizer Q.sub.b (referred to as **212** in FIG. 2) from which the quantized parameter **106b** is forwarded. The process is partially reversed in stereo parameter dequantizing means **126** shown in FIG. 3. Incoming quantized parameters **106a** and **106b** are dequantized in dequantizing means Q.sub.a.sup.-1 (referred to in FIG. 3 as **304**) and Q.sub.b.sup.-1 (referred to in FIG. 3 as **308**) to a' (referred to **104a'** in FIG. 3) and b' previously divided with scaling factor s in the encoder part **110**. Scaling means **306** determines the scaling factor s based upon the dequantized parameter a' (**104a**) in the same way as scaling means **206** in the encoder part **110**. The scaling factor is then multiplied with the result of the dequantization of quantized parameter **106b** in multiplying means **310** and dequantized parameter b' (referred to as **104b'** in FIG. 3) is obtained. Accordingly, the dequantization of a and the computation of the scaling factor is implemented in both the encoder part **110** and the decoder part **120**, ensuring that exactly the same value of s is used for encoding and decoding of b.

[0058] The non-uniform quantization for a and b is based upon a simple non-uniform quantizer for values in the range of 0 to 1 where the quantization step size for values around 1 is approximately four times that of the quantization step size for values around 0, and where the quantization step size increases with the value of the parameter. For example, the quantization step size can increase approximately linearly with the index identifying the corresponding dequantized value. For a quantizer with 8 intervals (i.e. 9 indicies), the following values can be obtained, where the quantization step size is the difference between two neighboring dequantized values.

TABLE-US-00002 TABLE 2 Dequantized values within the range of 0 to 1

Index	Value
0	0.0594
1	0.1375
2	0.2344
3	0.3500
4	0.4844
5	0.6375
6	0.8094
7	1.0000

[0059] This table is an example of a quantization scheme that could be used for dequantizing means Q.sub.b.sup.-1 (referred to as **308** in FIG. 3). However, a larger range of values must be handled for parameter a. An example of a quantization scheme for dequantizing means Q.sub.a.sup.-1 (referred to as **304** in FIG. 3) could simply be constructed by mirroring and concatenating the non-uniform quantization intervals shown in table 2 above to give a quantizer that can represent values in the range of -2 to 2, where the quantization step size for values around -2, 0, and 2 is approximately four times that of the quantization step size for values around -1 and 1. The resulting values are shown in table 3 below.

TABLE-US-00003 TABLE 3 Dequantized values within the range of -2 to 2

Index	Value
0	-2.000

1 -1.8094 2 -1.6375 3 -1.4844 4 -1.3500 5 -1.2344 6 -1.1375 7 -1.0594 8 -1.000 9 -0.9406 10
-0.8625 11 -0.7656 12 -0.6500 13 -0.5156 14 -0.3625 15 -0.1906 16 0 17 0.1906 18 0.3625 19
0.5156 20 0.6500 21 0.7656 22 0.8625 23 0.9406 24 1.000 25 1.0594 26 1.1375 27 1.2344 28
1.3500 29 1.4844 30 1.6375 31 1.8094 32 2.000

[0060] FIG. 4 shows the value of the scaling factor s as a function of a . It is a piecewise linear function, with $s=1$ (i.e. no scaling) for $a=-1$ and $a=1$ and $s=4$ (4 times coarser quantization of b) for $a=-2$, $a=0$ and $a=2$. It is pointed out that the function of FIG. 4 is an example and that other such functions are theoretically possible. The same reasoning is applicable to the quantization schemes.

[0061] The resulting non-uniform quantization of a and b is shown in the top left panel of FIG. 5, where each point in the (a, b) plane that can be represented by this quantizer is marked by a cross. Around the most sensitive points $(1, 0)$ and $(-1, 0)$, the quantization step size for both a and b is approximately 0.06, while it is approximately 0.2 for a and b around $(0, 0)$. Hence, the quantization steps are much more adapted to the JNDs than those of a uniform scalar quantization of a and b .

[0062] If coarser quantization would be desired, it is possible to simply drop every second dequantized value of the non-uniform quantizers, thereby doubling the quantization step sizes.

Table 4 shows the following coarse non-uniform quantizers for parameter b and the non-uniform quantizers for parameter a are obtained analogous to what has been shown above.

TABLE-US-00004 TABLE 4 Dequantized values for coarser quantization within the range of 0 to 1:

Index	Value
0	0
1	0.1375
2	0.3500
3	0.6375
4	1.000

[0063] The scaling function shown in FIG. 4 remains unchanged for coarse quantization, and the resulting coarse quantizer for (a, b) is shown in the top right panel of FIG. 5. Such coarse quantization can be desirable if the coding system is operated at very low target bit rates, where it can be advantageous to spend the bits saved by coarser quantization of the stereo parameters on coding the mono downmix signal M (referred to as **103** in FIG. 1) instead.

[0064] The difference in efficiency between a non-uniform and a uniform quantization of the stereo parameters a and b is demonstrated in FIG. 6. The differences are shown for a fine and a coarse quantization. The average bit consumption per second corresponding to 11 hours of music is shown. It can be concluded from the figure that the bit consumption for non-uniform quantization is substantially lower than for uniform quantization. Furthermore, it can be concluded that coarser non-uniform quantization reduces bit consumption per second more than coarser uniform quantization does.

[0065] Finally, a block diagram an example embodiment of a 5-3-5 parametric multichannel encoding and decoding system **700** is disclosed in FIG. 7. A multichannel signal comprising a left front channel **701**, a left surround channel **702**, a center front channel **703**, a right front channel **704** and a right surround channel **705** is received by the encoder part **710** of the system **700**. The signals of left front channel **701** and the left surround channel **702** are sent as input to a first “Advanced coupling” (ACPL) encoder **712** generating a left down mix **706** and stereo parameters $a_{\text{sub.L}}$ (referred to as **708a**) and $b_{\text{sub.L}}$ (referred to as **708b**). Similarly, the signals of right front channel **704** and the right surround channel **705** are sent as input to a second “Advanced coupling” (ACPL) encoder **713** generating a right down mix **707** and stereo parameters $a_{\text{sub.R}}$ (referred to as **709a**) and $b_{\text{sub.R}}$ (referred to as **709b**). Furthermore, the encoder part **710** comprises a 3-channel downmix encoder **714** transforming the signals of left downmix **706**, the center front channel **703** and the right downmix **707** to a bit stream **722**, a first stereo parameter quantization means **715** generating a first stream of quantized stereo parameters **720** based stereo parameters **708a** and **708b**, a second stereo parameter quantization means **716** generating a second stream of quantized stereo parameters **724** based on stereo parameters **709a** and **709b**, and a multiplexer **730** that generates the final bit stream **735** that also comprises the quantized stereo parameters that is conveyed to the decoder part **740**. The decoder part **740** comprises a de-multiplexer **742** which receives the incoming final bit stream **735** and regenerates the bit stream **722**, the first stream of quantized stereo parameters **720** and the second stream of quantized stereo parameters **724**. The

first stream of quantized stereo parameters **720** is received by a first stereo parameter dequantization means **745** which outputs dequantized stereo parameters **708a'** and **708 b'**. The second stream of quantized stereo parameters **724** is received by second stereo parameter dequantization means **746** which outputs dequantized stereo parameters **709a'** and **709b'**. The bit stream **722** is received by 3-channel downmix decoder **744** which outputs regenerated left down mix **706'**, reconstructed center front channel **703'** and regenerated right downmix **707'**. A first ACPL decoder **747** receives dequantized stereo parameters **708a'** and **708b'** as well as regenerated left downmix **706'** and outputs reconstructed left front channel **701'**, and reconstructed left surround channel **702'**. Similarly, a second ACPL decoder **748** receives dequantized stereo parameters **709a'**, **709b'**, and regenerated right downmix **707'** and outputs reconstructed right front channel **704'** and reconstructed right surround channel **705'**.

EQUIVALENTS, EXTENSION, ALTERNATIVES AND MISCELLANEOUS

[0066] Further embodiments of the present disclosure will become apparent to a person skilled in the art after studying the description above. Even though the present description and drawings disclose embodiments and examples, the disclosure is not restricted to these specific examples. Numerous modifications and variations can be made without departing from the scope of the present disclosure, which is defined by the accompanying claims. Any reference signs appearing in the claims are not to be understood as limiting their scope.

[0067] Additionally, variations to the disclosed embodiments can be understood and effected by the skilled person in practicing the disclosure, from a study of the drawings, the disclosure, and the appended claims. In the claims, the word “comprising” does not exclude other elements or steps, and the indefinite article “a” or “an” does not exclude a plurality. The mere fact that certain measures are recited in mutually different dependent claims does not indicate that a combination of these measures cannot be used to advantage.

[0068] The systems and methods disclosed herein above may be implemented as software, firmware, hardware, or a combination thereof. In a hardware implementation, the division of tasks between functional units referred to in the above description does not necessarily correspond to the division into physical units; to the contrary, one physical component may have multiple functionalities, and one task may be carried out by several physical components in cooperation. Certain components or all components may be implemented as software executed by a digital signal processor or microprocessor, or be implemented as hardware or as an application-specific integrated circuit. Such software may be distributed on computer-readable media, which may comprise computer storage media (or non-transitory media) and communication media (or transitory media). As is well known to a person skilled in the art, the term computer storage media includes both volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information such as computer-readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile discs (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic disk storage devices, or any other medium which can be used to store the desired information and which can be accessed by a computer. Further, it is well-known to the skilled person that communication media typically embodies computer-readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any information delivery media.

Claims

1. A method in an audio decoder for dequantization of quantized parameters relating to parametric spatial coding of audio signals, comprising: receiving at least a first quantized parameter and a second quantized parameter; dequantizing the quantized first parameter according to a first scalar

quantization scheme having non-uniform step-sizes to obtain a dequantized first parameter, wherein the non-uniform step-sizes are selected; accessing a scaling function which maps at least a value of the dequantized first parameter on scaling factors which increase with the step-sizes corresponding to the values of the dequantized first parameter, and determining a scaling factor by subjecting the dequantized first parameter to the scaling function; and dequantizing the second quantized parameter based on the scaling factor and a second scalar quantization scheme having non-uniform step-sizes to obtain a dequantized second parameter.
