

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385527
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Capoldi; Bruno et al.

Bearing with at least one segmented ring

Abstract

A bearing provides an outer ring and an inner ring capable of rotating concentrically relative to one another, at least one of the inner and outer rings being split into a plurality of successive circumferential ring segments. For each pair of facing ends of adjacent successive ring segments of the split-ring, one of the facing ends includes at least one protrusion made in one part with the associated ring segment and protruding into a recess of complementary shape formed onto the other facing end to align the pair of facing ends in radial direction.

Inventors: Capoldi; Bruno (Charentenay, FR), Ragot; David (Guillon, FR), Bertrand; David (Vermenton, FR)

Applicant: Aktiebolaget SKF (Gothenburg, SE)

Family ID: 1000008751962

Assignee: Aktiebolaget SKF (Gothenburg, SE)

Appl. No.: 18/442817

Filed: February 15, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240183403 A1	Jun. 06, 2024

Foreign Application Priority Data

DE	102021208342.0	Aug. 02, 2021
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc US 17877130 20220729 US 11905996 child-doc US 18442817

Publication Classification

Int. Cl.: F16C33/60 (20060101); F16C33/58 (20060101)

U.S. Cl.:

CPC F16C33/60 (20130101); F16C33/586 (20130101); F16C2226/76 (20130101); F16C2300/14 (20130101)

Field of Classification Search

CPC: F16C (19/381); F16C (33/504); F16C (33/586); F16C (33/60); F16C (2226/60); F16C (2226/62); F16C (2226/70); F16C (2226/76); F16C (2300/14); F16C (2360/31)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5657526	12/1996	Yatcko	29/898.04	F16C 13/04
8819939	12/2013	Pohlman	29/898.063	F16C 33/60
2009/0123104	12/2008	Abe	384/570	F16C 33/4605
2015/0275970	12/2014	Terada	384/560	F16C 43/06
2017/0074321	12/2016	Rittmann	N/A	F16C 33/128
2021/0131490	12/2020	Dondaine	N/A	F16C 19/545

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
02304216	12/1989	JP	N/A
2521914	12/1996	JP	N/A
2007292305	12/2006	JP	N/A

OTHER PUBLICATIONS

Machine Translation of JP-2521914-Y2 (Year: 1997). cited by examiner
Machine Translation of JP H02-304216 (Year: 1990). cited by examiner

Primary Examiner: Waits; Alan B

Attorney, Agent or Firm: GARCIA-ZAMOR INTELLECTUAL PROPERTY LAW, LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims priority to U.S. patent application Ser. No. 17/877,130, filed Jul. 29, 2022, which claims priority to German Patent Application no. 102021208342.0, filed Aug. 2, 2021, the contents of which is fully incorporated herein by reference.

TECHNICAL FIELD OF THE INVENTION

(2) The present invention relates to the field of bearings. The invention notably relates to the field

of large diameter rolling bearings that can accommodate axial and radial loads and having an inner ring and an outer ring arranged concentrically about an axis of rotation running in an axial direction.

BACKGROUND OF THE INVENTION

(3) Such large diameter rolling bearings may be used for example in a tunnel boring machine, in a mining extraction machine or in a wind turbine. Large diameter rolling bearings may also be used in the field of defence such as radars or chars.

(4) A large diameter rolling bearing comprises generally two concentric inner and outer rings, and at least one row of rolling elements, such as rollers, radially interposed between the rings.

(5) In some fields of applications, the rolling bearing is delivered with inner and outer rings formed as split rings in order to allow the transport and/or the assembly on the corresponding machine. In such case, each of the inner and outer rings is split into a plurality of successive circumferential ring segments.

(6) Therefore, after delivery, the ring segments must be joined together to assemble each split-ring.

(7) However, during assembly, the ring segments may not be aligned in the radial direction. In this case, the assembly process of the rolling bearing is interrupted until the ring segments are disassembled and then realigned.

(8) This adjustment step may be laborious, interrupts the assembly process and leads to increased costs of the overall rolling bearing.

(9) One aim of the present invention is to overcome these drawbacks.

SUMMARY OF THE INVENTION

(10) The invention relates to a bearing comprising an outer ring and an inner ring capable of rotating concentrically relative to one another, at least one of the inner and outer rings being split into a plurality of successive circumferential ring segments.

(11) According to a general feature, for each pair of facing ends of adjacent successive ring segments of the split-ring, one of the facing ends comprises at least one protrusion made in one part with the associated ring segment and protruding into a recess of complementary shape formed onto the other facing end to align the pair of facing ends in radial direction.

(12) With such an arrangement, the ring segments of the split ring may be easily and perfectly aligned in the radial direction during assembly. The use of such protrusion and recess facilitates the assembly and avoids disassembling the split ring in cases where the alignment of the ring segments is not perfect. The overall costs can be reduced, and the process may be facilitated.

(13) Advantageously, the protrusion extends in the circumferential direction from the facing end.

(14) Preferably, the protrusion is delimited in radial direction by two lateral flat trapezoidal leg faces. This leads to facilitate the assembly of the ring segments of the split ring.

(15) The protrusion may comprise a flat outer face connected to the lateral flat trapezoidal leg faces and extending radially.

(16) In one embodiment, each pair of adjacent successive ring segments of the split-ring is secured together with at least one fixing plate, the fixing plate being disposed inside first, and second grooves respectively provided on frontal faces of the ring segments, the fixing plate being set back or flush with at least the face of each of the ring segments from which the first or second groove is formed.

(17) Accordingly, the fixing plate do not protrude with respect to this frontal face of each ring segment provided with the first or second groove. Accordingly, the overall dimension of the bearing is not increased.

(18) Preferably, the fixing plate is set back or flush with the split-ring.

(19) Advantageously, an edge radius is provided between each flat trapezoidal leg face of the protrusion and the facing end, and between each flat trapezoidal leg face and the flat outer face, and an edge radius is provided between each flat trapezoidal leg face of the recess and the other facing end, and between each flat trapezoidal leg face and a flat inner bottom of the recess.

- (20) Advantageously, the bearing further comprises at least first and second alignment members extending through the fixing plate, the first alignment member protruding into a recess formed into the thickness of one of the ring segments, and the second alignment member protruding into a recess formed into the thickness of the other of the ring segments.
- (21) Accordingly, the ring segments of the split-ring may be easily and perfectly aligned during re-assembly, for example after the transport, with regard to its initial position during fabrication. The use of alignment members inserted into recesses facilitates the re-assembly process.
- (22) Preferably, the first and second alignment members are set back or flush with an outer surface of the fixing plate which is located on the side opposite to the first and second grooves of the ring segments. For example, each of the first and second alignment members may comprise a pin.
- (23) In one embodiment, the bearing further comprises at least one first fixing screw and at least one second fixing screws extending through the fixing plate. The first fixing screw is engaged inside a threaded hole formed onto one of the ring segments, and the second fixing screw is engaged inside a threaded hole formed onto the other of the ring segments. The threaded holes may be formed from the bottom of the associated groove.
- (24) The first and second fixing screws are distinct from the first and second alignment members.
- (25) Preferably, screw heads of the first and second fixing screws are set back or flush with the outer surface of the fixing plate which is located on the side opposite to the first and second grooves of the ring segments.
- (26) In one embodiment, each pair of adjacent successive ring segments of the split-ring may be secured together with an additional fixing plate, the additional fixing plate being disposed inside third and fourth grooves provided on frontal faces of the ring segments opposite to the frontal faces onto which are formed the first and second grooves, the additional fixing plate being set back or flush with at least these frontal faces.
- (27) Otherwise, the fixing plate(s) may be made from a rigid material, such as steel. This improves the rigidity of the bearing.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) At least one of the embodiments of the present invention is accurately represented by this application's drawings which are relied on to illustrate such embodiment(s) to scale and the drawings are relied on to illustrate the relative size, proportions, and positioning of the individual components of the present invention accurately relative to each other and relative to the overall embodiment(s). Those of ordinary skill in the art will appreciate from this disclosure that the present invention is not limited to the scaled drawings and that the illustrated proportions, scale, and relative positioning can be varied without departing from the scope of the present invention as set forth in the broadest descriptions set forth in any portion of the originally filed specification and/or drawings. The present invention and its advantages will be better understood by studying the detailed description of specific embodiments given by way of non-limiting examples and illustrated by the appended drawings on which:
- (2) FIG. 1 is a partial cross-section of a rolling bearing according to a first example of the invention,
- (3) FIG. 2 is a perspective view of an outer ring of the rolling bearing of FIG. 1,
- (4) FIG. 3 is a detail view of FIG. 2,
- (5) FIG. 4 is an exploded perspective view of FIG. 3,
- (6) FIG. 5 is a partial exploded view of the outer ring of FIGS. 2 to 4 with fixing plates, and
- (7) FIG. 6 is a detail perspective view of an outer ring of a rolling bearing according to a second example of the invention.

DETAILED DESCRIPTION OF THE INVENTION

(8) Those of ordinary skill in the art will appreciate from this disclosure that when a range is provided such as (for example) an angle/distance/number/weight/volume/spacing being between one (1 of the appropriate unit) and ten (10 of the appropriate units) that specific support is provided by the specification to identify any number within the range as being disclosed for use with a preferred embodiment. For example, the recitation of a percentage of copper between one percent (1%) and twenty percent (20%) provides specific support for a preferred embodiment having two point three percent (2.3%) copper even if not separately listed herein and thus provides support for claiming a preferred embodiment having two point three percent (2.3%) copper. By way of an additional example, a recitation in the claims and/or in portions of an element moving along an arcuate path by at least twenty (20°) degrees, provides specific literal support for any angle greater than twenty (20°) degrees, such as twenty-three (23°) degrees, thirty (30°) degrees, thirty-three-point five (33.5°) degrees, forty-five (45°) degrees, fifty-two (52°) degrees, or the like and thus provides support for claiming a preferred embodiment with the element moving along the arcuate path thirty-three-point five (33.5°) degrees. The rolling bearing as illustrated on FIG. 1 is a large diameter rolling bearing comprising an outer ring **10** and an inner ring **12**. The rolling bearing may for example be used in a tunnel boring machine, a wind turbine or any other application using a large diameter rolling bearing.

(9) The outer and inner rings **10**, **12** are concentric and extend axially along the bearing rotation axis (not shown) which runs in an axial direction. The rings **10**, **12** are of the solid type.

(10) The outer ring **10** is formed as a split-ring and comprises a first ring **14** and a second ring **16** stacked one relative to the other in the axial direction. Each of the first and second rings **14**, **16** of the outer ring is provided with a plurality of aligned through-holes (not illustrated) in order to be joined by fitting bolts.

(11) As will be described later, the outer ring **14** is also formed as a split-ring in the circumferential direction.

(12) In the illustrated example, the rolling bearing comprises three rows of axial rollers **18**, **20**, **22** which are arranged between the outer and inner rings **10**, **12** in order to form an axial thrust, and a row of radial rollers **24** which are arranged between the rings to form a radial thrust.

(13) The rollers **18** to **24** of one row are identical to one another. The axis of rotation of each roller **24** is parallel to the axis of the bearing and perpendicular to the axes of each of the rollers **18**, **20** and **22**. In the illustrated example, the row of rollers **18** is superimposed on the row of rollers **20**. In the illustrated example, the diameter of the rollers **24** is smaller than the diameter of the rollers **18** to **22**.

(14) The inner ring **12** comprises an annular protruding nose **26** engaging into an annular groove **28** of the outer ring. The nose **26** extends radially outwards. The groove **28** opens in a radial direction inwardly towards the inner ring **12**.

(15) The inner ring **12** also comprises an inner cylindrical bore **12a** and a stepped outer cylindrical surface **12b** which is radially opposite to the bore **12a**. The protruding nose **26** protrudes radially from the outer cylindrical surface **12b**. The inner ring **12** further comprises two opposite radial frontal faces **12c**, **12d** which axially delimit the bore **12a** and the outer cylindrical surface **12b**.

(16) The rows of rollers **18** to **22** are arranged axially between the nose **26** of the inner ring and the groove **28** of the outer ring. The rows of rollers **18**, **20** and the row of rollers **22** are disposed on each side of the nose **26** of the inner ring.

(17) The rollers **24** are arranged radially between raceways formed on the nose **26** and the groove **28**. The row of rollers **24** is radially offset outwards with respect to the rows of rollers **18** to **22**. The row of rollers **24** is axially located between the rows of rollers **18** to **22**.

(18) The outer ring **10** comprises an inner stepped cylindrical surface or bore **10a** from which the groove **28** is formed. The outer ring **10** also comprises an outer cylindrical surface **10b** which is radially opposite to the bore **10a**. The outer ring **10** further comprises two opposite radial frontal

faces **10c**, **10d** which axially delimit the bore **10a** and the outer surface **10b** of the ring.

(19) As previously mentioned, the outer ring **10** is divided in the circumferential direction. Each of the first and second rings **14**, **16** of the outer ring is segmented. Since the designs of the two rings **14**, **16** are similar, only the ring **14** will be described here.

(20) As shown on FIG. 2, the first ring **14** of the outer ring is formed by two successive circumferential ring segments **30**, **32**. Alternatively, the first ring **14** may comprise at least three successive circumferential ring segments.

(21) Each ring segment **30**, **32** of the first ring **14** of the outer ring is provided with a first end **30a**, **32a** and with a second end **30b**, **32b** which delimit the ring segment in the circumferential direction. The first end **30a**, **32a** and the second end **30b**, **32b** of each ring segment **30**, **32** are opposite in the circumferential direction.

(22) In the illustrated example, the first ends **30a**, **32a** of the ring segments **30**, **32** face each other and abut in the circumferential direction. Similarly, the second ends **30b**, **32b** of the ring segments **30**, **32** also face each other and abut in the circumferential direction. The first ends **30a**, **32a** form a first pair of facing ends, and the second ends **30b**, **32b** form a second pair of facing ends of the ring segments **30**, **32**.

(23) The ring segments **30**, **32** forming the first ring **14** may be identical one to another. The outer cylindrical surface of each ring segment **30**, **32** delimits partly the outer surface **10b** of the outer ring. One of the frontal faces of each ring segment **30**, **32** delimits partly the frontal face **10d** of the outer ring.

(24) As shown more clearly on FIGS. 3 and 4, the first end **30a** of the ring segment **30** comprises a protrusion **34** which protrudes outwards into a recess **36** of complementary shape formed on the first end **32a** of the ring segment **32**. The protrusion **34** is made in one part with the ring segment **30**. The protrusion **34** extends in the circumferential direction from the first end **30a**. The protrusion **34** extends axially along the first end **30a**. Here, the protrusion **34** extends axially along the entire length of the first end **30a**.

(25) The protrusion **34** is provided with two opposite lateral flat trapezoidal leg faces **34a**, **34b** which axially delimit the protrusion in the radial direction. The flat trapezoidal leg faces **34a**, **34b** extend obliquely outwards in the circumferential direction from the first end **30a**. In the illustrated example, each flat trapezoidal leg face **34a**, **34b** is connected to the first end **30a** with a sharp edge. The flat trapezoidal leg faces **34a**, **34b** extends obliquely towards each other.

(26) The protrusion **34** is also provided with a flat outer face **34c** connected to the flat trapezoidal leg faces **34a**, **34b**. The outer face **34c** extends radially. The outer face **34c** is offset in the circumferential direction with respect to the first end **30a** of the ring segment **30**. In the illustrated example, each flat trapezoidal leg face **34a**, **34b** is connected to the outer face **34c** with a sharp edge.

(27) The shape of the recess **36** formed on the first end **32a** of the ring segment **32** is complementary to that of the protrusion **34** of the first end **30a** of the ring segment **30**. The recess **36** extends inwards in the circumferential direction from the first end **32a**. The recess **36** extends axially along the first end **32a**. Here, the recess **36** extends axially along the entire length of the first end **32a**.

(28) The recess **36** is provided with two opposite lateral flat trapezoidal leg faces **36a**, **36b** which axially delimit the recess in the radial direction. The flat trapezoidal leg faces **36a**, **36b** extend obliquely inwards in the circumferential direction from the first end **32a**. In the illustrated example, each flat trapezoidal leg face **36a**, **36b** is connected to the first end **32a** with a sharp edge. The flat trapezoidal leg faces **36a**, **36b** extends obliquely towards each other.

(29) The recess **36** is also provided with a flat inner bottom **36c** connected to the flat trapezoidal leg faces **36a**, **36b**. The inner bottom **36c** extends radially. The inner bottom **36c** is offset in the circumferential direction with respect to the first end **32a** of the ring segment **32**. In the illustrated example, each flat trapezoidal leg face **36a**, **36b** is connected to the inner bottom **36c** with a sharp

edge.

(30) The protrusion **34** formed on the first end **30a** of the ring segment **30** is located inside the recess **36** formed on the first end **32a** of the ring segment **32**. The protrusion **34** is entirely housed inside the recess **36**. The flat trapezoidal leg faces **34a**, **34b** of the protrusion are respectively in contact with the flat trapezoidal leg faces **34a**, **34b** of the recess **36**. The outer face **34c** of the protrusion are in contact with the inner bottom **36c** of the recess.

(31) Referring once again to FIG. 2, the second end **32b** of the ring segment **32** comprises a protrusion **34** which protrudes outwards into a recess (not referenced) formed on the second end **30b** of the ring segment **30** in order to radially align these second ends **30b**, **32b** of the ring segments **20**. The protrusion **34** of the second end **32b** of the ring segment **32** and the recess of the second end **30b** of the ring segment **30** are respectively identical to the protrusion **34** of the first end **30a** of the ring segment **30** and the recess **36** of the first end **32a** of the ring segment **32** previously described.

(32) Advantageously, the first ends **30a**, **32a** and the second ends **30b**, **32b** of the ring segments **30**, **32** are formed by an electro-erosion cutting process.

(33) In the illustrated example, the outer ring **10** is also provided with two pairs of fixing plates **40**, **42** to secure together the successive ring segments **30**, **32**. Each pair of fixing plates **40**, **42** secures together each pair of facing end portions of two successive ring segments **30**, **32**. On FIG. 5, only one pair of fixing plates **40**, **42** is visible. The number of pair of fixing plates **40**, **42** is equal to the number of successive circumferential ring segments **30**, **32**.

(34) The mounting of one pair of fixing plates **40**, **42** will be described here, it being understood that the mounting of the other pair of fixing plates **40**, **42** is identical.

(35) In order to mount the fixing plate **40** on the outer ring, first and second grooves **44**, **46** are respectively formed on the ring segments **30**, **32** of the first ring **14** of the outer ring.

(36) The grooves **44**, **46** are provided on the frontal faces of the ring segments **30**, **32** delimiting partly the frontal face **10d** of the outer ring. The groove **44** opens on the first end **30a** in the circumferential direction. The groove **46** opens on the first end **32a** in the circumferential direction. The groove **46** faces the groove **44** in the circumferential direction. In the illustrated example, the groove **46** is identical to the groove **44**. Alternatively, the grooves **44**, **46** may have different shapes and/or dimensions.

(37) As will be described later, the fixing plate **40** is entirely housed inside the grooves **44**, **46** of the ring segments **30**, **32**. The fixing plate **40** is mounted radially against the bottoms of the grooves **44**, **46**.

(38) The rolling bearing also comprises first and second screws **48**, **50** to fix the fixing plate **40** inside the grooves **44**, **46** of the ring segments **30**, **32**. In the illustrated example, the rolling bearing comprises two first screws **48** and two second screws **50**. Alternatively, it could be possible to foresee a different number of first and second screws **48**, **50**.

(39) Each of the first screw **48** extends through the fixing plate **40** and is engaged inside a threaded hole **52** formed from the bottom of the groove **44**. Each threaded hole **52** extends axially into the thickness of the ring segment **30**. The first screws **48** secure the fixing plate **40** onto the ring segment **30**.

(40) Similarly, each of the second screw **50** extends through the fixing plate **40** and is engaged inside a threaded hole **54** formed from the bottom of the groove **46**. Each threaded hole **54** extends axially into the thickness of the ring segment **32**. The second screws **50** secure the fixing plate **40** onto the ring segment **32**.

(41) The rolling bearing further comprises first and second pins **56**, **58** extending through the fixing plate **40** and protruding respectively into first and second recesses **60**, **62** formed on the ring segments **30**, **32**. The first recesses **60** are formed from the bottom of the groove **44**. The second recesses **62** are formed from the bottom of the groove **46**. The first and second recesses **60**, **62** extend axially.

(42) Each pin **56, 58** is entirely housed inside the fixing plate **40** and the associated recess **60, 62**. Each pin **56, 58** is secured inside the associated recess **60, 62** by any appropriate means, for example by press-fitting.

(43) As previously mentioned, the fixing plate **40** is entirely housed inside the grooves **44, 46** of the ring segments **30, 32** of the first ring of the outer ring. In other words, the fixing plate **40** does not protrude with respect to the ring segments **30, 32**. In the illustrated example, the outer surface **40a** of the fixing plate is flush with the frontal faces of the ring segments **30, 32** delimiting partly the frontal face **10d** of the outer ring.

(44) The overall dimension of the rolling bearing is not increased by the fixing plate **40**. In order to not increase the overall dimension of the rolling bearing, in the illustrated example, the pins **56, 58** and the screw heads of screws **48, 50** are also set back with the outer surface **40a** of the fixing plate.

(45) Similarly, to the fixing plate **40**, in order to mount the fixing plate **42** on the outer ring, third and fourth grooves **64, 66** are respectively formed on the frontal faces of the ring segments **30, 32** which are opposite to the frontal faces onto which are formed the first and second grooves **44, 46**.

(46) The groove **64** opens on the first end **30a** in the circumferential direction. The groove **66** opens on the first end **32a** in the circumferential direction. The groove **66** faces the groove **64** in the circumferential direction. In the illustrated example, the groove **66** is identical to the groove **64**. Alternatively, the grooves **64, 66** may have different shapes and/or dimensions.

(47) The fixing plate **42** is entirely housed inside the grooves **64, 66** of the ring segments **30, 32**. The fixing plate **42** is mounted radially against the bottoms of the grooves **64, 66**.

(48) The rolling bearing also comprises first and second screws **68, 70** to fix the fixing plate **42** inside the grooves **64, 66** of the ring segments **30, 32**. In the illustrated example, the rolling bearing comprises two first screws **68** and two second screws **70**. Alternatively, it could be possible to foresee a different number of first and second screws **68, 70**.

(49) Each of the first screw **68** extends through the fixing plate **42** and is engaged inside a threaded hole (not visible) formed from the bottom of the groove **64**. Each threaded hole extends axially into the thickness of the ring segment **30**. The first screws **68** secure the fixing plate **42** onto the ring segment **30**.

(50) Similarly, each of the second screws **70** extends through the fixing plate **42** and is engaged inside a threaded hole (not visible) formed from the bottom of the groove **66**. Each threaded hole extends axially into the thickness of the ring segment **32**. The second screws **70** secure the fixing plate **42** onto the ring segment **32**.

(51) The rolling bearing further comprises first and second pins **72, 74** extending through the fixing plate **42** and protruding respectively into first and second recesses (not visible) formed on the ring segments **30, 32**. The first recesses are formed from the bottom of the groove **64**. The second recesses are formed from the bottom of the groove **66**. The first and second recesses **60, 62** extend axially.

(52) Each pin **72, 74** is entirely housed inside the fixing plate **42** and the associated recess. Each pin **72, 74** is secured inside the associated recess by any appropriate means, for example by press-fitting.

(53) As previously mentioned, the fixing plate **42** is entirely housed inside the grooves **64, 66** of the ring segments **30, 32** of the first ring of the outer ring. In other words, the fixing plate **42** does not protrude with respect the ring segments **30, 32**. The outer surface of the fixing plate is flush with the frontal faces of the ring segments **30, 32** onto which are formed the grooves **64, 66**. In the illustrated example, the pins **72, 74** and the screw heads of screws **68, 70** are also set back with the outer surface **40a** of the fixing plate.

(54) The example shown on FIG. 6, in which identical parts are given identical references, differs from the first example in that an edge radius is provided between each flat trapezoidal leg face **34a, 34b** of the protrusion and the first end **30a**, and also between each flat trapezoidal leg face **34a, 34b**

and the outer face **34c**. Similarly, an edge radius is provided between each flat trapezoidal leg face **36a**, **36b** of the recess and the first end **32a**, and also between each flat trapezoidal leg face **36a**, **36b** and the inner bottom **36c**. The edge radii may be equal.

(55) Such chamfers facilitate the assembly of the ring segments **30**, **32**, notably in case of deformations of these ring segments.

(56) In the illustrated examples, the outer ring **10** is formed as a split-ring in the axial direction. Alternatively, according to the design of the rolling bearing, the outer ring **10** may be not segmented in the axial direction, but only in the circumferential direction.

(57) In the previous described examples, only the outer ring **10** is segmented in the circumferential direction. Alternatively, or in combination, the inner ring may also be formed as a split-ring comprises at least two successive circumferential ring segments.

(58) In the described examples, the rolling bearing is provided with three rows of rolling elements. Alternatively, the rolling bearing may comprise only one row of rolling elements, or two rows of rolling elements, or four or more rows of rolling elements. In the illustrated example, the rolling elements are rollers. The rolling bearing may comprise other types of rolling elements, for example balls. In another variant, the bearing may also be a sliding bearing having no rolling element.

Claims

1. A bearing comprising: an outer ring and an inner ring capable of rotating concentrically relative to one another, at least one of the inner and outer rings being formed by a split-ring comprising a plurality of successive circumferential ring segments, wherein for each pair of facing ends of adjacent successive ring segments of the split-ring, the facing ends intermingle so as to partially overlap in a circumferential direction to align the pair of facing ends in a radial direction; the adjacent successive ring segments of the split ring each having circumferential groove therein; a fixing plate is detachably secured in the circumferential groove the adjacent successive ring segments to secure the adjacent successive ring elements in an aligned configuration, wherein one of the adjacent ring segments comprises two flat trapezoidal leg faces extending outwardly from the facing end, the two flat trapezoidal leg faces delineating a flat outer face of at least one protrusion that intermingles with its paired facing end of the other adjacent ring segment, the flat outer face being parallel to the facing end, and wherein the width of each of the two flat trapezoidal leg faces is shorter than the width of the flat outer face.
 2. The bearing of claim 1, wherein an edge radius is provided between each flat trapezoidal leg face of the at least one protrusion and the facing end, and between each flat trapezoidal leg face and the flat outer face.
 3. The bearing of claim 1, wherein the fixing plate is set back or flush with at least the face of each of the ring segments from which the circumferential groove is formed.
 4. The bearing of claim 3, further comprising at least one first fixing screw and at least one second fixing screw extending through the fixing plate, the first fixing screw being engaged inside a threaded hole formed onto one of the ring segments, and the second fixing screw being engaged inside a threaded hole formed onto the other of the ring segments.
-