

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250256396

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Scrivens; Jevin et al.

System And Method For Performing Robot Registration Using Free-Form Path

Abstract

A surgical system includes a manipulator in a base coordinate system and a navigation system in a localizer coordinate system. The manipulator includes a tool and the navigation system includes a tool tracker. A control system controls movement of the tool and the tool tracker along a free-form path. The control system obtains a dataset related to movement of the tool tracker along the free-form path and obtains a dataset related to movement of the tool along the free-form path. The control system maps the datasets relative to one another to establish a relationship between the localizer coordinate system and the base coordinate system.

Inventors: Scrivens; Jevin (Weston, FL), Qu; Huajin (Fort Lauderdale, FL), Bhatt; Amar (San Diego, CA)

Applicant: MAKO Surgical Corp. (Weston, FL)

Family ID: 1000008452088

Assignee: MAKO Surgical Corp. (Weston, FL)

Appl. No.: 19/052713

Filed: February 13, 2025

Related U.S. Application Data

us-provisional-application US 63552897 20240213

Publication Classification

Int. Cl.: B25J9/16 (20060101); A61B34/00 (20160101); A61B34/20 (20160101); A61B34/30 (20160101); B25J5/00 (20060101)

U.S. Cl.:

CPC **B25J9/1628** (20130101); **A61B34/20** (20160201); **A61B34/30** (20160201); **A61B34/70** (20160201); **B25J5/007** (20130101); **B25J9/1679** (20130101); A61B2034/2055 (20160201)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application claims the benefit of and priority to U.S. Provisional Patent Application Ser. No. 63/552,897, filed Feb. 13, 2024, which is hereby incorporated by reference into the present application in its entirety.

BACKGROUND

[0002] Robotic surgical systems, such as the MAKO® surgical robot, include a robotic arm that is supported by a base. An end effector is attached to the robotic arm. A base tracker is attached to the base of the robot and positionable via an adjustable support arm. The base tracker is detectable by a camera of a navigation system to track the position of the robot base.

[0003] “Robot registration” is a procedure for establishing a relationship between the base tracker and the base of the surgical robot. Robot registration is required, in part, due to the base tracker being adjustably set in any number of poses. Hence, the relationship between the base tracker and the base of the robot is unknown to the navigation system and must be determined using this procedure. In turn, this procedure confirms the accuracy of the robotic arm and the location of the cutting tool supported by the robotic arm, relative to the navigation system.

[0004] Conventionally, during robot registration, a user is prompted to move the robot arm and the tracker between vertices of a predefined cube to facilitate point collection from both the kinematics of the robot arm and tracker. These points are matched and compared throughout the robot registration process. However, during the registration process, the robotic system constrains movement of the robot arm to the predefined cube edges, thereby constraining the user's arm movements. There could also be obstructions to the robot arm or tracker along the cube edges. Additionally, movement along constrained cube edges can cause the camera to lose sight of the tracker. To avoid accuracy issues, the user must take the time to ensure the tracker is continuously visible throughout movement along the cube edges. Furthermore, the user must hold the robotic arm and the tracker static at each vertex of the cube for a threshold amount of time to ensure enough data is collected. This can add additional time to the registration process. Although the MAKO® registration process is robust, there is remains room for improvement in view of at least some of the challenges described above.

SUMMARY

[0005] This Summary introduces a selection of concepts in a simplified form that are further described below in the Detailed Description below. This Summary is not intended to limit the scope of the claimed subject matter nor identify key features or essential features of the claimed subject matter.

[0006] In a first aspect, a surgical system is provided. The surgical system comprises a manipulator including: a base establishing a base coordinate system; a robotic arm coupled to the base and being formed of links and joints; and a tool coupled to the robotic arm; a navigation system including: a base tracker coupled to the manipulator; a tool tracker configured to be coupled to the tool; and a localizer configured to track positions of the base tracker and the tool tracker in a localizer coordinate system; and a control system coupled to the manipulator and the navigation system and being configured to: control, with the robotic arm, movement of the tool and the tool tracker along a free-form path; obtain, from the localizer, a localizer dataset related to the tool

tracker and being derived from movement of the tool tracker along the free-form path; obtain, from the manipulator, a kinematic dataset related to the tool and being derived from movement of the tool along the free-form path; and map the localizer dataset and the kinematic dataset relative to one another to establish a relationship between the localizer coordinate system and the base coordinate system.

[0007] In a second aspect, a surgical system is provided. The surgical system comprises a manipulator including: a base establishing a base coordinate system; an arm coupled to the base and being formed of links and joints; and a tool coupled to the arm; a navigation system including: a base tracker coupled to the manipulator; a tool tracker configured to be coupled to the tool; and a localizer configured to track positions of the base tracker and the tool tracker in a localizer coordinate system; and a control system coupled to the manipulator and the navigation system and being configured to: obtain, from the localizer, a localizer dataset related to the tool tracker and being derived from movement of the tool tracker along the free-form path; obtain, from the manipulator, a kinematic dataset related to the tool and being derived from movement of the tool along the free-form path; and map the localizer dataset and the kinematic dataset relative to one another to establish a relationship between the localizer coordinate system and the base coordinate system.

[0008] In a third aspect, a surgical system is provided. The surgical system comprises a manipulator including: a base establishing a base coordinate system; a robotic arm coupled to the base and being formed of links and joints; and a tool coupled to the robotic arm; a navigation system including: a base tracker coupled to the manipulator; a tool tracker coupled to the tool; and a localizer configured to track positions of the base tracker and the tool tracker in a localizer coordinate system; and a control system coupled to the manipulator and the navigation system and being configured to: control, with the robotic arm, automatic movement of the tool and the tool tracker along a predetermined path; obtain, from the localizer, a localizer dataset related to the tool tracker and being derived from automatic movement of the tool tracker along the predetermined path; obtain, from the manipulator, a kinematic dataset related to the tool and being derived from automatic movement of the tool along the predetermined path; and map the localizer dataset and the kinematic dataset relative to one another to establish a relationship between the localizer coordinate system and the base coordinate system.

[0009] In a fourth aspect, a method of operating the surgical system of the first aspect is provided.

[0010] In a fifth aspect, a method of operating the surgical system of the second aspect is provided.

[0011] In a sixth aspect, a method of operating the surgical system of the third aspect is provided.

[0012] Any of the aspects above can be combined in part or in whole. Any of the aspects above can be combined in part or in whole with any of the following implementations. In some implementations, the manipulator comprises a cart that supports the robotic arm; the base coordinate system is established relative to the cart; and the base tracker is coupled to the cart by an adjustable support arm that extends from the cart.

[0013] In some implementations, the control system is configured to control, with the robotic arm, movement of the tool and the tool tracker in response external force applied to the tool by a user. In some implementations, the control system is further configured to control, with the robotic arm, movement of the tool and the tool tracker in a free mode whereby movement of the manipulator is unconstrained by a virtual boundary.

[0014] In some implementations, the free-form path is defined during movement of the tool and the tool tracker by the user, and the free-form path is unknown prior to movement of the tool and the tool tracker. In some implementations, the free-form path is defined by continuous movement of the tool and the tool tracker by the user and without requiring the tool and the tool tracker to be held static by the user at predetermined positions defined by the control system.

[0015] In some implementations, the surgical system further includes a display device and the control system is configured to provide, on the display device, an instruction or suggestion for the

user for moving the tool.

[0016] In some implementations, the control system maps the localizer dataset and the kinematic dataset relative to one another by further being configured to: obtain, from the localizer dataset, a plurality of localized positions of the tool tracker being derived from movement of the tool tracker along the free-form path; obtain, from the kinematic dataset, a plurality of kinematic positions of the tool being derived from movement of the tool along the free-form path; and map the localized positions and kinematic positions relative to one another to establish the relationship between the localizer coordinate system and the base coordinate system. In some implementations, the control system maps the localizer dataset and the kinematic dataset relative to one another by further being configured to: obtain, from the localizer dataset, a localized path related to the tool tracker and being derived from movement of the tool tracker along the free-form path; obtain, from the kinematic dataset, a kinematic path related to the tool and being derived from movement of the tool along the free-form path; and map the localized path and the kinematic path relative to one another to establish the relationship between the localizer coordinate system and the base coordinate system. In some implementations, the control system is further configured to: obtain the localizer dataset according to a first sampling rate; and obtain the kinematic dataset according to a second sampling rate being different than the first sampling rate; and map the localizer dataset and the kinematic dataset relative to one another to offset a latency between the first sampling rate and the second sampling rate. In some implementations, the first sampling rate exhibits the latency relative to the second sampling rate.

[0017] In some implementations, the control system establishes the relationship between the localizer coordinate system and the base coordinate system by being configured to: obtain a first relationship between the localizer coordinate system and the tool tracker from the localizer; obtain a second relationship between the tool tracker and the tool from predetermined data; obtain a third relationship between the tool and the base coordinate system from kinematic data of the manipulator; and combine the first, second, and third relationships. In some implementations, the control system is further configured to: obtain a fourth relationship between the base tracker and the localizer coordinate system from the localizer; and combine the first, second, third, and fourth relationships to establish a fifth relationship between the base tracker and the base coordinate system.

[0018] In some implementations, the base coordinate system is determinable relative to the robotic arm; and the base tracker is coupled to the robotic arm and is moveable with the robotic arm. In some implementations, the control system is configured to: obtain a predetermined relationship between the base tracker and the base coordinate system from kinematic data related to the manipulator; and compare the established fifth relationship between the base tracker and the base coordinate system with the predetermined relationship between the base tracker and the base coordinate system to verify accuracy of the established fifth relationship.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] Other advantages of the present disclosure will be readily appreciated, as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings.

[0020] FIG. 1 is a perspective view of a robotic surgical system including a localizer, a manipulator, a surgical tool, and a tool tracker.

[0021] FIG. 2 is a block diagram of controllers of the robotic surgical system of FIG. 1.

[0022] FIG. 3 is a schematic view illustrating registration of the robotic surgical system.

[0023] FIG. 4 is a flowchart illustrating a method of path registration.

[0024] FIG. 5A is a diagram illustrating the surgical tool and the tool tracker of FIG. 1 moving along a free-form path during the method of path registration of FIG. 4.

[0025] FIG. 5B is a diagram illustrating a localized dataset generated by the localizer of FIG. 1 and a kinematic dataset generated by the manipulator of FIG. 1 based on movement of the surgical tool and the tool tracker of FIG. 1 moving along the free-form path.

[0026] FIG. 5C is a diagram illustrating a portion of a localized dataset generated by the localizer of FIG. 1 and a portion of a kinematic dataset generated by the manipulator of FIG. 1 in an instance where the localized dataset is generated according to a first sampling rate and the kinematic dataset is generated according to a second sampling rate.

[0027] FIG. 5D is a diagram illustrating mapping of the portion of the localized dataset of FIG. 5C and projected positions of the kinematic dataset of FIG. 5C.

DETAILED DESCRIPTION

I. System Overview

[0028] With reference to the Figures, wherein like numerals indicate like or corresponding parts throughout the several views, a surgical system **10** (hereinafter “system”) and method for operating the system **10** are described herein and shown throughout the accompanying Figures.

[0029] As shown in FIG. 1, the system **10** is a robotic surgical system for treating an anatomy (surgical site) of a patient **12**, such as bone or soft tissue. In FIG. 1, the patient **12** is undergoing a surgical procedure. The anatomy in FIG. 1 includes a spine of the patient **12**. The surgical procedure may involve tissue removal or treatment. The robotic surgical system **10** described herein may be utilized for treating any anatomical structure(s), for example, such as joints, including knee joints, hip joints, shoulder joints, ankles joints, or any other bone structure(s) not described herein. The robotic surgical system **10** can be used to perform any type of procedure, including any spinal procedure, partial knee arthroplasty, total knee arthroplasty, total hip arthroplasty, anatomical shoulder arthroplasty, reverse shoulder arthroplasty, fracture repair surgery, osteotomies, and the like. The techniques described herein can be used with any type of robotic system and for any procedure.

[0030] The system **10** includes a manipulator **14**, which may also be referred to as a robotic manipulator. In one example, the manipulator **14** has a base **16** and plurality of links **18**. The plurality of links **18** may be commonly referred to as a robotic arm **18A**. In some instances, the manipulator **14** may include more than one robotic arm **18A**. A manipulator cart **17** supports the manipulator **14** such that the manipulator **14** is fixed to the manipulator cart **17**. The links **18** collectively form one or more arms of the manipulator **14**. The manipulator **14** may have a serial arm configuration (as shown in FIG. 1) or a parallel arm configuration. In other examples, more than one manipulator **14** may be utilized in a multiple arm configuration. The manipulator **14** comprises a plurality of joints (J) and a plurality of joint encoders **19** located at the joints (J) for determining position data of the joints (J). For simplicity, one joint encoder **19** is illustrated in FIG. 1, although it is to be appreciated that the other joint encoders **19** may be similarly illustrated. The manipulator **14** according to one example has six joints (J1-J6) implementing at least six-degrees of freedom (DOF) for the manipulator **14**. However, the manipulator **14** may have any number of degrees of freedom and may have any suitable number of joints (J) and redundant joints (J). In one example, each of the joints (J) of the manipulator **14** are actively driven and may be motorized joints (J). In other examples, each of the joints (J) may be passively driven. In still other examples, the joints (J) may include a combination of actively driven joints (J) and passively driven joints (J).

[0031] The base **16** of the manipulator **14** is generally a portion of the manipulator **14** that is stationary during usage thereby providing a fixed reference coordinate system (i.e., a virtual zero pose) for other components of the manipulator **14** or the system **10** in general. Generally, the origin of a base coordinate system is defined at the fixed reference of the base **16**. The base coordinate system may be referred to herein as a manipulator coordinate system MNPL. The fixed reference point of the base **16** may be defined with respect to any suitable portion of the manipulator **14**, such

as one or more of the links **18**. Alternatively, or additionally, the fixed reference point of the base **16** may be defined with respect to the manipulator cart **17**, such as where the manipulator **14** is physically attached to the cart **17**. In one example, the fixed reference point of the base **16** is defined at an intersection of the axes of joints **J1** and **J2**. Thus, although joints **J1** and **J2** are moving components in reality, the intersection of the axes of joints **J1** and **J2** is nevertheless a virtual fixed reference point, which does not move in the manipulator coordinate system MNPL. The manipulator **14** and/or manipulator cart **17** house a manipulator computer **26**, or other type of control unit.

[0032] The system **10** may include a surgical tool **20** coupled to the robotic arm **18A**. The surgical tool **20** may include any end effector suitable for a surgical procedure. In some instances, the surgical tool **20** may be a tool for manipulating the anatomy of a patient, such as a saw, a router, a reamer, an impactor, an ultrasonic aspirator, a probe, a cutting tool, a drill, a dilator, a screwdriver, or the like. Additionally, or alternatively, the surgical tool **20** may include an accessory and/or energy applicator, such as a saw blade, a cutting burr, a router, a reamer, an impactor, an ultrasonic aspirator, a probe, a cutting tool, a drill, a dilator, a screwdriver, or the like. The accessory and energy applicator may be integrated or separately attached to surgical tool **20**. The surgical tool **20** may also include a cutting guide. In some instances, the surgical tool **20** may include a tool holder or a guide tube for holding a tool, such as the tool holder/guide tube described in U.S. Provisional Patent Application No. 63/612,011, entitled, "Magnetic Spine Registration Tool", which is incorporated herein by reference. The tool holder/guide tube and the robotic arm **18A** may be separate components (i.e., two pieces) or the tool holder/guide tube and the robotic arm **18A** may be integral with one another (i.e., one piece).

[0033] The system **10** may include a tool tracker **106**. In one example, the tool tracker **106** may be temporarily coupled to the surgical tool **20**, such as the trackable array described in U.S. Pat. App. Pub. No. 2022/0134569, entitled, "Robotic Surgical System With Motorized Movement To A Starting Pose For A Registration Or Calibration Routine," the disclosure of which is hereby incorporated by reference, or such as the end effector tracker described in U.S. Pat. No. 10,350,012, entitled, "Method And Apparatus For Controlling A Haptic Device," the disclosure of which is hereby incorporated by reference, or such as the tool tracker in U.S. Provisional Patent Application No. 63/612,011, entitled, "Magnetic Spine Registration Tool", which is incorporated herein by reference. In other examples, the tool tracker **106** may be attachable to or detachable from the surgical tool **20** and/or attachable to or detachable from any other component of the manipulator **14**, such as one or more links of the robotic arm **18A**, e.g. a distal-most link of the manipulator (**J6**). For instance, the tool tracker **106** may include similar components as the tracker assembly described in U.S. Pat. App. Pub. No. 2023/0277256, entitled, "Robotic System Including A Link Tracker," the disclosure of which is hereby incorporated by reference, for attaching the tool tracker **106** to the surgical tool **20** or any other component of the manipulator **14**. For instance, the tool tracker **106** may be attached/detached to the surgical tool **20** or any other component of the manipulator **14** using a spring-biased latch, a magnetic connection, a snap-fit connection using flexible elements, or the like.

[0034] The tool tracker **106** may be coupled to the surgical tool **20** such that a relationship between the tool tracker **106** and the surgical tool **20** may be determinable. For example, the tool tracker **106** may include a reference surface configured to abut the surgical tool **20**, such as the reference surface described in U.S. Provisional Patent Application No. 63/612,011, entitled, "Magnetic Spine Registration Tool", which is incorporated herein by reference. Contact between the reference surface and the surgical tool **20** may indicate that the tool tracker **106** is properly coupled to the surgical tool **20** such that a location of the tool tracker **106** relative to the surgical tool **20** is fixed and that a relationship between the tool tracker **106** and the surgical tool **20** is determinable.

[0035] The tool tracker **106** may include one or more fiducial markers **FM**. In some instances, the fiducial markers **FM** may be coupled to or integrally formed with or manually coupled to the

surgical tool **20** and/or a component of the manipulator **14**. The fiducial markers FM may include any suitable shape. For example, the fiducial markers FM may include a cuboidal or spherical shape. The fiducial markers FM may be active or passive tracking elements.

[0036] Referring to FIG. 2, the system **10** includes one or more controllers **30** (hereinafter referred to as “controller”). The controller **30** includes software and/or hardware for controlling the manipulator **14**. The controller **30** directs the motion of components of the manipulator **14**, such as the robotic arm **18A**, and controls a state (position and/or orientation) of the surgical tool **20** with respect to a coordinate system. In one example, the coordinate system is the manipulator coordinate system MNPL, as shown in FIG. 1. The manipulator coordinate system MNPL has an origin located at any suitable pose with respect to the manipulator **14**. Axes of the manipulator coordinate system MNPL may be arbitrarily chosen as well. Generally, the origin of the manipulator coordinate system MNPL is defined at the fixed reference point of the base **16**. One example of the manipulator coordinate system MNPL is described in U.S. Pat. No. 9,119,655, entitled, “Surgical Manipulator Capable of Controlling a Surgical Instrument in Multiple Modes,” the disclosure of which is hereby incorporated by reference.

[0037] As shown in FIG. 1, the system **10** further includes a navigation system **32**. One example of the navigation system **32** is described in U.S. Pat. No. 9,008,757, filed on Sep. 24, 2013, entitled, “Navigation System Including Optical and Non-Optical Sensors,” hereby incorporated by reference. The navigation system **32** is configured to track movement of various objects. Such objects include, for example, the manipulator **14**, the surgical tool **20**, and/or the anatomy. The navigation system **32** tracks these objects to gather state information of one or more of the objects with respect to a (navigation) localizer coordinate system LCLZ. Coordinates in the localizer coordinate system LCLZ may be transformed to the manipulator coordinate system MNPL, and/or vice-versa, using transformation and registration techniques described herein.

[0038] The navigation system **32** can include a cart assembly **34** that houses a navigation computer **36**, and/or other types of control units. A navigation interface is in operative communication with the navigation computer **36**. The navigation interface includes one or more displays **38**. The navigation system **32** is capable of displaying a graphical representation of the relative states of the tracked objects to the operator using the one or more displays **38**. First and second input devices **40**, **42** may be used to input information into the navigation computer **36** or otherwise to select/control certain aspects of the navigation computer **36**. As shown in FIG. 1, such input devices **40**, **42** include interactive touchscreen displays. However, the input devices **40**, **42** may include any one or more of a keyboard, a mouse, a microphone (voice-activation), gesture control devices, head-mounted devices, and the like.

[0039] The navigation system **32** is configured to depict a visual representation of the anatomy and the manipulator **14**, and/or surgical tool **20** for visual guidance of any of the techniques described. The visual representation may be real (camera) images, virtual representations (e.g., computer models), or any combination thereof. The visual representation can be presented on any display viewable to the surgeon, such as the displays **38** of the navigation system **32**, head mounted devices, or the like. The representations may be augmented reality, mixed reality, or virtual reality.

[0040] The navigation system **32** also includes a navigation localizer **44** (hereinafter “localizer”) coupled to the navigation computer **36**. In one example, the localizer **44** is an optical localizer and includes a camera unit **46**. The camera unit **46** has an outer casing **48** that houses one or more optical sensors **50**.

[0041] The navigation system **32** may include one or more trackers. In one example, the trackers include the tool tracker **106**, a pointer tracker, one or more manipulator trackers **52**, and/or one or more patient trackers. In the illustrated example of FIG. 1, the manipulator tracker **52** is attached to a distal flange of the robotic arm **18A**. The manipulator tracker **52** may be affixed to any suitable component of the manipulator **14**, in addition to, or other than the surgical tool, such as the base **16** (i.e., tracker **52B**), or any one or more links **18** or joints J of the manipulator **14**. Additionally, or

alternatively, the manipulator tracker **52** may be secured to a surgical drape or drape assembly, as described in U.S. Pat. App. Pub. No. 2023/0277256, entitled, “Robotic System Including A Link Tracker,” the disclosure of which is hereby incorporated by reference. For instance, the manipulator tracker **52** may be secured to a surgical drape or drape assembly via an elastic band or snap ring. The patient trackers may be affixed to a vertebra of the patient **12** and/or the pelvis of the patient **12**. The pointer tracker may be affixed to a pointer used for registering the anatomy to the localizer coordinate system LCLZ. The trackers may be fixed to their respective components in any suitable manner.

[0042] As shown in FIG. **1**, the base tracker **52B** may be coupled to the cart **17** by an adjustable support arm **102**. As shown, the base tracker **52B** may be attached to one end of an adjustable support arm **102** and the adjustable support arm **102** may be attached at the other end to the cart **17**. The adjustable support arm **102** can be positioned and locked to place the base tracker **52B** in a fixed position relative to the cart **17**. An example of a base tracker **52B** coupled to an adjustable support arm can be like that described in U.S. patent application Ser. No. 17/513,324, entitled, “Robotic Surgical System With Motorized Movement To A Starting Pose For A Registration Or Calibration Routine”, or U.S. patent application Ser. No. 18/198,938, entitled, “Robotic System With Improved Configurations For Base Tracker”, the entire contents of which are hereby incorporated by reference in their entirety. Alternatively, or additionally, a base tracker **52B** may be coupled to the robotic arm **18A** and may be moveable with the robotic arm **18A**. For instance, the base tracker **52B** may include a plurality of (active or passive) tracking elements located on any number of links **18** of the manipulator **14**. In this case, the base tracker **52B** is formed of a tracking geometry from the various tracking elements, which move with movement of the robotic arm **18A**. An example of a base tracker **52B** formed by optical markers located on the links **18** may be like that described in U.S. patent application Ser. No. 18/115,964, entitled, “Robotic System with Link Tracker”, the entire contents of which is hereby incorporated by reference in its entirety. Alternatively, or additionally, the base tracker **52B** may be secured to a surgical drape or drape assembly, as described in U.S. Pat. App. Pub. No. 2023/0277256, entitled, “Robotic System Including A Link Tracker,” the disclosure of which is hereby incorporated by reference. For instance, the base tracker **52B** may be secured to a surgical drape or drape assembly via an elastic band or snap ring.

[0043] When optical localization is utilized, however, one or more of the trackers may include active markers **58**. The active markers **58** may include light emitting diodes (LEDs). Alternatively, the trackers described herein may have passive markers, such as reflectors, which reflect light emitted from the camera unit **46**. Other suitable markers not specifically described herein may be utilized.

[0044] The localizer **44** tracks the trackers to determine a state of one or more of the trackers which correspond respectively to the state of the object respectively attached thereto. The localizer **44** provides the state of the trackers to the navigation computer **36**. In one example, the navigation computer **36** determines and communicates the state the trackers to the manipulator computer **26**. As used herein, the state of an object includes, but is not limited to, data that defines the position and/or orientation of the tracked object or equivalents/derivatives of the position and/or orientation. For example, the state may be a pose of the object, and may include linear data, and/or angular velocity data, and the like.

[0045] Although one example of the navigation system **32** is shown in the Figures, the navigation system **32** may have any other suitable configuration for tracking the manipulator **14** and the patient **12**. The illustrated tracker configuration is provided merely as one example for tracking objects within the operating space. Any number of trackers may be utilized and may be located in positions or on objects other than shown. In other examples, such as described below, the localizer **44** may detect objects absent any trackers affixed to objects.

[0046] In one example, the navigation system **32** and/or localizer **44** are ultrasound-based. For

example, the navigation system **32** may comprise an ultrasound imaging device coupled to the navigation computer **36**. The ultrasound imaging device may be robotically controlled or may be hand-held. The ultrasound imaging device images any of the aforementioned objects, e.g., the manipulator **14** and the patient **12**, and generates state signals to the controller **30** based on the ultrasound images. The ultrasound images may be of any ultrasound imaging modality. The navigation computer **36** may process the images in near real-time to determine states of the objects. Ultrasound tracking can be performed absent the use of trackers affixed to the objects being tracked. The ultrasound imaging device may have any suitable configuration and may be different than the camera unit **46** as shown in FIG. **1**. One example of an ultrasound tracking system can be like that described in U.S. patent application Ser. No. 15/999,152, filed Aug. 16, 2018, entitled “Ultrasound Bone Registration With Learning-Based Segmentation And Sound Speed Calibration,” the entire contents of which are incorporated by reference herein.

[0047] In another example, the navigation system **32** and/or localizer **44** are radio frequency (RF)-based. For example, the navigation system **32** may comprise an RF transceiver coupled to the navigation computer **36**. The manipulator **14** and the patient **12** may comprise RF emitters or transponders attached thereto. The RF emitters or transponders may be passive or actively energized. The RF transceiver transmits an RF tracking signal and generates state signals to the controller **30** based on RF signals received from the RF emitters. The navigation computer **36** and/or the controller **30** may analyze the received RF signals to associate relative states thereto. The RF signals may be of any suitable frequency. The RF transceiver may be positioned at any suitable location to track the objects using RF signals effectively. Furthermore, the RF emitters or transponders may have any suitable structural configuration that may be much different than the trackers as shown in FIG. **1**.

[0048] In yet another example, the navigation system **32** and/or localizer **44** are electromagnetically based. For example, the navigation system **32** may comprise an EM transceiver coupled to the navigation computer **36**. The manipulator **14** and the patient **12** may comprise EM components attached thereto, such as any suitable magnetic tracker, electro-magnetic tracker, inductive tracker, or the like. The trackers may be passive or actively energized. The EM transceiver generates an EM field and generates state signals to the controller **30** based upon EM signals received from the trackers. The navigation computer **36** and/or the controller **30** may analyze the received EM signals to associate relative states thereto. Again, such navigation system **32** examples may have structural configurations that are different than the navigation system **32** configuration as shown throughout the Figures.

[0049] In yet another example, the navigation system **32** and/or localizer **44** utilize a machine vision system which includes a video camera coupled to the navigation computer **36**. The video camera is configured to locate a physical object in a target space. The physical object has a geometry represented by virtual object data stored by the navigation computer **36**. The detected objects may be tools, obstacles, anatomical features, trackers, or the like. The video camera and navigation computer **36** are configured to detect the physical objects using image processing techniques such as pattern, color, or shape recognition, edge detection, pixel analysis, neural net or deep learning processing, optical character recognition, barcode detection, or the like. The navigation computer **36** can compare the captured images to the virtual object data to identify and track the objects. A tracker may or may not be coupled to the physical object. If trackers are utilized, the machine vision system may also include infrared detectors for tracking the trackers and comparing tracking data to machine vision data. Again, such navigation system **32** examples may have structural configurations that are different than the navigation system **32** configuration as shown throughout the Figures. Examples of machine vision tracking systems can be like that described in U.S. Pat. No. 9,603,665, entitled “Systems and Methods for Establishing Virtual Constraint Boundaries” and/or like that described in U.S. Provisional Patent Application No. 62/698,502, filed Jul. 16, 2018, entitled “Systems and Method for Image Based Registration and

Calibration,” the entire contents of which are incorporated by reference herein.

[0050] The navigation system **32** and/or localizer **44** may have any other suitable components or structure not specifically recited herein. Furthermore, any of the techniques, methods, and/or components described above with respect to the camera-based navigation system **32** shown throughout the Figures may be implemented or provided for any of the other examples of the navigation system **32** described herein. For example, the navigation system **32** may utilize solely inertial tracking or any combination of tracking techniques.

[0051] As shown in FIG. **2**, the controller **30** further includes software modules. The software modules may be part of a computer program or programs that operate on the manipulator computer **26**, navigation computer **36**, or a combination thereof, to process data to assist with control of the system **10**. The software modules include instructions stored in one or more non-transitory computer readable medium or memory on the manipulator computer **26**, navigation computer **36**, or a combination thereof, to be executed by one or more processors of the computers **26**, **36**. Additionally, software modules for prompting and/or communicating with the operator may form part of the program or programs and may include instructions stored in memory on the manipulator computer **26**, navigation computer **36**, or a combination thereof. The operator interacts with the first and second input devices **40**, **42** and the one or more displays **38** to communicate with the software modules. The user interface software may run on a separate device from the manipulator computer **26** and navigation computer **36**.

[0052] The controller **30** includes a manipulator controller **60** for processing data to direct motion of the manipulator **14**. In one example, as shown in FIG. **1**, the manipulator controller **60** is implemented on the manipulator computer **26**. The manipulator controller **60** may receive and process data from a single source or multiple sources. The controller **30** further includes a navigation controller **62** for communicating the state data relating to the anatomy to the manipulator **14** to the manipulator controller **60**. The manipulator controller **60** receives and processes the state data provided by the navigation controller **62** to direct movement of the manipulator **14**. In one example, as shown in FIG. **1**, the navigation controller **62** is implemented on the navigation computer **36**. The manipulator controller **60** or navigation controller **62** may also communicate states of the patient **12** and manipulator **14** to the operator by displaying an image of the anatomy and the manipulator **14** on the one or more displays **38**. The manipulator computer **26** or navigation computer **36** may also command display of instructions or request information using the display **38** to interact with the operator and for directing the manipulator **14**.

[0053] The one or more controllers **30**, including the manipulator controller **60** and navigation controller **62**, may be implemented on any suitable device or devices in the system **10**, including, but not limited to, the manipulator computer **26**, the navigation computer **36**, and any combination thereof. As will be described herein, the controller **30** is not limited to one controller, but may include a plurality of controllers for various systems, components, or sub-systems of the surgical system **10**. These controllers may be in communication with each other (e.g., directly, or indirectly), and/or with other components of the surgical system **10**, such as via physical electrical connections (e.g., a tethered wire harness) and/or via one or more types of wireless communication (e.g., with a WiFi™ network, Bluetooth®, a radio network, and the like). Any of the one or more controllers **30** may be realized as or with various arrangements of computers, processors, control units, and the like, and may comprise discrete components or may be integrated (e.g., sharing hardware, software, inputs, outputs, and the like). Any of the one or more controllers may implement their respective functionality using hardware-only, software-only, or a combination of hardware and software. Examples of hardware include, but is not limited, single or multi-core processors, CPUs, GPUs, integrated circuits, microchips, or ASICs, digital signal processors, microcontrollers, field programmable gate arrays, systems on a chip, discrete circuitry, and/or other suitable hardware, and the like. The one or more controllers may implement software programs, software modules, algorithms, logical rules, look-up tables and other reference data, and various

software layers for implementing any of the capabilities described herein. Equivalents of the software and hardware for the one or more controllers **30**, and peripheral devices connected thereto, are fully contemplated.

[0054] As shown in FIG. **2**, the controller **30** includes a boundary generator **66**. The boundary generator **66** is a software module that may be implemented on the manipulator controller **60**. Alternatively, the boundary generator **66** may be implemented on other components, such as the navigation controller **62**. The boundary generator **66** generates virtual boundaries (VB) for constraining the manipulator **14** and/or the surgical tool **20**. Such virtual boundaries (VB) may also be referred to as virtual meshes, virtual constraints, line haptics, or the like. The virtual boundaries (VB) may be defined with respect to a 3-D bone model registered to one or more patient trackers such that the virtual boundaries (VB) are fixed relative to the bone model. The state of the manipulator **14** and/or the surgical tool **20** is tracked relative to the virtual boundaries (VB). In one example, the state of a center point of the surgical tool **20** is measured relative to the virtual boundaries (VB) for purposes of determining when and where haptic feedback force is applied to the manipulator **14**, or more specifically, the surgical tool **20**.

[0055] A tool path generator **68** is another software module run by the controller **30**, and more specifically, the manipulator controller **60**. The tool path generator **68** generates a path for the manipulator **14** and/or the surgical tool **20** to traverse, such as for removing sections of the anatomy to receive an implant. One exemplary system and method for generating the tool path is explained in U.S. Pat. No. 9,119,655, entitled, "Surgical Manipulator Capable of Controlling a Surgical Instrument in Multiple Modes," the disclosure of which is hereby incorporated by reference. In some examples, the virtual boundaries (VB) and/or tool paths may be generated offline rather than on the manipulator computer **26** or navigation computer **36**. Thereafter, the virtual boundaries (VB) and/or tool paths may be utilized at runtime by the manipulator controller **60**.

[0056] Additionally, it may be desirable to control the manipulator **14** in different modes of operation for the system **10**. For example, the system **10** may enable the manipulator **14** to interact with the site using manual and semi-autonomous modes of operation. An example of the semi-autonomous mode is described in U.S. Pat. No. 9,119,655, entitled, "Surgical Manipulator Capable of Controlling a Surgical Instrument in Multiple Modes," the disclosure of which is hereby incorporated by reference. In the semi-autonomous mode, the manipulator **14** directs movement of the robotic arm **18A** and/or the surgical tool **20** at the surgical site. In one instance, the controller **30** models the robotic arm **18A** and/or the surgical tool **20** as a virtual rigid body and determines forces and torques to apply to the virtual rigid body to advance and constrain the robotic arm **18A** and/or the surgical tool **20** along any trajectory or path in the semi-autonomous mode. Movement of the tool **20** in the semi-autonomous mode is constrained in relation to the virtual constraints generated by the boundary generator **66** and/or path generator **69**.

[0057] In the semi-autonomous mode, the manipulator **14** is capable of moving the robotic arm **18A** and/or surgical tool **20** free of operator assistance. Free of operator assistance may mean that an operator does not physically move the robotic arm **18A** and/or surgical tool **20** by applying external force to move the robotic arm **18A** and/or surgical tool **20**. Instead, the operator may use some form of control to manage starting and stopping of movement. For example, the operator may hold down a button of a control to start movement of the robotic arm **18A** and/or surgical tool **20** and release the button to stop movement of the robotic arm **18A** and/or surgical tool **20**.

Alternatively, the operator may press a button to start movement of the robotic arm **18A** and/or surgical tool **20** and press a button to stop motorized movement of the robotic arm **18A** and/or surgical tool **20** along the trajectory or path. The manipulator **14** uses motorized movement to advance the robotic arm **18A** and/or surgical tool **20** in accordance with pre-planned parameters.

[0058] Alternatively, the system **10** may be operated in the manual mode, a free mode, or a haptic mode. Here, in one instance, the operator manually directs, and the manipulator **14** controls, movement of the robotic arm **18A** and/or surgical tool **20** at the surgical site. The operator

physically contacts the robotic arm **18A** and/or surgical tool **20** to cause movement of the robotic arm **18A** and/or surgical tool **20**. In one implementation, the user applies force to cause displacement of the robotic arm **18A** and/or surgical tool **20** and the robotic system **10** can reactively provide haptic force feedback when the robotic arm **18A** and/or surgical tool **20** reaches certain virtual boundaries. In another implementation, the manipulator **14** monitors the forces and torques placed on the robotic arm **18A** and/or surgical tool **20** by the operator in order to position the robotic arm **18A** and/or surgical tool **20**. A sensor that is part of the manipulator **14**, such as a force-torque transducer, measures these external forces and torques applied to the robotic arm **18A** and/or surgical tool **20**, e.g., in six degrees of freedom. In one example, the sensor is coupled between the distal-most link of the manipulator (**J6**) and the robotic arm **18A** and/or surgical tool **20**. In response to the applied forces and torques, the one or more controllers **30**, **60**, **62** are configured to determine a commanded position of the robotic arm **18A** and/or surgical tool **20** by evaluating the forces/torques applied externally to the robotic arm **18A** and/or surgical tool **20** with respect to virtual model of the robotic arm **18A** and/or surgical tool **20** in a virtual simulation. The manipulator **14** then mechanically moves the robotic arm **18A** and/or surgical tool **20** to the commanded position in a manner that emulates the movement that would have occurred based on the forces and torques applied externally by the operator. Movement of the robotic arm **18A** and/or surgical tool **20** in the manual mode is also constrained in relation to the virtual constraints generated by the boundary generator **66** and/or path generator **69**.

II. Registration Overview

[0059] FIG. **3** illustrates transforms that may be utilized in registration of the system **10**. During registration of the system **10**, the controller **30** establishes a relationship **R** between the coordinate system of the localizer **44** (i.e., the localizer coordinate system **LCLZ**) and a coordinate system of the base **16** (i.e., the manipulator coordinate system **MNPL**).

[0060] The controller **30** may obtain a series of sub-relationships between components of the system **10** to establish the relationship **R** between the localizer coordinate system **LCLZ** and the manipulator coordinate system **MNPL**.

[0061] The controller **30** may obtain a sub-relationship **SR1** between the localizer coordinate system **LCLZ** and the tool tracker **106** from the localizer **44**. For example, the localizer **44** may track the tool tracker **106** and provide a location of the tool tracker **106** to the controller **30** as coordinates in the localizer coordinate system **LCLZ**.

[0062] The controller **30** may obtain a sub-relationship **SR2** between the tool tracker **106** and a component of the manipulator **14** from predetermined data. In the instance of FIG. **3**, the surgical tool **20** is shown as a distal flange of the robotic arm **18A**. The controller **30** may store, in memory, known data regarding a location of the tool tracker **106** relative to the distal flange to obtain the sub-relationship **SR2**. In some instances, the controller **30** may obtain a sub-relationship **SR2** between the tool tracker **106** and the surgical tool **20** from predetermined data. For example, the controller **30** may obtain the sub-relationship **SR2** between the tool tracker **106** and the surgical tool **20** based on known data regarding a location of the tool tracker **106** relative to the distal flange and based on known data regarding a location of the distal flange relative to the surgical tool **20**. In other instances, the controller **30** may obtain the sub-relationship **SR2** between the tool tracker **106** and the surgical tool **20** based on known data regarding a location of the tool tracker **106** relative to the surgical tool **20**.

[0063] The controller **30** may obtain a sub-relationship **SR3** between a component of the manipulator **14** and the manipulator coordinate system **MNPL** from kinematic data of the manipulator **14**. In the instance of FIG. **3**, the surgical tool **20** is shown as the distal flange of the robotic arm **18A**. The manipulator **14** may sense movement of the distal flange and the controller **30** may receive kinematic data from the manipulator controller **60** characterizing movement of the distal flange. In some instances, the controller **30** may obtain a sub-relationship **SR3** between the surgical tool **20** and the manipulator coordinate system **MNPL** from kinematic data of the

manipulator **14**. For example, the controller **30** may obtain the sub-relationship SR3 between the surgical tool **20** and the manipulator coordinate system MNPL based on known data regarding a location of the tool tracker **106** relative to the distal flange and based on kinematic data from the manipulator controller **60** characterizing movement of the distal flange. In other instances, the controller **30** may obtain the sub-relationship SR3 between the surgical tool **20** and the manipulator coordinate system MNPL based on kinematic data from the manipulator controller **60** characterizing movement of the surgical tool **20**.

[0064] For the sub-relationships SR2, SR3, the surgical tool **20** for which the sub-relationships SR2, SR3 are obtained may be any suitable component of the manipulator **14**. For example, the surgical tool **20** may be the robotic arm **18A**, a link **18** of the robotic arm **18A**, a joint (J) of the robotic arm **18A**, and/or the surgical tool **20**. The controller **30** is able to more accurately establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL in instances where the surgical tool **20** is the same for both sub-relationships SR2, SR3.

[0065] Once the controller **30** obtains a series of sub-relationships between components of the system **10**, the controller **30** may establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL by combining the sub-relationships. For example, the controller **30** may combine sub-relationships SR1, SR2, SR3 to establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL. Specifically, as shown in FIG. 3, the controller **30** may combine sub-relationships SR2, SR3 to determine the sub-relationship SR4 between the tool tracker **106** and the manipulator coordinate system MNPL. The controller **30** may then combine sub-relationships SR4, SR1 to establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL.

[0066] The controller **30** may additionally establish a sub-relationship SR6 between the base tracker **52B** and the manipulator coordinate system MNPL. The controller **30** may determine the sub-relationship SR6 in instances where the tool tracker **106** is a temporary tracker coupled to the surgical tool **20**, such as the instance of FIG. 3. In such instances, the tool tracker **106** may be decoupled from the surgical tool **20** during a surgical procedure and the surgical tool **20** may be unable to be tracked by the localizer **44** during the surgical procedure. As such, the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL is established in view of the base tracker **52B** in order for a location of the surgical tool **20** to be determined during such a surgical procedure. The controller **30** determines the sub-relationship SR6 between the base tracker **52B** and the manipulator coordinate system MNPL to establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL in view of the base tracker **52B**. In this way, during a surgical procedure where the tool tracker **106** is removed, the manipulator **14** may determine a location of the surgical tool **20** is determined using kinematic data, where a position of the manipulator **14** is established via the sub-relationship SR6.

[0067] In order to establish the sub-relationship SR6 between the base tracker **52B** and the manipulator coordinate system MNPL, the controller **30** may first obtain a sub-relationship SR5 between the base tracker **52B** and the localizer coordinate system LCLZ from the localizer **44**. For example, the localizer **44** may track the base tracker **52B** and provide a location of the base tracker **52B** and the tool tracker **106** to the controller **30** as coordinates in the localizer coordinate system LCLZ.

[0068] The controller **30** may then combine the sub-relationships SR1, SR2, SR3, SR5 to establish the sub-relationship SR6 between the base tracker **52B** and the manipulator coordinate system MNPL. Specifically, as shown in FIG. 3, the controller **30** may combine sub-relationships SR2, SR3 to determine the sub-relationship SR4 between the tool tracker **106** and the manipulator coordinate system MNPL. The controller **30** may also combine sub-relationships SR1, SR5 to

obtain a sub-relationship SR7 between the tool tracker **106** and the base tracker **52B**. The controller **30** may then combine sub-relationships SR4, SR7 to establish the sub-relationship SR6 between the base tracker **52B** and the manipulator coordinate system MNPL.

[0069] The controller **30** may also be configured to verify the accuracy of the established sub-relationship SR6 between the base tracker **52B** and the manipulator coordinate system MNPL in instances where the base tracker **52B** is coupled to a known location relative to the manipulator **14**. For reference, in instances where the base tracker **52B** is coupled to the cart **17** by an adjustable support arm **102**, a location of the base tracker **52B** may be unknown to the controller **30**. As such, the controller **30** establishes the sub-relationship SR6 between the base tracker **52B** and the manipulator coordinate system MNPL and uses the sub-relationship SR6 when determining a location of the surgical tool **20** during a surgical procedure where the tool tracker **106** is removed. Contrastingly, in instances where the base tracker **52B** is coupled to a known location relative to the manipulator **14**, the controller **30** may be configured to obtain a predetermined relationship between the base tracker **52B** and the manipulator coordinate system MNPL such that, after the controller **30** establishes the sub-relationship SR6, the controller **30** may compare the established sub-relationship SR6 with the predetermined relationship to verify accuracy of the established sub-relationship SR6. The controller **30** may verify the accuracy of the established sub-relationship SR6 as a means of verifying accuracy of the relationship R between the manipulator coordinate system MNPL and the localizer coordinate system LCLZ.

[0070] In instances where the base tracker **52B** is coupled for effecting continuous movement of the surgical tool **20** and the tool tracker **106** to a known location relative to the manipulator **14**, the base tracker **52B** may be coupled to any suitable component of the manipulator **14**. In one such instance, the base tracker **52B** may be coupled to and moveable with the robotic arm **18A** of the manipulator **14**. In such instances, the controller **30** may be configured to obtain the predetermined relationship between the base tracker **52B** and the manipulator coordinate system MNPL from kinematic data related to the manipulator **14**. The controller **30** may then compare the established sub-relationship SR1 between the base tracker **52B** and the manipulator coordinate system MNPL with the predetermined relationship between the base tracker **52B** and the manipulator coordinate system MNPL to verify accuracy of the established sub-relationship SR6. In other instances, the base tracker **52B** may be coupled to the cart **17**. tracker **52B** may be coupled to and moveable with the robotic arm **18A** of the manipulator **14**. In such instances, the controller **30** may be configured to receive the predetermined relationship between the base tracker **52B** and the manipulator coordinate system MNPL. The controller **30** may then compare the established sub-relationship SR1 between the base tracker **52B** and the manipulator coordinate system MNPL with the predetermined relationship between the base tracker **52B** and the manipulator coordinate system MNPL to verify accuracy of the established sub-relationship SR6.

[0071] The controller **30** may be configured to determine any other suitable sub-relationships. For example, in instances where the manipulator **14** includes more than one robotic arm **18A**, the controller **30** may determine a sub-relationship between the base tracker **52B** and one or more of the robotic arms **18A** to determine the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL. In such instances, one or more of the robotic arms **18A** may be coupled to one or more manipulator trackers **52**, which may be tracked by the localizer **44** during registration of patient anatomy. During registration of patient anatomy, the controller **30** may receive a location of the manipulator trackers **52** to determine a location of the one or more robotic arms **18A** and, furthermore, to determine the sub-relationship between the manipulator coordinate system MNPL, the localizer coordinate system LCLZ, and/or the base tracker **52B** and the one or more robotic arms **18A**.

III. Path Registration

A. Overview

[0072] The controller **30** may be configured to establish the relationship R between the manipulator

coordinate system MNPL and the localizer coordinate system LCLZ by performing path registration.

[0073] Generally, during path registration, the tool tracker **106** and the surgical tool **20** are moved along a path, with the localizer **44** tracking movement of the tool tracker **106** and the manipulator **14** sensing movement of the surgical tool **20**. The controller **30** may then register the manipulator coordinate system MNPL to the localizer coordinate system LCLZ based on localizer data from the localizer **44** and based on the kinematic data from the manipulator **14**. Referring to FIG. **3**, during path registration, the controller **30** may obtain the sub-relationship SR1 from the localizer **44** as the localizer **44** tracks the tool tracker **106** and provides localizer data related to movement of the tool tracker **106**, and the controller **30** may obtain the sub-relationship SR3 from the manipulator **14** as the manipulator **14** senses movement of the surgical tool **20** and provides kinematic data related to movement of the surgical tool **20**. As previously stated, the controller **30** may determine the sub-relationship SR2 between the tool tracker **106** and the surgical tool **20** from predetermined data. The controller **30** may then combine the sub-relationships SR1, SR2, SR3 to obtain the relationship R between the manipulator coordinate system MNPL and the localizer coordinate system LCLZ.

B. Method of Path Registration

[0074] To perform path registration, the controller **30** may execute steps **202-208** of a method **200** of path registration shown in FIG. **4**. As shown in FIG. **4**, during step **202**, the surgical tool **20** and the tool tracker **106** move along a path; during step **204**, the controller **30** may obtain, from the localizer **44**, a localizer dataset related to the tool tracker **106** and being derived from movement of the tool tracker **106** along the path; during step **206**, the controller **30** may obtain, from the manipulator **14**, a kinematic dataset related to the surgical tool **20** and being derived from movement of the surgical tool **20** along the path; and during step **208**, the controller **30** may map the localizer dataset and the kinematic dataset relative to one another to establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL.

[0075] Steps **202-208** may be ordered in any suitable order. For example, in some instances, steps **202-206** occur concurrently such that the controller **30** may control movement of the surgical tool **20** and the tool tracker **106** while obtaining the localizer dataset and the kinematic dataset. As another example, the controller **30** may obtain the localizer dataset during step **204** after the controller **30** obtains the kinematic dataset during step **206**.

i. MOVEMENT OF SURGICAL TOOL AND TOOL TRACKER

[0076] During step **202**, the surgical tool **20** and the tool tracker **106** move along a path. The path used during the method **200** of path registration may be a free-form path FFP defined by a user or a predetermined path defined by the controller **30**.

[0077] During step **202**, the controller **30** may be configured to control, with the robotic arm **18A**, movement of the surgical tool **20** and the tool tracker **106** along the path. For example, the controller **30** may be configured to control, with the robotic arm **18A**, movement of the surgical tool **20** and the tool tracker **106** in response external force provided by a user. In some instances, the external force may be provided by a user **105** to the robotic arm **18A** (as shown in FIG. **1**). In some instances, the external force may be provided by a user **105** to the surgical tool **20** (as shown in FIGS. **5A** and **5B**). The controller **30** receives the external force provided by the user **105** and directs motion of the robotic arm **18A** to move the surgical tool **20** and the tool tracker **106** along a path. In other instances, the controller **30** may be configured to control, with the robotic arm **18A**, automatic movement of the surgical tool **20** and the tool tracker **106**, e.g., along a predetermined path.

[0078] In some instances, during step **202**, the user **105** may control movement of the surgical tool **20** and the tool tracker **106**. For example, in instances where each of the joints (J) are passively driven, the robotic arm **18A** may be moved by an external force applied to the manipulator **14**. In some instances, the external force may be provided by the user **105** to the robotic arm **18A** (as shown in FIG. **1**). In some instances, the external force may be provided the user **105** to the

surgical tool **20** (as shown in FIGS. 5A and 5B). The user **105** provides external force and the provided external force may move the surgical tool **20** and the tool tracker **106** along the path.

a. Types of Paths

[0079] In all instances described herein, the path that the tool tracker **106** and the surgical tool **20** move along may be a free-form path FFP. A free-form path FFP is a path defined by a user in a manner that is unconstrained. For example, the free-form path FFP may be defined by a user without being constrained by virtual constraints generated by the boundary generator **66** and/or path generator **69**. An example free-form path FFP is shown in FIG. 5A. In the instance of FIG. 5A, the free-form path FFP is characterized as a circular path. In other instances, the free-form path FFP may be characterized as any continuous two or three-dimensional path for effecting continuous movement of the surgical tool **20** and the tool tracker **106**. The free-form path FFP may be characterized as a curved line, a straight line, and/or a combination of curved and straight lines. In some instances, the free-form path FFP may intersect itself.

[0080] In some instances, a user may define the free-form path FFP during movement of the tool tracker **106** and the surgical tool **20**. In such instances, the free-form path FFP may be unknown prior to movement of the surgical tool **20** and the tool tracker **106**. For example, the user **105** may define the free-form path FFP by providing an external force to the manipulator **14** to cause continuous movement of the surgical tool **20** and the tool tracker **106**. In such instances, the controller **30** may control, with the robotic arm **18A**, movement of the surgical tool **20** of the manipulator **14** and the tool tracker **106** in response to the external force and the resulting path travelled by the surgical tool **20** and the tool tracker **106** defines the free-form path FFP.

[0081] In some instances, a user may define the free-form path FFP prior to movement of the tool tracker **106** and the surgical tool **20**. For example, the user may define the free-form path FFP using a user interface and/or a computing system to cause continuous movement of the surgical tool **20** and the tool tracker **106**. For instance, the user may draw a line on a user interface (e.g. a tablet or a phone), and the line may be used to define the free-form path FFP. In another instance, the user may draw a line on a computing system using a user interface (e.g. a mouse), and the line may be used to define the free-form path FFP.

[0082] The user may consider any suitable factor when defining the free-form path FFP. For example, the user may define the free-form path FFP to prevent collisions between the manipulator **14**, the surgical tool **20**, and/or the tool tracker **106** with objects in the operating room.

Additionally, or alternatively, the user may define the free-form path FFP while prioritizing generation of the localizer dataset by the localizer **44**, prioritizing generation of the kinematic dataset by the manipulator **14**, and/or prioritizing a speed of the path registration method **200**. For example, the user may define the free-form path FFP such that the tool tracker **106** remains visible to the localizer **44** during the path registration method **200**.

[0083] The controller **30** may provide an instruction and/or suggestion to the user regarding the defined free-form path FFP. The instruction and/or suggestion may be provided on a display device of the system **10**, such as the display **38** in FIG. 1, and/or a user interface. Additionally, the instruction and/or suggestion may occur prior to, during, or after definition of the free-form path FFP by the user. For example, in instances where the controller **30** provides the instruction and/or suggestion during definition of the free-form path FFP, and the free-form path FFP is defined during movement of the surgical tool **20** and the tool tracker **106**, the controller **30** may provide, on the display **38**, a directional arrow instructing and/or suggesting the user **105** to move the surgical tool **20** and tool tracker **106** in a particular direction. In instances where the controller **30** provides the instruction and/or suggestion prior to definition of the free-form path FFP, the controller **30** may provide a sample free-form path FFP' for the user to consider when defining the free-form path FFP. An example of a sample free-form path FFP' is shown in FIG. 1 on the display **38**.

[0084] The controller **30** may provide the instruction and/or suggestion based on preventing collisions between the manipulator **14**, the surgical tool **20**, and/or the tool tracker **106** with objects

in the operating room, prioritizing generation of the localizer dataset by the localizer **44**, prioritizing generation of the kinematic dataset by the manipulator **14**, and/or prioritizing a speed of the path registration method **200**. As an example, the controller **30** may provide an instruction and/or suggestion reflecting a completeness of the free-form path FFP based on a threshold level of accuracy. For instance, the threshold level of accuracy may be based on whether the localizer/kinematic dataset generated/to be generated by the localizer **44**/manipulator **14** includes a sufficient amount of data points (e.g. localized positions P.sub.L/kinematic positions P.sub.M, which will be discussed in greater detail below). The threshold level of accuracy may also be based on an amount of time that the surgical tool **20** and tool tracker **106** has been moved/is to be moved along the free-form path FFP. The threshold level of accuracy may also be based on whether the data points (e.g. localized positions P.sub.L/kinematic positions P.sub.M, which will be discussed in greater detail below) of the localizer/kinematic dataset are sufficiently spaced, or whether the data points are too close to one another. As another example, the controller **30** may provide an instruction and/or suggestion to the user to modify the defined free-form path FFP based on preventing a collision between the manipulator **14**, the surgical tool **20**, and/or the tool tracker **106** with an object in the operating room.

[0085] In all instances described herein, the path that the tool tracker **106** and the surgical tool **20** move along may be a predetermined path. The predetermined path is a path defined by the controller **30**. For example, the predetermined path may be generated by the path generator **68** shown in FIG. **2**. The predetermined path may be characterized as any continuous two or three-dimensional path for effecting continuous movement of the surgical tool **20** and the tool tracker **106**. The predetermined path may be characterized as a curved line, a straight line, and/or a combination of curved and straight lines. In some instances, the predetermined path may intersect itself. In instances where the controller **30** defines the predetermined path, the controller **30** may control, with the robotic arm **18A**, automatic movement of the surgical tool **20** and the tool tracker **106** along the predetermined path. Additionally, in instances where the controller **30** defines the predetermined path, the user **105** may apply an external force to the manipulator in accordance with moving the surgical tool **20** and the tool tracker **106** along the predetermined path, and the controller **30** may control, with the robotic arm **18A**, movement of the surgical tool **20** and the tool tracker **106** along the predetermined path

[0086] In some instances, the predetermined path may be defined prior to or during movement of the surgical tool **20** and the tool tracker **106**. For example, the controller **30** may define movement of the surgical tool **20** and the tool tracker **106** during movement of the surgical tool **20** and the tool tracker **106** such that the surgical tool **20** and the tool tracker **106** avoid collisions with objects detected by the localizer **44**. As another example, the controller **30** may define movement of the surgical tool **20** and the tool tracker **106** prior to movement of the surgical tool **20** and the tool tracker **106** such that the method of path registration **200** is expedited.

[0087] The controller **30** may determine the predetermined path based on any suitable factor. For example, the controller **30** may define the predetermined path to prevent collisions between the manipulator **14**, the surgical tool **20**, and/or the tool tracker **106** with objects in the operating room. Additionally, or alternatively, the controller **30** may define the predetermined path while prioritizing generation of the localizer dataset by the localizer **44**, prioritizing generation of the kinematic dataset by the manipulator **14**, and/or prioritizing a speed of the path registration method **200**. For example, the controller **30** may define the predetermined path such that the tool tracker **106** remains visible to the localizer **44** during the path registration method **200**.

[0088] The controller **30** may provide an instruction and/or suggestion to the user regarding the predetermined path. The instruction and/or suggestion may be provided on a display device of the system **10**, such as the display **38** in FIG. **1**, and/or a user interface. In one example, the controller **30** may provide an instruction and/or suggestion to the user while the user moves the surgical tool **20** and the tool tracker **106** in accordance with the predetermined path. The controller **30** may

provide, on the display **38**, a directional arrow instructing and/or suggesting the user **105** to move the surgical tool **20** and tool tracker **106** to move the surgical tool **20** and tool tracker **106** in accordance with the predetermined path. The controller **30** may also provide an indication of a deviation of the surgical tool **20** and the tool tracker **106** from the predetermined path.

b. Unconstrained Movement

[0089] In some instances, during step **202**, movement of the surgical tool **20** and the tool tracker **106** may be unconstrained by virtual boundaries. In such instances, the controller **30** may control, with the robotic arm **18A**, movement of the surgical tool **20** and the tool tracker **106** in a free mode. For example, during registration of the system **10**, the controller **30** may enter the free mode and disregard virtual boundaries generated by the boundary generator **66**. Advantageously, in instances where the user **105** defines the free-form path FFP during movement of the surgical tool **20** and the tool tracker **106**, the user **105** may provide external force to the manipulator **14** to define the free-form path FFP in a manner that avoids obstructions in the operating room. Movement of the surgical tool **20** and the tool tracker **106** may also be unconstrained in instances where the controller **30** defines the predetermined path. In such instances, though the predetermined path is defined by the controller **30**, movement of the surgical tool **20** and the tool tracker **106** may be unconstrained such that the surgical tool **20** and the tool tracker **106** may deviate from the predetermined path. For example, the user **105** may provide external force to the manipulator **14** in a manner that deviates from the predetermined path to avoid obstructions in the operating room.

[0090] In some instances, during step **202**, movement of the surgical tool **20** and the tool tracker **106** may be constrained. For example, movement of the surgical tool **20** and the tool tracker **106** may be constrained in instances where the controller **30** defines the predetermined path. In some exemplary instances, the user **105** may provide an external force to the manipulator **14** and movement of the surgical tool **20** and the tool tracker **106** may be constrained to the predetermined path. In some exemplary instances, the controller **30** may control, with the robotic arm **18A**, automatic movement of the surgical tool **20** and the tool tracker **106** along the predetermined path such that movement of the surgical tool **20** and the tool tracker **106** are constrained to the predetermined path.

ii. TRACKING MOVEMENT OF TOOL TRACKER AND SENSING MOVEMENT OF SURGICAL TOOL

[0091] The localizer **44** tracks movement of the tool tracker **106** along the path and generates a localizer dataset **108**, shown in FIG. 5B. The localizer dataset **108** is related to the tool tracker **106** and is derived from movement of the tool tracker **106** along the path. The localizer dataset **108** may include a plurality of localized positions $P_{sub.L}$ of the tool tracker **106** (illustrated in FIG. 5B as a “.star-solid.”). The localized positions $P_{sub.L}$ may be derived from movement of the tool tracker **106** along the path. For example, in some instances, each of the localized positions $P_{sub.L}$ may be generated by the localizer **44** as the tool tracker **106** moves along a path. The localizer dataset **108** may additionally, or alternatively, include a localized path $PTH_{sub.L}$ of the tool tracker **106** (illustrated in FIG. 5B as a dot-dash line). The localized path $PTH_{sub.L}$ may be derived from movement of the tool tracker **106** along the path. For example, the localizer **44** may generate localized positions $P_{sub.L}$ as the tool tracker **106** moves along the path and the localizer **44** may then determine the localized path $PTH_{sub.L}$ as a best-fit line based on the localized positions $P_{sub.L}$. In this way, the localizer **44** may remove noise from the localizer dataset **108** when determining the localized path $PTH_{sub.L}$, where the noise may be created by random disturbances of the system **10** and/or by outlier localized positions $P_{sub.L}$ (e.g. when the tool tracker **106** is not visible by the localizer **44**). Additionally, after the localizer **44** determines the localized path $PTH_{sub.L}$, the localizer **44** may generate additional localized positions $P_{sub.L}$ based on the determined localized path $PTH_{sub.L}$. For example, the localizer **44** may sample localized position $P_{sub.L}$ from the determined localized path $PTH_{sub.L}$.

[0092] The manipulator **14** senses movement of the surgical tool **20** along the path and generates a

kinematic dataset **110**, shown in FIG. 5B. The kinematic dataset **110** is related to the surgical tool **20** and is derived from movement of the surgical tool **20** along the path. The kinematic dataset **110** may include a plurality of kinematic positions P.sub.M of the surgical tool **20** (illustrated in FIG. 5B as a “•”). The kinematic positions P.sub.M may be derived from movement of the surgical tool **20** along the path. For example, in some instances, each of the kinematic positions P.sub.M may be generated by the manipulator **14** as the surgical tool **20** moves along the path. The kinematic dataset **110** may additionally, or alternatively, include a kinematic path PTH.sub.M of the surgical tool **20** (illustrated in FIG. 5B as a dot-dash line). The kinematic path PTH.sub.M may be derived from movement of the surgical tool **20** along the path. For example, the manipulator **14** may generate kinematic positions P.sub.M as the surgical tool **20** moves along the path and the manipulator **14** may then determine the kinematic path PTH.sub.M as a best-fit line based on the kinematic positions P.sub.M. In this way, the manipulator **14** may remove noise from the kinematic dataset **110** when determining the kinematic path PTH.sub.M, where the noise may be created by random disturbances of the system **10** and/or by outlier kinematic positions P.sub.M. Additionally, after the manipulator **14** determines the kinematic path PTH.sub.M, the manipulator **14** may generate additional kinematic positions P.sub.M based on the determined kinematic path PTH.sub.M. For example, the manipulator **14** may sample kinematic positions P.sub.M from the determined kinematic path PTH.sub.M.

[0093] The controller **30** obtains the localizer data set **108** and the kinematic dataset **110** during steps **204**, **206**, respectively. As previously stated, the localizer data set **108** may include the localized positions P.sub.L and/or the localized path PTH.sub.L. As follows, during steps **204**, **206**, the controller **30** may obtain the localized positions P.sub.L and/or the localized path PTH.sub.L from the localizer **44**. Similarly, the kinematic data set **110** may include the kinematic positions P.sub.M and/or the kinematic path PTH.sub.M. As follows, during steps **204**, **206**, the controller **30** may obtain the kinematic positions P.sub.M and/or the kinematic path PTH.sub.M from the manipulator **14**.

[0094] In some instances, the controller **30** may generate the localized positions P.sub.L, the localized path PTH.sub.L, the kinematic positions P.sub.M, and/or the kinematic path PTH.sub.M after receiving the localizer dataset **108** during step **204** and after receiving the kinematic dataset **110** during step **206**. For example, the controller **30** may receive the localized positions P.sub.L included in the localizer dataset **108** and determine the localized path PTH.sub.L as a best-fit line based on the received localized positions P.sub.L. The controller **30** may also receive the kinematic positions P.sub.M included in the kinematic dataset **110** and determine the kinematic path PTH.sub.M as a best-fit line based on the received kinematic positions P.sub.M. As another example, the controller **30** may generate additional localized positions P.sub.L and/or additional kinematic positions P.sub.M based on a received or determined localized path PTH.sub.L and/or kinematic path PTH.sub.M, respectively. For instance, the controller **30** may sample localized positions P.sub.L from a received or determined localized path PTH.sub.L and the controller **30** may sample kinematic positions P.sub.M from a received or determined kinematic path PTH.sub.M.

iii. DETERMINING RELATIONSHIP BETWEEN MANIPULATOR COORDINATE SYSTEM AND LOCALIZER COORDINATE SYSTEM

[0095] During step **208**, the controller **30** maps the localizer dataset **108** and the kinematic dataset **110** relative to one another to establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL. The controller **30** may map the localized positions P.sub.L and one of or both of the kinematic positions P.sub.M and kinematic path PTH.sub.M relative to one another. Similarly, the controller **30** may map the localized path PTH.sub.L and one of or both of the kinematic positions P.sub.M and kinematic path PTH.sub.M relative to one another. For example, in an instance where the controller **30** obtains the localized positions P.sub.L and the kinematic positions P.sub.M during steps **204**, **206**, respectively, the controller **30**

may map the localized positions P.sub.L and kinematic positions P.sub.M relative to one another to establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL. In an instance where the controller **30** obtains the localized path PTH.sub.L and the kinematic path PTH.sub.M during steps **204**, **206**, respectively, the controller **30** may map the localized path PTH.sub.L and the kinematic path PTH.sub.M relative to one another to establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL.

[0096] The controller **30** may map the localizer dataset **108** and the kinematic dataset **110** relative to one another such that the localizer dataset **108** and the kinematic dataset **110** are substantially overlaid. For example, the controller **30** may map the localized positions P.sub.L and kinematic positions P.sub.M relative to one another by adjusting either the localized positions P.sub.L or the kinematic positions P.sub.M or both of the localized positions P.sub.L and the kinematic positions P.sub.M such that the localized positions P.sub.L and the kinematic positions P.sub.M are substantially overlaid. As another example, the controller **30** may map the localized path PTH.sub.L and the kinematic path PTH.sub.M relative to one another by adjusting either the localized path PTH.sub.L or the kinematic path PTH.sub.M or both of the localized path PTH.sub.L and the kinematic path PTH.sub.M such that the localized path PTH.sub.L and the kinematic path PTH.sub.M are substantially overlaid. The controller **30** may then establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL based on the adjustment. In a more specific instance, the controller **30** may establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL based on the adjustment and based on the sub-relationship SR2 between the tool tracker **106** and the surgical tool **20**.

iv. OTHER CONSIDERATIONS

[0097] In some instances, the localizer dataset **108** and the kinematic dataset **110** may not be synchronized in time. For example, the controller **30** may obtain the localizer dataset **108** according to a first sampling rate and the kinematic dataset **110** at a second sampling rate different than the first sampling rate, with the first sampling rate being different than the second sampling rate. As another example, the localized and kinematic datasets **108**, **110** may be temporally offset. For instance, the localizer **44** may track movement of the tool tracker **106** after the manipulator **14** begins sensing movement of the surgical tool **20**, or the manipulator **14** may begin sensing movement of the surgical tool **20** before the localizer **44** begins tracking movement of the tool tracker **106**.

[0098] The controller **30** may obtain the localizer dataset **108** according to a first sampling rate and the kinematic dataset **110** at a second sampling rate different than the first sampling rate. In such instances, the localizer **44** may track movement of the tool tracker **106** at the first sampling rate and generate the localized dataset **108** accordingly. For instance, the localizer **44** may generate the localized positions P.sub.L during movement of the tool tracker **106** according to the first sampling rate. Similarly, the manipulator **14** may sense movement of the surgical tool **20** at the second sampling rate and generate the kinematic dataset **110** accordingly. For instance, the manipulator **14** may generate the kinematic positions P.sub.M at the second sampling rate. In some instances, the second sampling rate may exhibit latency relative to the first sampling rate. For example, the manipulator **14** may sense movement of the surgical tool **20** at a slower rate than the localizer **44** tracks movement of the tool tracker **106**. In other instances, the first sampling rate may exhibit latency relative to the second sampling rate. For example, the manipulator **14** may sense movement of the surgical tool **20** at a faster rate than the localizer **44** tracks movement of the tool tracker **106**. Such an instance is shown in FIG. 5C. As shown, while the surgical tool **20** and the tool tracker **106** move along the path, the localizer **44** generates three localized positions P.sub.L1-P.sub.L3 and the manipulator **14** generates four kinematic positions P.sub.M1-P.sub.M4.

[0099] The localized and kinematic datasets **108**, **110** may be temporally offset. The localizer and

kinematic datasets **108**, **110** may be generated accordingly such that the localized/kinematic position P.sub.L, P.sub.M are temporally offset. In such instances, the localized positions PL and the kinematic positions PM are not captured by the localizer **44** and the manipulator **14**, respectively, at the same time.

[0100] During step **208**, the controller **30** may map the localizer dataset **108** and the kinematic dataset **110** relative to one another to offset a latency between the first sampling rate and the second sampling rate and to remove any temporal offset between the localizer dataset **108** and the kinematic dataset **110**. In this way, the controller **30** minimizes potential error that may result from the latency and the temporal offset. In instances including a latency between the first sampling rate and the second sampling rate, the localized and kinematic datasets **108**, **110** may include a different number of localized and kinematic positions P.sub.L, P.sub.M. In instances including a temporal offset exists between the localizer dataset **108** and the kinematic dataset **110**, the localized and kinematic positions P.sub.L, P.sub.M may be offset from one another. In both instances, the controller **30** may be configured to offset the latency and remove the temporal offset by mapping projected kinematic/localized positions and the localized/kinematic position P.sub.L, P.sub.M relative to one another. Instances where a unique localized or kinematic position P.sub.M, P.sub.L is mapped to a unique projected point may be referred to as “point-to-point” registration.

[0101] Referring to FIG. 5D, the controller **30** and/or the manipulator **14** may generate three projected kinematic positions P.sub.PROJ_M1-P.sub.PROJ_M3 corresponding to the three localized positions P.sub.L1-P.sub.L3 of FIG. 5C. The projected kinematic positions P.sub.PROJ_M1-P.sub.PROJ_M3 may be generated as points along the kinematic path PTH.sub.M. In some instances, the projected kinematic positions P.sub.PROJ_M1-P.sub.PROJ_M3 may be generated such that, after the localized positions P.sub.L and the projected kinematic positions are mapped to one another, a distance between the projected kinematic positions and the corresponding localized positions P.sub.L is minimized. FIG. 5D illustrates an instance where a distance between the projected kinematic positions P.sub.PROJ_M1-P.sub.PROJ_M3 and the three localized positions P.sub.L1-P.sub.L3 is minimized after mapping. The controller **30** may then map the projected kinematic positions P.sub.PROJ_M1-P.sub.PROJ_M3 and the three localized positions P.sub.L1-P.sub.L3 to establish the relationship R between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL.

[0102] Similarly, the controller **30** may be configured to offset the latency between the first sampling rate and the second sampling rate and to remove any temporal offset between the localizer dataset **108** and the kinematic dataset **110** based on mapping the projected localized positions and the kinematic positions P.sub.M relative to one another. The controller **30** and/or the localizer **44** may generate projected localized positions corresponding to the kinematic positions P.sub.M.

[0103] The projected kinematic/localized positions may be generated as points along the kinematic/localized path PTH.sub.M, PTH.sub.L, respectively. As previously stated, the kinematic/localized paths PTH.sub.M, PTH.sub.L may be derived from movement of the tool tracker **106** along the path. Specifically, the kinematic/localized paths PTH.sub.M, PTH.sub.L may be based on kinematic/localized positions P.sub.M, P.sub.L. In this way, although projected kinematic/localized positions may be mapped to localized/kinematic positions PTH.sub.L, PTH.sub.M, respectively, by the controller **30**, the kinematic and localized positions P.sub.M, P.sub.L are still considered by the controller **30** as part of the mapping.

[0104] Advantageously, the method **200** of path registration does not require the surgical tool **20** and the tool tracker **106** to be held static by the user at predetermined positions of the surgical tool **20** and the tool tracker **106** defined by the controller **30** for the controller **30** to determine a relationship between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL. In other words, during the method **200**, the surgical tool **20** and the tool tracker **106** may move continuously along the previously described free-form path FFP or the previously described

predetermined path without being held static at predetermined positions, and the controller **30** is able to determine the relationship between the localizer coordinate system LCLZ and the manipulator coordinate system MNPL. Contrastingly, in instances where the controller **30** defines predetermined positions of the surgical tool **20** and the tool tracker **106**, the localizer **44** tracks a position of the tool tracker **106** and the manipulator **14** senses a position of the surgical tool **20** at the predetermined positions. In one such instance, a user of the system causes movement of the surgical tool **20** and the tool tracker **106** along a path where the surgical tool **20** and the tool tracker **106** are statically held at predetermined positions where the localizer **44** is able to track the position of the tool tracker **106** to generate the localizer dataset, and where the manipulator **14** is able to sense the position of the surgical tool **20** to generate the kinematic dataset. However, during the method **200**, the controller **30** need not require predetermined positions of the surgical tool **20** and the tool tracker **106** as the localizer **44** is able to track the tool tracker **106** to generate the localizer dataset **108** and the manipulator **14** is able to sense movement of the surgical tool **20** to generate the kinematic dataset **110** during continuous movement of the surgical tool **20** and the tool tracker **106** along a path (e.g. the previously described free-form path FFP or the previously described predetermined path). The controller then maps the localizer dataset **108** and the kinematic dataset **110** relative to one another to establish the relationship R between the localizer coordinate system LCLZ and the base coordinate system MNPL.

[0105] The method **200** of path registration may also include any suitable steps described in U.S. patent application Ser. No. 17/513,324, entitled “Robotic Surgical System with Motorized Movement to a Starting Pose for a Registration or Calibration Routine”, which is incorporated herein by reference. For example, the method **200** may additionally include the steps described in the process **500** for providing a motorized movement of the robotic arm to a starting pose for a registration or calibration routine for the robotic arm, as described in U.S. patent application Ser. No. 17/513,324.

[0106] Although specific features of various embodiments of the disclosure may be shown in some drawings and not in others, this is for convenience only. In accordance with the principles of the disclosure, any feature of a drawing or other embodiment may be referenced and/or claimed in combination with any feature of any other drawing or embodiment.

[0107] This written description uses examples to describe embodiments of the disclosure and also to enable any person skilled in the art to practice the embodiments, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the disclosure is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal language of the claims.

Claims

1. A surgical system comprising: a manipulator including: a base establishing a base coordinate system; a robotic arm coupled to the base and being formed of links and joints; and a tool coupled to the robotic arm; a navigation system including: a base tracker coupled to the manipulator; a tool tracker configured to be coupled to the tool; and a localizer configured to track positions of the base tracker and the tool tracker in a localizer coordinate system; and a control system coupled to the manipulator and the navigation system and being configured to: control, with the robotic arm, movement of the tool and the tool tracker along a free-form path; obtain, from the localizer, a localizer dataset related to the tool tracker and being derived from movement of the tool tracker along the free-form path; obtain, from the manipulator, a kinematic dataset related to the tool and being derived from movement of the tool along the free-form path; and map the localizer dataset and the kinematic dataset relative to one another to establish a relationship between the localizer

coordinate system and the base coordinate system.

2. The surgical system of claim 1, wherein the control system is configured to control, with the robotic arm, movement of the tool and the tool tracker in response external force applied to the tool by a user.

3. The surgical system of claim 2, wherein the free-form path is defined during movement of the tool and the tool tracker by the user, and the free-form path is unknown prior to movement of the tool and the tool tracker.

4. The surgical system of claim 2, wherein the free-form path is defined by continuous movement of the tool and the tool tracker by the user and without requiring the tool and the tool tracker to be held static by the user at predetermined positions defined by the control system.

5. The surgical system of claim 2, further comprising a display device, and wherein the control system is configured to provide, on the display device, an instruction or suggestion for the user for moving the tool.

6. The surgical system of claim 1, wherein the control system is further configured to control, with the robotic arm, movement of the tool and the tool tracker in a free mode whereby movement of the manipulator is unconstrained by a virtual boundary.

7. The surgical system of claim 1, wherein the control system maps the localizer dataset and the kinematic dataset relative to one another by further being configured to: obtain, from the localizer dataset, a plurality of localized positions of the tool tracker being derived from movement of the tool tracker along the free-form path; obtain, from the kinematic dataset, a plurality of kinematic positions of the tool being derived from movement of the tool along the free-form path; and map the localized positions and kinematic positions relative to one another to establish the relationship between the localizer coordinate system and the base coordinate system.

8. The surgical system of claim 1, wherein the control system maps the localizer dataset and the kinematic dataset relative to one another by further being configured to: obtain, from the localizer dataset, a localized path related to the tool tracker and being derived from movement of the tool tracker along the free-form path; obtain, from the kinematic dataset, a kinematic path related to the tool and being derived from movement of the tool along the free-form path; and map the localized path and the kinematic path relative to one another to establish the relationship between the localizer coordinate system and the base coordinate system.

9. The surgical system of claim 1, wherein the control system is further configured to: obtain the localizer dataset according to a first sampling rate; and obtain the kinematic dataset according to a second sampling rate being different than the first sampling rate; and map the localizer dataset and the kinematic dataset relative to one another to offset a latency between the first sampling rate and the second sampling rate.

10. The surgical system of claim 9, wherein the first sampling rate exhibits the latency relative to the second sampling rate.

11. The surgical system of claim 1, wherein the control system establishes the relationship between the localizer coordinate system and the base coordinate system by being configured to: obtain a first relationship between the localizer coordinate system and the tool tracker from the localizer; obtain a second relationship between the tool tracker and the tool from predetermined data; obtain a third relationship between the tool and the base coordinate system from kinematic data of the manipulator; and combine the first, second, and third relationships.

12. The surgical system of claim 11, wherein the control system is further configured to: obtain a fourth relationship between the base tracker and the localizer coordinate system from the localizer; and combine the first, second, third, and fourth relationships to establish a fifth relationship between the base tracker and the base coordinate system.

13. The surgical system of claim 1, wherein: the manipulator comprises a cart that supports the robotic arm; the base coordinate system is established relative to the cart; and the base tracker is coupled to the cart by an adjustable support arm that extends from the cart.

14. The surgical system of claim 12, wherein: the base coordinate system is determinable relative to the robotic arm; and the base tracker is coupled to the robotic arm and is moveable with the robotic arm.

15. The surgical system of claim 14, wherein the control system is configured to: obtain a predetermined relationship between the base tracker and the base coordinate system from kinematic data related to the manipulator; and compare the established fifth relationship between the base tracker and the base coordinate system with the predetermined relationship between the base tracker and the base coordinate system to verify accuracy of the established fifth relationship.

16. A method of operating a surgical system, the surgical system comprising a manipulator including a base establishing a base coordinate system, a robotic arm coupled to the base and being formed of links and joints, and a tool coupled to the robotic arm, and a navigation system including a base tracker coupled to the manipulator, a tool tracker coupled to the tool, and a localizer configured to track positions of the base tracker and the tool tracker in a localizer coordinate system, and a control system coupled to the manipulator and the navigation system, the method comprising the control system performing the following steps: controlling, with the robotic arm, movement of the tool and the tool tracker along a free-form path; obtaining, from the localizer, a localizer dataset related to the tool tracker and being derived from movement of the tool tracker along the free-form path; obtaining, from the manipulator, a kinematic dataset related to the tool and being derived from movement of the tool along the free-form path; and mapping the localizer dataset and the kinematic dataset relative to one another for establishing a relationship between the localizer coordinate system and the base coordinate system.

17. The method of claim 16, comprising the control system controlling, with the robotic arm, movement of the tool and the tool tracker in response external force applied to the tool by a user.

18. The method of claim 17, comprising the control system defining the free-form path during movement of the tool and the tool tracker by the user, and wherein the free-form path is unknown prior to movement of the tool and the tool tracker.

19. The method of claim 17, comprising the control system defining the free-form path by continuous movement of the tool and the tool tracker by the user and without requiring the tool and the tool tracker to be held static by the user at predetermined positions defined by the control system.

20. A surgical system comprising: a manipulator including: a base establishing a base coordinate system; an arm coupled to the base and being formed of links and joints; and a tool coupled to the arm; a navigation system including: a base tracker coupled to the manipulator; a tool tracker configured to be coupled to the tool; and a localizer configured to track positions of the base tracker and the tool tracker in a localizer coordinate system; and a control system coupled to the manipulator and the navigation system and being configured to: obtain, from the localizer, a localizer dataset related to the tool tracker and being derived from movement of the tool tracker along a free-form path; obtain, from the manipulator, a kinematic dataset related to the tool and being derived from movement of the tool along the free-form path; and map the localizer dataset and the kinematic dataset relative to one another to establish a relationship between the localizer coordinate system and the base coordinate system.
