

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250255768

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Mooney; Luke et al.

SYSTEMS AND METHODS FOR AN ACTIVE EXOSKELETON WITH LOCAL BATTERY

Abstract

A method includes providing a battery holder of an ankle-foot exoskeleton wearable on a lower limb of a user, the battery holder configured to be disposed at the lower limb of the user and configured to receive a battery. The method includes providing an actuator of the ankle-foot exoskeleton, the actuator configured to receive power from the battery and generate torque about an axis of rotation of the lower limb. The method includes providing one or more housings of the ankle-foot exoskeleton, the one or more housings enclosing electronic circuitry configured to control delivery of the power from the battery to the actuator.

Inventors: Mooney; Luke (Sudbury, MA), Duval; Jean-François (Belmont, MA), Benz; Nicholas (Belmont, MA), Cummings; Jonathan (Concord, MA), Mooney; Matthew (Westford, MA)

Applicant: Dephy, Inc. (Boxborough, MA)

Family ID: 1000008574950

Assignee: Dephy, Inc. (Boxborough, MA)

Appl. No.: 19/195539

Filed: April 30, 2025

Related U.S. Application Data

parent US continuation 18244802 20230911 parent-grant-document US 12336953 child US 19195539

parent US continuation 17526454 20211115 parent-grant-document US 11752061 child US 18244802

parent US continuation 17022982 20200916 parent-grant-document US 11173093 child US 17526454

Publication Classification

Int. Cl.: **A61H3/00** (20060101); **A61F5/00** (20060101); **B25J9/00** (20060101); **B25J9/16** (20060101); **B25J19/00** (20060101); **H02P1/00** (20060101)

U.S. Cl.:

CPC **A61H3/00** (20130101); **A61F5/00** (20130101); **B25J9/0006** (20130101); **B25J9/16** (20130101); **B25J19/005** (20130101); **H02P1/00** (20130101); **B25J9/0009** (20130101)

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS [0001] This application claims the benefit of priority under 35 U.S.C. § 120 as a continuation of U.S. patent application Ser. No. 18/244,802, filed Sep. 11, 2023, which claims the benefit of priority under 35 U.S.C. § 120 as a continuation of U.S. patent application Ser. No. 17/526,454, filed Nov. 15, 2021, which claims the benefit of priority under 35 U.S.C. § 120 as a continuation of U.S. patent application Ser. No. 17/022,982, filed Sep. 16, 2020, each of which is hereby incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0003] The present disclosure generally relates to the field of exoskeletons.

BACKGROUND

[0004] Exoskeletons can be worn by a user to facilitate movement of limbs of the user.

SUMMARY

[0005] At least one aspect of the present disclosure is directed to an apparatus for a battery-powered active exoskeleton boot. The apparatus can include a shin pad to be coupled to a shin of a user below a knee of the user. The apparatus can include one or more housings enclosing electronic circuitry and an electric motor that can generate torque about an axis of rotation of an ankle joint of the user. At least one of the one or more housings can be coupled to the shin pad below the knee of the user. The apparatus can include a battery holder coupled to the shin pad. The battery holder can be located below the knee of the user and above the one or more housings enclosing the electronic circuitry. The apparatus can include a battery module held in the battery holder. The battery module can include a first power connector that electrically couples to a second power connector located in the battery holder to provide electric power to the electronic circuitry and the electric motor. The apparatus can include an output shaft coupled to the electric motor and extending through a bore in a housing of the one or more housings enclosing the electric motor. The electronic circuitry can control delivery of power from the battery module to the electric motor to generate torque about the axis of rotation of the ankle joint of the user.

[0006] Another aspect of the present disclosure is directed to a system for a battery-powered active exoskeleton boot. The system can include a shin pad of an exoskeleton to be coupled to a shin of a user below a knee of the user. The system can include one or more housings enclosing electronic circuitry and an electric motor that can generate torque about an axis of rotation of an ankle joint of the user. At least one of the one or more housings can be coupled to the shin pad below the knee of the user. The system can include a battery module held by the exoskeleton below the knee of the user and above the one or more housing enclosing the electronic circuitry. The battery module can include a first power connector that electrically couples to a second power connector to provide electric power to the electronic circuitry and the electric motor. The system can include one or more processors. The one or more processors can receive data corresponding to a performance of

the battery module. The data can include one or more of a temperature, current, voltage, battery percentage. The one or more processors can determine, based on a safety policy, to trigger a safety action. The one or more processors can instruct, based on the safety action, the electronic circuitry to adjust an amount of power delivered from the battery module to the electric motor to adjust an amount of torque generated about the axis of rotation of the ankle joint of the user.

[0007] Another aspect of the present disclosure is directed to a method of augmenting user motion. The method can include providing a battery-powered active exoskeleton boot. The battery-powered active exoskeleton boot can include a shin pad to be coupled to a shin of a user below a knee of the user. The battery-powered active exoskeleton boot can include one or more housings enclosing electronic circuitry and an electric motor that can generate torque about an axis of rotation of an ankle joint of the user. At least one of the one or more housings can be coupled to the shin pad below the knee of the user. The battery-powered active exoskeleton boot can include a battery holder coupled to the shin pad. The battery holder can be located below the knee of the user and above the one or more housings enclosing the electronic circuitry. The battery-powered active exoskeleton boot can include a battery module held in the battery holder. The battery module can include a first power connector that electrically couples to a second power connector located in the battery holder while attached to the battery holder to provide electric power to the electronic circuitry and the electric motor. The battery-powered active exoskeleton boot can include an output shaft coupled to the electric motor and extending through a bore in a housing of the one or more housings enclosing the electric motor. The electronic circuitry can control delivery of power from the battery module to the electric motor to generate torque about the axis of rotation of the ankle joint of the user.

[0008] Those skilled in the art will appreciate that the summary is illustrative only and is not intended to be in any way limiting. Other aspects, inventive features, and advantages of the devices and/or processes described herein, as defined solely by the claims, will become apparent in the detailed description set forth herein and taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The details of one or more implementations of the subject matter described in this specification are set forth in the accompanying drawings and the description below. Other features, aspects, and advantages of the subject matter will become apparent from the description, the drawings, and the claims.

[0010] FIG. 1 illustrates a schematic diagram of an exoskeleton, according to an embodiment.

[0011] FIG. 2 illustrates a schematic diagram of an exoskeleton, according to an embodiment.

[0012] FIG. 3 illustrates a schematic diagram of a battery module, according to an embodiment.

[0013] FIG. 4 illustrates a cross-section of a battery module, according to an embodiment.

[0014] FIG. 5 illustrates a schematic diagram of a battery module, according to an embodiment.

[0015] FIG. 6 illustrates a schematic diagram of a printed circuit board of a battery module, according to an embodiment.

[0016] FIG. 7 illustrates a schematic diagram of the printed circuit board of a battery module, according to an embodiment.

[0017] FIG. 8 illustrates a schematic diagram of a battery module, according to an embodiment.

[0018] FIG. 9 illustrates a schematic diagram of a battery module, according to an embodiment.

[0019] FIG. 10 illustrates a cross-section of a battery module, according to an embodiment.

[0020] FIG. 11 illustrates a cross-section of a battery module, according to an embodiment.

[0021] FIG. 12A illustrates a schematic diagram of an exoskeleton, according to an embodiment.

[0022] FIG. 12B illustrates a schematic diagram of a battery management system, according to an

embodiment.

[0023] FIG. **13** illustrates a schematic diagram of an exoskeleton, according to an embodiment.

[0024] FIG. **14** illustrates a schematic diagram of the exoskeleton and internal parts, according to an embodiment.

[0025] FIG. **15** illustrates a side view of an exoskeleton, according to an embodiment.

[0026] FIG. **16** illustrates a schematic diagram of an exoskeleton, according to an embodiment.

[0027] FIG. **17** illustrates a schematic diagram of an exoskeleton and internal parts, according to an embodiment.

[0028] FIG. **18** illustrates a schematic diagram of an exoskeleton and internal parts, according to an embodiment.

[0029] FIG. **19** illustrates a side view of an exoskeleton, according to an embodiment.

[0030] FIG. **20** illustrates a side view of an exoskeleton, according to an embodiment.

[0031] FIG. **21** illustrates a method of augmenting user motion, according to an embodiment.

[0032] FIG. **22** illustrates a schematic diagram of the exoskeleton and an integrated battery module, according to an embodiment.

[0033] FIG. **23** illustrates a schematic diagram of the exoskeleton and an integrated battery module, according to an embodiment.

[0034] FIG. **24** illustrates a schematic diagram of the exoskeleton and an integrated battery module, according to an embodiment.

[0035] FIG. **25** illustrates a schematic diagram of the exoskeleton and an integrated battery module, according to an embodiment.

[0036] FIG. **26** illustrates a block diagram of an architecture for a computing system employed to implement various elements of the system and methods depicted in FIGS. **1-25**, according to an embodiment.

[0037] Like reference numbers and designations in the various drawings indicate like elements.

DETAILED DESCRIPTION

[0038] This disclosure relates generally to performance enhancing wearable technologies.

Particularly, this disclosure relates to apparatuses, systems, and methods for an active exoskeleton with a local battery. The local battery can include an onboard power source that is used to power electronics and one or more actuators.

I. Exoskeleton Overview

[0039] Exoskeletons (e.g., battery-powered active exoskeleton, battery-powered active exoskeleton boot, lower limb exoskeleton, knee exoskeleton, or back exoskeleton) can include devices worn by a person to augment physical abilities. Exoskeletons can be considered passive (e.g., not requiring an energy source such as a battery) or active (e.g., requiring an energy source to power electronics and usually one or many actuators). Exoskeletons may be capable of providing large amounts of force, torque and/or power to the human body in order to assist with motion.

[0040] Exoskeletons can transfer energy to the user or human. Exoskeletons may not interfere with the natural range of motion of the body. For example, exoskeletons can allow a user to perform actions (e.g., walking, running, reaching, or jumping) without hindering or increasing the difficulty of performing these actions. Exoskeletons can reduce the difficulty of performing these actions by reducing the energy or effort the user would otherwise exert to perform these actions. Exoskeletons can convert the energy into useful mechanical force, torque, or power. Onboard electronics (e.g., controllers) can control the exoskeleton. Output force and torque sensors can also be used to make controlling easier.

[0041] FIG. **1** illustrates a schematic diagram of an exoskeleton **100**. The exoskeleton **100** can be referred to as a lower limb exoskeleton, lower limb exoskeleton assembly, lower limb exoskeleton system, ankle exoskeleton, ankle foot orthosis, knee exoskeleton, hip exoskeleton, exoskeleton boot, or exoboot. The exoskeleton **100** can include a water resistant active exoskeleton boot. For example, the exoskeleton **100** can resist the penetration of water into the interior of the exoskeleton

100. The exoskeleton **100** can include a water resistant active exoskeleton boot. For example, the exoskeleton **100** can be impervious to liquids (e.g., water) and non-liquids (e.g., dust, dirt, mud, sand, or debris). The exoskeleton **100** can remain unaffected by water or resist the ingress of water, such as by decreasing a rate of water flow into the interior of the exoskeleton **100** to be less than a target rate indicative of being water resistant or waterproof. For example, the exoskeleton **100** can operate in 3 feet of water for a duration of 60 minutes. The exoskeleton **100** can have an ingress protection rating (IP) rating of 68. The exoskeleton **100** can have a National Electrical Manufacturer Association (NEMA) rating of 4×, which can indicate that the exoskeleton **100** has a degree of protection with respect to harmful effects on the equipment due to the ingress of water (e.g., rain, sleet, snow, splashing water, and hose directed water), and that the exoskeleton can be undamaged by the external formation of ice on the enclosure.

[0042] The exoskeleton **100** can include a shin pad **125** (e.g., shin guard). The shin pad **125** can be coupled to a shin of a user below a knee of the user. The shin pad **125** can be coupled to the shin of the user to provide support. The shin pad **125** can include a piece of equipment to protect the user from injury. For example, the shin pad **125** can protect the lower extremities of the user from external impact. The shin pad **125** can interface with the shin of the user. The shin pad **125** can include a band (e.g., adjustable band) configured to wrap around the shin of the user. The shin pad **125** can secure the upper portion of the exoskeleton **100** to the body of the user. The shin pad **125** can secure or help secure the exoskeleton **100** to the shin, leg, or lower limb of the user. The shin pad **125** can provide structural integrity to the exoskeleton **100**. The shin pad **125** can support other components of the exoskeleton **100** that can be coupled to the shin pad **125**. The shin pad **125** can be made of lightweight, sturdy, and/or water resistant materials. For example, the shin pad **125** can be made of plastics, aluminum, fiberglass, foam rubber, polyurethane, and/or carbon fiber.

[0043] The exoskeleton **100** can include one or more housings **105**. At least one of the one or more housings **105** can be coupled to the shin pad **125** below the knee of the user. The shin pad **125** can be coupled to the at least one housing via a shin lever. The shin lever can extend from the at least one housing to the shin pad **125**. The shin lever can include a mechanical structure that connects the shin pad **125** to a chassis. The chassis can include a mechanical structure that connects static components.

[0044] The one or more housings **105** can enclose electronic circuitry (e.g., electronic circuitry **1405**). The one or more housings **105** can encapsulate some or all the electronics of the exoskeleton **100**. The one or more housings **105** can include an electronics cover (e.g., case). The one or more housings **105** can enclose an electric motor (e.g., motor **1230**). The electric motor can generate torque about an axis of rotation of an ankle joint of the user. The ankle joint can allow for dorsiflexion and/or plantarflexion of the user's foot. The exoskeleton **100** can include an ankle joint component **120** that rotates about the axis of rotation the ankle joint. The ankle joint component **120** can be positioned around or adjacent to the ankle joint.

[0045] The exoskeleton **100** can include a rotary encoder **155** (e.g., shaft encoder, first rotary encoder, or motor encoder). The rotary encoder **155** can be enclosed within the one or more housings **105**. The rotary encoder **155** can measure an angle of the electric motor. The angle of the electric motor can be used by the controller to determine an amount of torque applied by the exoskeleton **100**. For example, the angle of the electric motor can correspond to an amount of torque applied by the exoskeleton **100**. An absolute angle of the electric motor can correspond to an amount of torque applied by the exoskeleton **100**. The rotary encoder **155** can include an inductive encoder. The ankle joint component **120** can be actuated by a motor (e.g., electric motor). The rotary encoder **155** can include a contactless magnetic encoder or an optical encoder.

[0046] The exoskeleton **100** can include a second rotary encoder **160** (e.g., ankle encoder). The second rotary encoder **160** can measure an angle of the ankle joint. The angle of the ankle joint can be used by the controller to determine an amount of torque applied by the exoskeleton **100**. The second rotary encoder **160** can include a first component enclosed in the one or more housings **105**

and in communication with the electronic circuitry **1405**. The second rotary encoder **160** can include a second component located outside the one or more housings **105** and configured to interact with the first component. The second rotary encoder **160** can include a contactless magnetic encoder, a contactless inductive encoder, or an optical encoder. The second rotary encoder **160** can detect the angle of the ankle joint while the rotary encoder **155** can detect the angle of the electric motor. The angle of the electric motor can be different from the angle of the ankle joint. The angle of the electric motor can be independent of the angle of the ankle joint. The angle of the ankle joint can be used to determine an output (e.g., torque) of the electric motor. The ankle joint component **120** can be coupled to the second rotary encoder **160**.

[0047] The one or more housings **105** can encapsulate electronics that are part of the exoskeleton **100**. The one or more housings **105** can form a fitted structure (e.g., clamshell structure) to enclose the electronic circuitry and the electric motor. The fitted structure can be formed from two or more individual components. The individual components of the fitted structure can be joined together to form a single unit. The one or more housings **105** can be formed of plastic or metal (e.g., aluminum). An adhesive sealant can be placed between individual components of the fitted structure and under the electronics cover. A gasket can be placed between individual components of the fitted structure and under the electronics cover. The gasket can be placed in the seam between the individual components of the fitted structure.

[0048] A sealant **165** can be placed in contact with the one or more housings **105** to close the one or more housings **105** and prevent an ingress of water into the one or more housings **105**. The sealant **165** used to close the one or more housings **105** can include an adhesive sealant (e.g., super glue, epoxy resin, or polyvinyl acetate). The adhesive sealant can include a substance used to block the passage of fluids through the surface or joints of the one or more housings **105**. The sealant **165** used to close the one or more housings **105** can include epoxy. The sealant **165** can permanently seal or close the one or more housings **105**. For example, the sealant **165** can seal or close the one or more housings **105** such that the one or more housings are not removably attached to one another.

[0049] The exoskeleton **100** can couple with a boot **110**. For example, the exoskeleton **100** can be attached to the boot **110**. The boot **110** can be worn by the user. The boot **110** can be connected to the exoskeleton **100**. The exoskeleton **100** can be compatible with different boot shapes and sizes.

[0050] The exoskeleton **100** can include an actuator **130** (e.g., actuator lever arm, or actuator module). The actuator **130** can include one or more of the components in the exoskeleton **100**. For example, the actuator **130** can include the one or more housings **105**, the footplate **115**, the ankle joint component **120**, the actuator belt **135**, and the post **150**, while excluding the boot **110**. The boot **110** can couple the user to the actuator **130**. The actuator **130** can provide torque to the ground and the user.

[0051] The exoskeleton **100** can include a footplate **115** (e.g., carbon insert, carbon shank). The footplate **115** can include a carbon fiber structure located inside of the sole of the boot **110**. The footplate **115** can be made of a carbon-fiber composite. The footplate **115** can be inserted into the sole of the boot **110**. The footplate **115** can be used to transmit torque from the actuator **130** to the ground and to the user. The footplate **115** can be located in the sole of the exoskeleton **100**. This footplate **115** can have attachment points that allow for the connection of the exoskeleton's mechanical structure. An aluminum insert with tapped holes and cylindrical bosses can be bonded into the footplate **115**. This can create a rigid mechanical connection to the largely compliant boot structure. The bosses provide a structure that can be used for alignment. The footplate **115** can be sandwiched between two structures, thereby reducing the stress concentration on the part. This design can allow the boot to function as a normal boot when there is no actuator **130** attached.

[0052] The exoskeleton **100** can include an actuator belt **135** (e.g., belt drivetrain). The actuator belt **135** can include a shaft that is driven by the motor and winds the actuator belt **135** around itself. The actuator belt **135** can include a tensile member that is pulled by the spool shaft and

applies a force to the ankle lever. Tension in the actuator belt **135** can apply a force to the ankle lever. The exoskeleton **100** can include an ankle lever. The ankle lever can include a lever used to transmit torque to the ankle. The exoskeleton **100** can be used to augment the ankle joint.

[0053] The exoskeleton **100** can include a power button **140** (e.g., switch, power switch). The power button **140** can power the electronics of the exoskeleton **100**. The power button **140** can be located on the exterior of the exoskeleton **100**. The power button **140** can be coupled to the electronics in the interior of the exoskeleton **100**. The power button **140** can be electrically connected to an electronic circuit. The power button **140** can include a switch configured to open or close the electronic circuit. The power button **140** can include a low-power, momentary push-button configured to send power to a microcontroller. The microcontroller can control an electronic switch.

[0054] The exoskeleton **100** can include a battery holder **170** (e.g., charging station, dock). The battery holder **170** can be coupled to the shin pad **125**. The battery holder **170** can be located below the knee of the user. The battery holder **170** can be located above the one or more housings **105** enclosing the electronic circuitry. The exoskeleton **100** can include a battery module **145** (e.g., battery). The battery holder **170** can include a cavity configured to receive the battery module **145**. A coefficient of friction between the battery module **145** and the battery holder **170** can be established such that the battery module **145** is affixed to the battery holder **170** due to a force of friction (e.g., frictional force) based on the coefficient of friction and a force of gravity. The coefficient of friction can include values in a range of 0.5 and 1. For example, the coefficient of friction between the battery module **145** and the battery holder **170** can include 0.5, 0.6, 0.7, 0.8, 0.9, or 1, inclusive. The frictional force can include values in a range of 1 newtons (N) and 10 newtons. For example, the frictional force can include 1 N, 2 N, 3 N, 4 N, 5 N, 6 N, 7 N, 8 N, 9 N, or 10 N, inclusive. The battery module **145** can be affixed to the battery holder **170** absent a mechanical button or mechanical latch. The battery module **145** can be affixed to the battery holder **170** via a lock, screw, or toggle clamp. The battery holder **170** and the battery module **145** can be an integrated component (e.g., integrated battery). The integrated battery can be supported by a frame of the exoskeleton **100** as opposed to having a separated enclosure. The integrated battery can include a charging port. For example, the charging port can include a barrel connector or a bullet connector. The integrated battery can include cylindrical cells or prismatic cells.

[0055] The battery module **145** can power the exoskeleton **100**. The battery module **145** can include one or more electrochemical cells. The battery module **145** can supply electric power to the exoskeleton **100**. The battery module **145** can include a power source (e.g., onboard power source). The power source can be used to power electronics and one or more actuators. The battery module **145** can include a battery pack. The battery pack can be coupled to the one or more housings **105** below a knee of the user. The battery pack can include an integrated battery pack. The integrated battery pack can remove the need for power cables, which can reduce the snag hazards of the system. The integrated battery pack can allow the system to be a standalone unit mounted to the user's lower limb. The battery module **145** can include a battery management system **1224** to perform various operations. For example, the system can optimize the energy density of the unit, optimize the longevity of the cells, and enforce safety protocols to protect the user.

[0056] The battery module **145** can include a removable battery. The battery module **145** can be referred to as a local battery because it is located on the exoboot **100** (e.g., on the lower limb or below the knee of the user), as opposed to located on a waist or back of the user. The battery module **145** can include a weight-mounted battery, which can refer to the battery being held in place on the exoboos **100** via gravity and friction, as opposed to a latching mechanism. The battery module **145** can include a water resistant battery or a waterproof battery. The exoskeleton **100** and the battery module **145** can include water resistant connectors. The weight of the battery module **145** can include values in a range of 250 grams to 280 grams. For example, the weight of the battery module **145** can include 250 grams, 255 grams, 260 grams, 265 grams, 270 grams, 275

grams, or 280 grams, inclusive.

[0057] The battery module **145** can include a high-side switch (e.g., positive can be interrupted). The battery module **145** can include a ground that is always connected. The battery module **145** can include light emitting diodes (LEDs). For example, the battery module **145** can include three LEDs used for a user interface. The LEDs can be visible from one lens so that the LEDs appear as one multicolor LED. The LEDs can blink in various patterns and/or colors to communicate a state of the battery module **145** (e.g., fully charged, partially charged, low battery, or error).

[0058] The exoskeleton **100** can include a post **150**. The post **150** can include a mechanical structure that connects to the boot **110**. The post **150** can couple the ankle joint component **120** with the footplate **115**. The post **150** can be attached at a first end to the footplate **115**. The post **150** can be attached at a second end to the ankle joint component **120**. The post **150** can pivot about the ankle joint component **120**. The post **150** can include a mechanical structure that couples the footplate **115** with the ankle joint component **120**. The post **150** can include a rigid structure. The post **150** can be removably attached to the footplate **115**. The post **150** can be removably attached to the ankle joint component **120**. For example, the post **150** can be disconnected from the ankle joint component **120**.

[0059] The exoskeleton **100** can include a rugged system used for field testing. The exoskeleton **100** can include an integrated ankle lever guard (e.g., nested lever). The exoskeleton **100** can include a mechanical shield to guard the actuator belt **135** and ankle lever transmission from the environment. The housing structure of the system can extend to outline the range of travel of the ankle lever (e.g., lever arm **2040**) on the lateral and medial side.

II. Active Exoskeleton with Local Battery

[0060] Exoskeletons **100** can transform an energy source into mechanical forces that augment human physical ability. Exoskeletons **100** can have unique power requirements. For example, exoskeletons **100** can use non-constant power levels, such as cyclical power levels with periods of high power (e.g., 100 to 1000 Watts) and periods of low or negative power (e.g., 0 Watts). Peaks in power can occur once per gait cycle. Batteries configured to provide power to the exoskeleton **100** can be the source of various issues. For example, batteries located near the waist of a user can require exposed cables that extend from the battery to the lower limb exoskeleton. These cables can introduce snag hazards, make the device cumbersome, and add mass to the system. Additionally, long cables with high peak power can result in excess radio emissions and higher voltage drops during high current peaks. Thus, systems, methods and apparatus of the present technical solution provide an exoskeleton with a local battery that can perform as desired without causing snag hazards, power losses, and radio interference. Additionally, the battery can be located close to the knee such that the mass felt by the user is reduced as compared to a battery located close the foot of the user.

[0061] FIG. 2 illustrates a schematic diagram of the exoskeleton **100**. The exoskeleton **100** includes the one or more housings **105**, the boot **110** the footplate **115**, the ankle joint component **120**, shin pad **125**, the actuator **130**, the actuator belt **135**, the power button **140**, the battery module **145**, the post **150**, the rotary encoder **155**, and the second rotary encoder **160**. The battery module **145** can be inserted into the exoskeleton **100**. The battery module **145** can include a sealed battery. The battery module **145** can coupled with the exoskeleton **100** via a waterproof or water resistant connection. The battery module **145** can connect locally (e.g., proximate) to the exoskeleton **100** such that a wire is not needed to run from the battery module **145** to the electronics.

[0062] The battery module **145** can be held in the battery holder **170**. The battery module **145** can be integrated with the battery holder **170**. The battery module **145** can be held by, or affixed to, the exoskeleton **100** itself. For example, the battery module **145** can be affixed, attached, or integrated with a portion of the exoskeleton **100** without a separate housing or battery holder **170**.

[0063] In implementations, the battery module **145** can be held by the battery holder **170** in a fixed or integrated manner, or in a removeable manner. For example, the battery module **145** can be

removably affixed to the battery holder **170**. For example, the battery module **145** can slide in and out of the battery holder **170**. By removably affixing the battery module **145** to the battery holder **170**, the battery module **145** can be replaced with another battery module **145**, or the battery module **145** can be removed for charging. The battery module **145** can include a first power connector **205** that electrically couples to a second power connector **210** located in the battery holder **170** while attached to the battery holder **170** to provide electric power to the electronic circuitry and the electric motor. The first power connector **205** and the second power connector **210** can couple (e.g., connect) the battery module **145** with the electronic circuitry. The first power connector **205** and the second power connector **210** can couple the battery module **145** with the one or more housings **105**. The first power connector **205** can be recessed in the battery module **145** to protect the first power connector **205** from loading and impacts. The first power connector **205** and the second power connector **210** can include wires (e.g., two wires, three wires, or four wires). The battery module **145** can communicate with the electronic circuitry via the first power connector **205** and the second power connector **210**. The first power connector **205** and the second power connector **210** can include an exposed connector.

[0064] FIG. **3** illustrates a schematic diagram of the battery module **145**. The first power connector **205** can include a blade connector **305**. A blade connector **305** can be a type of single wire, plug-and-socket connection using a flat conductive blade that can be inserted into a receptacle. The second power connector **210** can include a receptacle **310** configured to receive the blade connector **305** absent an exposed cable. For example, the blade connector **305** can slide into the receptacle **310**. The blade connector **305** can include an asymmetric and keyed design to prevent improper affixation of the battery module **145** to the battery holder **170**. The blade connector **305** can include a design to tolerate small connector misalignment. The blade connector **305** can be recessed within a power connector housing to prevent damage to the blade connector **305**. The geometry of the battery module **145** can allow for storage and packing efficiency. The battery module **145** can include a gripping element to allow for ergonomic ease of removal and insertion of the battery module **145** into the battery holder **170**. The battery module **145** can be made of lightweight plastics or metals. The battery module **145** can be made of heat insulating materials to prevent heat generated by the battery cells from reaching the user. One or more faces of the battery module **145** can be made of metal to dissipate heat.

[0065] The first power connector **205** can include a serial data communication port to provide at least one of battery state data, a battery test function, a smart charging function, or a firmware upgrade. The battery state data can include the health of the battery module **145**. The battery test function can include probing the battery module **145**. The smart charging function can include using a high voltage to charge the battery module **145**. The first power connector **205** can include a pin **315**. The pin **315** can provide serial data. The pin **315** can be further configured to receive a voltage input greater than or equal to a threshold to wake up a battery management system **1224** of the battery module **145**. The pin **315** can be configured to receive a voltage input greater than or equal to a threshold to put the battery management system **1224** to sleep. The pin **315** can be configured to receive a voltage input greater than or equal to a threshold to put the battery management system **1224** in a bootloader mode. The pin **315** can include a serial port to allow the exoskeleton **100** to access data from the battery management system **1224**. The serial port can allow a computer to be connected to the battery module **145** to monitor its state. The serial port can be used to support a bootloader (e.g., boot program, bootstrap loader). The bootloader can include a piece of software that loads into the working memory after start-up. The serial port can be used to upgrade the firmware (e.g., via the bootloader). The serial port can be connected to the power button **140**. The pin **315** can wake up the battery module **145**. The pin **315** can put the battery module **145** in and out of ship mode. Ship mode can include a ship mode circuit that prolongs the battery life of the battery module **145**. The battery module **145** can be electronically disconnected from the rest of the system to minimize power drain while the exoskeleton **100** is idle. When the

exoskeleton **100** is turned on, the battery module **145** can be connected to the rest of the exoskeleton **100** and stays connected until the system goes back into ship mode. An external signal used to put the battery in and out of ship mode. The external signal used to put the battery in an out of ship mode can be used to start the bootloader.

[0066] FIG. **4** illustrates a cross-section of the battery module **145**. The battery module **145** can include a printed circuit board **405**. The printed circuit board **405** can be enclosed within the battery module **145**. The battery module **145** can include the first power connector **205**. The first power connector **205** can be disposed on an exterior of the battery module **145**. The first power connector **205** can be coupled to the printed circuit board **405**.

[0067] Safety features can be implemented in the battery module **145**. For example, the printed circuit board **405** can include an analog front end (AFE) chip. The AFE chip can read cell voltages, measure current, and implement safety features (e.g., over current, short circuit, undervoltage, or overvoltage). The AFE chip can turn the charge and discharge metal-oxide-semiconductor field-effect transistors (MOSFETs) off when issues are detected, thus disconnecting the output of the pack from the cells. The printed circuit board **405** can include a microcontroller with firmware. The microcontroller can configure the AFE chip's safety limits. The microcontroller can handle error recovery, transitions, charging, discharging, and temperature limits. The microcontroller can be responsible for user interfacing. The microcontroller can be responsible for turning the charge and discharge MOSFETs on when warranted by the state machine. The microcontroller can handle fault conditions like a charger that is outputting current above a threshold and temperatures above a threshold (e.g. temperatures that are not immediately dangerous but that could lead to issues). The printed circuit board **405** can include hardware protections such as a transient-voltage suppressor (TVS) and fuse used to protect against reverse polarity, overvoltage and over current (both in charge in discharge). They can trigger if the AFE chip and the microcontroller fail at reacting to a fault. The microcontroller can run briefly (e.g., once every 10 or 100 ms) and then enter into a low power mode (e.g., drawing microamperes). The AFE chip can handle tasks that the microcontroller does not handle. This combination can allow for a low current design and a battery module **145** with a long shelf-life (e.g., more than 200 days). Communication between different components on the printed circuit board **405** can be wired or wireless (e.g., use a radio module, Bluetooth). The battery module **145** can be charged via inductive coupling or a via wire connection. The microcontroller can be connected to the serial port. The microcontroller can be connected to the battery management system **1224**.

[0068] The firmware can save statistics (e.g., battery module statistics) in non-volatile memory. Battery module statistics can include number of cycles, minimum and maximum temperatures recorded, a fault counter (e.g., how many times did the battery module **145** shutdown due to short-circuit discharge or overcurrent during discharge), average mAh, average charging time, or average discharging time. The battery module **145** can communicate the battery module statistics when the battery module **145** is connected to a user application. The firmware can implement a low voltage per cell state in which the battery module **145** has a higher energy density (e.g., use 950 mAh out of the theoretical 1000 mAh maximum), but the number of charge/discharge cycles is lower before that capacity starts diminishing or before it is limited due to safety concerns. The firmware can implement a high voltage per cell state in which the battery module **145** has lower energy density (say 900 mAh) but it will support more cycles. The battery module **145** can change its position at runtime on the energy density vs. cycle life spectrum. For example, a button can be pressed that will allow a deeper discharge as compared to normal battery module operation. The firmware can control the number of charge and discharge cycles that the battery module **145** can support. The firmware can block the battery module **145** after a threshold number of cycles as a safety measure.

[0069] The exoskeleton **100** can communicate with the battery module **145** during operation. The exoskeleton **100** can use battery management system information to determine when safety measures will trigger. For example, during a high current peak (e.g., 15 A) or when the temperature

is near a threshold, the power output can be turned off. The exoskeleton **100** can temporarily increase safety limits for very specific use cases (e.g., specific environmental conditions, battery life). The battery module **145** can prevent the exoskeleton **100** from shutting down by going into a low power mode and conserving power. The exoskeleton **100** can put the battery module **145** in ship mode if a major error is detected and the exoskeleton **100** wants to prevent the user from power cycling. The battery management system **1224** can be adapted to support more or less series cells, parallel cells, larger capacity cells, cylindrical cells, different lithium chemistries, etc.

[0070] FIG. 5 illustrates a schematic diagram of the battery module **145**. The battery module **145** can include a plurality of battery cells **505**. The battery module **145** can include a plurality of prismatic cells or cylindrical cells. The battery module **145** can include a plurality of prismatic lithium cells (e.g., LiPo cells, LiFePO₄ cells). The battery module **145** can include a plurality of prismatic LiFePO₄ (lithium iron phosphate) cells. The battery module **145** can include a plurality of prismatic LiPo (lithium-polymer) pouch cells. The plurality of prismatic LiPo pouch cells can deliver high power during peak loads. The plurality of prismatic LiPo pouch cells can have a higher energy density than that of cylindrical cells. The plurality of prismatic LiPo pouch cells can be packed more tightly as compared with cylindrical cells. The plurality of prismatic LiPo pouch cells can be safer than cylindrical cells in the case of a catastrophic failure of the battery module **145**. The battery module **145** can include a frame **510** within a housing of the battery module **145**. The battery module **145** can include the printed circuit board **405**. The plurality of battery cells **505** can be soldered to the printed circuit board **405**. Thermocouples can be located between each cell of the plurality of battery cells **505** to monitor the temperature of each of the cells. The battery module **145** can include a plurality of prismatic lithium cells.

[0071] FIGS. 6 and 7 illustrate schematic diagrams of the printed circuit board **405** of the battery module **145**. The printed circuit board **405** can be soldered to the plurality of battery cells **505**. The printed circuit board **405** can include a signal trace. The signal trace can electrically connect the plurality of battery cells **505** to one or more battery balancers. The printed circuit board **405** can include the first power connector **205**. The first power connector **205** can be coupled to the printed circuit board **405**. The printed circuit board **405** can connect the plurality of battery cells **505** in series. The printed circuit board **405** can connect the plurality of battery cells **505** in parallel.

[0072] FIG. 8 illustrates a schematic diagram of the battery module **145**. The battery module **145** can include the plurality of battery cells **505** and the frame **510**. An edge **805** of each of the plurality of battery cells **505** can be attached to a portion **810** of the frame **510** within the housing of the battery module **145**. The plurality of battery cells **505** can be attached to the portion **810** of the frame **510** via an adhesive. The battery module **145** can include multiple battery cells **505**. For example, the battery module **145** can include three to twelve battery cells **505** (e.g., eight battery cells or nine battery cells). Each of the battery cells **505** can be separated by a space allowing room for expansion. The portion **810** of the frame **510** can separate each of the plurality of battery cells **505**.

[0073] FIG. 9 illustrates a schematic diagram of the battery module **145**. The battery module **145** can include the first power connector **205**. The first power connector **205** can be configured to couple with the second power connector **210**. The second power connector **210** can be located in the battery holder **170** (not shown). The battery module **145** can include a chassis **905**. The printed circuit board **405** and the plurality of battery cells **505** can be installed onto the chassis **905**. Front and rear covers of the chassis **905** can be installed to protect the printed circuit board **405** and the plurality of battery cells **505**, support the first power connector **205**, and prevent water ingress. An adhesive can be located on the rear cover to support the plurality of battery cells **505**. The chassis **905** can include the frame **510**.

[0074] FIGS. 10 and 11 illustrates cross-sections of the battery module **145**. An edge **805** of each of the plurality of battery cells **505** can be attached to a portion **810** of the frame **510** within the housing of the battery module **145**. The portion **810** of the frame **510** can separate each of the

plurality of battery cells **505**. The portion **810** of the frame **510** can provide a gap between each of the plurality of battery cells **505** to allow room for the battery cells **505** to expand during operation of the exoskeleton **100**.

[0075] FIG. **12A** illustrates a schematic diagram of an exoskeleton **100**. The exoskeleton **100** can include a motor **1230**. The motor **1230** can generate torque about an axis of rotation of an ankle joint of the user. The exoskeleton **100** can include the battery module **145**. The exoskeleton **100** can include a computing system **1200**. The exoskeleton **100** can include one or more processors **1202**, memory **1204**, one or more temperature sensors **106** (e.g., thermocouples), and one or more battery balancers **1208**. The one or more processors **1202**, memory **1204**, and one or more temperature sensors **1206** can be located within the computing system **1200**.

[0076] The one or more processors **1202** can receive data corresponding to a performance of the battery module **145**. The data can include one or more of a temperature, current, voltage, battery percentage, internal state or firmware version. The one or more processors **1202** can determine, based on a safety policy, to trigger a safety action. The safety policy can include triggering the safety action if a threshold temperature, voltage or battery percentage is crossed. For example, the safety policy can include triggering the safety action if a temperature of one or more of the plurality of battery cells **505** is higher than a threshold temperature. The safety policy can include triggering the safety action if a battery percentage of the battery module **145** is below a threshold battery percentage. The safety policy can include triggering the safety action if a measured temperature is higher than the threshold temperature. The measured temperature can include the temperature of the printed circuit board **405** and battery cells **505**. The measured temperature can include the temperature of the printed circuit board **405** and battery cells **505** measured in two locations. The safety policy can include triggering the safety action if a measured voltage is higher than the threshold voltage.

[0077] The one or more processors **1202** can instruct, based on the safety action, the electronic circuitry to adjust delivery of power from the battery module **145** to the electric motor to reduce an amount of torque generated about the axis of rotation of the ankle joint of the user. The safety action can include lowering or reducing the amount of torque generated about the axis of rotation of the ankle joint of the user. The safety action can include increasing the amount of torque generated about the axis of rotation of the ankle joint of the user.

[0078] The one or more temperature sensors **1206** can be placed between the plurality of battery cells **505** to provide an indication of a temperature between the plurality of battery cells **505**. A temperature sensor of the one or more temperature sensors **1206** can be mounted on the printed circuit board **405** to measure a temperature of the printed circuit board **405**. The electronic circuitry **1405** can control the delivery of power from the battery module **145** to the electric motor based at least in part on the indication of the temperature between the plurality of battery cells **505** or the temperature of the printed circuit board **405**.

[0079] The one or more battery balancers **1208** can be configured to actively transfer energy from a first battery cell of the plurality of battery cells **505** to a second battery cell of the plurality of battery cells **505** having less charge than the first battery cell. A signal trace **1210** can electrically connect the plurality of battery cells **505** to the one or more battery balancers **1208**. The signal trace **1210** can be located on the printed circuit board **405**. The one or more battery balancers **1208** can be located within the battery module **145**.

[0080] The exoskeleton **100** can include the battery module **145**. The battery module **145** can include the plurality of battery cells **505**, one or more temperature sensors **1206**, and a battery management system **1224**. The battery management system **1224** can perform various operations. For example, the battery management system **1224** can optimize the energy density of the unit, optimize the longevity of the cells, and enforce the required safety to protect the user. The battery management system **1224** can go into ship mode by electrically disconnecting the battery module **145** from the rest of the system to minimize power drain while the system is idle. The battery

management system **1224** can go into ship mode if a major fault is detected. For example, if one or more of the plurality of battery cells **505** self-discharge at a rate higher than a threshold, the battery management system **1224** can re-enable the charging port.

[0081] While these components are shown as part of the exoskeleton **100**, they can be located in other locations such as external to the exoskeleton **100**. For example, the battery management system **1224** or the computing system **1200** can be located external to the exoskeleton **100** for testing purposes.

[0082] FIG. **12B** illustrates a schematic diagram of the battery management system **1224**. The battery management system **1224** can include one or more clips **1250**. The one or more clips **1250** can be configured to hold one or more battery cells of the plurality of battery cells **505**. For example, the one or more clips **1250** can be configured to hold one or more cylindrical cells. A battery cell of the plurality of battery cells **505** can be positioned between a first clip of the one or more clips **1250** and a second clip of the one or more clips **1250**.

[0083] FIG. **13** illustrates a schematic diagram of the exoskeleton **100**. The exoskeleton **100** can include the one or more housings **105**, the footplate **115**, the ankle joint component **120**, shin pad **125**, the actuator **130**, the actuator belt **135**, the post **150**, the rotary encoder **155**, the second rotary encoder **160**, and the sealant **165** as described above. The one or more housings **105** can be coupled to the shin pad **125**. The post **150** can couple the ankle joint component **120** with the footplate **115**. The actuator **130** can include the one or more housings **105**, the footplate **115**, the ankle joint component **120**, the actuator belt **135**, and the post **150**. The rotary encoder **155** can measure an angle of the electric motor. The second rotary encoder **160** can measure an angle of the ankle joint. The sealant **165** can be placed in contact with the one or more housings **105** to close the one or more housings **105** and prevent an ingress of water into the one or more housings **105**.

[0084] FIG. **14** illustrates a schematic diagram of the exoskeleton **100** and internal parts. The exoskeleton **100** can include the one or more housings **105**, the ankle joint component **120**, the actuator **130**, the power button **140**, the rotary encoder **155**, the second rotary encoder **160**, and the sealant **165** as described above. The internal parts can include electronic circuitry **1405** (e.g., electronic circuit, circuitry, electronics). The electronic circuitry **1405** can include individual electronic components (e.g., resistors, transistors, capacitors, inductors, diodes, processors, or controllers). The power button **140** can be electrically connected to the electronic circuitry **1405**. The electronic circuitry **1405** can be located behind the electric motor. The electronic circuitry **1405** can include the main electronics board. The rotary encoder **155** can be located between the motor and electronic circuitry **1405**. The electronic circuitry **1405** can control delivery of power from the battery module **145** to the electric motor to generate torque about the axis of rotation of the ankle joint of the user.

[0085] FIG. **15** illustrates a side view of the exoskeleton **100**. The exoskeleton **100** can include the one or more housings **105**, ankle joint component **120**, the actuator **130**, the rotary encoder **155**, the second rotary encoder **160**, the sealant **165**, and electronic circuitry **1405** as described above. The exoskeleton **100** can include an output shaft **1505** (e.g., motor rotor, spool shaft, pinion gear, spur gear, or toothed pulley). The output shaft **1505** can be coupled to the electric motor. The output shaft **1505** can extend through a bore **1510** in a housing of the one or more housings **105** enclosing the electric motor. The bore **1510** can receive the output shaft **1505**. An encoder chip can be located on the electronics board on a first side of the electric motor. The encoder chip can measure the angular position of the rotary encoder **155**. The exoskeleton **100** can include a transmission (e.g., gearbox) configured to couple the output shaft **1505** to the electric motor. The transmission can include a machine in a power transmission system. The transmission can provide controlled application of power. The output shaft **1505** can be integrated into the motor rotor. The output shaft **1505** can be part of a mechanism (e.g., gears, belts, linkage, or change). An ankle shaft can extend through the second rotary encoder **160** which can increase the structural integrity of the exoskeleton **100**.

[0086] The exoskeleton **100** can include a first component of the fitted structure **1515** (e.g., first clamshell structure). The exoskeleton **100** can include a second component of the fitted structure **1520** (e.g., second clamshell structure). The first component of the fitted structure **1515** can be coupled with the second component of the fitted structure **1520**. The first component of the fitted structure **1515** can be attached to the second component of the fitted structure **1520** via the sealant **165** (e.g., adhesive sealant). The first component of the fitted structure **1515** can be coupled to the second component of the fitted structure **1520** such that the fitting prevents or decreases a rate of water flow into the interior of the exoskeleton **100**. The fitted structure can include two or more components such that the assembly components prevents or decreases a rate of water flow into the interior of the exoskeleton **100**. The first component of the fitted structure **1515** and the second component of the fitted structure **1520** can be stationary components. The number of individual components of the fitted structure can be minimized to decrease the number of possible entry points for water to enter the exoskeleton **100**. The possible entry points can include seams and/or moving parts of the exoskeleton **100**. The seams can be permanently sealed via the sealant **165**. [0087] An adhesive sealant (e.g., super glue, epoxy resin, or polyvinyl acetate) can be placed between the first component of the fitted structure **1515** and the second component of the fitted structure **1520**. The adhesive sealant can prevent or decrease the rate of water flow through the seam between the first component of the fitted structure **1515** and the second component of the fitted structure **1520** into the interior of the exoskeleton **100**. The adhesive sealant can be placed under the electronics cover. The adhesive sealant can prevent or decrease the rate of water flow through the seam between the electronics cover and the exoskeleton one or more housings **105** into the interior of the exoskeleton **100**.

[0088] A gasket can be placed between the first component of the fitted structure **1515** and the second component of the fitted structure **1520**. The gasket can be placed in the seam between the first component of the fitted structure **1515** and the second component of the fitted structure **1520**. The gasket can prevent or decrease the rate of water flow through the seam between the first component of the fitted structure **1515** and the second component of the fitted structure **1520**. [0089] FIG. **16** illustrates a schematic diagram of the exoskeleton **100**. The exoskeleton **100** can include the one or more housings **105**, the footplate **115**, the ankle joint component **120**, the shin pad **125**, the actuator **130**, the post **150**, the rotary encoder **155**, the second rotary encoder **160**, and the sealant **165** as described above. The one or more housings **105** can be coupled to the shin pad **125**. The post **150** can couple the ankle joint component **120** with the footplate **115**. The actuator **130** can include the one or more housings **105**, the footplate **115**, the ankle joint component **120**, and the post **150**. The rotary encoder **155** can measure an angle of the electric motor. The second rotary encoder **160** can measure an angle of the ankle joint.

[0090] FIG. **17** and FIG. **18** illustrate schematic diagrams of the exoskeleton **100** and internal parts. The exoskeleton **100** can include the one or more housings **105**, the footplate **115**, the ankle joint component **120**, shin pad **125**, the actuator **130**, the post **150**, the rotary encoder **155**, the second rotary encoder **160**, the sealant **165**, and electronic circuitry **1405** as described above. The internal parts can include an electronic circuit (e.g., circuitry). The electronic circuit can include individual electronic components (e.g., resistors, transistors, capacitors, inductors, diodes, processors, or controllers). The motor rotor can be connected to the output shaft **1505**.

[0091] FIG. **19** illustrates a side view of the exoskeleton **100**. The exoskeleton **100** can include the one or more housings **105**, the actuator **130**, the rotary encoder **155**, the second rotary encoder **160**, and the sealant **165**, the output shaft **1505**, and the bore **1510** as described above. The exoskeleton **100** can include an output shaft **1505** (e.g., motor rotor). The output shaft **1505** can be coupled to the electric motor. The output shaft **1505** can extend through a bore **1510** in a housing of the one or more housings **105** enclosing the electric motor. The bore **1510** can receive the output shaft **1505**. A magnet can be located on a first side of the electric motor. An encoder chip can be located on the electronics board on the first side of the electric motor. The encoder chip can measure the angular

position of the rotary encoder **155**. An ankle shaft can extend through the second rotary encoder **160** which can increase the structural integrity of the exoskeleton **100**. The exoskeleton **100** can include a transmission (e.g., gearbox) configured to couple the output shaft **1505** to the electric motor. The transmission can include a machine in a power transmission system. The transmission can provide controlled application of power.

[0092] FIG. **20** illustrates a side view of an exoskeleton **100**. The exoskeleton **100** can include a motor **2005** (e.g., electric motor), a motor timing pulley **2010** (e.g., timing pulley), a motor timing belt **2015** (e.g., timing belt), the second rotary encoder **160** (e.g., an ankle encoder PCB, ankle encoder printed circuit board, second rotary encoder PCB, or ankle encoder), an ankle shaft **2025**, a motor encoder magnet **2030**, a motor encoder **2035**, a lever arm **2040** (e.g., ankle lever), and an ankle encoder magnet **2045**. The ankle shaft **2025** can extend through the second rotary encoder **160** to increase the structural integrity of the exoskeleton **100**. The motor timing belt **2015** can be coupled to a sprocket **2050**. The sprocket **2050** can be coupled with a spool. The motor encoder magnet **2030** can be located on the first side of the electric motor.

[0093] FIG. **21** illustrates a method **2100** of augmenting user motion. The method **2100** can include providing, to a user, a battery-powered active exoskeleton boot (BLOCK **2105**). The battery-powered active exoskeleton boot can include a shin pad to be coupled to a shin of a user below a knee of the user. The battery-powered active exoskeleton boot can include one or more housings enclosing electronic circuitry and an electric motor that can generate torque about an axis of rotation of an ankle joint of the user. At least one of the one or more housings can be coupled to the shin pad below the knee of the user. The battery-powered active exoskeleton boot can include a battery holder coupled to the shin pad. The battery holder can be located below the knee of the user and above the one or more housings enclosing the electronic circuitry. The battery-powered active exoskeleton boot can include a battery module removably affixed to the battery holder. The battery module can include a first power connector that electrically couples to a second power connector located in the battery holder while attached to the battery holder to provide electric power to the electronic circuitry and the electric motor. The battery-powered active exoskeleton boot can include an output shaft coupled to the electric motor and extending through a bore in a housing of the one or more housings enclosing the electric motor. The electronic circuitry can control delivery of power from the battery module to the electric motor to generate torque about the axis of rotation of the ankle joint of the user.

[0094] In some embodiments, the first power connector includes a blade connector. The second power connector can include a receptacle configured to receive the blade connector absent an exposed cable. The battery module can include a plurality of battery cells. The battery module can include a printed circuit board soldered to the plurality of battery cells. The battery module can include one or more battery balancers configured to actively transfer energy from a first battery cell of the plurality of battery cells to a second battery cell of the plurality of battery cells having less charge than the first battery cell. The battery module can include a signal trace, on the printed circuit board, that electrically connects the plurality of battery cells to the one or more battery balancers.

[0095] In some embodiments, the method **2100** includes providing, via a serial data communication port of the first power connector, at least one of battery state data, a battery test function, a smart charging function, or a firmware upgrade. The battery state data can include the health of the battery module. The battery test function can include probing the battery module. The smart charging function can include using a high voltage to charge the battery module. A pin of the first power connector that provides serial data can be further configured to receive a voltage input greater than or equal to a threshold to wake up a battery management system of the battery module. The pin can be configured to receive a voltage input greater than or equal to a threshold to put the battery management system to sleep. The pin can be configured to receive a voltage input greater than or equal to a threshold to put the battery management system in a bootloader mode.

[0096] The method **2100** can include receiving data corresponding to battery module performance (BLOCK **2110**). For example, the method **2100** can include receiving, by one or more processors of the battery-powered active exoskeleton boot, data corresponding to a performance of the battery module, the data comprising one or more of a temperature, current, voltage, battery percentage. For example, the data can include a temperature from one or more temperature sensors of the computing system. The data can include a temperature from one or more temperature sensors of the battery module.

[0097] The method **2100** can include determining to trigger a safety action (BLOCK **2115**). For example, the method **2100** can include determining, by the one or more processors, based on a safety policy, to trigger a safety action. The safety policy can include triggering the safety action if a threshold temperature, voltage or battery percentage is crossed. For example, the safety policy can include triggering the safety action if a temperature of one or more of the plurality of battery cells is higher than a threshold temperature. The safety policy can include triggering the safety action if a battery percentage of the battery module is below a threshold battery percentage. The measured temperature can include the temperature of the printed circuit board and battery cells. The measured temperature can include the temperature of the printed circuit board and battery cells measured in two locations. The safety policy can include triggering the safety action if a measured voltage is higher than the threshold voltage.

[0098] The method **2100** can include instructing circuitry to adjust power delivery (BLOCK **2120**). For example, the method **2100** can include instructing, by the one or more processors, based on the safety action, the electronic circuitry to adjust delivery of power from the battery module to the electric motor to reduce an amount of torque generated about the axis of rotation of the ankle joint of the user. The safety action can include lowering or reducing the amount of torque generated about the axis of rotation of the ankle joint of the user. The safety action can include increasing the amount of torque generated about the axis of rotation of the ankle joint of the user.

[0099] FIGS. 22-25 illustrate a schematic diagrams of the exoskeleton **100** and an integrated battery module **2205**. The exoskeleton **100** can include the one or more housings **105**, the ankle joint component **120**, the shin pad **125**, the post **150**, the rotary encoder **155**, the second rotary encoder **160**, the printed circuit board **405**, the plurality of battery cells **505**, the one or more clips **1250**, and the battery holder **170** as described above. The one or more housings **105** can be coupled to the shin pad **125**. The rotary encoder **155** can measure an angle of the electric motor. The second rotary encoder **160** can measure an angle of the ankle joint. The plurality of battery cells **505** can include cylindrical cells.

[0100] The exoskeleton **100** can include the integrated battery module **2205** (e.g., integrated battery). The integrated battery module **2205** can be integrated with the exoskeleton **100**. The integrated battery module **2205** can be part of the exoskeleton. For example, the integrated battery module **2205** and the one or more housings **105** can be formed of one piece, as opposed to a removable battery module that is not integrated with the one or more housings **105**. The removable battery module can include a battery module whereby the plurality of battery cells **505** are enclosed in a casing that is configured to slide out of the battery holder **170**. The integrated battery module **2205** can include a battery module whereby each of the plurality of battery cells **505** are configured to be positioned between the one or more clips **1250**. The integrated battery module **2205** can be permanently attached to the one or more housings **105** of the exoskeleton **100**. For example, the integrated battery module **2205** may not be removable. The battery cells of the integrated battery module **2205** can be soldered or otherwise coupled or affixed to the PCB or portion of the exoskeleton **100**.

[0101] FIG. 23 illustrates a PCB **405** that is integrated to the exoskeleton, in accordance with implementations. The PCB **405** can be the exterior side (e.g., the side of the exoskeleton opposite the side of the exoskeleton adjacent to the leg of a user) of the exoskeleton, while the integrated battery module **2205** can be on the interior of the exoskeleton **100**. In some cases, the integrated

battery module **2205** can be on the exterior of the exoskeleton **100** while the PCB **405** can be on the interior of the exoskeleton **100**.

[0102] FIG. **24** depicts battery cells **505** that are integrated with the exoskeleton **100**, in accordance with implementations. The battery cells **505** can be directly coupled or affixed to a portion of the exoskeleton or PCB **405**. The battery cells **505** can be coupled using solder, an adhesive, or fasteners to a portion of the PCB **405** or clips configured to hold the battery cells **505** to a portion of the exoskeleton **100**. The battery cells **505** can be coupled to a side of the exoskeleton **100** that is adjacent to the shin pad **125**. For example, the integrated battery cells **505** can be located in between the shin pad **125** and the PCB **405**, whereas in the removable battery module configuration, the PCB **405** can be located in between the shin pads **125** and the battery module.

[0103] FIG. **25** illustrates an integrated battery holder for battery cells **505**, in accordance with implementations. The battery holder **170** can be integrated with the exoskeleton **100**. The battery holder **170** can form a part of the exoskeleton **100**. The battery holder **170** can provide structural support, integrity or functionality to the exoskeleton **100**. The battery holder **170** can receive battery cells **505**, and couple the battery cells **505** to the battery holder **170**. The battery cells **405** can be fixedly attached to the battery holder **170**, or the battery cells **505** can be removably attached to the battery holder **170**. For example, in the integrated battery configuration, the battery cells **505** couple to the battery holder **170**, and the battery electronics, including the battery balancer, can be fixedly coupled to the exoskeleton, for example. However, in the removable battery module configuration, certain battery electronics can be part of the battery module and be removable, such as the battery balancer component, for example.

[0104] FIG. **26** illustrates a block diagram of an architecture for a computing system employed to implement various elements of the system and methods depicted in FIGS. **1-21**, according to an embodiment. FIG. **26** is a block diagram of a data processing system including a computer system **2600** in accordance with an embodiment. The computer system can include or execute a coherency filter component. The data processing system, computer system or computing device **2600** can be used to implement one or more components configured to process data or signals depicted in FIGS. **1-25**. The computing system **2600** includes a bus **2605** or other communication component for communicating information and a processor **2610a-n** or processing circuit coupled to the bus **2605** for processing information. The computing system **2600** can also include one or more processors **2610** or processing circuits coupled to the bus for processing information. The computing system **2600** also includes main memory **2615**, such as a random access memory (RAM) or other dynamic storage device, coupled to the bus **2605** for storing information, and instructions to be executed by the processor **2610**. Main memory **2615** can also be used for storing time gating function data, temporal windows, images, reports, executable code, temporary variables, or other intermediate information during execution of instructions by the processor **2610**. The computing system **2600** may further include a read only memory (ROM) **2620** or other static storage device coupled to the bus **2605** for storing static information and instructions for the processor **2610**. A storage device **2625**, such as a solid state device, magnetic disk or optical disk, is coupled to the bus **2605** for persistently storing information and instructions.

[0105] The computing system **2600** may be coupled via the bus **2605** to a display **2635** or display device, such as a liquid crystal display, or active matrix display, for displaying information to a user. An input device **2630**, such as a keyboard including alphanumeric and other keys, may be coupled to the bus **2605** for communicating information and command selections to the processor **2610**. The input device **2630** can include a touch screen display **2635**. The input device **2630** can also include a cursor control, such as a mouse, a trackball, or cursor direction keys, for communicating direction information and command selections to the processor **2610** and for controlling cursor movement on the display **2635**.

[0106] The processes, systems and methods described herein can be implemented by the computing system **2600** in response to the processor **2610** executing an arrangement of instructions contained

in main memory **2615**. Such instructions can be read into main memory **2615** from another computer-readable medium, such as the storage device **2625**. Execution of the arrangement of instructions contained in main memory **2615** causes the computing system **2600** to perform the illustrative processes described herein. One or more processors in a multi-processing arrangement may also be employed to execute the instructions contained in main memory **2615**. In some embodiments, hard-wired circuitry may be used in place of or in combination with software instructions to effect illustrative implementations. Thus, embodiments are not limited to any specific combination of hardware circuitry and software.

[0107] Although an example computing system has been described in FIG. **26**, embodiments of the subject matter and the functional operations described in this specification can be implemented in other types of digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them.

[0108] Embodiments of the subject matter and the operations described in this specification can be implemented in digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them. The subject matter described in this specification can be implemented as one or more computer programs, e.g., one or more circuits of computer program instructions, encoded on one or more computer storage media for execution by, or to control the operation of, data processing apparatus. Alternatively or in addition, the program instructions can be encoded on an artificially generated propagated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal that is generated to encode information for transmission to suitable receiver apparatus for execution by a data processing apparatus. A computer storage medium can be, or be included in, a computer-readable storage device, a computer-readable storage substrate, a random or serial access memory array or device, or a combination of one or more of them. Moreover, while a computer storage medium is not a propagated signal, a computer storage medium can be a source or destination of computer program instructions encoded in an artificially generated propagated signal. The computer storage medium can also be, or be included in, one or more separate components or media (e.g., multiple CDs, disks, or other storage devices).

[0109] The operations described in this specification can be performed by a data processing apparatus on data stored on one or more computer-readable storage devices or received from other sources. The term “data processing apparatus” or “computing device” encompasses various apparatuses, devices, and machines for processing data, including by way of example a programmable processor, a computer, a system on a chip, or multiple ones, or combinations of the foregoing. The apparatus can include special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit). The apparatus can also include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, a cross-platform runtime environment, a virtual machine, or a combination of one or more of them. The apparatus and execution environment can realize various different computing model infrastructures, such as web services, distributed computing and grid computing infrastructures.

[0110] A computer program (also known as a program, software, software application, script, or code) can be written in any form of programming language, including compiled or interpreted languages, declarative or procedural languages, and it can be deployed in any form, including as a stand-alone program or as a circuit, component, subroutine, object, or other unit suitable for use in a computing environment. A computer program may, but need not, correspond to a file in a file system. A program can be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more circuits, subprograms, or

portions of code). A computer program can be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

[0111] Processors suitable for the execution of a computer program include, by way of example, microprocessors, and any one or more processors of a digital computer. A processor can receive instructions and data from a read only memory or a random access memory or both. The elements of a computer are a processor for performing actions in accordance with instructions and one or more memory devices for storing instructions and data. A computer can include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic, magneto optical disks, or optical disks. A computer need not have such devices. Moreover, a computer can be embedded in another device, e.g., a personal digital assistant (PDA), a Global Positioning System (GPS) receiver, or a portable storage device (e.g., a universal serial bus (USB) flash drive), to name just a few. Devices suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto optical disks; and CD ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

[0112] To provide for interaction with a user, implementations of the subject matter described in this specification can be implemented on a computer having a display device, e.g., a CRT (cathode ray tube) or LCD (liquid crystal display) monitor, for displaying information to the user and a keyboard and a pointing device, e.g., a mouse or a trackball, by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback, e.g., visual feedback, auditory feedback, or tactile feedback; and input from the user can be received in any form, including acoustic, speech, or tactile input.

[0113] The implementations described herein can be implemented in any of numerous ways including, for example, using hardware, software or a combination thereof. When implemented in software, the software code can be executed on any suitable processor or collection of processors, whether provided in a single computer or distributed among multiple computers.

[0114] Also, a computer may have one or more input and output devices. These devices can be used, among other things, to present a user interface. Examples of output devices that can be used to provide a user interface include printers or display screens for visual presentation of output and speakers or other sound generating devices for audible presentation of output. Examples of input devices that can be used for a user interface include keyboards, and pointing devices, such as mice, touch pads, and digitizing tablets. As another example, a computer may receive input information through speech recognition or in other audible format.

[0115] Such computers may be interconnected by one or more networks in any suitable form, including a local area network or a wide area network, such as an enterprise network, and intelligent network (IN) or the Internet. Such networks may be based on any suitable technology and may operate according to any suitable protocol and may include wireless networks, wired networks or fiber optic networks.

[0116] A computer employed to implement at least a portion of the functionality described herein may comprise a memory, one or more processing units (also referred to herein simply as “processors”), one or more communication interfaces, one or more display units, and one or more user input devices. The memory may comprise any computer-readable media, and may store computer instructions (also referred to herein as “processor-executable instructions”) for implementing the various functionalities described herein. The processing unit(s) may be used to execute the instructions. The communication interface(s) may be coupled to a wired or wireless network, bus, or other communication means and may therefore allow the computer to transmit

communications to or receive communications from other devices. The display unit(s) may be provided, for example, to allow a user to view various information in connection with execution of the instructions. The user input device(s) may be provided, for example, to allow the user to make manual adjustments, make selections, enter data or various other information, or interact in any of a variety of manners with the processor during execution of the instructions.

[0117] The various methods or processes outlined herein may be coded as software that is executable on one or more processors that employ any one of a variety of operating systems or platforms. Additionally, such software may be written using any of a number of suitable programming languages or programming or scripting tools, and also may be compiled as executable machine language code or intermediate code that is executed on a framework or virtual machine.

[0118] In this respect, various inventive concepts may be embodied as a computer readable storage medium (or multiple computer readable storage media) (e.g., a computer memory, one or more floppy discs, compact discs, optical discs, magnetic tapes, flash memories, circuit configurations in Field Programmable Gate Arrays or other semiconductor devices, or other non-transitory medium or tangible computer storage medium) encoded with one or more programs that, when executed on one or more computers or other processors, perform methods that implement the various embodiments of the solution discussed above. The computer readable medium or media can be transportable, such that the program or programs stored thereon can be loaded onto one or more different computers or other processors to implement various aspects of the present solution as discussed above.

[0119] The terms “program” or “software” are used herein to refer to any type of computer code or set of computer-executable instructions that can be employed to program a computer or other processor to implement various aspects of embodiments as discussed above. One or more computer programs that when executed perform methods of the present solution need not reside on a single computer or processor, but may be distributed in a modular fashion amongst a number of different computers or processors to implement various aspects of the present solution.

[0120] Computer-executable instructions may be in many forms, such as program modules, executed by one or more computers or other devices. Program modules can include routines, programs, objects, components, data structures, or other components that perform particular tasks or implement particular abstract data types. The functionality of the program modules can be combined or distributed as desired in various embodiments.

[0121] Also, data structures may be stored in computer-readable media in any suitable form. For simplicity of illustration, data structures may be shown to have fields that are related through location in the data structure. Such relationships may likewise be achieved by assigning storage for the fields with locations in a computer-readable medium that convey relationship between the fields. However, any suitable mechanism may be used to establish a relationship between information in fields of a data structure, including through the use of pointers, tags or other mechanisms that establish relationship between data elements.

[0122] Any references to implementations or elements or acts of the systems and methods herein referred to in the singular can include implementations including a plurality of these elements, and any references in plural to any implementation or element or act herein can include implementations including only a single element. References in the singular or plural form are not intended to limit the presently disclosed systems or methods, their components, acts, or elements to single or plural configurations. References to any act or element being based on any information, act or element may include implementations where the act or element is based at least in part on any information, act, or element.

[0123] Any implementation disclosed herein may be combined with any other implementation, and references to “an implementation,” “some implementations,” “an alternate implementation,” “various implementations,” “one implementation” or the like are not necessarily mutually exclusive

and are intended to indicate that a particular feature, structure, or characteristic described in connection with the implementation may be included in at least one implementation. Such terms as used herein are not necessarily all referring to the same implementation. Any implementation may be combined with any other implementation, inclusively or exclusively, in any manner consistent with the aspects and implementations disclosed herein.

[0124] References to “or” may be construed as inclusive so that any terms described using “or” may indicate any of a single, more than one, and all of the described terms. References to at least one of a conjunctive list of terms may be construed as an inclusive OR to indicate any of a single, more than one, and all of the described terms. For example, a reference to “at least one of ‘A’ and ‘B’” can include only ‘A’, only ‘B’, as well as both ‘A’ and ‘B’. Elements other than ‘A’ and ‘B’ can also be included.

[0125] The systems and methods described herein may be embodied in other specific forms without departing from the characteristics thereof. The foregoing implementations are illustrative rather than limiting of the described systems and methods.

[0126] Where technical features in the drawings, detailed description or any claim are followed by reference signs, the reference signs have been included to increase the intelligibility of the drawings, detailed description, and claims. Accordingly, neither the reference signs nor their absence have any limiting effect on the scope of any claim elements.

[0127] The systems and methods described herein may be embodied in other specific forms without departing from the characteristics thereof. The foregoing implementations are illustrative rather than limiting of the described systems and methods. Scope of the systems and methods described herein is thus indicated by the appended claims, rather than the foregoing description, and changes that come within the meaning and range of equivalency of the claims are embraced therein.

Claims

1. A method, comprising: providing a battery holder of an ankle-foot exoskeleton wearable on a lower limb of a user, the battery holder configured to be disposed at the lower limb of the user and configured to receive a battery; providing an actuator of the ankle-foot exoskeleton, the actuator configured to receive power from the battery and generate torque about an axis of rotation of the lower limb; and providing one or more housings of the ankle-foot exoskeleton, the one or more housings enclosing electronic circuitry configured to control delivery of the power from the battery to the actuator.
2. The method of claim 1, comprising: decreasing power output responsive to a determination that a temperature of the battery is greater than a threshold.
3. The method of claim 1, comprising: decreasing power output responsive to a determination that a current of the battery is greater than a threshold.
4. The method of claim 1, comprising: decreasing an amount of torque generated about the axis of rotation of the lower limb responsive to a determination that a temperature of the battery is greater than a threshold.
5. The method of claim 1, comprising: decreasing an amount of torque generated about the axis of rotation of the lower limb responsive to a determination that a temperature of the electronic circuitry is greater than a threshold.
6. The method of claim 1, wherein: the ankle-foot exoskeleton comprises a power connector; and the power connector is configured to couple the battery with the electronic circuitry.
7. The method of claim 1, wherein: the battery comprises a first power connector; the ankle-foot exoskeleton comprises a second power connector; and the first power connector configured to be coupled with the second power connector.
8. The method of claim 1, wherein the battery comprises a recessed power connector.

- 9.** The method of claim 1, wherein: the ankle-foot exoskeleton comprises a shin pad configured to contact the lower limb of the user; and the shin pad is mechanically coupled with the battery holder.
- 10.** The method of claim 1, wherein the battery comprises a power connector including a serial data communication port configured to provide a state of the battery.
- 11.** The method of claim 1, wherein the battery comprises a pin configured to receive a voltage input.
- 12.** The method of claim 1, wherein the ankle-foot exoskeleton is wearable on at least one of a foot or ankle of the user.
- 13.** The method of claim 1, wherein the battery comprises a blade connector.
- 14.** The method of claim 1, wherein the ankle-foot exoskeleton comprises a user interface configured to provide an indication of a state of the battery.
- 15.** An apparatus, comprising: an ankle-foot exoskeleton wearable on a lower limb of a user, the ankle-foot exoskeleton comprising: a battery holder configured to be disposed at the lower limb of the user and configured to receive a battery; an actuator configured to receive power from the battery and generate torque about an axis of rotation of the lower limb; and one or more housings enclosing electronic circuitry configured to control delivery of the power from the battery to the actuator.
- 16.** The apparatus of claim 15, wherein: the ankle-foot exoskeleton comprises a power connector; and the power connector is configured to couple the battery with the electronic circuitry.
- 17.** The apparatus of claim 15, wherein: the battery comprises a first power connector; the ankle-foot exoskeleton comprises a second power connector; and the first power connector configured to be coupled with the second power connector.
- 18.** A system for an ankle-foot exoskeleton, comprising: a battery holder of the ankle-foot exoskeleton wearable on a lower limb of a user, the battery holder configured to be disposed at the lower limb of the user and configured to receive a battery; an actuator of the ankle-foot exoskeleton, the actuator configured to receive power from the battery and generate torque about an axis of rotation of the lower limb; and one or more housings of the ankle-foot exoskeleton, the one or more housings enclosing electronic circuitry configured to control delivery of the power from the battery to the actuator.
- 19.** The system of claim 18, wherein the electronic circuitry is configured to: decrease an amount of torque generated about the axis of rotation of the lower limb responsive to a determination that a temperature of the battery is greater than a threshold.
- 20.** The system of claim 18, wherein the electronic circuitry is configured to: decrease an amount of torque generated about the axis of rotation of the lower limb responsive to a determination that a temperature of the electronic circuitry is greater than a threshold.
-