

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250250861

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

MAXFIELD; Bradley Scott et al.

---

### COMBINATION LADDERS, LADDER COMPONENTS AND RELATED METHODS

---

#### Abstract

Ladders and ladder components are described herein, including multipurpose and adjustable ladders. In one embodiment, a ladder includes a first assembly having rails and rungs, a second assembly having rails and rungs, and one or more hinges coupling the first and second assemblies together such that the first and second assembly may be positioned relative to one another in at least a position or state and at least a second position or state. A top cap is coupled to the rails of the first assembly, such that when the first and second assemblies are in the first position, the rails of the second assembly do not contact the top cap. When the first and second assemblies are in the second position, each rail of the second assembly is at least partially nested in one of a pair of channels formed in the top cap.

---

**Inventors:** MAXFIELD; Bradley Scott (Mapleton, UT), Moss; N. Ryan (Mapleton, UT), Russell; Brian B. (Saratoga Springs, UT)

**Applicant:** LITTLE GIANT LADDER SYSTEMS, LLC (Springville, UT)

**Family ID:** 68764675

**Appl. No.:** 19/190118

**Filed:** April 25, 2025

#### Related U.S. Application Data

parent US continuation 19025538 20250116 PENDING child US 19190118

parent US continuation 18828597 20240909 PENDING child US 19025538

parent US continuation 17848823 20220624 parent-grant-document US 12152445 child US 18828597

parent US continuation 16435232 20190607 parent-grant-document US 11441356 child US 17848823

us-provisional-application US 62682673 20180608

## Publication Classification

**Int. Cl.:** **E06C7/50** (20060101); **E06C1/32** (20060101); **E06C1/383** (20060101); **E06C7/14** (20060101); **E06C7/18** (20060101); **E06C7/42** (20060101); **E06C7/46** (20060101); **E06C7/48** (20060101); **F16C11/10** (20060101)

**U.S. Cl.:**

**CPC** **E06C7/50** (20130101); **E06C1/32** (20130101); E06C7/182 (20130101); E06C7/48 (20130101); E06C7/482 (20130101)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application is a continuation of U.S. patent application Ser. No. 19/025,538, filed 16 Jan. 2025, which is a continuation of U.S. patent application Ser. No. 18/828,597, filed 9 Sep. 2024, which is a continuation of U.S. patent application Ser. No. 17/848,823, filed 24 Jun. 2022 and issued as U.S. Pat. No. 12,152,445 on 26 Nov. 2024, which is a continuation of U.S. patent application Ser. No. 16/435,232, filed 7 Jun. 2019 and issued as U.S. Pat. No. 11,441,356 on 24 Aug. 2022, which claims the benefit of U.S. Provisional Patent Application No. 62/682,673, filed 8 Jun. 2018, U.S. Provisional Patent Application No. 62/732,997, filed 18 Sep. 2018, and U.S. Provisional Patent Application No. 62,834,076, filed 15 Apr. 2019, the entire disclosures of which are incorporated by reference herein. [0002] This application is also related to U.S. patent application Ser. No. 29/679,726, filed on 8 Feb. 2019 and issued as U.S. Design Patent No. D911,555 on 23 Feb. 2021, U.S. patent application Ser. No. 29/679,733, filed 8 Feb. 2019 and issued as U.S. Design Patent No. D912,848 on 9 Mar. 2021, U.S. patent application Ser. No. 29/667,352, filed 19 Oct. 2018 and issued as U.S. Design Patent No. D935,054 on 2 Nov. 2021, U.S. patent application Ser. No. 29/667,354, filed 19 Oct. 2018 and issued as U.S. Design Patent No. D 943,772 on 15 Feb. 2022, U.S. patent application Ser. No. 29/667,356, filed 19 Oct. 2018 and issued as U.S. Design Patent No. D912,847 on 9 Mar. 2021, and U.S. patent application Ser. No. 29/667,357, filed 19 Oct. 2018 and issued as U.S. Design Patent No. D885,607 on 26 May 2020, the entire disclosures of which are incorporated by reference herein.

## BACKGROUND

[0003] The present invention relates generally to ladders including various embodiments of combination ladders, as well as various ladder components. Ladders are conventionally utilized to provide a user thereof with improved access to elevated locations that might otherwise be inaccessible. Ladders come in many shapes and sizes, such as straight ladders, straight extension ladders, step ladders, and combination step and extension ladders. So-called combination ladders may incorporate, in a single ladder, many of the benefits of multiple ladder designs.

[0004] Ladders known as step ladders, sometimes referred to as A-frame ladders, are self-supporting ladders, meaning that they do not need to be leaned against a wall, pole or other structure for stability. Rather, step ladders may be positioned on a floor (or other similar surface) such that at least three, and conventionally four, feet of the ladder provide a stable support structure for a user to climb upon, even in an open space (e.g., outside or in the middle of a room) without a wall, roof, pole or other type of structure being necessary for the stability of the ladder.

[0005] Ladders such as combination ladders are highly utilized by various tradesman as well as homeowners. Such ladders are “self-supporting” in one configuration (e.g., in step ladder configuration) such that they do not need to have the upper end of the ladder to be positioned against a supporting structure (e.g., a wall or the edge of a roof). Rather, when in such a configuration, combination ladders conventionally utilize four feet, spaced from one another, to provide a stable structure and to support the ladder and a user when placed on, for example, a floor or the ground. This enables a user of the ladder to gain access to elevated areas even though the accessed area may be, for example, in the middle of a room, away from walls or other potential supporting structures that are conventionally required when using a straight ladder or an extension ladder.

[0006] Combination ladders may be placed in other configurations, including one wherein the ladder substantially extends in a single plane, such as a straight ladder or an extension ladder, providing access to increased height (as compared to when it is in the step ladder configuration) but typically requiring some elevated structure to support the ladder (e.g., a wall or the edge of a roof).

[0007] For these reasons and others, combination ladders have become a popular form of ladders and comprise a substantial segment of the ladder market. However, there are always areas of potential improvement.

#### SUMMARY

[0008] The present disclosure sets forth various embodiments of ladders and ladder components including adjustable, multipurpose ladders.

[0009] In accordance with one embodiment, a ladder is provided that includes a first assembly and a second assembly. The first assembly comprises a first pair of spaced apart rails and a plurality of rungs extending between and coupled to the first pair of spaced apart rails. The second assembly comprises a second pair of spaced apart rails and at least one rung extending between and coupled to the second pair of spaced apart rails. The ladder further includes a pair of hinges pivotally coupling the first pair of spaced apart rails with the second pair of spaced apart rails such that the first pair of rails are selectively positionable relative to the second pair of rails in at least a first, a second and a third position. A top cap is coupled to the first pair of spaced apart rails, wherein the first and second pair of spaced apart rails are in the first position, the second pair of rails do not contact the top cap, and wherein, when the first and second pair of spaced apart rails are in the second position, each rail of the second pair of spaced apart rails is at least partially nested in one of a pair of channels formed in the top cap.

[0010] In one embodiment, when the first and second pair of spaced apart rails are in the third position, the second pair of rails do not contact the top cap.

[0011] In one embodiment, the ladder further comprises a selectively positionable rail coupled with at least one of the first assembly, the second assembly and the top cap.

[0012] In one embodiment, the selectively positionable rail includes a pair of side members and at least one cross member coupled between the pair of side members.

[0013] In one embodiment, the ladder further comprises an accessory coupled with the second pair of spaced apart rails, the accessory including a first pair of engagement surfaces forming an interior 90 degree angle, and a second pair of engagement surfaces forming an exterior 90 degree angle.

[0014] In one embodiment, the ladder further comprises a pair of feet, each foot of the pair of feet coupled to an associated rail of the second pair of spaced apart rails, wherein the accessory is coupled with the second pair of rails at a location between the pair of feet and the at least one rung.

[0015] In one embodiment, the first pair of engagement surfaces includes a first engagement surface and a second engagement surface, and wherein a notch is formed between the first engagement surface and the second engagement surface, the notch including a rear wall, a first side wall and a second side wall, wherein the first side wall and the second side wall are spaced from each other a distance of approximately 1.5 inches or greater.

[0016] In one embodiment the accessory is removably coupled with the second pair of rails.

[0017] In one embodiment, each hinge of the pair of hinges includes a first lock ring, a second lock ring selectively rotatable relative to the first lock ring about an axis, a geared member having at least one cog on a periphery thereof and disposed axially between the first lock ring and the second lock ring, the geared member having an axially protruding shaft including a ramped portion, an annular recess and an abutment shoulder between the ramped portion and the annular recess, and an annular coiled spring disposed about a portion of the shaft and configured to contract within the annular recess upon displacement of the geared member towards the second lock ring.

[0018] In one embodiment, the first pair of spaced apart rails exhibits a first width at a first height of the first assembly and a second width at a second height of the first assembly, the second width being greater than the first width.

[0019] In one embodiment, the second pair of spaced apart rails are substantially parallel to each other.

[0020] In one embodiment, the second assembly exhibits a width of approximately 14.5 inches or less.

[0021] In one embodiment, the top cap includes a first body portion and a second body portion selectively displaceable relative to the first body portion.

[0022] In one embodiment, the ladder further comprises a cushion disposed on a surface of the second body portion.

[0023] In another embodiment of the present disclosure, a ladder is provided that comprises a first assembly and a second assembly. The first assembly includes a first pair of spaced apart rails, a plurality of rungs extending between and coupled to the first pair of spaced apart rails, and a first pair of feet coupled with the pair of spaced apart rails. The second assembly includes a second pair of spaced apart rails extending substantially parallel to one another, at least one rung extending between and coupled to the second pair of spaced apart rails, and a second pair of feet coupled with the second pair of spaced apart rails. The ladder further includes a pair of hinges pivotally coupling the first pair of spaced apart rails with the second pair of spaced apart rails and a top cap coupled to the first pair of spaced apart rails. The first assembly exhibits a first width at a location adjacent the pair of hinges and a second width adjacent the first pair of feet, the second width being greater than the first width.

[0024] In one embodiment, the second assembly exhibits an overall width of approximately 14.5 inches or less.

[0025] In one embodiment, each rail of the first pair of spaced apart rails includes a first section and a second section, the first section being substantially linear and being coupled with a hinge of the pair of hinges, the second section being flared and extending between the first section and a foot of the pair of feet.

[0026] In one embodiment the second section is arcuate.

[0027] In one embodiment the first pair of spaced apart rails are formed of a material comprising fiberglass.

[0028] In one embodiment, the first sections of the first pair of spaced apart rails are substantially parallel with each other.

[0029] In one embodiment, the first pair of rails are selectively positionable relative to the second pair of rails in at least a first, a second and a third position.

[0030] In one embodiment, the first and second pair of spaced apart rails are in the first position, the second pair of rails do not contact the top cap, and wherein, when the first and second pair of spaced apart rails are in the second position, each rail of the second pair of spaced apart rails are at least partially nested in one of a pair of channels formed in the top cap.

[0031] In one embodiment, the top cap includes a first body portion and a second body portion selectively displaceable relative to the first body portion.

[0032] In one embodiment, the second body portion includes a first, substantially flat engagement surface, and a pair of protruding members extending away from the substantially flat engagement

surface.

[0033] In one embodiment, the pair of protruding members includes a first protruding member having a first angled surface and a second angled surface, a second protruding member having a third angled surface and a fourth angled surface, wherein the first angled surface and the third angled surface form an interior 90 degree angle relative to each other and wherein the second angled surface and the fourth angled surface form an exterior angle relative to each other.

[0034] In one embodiment, the ladder further comprises a channel disposed between the first protruding member and the second protruding member.

[0035] In one embodiment, the channel exhibits a width of approximately 1.5 to approximately 1.625 inches.

[0036] In a further embodiment of the present disclosure, a ladder is provided that includes a first assembly and a second assembly. The first assembly includes a first pair of spaced apart rails and a plurality of rungs extending between and coupled to the first pair of spaced apart rails. The second assembly includes a second pair of spaced apart rails and at least one rung extending between and coupled to the second pair of spaced apart rails. The ladder further includes a pair of hinges pivotally coupling the first pair of spaced apart rails with the second pair of spaced apart rails such that the first pair of rails are selectively positionable relative to the second pair of rails in at least a first position and a second position, wherein the second pair of rails extend from the first pair of rails at an acute angle when in the first position, and wherein the second pair of rails extend from the first pair of rails in a generally parallel direction when in the second position. The ladder additionally includes pair of feet, each foot of the pair of feet being coupled to a lower portion of an associated rail of the second pair of rails. Each foot includes a body having a first side wall, a second side wall, a front wall and a rear wall defining an opening that engages the associated rail, a first surface-engaging portion opposite the opening, and a second surface-engaging portion extending along the rear wall.

[0037] In one embodiment, the second surface-engaging portion forms an acute projected angle with a rear surface of its associated rail.

[0038] In one embodiment, the acute projected angle is between approximately 14 degrees and approximately 16 degrees.

[0039] In one embodiment, the acute projected angle is approximately 15 degrees.

[0040] In one embodiment, the ladder further comprises a first cushioned portion between the rear wall and the second surface-engaging portion.

[0041] In one embodiment, the first wall, the second wall, the front wall and the rear wall are formed of a first material, and wherein the first surface-engaging portion, the second surface-engaging portion and the first cushioned portion are formed of a second material, the second material being different from the first material.

[0042] In one embodiment, the second material is overmolded onto the first material.

[0043] In one embodiment, the ladder further comprises a third surface-engaging portion positioned adjacent the first side wall.

[0044] In one embodiment, the third surface-engaging portion is positioned at an angle of approximately 45 degrees relative to the second surface-engaging portion.

[0045] In one embodiment, the ladder further comprises a fourth surface-engaging portion positioned adjacent the second side wall.

[0046] In one embodiment, the fourth surface-engaging portion is positioned at an angle of approximately 45 degrees relative to the second surface-engaging portion.

[0047] In one embodiment, the first surface-engaging portion comprises a first set of ridges and the second surface-engaging portion comprises a second set of ridges.

[0048] In one embodiment, the first set of ridges extend lengthwise in a direction that is substantially perpendicular to the first sidewall.

[0049] In one embodiment, the second set of ridges extend lengthwise in a direction that is

substantially perpendicular to the direction of the first set of ridges.

[0050] In one embodiment, the ladder further comprises a top cap coupled to the first pair of spaced apart rails, wherein the first and second pair of spaced apart rails are in the first position, the second pair of rails do not contact the top cap, and wherein, when the first and second pair of spaced apart rails are in the second position, each rail of the second pair of spaced apart rails are at least partially nested in one channel of a pair of channels formed in the top cap.

[0051] In accordance with yet another embodiment of the present disclosure, a ladder foot is provided that comprises a body having a first side wall, a second side wall, a front wall and a rear wall defining an opening that engages the associated rail, a first surface-engaging portion opposite the opening and a second surface-engaging portion extending along the rear wall.

[0052] In one embodiment, the second surface-engaging portion forms an acute angle with a surface the rear wall.

[0053] In one embodiment the acute angle is between approximately 14 degrees and approximately 16 degrees.

[0054] In one embodiment the acute angle is approximately 15 degrees.

[0055] In one embodiment, the ladder foot further comprises a third surface-engaging portion adjacent the first side wall.

[0056] In one embodiment, the third surface-engaging portion forms an angle of approximately 45 degrees with the second surface-engaging portion.

[0057] In one embodiment, the ladder foot further comprises a first cushioned portion between the rear wall and the second surface-engaging portion and a second cushion portion between the first side wall and the third surface-engaging portion.

[0058] In one embodiment, the first wall, the second wall, the front wall and the rear wall are formed of a first material, and wherein the first surface-engaging portion, the second surface-engaging portion, the third surface-engaging portion, the first cushioned portion and the second cushioned portion are formed of a second material, the second material being different from the first material.

[0059] In one embodiment, the second material is overmolded onto the first material.

[0060] In yet a further embodiment of the present disclosure, another ladder is provided that comprises a first assembly and second assembly. The first assembly comprises a first pair of spaced apart rails and a plurality of rungs extending between and coupled to the first pair of spaced apart rails, The second assembly comprises a second pair of spaced apart rails and at least one rung extending between and coupled to the second pair of spaced apart rails. The ladder further includes a pair of hinges pivotally coupling the first pair of spaced apart rails with the second pair of spaced apart rails. Each hinge of the pair of hinges comprises a first lock ring, a second lock ring selectively rotatable relative to the first lock ring about an axis, a geared member having at least one cog on a periphery thereof and disposed axially between the first lock ring and the second lock ring, the geared member having an axially protruding shaft including a ramped portion, an annular recess and an abutment shoulder between the ramped portion and the annular recess, and an annular coiled spring disposed about a portion of the shaft and configured to contract within the annular recess upon displacement of the geared member towards the second lock ring.

[0061] In one embodiment, the first lock ring further includes a plurality of radially inwardly extending protrusions, each protrusion including a first inclined surface and a second inclined surface, wherein upon relative rotation of the first lock ring and the second lock ring, at least one of the first and second inclined surfaces engage the at least one cog to displace the geared member axially towards the first lock ring.

[0062] In one embodiment, the pair of hinges are configured to selectively lock the second assembly relative the first assembly in a first position and at least a second position.

[0063] In one embodiment, the second pair of rails extend from the first pair of rails at an acute angle when in the first position, and wherein the second pair of spaced rails extend from the first

pair of rails in a generally parallel direction when in the second position.

[0064] In one embodiment, the pair of hinges are configured to selectively lock the second assembly relative to the first assembly in a third position, wherein the second pair of spaced apart rails are positioned adjacent to, and extend generally parallel to, the first pair of spaced apart rails.

[0065] In yet another embodiment of the present disclosure, a ladder rail and hinge assembly is provided what includes a first rail, a second rail, and a hinge assembly pivotally coupling the first rail with the second rail. The hinge assembly comprises a first lock ring, a second lock ring selectively rotatable relative to the first lock ring about an axis, a geared member having at least one cog on a periphery thereof and disposed axially between the first lock ring and the second lock ring, the geared member having an axially protruding shaft including a ramped portion, an annular recess and an abutment shoulder between the ramped portion and the annular recess, and an annular coiled spring disposed about a portion of the shaft and configured to contract within the annular recess upon displacement of the geared member towards the second lock ring.

[0066] In one embodiment, the first lock ring further includes a plurality of radially inwardly extending protrusions, each protrusion including a first inclined surface and a second inclined surface, wherein upon relative rotation of the first lock ring and the second lock ring, at least one of the first and second inclined surfaces engage the at least one cog to displace the geared member axially towards the first lock ring.

[0067] In one embodiment, the hinge assembly is configured to selectively lock the first rail relative the second rail in a first position, a second position, and at least a third position.

[0068] In another embodiment according to the present disclosure, a ladder is provided that comprises a first assembly and a second assembly. The first assembly includes a first pair of spaced apart rails and a plurality of rungs extending between and coupled to the first pair of spaced apart rails. The second assembly includes a second pair of spaced apart rails and at least one rung extending between and coupled to the second pair of spaced apart rails. The ladder further includes a pair of hinges pivotally coupling the first pair of spaced apart rails with the second pair of spaced apart rails such that the first pair of rails are selectively positionable relative to the second pair of rails in at least a first a first position and a second position, wherein the second pair of rails extend from the first pair of rails at an acute angle when in the first position, and wherein the second pair of rails extend from the first pair of rails in a generally parallel direction when in the second position. A top cap is coupled with the first pair of rails and an an accessory coupled with the second pair of rails. The accessory includes a first pair of engagement surfaces forming an interior 90 degree angle, and a second pair of engagement surfaces forming an exterior 90 degree angle.

[0069] In one embodiment, the first pair of engagement surfaces include a first engagement surface and a second engagement surface, and wherein a notch is formed between the first engagement surface and the second engagement surface, the notch including a rear wall, a first side wall and a second side wall, wherein the first side wall and the second side wall are spaced from each other a distance of approximately 1.5 inches or greater.

[0070] In one embodiment, the second pair of engagement surfaces include a third engagement surface and a fourth engagement surface, and wherein a fifth engagement surface extends between the first engagement surface and the third engagement surface and wherein the sixth engagement surface extends between the second engagement surface and the fourth engagement surface.

[0071] In one embodiment, the first pair of engagement surfaces and the second pair of engagement surfaces include grooves and ridges extending between an upper surface of the accessory and a lower surface of the accessory.

[0072] In one embodiment, the accessory is removably coupled with the second pair of rails.

[0073] In one embodiment, the accessory includes an upper surface having at least one recess formed therein.

[0074] In one embodiment, the first and second pair of spaced apart rails are in the first position, the second pair of rails do not contact the top cap, and wherein, when the first and second pair of

spaced apart rails are in the second position, each rail of the second pair of spaced apart rails are at least partially nested in one of a pair of channels formed in the top cap.

[0075] In one embodiment, the top cap includes a front face, a top face, a rear face, and a pair of protruding members extending from the rear face, wherein the pair of protruding members include: a first protruding member having a first angled surface and a second angled surface, and a second protruding member having a third angled surface and a fourth angled surface, wherein the first angled surface and the third angled surface form an interior 90 degree angle relative to each other and wherein the second angled surface and the fourth angles surface form an exterior angle relative to each other.

[0076] In one embodiment, a channel is disposed between the first protruding member and the second protruding member.

[0077] In one embodiment, the second assembly further includes a pair of feet coupled with the second pair of spaced apart rails, and wherein the accessory is positioned between the pair of feet and the at least one rung.

[0078] In one embodiment, the at least one rung includes a second plurality of rungs including a rung closest to the pair of feet, and wherein accessory is positioned between the pair of feet and the rung closest to the pair of feet.

[0079] In a further embodiment according the present disclosure, an accessory for a ladder is provided. The accessory comprises a body having a first engagement surface and a second engagement surface forming an interior 90 degree angle, a third engagement surface and a fourth engagement surface forming an exterior 90 degree angle, a fifth engagement surface and a sixth engagement surface that are substantially coplanar, and a pair of notches sized, shaped and configured to engage a pair of rails of a ladder.

[0080] In one embodiment, the accessory further comprises a third notch disposed between the first and second engagement surfaces, the third notch including a rear wall, a first side wall and a second side wall, wherein the first side wall and the second side wall are spaced from each other a distance of approximately 1.5 inches or greater.

[0081] In one embodiment, the first engagement surface and the second engagement surface each are located between the third engagement surface and the fourth engagement surface.

[0082] In one embodiment, the fifth engagement surface extends between the first engagement surface and the third engagement surface and wherein the sixth engagement surface extends between the second engagement surface and the fourth engagement surface.

[0083] In one embodiment, the accessory includes an upper surface having at least one recess formed therein.

[0084] In another embodiment according the present disclosure, another ladder is provided. The ladder comprises a first assembly and second assembly. The first assembly comprises a first pair of spaced apart rails and a plurality of rungs extending between and coupled to the first pair of spaced apart rails. The second assembly comprises a second pair of spaced apart rails and at least one rung extending between and coupled to the second pair of spaced apart rails. The ladder further includes a pair of hinges pivotally coupling the first pair of spaced apart rails with the second pair of spaced apart rails such that the first pair of rails are selectively positionable relative to the second pair of rails in at least a first a first position and a second position, wherein the second pair of rails extend from the first pair of rails at an acute angle when in the first position, and wherein the second pair of rails extend from the first pair of rails in a generally parallel direction when in the second position. Additionally, the ladder includes a pair of extension members slidably coupled with the first pair of rails and a top cap coupled with the pair of extension members, wherein the top cap is displaceable between a first top cap position, wherein the top cap is immediately adjacent upper ends of the first of rails, and a second top cap position wherein the top cap is spaced apart from the upper ends of the first pair of rails.

[0085] In one embodiment, the ladder further comprises at least one locking mechanism configured



to selectively lock at least one of the extension members in at least two different positions relative to its associated rail of the first pair of rails.

[0086] In one embodiment, the first top cap position and the second top cap position are spaced a distance of at least approximately 1 foot apart.

[0087] In one embodiment, an uppermost rung of the plurality of rungs exhibits a depth that is greater than a depth of the rails of the first pair of rails.

[0088] In yet another embodiment, a ladder is provided that comprises a first assembly and second assembly. The first assembly comprises a first pair of spaced apart rails and a plurality of rungs extending between and coupled to the first pair of spaced apart rails. The second assembly comprises a second pair of spaced apart rails. The ladder further includes a pair of hinges pivotally coupling the first assembly with the second assembly and a top cap. The top cap includes a first body portion coupled with the first assembly, and a second body portion pivotally coupled with the first body portion, wherein when in a first position, the second body portion presents a substantially planar surface for engagement with a vertical support structure, and wherein when in a second position, the second body presents at least one pair of angled engagement surfaces for engagement with a vertical support structure.

[0089] In one embodiment, the second body includes at least one canister.

[0090] In one embodiment, the at least one canister includes a lid hingedly coupled with a body of the canister.

[0091] In one embodiment, the top cap includes a pair of channels formed in the first body portion including first channel adjacent a first side of the second body portion and a second channel adjacent a second side of the second body portion, wherein the pair of channels are configured to receive portions of the second pair of spaced apart rails when the second pair of spaced apart rails are rotated to a position such that they extend upward beyond the top cap and are substantially parallel with the first pair of spaced apart rails.

[0092] In one embodiment, the pair of angled surfaces form a 90 degree interior angle.

[0093] In one embodiment, the pair of angled surfaces form a 90 degree exterior angle.

[0094] In one embodiment, the second body portion further includes a second pair of angled surfaces forming a 90 degree interior angle.

[0095] In one embodiment, the second body portion further includes a channel disposed between the first protruding member and the second protruding member.

[0096] In one embodiment, the channel exhibits a width of approximately 1.5 to approximately 1.625 inches.

[0097] In accordance with another embodiment of the present disclosure, a top cap is provided. The top cap comprises a first body portion configured for coupling with a pair of rails of a ladder and a second body portion pivotally coupled with the first body portion, wherein when in a first position, the second body portion presents a substantially planar surface for engagement with a vertical support structure, and wherein when in a second position, the second body presents at least one pair of angled engagement surfaces for engagement with a vertical support structure.

[0098] In one embodiment, the second body includes at least one canister and a lid hingedly coupled with a body of the canister.

[0099] In one embodiment, the top cap further includes a pair of channels formed in the first body portion including first channel adjacent a first side of the second body portion and a second channel adjacent a second side of the second body portion, wherein the pair of channels are configured to receive portions of the second pair of spaced apart rails when the second pair of spaced apart rails are rotated to a position such that they extend upward beyond the top cap and are substantially parallel with the first pair of spaced apart rails.

[0100] In one embodiment, the pair of angled surfaces form a 90 degree interior angle and wherein the top cap includes a second pair of angled surfaces forming a 90 degree exterior angle.

[0101] In one embodiment, the second body portion further includes a channel disposed between

the first protruding member and the second protruding member, wherein the channel exhibits a width of approximately 1.5 to approximately 1.625 inches.

[0102] The described embodiments are not mutually exclusive of each other. Rather, various features, components or elements of one described embodiment may be used in conjunction with features, components or elements of other described embodiments.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0103] The foregoing and other advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings in which:

[0104] FIG. 1 is a front perspective view of a ladder in a first state according to an embodiment of the present disclosure;

[0105] FIG. 2 is a front perspective of the ladder shown in FIG. 1 while in a second state;

[0106] FIG. 3 is an enlarged rear perspective of the ladder shown in FIGS. 2;

[0107] FIG. 4 is a front perspective view of the ladder shown in FIGS. 1 and 2 while in a third state;

[0108] FIGS. 5 and 6 show a lower portion of a ladder in accordance with an embodiment of the present disclosure;

[0109] FIGS. 7-10 are various views of a ladder in accordance with an embodiment of the present disclosure;

[0110] FIGS. 11-14 are various views of a ladder in accordance with another embodiment of the present disclosure;

[0111] FIGS. 15A-18C depict a top cap of a ladder in accordance with an embodiment of the present disclosure;

[0112] FIGS. 19 and 20 are perspective and rear views, respectively, of a ladder in accordance with an embodiment of the present disclosure;

[0113] FIGS. 21-23 are various views of the ladder shown in FIGS. 19 and 20 in various states;

[0114] FIG. 24 is a perspective view of a ladder in accordance with an embodiment of the present disclosure;

[0115] FIGS. 25A and 25B are right and left perspective views of a hinge assembly which may be used with a ladder according to an embodiment of the present disclosure;

[0116] FIG. 26 is a front view of the hinge assembly shown in FIGS. 25A and 25B with a portion made transparent to depict certain components;

[0117] FIG. 27 is an exploded view of the hinge assembly shown in FIGS. 25A and 25B;

[0118] FIG. 28 is a sectional view of the hinge assembly shown in FIGS. 25A and 25B while in a locked state;

[0119] FIGS. 29-31 are various additional views of the hinge assembly shown in FIGS. 25A and 25B while in a locked state;

[0120] FIGS. 32 and 33 are sectional views of the hinge assembly shown in FIGS. 25A and 25B while transitioning from a locked state to an unlocked state;

[0121] FIG. 34 is a sectional view of the hinge assembly shown in FIGS. 25A and 25B while in an unlocked state;

[0122] FIGS. 35-37 are various additional views of the hinge assembly shown in FIGS. 25A and 25B while in an unlocked state;

[0123] FIG. 38 shows a portion of the hinge assembly according to an embodiment of the present disclosure;

[0124] FIG. 39 is a perspective view of a foot for a ladder having an integrated wall pad according to an embodiment of the disclosure;

[0125] FIG. **40** shows a lower portion of a ladder incorporating the foot shown in FIG. **39** in a stored or collapsed state;

[0126] FIG. **41** shows a lower portion of a ladder incorporating the foot shown in FIG. **39** with the ladder in a deployed, step-ladder configuration;

[0127] FIG. **42** is a side view of a portion of a ladder incorporating the foot shown in FIG. **39** with the ladder in a deployed, straight-ladder configuration;

[0128] FIG. **43** is a perspective view of a portion of a ladder incorporating the foot shown in FIG. **39** with the ladder in a deployed, straight-ladder configuration;

[0129] FIG. **44** is a perspective view of a ladder component according to an embodiment of the present disclosure;

[0130] FIG. **45** is a front perspective view of a ladder in a step-ladder configuration with the component shown in FIG. **44** attached to the ladder;

[0131] FIG. **46** is a rear perspective view of the ladder shown in FIG. **45** while in a stored or collapsed condition;

[0132] FIG. **47** is a front perspective view of the ladder shown in FIG. **45** while in an extended condition;

[0133] FIGS. **48** and **49** are enlarged views of the upper portion of the ladder shown in FIG. **47**;

[0134] FIG. **50** is a perspective view of a ladder according to another embodiment of the present disclosure;

[0135] FIG. **51** is an enlarged view of an upper portion of the ladder shown in FIG. **50**;

[0136] FIG. **52** is a perspective view of the ladder shown in FIG. **50** wherein the top cap is in an extended position according to another embodiment of the present disclosure;

[0137] FIG. **53** is an enlarged view of an upper portion of the ladder shown in FIG. **52**;

[0138] FIG. **54** is a rear perspective view of an upper portion of a ladder showing a ladder component in accordance with another embodiment of the present disclosure;

[0139] FIGS. **55** and **56** are perspective views, and FIG. **57** is a top view, of the ladder and component shown in FIG. **54** while in various states or configurations;

[0140] FIG. **58** is a top perspective view of a foot for a ladder having an integrated wall pad according to an embodiment of the disclosure;

[0141] FIG. **59** is a bottom perspective view of the foot shown in FIG. **58**;

[0142] FIG. **60** is a top view of a ladder incorporating the foot shown in FIG. **58** with the ladder in a deployed, straight-ladder configuration against a support exhibiting an exterior corner;

[0143] FIG. **61** is a top view of a ladder incorporating the foot shown in FIG. **58** with the ladder in a deployed, straight-ladder configuration against a support exhibiting an interior corner;

[0144] FIG. **62** is a perspective view of a portion of a ladder incorporating a spreader structure with the ladder in a step ladder configuration;

[0145] FIG. **63** is a side view of a portion of the ladder shown in FIG. **62** with the ladder in a leaning ladder configuration;

[0146] FIG. **64** is a side perspective view of a portion of the ladder shown in FIG. **62** with the ladder in a straight-ladder configuration;

[0147] FIG. **65** is a perspective view of a ladder according to another embodiment of the present disclosure in a step ladder configuration;

[0148] FIG. **66** is a perspective view of the ladder shown in FIG. **65** in a leaning-ladder configuration;

[0149] FIG. **67** is a perspective view of the ladder shown in FIG. **65** in another state with the rear assembly extended; and

[0150] FIG. **68** is a perspective view of the ladder shown in FIG. **65** in an extended, straight-ladder configuration.

#### DETAILED DESCRIPTION

[0151] Various embodiments of ladders and ladder components are described herein. The described

embodiments are not mutually exclusive of each other. Rather, various features, components or elements of one described embodiment may be used in conjunction with features, components or elements of other described embodiments.

[0152] Referring to FIGS. **1-4** a ladder **100** is shown in accordance with an embodiment of the present disclosure. The ladder **100** includes a first assembly **102** having a pair of spaced apart rails **104** and a plurality of rungs **106** extending between and coupled to the rails **104**. For purposes of convenience, the rungs **106** and rails **104** of the first assembly **102** may be referred to herein as “front rungs **106**” or “front rails **104**” respectively.

[0153] The front rungs **106** are spaced apart, substantially parallel to one another, and are configured to be substantially level when the ladder **100** is in an orientation of intended use so that the rungs **106** may be used as “steps” for a user to ascend the ladder **100** as will be appreciated by those of ordinary skill in the art. In various embodiments, the upper surface of the rungs **106** may include traction features (e.g., grooves and ridges, grip tape or other anti-slip features) to provide traction to a user while standing on the rungs **106**. A top cap **110** may be coupled with the upper portions of the front rails **104** and configured to support the weight of a user in the event that a user stands on the top cap **110**. The upper surface of the top cap **110** may also include traction or anti-slip features to provide traction to a user while standing thereon.

[0154] The ladder **100** also includes a second assembly **112** having a pair of spaced apart rails **114**. A plurality of rungs **116** extend between and are coupled to the spaced apart rails **114**. For purposes of convenience, the rungs **116** and rails **114** of the second assembly may be referred to herein as “rear rungs **116**” and “rear rails **114**” respectively. It is noted that the use of the terms “front” and “rear” herein is not to be considered limiting although describing relative positions of the components when the ladder **100** is in a step ladder configuration. Rather, use of “front” and “rear” is for purposes of convenience and clarity in describing various components or assemblies of the embodiments of the present disclosure.

[0155] The rear rungs **116** are spaced apart, substantially parallel to one another, and are configured to be substantially level when the ladder **100** is in an orientation for intended use so that the rear rungs **116** may be used as “steps” for a user to ascend the ladder **100**. In various embodiments, the upper surface (considering the orientation of the ladder as viewed in FIG. **1**) of the rear rungs **116** may include traction features (e.g., grooves and ridges, grip tape or other anti-slip features) to provide traction to a user while standing on the rear rungs **116**. Additionally, or alternatively, in some embodiments, the rear rungs **116** may include traction features or anti-slip features formed the lower surface thereof (again, as viewed in FIG. **1**). In some embodiments, the second assembly **112** may include support structure **117** which may be used, for example, to engage the wall, post, stud or vertical support when the ladder **100** is in a straight-ladder or extended state such as shown in FIG. **2**. In other embodiments, the support structure **117** may be replaced with another rung or with some other structure such as discussed herein below.

[0156] The second assembly **112** is pivotally coupled with the first assembly **102** via a pair of hinge assemblies **120** (sometimes referred to as “hinges” herein for purposes of brevity). In the embodiment shown, the hinges **120** are spaced away from the top cap **110** along the length of the front rails **104** of the first assembly **102**. For example, the hinges **120** may be positioned adjacent the rung **106** that is closest to the top cap **110**. In one embodiment, this may be approximately **12** inches from the top of the first assembly **102**. The hinges **120** are configured to selectively lock the first assembly **102** and the second assembly **112** in one or more desired positions relative to each other. Thus, for example, in FIG. **1**, the first and second assemblies **102** and **112** are locked such that the rear rails **114** extend at an acute angle relative to the front rails **104**, placing the ladder in a step ladder configuration.

[0157] It is noted that, in some embodiments, the ladder **100** does not include any spreader mechanisms (e.g., hinged, folding braces or other structures that extend between the first and second assemblies) that are conventionally used to accommodate the folding of the ladder as well

as the “locking” of the first and second assemblies **102** and **112** relative to each other in a step ladder configuration. Instead, in various embodiments of the present disclosure, the locking of the hinges **120** maintain the desired positioning of the first and second assemblies **102** and **112** in a deployed, step ladder configuration as shown in FIG. 1.

[0158] As seen in FIGS. 2 and 3, the hinges **120** also enable the second assembly **112** to selectively rotate relative to the first assembly **102** such that the rear rails **114** may be positioned to extend at an angle of substantially **180** degrees from the front rails **104**. Stated another way, the front rails **104** and rear rails **114** extend from each other in a generally parallel manner with a significant portion of the second assembly **112** extending upwards and beyond the top cap **110**. The hinges **120** may also be configured to lock the first and second assemblies **102** and **112** in this relative position, which may be considered a straight ladder configuration, providing a user with the ability to reach extended heights (beyond that of the step ladder configuration) when the ladder **100** is leaned against an appropriate support surface (e.g., a wall or the edge of a roof).

[0159] When the ladder **100** is in a straight ladder configuration, such as shown in FIGS. 2 and 3, portions of the rails **114** of the second assembly **112** are received by, and abut against one or more surfaces of channels **122** that are formed in the rear face of the top cap **110** such that the rear rails **114** (or at least a portion thereof) nest within the channels **122**. As will be detailed further below, the positioning of a portion of the rear rails **114** within the channels **122** forms a structure that might be referred to as an open-mortise and through-tenon arrangement. This configuration provides strength and stability to the resultant straight ladder, with an overlap of the front rails **104** and rear rails **114** occurring between the hinges **120** and the channels **122**.

[0160] It is noted that with the second assembly **112** “flipped up” into a position that places the ladder **100** in a straight ladder configuration (e.g., FIGS. 2 and 3), one of the rear rungs **116** may align with the upper surface of the top cap **110**, providing an extended support surface (i.e., the combined surface areas of the upper surface of the top cap **110** and the tread surface of the adjacent rung **116**) on which a user may stand. Additionally, the other rungs **116** of the second assembly **112** are spaced similarly to the rungs **106** of the first assembly **102** so that a user may continue to climb from the rungs **106** of the first assembly **102**, onto the top cap **110**, and on to the rungs **116** of the second assembly **112** in a continuous and uninterrupted manner, and without a change in spacing from one step to another, as the user ascends and descends the ladder **100**.

[0161] As noted above, the hinges **120** may be configured to lock when in the position shown in FIGS. 2 and 3, providing a certain amount of structural rigidity between the two assemblies **102** and **112**. Additionally, the rear rails **114** may each abut a back surface of their corresponding channel **122** such that force (e.g., from a user climbing the ladder **100**) is transferred through the first assembly **102**, via the top cap **110**, to the rear rails **114**. In addition to the transfer of this type of force, it is noted that lateral forces (e.g., forces extending in a direction along an axis that passes through both front rails **104**) may also be distributed through the top cap **110**, through the sidewalls of the channels **122** to the rear rails **114** (or vice versa), and in combination with the connections provided by the hinges **120**, again providing significant strength and stability to the ladder **100** when in the configuration shown in FIGS. 2 and 3.

[0162] Referring to FIG. 4, the second assembly **112** may be selectively positioned, relative to the first assembly, in a storage or leaning configuration, wherein the rear rails **114** are placed adjacent to, and extend substantially parallel to, the front rails **104**. In this configuration, no portion of the second assembly extends upwards beyond the top cap **110** (or otherwise contacts the top cap **110**) as occurs in the straight ladder configuration. In this configuration, the ladder **100** may be stored in relatively compact space, or it may be used to lean up against a supporting surface or an object (e.g., a wall or a pole), placing the user closer to the supporting surface. As will be discussed in further detail below, a cushion or other resilient and/or non-marking material may be located on a back face of the top cap **110** to engage with a support surface (e.g., a wall) so that the ladder does not scratch or otherwise mar the support surface.

[0163] The first assembly **102** and the second assembly **112** may additionally include feet **130** and **132** formed at, or coupled to, the end of the front and rear rails **104** and **114**, respectively. The feet **130** and **132** may be configured to engage a supporting surface such as the ground when in a step ladder configuration, while the feet **132** may also be configured to engage a supporting surface such as a wall when in a straight ladder configuration.

[0164] The feet **130** and **132** may exhibit any of a variety of configurations depending on, for example, the type of environment in which the ladder is anticipated to be used. For example, the feet **130** and **132** may be formed of a plastic or polymer material and be configured with a plurality of ridges, knobs or other engagement features configured to provide increased friction between the ladder and a relatively rigid supporting surface (e.g., concrete, tile or wood). Additionally, or alternatively, the feet **130** and **132** may include features such as barbs or other sharp protrusions configured to dig into a relatively softer supporting surface (e.g., dirt or grass). In some embodiments, the feet may be configured such as described in U.S. Pat. No. 9,016,434 to Moss et al., the disclosure of which is incorporated by reference herein in its entirety. In other embodiments, the feet may be configured such as described in U.S. patent application Ser. No. 15/897,995, filed on Feb. 15, 2018, the disclosure of which is incorporated by reference herein in its entirety. As will be discussed in further detail below, in some embodiments, the feet may be configured to be selectively positionable relative to their associated rails.

[0165] In some embodiments, the ladder **100** may include other components including, for example, various bracing members or other structural components. For example, one or more brace members may be used to provide increased strength, rigidity, and/or durability to the ladder. In one example, with reference to FIGS. 1-6, brace members **140** may be coupled between the rails (e.g., the front rails **104**) and their associated rungs (e.g., the front rungs **106**). Such a brace **140** may be coupled to the various members by mechanical fastening, material joining, use of adhesives, or other techniques. In one particular example, the brace may be fastened to one component (e.g., to a rung **106**) by way of a mechanical fastener, while being coupled with another component (e.g., to a front rail **104**) merely by encircling the component. Examples of some potential braces, along with techniques of coupling braces with associated components, are described in U.S. patent application Ser. No. 15/952,437, filed on Apr. 13, 2018, the disclosure of which is incorporated by reference herein in its entirety.

[0166] In some embodiments, a mechanism or assembly **144**, configured as a last-step indicator, may be incorporated into or otherwise associated with a lowermost rung or the ladder (e.g., the lowermost rung **106** of the first assembly **102**). The assembly **144** may be configured such that, when a user is descending the ladder **100** and places their weight on the lowermost rung, an alert (e.g., a sound, light, or vibrational signal) is provided to the user, indicating that this is the last rung in their descent, and that their next “step down” will be to the supporting surface (e.g., the floor or ground). Some examples of mechanisms or assemblies used as last-step indicators are described in U.S. patent application Ser. No. 14/849,917, filed on Sep. 10, 2015, the disclosure of which is incorporated by reference herein in its entirety.

[0167] The first and second assemblies **102** and **112** may be formed of a variety of materials and using a variety of manufacturing techniques. For example, in one embodiment, the front and rear rails **104** and **114** may be formed of a composite material, such as fiberglass, while the rungs **106** and **116** and other structural components may be formed of aluminum or an aluminum alloy. In some embodiments, the top cap **110** may be formed of a plastic material and may be molded. In other embodiments, the assemblies **102** and **112** (and their various components) may be formed of a variety of other materials including, for example, other composites, plastics, polymers, metals and metal alloys.

[0168] It is noted that, in some embodiments, the front rails **104** may be tapered, angled or curved such that the lowermost portions of the two front rails **104** are spaced further from one another than the uppermost portions of the two front rails **104**. In some embodiments, such as best seen in FIG.

5, the front rails **104** exhibit a curved geometry in at least a lower portion of the rails, bending outwards from each other. This may be the case even in embodiments where the rails **104** are formed of composite materials such as, for example, fiberglass. The curved portion of the front rails **104** at their lower ends provides a widened base which increases the lateral stability of the ladder **100**. Additionally, the straight portions, or parallel sections, at the upper ends of the front rails **104** enable the hinges **120** to be assembled to two parallel components, preventing binding of the hinges **120** when the second assembly **112** transitions between its various positions or states. [0169] It is noted that in other embodiments, the first and/or second assemblies **102** and **112** may each include rails that are straight and parallel to each other; straight and flared (e.g., the lower portions of the rails exhibiting a greater distance from each other than the upper portions of the rails); bent with an angular change; bent with a curved portion; or some combination of the above. [0170] Referring now to FIGS. 7-10, in some embodiments, the ladder **100** may include a component such as a retractable rail **150** that extends from the top cap **110** and may assist a user in maintaining their balance and stability while standing on one of the upper rungs **106** of the first assembly **102**. The rail **150** may include a cross member **152** coupled between a pair of spaced apart legs **154**. The cross member **152** may include a surface that generally matches or mirrors the upper surface of the top cap **110** (e.g., in terms of traction or anti-slip features or materials) so as to become substantially integrated with the top cap **110** when it is in a stored position. The rail **150** is displaceable between a stored position or configuration (see FIG. 7) and an extended or deployed position or configuration (see FIGS. 8-10). In some embodiments, the rail **150** may be maintained in an extended position by a locking mechanism (e.g., a spring biased button, a detent mechanism, a latch, etc.). In other embodiments, the rail **150** may be maintained in an extended position by way of a frictional force or a biasing force exhibited between, for example, the legs **154** and adjacent surfaces of the top cap **110**. As seen in FIG. 7, when the rail **150** is in the stored or retracted position, the legs **154** may extend down through one or more of the rungs **106** along the inner surfaces of the front rails **104**. In some embodiments, the front rails **104** of the first assembly **102** may be formed as channels (e.g., c-shaped channels), wherein the legs **154** are positioned within the hollow or recessed portion of the channel, keeping the legs **154** out of the path of a user's feet as they climb the rungs **106** of the first assembly **102**.

[0171] In some embodiments, the feet of one or both of the assemblies **102** and **112** may be selectively positionable by a user. For example, referring to FIGS. 11-14, the feet **132** coupled to the ends of the rear rails **114** may each include a coupling portion **160** coupled to an associated rear rail **114**. The feet **132** may each further include a lateral extension portion **162** extending laterally away from the associated rear rail **114**, and a surface engagement portion **164** that is configured to engage a supporting surface. The feet **132** are each independently rotatable about an axis that extends substantially along the length of the associated rear rail **114**, and may each be locked or maintained in a variety of positions by detent mechanisms, push button locks, clamping mechanisms, or a variety of other mechanisms or devices.

[0172] Referring to FIGS. 11 and 12, when the ladder is in a step ladder configuration, the feet **132** may be positioned relative to the rear rails **114** such that the surface engagement portions **164** are positioned laterally outward from the rear rails **114** (e.g., at 180 degrees) and such that the feet engage a supporting surface (e.g., the ground, a floor or other generally horizontal structure) at a width that is greater than the width of the rear rails **114**. In some embodiments, the surface engagement portions **164** may extend in substantially the same plane as the associated rear rails **114**, maximizing the width at which the surface engagement portions **164** engage the supporting surface. Thus, for example, in some embodiments, the rear rails **114** may exhibit a width of approximately 14.5 inches or less (and in some embodiments 14 inches or less), while the feet **132** may be configured to exhibit a width of approximately 18 to approximately 24 inches or greater, providing substantial stability to the ladder **100** when used in a step ladder configuration.

[0173] In some embodiments, the feet **132** may be rotated to a position that is substantially 90

degrees, in either rotational direction, from the position shown in FIGS. **11** and **12**. It is noted that in embodiments where the rear rails **114** are configured to exhibit a width of 14.5 inches or less, that the second assembly **112** may be placed between adjacent studs of typical wall construction (prior to sheet rock or other surfaces being installed), enabling a user to get closer to a wall (e.g., the top cap **110** moves closer to the wall when the second assembly **112** is passed through the space between two adjacent studs) providing enhanced access to a desired work location.

[0174] The feet **132** may be rotated to, and locked at, other positions as well. For example, as shown in FIGS. **13** and **14**, when the ladder is in a straight ladder configuration, it may be desirable in some circumstances to rotate the feet **132** such that the surface engagement portions **164** extend generally inward (generally toward each other) from the rear rails **114** but at an angle (e.g., in a direction back toward the first assembly **102**) relative to the plane in which the rear rails **114** extend. The surface engagement portions **164** may thus be configured to generally mimic or function as a v-rung for engagement with a pole (e.g., a power pole, telephone pole, etc.) or other vertical structure when the ladder **100** is in a straight ladder configuration. In one embodiment, the feet **132** may be rotated so that the surface engagement portions **164** extend at an angle of between approximately 20 degrees and approximately 45 degrees relative to the plane in which the rear rails **114** extend. Of course, the feet **132** may be placed in other angular positions as well.

[0175] In some embodiments, the feet **132** may be configured to be rotated to, and locked at, angular positions such that the surface engagement portions **164** extend generally outward from the rear rails **114** (away each other) but at an angle (away the first assembly **102**) relative to the plane in which the rear rails **114** extend such as is shown in dashed lines in FIG. **14**. The surface engagement portions **164** may then function as a wall stand-off device, providing increased width of contact with a wall (or gutter, or other supporting structure) when the ladder **100** is in a straight ladder configuration. In one embodiment, the feet **132** may be rotated so that the surface engagement portions **164** extend at an angle of between approximately 5 degrees and approximately 45 degrees relative to the plane in which the rear rails **114** extend. In some embodiments, the feet **132** may be rotated such that the surface engagement portions **164** extend directly towards each other (at 0 degrees) to minimize the width of the feet **132** in certain circumstances, including for storage or transportation. Of course, the feet **132** may be placed in other angular positions as well.

[0176] It is noted that, because the surface engagement portions **164** may engage a variety of different structures (e.g., ground, poles, walls, etc.), the surface engagement portions **164** may include a variety of surfaces (e.g., **164A**, **164B** and **164C**) having grooves, ribs, or other traction features formed therein. Thus, for example, a first surface **164A** may be configured to engage poles or other vertical structures when in a straight ladder configuration, a second surface **164B** may be configured to engage gutters or walls when in a straight ladder configuration, and a third surface **164C** may be configured to engage a ground surface when in a stepladder configuration.

[0177] Referring now to FIGS. **15A-18C**, a top cap **110** may include a variety of features. For example, as previously noted, a pair of channels **122** may be formed in a rear portion of the top cap **110**, the channels **122** being sized and configured to receive portions of the rear rails **114** therein when the ladder **100** is placed in a straight ladder configuration. When in a straight ladder configuration, a bottom (or innermost) surface **170A** of each channel **122** may contact a surface **172A** of an associated rear rail **114** (see, e.g., FIGS. **2** and **3**). Additionally, side surfaces **170B** and **170C** may be configured to provide lateral support by engaging corresponding side surfaces **172B** and **172C**, respectively, of an associated rear rail **114**. Thus, for example, if a force is applied to the ladder **100** in a lateral direction (e.g., as shown by directional arrows **174A** and **174B** in FIG. **2**), a minor amount of lateral deflection may occur in the rear rails **114** (and/or front rails **104**), wherein the side surfaces **170B** and **170C** act as stops or abutment members to limit further lateral deflection or displacement of the rear rails **114** relative to the front rails **104** due to the nesting of the rear rails **114** within the channels **122**.



[0178] As also previously mentioned, a cushion or pad **180** or other structure may be positioned along a rear face of the top cap **110** such that the top cap **110** may be leaned or pressed against, for example, a wall when used in a leaning configuration. As seen in FIGS. **15A-18C**, the top cap **110** may include a first body portion **182** that is coupled to the front rails **104**, and a second body portion **184** (which may include a detachable accessory) that is selectively positionable (and lockable) relative to the first body portion **182**. For example, the second body portion **184** may be positioned in a first position such that a surface **186** (on which the cushion or pad **180** may be located) is positioned generally adjacent to the rear face **188** of the first body portion **182**. It is noted that in some embodiments, the surface **186** and adjacent rear face **188** may be angled relative to each other (e.g., an angle measuring greater than **180** degrees when measuring from the surface **186** to the rear face **188**). In some embodiments, the rear face **188** may be angled such that it abuts against a surface of a rear rung **116** when in a straight ladder position or configuration, providing enhanced strength and rigidity to the ladder **100**. In other embodiments, there may be a gap or small space between the rear face **188** and the adjacent rear rung **116**.

[0179] In some embodiments, the second body portion **184** may be pivotally coupled with the first body portion **182** by way of a pivoting structure such that the second body portion **184** may rotate to at least a second position relative to the first body portion **182**. As seen in FIGS. **15B** and **15C**, a pivoting structure may include a pair of locking buttons **190** having keyed or geared portions **193** configured to engage corresponding openings **195** (e.g., openings that have portions sized and shaped to receive the keyed portions **193**) formed in the first body portion **182** of the top cap **110**. When the keyed portions **193** are engaged in corresponding openings **195**, as shown in FIGS. **15B** and **15C** (note that FIG. **15C** depicts the top cap **110** with the second body portion **184** removed for purposes of clarity), the second body portion **184** is locked in place and prevented from rotating relative to the first body portion **182**. However, when the locking buttons are displaced axially along a pivot axis such that the keyed portions **193** disengage the openings **195** (see FIGS. **16B** and **16C**—with FIG. **16C** depicting the top cap **110** with the second body portion **184** removed for purposes of clarity), the second body portion **184** and lock button may rotate relative to the first body portion **182** such as depicted in FIG. **16A**.

[0180] When the second body portion **184** is rotated to a second position (e.g., such as shown in FIG. **17**), and upon alignment of the keyed portions **193** with corresponding features in the opening **195**, the lock buttons **190** may be displaced axially by a biasing member **197**, such as a spring, such that they keyed portions **193** engage the openings **195** and the second portion **184** is locked into place relative to the first portion **182** in the second position.

[0181] As seen in FIG. **17**, when the second body portion **184** is rotated into a second position, various features of the second body portion **184** may protrude outwardly from the rear face **188** of the first body portion **182**. For example, the second body portion **184** may include a pair of protruding structures **192** providing a first pair of angled engagement surfaces **194A** and **194B**, a second pair of angled engagement surfaces **196A** and **196B**, and a channel **198** that is located adjacent to, and in between, the first pair of engagement surfaces **194A** and **194B**.

[0182] With the second body portion **184** selectively locked in the second position by locking buttons **190** (or by other appropriate mechanisms or structures such as detent mechanisms, latches, frictional arrangements, etc.), the first pair of angled engagement surfaces **194A** and **194B** may be positioned and oriented to define an interior angle of a desired magnitude therebetween (e.g., approximately 90 degrees). The second pair of engagement surfaces **196A** and **196B** may be positioned and oriented to define an exterior angle of a desired magnitude (e.g., approximately 90 degrees). In some embodiments, cushions or pads **199** may be placed on each of the engagement surfaces **194A**, **194B**, **196A** and **196B** such as best seen in FIG. **17**.

[0183] Referring to FIG. **18A**, when used in a leaning configuration (see, e.g., FIG. **4**), the ladder **100** may be leaned against an exterior wall corner **200** such that the first pair of engagement surfaces **194A** and **194B** each engage adjacent walls **202A** and **202B** that form the exterior corner

**200**, providing balance and stability to the ladder **100** and enabling a user to get laterally closer to the wall.

[0184] Referring to FIG. **18B**, when used in a leaning configuration, the ladder **100** may be leaned against an interior wall corner **204** such that the second pair of engagement surfaces **196A** and **196B** each engage adjacent walls **206A** and **206B** that form the interior corner **204**, again providing balance and stability to the ladder **100** and enabling a user to get laterally closer to the wall.

[0185] Further, when used in a leaning configuration the ladder **100** may be braced against a vertical support structure, such as a stud **208** (e.g., a vertically oriented 2×4, 2×6, etc.) of a framed wall, by positioning the stud **208** within the channel **198**, providing balance and stability to the ladder **100** and enabling a user to get laterally closer to the wall. Thus, in some embodiments, the channel **198** may be configured to exhibit a width between its side walls of approximately 1.5 inches or slightly larger (e.g., approximately 1.5625 to approximately 1.625 inches) to provide a sliding fit of a standardized stud within the channel **198**.

[0186] The top cap **110** may also include other features including, for example, openings **210** for placing tools or other components therein (e.g., screwdrivers, handles of hammers, etc.), recesses **212** for holding tools or supplies (e.g., nails or screws), or features for coupling accessories with the top cap. In some embodiments, such features may be formed in the first body portion **182**, in the second body portion **184**, or in both.

[0187] Referring to FIG. **19-23**, in some embodiments, the ladder **100** may include a selectively positionable rail member **220**. In one example, the rail member **220** may include a pair of side members **222**, with each side member **222** being rotatably coupled with an associated one of the rear rails **114**. The side members **222** may extend a substantial portion of the length of the rear rails **114**. In one embodiment, the cross-members **224** may extend between and be coupled with the side members **222**. When the rail member **220** is in the position or state shown in FIGS. **19-21**, at least some of the cross-members **224** may be spaced from each other such that they are located adjacent to associated rear rungs **116**. These cross-members **224** may serve as “depth extensions” of the rear rungs **116**, providing increased surface area on which a user may stand.

[0188] As seen in FIG. **22**, the rail member **220** may be rotated upwards relative to the rear rails **114** such that a substantial portion (e.g., half or more) of the rail member **220** extends upward above the top cap **110**. The rail member **220** may be locked in this, or other positions, relative to the first and second assemblies **102** and **112** (e.g., by way of detent mechanisms, latches, locking hinges, interference fits with the top cap **110** or other components, etc.). When locked in the position shown in FIG. **22**, the rail member **220** provides a stable device for a user to grasp while they are, for example, standing on the front rungs **106**. This enables a user to more safely stand on higher rungs of the ladder than without such a rail member **220**.

[0189] When the rail member **220** is positioned in a “stored” position relative to the rear rails **114**, such as shown in FIGS. **19-21**, the ladder **100** may still be placed in other configurations such as a straight ladder or a leaning ladder configuration. For example, as shown in FIG. **23**, the rail member **220** may rotate with the second assembly **112** relative to the first assembly **102**, into a straight ladder configuration, where at least some of the cross-members **224** are aligned with the rear rungs **116**, enabling a user to climb and stand on the rear rungs **116**, with the cross-members **224** providing increased surface area on which they may stand.

[0190] Referring briefly to FIG. **24**, in other embodiments, a rail member **230**, similar to that shown and described with respect to FIGS. **19-23**, may be associated with the first assembly **102** rather than the second assembly **112**. For example, the rail member **230** may be pivotally or rotatably coupled to the front rails **104**, and selectively rotatable from the position shown in FIG. **24**, to an upright position such that a substantial portion thereof extends upwards and above the top cap (similar to the rail member **220** shown in FIG. **22**). As with the embodiment shown and described with respect to FIGS. **19-23**, the rail member **230** may include side members **232** and cross-members **234** extending between, and coupled to, the side members **232**. At least some of the

cross-members **234** may be aligned with associated front rungs **106**, acting as depth extenders and providing an increased surface area on which a user may stand. As with the rail member **220** previously described, the rail members **230** may be locked into various positions by appropriate mechanisms.

[0191] Referring now to FIGS. **25A-38**, a hinge assembly **120** is shown. The hinge assembly **120** includes a first mounting leg **250** and a second mounting leg **252**. In some embodiments, the first mounting leg **250** may be configured for fixed coupling with the first assembly **102** (e.g., direct coupling with an associated front rail **104**). The second mounting leg **252** may be configured for fixed coupling with the second assembly (e.g., direct coupling with an associated rear rail **114**). As will be described hereinbelow, the first leg **250** and second leg **252** are selectively rotatable, relative to each other, about an axis **240**, and may be locked in a variety of different positions relative to each other.

[0192] FIG. **27** depicts an exploded view of the hinge assembly **120** and its various parts according to an embodiment of the present disclosure. In one embodiment, the first leg **250** may include a plate member **250A** and a lock ring **250B** fixedly coupled therewith. Likewise, the second leg **252** may include a plate member **252A** and a lock ring **252B** fixedly coupled therewith. A geared member **256** (e.g., a member having one or more projecting cogs **258** extending from a periphery thereof) and a biasing member, such as a spring **260**, are positioned between the two lock rings **250B** and **252B**. The geared member **256** includes a shaft member **262** that extends along the rotational axis **240** of the hinge assembly **120** and, in some embodiments, may at least partially extend through an opening in the second lock ring **252B**. In other embodiments, the second lock ring **252B** may not have an opening, and the shaft **262** may not extend beyond the second lock ring **252B**.

[0193] A hinge pin **264** extends through openings in the plates **250A** and **250B**, the lock rings **252A** and **252B**, and the geared member **256** along the rotational axis **240**. A nut **266** or other fastener may be coupled with the pin **264** to couple the assembly together.

[0194] A detent member or mechanism may be associated with the geared member **256** to hold the geared member **256** in a desired position along the axis **240** between the two lock rings **252A** and **252B** as will be described in further detail below. In some embodiments, the detent mechanism may include an annular coiled spring **268** (sometimes referred to as a canted spring) positioned in a recessed portion of the second lock plate **252B** and adjacent the associated plate member **252A** (although other configurations are also contemplated for the location of the spring and associated structures). An actuating button **270** may have a first portion **270A** located externally of the first plate member **250A**, and have at least another portion **270B** thereof (e.g., axial fingers) that extends through the plate member **250A** as well as a retainer member **171** (also shown in FIG. **26**) and is configured for establishing contact with the geared member **256**. Various fasteners (e.g., bolts, screws, rivets, clips, washers, etc.) may be used to couple the components of the hinge assembly together, in addition to the pin **264** and nut **266**.

[0195] In operation, the two legs **250** and **252** may be locked at a given angular orientation relative to each other, such as in the position shown in FIGS. **25A** and **25B**, or at a variety of other positions. As illustrated in FIGS. **28-31**, when the hinge assembly **120** is in a locked state, the geared member **256** is axially positioned such that one or more of its cogs **258** are partially disposed in an associated recess **272** of the first lock ring **250B** and partially disposed within an associated recess **274** of the second lock ring **252B**—the two recesses **272** and **274** being aligned with one another. Thus, the cog **258** provides an interference structure, preventing the first lock ring **250B** and the second lock ring **252B** from rotating relative to one another about the axis **240**. As seen best in FIG. **28**, when in a locked position, the geared member **256** is biased axially against an inner face **276** of the first lock ring **250B** by the biasing spring **260**. The biasing spring **260** may be placed between the second lock ring **252B** and the geared member **256**, and in some embodiments, positioned concentrically about the shaft member **262** of the geared member **256**.

[0196] Referring to FIGS. 32 and 33, when a user desires to unlock the hinge 120 and rotate the leg members 250 and 252 to different relative positions, a force is applied to the button 270 in the axial direction towards the geared member 256 as indicated by arrow 280. This force overcomes the biasing force of the spring 260 and effects displacement of the button 270, and thus displacement of the geared member 256, toward the second lock ring 252B. For example, comparing FIG. 32 with FIG. 28, a gap 282 is shown in FIG. 32 between the geared member 256 and the inner face 276 of the first lock ring 250B. Similarly, the gap 282 is enlarged in FIG. 33 as compared to that shown in FIG. 32, showing further displacement of the geared member 256 along the axis 240 away from the inner face 276 of the first lock ring along the axis 240. Additionally, in reviewing FIGS. 32 and 33, one can see the shaft member 262 being displaced along the axis 240 through an opening 284 of the second lock ring 252B and toward the second plate member 252A.

[0197] Referring to FIGS. 34-37, when the geared member 256 has become sufficiently displaced along the axis 240, the cogs 258 become axially displaced and disengaged from the recesses 272 of the first lock ring 250B while being further displaced into the recesses 274 of the second lock ring 252B. For example, as shown in FIGS. 36 and 37, the cogs 258 may be completely positioned within the recesses 274 of the second lock ring 252B while FIG. 34 shows the geared member 256 being axially positioned to contact an inner face 290 of the second lock ring 252B. Of course, other configurations are contemplated wherein the cogs are disengaged from the recesses 272 of the first lock ring 250B without necessarily abutting any axial surface (e.g., inner face 290) of the second lock ring 252B.

[0198] When in this position, the shaft member 262 has become displaced such that a first ramped section 292 is displaced through the opening 284 of the second lock ring 252B and beyond the annular spring 268 (which may be axially held in place by a washer or other structure) which radially contracts about an annular recessed portion 294 of the shaft and abuts a shoulder 296 positioned between the ramped section 292 and the recessed portion. The annular spring thus holds the shaft member 262 and gear member 256 in the position shown in FIGS. 34-37 (keeping the hinge assembly “unlocked”) until action is taken to release the shaft member 262 and gear member 256 from this position as will be described below. It is noted that the configuration of the shaft member 262 and the annular spring 268 acts as a detent or detent-like mechanism in holding the geared member 256 in a desired position until a prescribed force is applied to the gear member for its release. In other embodiments, other locking mechanisms, including other detent arrangements, may be used to hold the geared member 256 in a desired position during operation of the hinge.

[0199] Referring to FIG. 38, the first lock ring 250B may include a plurality of circumferentially-spaced, radially-inward extending protrusions 300 that may each include a pair of ramped or angled surfaces 302. One or more of the cogs 258 of the geared member 256 may additionally include chamfers 304 (which may be referred to as circumferentially oriented chamfers) formed at or near their radially outermost extents which are positioned and oriented to engage the ramped surfaces 302. When the hinge assembly 120 is in an unlocked state (e.g., see FIGS. 34-37), and the leg members 250 and 252 are rotated relative to each other, the ramped surfaces 302 of the radial protrusions 300 engage with the cogs 258 (e.g., with the chamfered portions 304), pushing the geared member 256 axially back towards the first lock ring 250B until the shaft member 262 is retracted a sufficient distance to become released from the annular spring 262 (placing the geared member 256 in axial position similar to that shown in FIG. 33). Upon further rotation of the leg members 250 and 252 relative to each other, some of the recesses 272 of the first lock ring 250B become aligned with the cogs 258 of the geared member 256 and the spring 260 forces the geared member 256 axially further towards the first lock ring 250B, locking the two leg members 250 and 252 from moving relative to each other. The hinge 120 may be repeatedly unlocked, rotated, and locked using a similar sequence of events, enabling the leg members 250 and 252 to be selectively locked in a variety of different relative positions including those that correspond with a step ladder configuration, a straight ladder configuration, and a leaning ladder, or stored ladder configuration.

[0200] It is noted that, in other embodiments, other hinge assemblies may be used with the ladder **100**. Other, non-limiting examples of hinges that may be used with ladders described herein is set forth in U.S. patent application Ser. No. 15/622,343, filed on Jun. 14, 2017, and U.S. Provisional Patent Application No. 62/514,348, filed on Jun. 2, 2017, the disclosures of which are incorporated by reference herein in their entireties.

[0201] Referring to FIGS. **39-43**, a foot **132** is shown in accordance with another embodiment of the disclosure. The foot **132** may include a body portion **320** having an opening **322** formed therein to receive a portion of a rail (e.g., rail **114** of the second assembly **112**). In one embodiment, the opening **322** may be configured as to receive a rail having a rectangular- or square-shaped profile such as shown in FIG. **39**. In other embodiments, the opening may be configured to receive other profiles or cross-sectional shapes including, for example, rails having a C-shaped or H-shaped cross-sectional profile.

[0202] The foot includes a first surface engaging portion **324**, which may be referred to as a horizontal surface engaging portion, and a second surface engaging portion **326**, which may be referred to as a vertical surface engaging portion. Each of the first and second surface engaging portions **324** and **326** may be configured to engage a support surface and resist movement of the foot **132** (and, thus, the ladder) relative to the support surface. The surface engaging portions **324** and **326** may include a variety of surfaces having grooves, ribs, or other traction features formed therein. For example, the first surface engaging portion **324** may include a plurality of ribs or ridges **328** extending across a width ‘W’ of the foot **132** (e.g., extending in a direction parallel with, or substantially parallel with, an axis that extends through both feet **132** of the ladder **100**). Adjacent ridges or ribs **328** may define parallel grooves extending therebetween. Thus, when the ladder **100** is in a step ladder state (e.g., as shown in FIG. **41**), the first surface engaging portion **324** will assist in resisting sliding or slipping, relative to the ground or other support surface, in a direction that is substantially perpendicular to the length of the ribs or ridges **328**. It is noted that the general surface geometry of the first surface engaging portion **324** may be arcuate, such as shown in the drawings, or may be generally flat or planar, or exhibit some other geometry.

[0203] Additionally, in one embodiment, the second engaging surface **326** may include a plurality of ribs or ridges **330** extending along a length ‘L’ in a direction that is substantially perpendicular to the ribs or ridges **328** of the first surface engaging portion **324**. It is noted that the second surface engaging portion **326** may extend the entire height of an adjacent rear wall **346**. Stated another way, the second surface engaging portion **326** may extend from approximately an upper end of the foot **132** (along a plane where the opening **322** is located) down to the first surface engaging portion **324**.

[0204] The second set of ribs or ridges **330** may also define generally parallel grooves between adjacent ridges **330** and be configured to resist or impede sliding or slipping, relative to a vertical wall or other support surface, in a direction substantially perpendicular to the length of the ribs or ridges **330**. Thus, when the ladder **100** is in a straight ladder configuration (FIGS. **42** and **43**), the second surface engaging portion **326** may rest against a wall (or other support structure) and resist sliding “sideways” along the surface of the wall. Of course, other anti-slip features, and other orientations or arrangements of anti-slip features are also contemplated as being formed in the surface engaging portions (e.g., patterns of raised protrusions having round, diamond or other polygonal geometries).

[0205] The body **320** may be defined by spaced apart side walls **340** and **342**, a front wall **344** extending between the side walls and a rear wall **346** spaced from the front wall **344** and extending between the side walls (it being noted that “front” and “rear” are simply used for purposes of convenience in designation of the different walls and that such should not be considered limiting). A thickened section **348**, which may also be referred to as a cushioned section, is positioned adjacent the rear wall **346** of the body **320**. Likewise, a thickened or cushioned section **350** may be positioned at the bottom of the foot **132**, opposite the opening **322** and below a floor of the body

**320** (not shown), which is coupled with at least one of the walls (**340**, **342**, **344**, **346**) or any combination of the walls, including all of them. The thickened or cushioned portions **348** and **350** may comprise a material that is softer and more yielding than that of the body **320** (e.g., the walls **340**, **342**, **344**, **346** and the floor). In some embodiments, the thickened portions **348** and **350** may include a non-marking rubberized or elastomer material that is overmolded onto a plastic body material. In other embodiments, the entire foot **132** may be formed as a unitary, homogenized component (or a substantially unitary, homogenized component) comprising a non-marking rubberized or elastomer material. The ridges and grooves of the surface engaging portions **324** and **326** may be formed in a surface of the thickened portions **348** and **350**, respectively.

[0206] The second surface engaging portion **326** (associated with the thickened or cushioned portion **348** positioned along the rear wall **346** of the body **320**) may be configured to exhibit a surface oriented at a desired angle relative to the longitudinal length of the rail to which it is coupled. Thus, for example, when the ladder **100** is in a straight ladder configuration and placed against a wall or other vertical support surface **360** (as shown in FIG. **42**), the second surface engaging portion **326** may form a projected angle  $\alpha$  with respect to a rear surface **362** of the associated rear rail **114**. In some embodiments, the angle  $\alpha$  may be between approximately 13 degrees and 17 degrees. In some embodiments, the angle  $\alpha$  may be between approximately 14 degrees and 16 degrees. In one embodiment, the angle  $\alpha$  may be approximately 15 degrees. Stated another way, the second surface engaging portion **326** may be angled such that when a ladder is leaned against a vertical support at a desired angle, the surface plane of the second surface engaging portion **326** is parallel, or substantially parallel, with the vertical support surface **360**.

[0207] In some embodiments, the foot **132** may be coupled to a rear rail **114** by fasteners (e.g., rivets, screws, etc.). In other embodiments, the foot **132** may be coupled with a rear rail **114** by adhesives. In other embodiments, the foot **132** may be coupled with the rear rail **114** by way of compression fit, interference fit, or by overmolding techniques. In one embodiment, the foot **132** may be coupled with a rear rail **114** using techniques and constructions describe in U.S. Provisional Patent No. 62/732,997, filed on Sep. 18, 2018, entitled COMBINATION LADDERS AND FOOT FOR COMBINATION LADDERS, the disclosure of which is incorporated by reference herein in its entirety.

[0208] Referring now to FIG. **44**, an accessory **400** is shown in accordance with an embodiment of the present disclosure. The in one embodiment, the accessory **400** may be configured such as shown in U.S. Design patent application Ser. No. 29/667,357, filed Oct. 19, 2018, and entitled “Accessory for Ladder,” the disclosure of which is incorporated by reference herein in its entirety.

[0209] The accessory **400** may include a variety of features including, for example, hooks, slots, and/or openings (generally indicated as **402**) for placing or attaching tools or other components therein (e.g., screwdrivers, handles of hammers, lanyards attached to power tools, electrical cords, etc.), recesses **404** for holding tools or supplies (e.g., nails or screws), and/or features for coupling accessories with the top cap. In one embodiment, notches may be formed for holding a tablet or a smart phone or other type of communications device. For example, as shown in FIG. **44**, one of the recesses (**404A**) may exhibit a shape and size to hold a cup or a paint can, but also include an adjacent recess **406** on a first side and one or more notches **408** aligned with the recess **406**, that are collectively and cooperatively sized and shaped for receipt of an electronic tablet or smart phone, enabling the tablet or smart phone to be positioned or propped up in a viewing mode for a user to watch or view (e.g., watch a “how to” video) while standing on the ladder.

[0210] The accessory **400** may include a pair of recesses or notches **410** formed in the body for receipt of ladder rails (e.g., ladder rails **114** of the second assembly **112**) for coupling the accessory **400** to a ladder. As shown in FIGS. **45-48**, the accessory **400** may be coupled to the ladder rails **114** of the second assembly **112** adjacent the feet **132** of the second assembly **112**. In some cases, the accessory **400** may be positioned adjacent the rung **116** that is closest to the feet **132**. For example, the accessory **400** may be removably coupled with the rails **114** of the second assembly **112** (using

a removable screw, bolt, or a latching device) and then be used or removed as desired by a user of the ladder. In some cases, the accessory **400** may be positioned adjacent a rung **116** or even take place of such a rung and be effectively fixed to the rails **114** of the second assembly **112** such that a user could not easily remove the accessory **400** in a nondestructive manner (e.g., such as by drilling through rivets or other fasteners or by destroying an adhesive or material bond between the accessory and the rails). Thus, when the ladder **100** is in a step ladder configuration (FIG. **45**) or a stored configuration (FIG. **46**), the accessory is positioned toward the “bottom” of the second assembly **112**. Additionally, as seen in FIGS. **45** and **46**, the accessory **400** is sized, shaped and positioned such that it doesn't cause interference between the second assembly **112** and the first assembly **102** when placed in the stored state (FIG. **45**).

[0211] Referring to FIGS. **47-49**, when the ladder **100** is in an extended state, the accessory may be positioned near the feet **132** adjacent the uppermost rung **116** (e.g., between the uppermost rung **116** and the feet **132**).

[0212] The accessory **400** may include a variety of features for engaging a support surface (e.g., a wall, post, or other structure). For example, the accessory **400** may include a first pair of angled engagement surfaces **420A** and **420B** positioned and oriented to define an interior angle of a desired magnitude therebetween (e.g., approximately 90 degrees). The accessory may further include a second pair of engagement surfaces **422A** and **422B** positioned and oriented to define an exterior angle of a desired magnitude (e.g., approximately 90 degrees). A third set of engagement surfaces **424A** and **424B** may be located between associated ones of the angled engagement surfaces (e.g., engagement surface **424A** is between angled surfaces **420A** and **422A**).

[0213] When the ladder is used in an extended configuration, the ladder **100** may be leaned against an exterior wall corner such that the first pair of engagement surfaces **420A** and **420B** each engage adjacent walls that form the exterior corner (such as described above with respect to embodiments of the top cap), providing balance and stability to the ladder **100** and enabling a user to get laterally closer to the wall. Additionally, when the ladder **100** is leaned against an interior wall corner, the second pair of engagement surfaces **420A** and **420B** each engage adjacent walls that form the interior corner (such as describe above with respect to embodiments of the top cap), again providing balance and stability to the ladder **100** and enabling a user to get laterally closer to the wall. Likewise, when the ladder **100** is leaned against a flat wall or support structure, the third engagement surfaces **424A** and **424B** may engage the flat surface to provide a stable support.

[0214] In some embodiments, the engagement surfaces may be configured with ribs and grooves to provide a traction or gripping surface. In some embodiments, additional cushions or pads may be placed on each of the engagement surfaces. The engagement surfaces may, thus, be configured to provide added traction or stability when engaging support surfaces, as well as be configured to avoid marring or marking the support surface with which they engage.

[0215] Further, a notch or recess **426** may be positioned in the center of the accessory, between the first angled engagement surfaces **420A** and **420B**, so that the ladder **100** may be braced against a vertical support structure, such as a stud (e.g., a vertically oriented 2×4 or 2×6) of a framed wall, by positioning the stud within the notch or recess **426**, providing balance and stability to the ladder **100** and enabling a user to get laterally closer to the wall. Thus, in some embodiments, the channel **426** may be configured to exhibit a width between its side walls of approximately 1.5 inches or slightly larger (e.g., approximately 1.5625 to approximately 1.625 inches) to provide a sliding fit of a standardized stud within the channel **426**.

[0216] Referring now to FIGS. **50-53**, a ladder **100** is shown in accordance with another embodiment of the disclosure. The ladder **100** may be configured generally similar to other embodiments described herein, but also includes a height-adjustable top cap **110**. The top cap **110** is coupled to a pair of extension members **440**. Each extension member **440** is slidably coupled with an upper portion of an associated front rail **104** of the first assembly **102**. In one embodiment, the sliding members **440** may be at least partially disposed within a channel or recess formed by the

front rails **104** (e.g., in the hollow of a c-channel from which the rails may be formed). Locking mechanisms **442** may be used to selectively lock the extension members **440** in desired positions relative to the front rails **104**. For example, in one embodiment, the locking mechanisms may include a pin that extends through its associated front rail **104** and selectively extends into, and retracts out of, openings or recesses formed in the extension members **440**. Thus, the top cap **110** may be locked in a collapsed or retracted position as shown in FIGS. **50** and **51** such that the ladder functions similar to previously described embodiments. However, a user may selectively actuate the locking mechanisms **442** to release the extension members **440**, displace the top cap upwards to an extended position, and then release or re-actuate the locking mechanisms **442** to selectively lock the top cap in the new extended position as shown in FIGS. **52** and **53**. Of course, the top cap may be positioned, and selectively locked, at a variety of additional heights (e.g., partially extended) between the two positions shown in FIGS. **50-53**.

[0217] When placed in an extended position, such as shown in FIGS. **52** and **53**, the top cap **110** may serve as a working surface, or as a stabilizing structure, for a user standing on an upper rung **106** of the first assembly **102**. It is noted that, as shown in FIGS. **52** and **53**, the uppermost rung **106** of the first assembly **102** may be configured with increased surface area for a user to stand on. For example, the uppermost rung **106** may include a portion **106A** that extends beyond the edges of the front rails **104** of the first assembly **102** and towards the second assembly **112**. In some embodiments, the increased surface area of this rung **106**, as well as the height-extended top cap **110**, may provide a more comfortable and/or stable structure to work from.

[0218] Referring now to FIGS. **54-57**, a top cap **110** is shown and described with a second body portion **460**, or accessory, according to another embodiment of the present disclosure. The top cap **110** may include a first body portion **182** that is coupled to the front rails **104** (or to extension members such as previously described), and a second body portion **460** (which may include a detachable accessory) that is selectively positionable (and lockable) relative to the first body portion **182**. For example, the second body portion **460** may be positioned in a first position such that a surface **462** (on which a cushion or pad **464** may be located) is positioned generally adjacent to the rear face **188** of the first body portion **182**. It is noted that in some embodiments, the surface **462** and adjacent rear face **188** may be angled relative to each other (e.g., an angle measuring greater than **180** degrees when measuring from the surface **462** to the rear face **188**) such as has been described with respect to other embodiments herein. In some embodiments, the rear face **188** may be angled such that it abuts against a surface of a rear rung **116** when in a straight ladder or extended configuration, providing enhanced strength and rigidity to the ladder **100**. In other embodiments, there may be a gap or small space between the rear face **188** and the adjacent rear rung **116**.

[0219] In some embodiments, the second body portion **460** may be pivotally coupled with the first body portion **182** by way of a pivoting structure (e.g., such as associated with locking buttons **190** previously described herein), such that the second body portion **460** may rotate to at least a second position relative to the first body portion **182**. When the second body portion **460** is rotated to a second position (e.g., such as shown in FIG. **55**), the second portion **184** may be locked into place relative to the first portion **182**.

[0220] As seen in FIG. **55**, when the second body portion **460** is rotated into a second position, various features of the second body portion **460** may protrude outwardly from the rear face **188** of the first body portion **182**. For example, the second body portion **460** may include a pair of protruding bodies or structures **470** providing a first pair of angled engagement surfaces **472A** and **472B**, a second pair of angled engagement surfaces **474A** and **474B**, and a channel **476** that is located adjacent to, and in between, the first pair of engagement surfaces **472A** and **472B** (see, also, FIG. **57**).

[0221] With the second body portion **460** selectively locked in the second position by locking buttons **190** (or by other appropriate mechanisms or structures such as detent mechanisms, latches,



frictional arrangements, etc.), the first pair of angled engagement surfaces **472A** and **472B** may be positioned and oriented to define an interior angle of a desired magnitude therebetween (e.g., approximately 90 degrees). The second pair of engagement surfaces **474A** and **474B** may be positioned and oriented to define an exterior angle of a desired magnitude (e.g., approximately 90 degrees). In some embodiments, cushions or pads may be placed on the engagement surfaces. [0222] As with previously described embodiments, when used in a leaning configuration, the ladder **100** may be leaned against an exterior wall corner such that the first pair of engagement surfaces **472A** and **472B** each engage adjacent walls that form the exterior corner, providing balance and stability to the ladder **100** and enabling a user to get laterally closer to the wall. Additionally, the ladder **100** may be leaned against an interior wall corner such that the second pair of engagement surfaces **474A** and **474B** each engage adjacent walls that form the interior corner, again providing balance and stability to the ladder **100** and enabling a user to get laterally closer to the wall.

[0223] Further, when used in a leaning configuration the ladder **100** may be braced against a vertical support structure, such as a stud or a post or pole (e.g., a vertically oriented 2×4, 2×6, etc.) of a framed wall, by positioning the stud within the channel **476**, providing balance and stability to the ladder **100** and enabling a user to get laterally closer to the wall. Thus, in some embodiments, the channel **476** may be configured to exhibit a width between its side walls of approximately 1.5 inches or slightly larger (e.g., approximately 1.5625 to approximately 1.625 inches) to provide a sliding fit of a standardized stud within the channel **476**.

[0224] When the second body portion **460** is in the first position (see FIG. **54**), the pad **464** and/or surface **462** may be abutted against a generally planar support surface to provide stability to the ladder **100** while in a leaning configuration.

[0225] As further depicted in FIGS. **56** and **57**, it is additionally noted that the protruding bodies or structures **470** may be configured as containers, having a substantially hollow internal space **480** or cavity and a removable lid **482**. In one embodiment, the lid **482** may be coupled with the protruding structure **470** by way of a hinge **484**. Thus, the second body portion **460** may serve multiple functions, including providing a convenient storage space for supplies, tools or other resources that can stay within the container even when the ladder **100** is not being used or while its being transported or stored.

[0226] Referring to FIGS. **58-61** a foot **132** is shown in accordance with another embodiment of the disclosure. The foot **132** may include a body portion **500** having an opening **502** formed therein to receive a portion of a rail (e.g., rail **114** of the second assembly **112**). In one embodiment, the opening **502** may be configured as to receive a rail having a rectangular- or square-shaped profile. In other embodiments, the opening may be configured to receive other profiles or cross-sectional shapes including, for example, rails having a C-shaped or H-shaped cross-sectional profile.

[0227] The foot **132** includes a first surface engaging portion **504**, which may be referred to as a horizontal surface engaging portion, a second surface engaging portion **506**, which may be referred to as a planar vertical surface engaging portion, and a third surface engaging portion **508**, which may be referred to as an angular or corner surface engaging portion. Each of the first, second and third surface engaging portions **504**, **506** and **508** may be configured to engage a support surface and resist movement of the foot **132** (and, thus, the ladder) relative to the support surface. The surface engaging portions **504**, **506** and **508** may include a variety of surfaces having grooves, ribs, or other traction features formed therein. For example, the first surface engaging portion **504** may include a plurality of ribs or ridges **510** extending across a width 'W' of the body **500** (e.g., extending in a direction parallel with, or substantially parallel with, an axis that extends through both feet **132** of the ladder **100**). Adjacent ridges or ribs **510** may define parallel grooves extending therebetween. Thus, when the ladder **100** is in a step ladder state, the first surface engaging portion **504** will assist in resisting sliding or slipping, relative to the ground or other support surface, in a direction that is substantially perpendicular to the length of the ribs or ridges **510**. It is noted that

the general surface geometry of the first surface engaging portion **504** may be planar (with the peaks of the ridges extending to a common plane), such as shown in the drawings, or may be generally arcuate, or exhibit some other geometry.

[0228] Additionally, in one embodiment, the second engaging surface **506** may include a plurality of ribs or ridges **512** extending along a length 'L' in a direction that is substantially perpendicular to the ribs or ridges **510** of the first surface engaging portion **504**. In one embodiment, the second surface engaging portion **506** may extend from approximately an upper end of the foot **132** (along a plane where the opening **502** is located) down to the first surface engaging portion **504**.

[0229] The second set of ribs or ridges **512** may also define generally parallel grooves between adjacent ridges **512** and be configured to resist or impede sliding or slipping, relative to a vertical wall or other support surface, in a direction substantially perpendicular to the length of the ribs or ridges **512**. Thus, when the ladder **100** is in a straight ladder configuration (such as previously described with respect to FIGS. **42** and **43** hereinabove), the second surface engaging portion **506** may rest against a wall (or other support structure) and resist sliding "sideways" along the surface of the wall. Of course, other anti-slip features, and other orientations or arrangements of anti-slip features are also contemplated as being formed in the surface engaging portions (e.g., patterns of raised protrusions having round, diamond or other polygonal geometries).

[0230] The third engaging surface **508** may be oriented generally at an angle relative to the second engaging surface **506**. For example, in one embodiment, the third engaging surface **508** may be oriented generally at an angle of approximately 45 degrees relative to the second engaging surface. In one embodiment, the third engaging surface **508** may include a plurality of ribs or ridges **514** extending along a length in a direction that is substantially parallel to the ribs or ridges **512** of the second surface engaging portion **504**. In one embodiment, the third surface engaging portion **508** may extend from approximately an upper end of the foot **132** (along a plane where the opening **502** is located) down to the first surface engaging portion **504**.

[0231] The third set of ribs or ridges **514** may also define generally parallel grooves between adjacent ridges **514** and be configured to resist or impede sliding or slipping, relative to a vertical wall or other support surface, in a direction substantially perpendicular to the length of the ribs or ridges **514**. In one embodiment, the feet **132** may be placed on the rear rails **114** of a ladder such that the third engagement surfaces **508** face generally inwardly (toward each other) so that, when the ladder is in a straight ladder configuration, the third engagement surfaces **508** can engage the adjacent walls **516** (or other support structures) that form an exterior 90 degree corner such as shown in FIG. **60**. In another embodiment, the feet **132** may be placed on the rear rails **114** of a ladder such that the third engagement surfaces **508** face generally outwardly (toward each other) so that, when the ladder is in a straight ladder configuration, the third engagement surfaces **508** can engage the adjacent walls **518** (or other support structures) that form an interior 90 degree corner such as shown in FIG. **61**. The feet **132** may be removable from the rear rails **114** to accommodate a change in engaging interior corners and exterior corners.

[0232] In other embodiments, the feet **132** may include a fourth engagement surface positioned such that the second engagement surface **506** is located between the third engagement surface **508** and the fourth engagement surface. The fourth engagement surface may be configured generally similarly to the third engagement surface **508** and be generally oriented at an angle of approximately 90 degrees from the third engagement surface such that a single foot may be used to engage flat, vertically planar surfaces (see FIG. **42**), exterior corners (see FIG. **60**) and interior corners (see FIG. **61**).

[0233] For embodiments having three or four (or more) engagement surfaces, the foot **132** may be generally configured similar to that which is described above regarding FIGS. **39-42** with respect to materials, wall segments, thickened or cushioned portions, etc.

[0234] Referring to FIGS. **62-64**, a ladder **100** is shown having a spreader structure **540**. The spreader structure **540** may include a generally U-shaped bar or hoop having a pair of laterally

spaced legs **542** and an end portion or a connecting leg **544** extending between the laterally spaced legs **542**. Each of the laterally spaced legs **542** may have an end **546** thereof hingedly or pivotally coupled to the first assembly **102** by way of associated brackets **548**. The spreader structure may include a laterally outward extending bend **550** formed in each of the laterally spaced legs **542**. The connecting leg **544** may have a discrete section **552** configured to exhibit a width that is less than a width of the space between the rear rails **114**. When the ladder **100** is in a step ladder configuration, such as shown in FIG. **62**, the spreader structure **540** extends rearwardly from the first assembly **102** and encircles the second assembly **112**. The spreader structure **540** serves to reinforce the locking hinge mechanisms **120** and prevent the second assembly **112** from splaying relative to the first assembly **102**. If the second assembly **112** attempts to splay relative to the first assembly **102**, the connecting portion **544** will catch on a portion of an abutment bracket **560** that protrudes rearwardly from a rear surface of the rear rails **114**, preventing the spreader structure from sliding further upwards on the rear rails **114**, thereby preventing the splaying of the second assembly **112** relative to the first assembly **102** when the ladder **100** is in a step ladder configuration.

[0235] Thus, with larger ladders (e.g., 8 foot ladders or taller, when in a step ladder configuration), the spreader structure **540** may provide additional strength and stability to the ladder **100**.

[0236] As seen in FIG. **63**, when the ladder **100** is in a leaning or stored configuration, the spreader structure **540** pivots to collapse against the second assembly **112**, with the discrete section **552** of the connecting leg **544** extending between the rear rails **114**. Additionally, when the ladder **100** is in a straight ladder configuration, as shown in FIG. **64**, the spreader structure **540** pivots upward such that lateral extending bends **550** pass over the hinge mechanisms **120** (and any associated bracketing). A gain the discrete section **552** of the connecting leg **544** extends between the rear rails **114**. Thus, the spreader structure **540** may pivot automatically as the ladder **100** transitions from a straight ladder configuration, to a step ladder configuration, and then to a leaning configuration.

[0237] Referring now to FIGS. **65-68**, a ladder **600** is shown according to another embodiment of the present disclosure. The ladder **600** is configured generally as described with respect to the ladder **100** described hereinabove, including a first assembly **102** coupled with a second assembly **112** by way of hinges **120**. The ladder **600** may further include a top cap **110** and other features such as described hereinabove. However, the second assembly **112** may be configured with an inner rail assembly **602** having a pair of rails **604** and a plurality of rungs **606**, and an outer rail assembly **612** having a pair of rails **614** and a plurality of rungs **616**. The outer assembly **612** is slidably coupled with the inner rail assembly **602**. Thus, the inner and outer rail assemblies **602** and **612** may be collapsed, such as shown in FIG. **65** (and FIG. **66**), such that most (if not all) of the rungs **606** of the inner assembly **602** and most (if not all) of the rungs **616** of the outer assembly **612** are aligned in pairs so as to act as a single “step” when a user stands on the rungs **606** and **616**.

[0238] The outer assembly **612** may be extended from the inner assembly **602**, such as shown in FIGS. **67** and **68** to adjust the length of the second assembly **612**. For example, when in a step ladder configuration, the second assembly **612** may be extended for use on stairs or some other uneven support surface. Additionally, when in a straight ladder or extended configuration, such as shown in FIG. **68**, the second assembly **602** may be extended to reach greater heights. The second assembly **612** may be adjusted to several different heights, with each height corresponding with an increment of adjustment equal to the spacing between adjacent rungs (e.g., between adjacent rungs **606** of the inner assembly **602** or between adjacent rungs **616** of the outer assembly **612**).

[0239] Adjustment mechanisms **620**, also referred to as locking mechanisms, may be used to selectively release the outer rail assembly **612** from the inner rail assembly **602** and to selectively lock or maintain the inner and outer rail assemblies **602** and **612** relative to each other. Examples of locking mechanisms and related inner/outer assembly configurations are described, for example, in U.S. Pat. No. 8,186,481, issued May 29, 2012, the disclosure of which is incorporated by reference herein in its entirety.

[0240] While the invention may be susceptible to various modifications and alternative forms,

specific embodiments have been shown by way of example in the drawings and have been described in detail herein. However, it should be understood that the invention is not intended to be limited to the particular forms disclosed. Additionally, features, components and elements of one embodiment may be combined with features, components and elements of other embodiments without limitation. The invention includes all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.

## Claims

1. A combination ladder, comprising: a first rail assembly, including: a first pair of rails spaced apart from each other, wherein lower ends of the first pair of rails are spaced a greater distance apart than upper ends of the first pair of rails; a first set of cross-members extending between and coupled to the first pair of rails, wherein the first set of cross-members is positioned entirely within a first volumetric envelope defined between front faces of the first pair of rails and opposite rear faces of the first pair of rails, and wherein a first cross-member of the first set of cross-members extending between the lower ends of the first pair of rails has a greater length than a second cross-member of the first set of cross-members extending between the upper ends of the first pair of rails; a pair of feet respectively coupled to the first pair of rails; a pair of brace members coupled to the first cross-member and coupled to the first pair of rails below the first cross-member; and a top cap extending between and coupled to the upper ends, wherein two channels are formed in the top cap and each include two lateral side surfaces and an innermost surface extending between the two lateral side surfaces, wherein the innermost surfaces of the two channels face toward a rear side of the top cap; and a second rail assembly, including: a second pair of rails spaced apart from each other; a second set of cross-members extending between and coupled to the second pair of rails; wherein the second rail assembly is pivotally coupled with the first rail assembly at a pair of hinges, wherein the first pair of rails and the second pair of rails are lockable in at least a first position, a second position, and a third position by a locking mechanism including at least two laterally-displaceable members; wherein in the first position, the first pair of rails is arranged parallel to the second pair of rails and with the lower ends of the first pair of rails adjacent to the second pair of rails, wherein in the second position, the first pair of rails is arranged in a stepladder configuration relative to the second pair of rails; wherein in the third position, the first pair of rails is arranged parallel to the second pair of rails, with the lower ends of the first pair of rails extending away from the second pair of rails, with the two channels at least partially receiving the second rail assembly nested within at least three sides of each channel of the two channels; wherein in the third position, the top cap provides an upper support surface to support a user ascending or descending the ladder; and wherein the at least two laterally-displaceable members are movable between a locked position and an unlocked position, the locked position being laterally outwardly positioned relative to the unlocked position; wherein the first pair of rails and the second pair of rails each comprise at least one composite fiberglass material.
2. The combination ladder of claim 1, wherein in the third position, the second pair of rails is offset from the first pair of rails.
3. The combination ladder of claim 1, wherein the at least two laterally-displaceable members are separately movable between their locked and unlocked positions.
4. The combination ladder of claim 1, wherein a pivot axis of the pair of hinges is offset from a longitudinal axis of the first pair of rails.
5. The combination ladder of claim 1, wherein the first set of cross-members comprises rungs or steps.
6. A combination ladder, comprising: a first assembly, including: a first pair of rails spaced apart from each other, wherein lower ends of the first pair of rails are spaced a greater distance apart than upper ends of the first pair of rails; a first set of cross-members extending between and coupled to

the first pair of rails, wherein the first set of cross-members is positioned entirely within a first volumetric envelope defined between front faces of the first pair of rails and opposite rear faces of the first pair of rails, and wherein a first cross-member of the first set of cross-members extends between the lower ends of the first pair of rails has a greater length than a second cross-member of the first set of cross-members extending between the upper ends of the first pair of rails; a pair of feet respectively coupled to the first pair of rails; and a pair of brace members coupled to the first cross-member and coupled to the first pair of rails below the first cross-member; a top cap extending between and coupled to the upper ends, wherein two channels are formed in the top cap and each include two lateral side surfaces and an innermost surface extending between the two lateral side surfaces, wherein the innermost surfaces of the two channels face toward a rear side of the top cap; and a second assembly, including: a second pair of rails spaced apart from each other, each of the second pair of rails including a main portion and a mounting portion; and a second set of cross-members extending between and coupled to the second pair of rails; a pair of hinge assemblies coupled to upper ends of the second pair of rails via the mounting portions of the second pair of rails, the pair of hinge assemblies effecting pivoting coupling between the first pair of rails and the second pair of rails, wherein the first pair of rails and the second pair of rails are lockable in at least a first position, a second position, and a third position by a locking mechanism including at least two laterally-displaceable members; wherein in the first position, the first pair of rails is arranged parallel to the second pair of rails and with the lower ends of the first pair of rails adjacent to the second pair of rails, wherein in the second position, the first pair of rails is arranged in a stepladder configuration relative to the second pair of rails; wherein in the third position, the first pair of rails is arranged parallel to the second pair of rails, with the lower ends of the first pair of rails extending away from the second pair of rails, with the two channels at least partially receiving the second pair of rails, and with each channel of the two channels at least partially covering at least three sides of each of the second pair of rails; wherein in the third position, the top cap provides an upper support surface to support a user ascending or descending the ladder; and wherein the at least two laterally-displaceable members are movable between a locked position and an unlocked position, the locked position being laterally outwardly positioned relative to the unlocked position; wherein the first pair of rails and the second pair of rails each comprise at least one composite fiberglass material.

**7.** The combination ladder of claim 6, wherein in the third position, the second pair of rails is offset from the first pair of rails.

**8.** The combination ladder of claim 6, wherein the at least two laterally-displaceable members are separately movable between their locked and unlocked positions.

**9.** The combination ladder of claim 6, wherein a pivot axis of the pair of hinges is offset from a longitudinal axis of the first pair of rails.

**10.** The combination ladder of claim 6, wherein the first set of cross-members comprises rungs or steps.

**11.** A combination ladder, comprising: a first assembly, including: a pair of rails spaced apart from each other, wherein lower ends of the pair of rails are spaced a greater distance apart than upper ends of the pair of rails; a first set of cross-members extending between and coupled to the pair of rails, wherein the first set of cross-members is positioned entirely within a first volumetric envelope defined between front faces of the pair of rails and opposite rear faces of the pair of rails, and wherein a first cross-member of the first set of cross-members extending between the lower ends of the pair of rails has a greater length than a second cross-member of the first set of cross-members extending between the upper ends of the pair of rails; a pair of feet respectively coupled to the pair of rails; and a pair of brace members coupled to the pair of rails and to the first cross-member, the pair of brace members extending toward the pair of feet from the first cross-member; and a top cap extending between and coupled to the upper ends, wherein two channels are formed in the top cap and each include two lateral side surfaces and an innermost surface extending

between the two lateral side surfaces, wherein the innermost surfaces of the two channels face toward a rear side of the top cap; and a second assembly, including: a pair of substantially linear members spaced apart from each other; and a second set of cross-members extending between and coupled to the pair of substantially linear members; wherein upper ends of the pair of substantially linear members are pivotally coupled with the pair of rails at a pair of hinges, wherein the pair of rails and the pair of substantially linear members are lockable in at least a first position, a second position, and a third position by a locking mechanism including at least two laterally-displaceable members; wherein in the first position, the pair of rails is substantially parallel to the pair of substantially linear members with the lower ends of the pair of rails adjacent to the pair of linear members, wherein in the second position, the pair of rails is in a stepladder configuration relative to the pair of substantially linear members; wherein in the third position, the pair of rails is parallel to the pair of substantially linear members with the lower ends of the pair of rails extending away from the pair of substantially linear members, with the two channels receiving the pair of substantially linear members, and with each channel of the two channels at least partially covering at least three sides of each substantially linear member of the second pair of substantially linear members; wherein in the third position, the top cap provides an upper support surface to support a user ascending or descending the ladder; and wherein the at least two laterally-displaceable members are movable between a locked position and an unlocked position, the locked position being laterally outwardly positioned relative to the unlocked position.

**12.** The combination ladder of claim 11, wherein in the third position, the pair of substantially linear members is offset from the pair of rails.

**13.** The combination ladder of claim 11, wherein the at least two laterally-displaceable members are separately movable between their locked and unlocked positions.

**14.** The combination ladder of claim 11, wherein a pivot axis of the pair of hinges is offset from a longitudinal axis of the pair of rails.

**15.** The combination ladder of claim 11, wherein the first set of cross-members comprises rungs or steps.

**16.** The combination ladder of claim 11, wherein each substantially linear member of the pair of substantially linear members includes a main portion and a mounting portion, the mounting portion being positioned at the upper end of the substantially linear member, extending from the main portion, and pivotally coupled with the first assembly at the pair of hinges.

---