

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12384324
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Penfold; Harrison Luke et al.

---

### Tongue assembly

---

#### Abstract

A locking tongue assembly for a seatbelt system includes a body having a belt webbing opening through which a belt webbing is passable and in which a cinch bar is locatable for cinching the belt webbing, the cinch bar having a main body portion and first and second end portions, the belt webbing opening being defined by axially spaced apart first and second sidewalls, each of which is adapted to receive a respective end portion of the cinch bar, and a stop portion in the belt webbing opening for urging against the main body portion of the cinch bar.

---

<b>Inventors:</b>	<b>Penfold; Harrison Luke (Campbellfield, AU), Hickling; Cameron Scott (Campbellfield, AU), Hickling; Harry Charles William (Campbellfield, AU), Keesing; Douglas Lewis Moss (Campbellfield, AU)</b>
<b>Applicant:</b>	<b>APV Corporation Pty Ltd (Campbellfield, AU)</b>
<b>Family ID:</b>	<b>1000008751042</b>
<b>Assignee:</b>	<b>APV CORPORATION PTY LTD. (Campbellfield, AU)</b>
<b>Appl. No.:</b>	<b>17/926770</b>
<b>Filed (or PCT Filed):</b>	<b>May 19, 2021</b>
<b>PCT No.:</b>	<b>PCT/AU2021/050467</b>
<b>PCT Pub. No.:</b>	<b>WO2021/232097</b>
<b>PCT Pub. Date:</b>	<b>November 25, 2021</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230202424 A1	Jun. 29, 2023

#### Foreign Application Priority Data

---

## Publication Classification

**Int. Cl.:** B60R22/30 (20060101); A44B11/25 (20060101); B60R22/12 (20060101)

**U.S. Cl.:**

**CPC** B60R22/30 (20130101); A44B11/2553 (20130101); A44B11/2561 (20130101); B60R22/12 (20130101);

## Field of Classification Search

**CPC:** A44B (11/2553); A44B (11/2561); A44B (11/2549); A44B (11/2557); B60R (22/30); B60R (22/12); B60R (2022/1812); B60R (2022/285); Y10T (24/4016); Y10T (24/4047); Y10T (24/45241); Y10T (24/4084)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4551889	12/1984	Narayan	N/A	N/A
4962572	12/1989	Prentkowski	N/A	N/A
5058244	12/1990	Fernandez	N/A	N/A
5806148	12/1997	McFalls	24/171	A44B 11/2561
5870816	12/1998	McFalls	N/A	N/A
9409537	12/2015	Zhang	N/A	B60R 22/28
2007/0050953	12/2006	Versellie	N/A	N/A
2012/0068520	12/2011	McFalls	24/593.1	A44B 11/2561
2013/0341994	12/2012	Boughner	N/A	N/A
2015/0314749	12/2014	Moker	N/A	N/A
2016/0206050	12/2015	Aoyagi	N/A	B60R 22/30
2017/0144623	12/2016	Cahill	N/A	B60R 22/28
2018/0220749	12/2017	Kato	N/A	A44B 11/2561
2019/0135224	12/2018	Krambeck	N/A	B60R 22/1855
2019/0263349	12/2018	Ruthinowski	N/A	N/A
2021/0345734	12/2020	Hermann	N/A	A44B 11/2557

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2011062966	12/2010	WO	N/A
2013099590	12/2012	WO	N/A

### OTHER PUBLICATIONS

International Search Report and Written Opinion from PCT/AU2021/050467, mailed Jul. 19, 2021 (11 pages). cited by applicant

---

## Background/Summary

### CROSS REFERENCES TO RELATED APPLICATIONS

(1) This application is a U.S. National Stage of International Application No. PCT/AU2020/050467, filed May 19, 2021, and entitled “TONGUE ASSEMBLY,” which claims priority to Australian Patent Application No. 2020901613, filed on May 20, 2020, which are each hereby incorporated by reference in their entirety.

### FIELD OF THE INVENTION

(2) The invention relates to a locking tongue assembly for a seatbelt system.

### BACKGROUND

(3) Existing locking tongues assemblies have a cinch bar that is located in a locking tongue body for clamping a belt webbing as a safety feature. Existing locking tongue assemblies are prone to vandalism. In particular, a person could easily pull or dislodge the cinch bar from the locking tongue body thereby disabling or compromising the safety feature of the locking tongue assembly.

(4) There is a need for improved locking tongue assembly that is tamperproof and/or that cannot be disassembled.

(5) Accordingly, it is desired to address one or more of the above or at least provide a useful alternative.

### SUMMARY OF THE INVENTION

(6) According to an aspect of the present invention, there is provided a tongue assembly for a seatbelt system, the tongue assembly including: a body having a belt webbing opening through which a belt webbing is passable and in which a cinch bar is locatable for cinching the belt webbing, the cinch bar having a main body portion and first and second end portions, the belt webbing opening being defined by axially spaced apart first and second sidewalls each of which is adapted to receive a respective end portion of the cinch bar, and a stop portion in the belt webbing opening for urging against the main body portion of the cinch bar when the cinch bar is in a first position in which only the first end portion of the cinch bar is received by a first sidewall while the second end portion is aligned with the second sidewall without being received by the second sidewall, wherein moving the cinch bar from the first position towards the second sidewall in a second position where the second end portion of the cinch bar is received by the second sidewall results in the body portion of the cinch bar being removed from the stop portion, wherein, in the second position, the first sidewall still receives a portion of the first end portion, and wherein the stop portion prevents movement of the main body portion towards the first sidewall thereby trapping the cinch bar within the belt webbing opening.

(7) The cinch bar is preferably rotatable in the belt webbing opening when the cinch bar is in the second position to cinch the belt webbing. The stop portion preferably resists rotation of the cinch bar when the cinch bar is in the first position.

(8) When the cinch bar is in the first position, the second end portion of the cinch bar is up to about 3.5 mm from the second sidewall. Preferably the second end portion of the cinch bar is between about 0.1 mm and 3.5 mm from the second sidewall. Further preferably, the second end portion of the cinch bar is up to about 2.3 mm from the second sidewall. In other embodiments, the second end portion is about 1.5 mm from the second sidewall when the cinch bar is in the first position.

(9) The tongue assembly preferably further includes the cinch bar. The main body and the two end portions of the cinch bar may be integrally formed as a single piece.

(10) The first end portion of the cinch bar may be frustoconical. In some embodiments, each of the first and second end portions are frustoconical. The frustoconical end portion may have a tapered wall portion at an angle of up to  $30^{\circ}$  to a longitudinal angle through the cinch bar. Preferably, the tapered wall is at an angle of up to about  $10^{\circ}$ . Further preferably, the angle of the tapered wall is between  $1^{\circ}$  and about  $5^{\circ}$  inclusive to a longitudinal axis through the cinch bar. More preferably, the angle is at least about  $2^{\circ}$ .

(11) The first end portion of the cinch bar is preferably longer than the second end portion of the cinch bar. The first end portion may be at least 1.5 times a length of the second end portion. Preferably, the first end portion is at least 2.0 times the length of the second end portion.

(12) The first sidewall preferably has an aperture for receiving the first end portion, the aperture being defined by tapered wall portion to define a narrow or restricted opening into the aperture. The second sidewall preferably also has an aperture for receiving the second end portion. The aperture in the second side wall may also be defined by a tapered wall portion to define a narrow or restricted opening into the aperture. Alternatively, the aperture in the first or second sidewalls may be substantially cylindrical.

(13) The stop portion preferably creates an interference to the cinch bar in the first position.

(14) A range of side-to-side movement of the cinch bar in the belt webbing opening after the cinch bar is in the second position is may be less than each of the first and second end portions.

(15) A distance of the first sidewall to an edge of the stop portion against which the cinch bar is braceable is preferably less than a length of the first end portion.

(16) The stop portion may be adjacent to the first end portion. The stop portion preferably defines a step in the belt webbing opening. When the cinch bar is in the second position, the step preferably provides an overlap of up to about 4.0 mm with the cinch bar. Preferably, the overlap is at least about 0.1 mm. An amount of overlap between the step and the cinch bar preferably varies depending on a rotation of the cinch bar in the opening.

(17) A distance of the first sidewall to the step is preferably less than a length of the first end portion. The distance may be up to about 5.0 mm. Preferably, the distance is at least about 0.2 mm. When the cinch bar is against the second sidewall, the first end portion of the cinch bar is preferably trapped by the first sidewall. When the cinch bar is against the stop portion, the second end portion of the cinch bar is trapped by the second sidewall.

(18) According to another aspect of the present invention, there is provided a method of assembling a tongue assembly for a seatbelt system, the tongue assembly including a body having a belt webbing opening through which a belt webbing is passable and in which a cinch bar is locatable for cinching the belt webbing, the cinch bar having a main body portion and first and second end portions, the belt webbing opening being defined by axially spaced apart first and second sidewalls each of which is adapted to receive a respective end portion of the cinch bar, and a stop portion in the belt webbing opening between the first sidewall and the second sidewall, the method including: inserting the cinch bar at an angle into the belt webbing opening such that the first end portion of the cinch bar is received by the first sidewall; aligning the second end of the cinch bar with the second sidewall such that the stop portion urges against the main body portion of the cinch bar; and moving the cinch bar towards the second sidewall such that the second end of the cinch bar is received by the second sidewall and the body portion of the cinch bar is removed from the stop portion while the first sidewall still receives a portion of the first end portion, wherein the stop portion prevents movement of the main body portion towards the first sidewall thereby trapping the cinch bar within the belt webbing opening.

(19) The cinch bar is preferably rotatable when the main body portion of the cinch bar is clear of the stop portion. The method may further include passing the belt webbing through the belt webbing opening when the main body portion of the cinch bar is clear of the stop portion.

(20) According to a further aspect of the present invention, there is provided a tongue assembly for a seatbelt system, the tongue assembly including: a body having a belt webbing opening through

which a belt webbing is passable, the belt webbing opening being defined by axially spaced apart sidewalls, and a cinch bar in the belt webbing opening, the cinch bar having a main body portion for cinching the belt webbing and first and second end portions each of which is trapped by a respective one of said sidewalls as the cinch bar is moved within the belt webbing opening thereby preventing removal of the cinch bar from the belt webbing opening.

(21) The main body and the two end portions of the cinch bar may be integrally formed as a single piece. The cinch bar has no moving parts.

(22) The tongue assembly may further include a stop feature in the belt webbing opening, wherein the stop feature is configured to prevent movement of the cinch bar towards one of the two sidewalls to thereby trap the end portion in the other sidewall. The stop feature preferably provides an interference fit to the cinch bar when it is inserted into the belt webbing opening.

(23) The first end portion of the cinch bar is preferably longer than the second end portion.

(24) A further aspect of the present invention provides a cinch bar for a locking tongue assembly, the cinch bar including: an elongate portion member for cinching a belt webbing; and a first end portion and a second end portion on opposite ends of the body member, the first end portion having a length greater than a length of the second end portion.

(25) The elongate body portion and the two end portions of the cinch bar are preferably integrally formed as a single piece. The cinch bar may be formed of a rigid material that resists deformation. For example, the cinch bar may be formed from a rigid plastic material.

(26) At least one of the first end portion and second end portion is substantially frustoconical. Preferably, both of the end portions is substantially frustoconical. In other embodiments, only one of the end portions is substantially frustoconical.

(27) Preferably, the cinch bar may be configured for the locking tongue assembly of the previously described aspects of the invention.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The invention will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

(2) FIGS. 1A and 1B show a plan view and an exploded perspective view respectively of a tongue assembly according to a first embodiment of the present invention;

(3) FIGS. 2A to 2E show the cinch bar of the tongue assembly according to the first embodiment of the present invention being inserted into the belt webbing opening of the tongue body;

(4) FIGS. 3A to 3E show the cinch bar of the tongue assembly according to the first embodiment of the present invention in a first position in the tongue body; and

(5) FIGS. 4A to 4G show the cinch bar of the tongue assembly according to the first embodiment of the present invention in a second position in the tongue body.

### DETAILED DESCRIPTION

(6) FIGS. 1A and 1B illustrate a locking tongue assembly **100** for a seatbelt system according to an embodiment of the present invention. The locking tongue assembly **100** is for use with a three-point continuous loop seat belt system.

(7) The tongue assembly **100** has a tongue body **120** having a belt webbing opening **122** through which a belt webbing is passable and in which a cinch bar **140** is locatable for cinching the belt webbing. Once the cinch bar **140** is located within the opening **122**, the cinch bar cannot be removed from the tongue body **120**. After the belt webbing is threaded through the opening, it would be even more difficult for the cinch bar to be removed from the tongue body. The cinch bar is rotatable about a central axis within the opening **122**. In addition, the cinch bar is slidable along the central axis within the opening. The opening **122** has a rough texture at the cinching surface to

increase the cinch holding force.

(8) The cinch bar **140** has a main body portion **142**, a first end portion **144**, and a second end portion **146**. The main body **142** and the two end portions **144**, **146** of the cinch bar are integrally formed as a single unitary piece. The cinch bar **140** has no moving parts.

(9) The cinch bar additionally includes a key portion (or a tab portion) **148** near the first end portion **144** that is engagable with a slot **121** of in a first sidewall defining the belt webbing opening **122** to guide the cinch bar as it is inserted into the opening and to reduce webbing abrasion around the first end portion of the bar. In other embodiments, the cinch bar does not have a key portion.

(10) The main body portion **142** is an elongate member having a length that is less than a length of the belt webbing opening **122**. However, a total length of the cinch bar **140**, from the first end portion to the other end portion, is greater than the length of the opening **122**. The main body portion **142** has a plurality of spaced apart ribs along its length. A cross-sectional profile of the body portion **142** is larger than a cross-sectional profile of each of the first and second end portions **144**, **146**. The main body portion may be substantially cylindrical with an irregular shape. For example, the main body may have an egg-shape or oval shape.

(11) Each of the first and second end portions **144**, **146** are provided at opposite ends of the main body portion **142** of the cinch bar. The end portions are adapted to engage, or locate in, sidewalls of the tongue body **120** that define the opening **122**. As the cinch bar **140** is rotated about the central axis and/or slid along the central axis in the opening **122**, the cinch bar would remain trapped within the belt webbing opening **122**. In particular, both the first and second end portions of the cinch bar **140** will remain trapped within respective sidewalls of the tongue body as the cinch bar is rotated and/or slid in the opening thereby preventing removal of the cinch bar from the opening.

(12) The first end portion **144** has a length of about 4.0 mm to about 11.0 mm. The first end portion of the cinch bar is frustoconical. The frustoconical end portion has a tapered wall portion at an angle of about 2° to a longitudinal axis through the cinch bar. In other embodiments, the frustoconical end portion has a tapered wall portion that is at an angle of between about 1 to 5°, or up to 30°, to a longitudinal axis through the cinch bar. The tapered wall of the first end portion facilitates the insertion of the cinch bar into the respective sidewall of the body **120**. In particular, there is some clearance between the tapered wall portion and aperture in the sidewall into which the end portion is located, which allows the cinch bar to be angled into the respective sidewall of the tongue body **120** and pushed into the opening. To insert the cinch bar **140** in the opening **122**, the cinch bar is angled into the tongue body at an angle of between about 5° and 15° to the central axis through the opening and pushed into the opening.

(13) The second end portion **146** is shorter than the first end portion **144**. The second end portion **146** has a length of about 2.0 mm to 6.0 mm. The second end portion **146** has a substantially cylindrical shape. In other embodiments, the second end portion may also have a frustoconical shape. The second end portion **146** is shorter than then first end portion **144**. The second sidewall **126** of the tongue body braces against the main body portion of the cinch bar when the cinch bar is moved towards the second wall. When the cinch bar braces against the second sidewall of the tongue body, the first end portion of the cinch bar will remain trapped by the first sidewall.

(14) The first and second end portions have a substantially circular profile. The circular profile of the first and second end portions **144**, **146** enable the cinch bar to rotate within the belt webbing opening. As described above, the first and second end portions **144**, **146** can be frustoconical. In other embodiments, the first and second end portions are both cylindrical in shape.

(15) The belt webbing opening **122** is defined by axially spaced apart first and second sidewalls **124**, **126**. Each sidewall **124**, **126** is adapted to receive a respective end portion **144**, **146** of the cinch bar. In particular, the first sidewall **124** is for receiving the first end portion **144** of the cinch bar, and the second sidewall **126** is for receiving the second end portion **146** of the cinch bar. Each sidewall **124**, **126** has an aperture (or channel) in which the respective end portion of the cinch bar

is locatable. Each aperture is generally cylindrical, having a substantially tapering cross-sectional area through the depth of the aperture such that the aperture has a narrow opening. The aperture is tapered outwardly into the sidewall. That is, a cross-sectional area of the aperture at one end of the aperture on the face of the sidewall is smaller than a cross-sectional area of the aperture at an opposite end of the aperture. The aperture in each sidewall is dimensioned to be larger, or at least slightly larger, than the circular profile of the respective first and second end portions of the cinch bar as previously described. The belt webbing opening **122** accommodates the irregular shape of the main body portion **142** of the cinch bar **140**, as previously discussed above, and allows for a forward and rearward rotation of the cinch bar in the opening **122**. When the end portions of the cinch bar are located in the respective sidewalls, the first and second end portions would not hold any load. There is a clearance between the end portion and the walls of the aperture surrounding the end portion. In other embodiments, when the cinch bar is located in the opening, the first and second portions hold some load.

(16) The tongue body **120** include a stop portion (or stop feature, or trapping portion) **128** in the belt webbing opening **122**. The stop portion **128** provides a step within the belt webbing opening **122**. The stop portion **128** is for limiting a sliding or lateral movement of the cinch bar in the belt webbing opening **122**. In particular, when the cinch bar **120** is located within the belt webbing opening, the stop portion **128** provides a surface against which a portion of the cinch bar **120** is braceable to prevent movement of the cinch bar towards the stop portion **128**. The stop portion **128** is located adjacent or near the first sidewall **124** that receives the first end portion **144** of the cinch bar. The stop portion **128** prevents movement of the main body portion **142** of the cinch bar towards the first sidewall to any extent that the second end portion of the cinch bar would be free of the second sidewall—thereby, the second end portion of the cinch bar would remain trapped by the second sidewall. As previously described above, the first end portion of the cinch bar would remain trapped by the first sidewall when the cinch bar is moved towards the second sidewall.

Accordingly, because both of the first and second end portions are trapped by the first and second sidewalls of the locking tongue body over a full range of movement of the cinch bar in the belt webbing opening, the cinch bar is prevented from removal from the tongue body. The stop portion defines a step in the opening **122** or an area of increased thickness in the opening **122**. The step provides an overlap of about 0.1 mm with the cinch bar body when the belt webbing is not provided through the opening **122** and an overlap of up to about 2.5 mm when the belt webbing is provided through the opening **122**. In other embodiments, the overlap may be up to about 4.0 mm when the belt webbing is provided through the opening.

(17) The stop portion **128** extends from the first sidewall and has a length that is less than a length of first end portion of the cinch bar and greater than a length of the second end portion of the cinch bar. The length of the stop portion **128** is about 0.2 mm. In other embodiments, the length may be up to about 5.0 mm, such as from about 2.0 mm to about 5.0 mm, for example, from about 3.5 mm to about 4.5 mm. In other embodiments, the stop portion may be separate from the first sidewall and located within a distance from the first sidewall that is less than each of the first and second end portions. In further embodiments, there may be a plurality of spaced apart stop portions within the belt webbing opening.

(18) The stop portion **128** additionally provides an interference fit for the cinch bar during assembly of the locking tongue assembly when the cinch bar is angled into the first sidewall and pushed into belt webbing opening **122**. The stop portion **128** urges against the main body portion **142** of the cinch bar when the cinch bar **140** is in a first position in which only the first end portion **144** of the cinch bar **140** is received by a first sidewall **124** while the second end portion **146** is aligned with the second sidewall **126** without being received by the second sidewall **126**. Moving the cinch bar **140** from the first position towards the second sidewall **126** in a second position where the second end portion **146** of the cinch bar **140** is received by the second sidewall **126** results in the body portion of the cinch bar **140** being removed from the stop portion **128**. In the

second position, the first sidewall **124** still receives a portion of the first end portion **144**. As the stop portion is an enlarged area that restricts a passage through the opening **122** and because the first and second end portions **144**, **146** are trapped by their respective first and second sidewalls **124**, **126**, main body portion **142** of the cinch bar **140** cannot be moved onto the stop portion after the cinch bar is in the second position. Thereby, the cinch bar **140** would remain trapped in the opening **140** after it is moved to the second position.

(19) The first sidewall, the second sidewall and the stop portion of the tongue body **120** are integrally formed as a single piece. The tongue body **120** is injection molded. Preferably, the tongue body **120** is moulded with respect to a sheet of metal that forms the tongue portion of the tongue body that is insertable into a belt buckle. The tongue body **120** is a rigid plastic component.

(20) When the cinch bar **140** is in the first position, the cinch bar the stop portion resists rotation of the cinch bar. Additionally, when the cinch bar is in the first position, the second end portion of the cinch bar is about 1.5 mm from the second sidewall. In other embodiments, the second end portion is up to about 3.5 mm from the second sidewall when the cinch bar is in the first position. In yet other embodiments, there is no clearance between the second end portion of the cinch bar and the second sidewall when the cinch bar is in the second position.

(21) FIGS. 2A to 2E show different views of the locking tongue assembly **100** with the cinch bar **140** being inserted into the belt webbing opening **122** of the tongue body **120**. FIG. 2B shows a view from one end of the locking tongue assembly **100**, while FIG. 2C is a cross-sectional view of the locking tongue assembly **100** through the central, longitudinal axis of the cinch bar **140**. FIG. 2D is a detailed view of area B of FIG. 2C. FIG. 2E is a cross-sectional view taken along line X-X of FIG. 2D. The cinch bar **140** is angled into the opening **122** such that the first end portion **144** of the cinch bar **140** is inserted into the aperture in the first sidewall **124**. The angle of insertion of the cinch bar **140** into the opening **122** is up to about 10°. The key portion **148** of the cinch bar **140** is directed towards the slot **121** in the first sidewall **124** as the cinch bar is angled into the opening **122**. As the cinch bar **140** is being angled into the first sidewall **124**, there is a clearance between the cinch bar **140** and the stop portion **128** such that the cinch bar **140** can be inserted into the first sidewall **124** without any substantial interference from the stop portion **128**. The tapered walls of the first end portion **144** and the tapered walls of the aperture in the first sidewall **124** assist in guiding the first end portion **144** into the first sidewall **124**. As the cinch bar **140** is angled into and pushed towards the first sidewall **124** to locate the first end portion **144** in the first sidewall **124**, the cinch bar **140** will move into the opening **122** such that the second end portion **146** would become aligned with the aperture in the second sidewall **126**. In addition, the key portion **148** is inserted into the slot **121** when the cinch bar is angled towards and moved into the opening **122**. The second sidewall **126** does not interrupt or block movement of the second end portion **146** of the cinch bar **140** as the cinch bar **140** is moved into the opening **122**. In particular, there is sufficient clearance between the second end portion **146** and the second sidewall **126** as the cinch bar **140** is moved into the opening **122**.

(22) FIGS. 3A to 3E show different views of the locking tongue assembly **100** with the cinch bar **140**, in a first position, in which it is aligned within the belt webbing opening **122** of the tongue body **120** after the cinch bar **140** is angled into and pushed towards the first sidewall **124** as previously described. FIG. 3B shows a view from one end of the locking tongue assembly **100**, while FIG. 3C is a cross-sectional view of the locking tongue assembly **100** through the central, longitudinal axis of the cinch bar **140**. FIG. 3D is a detailed view of area D of FIG. 3C. FIG. 3E is a cross-sectional view taken along line Y-Y of FIG. 3D. In this first position, the key portion **148** is fully inserted into the slot **121** in the first sidewall **124**. Also, in this position, the main body portion **142** of the cinch bar **140** urges against the stop portion **128** that is adjacent to the first sidewall **124**. The stop portion **128** in particular provides an interference to the cinch bar **140** in the opening **122**. The stop portion **128** pushes against the main body portion **142** of the cinch bar **140** and forces (or biases) the cinch bar **140** outwards from the opening **122** as indicated by the arrows in FIG. 3E.



The main body portion **142** and the stop portion **128** are made from a rigid material that resists deformation when the stop portion **128** and the main body portion **142** urge against each other. Further, in the first position, the second end portion **146** of the cinch bar **122** would be aligned with the aperture in the second sidewall **126**. There is a spacing or clearance, of up to about 3.5 mm, between the second end portion **146** and the second sidewall **126** when the cinch bar is in the first position.

(23) FIGS. **4A** to **4E** show different views of the locking tongue assembly **100** with the cinch bar **140** moved from the first position towards the second sidewall, in a second position, so as to remove the body portion **142** of the cinch bar from the stop portion **128**. FIG. **4B** shows a view from one end of the locking tongue assembly **100**, while FIG. **4C** is a cross-sectional view of the locking tongue assembly **100** through the central, longitudinal axis of the cinch bar **140**. FIG. **4D** is a detailed view of area F of FIG. **4C**. FIG. **4E** is a cross-sectional view taken along line Z.sub.1-Z.sub.1 of FIG. **4D**. In the second position, the cinch bar **140** is moved towards the second sidewall **126** such that the second end portion **146** of the cinch bar is at least fully received by the aperture in the second sidewall. The length of the second end portion is less than the length of the stop portion such that the second end portion does not need to be fully located in the second sidewall **126** before the main body portion **142** is removed from the stop portion **128**. When the main body portion **142** of the cinch bar is removed from the stop portion **128**, the stop portion **128** now limits the range of movement of the cinch bar in the opening **122**. In particular, the cinch bar would be restricted by the stop portion **128** from moving towards the first sidewall **124**. Due to the stop portion **128**, a range of side-to-side (or lateral) movement of the cinch bar **140** in the opening **122** is less than a length of the first end portion **144** of the cinch bar and is less than a length of the second end portion **146** of the cinch bar. The range of side-to-side movement of the cinch bar within the opening is the distance between the stop portion **128** to the second sidewall **126** minus length of the cinch bar body **142**. Thereby, the first and second end portions of the cinch bar would remain trapped or locked within the first sidewall over the range of side-to-side movement of the cinch bar **140**. When the cinch bar **140** is moved towards the second sidewall **126**, the key portion **148** can be freed from the slot **121** of the tongue body **120** thereby allowing the cinch bar **140** to be rotated towards a forward position or rearward position in the opening **122**.

(24) In the second position, and with reference to FIGS. **4D** and **4E**, when cinch bar **140** is in a rearward position in the opening **122** of the tongue body, there is an overlap d.sub.1 of at least about 0.1 mm between the main body portion **142** of the cinch bar and the stop portion **128** in the opening **122** of the tongue body **120**. This overlap prevents the main body portion **142** of the cinch bar from moving towards the first sidewall **124**. Accordingly, removing the cinch bar **140** from the opening **122** is made difficult.

(25) FIG. **4F** is a detailed view of area F', which corresponds to area F of FIG. **4C**, but shows the cinch bar **140** in a forward position. FIG. **4G** is a cross-sectional view taken along line Z.sub.2-Z.sub.2 of FIG. **4F**. In the second position, and with reference FIGS. **4F** and **4G**, due to the irregular shape of the main body portion **142** of the cinch bar **140**, when the cinch bar **140** is in a forward position, there is a larger overlap d.sub.2 between the main body portion **142** and the stop portion **128**. The overlap is about 2.5 mm. The cinch bar **140** would be in the forward position when belt webbing is passed through the opening. Thereby, once the belt webbing is passed through the opening **122**, it would be even more difficult to move the cinch bar towards first sidewall **124** thereby preventing any removal of the cinch bar from the opening **122**.

(26) While various embodiments of the present invention have been described above, it should be understood that they have been presented by way of example only, and not by way of limitation. It will be apparent to a person skilled in the relevant art that various changes in form and detail can be made therein without departing from the spirit and scope of the invention. Thus, the present invention should not be limited by any of the above described exemplary embodiments.

(27) The reference in this specification to any prior publication (or information derived from it), or

to any matter which is known, is not, and should not be taken as an acknowledgment or admission or any form of suggestion that that prior publication (or information derived from it) or known matter forms part of the common general knowledge in the field of endeavor to which this specification relates.

(28) Throughout this specification and the claims which follow, unless the context requires otherwise, the word 'comprise', and variations such as 'comprises' and 'comprising', will be understood to imply the inclusion of a stated integer or step or group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

## Claims

1. A tongue assembly for a seatbelt system, the tongue assembly including: a body having a belt webbing opening through which a belt webbing is passable and in which a cinch bar is locatable for cinching the belt webbing, the cinch bar having a main body portion and first and second end portions, the belt webbing opening being defined by axially spaced apart first and second sidewalls each of which is adapted to receive a respective end portion of the cinch bar, and a stop portion in the belt webbing opening for urging against the main body portion of the cinch bar when the cinch bar is in a first position in which only the first end portion of the cinch bar is received by a first sidewall while the second end portion is aligned with the second sidewall without being received by the second sidewall, wherein moving the cinch bar from the first position towards the second sidewall in a second position where the second end portion of the cinch bar is received by the second sidewall results in the body portion of the cinch bar being removed from the stop portion, wherein, in the second position, the first sidewall still receives a portion of the first end portion, and wherein the stop portion prevents movement of the main body portion towards the first sidewall thereby trapping the cinch bar within the belt webbing opening.
  2. The tongue assembly of claim 1, wherein the cinch bar is rotatable in the belt webbing opening when the cinch bar is in the second position to cinch the belt webbing, and the stop portion resists rotation of the cinch bar when the cinch bar is in the first position.
  3. The tongue assembly of claim 1, further including the cinch bar.
  4. The tongue assembly of claim 3, wherein the first end portion of the cinch bar is frustoconical.
  5. The tongue assembly of claim 4, wherein the first end portion has a tapered wall portion at an angle up to about 5° to a longitudinal axis through the cinch bar.
  6. The tongue assembly of claim 3, wherein the first end portion is longer than the second end portion.
  7. The tongue assembly of claim 3, wherein the main body and the first and second end portions of the cinch bar are integrally formed as a single piece.
  8. The tongue assembly of claim 1, wherein the first sidewall has an aperture for receiving the first end portion, the aperture being defined by tapered wall portion to define a narrow opening into the aperture.
  9. The tongue assembly of claim 1, wherein the stop portion provides an interference to the cinch bar in the first position.
  10. The tongue assembly of claim 1, wherein a range of side-to-side movement of the cinch bar in the belt webbing opening after the cinch bar is in the second position is less than each of the first and second end portions.
  11. The tongue assembly of claim 1, wherein a distance of the first sidewall to an edge of the stop portion against which the cinch bar is braceable is less than a length of the first end portion.
-