

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12387493
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Stojancic; Mihailo et al.

Machine learning for recognizing and interpreting embedded information card content

Abstract

Metadata for highlights of a video stream is extracted from card images embedded in the video stream. The highlights may be segments of a video stream, such as a broadcast of a sporting event, that are of particular interest to one or more users. Card images embedded in video frames of the video stream are identified and processed to extract text. The text characters may be recognized by applying a machine-learned model trained with a set of characters extracted from card images embedded in sports television programming contents. The training set of character vectors may be pre-processed to maximize metric distance between the training set members. The text may be interpreted to obtain the metadata. The metadata may be stored in association with the portion of the video stream. The metadata may provide information regarding the highlights, and may be presented concurrently with playback of the highlights.

Inventors:	Stojancic; Mihailo (San Jose, CA), Packard; Warren (Palo Alto, CA)
Applicant:	STATS LLC (Chicago, IL)
Family ID:	1000008747974
Assignee:	STATS LLC (Chicago, IL)
Appl. No.:	17/808941
Filed:	June 24, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220327829 A1	Oct. 13, 2022

Related U.S. Application Data

division parent-doc US 16411710 20190514 US 11373404 child-doc US 17808941
us-provisional-application US 62746454 20181016
us-provisional-application US 62712041 20180730
us-provisional-application US 62680955 20180605
us-provisional-application US 62673411 20180518
us-provisional-application US 62673413 20180518
us-provisional-application US 62673412 20180518

Publication Classification

Int. Cl.: **G06V40/20** (20220101); **G06F16/908** (20190101); **G06T7/12** (20170101); **G06V20/40** (20220101); **G06V20/62** (20220101); **G06V30/148** (20220101); **H04N21/234** (20110101); **H04N21/2343** (20110101); **H04N21/25** (20110101); **H04N21/435** (20110101); **H04N21/44** (20110101); **H04N21/458** (20110101); **H04N21/81** (20110101); **H04N21/84** (20110101); **H04N21/845** (20110101); **H04N21/8549** (20110101)

U.S. Cl.:

CPC **G06V20/42** (20220101); **G06F16/908** (20190101); **G06T7/12** (20170101); **G06V20/41** (20220101); **G06V20/46** (20220101); **G06V20/48** (20220101); **G06V30/153** (20220101); **G06V40/20** (20220101); **H04N21/435** (20130101); **H04N21/44008** (20130101); **H04N21/458** (20130101); **H04N21/8133** (20130101); **H04N21/84** (20130101); G06T2207/20132 (20130101); G06V20/44 (20220101)

Field of Classification Search

CPC: G06F (16/908); G06T (2207/20132); G06T (7/12); G06V (20/41); G06V (20/42); G06V (20/44); G06V (20/46); G06V (20/48); G06V (20/635); G06V (30/153); G06V (40/20); G06V (40/23); H04N (21/23418); H04N (21/234336); H04N (21/251); H04N (21/435); H04N (21/44008); H04N (21/458); H04N (21/8133); H04N (21/84); H04N (21/8549)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5177931	12/1992	Latter	N/A	N/A
5557042	12/1995	Paukkunen et al.	N/A	N/A
5681396	12/1996	Madanshetty et al.	N/A	N/A
5923607	12/1998	Suh	N/A	N/A
5954611	12/1998	Mills et al.	N/A	N/A
6005562	12/1998	Shiga et al.	N/A	N/A
6185527	12/2000	Petkovic et al.	N/A	N/A
6195458	12/2000	Varnick et al.	N/A	N/A
6721490	12/2003	Yao et al.	N/A	N/A
7174512	12/2006	Martin et al.	N/A	N/A
7197715	12/2006	Valeria	N/A	N/A
7386217	12/2007	Zhang	N/A	N/A
7543322	12/2008	Bhogal et al.	N/A	N/A

7633887	12/2008	Panwar et al.	N/A	N/A
7646962	12/2009	Ellis et al.	N/A	N/A
7680894	12/2009	Diot et al.	N/A	N/A
7742111	12/2009	Shiu et al.	N/A	N/A
7774811	12/2009	Poslinski et al.	N/A	N/A
7818368	12/2009	Yang et al.	N/A	N/A
7825989	12/2009	Greenberg	N/A	N/A
7831112	12/2009	Wang et al.	N/A	N/A
7849487	12/2009	Vosseller	N/A	N/A
7929808	12/2010	Seaman et al.	N/A	N/A
8024753	12/2010	Kummer et al.	N/A	N/A
8046798	12/2010	Schlack et al.	N/A	N/A
8079052	12/2010	Chen et al.	N/A	N/A
8099315	12/2011	Amento	N/A	N/A
8103107	12/2011	Yamamoto	N/A	N/A
8104065	12/2011	Aaby et al.	N/A	N/A
8140570	12/2011	Ingrassia et al.	N/A	N/A
8196168	12/2011	Bryan et al.	N/A	N/A
8209713	12/2011	Lai et al.	N/A	N/A
8269857	12/2011	Ishizaka	N/A	N/A
8296797	12/2011	Olstad et al.	N/A	N/A
8296808	12/2011	Hardacker et al.	N/A	N/A
8312486	12/2011	Briggs et al.	N/A	N/A
8320674	12/2011	Guillou et al.	N/A	N/A
8424041	12/2012	Candelore et al.	N/A	N/A
8427356	12/2012	Satish	N/A	N/A
8457768	12/2012	Hammer et al.	N/A	N/A
8522300	12/2012	Relyea et al.	N/A	N/A
8535131	12/2012	Packard et al.	N/A	N/A
8595763	12/2012	Packard et al.	N/A	N/A
8627349	12/2013	Kirby et al.	N/A	N/A
8688434	12/2013	Birnbaum et al.	N/A	N/A
8689258	12/2013	Kemo	N/A	N/A
8702504	12/2013	Hughes et al.	N/A	N/A
8713008	12/2013	Negi	N/A	N/A
8752084	12/2013	Lai et al.	N/A	N/A
8793579	12/2013	Halliday et al.	N/A	N/A
8966513	12/2014	John et al.	N/A	N/A
8973038	12/2014	Gratton	N/A	N/A
8973068	12/2014	Kotecha et al.	N/A	N/A
8990418	12/2014	Bragg et al.	N/A	N/A
9038127	12/2014	Hastings et al.	N/A	N/A
9060210	12/2014	Packard et al.	N/A	N/A
9066156	12/2014	Kapa	N/A	N/A
9213986	12/2014	Buchheit et al.	N/A	N/A
9251853	12/2015	Jeong et al.	N/A	N/A
9253533	12/2015	Morgan et al.	N/A	N/A
9264779	12/2015	Kirby et al.	N/A	N/A
9420333	12/2015	Martch et al.	N/A	N/A
9443158	12/2015	Haskins	N/A	N/A

9451202	12/2015	Beads	N/A	N/A
9565474	12/2016	Petruzzelli et al.	N/A	N/A
9578377	12/2016	Malik et al.	N/A	N/A
9583149	12/2016	Stieglitz	N/A	N/A
9648379	12/2016	Howcroft	N/A	N/A
9715902	12/2016	Coviello et al.	N/A	N/A
9788062	12/2016	Dimov et al.	N/A	N/A
9805268	12/2016	King et al.	N/A	N/A
9888279	12/2017	Ishtiaq et al.	N/A	N/A
10025986	12/2017	Grieb	N/A	G09B 19/0038
10056116	12/2017	Packard et al.	N/A	N/A
10250838	12/2018	Herz	N/A	G06V 20/62
10297287	12/2018	Maisenbacher et al.	N/A	N/A
10419830	12/2018	Packard et al.	N/A	N/A
10433030	12/2018	Packard et al.	N/A	N/A
2001/0013123	12/2000	Freeman et al.	N/A	N/A
2001/0026609	12/2000	Weinstein et al.	N/A	N/A
2002/0041752	12/2001	Abiko et al.	N/A	N/A
2002/0059610	12/2001	Ellis	N/A	N/A
2002/0067376	12/2001	Martin et al.	N/A	N/A
2002/0075402	12/2001	Robson et al.	N/A	N/A
2002/0136528	12/2001	Dagtas	N/A	N/A
2002/0157095	12/2001	Masumitsu et al.	N/A	N/A
2002/0157101	12/2001	Schrader et al.	N/A	N/A
2002/0174430	12/2001	Ellis et al.	N/A	N/A
2002/0178444	12/2001	Trajkovic et al.	N/A	N/A
2002/0180774	12/2001	Errico et al.	N/A	N/A
2002/0194095	12/2001	Koren	N/A	N/A
2003/0012554	12/2002	Ieidler et al.	N/A	N/A
2003/0023742	12/2002	Allen et al.	N/A	N/A
2003/0056220	12/2002	Thornton et al.	N/A	N/A
2003/0063798	12/2002	Li et al.	N/A	N/A
2003/0066077	12/2002	Gutta	N/A	N/A
2003/0118014	12/2002	Iyer et al.	N/A	N/A
2003/0126605	12/2002	Betz et al.	N/A	N/A
2003/0126606	12/2002	Buczak et al.	N/A	N/A
2003/0154475	12/2002	Rodriguez et al.	N/A	N/A
2003/0172376	12/2002	Coffin	N/A	N/A
2003/0188317	12/2002	Liew et al.	N/A	N/A
2003/0189674	12/2002	Inoue et al.	N/A	N/A
2003/0208763	12/2002	McElhatten et al.	N/A	N/A
2003/0229899	12/2002	Thompson et al.	N/A	N/A
2004/0003403	12/2003	Marsh	N/A	N/A
2004/0041831	12/2003	Zhang	N/A	N/A
2004/0167767	12/2003	Xiong et al.	N/A	N/A
2004/0181807	12/2003	Theiste et al.	N/A	N/A
2005/0005308	12/2004	Logan et al.	N/A	N/A
2005/0015712	12/2004	Plastina	N/A	N/A
2005/0030977	12/2004	Casey et al.	N/A	N/A

2005/0044570	12/2004	Poslinski	N/A	N/A
2005/0071865	12/2004	Martins	N/A	N/A
2005/0071881	12/2004	Deshpande	N/A	N/A
2005/0091690	12/2004	Delpuch et al.	N/A	N/A
2005/0120368	12/2004	Goronzy et al.	N/A	N/A
2005/0125302	12/2004	Brown et al.	N/A	N/A
2005/0149965	12/2004	Neogi	N/A	N/A
2005/0152565	12/2004	Jouppi et al.	N/A	N/A
2005/0154987	12/2004	Otsuka et al.	N/A	N/A
2005/0166230	12/2004	Gaydou et al.	N/A	N/A
2005/0180568	12/2004	Krause	N/A	N/A
2005/0182792	12/2004	Israel et al.	N/A	N/A
2005/0191041	12/2004	Braun et al.	N/A	N/A
2005/0198570	12/2004	Otsuka et al.	N/A	N/A
2005/0204294	12/2004	Burke	N/A	N/A
2005/0240961	12/2004	Jerding et al.	N/A	N/A
2005/0264705	12/2004	Kitamura	N/A	N/A
2006/0020962	12/2005	Stark et al.	N/A	N/A
2006/0085828	12/2005	Dureau et al.	N/A	N/A
2006/0174277	12/2005	Sezan et al.	N/A	N/A
2006/0190615	12/2005	Panwar et al.	N/A	N/A
2006/0218573	12/2005	Proebstel	N/A	N/A
2006/0238656	12/2005	Chen et al.	N/A	N/A
2006/0253581	12/2005	Dixon et al.	N/A	N/A
2006/0282852	12/2005	Purpura et al.	N/A	N/A
2006/0282869	12/2005	Plourde	N/A	N/A
2007/0033616	12/2006	Gutta	N/A	N/A
2007/0058930	12/2006	Iwamoto	N/A	N/A
2007/0083901	12/2006	Bond	N/A	N/A
2007/0127894	12/2006	Ando et al.	N/A	N/A
2007/0146554	12/2006	Strickland et al.	N/A	N/A
2007/0154163	12/2006	Cordray	N/A	N/A
2007/0154169	12/2006	Cordray et al.	N/A	N/A
2007/0157235	12/2006	Teunissen	N/A	N/A
2007/0157249	12/2006	Cordray et al.	N/A	N/A
2007/0157253	12/2006	Ellis et al.	N/A	N/A
2007/0157285	12/2006	Frank et al.	N/A	N/A
2007/0162924	12/2006	Radhakrishnan et al.	N/A	N/A
2007/0169165	12/2006	Crull et al.	N/A	N/A
2007/0188655	12/2006	Ohta	N/A	N/A
2007/0199040	12/2006	Kates	N/A	N/A
2007/0201764	12/2006	Jung et al.	N/A	N/A
2007/0204302	12/2006	Calzone	N/A	N/A
2007/0212023	12/2006	Whitlock	N/A	N/A
2007/0226766	12/2006	Poslinski et al.	N/A	N/A
2007/0239856	12/2006	Abadir	N/A	N/A
2007/0245379	12/2006	Agnihortri	N/A	N/A
2007/0250777	12/2006	Chen et al.	N/A	N/A
2007/0288951	12/2006	Ray et al.	N/A	N/A
2008/0022012	12/2007	Wang	N/A	N/A

2008/0060006	12/2007	Shanks et al.	N/A	N/A
2008/0064490	12/2007	Ellis	N/A	N/A
2008/0086743	12/2007	Cheng et al.	N/A	N/A
2008/0092168	12/2007	Logan et al.	N/A	N/A
2008/0097949	12/2007	Kelly et al.	N/A	N/A
2008/0109307	12/2007	Ullah	N/A	N/A
2008/0115166	12/2007	Bhogal et al.	N/A	N/A
2008/0134043	12/2007	Georgis et al.	N/A	N/A
2008/0155602	12/2007	Collet et al.	N/A	N/A
2008/0159708	12/2007	Kazama et al.	N/A	N/A
2008/0163305	12/2007	Johnson et al.	N/A	N/A
2008/0168503	12/2007	Sparrell	N/A	N/A
2008/0175486	12/2007	Yamamoto	N/A	N/A
2008/0178219	12/2007	Grannan	N/A	N/A
2008/0193016	12/2007	Lim et al.	N/A	N/A
2008/0195457	12/2007	Sherman et al.	N/A	N/A
2008/0235348	12/2007	Dasgupta	N/A	N/A
2008/0239169	12/2007	Moon et al.	N/A	N/A
2008/0244666	12/2007	Moon et al.	N/A	N/A
2008/0270038	12/2007	Partovi et al.	N/A	N/A
2008/0271078	12/2007	Gossweiler et al.	N/A	N/A
2008/0300982	12/2007	Larson et al.	N/A	N/A
2008/0303942	12/2007	Chang et al.	N/A	N/A
2008/0307485	12/2007	Clement et al.	N/A	N/A
2008/0320523	12/2007	Morris et al.	N/A	N/A
2009/0025027	12/2008	Craner	N/A	N/A
2009/0034932	12/2008	Oisel	N/A	N/A
2009/0055385	12/2008	Jean et al.	N/A	N/A
2009/0080857	12/2008	St. John-Larkin	N/A	N/A
2009/0082110	12/2008	Relyea et al.	N/A	N/A
2009/0102984	12/2008	Mina et al.	N/A	N/A
2009/0138902	12/2008	Kamen	N/A	N/A
2009/0144777	12/2008	Mikami et al.	N/A	N/A
2009/0158357	12/2008	Miller	N/A	N/A
2009/0178071	12/2008	Whitehead	N/A	N/A
2009/0210898	12/2008	Childress et al.	N/A	N/A
2009/0228911	12/2008	Vriisen	N/A	N/A
2009/0234828	12/2008	Tu	N/A	N/A
2009/0235313	12/2008	Maruyama et al.	N/A	N/A
2009/0249412	12/2008	Bhogal et al.	N/A	N/A
2009/0293093	12/2008	Igarashi	N/A	N/A
2009/0299824	12/2008	Barnes	N/A	N/A
2009/0325523	12/2008	Choi	N/A	N/A
2010/0040151	12/2009	Garrett	N/A	N/A
2010/0064306	12/2009	Tiongson et al.	N/A	N/A
2010/0071007	12/2009	Meijer	N/A	N/A
2010/0071062	12/2009	Choyi et al.	N/A	N/A
2010/0086277	12/2009	Craner	N/A	N/A
2010/0089996	12/2009	Koolar	N/A	N/A
2010/0115554	12/2009	Drouet et al.	N/A	N/A

2010/0122294	12/2009	Craner	N/A	N/A
2010/0123830	12/2009	Vunic	N/A	N/A
2010/0125864	12/2009	Dwyer et al.	N/A	N/A
2010/0146560	12/2009	Bonfrer	N/A	N/A
2010/0153856	12/2009	Russ	N/A	N/A
2010/0153983	12/2009	Phillmon et al.	N/A	N/A
2010/0153999	12/2009	Yates	N/A	N/A
2010/0158479	12/2009	Craner	N/A	N/A
2010/0166389	12/2009	Knee et al.	N/A	N/A
2010/0169925	12/2009	Takegoshi	N/A	N/A
2010/0218214	12/2009	Fan et al.	N/A	N/A
2010/0251295	12/2009	Amento et al.	N/A	N/A
2010/0251304	12/2009	Donoghue et al.	N/A	N/A
2010/0251305	12/2009	Kimble et al.	N/A	N/A
2010/0262986	12/2009	Adimatvam et al.	N/A	N/A
2010/0269144	12/2009	Forsman et al.	N/A	N/A
2010/0319019	12/2009	Iazza	N/A	N/A
2010/0322592	12/2009	Casagrande	N/A	N/A
2010/0333131	12/2009	Parker et al.	N/A	N/A
2011/0016492	12/2010	Marita	N/A	N/A
2011/0016493	12/2010	Lee et al.	N/A	N/A
2011/0019839	12/2010	Nandury	N/A	N/A
2011/0052156	12/2010	Kuhn	N/A	N/A
2011/0072448	12/2010	Stiers et al.	N/A	N/A
2011/0082858	12/2010	Yu et al.	N/A	N/A
2011/0096228	12/2010	Deigmoeller et al.	N/A	N/A
2011/0109801	12/2010	Thomas et al.	N/A	N/A
2011/0138418	12/2010	Choi et al.	N/A	N/A
2011/0161242	12/2010	Chung et al.	N/A	N/A
2011/0173337	12/2010	Walsh et al.	N/A	N/A
2011/0202956	12/2010	Connelly et al.	N/A	N/A
2011/0206342	12/2010	Thompson et al.	N/A	N/A
2011/0212756	12/2010	Packard et al.	N/A	N/A
2011/0217024	12/2010	Schlieski et al.	N/A	N/A
2011/0231887	12/2010	West	N/A	N/A
2011/0239249	12/2010	Murison et al.	N/A	N/A
2011/0243533	12/2010	Stern et al.	N/A	N/A
2011/0252451	12/2010	Turgeman et al.	N/A	N/A
2011/0286721	12/2010	Craner	N/A	N/A
2011/0289410	12/2010	Paczkowski et al.	N/A	N/A
2011/0293113	12/2010	McCarthy	N/A	N/A
2012/0020641	12/2011	Sakaniwa et al.	N/A	N/A
2012/0047542	12/2011	Lewis et al.	N/A	N/A
2012/0052941	12/2011	Mo	N/A	N/A
2012/0060178	12/2011	Minakuchi et al.	N/A	N/A
2012/0082431	12/2011	Sengupta et al.	N/A	N/A
2012/0106932	12/2011	Grevers, Jr.	N/A	N/A
2012/0110615	12/2011	Kilar et al.	N/A	N/A
2012/0110616	12/2011	Kilar et al.	N/A	N/A
2012/0124625	12/2011	Foote et al.	N/A	N/A

2012/0131613	12/2011	Ellis et al.	N/A	N/A
2012/0185895	12/2011	Wong et al.	N/A	N/A
2012/0204209	12/2011	Kuba	N/A	N/A
2012/0216118	12/2011	Lin et al.	N/A	N/A
2012/0230651	12/2011	Chen	N/A	N/A
2012/0237182	12/2011	Eyer	N/A	N/A
2012/0246672	12/2011	Sridhar et al.	N/A	N/A
2012/0260295	12/2011	Rondeau	N/A	N/A
2012/0263439	12/2011	Lassman et al.	N/A	N/A
2012/0278834	12/2011	Richardson	N/A	N/A
2012/0278837	12/2011	Gurtis et al.	N/A	N/A
2012/0284745	12/2011	Strange	N/A	N/A
2012/0311633	12/2011	Mandrekar et al.	N/A	N/A
2012/0324491	12/2011	Bathiche et al.	N/A	N/A
2013/0014159	12/2012	Wiser et al.	N/A	N/A
2013/0042179	12/2012	Cormack et al.	N/A	N/A
2013/0055304	12/2012	Kirby et al.	N/A	N/A
2013/0061313	12/2012	Cullimore et al.	N/A	N/A
2013/0073473	12/2012	Heath	N/A	N/A
2013/0074109	12/2012	Skelton et al.	N/A	N/A
2013/0114940	12/2012	Merzon et al.	N/A	N/A
2013/0128119	12/2012	Madathodivil et al.	N/A	N/A
2013/0138435	12/2012	Weber	N/A	N/A
2013/0138693	12/2012	Sathish et al.	N/A	N/A
2013/0145023	12/2012	Li et al.	N/A	N/A
2013/0160051	12/2012	Armstrong et al.	N/A	N/A
2013/0174196	12/2012	Herlein	N/A	N/A
2013/0194503	12/2012	Yamashita	N/A	N/A
2013/0226983	12/2012	Reining et al.	N/A	N/A
2013/0251331	12/2012	Sambongi	N/A	N/A
2013/0263189	12/2012	Gamer	N/A	N/A
2013/0268620	12/2012	Osminer	N/A	N/A
2013/0268955	12/2012	Conrad et al.	N/A	N/A
2013/0283162	12/2012	Aronsson et al.	N/A	N/A
2013/0291037	12/2012	Im et al.	N/A	N/A
2013/0298146	12/2012	Conrad et al.	N/A	N/A
2013/0298151	12/2012	Leske et al.	N/A	N/A
2013/0325869	12/2012	Reiley et al.	N/A	N/A
2013/0326406	12/2012	Reiley et al.	N/A	N/A
2013/0326575	12/2012	Robillard et al.	N/A	N/A
2013/0332962	12/2012	Moritz et al.	N/A	N/A
2013/0332965	12/2012	Seyller et al.	N/A	N/A
2013/0346302	12/2012	Purves et al.	N/A	N/A
2014/0016864	12/2013	Chattopadhyay et al.	N/A	N/A
2014/0023348	12/2013	O'Kelly et al.	N/A	N/A
2014/0028917	12/2013	Smith et al.	N/A	N/A
2014/0032709	12/2013	Saussy et al.	N/A	N/A
2014/0062696	12/2013	Packard et al.	N/A	N/A
2014/0067825	12/2013	Oztaskent et al.	N/A	N/A

2014/0067828	12/2013	Archibong	N/A	N/A
2014/0067939	12/2013	Packard et al.	N/A	N/A
2014/0068675	12/2013	Mountain	N/A	N/A
2014/0068692	12/2013	Archibong et al.	N/A	N/A
2014/0074866	12/2013	Shah	N/A	N/A
2014/0082670	12/2013	Papish	N/A	N/A
2014/0088952	12/2013	Fife et al.	N/A	N/A
2014/0114647	12/2013	Allen	N/A	N/A
2014/0114966	12/2013	Bilinski et al.	N/A	N/A
2014/0123160	12/2013	van Coppenolle et al.	N/A	N/A
2014/0130094	12/2013	Kirby et al.	N/A	N/A
2014/0139555	12/2013	Levy	N/A	N/A
2014/0140680	12/2013	Jo	N/A	N/A
2014/0150009	12/2013	Sharma	N/A	N/A
2014/0153904	12/2013	Adimatvam et al.	N/A	N/A
2014/0157327	12/2013	Roberts et al.	N/A	N/A
2014/0161417	12/2013	Kurupacheril et al.	N/A	N/A
2014/0215539	12/2013	Chen et al.	N/A	N/A
2014/0223479	12/2013	Krishnamoorthi et al.	N/A	N/A
2014/0282714	12/2013	Hussain	N/A	N/A
2014/0282741	12/2013	Shoykhet	N/A	N/A
2014/0282744	12/2013	Hardy et al.	N/A	N/A
2014/0282745	12/2013	Chipman et al.	N/A	N/A
2014/0282759	12/2013	Harvey et al.	N/A	N/A
2014/0282779	12/2013	Navarro	N/A	N/A
2014/0294201	12/2013	Johnson et al.	N/A	N/A
2014/0298378	12/2013	Kelley	N/A	N/A
2014/0310819	12/2013	Cakarel et al.	N/A	N/A
2014/0313341	12/2013	Stribling	N/A	N/A
2014/0321831	12/2013	Olsen et al.	N/A	N/A
2014/0325556	12/2013	Hoang et al.	N/A	N/A
2014/0331260	12/2013	Gratton	N/A	N/A
2014/0333841	12/2013	Steck	N/A	N/A
2014/0351045	12/2013	Abihssira et al.	N/A	N/A
2014/0373079	12/2013	Friedrich et al.	N/A	N/A
2015/0003814	12/2014	Miller	N/A	N/A
2015/0012656	12/2014	Phillips et al.	N/A	N/A
2015/0020097	12/2014	Freed et al.	N/A	N/A
2015/0040176	12/2014	Hybertson et al.	N/A	N/A
2015/0052568	12/2014	Glennon et al.	N/A	N/A
2015/0054975	12/2014	Emmett et al.	N/A	N/A
2015/0058890	12/2014	Kapa	N/A	N/A
2015/0082172	12/2014	Shakib et al.	N/A	N/A
2015/0095932	12/2014	Ren	N/A	N/A
2015/0110461	12/2014	Maisenbacher et al.	N/A	N/A
2015/0110462	12/2014	Maisenbacher et al.	N/A	N/A
2015/0118992	12/2014	Wyatt et al.	N/A	N/A
2015/0181132	12/2014	Kummer et al.	N/A	N/A

2015/0181279	12/2014	Martch et al.	N/A	N/A
2015/0189377	12/2014	Wheatley et al.	N/A	N/A
2015/0243326	12/2014	Pacurariu et al.	N/A	N/A
2015/0249803	12/2014	Tozer et al.	N/A	N/A
2015/0249864	12/2014	Tang et al.	N/A	N/A
2015/0281778	12/2014	Khafa et al.	N/A	N/A
2015/0297949	12/2014	Aman	348/157	G06T 7/246
2015/0310725	12/2014	Koskan et al.	N/A	N/A
2015/0310894	12/2014	Stieglitz	N/A	N/A
2015/0319510	12/2014	Ould Dellahy et al.	N/A	N/A
2015/0334461	12/2014	Yu	N/A	N/A
2015/0358687	12/2014	Kummer	N/A	N/A
2015/0358688	12/2014	Kummer	N/A	N/A
2016/0066020	12/2015	Mountain	N/A	N/A
2016/0066026	12/2015	Mountain	N/A	N/A
2016/0066042	12/2015	Dimov et al.	N/A	N/A
2016/0066049	12/2015	Mountain	N/A	N/A
2016/0066056	12/2015	Mountain	N/A	N/A
2016/0073172	12/2015	Sharples	N/A	N/A
2016/0088351	12/2015	Petruzzelli	N/A	N/A
2016/0105708	12/2015	Packard et al.	N/A	N/A
2016/0105733	12/2015	Packard et al.	N/A	N/A
2016/0105734	12/2015	Packard et al.	N/A	N/A
2016/0191147	12/2015	Martch	N/A	N/A
2016/0198229	12/2015	Keipert	N/A	N/A
2016/0261929	12/2015	Lee et al.	N/A	N/A
2016/0309212	12/2015	Martch et al.	N/A	N/A
2017/0017834	12/2016	Sabitov	N/A	G06V 40/172
2017/0069159	12/2016	Vikranth et al.	N/A	N/A
2017/0116466	12/2016	Resnick	N/A	G06V 20/46
2017/0347014	12/2016	Chien	N/A	N/A
2018/0014072	12/2017	Dimov et al.	N/A	N/A
2018/0020243	12/2017	Ni et al.	N/A	N/A
2018/0189615	12/2017	Kang	N/A	G06N 3/08
2019/0138943	12/2018	Akolkar	N/A	G06N 5/022
2019/0205652	12/2018	Ray et al.	N/A	N/A
2019/0354763	12/2018	Stojancic et al.	N/A	N/A
2019/0354764	12/2018	Stojancic et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101650722	12/2010	CN	N/A
105912560	12/2015	CN	N/A
1469476	12/2003	EP	N/A
1865716	12/2006	EP	N/A
2902568	12/2006	EP	N/A
2107477	12/2008	EP	N/A
2309733	12/2010	EP	N/A

2403239	12/2011	EP	N/A
2464138	12/2011	EP	N/A
H07160830	12/1994	JP	N/A
H1055412	12/1997	JP	N/A
10322622	12/1997	JP	N/A
2001251581	12/2000	JP	N/A
2004072540	12/2003	JP	N/A
2004260297	12/2003	JP	N/A
2005-317165	12/2004	JP	N/A
2006211311	12/2005	JP	N/A
2006-245745	12/2005	JP	N/A
2006333451	12/2005	JP	N/A
2007202206	12/2006	JP	N/A
2008167019	12/2007	JP	N/A
2008176538	12/2007	JP	N/A
2012-029150	12/2011	JP	N/A
5034516	12/2011	JP	N/A
2013-175854	12/2012	JP	N/A
2014-157460	12/2013	JP	N/A
2014187687	12/2013	JP	N/A
2017-021523	12/2016	JP	N/A
2017097718	12/2016	JP	N/A
2017522648	12/2016	JP	N/A
2018005397	12/2017	JP	N/A
2004-0025073	12/2003	KR	N/A
2006-0128295	12/2005	KR	N/A
WO-9837694	12/1997	WO	N/A
WO-0243353	12/2001	WO	N/A
WO-2005059807	12/2004	WO	N/A
WO-2007064987	12/2006	WO	N/A
WO-2007098067	12/2006	WO	N/A
WO-2009073925	12/2008	WO	N/A
WO-2011040999	12/2010	WO	N/A
WO-2013016626	12/2012	WO	N/A
WO-2013166456	12/2012	WO	N/A
WO-2014072742	12/2013	WO	N/A
WO-2014164782	12/2013	WO	N/A
WO-2014179017	12/2013	WO	N/A
WO-2016030380	12/2015	WO	N/A
WO-2016030384	12/2015	WO	N/A
WO-2016030477	12/2015	WO	N/A
WO-2016033545	12/2015	WO	N/A
WO-2016034899	12/2015	WO	N/A
WO-2016055761	12/2015	WO	N/A
WO-2016057416	12/2015	WO	N/A
WO-2016057844	12/2015	WO	N/A
WO-2019222409	12/2018	WO	N/A

OTHER PUBLICATIONS

US 10,462,538 B2, 10/2019, Packard et al. (withdrawn) cited by applicant

Extended European Search Report for European Application No. 19 80 3524, mailed Apr. 22, 2022. cited by applicant

BoxtishrTV's API; www_boxfish_com, (retrieved Mar. 28, 2017), 5 pages. cited by applicant

International Search Report for PCT/US2014/060651 dated Jan. 19, 2015 (9 pages). cited by applicant

International Search Report for PCT/US2014/060649 dated Jan. 8, 2015 (9 pages). cited by applicant

Jin, S.H., et al., "Intelligent broadcasting system and services for personalized semantic contents consumption", *Expert Systems with Applications*, Oxford, GB, vol. 31, No. 1, Jul. 1, 2006, pp. 164-173. cited by applicant

Jin, S.H., et al., "Real-time content filtering for live broadcasts in TV terminals", *Multimedia Tools and Applications*, Kluwer Academic Publishers, BO, vol. 36, No. 3, Jun. 29, 2007, pp. 285-301. cited by applicant

Thuuz Sports, "Frequently Asked Questions", www.thuuz.com/faq/, (retrieved Mar. 28, 2017), 5 pages. cited by applicant

R. Natarajan et al. "Audio-Based Event Detection in Videos—A Comprehensive Survey", *Int. Journal of Engineering and Technology*, vol. 6 No. 4 Aug.-Sep. 2014. cited by applicant

Q. Huang et al. Hierarchical Language Modeling for Audio Events Detection in a Sports Game, IEEE International conference on Acoustics, Speech and Signal Processing, 2010. cited by applicant

Q. Huang et al. "Inferring the Structure of a Tennis Game Using Audio Information", *IEEE Trans. on Audio Speech and Language Proc.*, Oct. 2011. cited by applicant

M. Baillie et al. "Audio-based Event Detection for Sports Video", *International Conference on Image and Video, CIVR 2003*. cited by applicant

Y. Rui et al. "Automatically Extracting Highlights for TV Baseball Programs", *Proceedings of the eighth ACM International conference on Multimedia*, 2000. cited by applicant

D. A. Sadlier et al. "A Combined Audio-Visual Contribution to Event Detection in Field Sports Broadcast Video. Case Study: Gaelic Football", *Proceedings of the 3rd IEEE International Symposium on Signal Processing and Information Technology*, Dec. 2003_. cited by applicant

E Kijak et al. "Audiovisual Integration for Tennis Broadcast Structuring", *Multimedia Tools and Applications*, Springer, vol. 30, Issue 3, pp. 289-311, Sep. 2006. cited by applicant

A. Baijal et al. "Sports Highlights Generation Based on Acoustic Events Detection: A Rugby Case Study", *IEEE International Conference on Consumer Electronics (ICCE)*, pp. 20-23, 2015. cited by applicant

J. Han et al. "A Unified and Efficient Framework for Court-Net Sports Video Analysis Using 3-D Camera Modeling", *Proceedings vol. 6506, Multimedia Content Access: Algorithms and Systems; 65060F (2007)*. cited by applicant

Huang-Chia Shih "A Survey on Content-aware Video Analysis for Sports", *IEEE Trans. on Circuits and Systems for Video Technology*, vol. 99, No. 9, Jan. 2017. cited by applicant

A. Krizhevsky et al. "ImageNet Classification with Deep Convolutional Neural Networks", In *Proc. NIPS*, pp. 1097-1105, 2012. cited by applicant

D. A. Sadlier et al. Event Detection in Field Sports Video Using Audio—Visual Features and a Support Vector Machine, *IEEE Trans. on Circuits and Systems for Video Technology*, vol. 15, No. 10, Oct. 2005. cited by applicant

P. F. Felzenszwalb et al. "Efficient Graph-Based Image Segmentation", *International Journal of Computer Vision*, Sep. 2004, vol. 59, Issue 2, pp. 167-181. cited by applicant

C. J. C. Burges "A Tutorial on Support Vector Machines for Pattern Recognition", *Springer, Data Mining and Knowledge Discovery*, Jun. 1998, vol. 2, Issue 2, pp. 121-167. cited by applicant

Y.A. LeCun et al. "Efficient BackProp" Neural Networks: Tricks of the Trade. Lecture Notes in Computer Science, vol. 1700, Springer, 2012. cited by applicant

L. Neumann, J. Matas, Real-Time Scene Text Localization and Recognition, 5th IEEE Conference on Computer Vision and Pattern Recognition, Jun. 2012. cited by applicant

R. Smith "An Overview of the Tesseract OCR Engine", International Conference on Document Analysis and Recognition (ICDAR), 2007. cited by applicant

M. Merler, et al., "The Excitement of Sports: Automatic Highlights Using AudioNisual Cues", Dec. 31, 2017, pp. 2520-2523. cited by applicant

H. Harb, et al., Highlights Detection in Sports Videos Based on Audio Analysis, pp. 1-4, Sep. 2009. cited by applicant

J. Ye, et al. Audio-Based Sports Highlight Detection by Fourier Local-Auto-Correlations, 11th Annual Conference of the International Speech Communication Association, Sep. 2010, pp. 2198-2201. cited by applicant

Miyamori, Hisashi "Automatic Generation of Personalized Digest Based on Context Flow and Distinctive Events", IEICE Technical Report, Jul. 10, 2003, vol. 103, No. 209, pp. 35-40. cited by applicant

Office Action issued in JP Application No. 2020-564734, 15 pages, dated Jun. 22, 2023. cited by applicant

Office Action issued in CN Application No. 201980044176.8, 8 pages, dated Jun. 1, 2023. cited by applicant

Primary Examiner: Miller; Brandon J

Attorney, Agent or Firm: Bookoff McAndrews PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a divisional of U.S. application Ser. No. 16/411,710, for "Machine Learning for Recognizing and Interpreting Embedded Information Card Content" filed May 14, 2019, which claims the benefit of U.S. Provisional Application Ser. No. 62/673,412 for "Machine Learning for Recognizing and Interpreting Embedded Information Card Content", filed May 18, 2018, the content of both of which are incorporated herein by reference in their entireties. (2) The present application is a divisional of U.S. application Ser. No. 16/411,710, for "Machine Learning for Recognizing and Interpreting Embedded Information Card Content" filed May 14, 2019, which claims the benefit of U.S. Provisional Application Ser. No. 62/673,411 for "Video Processing for Enabling Sports Highlights Generation", filed May 18, 2018, which is incorporated herein by reference in its entirety. (3) The present application is a divisional of U.S. application Ser. No. 16/411,710, for "Machine Learning for Recognizing and Interpreting Embedded Information Card Content" filed May 14, 2019, which claims the benefit of U.S. Provisional Application Ser. No. 62/673,413 for "Video Processing for Embedded Information Card Localization and Content Extraction", filed May 18, 2018, which is incorporated herein by reference in its entirety. (4) The present application is a divisional of U.S. application Ser. No. 16/411,710, for "Machine Learning for Recognizing and Interpreting Embedded Information Card Content" filed May 14, 2019, which claims the benefit of U.S. Provisional Application Ser. No. 62/680,955 for "Audio Processing for Detecting Occurrences of Crowd Noise in Sporting Event Television Programming", filed Jun. 5, 2018, which is incorporated herein by reference in its entirety. (5) The present application is a divisional of U.S. application Ser. No. 16/411,710, for "Machine Learning for Recognizing and Interpreting

Embedded Information Card Content” filed May 14, 2019, which claims the benefit of U.S. Provisional Application Ser. No. 62/712,041 for “Audio Processing for Extraction of Variable Length Disjoint Segments from Television Signal”, filed Jul. 30, 2018, which is incorporated herein by reference in its entirety. (6) The present application is a divisional of U.S. application Ser. No. 16/411,710, for “Machine Learning for Recognizing and Interpreting Embedded Information Card Content” filed May 14, 2019, which claims the benefit of U.S. Provisional Application Ser. No. 62/746,454 for “Audio Processing for Detecting Occurrences of Loud Sound Characterized by Short-Time Energy Bursts”, filed Oct. 16, 2018, which is incorporated herein by reference in its entirety. (7) The present application is related to U.S. Utility application Ser. No. 13/601,915 for “Generating Excitement Levels for Live Performances,” filed Aug. 31, 2012 and issued on Jun. 16, 2015 as U.S. Pat. No. 9,060,210, which is incorporated by reference herein in its entirety. (8) The present application is related to U.S. Utility application Ser. No. 13/601,927 for “Generating Alerts for Live Performances,” filed Aug. 31, 2012 and issued on Sep. 23, 2014 as U.S. Pat. No. 8,842,007, which is incorporated by reference herein in its entirety. (9) The present application is related to U.S. Utility application Ser. No. 13/601,933 for “Generating Teasers for Live Performances,” filed Aug. 31, 2012 and issued on Nov. 26, 2013 as U.S. Pat. No. 8,595,763, which is incorporated by reference herein in its entirety. (10) The present application is related to U.S. Utility application Ser. No. 14/510,481 for “Generating a Customized Highlight Sequence Depicting an Event”, filed Oct. 9, 2014, which is incorporated by reference herein in its entirety. (11) The present application is related to U.S. Utility application Ser. No. 14/710,438 for “Generating a Customized Highlight Sequence Depicting Multiple Events”, filed May 12, 2015, which is incorporated by reference herein in its entirety. (12) The present application is related to U.S. Utility application Ser. No. 14/877,691 for “Customized Generation of Highlight Show with Narrative Component”, filed Oct. 7, 2015, which is incorporated by reference herein in its entirety. (13) The present application is related to U.S. Utility application Ser. No. 15/264,928 for “User Interface for Interaction with Customized Highlight Shows”, filed Sep. 14, 2016, which is incorporated by reference herein in its entirety. (14) The present application is related to U.S. Utility application Ser. No. 16/411,704 for “Video Processing for Enabling Sports Highlights Generation”, filed on the same date as the present application, which is incorporated by reference herein in its entirety. (15) The present application is related to U.S. Utility application Ser. No. 16/411,713 for “Video Processing for Embedded Information Card Localization and Content Extraction”, filed on the same date as the present application, which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) The present document relates to techniques for identifying multimedia content and associated information on a television device or a video server delivering multimedia content, and enabling embedded software applications to utilize the multimedia content to provide content and services synchronously with delivery of the multimedia content. Various embodiments relate to methods and systems for providing automated video and audio analysis that are used to identify and extract important event-based video segments in sports television video content, to identify video highlights, and to associate metadata with such highlights for pre-game, in-game and post-game review.

DESCRIPTION OF THE RELATED ART

(2) Enhanced television applications such as interactive advertising and enhanced program guides with pre-game, in-game and post-game interactive applications have long been envisioned. Existing cable systems that were originally engineered for broadcast television are being called on to support a host of new applications and services including interactive television services and enhanced (interactive) programming guides.

(3) Some frameworks for enabling enhanced television applications have been standardized.

Examples include the OpenCable™ Enhanced TV Application Messaging Specification, as well as the Tru2way specification, which refer to interactive digital cable services delivered over a cable video network and which include features such as interactive program guides, interactive ads, games, and the like. Additionally, cable operator “OCAP” programs provide interactive services such as e-commerce shopping, online banking, electronic program guides, and digital video recording. These efforts have enabled the first generation of video-synchronous applications, synchronized with video content delivered by the programmer/broadcaster, and providing added data and interactivity to television programming.

(4) Recent developments in video/audio content analysis technologies and capable mobile devices have opened up an array of new possibilities in developing sophisticated applications that operate synchronously with live TV programming events. These new technologies and advances in computer vision and video processing, as well as improved computing power of modern processors, allow for real-time generation of sophisticated programming content highlights accompanied by metadata.

SUMMARY

(5) Methods and systems are presented for automatic real time processing of sporting event television programming content for embedded information card localization and embedded text string recognition and interpretation. In at least one embodiment, a machine-learned character classification model is generated based on a training set of characters extracted from a plurality of information cards (card images) embedded in sporting event television programming content. The extracted character images are processed to generate a standardized training set of multidimensional character vectors in a multidimensional vector space. A principal component analysis (PCA) is then performed on this training set, such that orthogonal basis vectors are derived spanning the vector space of the training set.

(6) In at least one embodiment, the dimensionality of the training set vector space is reduced by selecting a limited number of representative orthogonal vectors from the orthogonal basis. A classification model is generated for this specific set of projected alphanumeric characters appearing in embedded information cards by utilizing a machine learning algorithmic structure, which may be a known machine learning algorithm such as a multi-class support vector machines (SVM) or convolutional neural network (CNNs) algorithm.

(7) In at least one embodiment, sporting event television programming content is processed in real-time to extract queries (embedded characters from character strings in information cards), and to set up a query infrastructure with individual character images extracted from embedded character strings. In another embodiment, the individual query images are normalized to generate a query vector for each query character; subsequently, these query vectors are projected onto the orthogonal basis spanning the training vector space to generate projected query vectors. In yet another embodiment, the projected query vectors are recognized (predicted) by applying a previously learned character classification model on each projected query vector. Finally, predicted query characters (forming a predicted character string) are interpreted by meaning extraction. In at least one embodiment, meaning extraction is performed based on the known character string positions in various television programming card image types, as well as based on the knowledge of locations of individual characters within a character string. In at least one embodiment, the extracted information is automatically appended to sporting event metadata associated with the sporting event video highlights.

(8) In at least one embodiment, a method for extracting metadata from a video stream includes storing at least a portion of the video stream, identifying one or more card images embedded in one or more video frames of the portion of the video stream, and subsequently processing the one or more information card images to extract text. In yet another embodiment, the text extracted from the information card images is interpreted to generate and store metadata in association with the portion of the video stream.

- (9) In at least one embodiment, the video stream may be a broadcast of a sporting event. The portion of the video stream may be a highlight deemed to be of particular interest to one or more users. The metadata may be descriptive of the highlight.
- (10) In at least one embodiment, the method may further include playing the video stream for a user during at least one of identifying the one or more card images, processing the one or more card images, and interpreting the text.
- (11) In at least one embodiment, the method may further include playing the highlight for a user and presenting the metadata to the user during playback of the highlight. The metadata may provide real-time information related to the highlight and a timeline of the card images from which the metadata have been obtained.
- (12) In at least one embodiment, extracting the text may include identifying one or more character strings within the one or more card images, and recording a location and/or a size of a character image of a card image of the one or more card images that corresponds to each character of the one or more character strings.
- (13) In at least one embodiment, extracting the text may further include disambiguating character boundaries of characters of the one or more character strings by performing multiple comparisons of detected character boundaries, and purging the character boundaries that appear too close to each other.
- (14) In at least one embodiment, extracting the text may further include performing image validation for characters of the one or more character strings by establishing a contrast ratio between low and high intensity pixel counts.
- (15) In at least one embodiment, interpreting the text may include generating queries based on the text, generating n-dimensional query feature vectors, projecting the n-dimensional query feature vectors onto a training set orthogonal basis, applying the projected n-dimensional query feature vectors to a classification model to produce predicted queries, and extracting meaning of the text from the predicted queries.
- (16) In at least one embodiment, the method may further include generating training set feature vectors, and using the training set feature vectors to derive the training set orthogonal basis.
- (17) In at least one embodiment, the method may further include generating training set feature vectors, and using the training set feature vectors and derived training set orthogonal basis vectors to generate the classification model.
- (18) In at least one embodiment, interpreting the text may further include using at least two selections from the group consisting of a string length of one or more character strings within the text, a position of character boundaries and/or characters within the text, and a horizontal position of character boundaries and/or characters within the text.
- (19) In at least one embodiment, storing the metadata in association with the portion of the video stream may include storing a video frame number of the one or more video frames, associated with queries.
- (20) In at least one embodiment, interpreting the text may include ascertaining field positions of characters of one or more character strings of the text, ascertaining alphanumeric values of the characters, and using the field positions and alphanumeric values to sequentially interpret the one or more character strings.
- (21) In at least one embodiment, interpreting the text may further include obtaining positional and other information regarding one or more card fields of each of the card images, and using the positional and other information to compensate for one or more possible missing front characters of the one or more character strings.
- (22) In at least one embodiment, a method for generating a character recognition and classification model is described in relation to the automatic video highlight generation. The method includes extracting and storing at least a portion of the video stream for which automatic highlight metadata is to be generated, identifying one or more information card images embedded in one or more

video frames of the portion of the video stream, and processing the one or more information card images to extract a plurality of character images. The method further includes generating training feature vectors associated with the plurality of character images, processing the training feature vectors, using at least some of the training feature vectors to train a character recognition and classification model, and subsequently storing the processed training set and the classification model. The training feature vectors may be processed in a manner that increases uniqueness of the training feature vectors by increasing mutual metric distance of the training feature vectors, and/or by reducing dimensionality of an overall vector space containing the training feature vectors.

(23) In at least one embodiment, the method may further include prior to generating the training feature vectors, normalizing the character images to a standard size and/or a standard illumination.

(24) In at least one embodiment, generating the training feature vectors may include formatting a set of n pixels extracted from the character images into n -dimensional vectors.

(25) In at least one embodiment, the method may further include performing a principal component analysis on the training feature vectors. Using at least some of the training feature vectors to train the classification model may include selecting a subset of the training feature orthogonal basis vectors, and using the subset of the orthogonal basis vectors to train the character recognition and classification model.

(26) In at least one embodiment, the orthogonal basis vectors may span the overall training feature vector space. Reducing a dimensionality of the overall training feature vector space may include selecting a limited number of the orthogonal basis vectors which represent the said training feature vector space sufficiently accurately. Reducing the dimensionality of the overall training vector space may include selecting only orthogonal basis vectors that correspond to a set of largest singular values derived from a matrix of the orthogonal basis vectors. Storing the classification model may include storing a limited number of the orthogonal basis vectors for subsequent use in classification model generation and/or query processing. Generating the classification model may include using a limited number of the training set orthogonal basis vectors in conjunction with a machine learning algorithm selected from the group consisting of SVM and CNN.

(27) In at least one embodiment, the method may further include processing the one or more information card images to extract text, interpreting the text to obtain metadata, and storing the metadata in association with the portion of the video stream. The method further includes playing the portion of the video stream for a user, and presenting the metadata to the user during playback of the portion of the video stream. The video stream may be a broadcast of a sporting event. The portion of the video stream may include a highlight deemed to be of particular interest to one or more users. The metadata may be descriptive of the highlight.

(28) In at least one embodiment, extracting the text may include extracting text strings of the text as queries.

(29) In at least one embodiment, extracting the text may include extracting at least one of a current time within the sporting event, a current phase of the sporting event, a game clock pertaining to the sporting event, and a game score pertaining to the sporting event.

(30) Further details and variations are described herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings, together with the description, illustrate several embodiments. One skilled in the art will recognize that the particular embodiments illustrated in the drawings are merely exemplary, and are not intended to limit scope.

(2) FIG. 1A is a block diagram depicting a hardware architecture according to a client/server embodiment, wherein event content is provided via a network-connected content provider.

- (3) FIG. 1B is a block diagram depicting a hardware architecture according to another client/server embodiment, wherein event content is stored at a client-based storage device.
- (4) FIG. 1C is a block diagram depicting a hardware architecture according to a standalone embodiment.
- (5) FIG. 1D is a block diagram depicting an overview of a system architecture, according to one embodiment.
- (6) FIG. 2 is a schematic block diagram depicting examples of data structures that may be incorporated into the card images, user data, highlight data, and classification model, according to one embodiment.
- (7) FIG. 3 is a screenshot diagram of an example of a video frame from a video stream, showing in-frame embedded information card images as may be found in sporting event television programming contents.
- (8) FIG. 4 is a flowchart depicting an overall application process for real-time receiving and processing of television programming content for in-frame information card localization and content extraction and rendering, according to one embodiment.
- (9) FIG. 5 is a flowchart depicting internal processing of a detected and extracted information card image for character string bounding box extraction, according to one embodiment.
- (10) FIG. 6 is a flowchart depicting a method for processing text boxes for final bounded character images validation and associated positional parameters extraction, according to one embodiment.
- (11) FIG. 7 is a flowchart depicting a method for query generation from embedded information card text images, according to one embodiment.
- (12) FIG. 8 is a flowchart depicting a method for generating predicted alphanumeric characters for extracted query character strings based on a machine-learned classification model, according to one embodiment.
- (13) FIG. 9 is a flowchart depicting a method for predicted query alphanumeric string interpretation, according to one embodiment.
- (14) FIG. 10 is a flowchart depicting preprocessing of training set vectors and subsequent classification model generation based on a multi-class SVM classifier or a CNN classifier, according to one embodiment.
- (15) FIG. 11 is a flowchart depicting an overall process of reading and interpreting text fields in information cards, and updating video highlight metadata with in-frame real-time information, according to one embodiment.

DETAILED DESCRIPTION

Definitions

(16) The following definitions are presented for explanatory purposes only, and are not intended to limit scope. Event: For purposes of the discussion herein, the term “event” refers to a game, session, match, series, performance, program, concert, and/or the like, or portion thereof (such as an act, period, quarter, half, inning, scene, chapter, or the like). An event may be a sporting event, entertainment event, a specific performance of a single individual or subset of individuals within a larger population of participants in an event, or the like. Examples of non-sporting events include television shows, breaking news, socio-political incidents, natural disasters, movies, plays, radio shows, podcasts, audiobooks, online content, musical performances, and/or the like. An event can be of any length. For illustrative purposes, the technology is often described herein in terms of sporting events; however, one skilled in the art will recognize that the technology can be used in other contexts as well, including highlight shows for any audiovisual, audio, visual, graphics-based, interactive, non-interactive, or text-based content. Thus, the use of the term “sporting event” and any other sports-specific terminology in the description is intended to be illustrative of one possible embodiment, but is not intended to restrict the scope of the described technology to that one embodiment. Rather, such terminology should be considered to extend to any suitable non-sporting context as appropriate to the technology. For ease of description, the term “event” is also used to

refer to an account or representation of an event, such as an audiovisual recording of an event, or any other content item that includes an accounting, description, or depiction of an event. **Highlight:** An excerpt or portion of an event, or of content associated with an event, that is deemed to be of particular interest to one or more users. A highlight can be of any length. In general, the techniques described herein provide mechanisms for identifying and presenting a set of customized highlights (which may be selected based on particular characteristics and/or preferences of the user) for any suitable event. “Highlight” can also be used to refer to an account or representation of a highlight, such as an audiovisual recording of a highlight, or any other content item that includes an accounting, description, or depiction of a highlight. Highlights need not be limited to depictions of events themselves, but can include other content associated with an event. For example, for a sporting event, highlights can include in-game audio/video, as well as other content such as pre-game, in-game, and post-game interviews, analysis, commentary, and/or the like. Such content can be recorded from linear television (for example, as part of the video stream depicting the event itself), or retrieved from any number of other sources. Different types of highlights can be provided, including for example, occurrences (plays), strings, possessions, and sequences, all of which are defined below. Highlights need not be of fixed duration, but may incorporate a start offset and/or end offset, as described below. **Content Delineator:** One or more video frames that indicate the start or end of a highlight. **Occurrence:** Something that takes place during an event. Examples include: a goal, a play, a down, a hit, a save, a shot on goal, a basket, a steal, a snap or attempted snap, a near-miss, a fight, a beginning or end of a game, quarter, half, period, or inning, a pitch, a penalty, an injury, a dramatic incident in an entertainment event, a song, a solo, and/or the like. Occurrences can also be unusual, such as a power outage, an incident with an unruly fan, and/or the like. Detection of such occurrences can be used as a basis for determining whether or not to designate a particular portion of a video stream as a highlight. Occurrences are also referred to herein as “plays”, for ease of nomenclature, although such usage should not be construed to limit scope. Occurrences may be of any length, and the representation of an occurrence may be of varying length. For example, as mentioned above, an extended representation of an occurrence may include footage depicting the period of time just before and just after the occurrence, while a brief representation may include just the occurrence itself. Any intermediate representation can also be provided. In at least one embodiment, the selection of a duration for a representation of an occurrence can depend on user preferences, available time, determined level of excitement for the occurrence, importance of the occurrence, and/or any other factors. **Offset:** The amount by which a highlight length is adjusted. In at least one embodiment, a start offset and/or end offset can be provided, for adjusting start and/or end times of the highlight, respectively. For example, if a highlight depicts a goal, the highlight may be extended (via an end offset) for a few seconds so as to include celebrations and/or fan reactions following the goal. Offsets can be configured to vary automatically or manually, based for example on amount of time available for the highlight, importance and/or excitement level of the highlight, and/or any other suitable factors. **String:** A series of occurrences that are somehow linked or related to one another. The occurrences may take place within a possession (defined below), or may span multiple possessions. The occurrences may take place within a sequence (defined below), or may span multiple sequences. The occurrences can be linked or related because of some thematic or narrative connection to one another, or because one leads to another, or for any other reason. One example of a string is a set of passes that lead to a goal or basket. This is not to be confused with a “text string,” which has the meaning ordinarily ascribed to it in the computer programming arts. **Possession:** Any time-delimited portion of an event. Demarcation of start/end times of a possession can depend on the type of event. For certain sporting events wherein one team may be on the offensive while the other team is on the defensive (such as basketball or football, for example), a possession can be defined as a time period while one of the teams has the ball. In sports such as hockey or soccer, where puck or ball possession is more fluid, a possession can be considered to extend to a period of time wherein one

of the teams has substantial control of the puck or ball, ignoring momentary contact by the other team (such as blocked shots or saves). For baseball, a possession is defined as a half-inning. For football, a possession can include a number of sequences in which the same team has the ball. For other types of sporting events as well as for non-sporting events, the term “possession” may be somewhat of a misnomer, but is still used herein for illustrative purposes. Examples in a non-sporting context may include a chapter, scene, act, television segment, or the like. For example, in the context of a music concert, a possession may equate to performance of a single song. A possession can include any number of occurrences. Sequence: A time-delimited portion of an event that includes one continuous time period of action. For example, in a sporting event, a sequence may begin when action begins (such as a face-off, tipoff, or the like), and may end when the whistle is blown to signify a break in the action. In a sport such as baseball or football, a sequence may be equivalent to a play, which is a form of occurrence. A sequence can include any number of possessions, or may be a portion of a possession. Highlight show: A set of highlights that are arranged for presentation to a user. The highlight show may be presented linearly (such as a video stream), or in a manner that allows the user to select which highlight to view and in which order (for example by clicking on links or thumbnails). Presentation of highlight show can be non-interactive or interactive, for example allowing a user to pause, rewind, skip, fast-forward, communicate a preference for or against, and/or the like. A highlight show can be, for example, a condensed game. A highlight show can include any number of contiguous or non-contiguous highlights, from a single event or from multiple events, and can even include highlights from different types of events (e.g. different sports, and/or a combination of highlights from sporting and non-sporting events). User/viewer: The terms “user” or “viewer” interchangeably refer to an individual, group, or other entity that is watching, listening to, or otherwise experiencing an event, one or more highlights of an event, or a highlight show. The terms “user” or “viewer” can also refer to an individual, group, or other entity that may at some future time watch, listen to, or otherwise experience either an event, one or more highlights of an event, or a highlight show. The term “viewer” may be used for descriptive purposes, although the event need not have a visual component, so that the “viewer” may instead be a listener or any other consumer of content. Narrative: A coherent story that links a set of highlight segments in a particular order. Excitement level: A measure of how exciting or interesting an event or highlight is expected to be for a particular user or for users in general. Excitement levels can also be determined with respect to a particular occurrence or player. Various techniques for measuring or assessing excitement level are discussed in the above-referenced related applications. As discussed, excitement level can depend on occurrences within the event, as well as other factors such as overall context or importance of the event (playoff game, pennant implications, rivalries, and/or the like). In at least one embodiment, an excitement level can be associated with each occurrence, string, possession, or sequence within an event. For example, an excitement level for a possession can be determined based on occurrences that take place within that possession. Excitement level may be measured differently for different users (e.g. a fan of one team vs. a neutral fan), and it can depend on personal characteristics of each user. Metadata: Data pertaining to and stored in association with other data. The primary data may be media such as a sports program or highlight. Card Image: An image in a video frame that provides data regarding anything depicted in the video, such as an event, a depiction of an event, or a portion thereof. Exemplary card images contain game scores, game clocks, and/or other statistics from sporting events. Card images may appear temporarily or for the full duration of a video stream; those that appear temporarily may pertain particularly to the portion of a video stream in which they appear. Character Image: A portion of an image that is believed to pertain to a single character. The character image may include the region surrounding the character. For example, a character image may include a generally rectangular bounding box surrounding a character. Character: A symbol that can be part of a word, number, or representation of a word or number. Characters can include letters, numbers, and special characters, and may be in

any language. Character String: A set of characters that is grouped together in a manner indicating that they pertain to a single piece of information, such as the name of the team playing in a sporting event. An English language character string will often be arranged horizontally and read left-to-right. However, character strings may be arranged differently in English and in other languages.

Overview

(17) According to various embodiments, methods and systems are provided for automatically creating time-based metadata associated with highlights of television programming of a sporting event. The highlights and associated in-frame time-based information may be extracted synchronously with respect to the television broadcast of a sporting event, or while the sporting event video content is being streamed via a video server from a backup device after the television broadcast of a sporting event.

(18) In at least one embodiment, a software application operates synchronously with playback and/or receipt of the television programming content to provide information metadata associated with content highlights. Such software can run, for example, on the television device itself, or on an associated set-top box (STB), or on a video server with the capability of receiving and subsequently streaming programming content, or on a mobile device equipped with the capability of receiving a video feed including live programming. In at least one embodiment, the highlights and associated metadata application operate synchronously with television programming content presentation.

(19) Interactive television applications can enable timely, relevant presentation of highlighted television programming content to users who are watching television programming either on a primary television display, or on a secondary display such as a tablet, laptop, or smartphone. A set of video clips representing television broadcast content highlights may be generated and/or stored in real-time, along with a database containing time-based metadata describing in more detail the events presented by highlight video clips.

(20) The metadata accompanying video clips can be any information such as textual information, a set of images, and/or any type of audiovisual data. One type of metadata associated with in-game and post-game video content highlights carries real-time information about sporting game parameters extracted directly from live programming content by reading information cards (“card images”) embedded in one or more of video frames of the programming content. In at least one embodiment, the described system and method enable this type of automatic metadata generation, thus associating the card image content with video highlights of the analyzed digital video stream.

(21) In various embodiments, an automated process is described, including: receiving a digital video stream, analyzing one or more video frames of the digital video stream for the presence and extraction of card images, localizing text boxes within the card images, and recognizing and interpreting strings of characters residing within the text boxes.

(22) The automated metadata generation video system presented herein may receive a live broadcast video stream or a digital video streamed via a computer server, and may process the video stream in real-time using computer vision and machine learning techniques to extract metadata from embedded information cards.

(23) In at least one embodiment, character strings associated with the extracted information card text fields are identified, and the location and size of the image of each character in the string of characters are recorded. Subsequently, any number of characters in text strings from various fields of the information card are recognized and text strings with recognized characters are interpreted, providing real-time information related to the sporting event television programming, such as current time and phase of the game, game score, play information, and/or the like.

(24) In another embodiment, individual character images are extracted from embedded character strings, and subsequently used to generate normalized query vectors. These normalized query vectors are then projected onto the orthogonal basis spanning the training vector space, said training vectors previously assembled and used to train a machine learning classifier such as, for example, a multi-class support vector machine (SVM) classifier (e.g. C. BURGESS, “A Tutorial on

Support Vector Machines for Pattern Recognition”, Kluwer Academic Publishers, 1998). Projected queries are subsequently used to generate query predictions as an output of a pre-trained classification model produced by exemplary SVM training mechanisms. It should be noted that classification models are not limited to the SVM-based models. Classification models may be also produced using other techniques, such as convolutional neural networks (CNNs), and with a multitude of variations in CNN algorithmic mechanisms (e.g. Y. LeCun et al., “Efficient NN Back Propagation”, Springer 1998) suitable to the training data set presented herein.

(25) In yet another embodiment, query character predictions are generated by applying projected query character vectors against a previously developed, machine learned classification model. In this step, a string of predicted characters is generated in accordance with previously established classification labels, and the predicted strings of alphanumeric characters are passed to a recognition and interpretation process. The query recognition and interpretation process applies previous knowledge and positional understanding of characters residing in a multitude of information card fields. The meaning of each predicted alphanumeric character, positioned in a particular group of characters, is further interpreted, and the derived information is appended to the video highlight metadata handled by the video highlight generation application.

(26) In yet another embodiment, a character classification model generation is considered, wherein the model is based on a training set of characters extracted from any number of information cards embedded in sporting event television programming content. Character bounding boxes are detected, and characters are extracted from a multitude of information cards. These character images are subsequently normalized to a standardized size and illumination, to form a descriptor associated with each particular character from a set of alphanumeric characters appearing in embedded information cards. In this manner, each extracted character image represents an n-dimensional vector in a multidimensional vector space containing the training set of vectors. The n-dimensional training vectors, representing the set of character images, are further processed to increase uniqueness and mutual metric distance, as well as to reduce the dimensionality of the overall vector space of training vectors.

(27) In at least one embodiment, a principal component analysis (e.g. G. Golub and F. Loan, “Matrix Computations”, Johns Hopkins Univ. Press, Baltimore, 1989) is performed on the training vector set. Thus, an orthogonal basis of vectors is devised from the training set, such that the orthogonal basis vectors span the training set vector space. In addition, the dimensionality of the training set vector space is reduced by selecting a limited number of orthogonal basis vectors such that only the most important orthogonal vectors, associated with the largest set of singular values, generated by singular value decomposition of the training set matrix of basis vectors, are retained. Subsequently, the selected training set basis vectors are saved for later use in classification model generation with one or more of available algorithmic structures for data set classification, such as a multi-class SVM-based classifier, or a CNN-based classifier.

(28) System Architecture

(29) According to various embodiments, the system can be implemented on any electronic device, or set of electronic devices, equipped to receive, store, and present information. Such an electronic device may be, for example, a desktop computer, laptop computer, television, smartphone, tablet, music player, audio device, kiosk, set-top box (STB), game system, wearable device, consumer electronic device, and/or the like.

(30) Although the system is described herein in connection with an implementation in particular types of computing devices, one skilled in the art will recognize that the techniques described herein can be implemented in other contexts, and indeed in any suitable device capable of receiving and/or processing user input, and presenting output to the user. Accordingly, the following description is intended to illustrate various embodiments by way of example, rather than to limit scope.

(31) Referring now to FIG. 1A, there is shown a block diagram depicting hardware architecture of

a system **100** for automatically extracting metadata from card images embedded in a video stream of an event, according to a client/server embodiment. Event content, such as the video stream, may be provided via a network-connected content provider **124**. An example of such a client/server embodiment is a web-based implementation, wherein each of one or more client devices **106** runs a browser or app that provides a user interface for interacting with content from various servers **102**, **114**, **116**, including data provider(s) servers **122**, and/or content provider(s) servers **124**, via communications network **104**. Transmission of content and/or data in response to requests from client device **106** can take place using any known protocols and languages, such as Hypertext Markup Language (HTML), Java, Objective C, Python, JavaScript, and/or the like.

(32) Client device **106** can be any electronic device, such as a desktop computer, laptop computer, television, smartphone, tablet, music player, audio device, kiosk, set-top box, game system, wearable device, consumer electronic device, and/or the like. In at least one embodiment, client device **106** has a number of hardware components well known to those skilled in the art. Input device(s) **151** can be any component(s) that receive input from user **150**, including, for example, a handheld remote control, keyboard, mouse, stylus, touch-sensitive screen (touchscreen), touchpad, gesture receptor, trackball, accelerometer, five-way switch, microphone, or the like. Input can be provided via any suitable mode, including for example, one or more of: pointing, tapping, typing, dragging, gesturing, tilting, shaking, and/or speech. Display screen **152** can be any component that graphically displays information, video, content, and/or the like, including depictions of events, highlights, and/or the like. Such output may also include, for example, audiovisual content, data visualizations, navigational elements, graphical elements, queries requesting information and/or parameters for selection of content, or the like. In at least one embodiment, where only some of the desired output is presented at a time, a dynamic control, such as a scrolling mechanism, may be available via input device(s) **151** to choose which information is currently displayed, and/or to alter the manner in which the information is displayed.

(33) Processor **157** can be a conventional microprocessor for performing operations on data under the direction of software, according to well-known techniques. Memory **156** can be random-access memory, having a structure and architecture as are known in the art, for use by processor **157** in the course of running software for performing the operations described herein. Client device **106** can also include local storage (not shown), which may be a hard drive, flash drive, optical or magnetic storage device, web-based (cloud-based) storage, and/or the like.

(34) Any suitable type of communications network **104**, such as the Internet, a television network, a cable network, a cellular network, and/or the like can be used as the mechanism for transmitting data between client device **106** and various server(s) **102**, **114**, **116** and/or content provider(s) **124** and/or data provider(s) **122**, according to any suitable protocols and techniques. In addition to the Internet, other examples include cellular telephone networks, EDGE, 3G, 4G, long term evolution (LTE), Session Initiation Protocol (SIP), Short Message Peer-to-Peer protocol (SMPP), SS7, Wi-Fi, Bluetooth, ZigBee, Hypertext Transfer Protocol (HTTP), Secure Hypertext Transfer Protocol (SHTTP), Transmission Control Protocol/Internet Protocol (TCP/IP), and/or the like, and/or any combination thereof. In at least one embodiment, client device **106** transmits requests for data and/or content via communications network **104**, and receives responses from server(s) **102**, **114**, **116** containing the requested data and/or content.

(35) In at least one embodiment, the system of FIG. 1A operates in connection with sporting events; however, the teachings herein apply to nonsporting events as well, and it is to be appreciated that the technology described herein is not limited to application to sporting events. For example, the technology described herein can be utilized to operate in connection with a television show, movie, news event, game show, political action, business show, drama, and/or other episodic content, or for more than one such event.

(36) In at least one embodiment, system **100** identifies highlights of broadcast events by analyzing a video stream of the event. This analysis may be carried out in real-time. In at least one

embodiment, system **100** includes one or more web server(s) **102** coupled via a communications network **104** to one or more client devices **106**. Communications network **104** may be a public network, a private network, or a combination of public and private networks such as the Internet. Communications network **104** can be a LAN, WAN, wired, wireless and/or combination of the above. Client device **106** is, in at least one embodiment, capable of connecting to communications network **104**, either via a wired or wireless connection. In at least one embodiment, client device may also include a recording device capable of receiving and recording events, such as a DVR, PVR, or other media recording device. Such recording device can be part of client device **106**, or can be external; in other embodiments, such recording device can be omitted. Although FIG. **1A** shows one client device **106**, system **100** can be implemented with any number of client device(s) **106** of a single type or multiple types.

(37) Web server(s) **102** may include one or more physical computing devices and/or software that can receive requests from client device(s) **106** and respond to those requests with data, as well as send out unsolicited alerts and other messages. Web server(s) **102** may employ various strategies for fault tolerance and scalability such as load balancing, caching and clustering. In at least one embodiment, web server(s) **102** may include caching technology, as known in the art, for storing client requests and information related to events.

(38) Web server(s) **102** may maintain, or otherwise designate, one or more application server(s) **114** to respond to requests received from client device(s) **106**. In at least one embodiment, application server(s) **114** provide access to business logic for use by client application programs in client device(s) **106**. Application server(s) **114** may be co-located, co-owned, or co-managed with web server(s) **102**. Application server(s) **114** may also be remote from web server(s) **102**. In at least one embodiment, application server(s) **114** interact with one or more analytical server(s) **116** and one or more data server(s) **118** to perform one or more operations of the disclosed technology.

(39) One or more storage devices **153** may act as a “data store” by storing data pertinent to operation of system **100**. This data may include, for example, and not by way of limitation, card data **154** pertinent to card images embedded in video streams presenting events such as sporting events, user data **155** pertinent to one or more users **150**, highlight data **164** pertinent to one or more highlights of the events, and/or a classification model **165**, which may be used to predict and/or extract text from card data **154**.

(40) Card data **154** can include any information related to card images embedded in the video stream, such as the card images themselves, subsets thereof such as character images, text extracted from the card images such as characters and character strings, and attributes of any of the foregoing that can be helpful in text and/or meaning extraction. User data **155** can include any information describing one or more users **150**, including for example, demographics, purchasing behavior, video stream viewing behavior, interests, preferences, and/or the like. Highlight data **164** may include highlights, highlight identifiers, time indicators, categories, excitement levels, and other data pertaining to highlights. Classification model **165** may include machine trained classification model, queries, query feature vectors, training set orthogonal bases, predicted queries, extracted text meaning, and/or other information that facilitates extraction of text and/or meaning from card data **154**. Card data **154**, user data **155**, highlight data **164**, and classification model **165** will be described in detail subsequently.

(41) Notably, many components of system **100** may be, or may include, computing devices. Such computing devices may each have an architecture similar to that of the client device **106**, as shown and described above. Thus, any of communications network **104**, web servers **102**, application servers **114**, analytical servers **116**, data providers **122**, content providers **124**, data servers **118**, and storage devices **153** may include one or more computing devices, each of which may optionally have an input device **151**, display screen **152**, memory **156**, and/or a processor **157**, as described above in connection with client devices **106**.

(42) In an exemplary operation of system **100**, one or more users **150** of client devices **106** view

content from content providers **124**, in the form of video streams. The video streams may show events, such as sporting events. The video streams may be digital video streams that can readily be processed with known computer vision techniques.

(43) As the video streams are displayed, one or more components of system **100**, such as client devices **106**, web servers **102**, application servers **114**, and/or analytical servers **116**, may analyze the video streams, identify highlights within the video streams, and/or extract metadata from the video stream, for example, from embedded card images and/or other aspects of the video stream. This analysis may be carried out in response to receipt of a request to identify highlights and/or metadata for the video stream. Alternatively, in another embodiment, highlights may be identified without a specific request having been made by user **150**. In yet another embodiment, the analysis of video streams can take place without a video stream being displayed.

(44) In at least one embodiment, user **150** can specify, via input device(s) **151** at client device **106**, certain parameters for analysis of the video stream (such as, for example, what event/games/teams to include, how much time user **150** has available to view the highlights, what metadata is desired, and/or any other parameters). User preferences can also be extracted from storage, such as from user data **155** stored in one or more storage devices **153**, so as to customize analysis of the video stream without necessarily requiring user **150** to specify preferences. In at least one embodiment, user preferences can be determined based on observed behavior and actions of user **150**, for example, by observing website visitation patterns, television watching patterns, music listening patterns, online purchases, previous highlight identification parameters, highlights and/or metadata actually viewed by user **150**, and/or the like.

(45) Additionally or alternatively, user preferences can be retrieved from previously stored preferences that were explicitly provided by user **150**. Such user preferences may indicate which teams, sports, players, and/or types of events are of interest to user **150**, and/or they may indicate what type of metadata or other information related to highlights, would be of interest to user **150**. Such preferences can therefore be used to guide analysis of the video stream to identify highlights and/or extract metadata for the highlights.

(46) Analytical server(s) **116**, which may include one or more computing devices as described above, may analyze live and/or recorded feeds of play-by-play statistics related to one or more events from data provider(s) **122**. Examples of data provider(s) **122** may include, but are not limited to, providers of real-time sports information such as STATS™, Perform (available from Opta Sports of London, UK), and SportRadar of St. Gallen, Switzerland. In at least one embodiment, analytical server(s) **116** generate different sets of excitement levels for events; such excitement levels can then be stored in conjunction with highlights identified by system **100** according to the techniques described herein.

(47) Application server(s) **114** may analyze the video stream to identify the highlights and/or extract the metadata. Additionally or alternatively, such analysis may be carried out by client device(s) **106**. The identified highlights and/or extracted metadata may be specific to a user **150**; in such case, it may be advantageous to identify the highlights in client device **106** pertaining to a particular user **150**. Client device **106** may receive, retain, and/or retrieve the applicable user preferences for highlight identification and/or metadata extraction, as described above. Additionally or alternatively, highlight generation and/or metadata extraction may be carried out globally (i.e., using objective criteria applicable to the user population in general, without regard to preferences for a particular user **150**). In such a case, it may be advantageous to identify the highlights and/or extract the metadata in application server(s) **114**.

(48) Content that facilitates highlight identification and/or metadata extraction may come from any suitable source, including from content provider(s) **124**, which may include websites such as YouTube, MLB.com, and the like; sports data providers; television stations; client- or server-based DVRs; and/or the like. Alternatively, content can come from a local source such as a DVR or other recording device associated with (or built into) client device **106**. In at least one embodiment,

application server(s) **114** generate a customized highlight show, with highlights and metadata, available to user **150**, either as a download, or streaming content, or on-demand content, or in some other manner.

(49) As mentioned above, it may be advantageous for user-specific highlight identification and/or metadata extraction to be carried out at a particular client device **106** associated with a particular user **150**. Such an embodiment may avoid the need for video content or other high-bandwidth content to be transmitted via communications network **104** unnecessarily, particularly if such content is already available at client device **106**.

(50) For example, referring now to FIG. **1B**, there is shown an example of a system **160** according to an embodiment wherein at least some of the card data **154**, highlight data **164**, and classification model **165** are stored at client-based storage device **158**, which may be any form of local storage device available to client device **106**. An example is a DVR on which events may be recorded, such as for example video content for a complete sporting event. Alternatively, client-based storage device **158** can be any magnetic, optical, or electronic storage device for data in digital form; examples include flash memory, magnetic hard drive, CD-ROM, DVD-ROM, or other device integrated with client device **106** or communicatively coupled with client device **106**. Based on the information provided by application server(s) **114**, client device **106** may extract metadata from card data **154** stored at client-based storage device **158** and store the metadata as highlight data **164** without having to retrieve other content from a content provider **124** or other remote source. Such an arrangement can save bandwidth, and can usefully leverage existing hardware that may already be available to client device **106**.

(51) Returning to FIG. **1A**, in at least one embodiment, application server(s) **114** may identify different highlights and/or extract different metadata for different users **150**, depending on individual user preferences and/or other parameters. The identified highlights and/or extracted metadata may be presented to user **150** via any suitable output device, such as display screen **152** at client device **106**. If desired, multiple highlights may be identified and compiled into a highlight show, along with associated metadata. Such a highlight show may be accessed via a menu, and/or assembled into a “highlight reel,” or set of highlights, that plays for the user **150** according to a predetermined sequence. User **150** can, in at least one embodiment, control highlight playback and/or delivery of the associated metadata via input device(s) **151**, for example to: select particular highlights and/or metadata for display; pause, rewind, fast-forward; skip forward to the next highlight; return to the beginning of a previous highlight within the highlight show; and/or perform other actions.

(52) Additional details on such functionality are provided in the above-cited related U.S. patent applications.

(53) In at least one embodiment, one more data server(s) **118** are provided. Data server(s) **118** may respond to requests for data from any of server(s) **102**, **114**, **116**, for example to obtain or provide card data **154**, user data **155**, highlight data **164**, and/or the classification model **165**. In at least one embodiment, such information can be stored at any suitable storage device **153** accessible by data server **118**, and can come from any suitable source, such as from client device **106** itself, content provider(s) **124**, data provider(s) **122**, and/or the like.

(54) Referring now to FIG. **1C**, there is shown a system **180** according to an alternative embodiment wherein system **180** is implemented in a stand-alone environment. As with the embodiment shown in FIG. **1B**, at least some of the card data **154**, user data **155**, highlight data **164**, and classification model **165** may be stored at a client-based storage device **158**, such as a DVR or the like. Alternatively, client-based storage device **158** can be flash memory or a hard drive, or other device integrated with client device **106** or communicatively coupled with client device **106**.

(55) User data **155** may include preferences and interests of user **150**. Based on such user data **155**, system **180** may extract metadata within card data **154** to present to user **150** in the manner

described herein. Additionally or alternatively, metadata may be extracted based on objective criteria that are not based on information specific to user **150**.

(56) Referring now to FIG. **1D**, there is shown an overview of a system **190** with architecture according to an alternative embodiment. In FIG. **1D**, the system **190** includes a broadcast service such as content provider(s) **124**, a content receiver in the form of client device **106** such as a television set with a STB, a video server such as analytical server(s) **116** capable of ingesting and streaming television programming content, and/or other client devices **106** such as a mobile device and a laptop, which are capable of receiving and processing television programming content, all connected via a network such as communications network **104**. A client-based storage device **158**, such as a DVR, may be connected to any of client devices **106** and/or other components, and may store a video stream, highlights, highlight identifiers, and/or metadata to facilitate identification and presentation of highlights and/or extracted metadata via any of client devices **106**.

(57) The specific hardware architectures depicted in FIGS. **1A**, **1B**, **1C**, and **1D** are merely exemplary. One skilled in the art will recognize that the techniques described herein can be implemented using other architectures. Many components depicted therein are optional and may be omitted, consolidated with other components, and/or replaced with other components.

(58) In at least one embodiment, the system can be implemented as software written in any suitable computer programming language, whether in a standalone or client/server architecture.

Alternatively, it may be implemented and/or embedded in hardware.

(59) Data Structures

(60) FIG. **2** is a schematic block diagram depicting examples of data structures that may be incorporated into card data **154**, user data **155**, highlight data **164**, and classification model **165**, according to one embodiment.

(61) As shown, card data **154** may include a record for each of a plurality of card images embedded in one or more video streams. Each of the card images may contain one or more character strings **200**. Each of the character strings **200** may have records for n characters. Each such record may have a character image **202**, a processed character image **203**, character boundaries **204**, a size **205**, a location **206**, a contrast ratio **207**, and/or an interpretation **208**. Each of the character strings **200** may further have a string length **209**, indicating the length of the character string **200** (for example, in characters, pixels, or the like).

(62) Character image **202** may be the particular portion of the card image that contains a single character. Processed character image **203** may be character image **202** after application of one or more processing steps, such as normalization for size, brightness, and/or the like.

(63) Character boundaries **204** may indicate the boundaries of character image **202**, processed character image **203**, and/or the character represented in character image **202** and processed character image **203**.

(64) Size **205** may be the size of character image **202**, processed character image **203**, and/or the character represented in character image **202** and processed character image **203**, for example, in pixels.

(65) Location **206** may be the position of character image **202**, processed character image **203**, and/or the character represented in character image **202** and processed character image **203** within the card image. In some examples, location **206** may indicate position in two dimensions (for example, x and y coordinates of a corner or center of character image **202**, processed character image **203**, and/or the character represented in character image **202** and processed character image **203**).

(66) Contrast ratio **207** may be an indicator of contrast of character image **202**, processed character image **203**, and/or the character represented in character image **202** and processed character image **203**. In some examples, contrast ratio **207** may be the ratio of luminance values of one or more brightest pixels, to that of one or more darkest pixels, within character image **202**, processed character image **203**, and/or the character represented in character image **202** and processed

character image **203**.

(67) Interpretation **208** may be the specific character, for example, a, b, c, 1, 2, 3, #, &, etc., believed to be represented in character image **202** after some analysis has been performed to interpret character string **200**.

(68) The structure of card data **154** set forth in FIG. 2 is merely exemplary; in some embodiments, data pertinent to card images embedded in a video stream may be organized differently. For example, in other embodiments, each character string may not necessarily be broken down into individual character images. Rather, character strings may be interpreted as a whole, and data useful to interpretation of the character string may be stored for the entire character string. Further, in alternative embodiments, data not specifically described above may be incorporated into card data **154**. The structures of user data **155**, highlight data **164**, and classification model **165** of FIG. 2 are likewise merely exemplary; many alternatives may be envisioned by a person of skill in the art.

(69) As further shown, user data **155** may include records pertaining to users **150**, each of which may include demographic data **212**, preferences **214**, viewing history **216**, and purchase history **218** for a particular user **150**.

(70) Demographic data **212** may include any type of demographic data, including but not limited to age, gender, location, nationality, religious affiliation, education level, and/or the like.

(71) Preferences **214** may include selections made by user **150** regarding his or her preferences. Preferences **214** may relate directly to highlight and metadata gathering and/or viewing, or may be more general in nature. In either case, preferences **214** may be used to facilitate identification and/or presentation of the highlights and metadata to user **150**.

(72) Viewing history **216** may list the television programs, video streams, highlights, web pages, search queries, sporting events, and/or other content retrieved and/or viewed by the user **150**.

(73) Purchase history **218** may list products or services purchased or requested by user **150**.

(74) As further shown, highlight data **164** may include records for *j* highlights **220**, each of which may include a video stream **222**, an identifier, and/or metadata **224** for a particular highlight **220**.

(75) Video stream **222** may include video depicting highlight **220**, which may be obtained from one or more video streams of one or more events (for example, by cropping the video stream to include only video stream **222** pertaining to highlight **220**). Identifier **223** may include time codes and/or other indicia that indicate where highlight **220** resides within the video stream of the event from which it is obtained.

(76) In some embodiments, the record for each of highlights **220** may contain only one of video stream **222** and identifier **223**. Highlight playback may be carried out by playing video stream **222** for user **150**, or by using identifier **223** to play only the highlighted portion of the video stream for the event from which the highlight **220** is obtained.

(77) Metadata **224** may include information about highlight **220**, such as the event date, season, and groups or individuals involved in the event or the video stream from which highlight **220** was obtained, such as teams, players, coaches, anchors, broadcasters, and fans, and/or the like. Among other information, metadata **224** for each highlight **220** may include a time **225**, phase **226**, clock **227**, score **228**, and/or frame number **229**.

(78) Time **225** may be a time, within video stream **222**, from which highlight **220** is obtained, or within video stream **222** pertaining to highlight **220**, at which metadata is available. In some examples, time **225** may be the playback time, within video stream **222**, pertaining to highlight **220**, at which a card image is displayed containing metadata **224**.

(79) Phase **226** may be the phase of the event pertaining to highlight **220**. More particularly, phase **226** may be the stage of a sporting event at which the card image is displayed containing metadata **224**. For example, phase **226** may be “third quarter,” “second inning,” “bottom half,” or the like.

(80) Clock **227** may be the game clock pertaining to highlight **220**. More particularly, clock **227** may be state of the game clock at the time the card image is displayed containing metadata **224**.

For example, clock **227** may be “15:47” for a card image displayed with fifteen minutes and forty-seven seconds displayed on the game clock.

(81) Score **228** may be the game score pertaining to highlight **220**. More particularly, score **228** may be the score when the card image is displayed containing metadata **224**. For example, score **228** may be “45-38,” “7-0,” “30-love,” or the like.

(82) Frame number **229** may be the number of the video frame, within the video stream from which highlight **220** is obtained, or video stream **222** pertaining to highlight **220**, that relates most directly to highlight **220**. More particularly, frame number **229** may be the number of such a video frame at which the card image is displayed containing metadata **224**.

(83) As shown further, classification model **165** may include a variety of information that facilitates extraction and interpretation of character strings **200**. This, in turn, may enable automated generation of metadata **224** for highlights **220**. Specifically, classification model **165** may include queries **230**, query feature vectors **232**, orthogonal basis **234**, predicted queries **236**, and/or text meaning **238**.

(84) The operation of queries **230**, query feature vectors **232**, orthogonal basis **234**, and predicted queries **236** are set forth in greater detail herein. Text meaning **238** may be the interpretation of character strings **200**, rendered in a manner that can be easily copied into metadata **224**.

(85) The data structures set forth in FIG. 2 are merely exemplary. Those of skill in the art will recognize that some of the data of FIG. 2 may be omitted or replaced with other data in the performance of highlight identification and/or metadata extraction. Additionally or alternatively, data not shown in FIG. 2 may be used in the performance of highlight identification and/or metadata extraction.

(86) Card Images

(87) Referring now to FIG. 3, there is shown a screenshot diagram of an example of a video frame **300** from a video stream with embedded information in the form of card images, as may frequently appear in sporting event television programming. FIG. 3 depicts a card image **310** in the lower right-hand side of video frame **300**, and a second card image **320** extending along the bottom of video frame **300**. Card images **310**, **320** may contain embedded information such as the game phase, current clocks, and current scores.

(88) In at least one embodiment, the information in card images **310**, **320** is localized and processed for automatic recognition and interpretation of embedded text in card images **310**, **320**. The interpreted text may then be assembled into textual metadata describing the status of the sporting game at particular point of time within the sporting event timeline.

(89) Notably, card image **310** may pertain to the sporting event currently being shown, while second card image **320** may contain information for a different sporting event. In some embodiments, only card images containing information deemed to be pertinent to the currently playing sporting event is processed for metadata generation. Thus, without limiting scope, the exemplary description below assumes that only card image **310** will be processed. However, in alternative embodiments, it may be desirable to process multiple card images in a given video frame **300**, even including card images pertaining to other sporting events.

(90) As shown in FIG. 3, card image **310** can provide several different types of metadata **224**, including team names **330**, scores **340**, prior team performance **350**, a current game stage **360**, a game clock **370**, a play status **380**, and/or other information **390**. Each of these may be extracted from within card image **310** and interpreted to provide metadata **224** corresponding to highlight **220** containing video frame **300**, and more particularly, to video frame **300** in which card image **310** is displayed.

(91) Metadata Extraction

(92) FIG. 4 is a flowchart depicting a method **400**, according to one embodiment, carried out by an application running, for example, on one of client devices **106**, and/or analytical servers **116**, that receives a video stream **222** and performs on-the-fly processing of video frames **300** for extraction

of metadata from card images such as **310**. System **100** of FIG. **1A** will be referenced as the system carrying out method **400** and those that follow; however, alternative systems, including but not limited to system **160** of FIG. **1B**, system **180** of FIG. **1C**, and/or system **190** of FIG. **1D**, may be used in place of system **100** of FIG. **1A**.

(93) Method **400** of FIG. **4** depicts, in more detail, the process outlined above. A video stream, such as a video stream **222** corresponding to a highlight **220** that has been previously identified, may be received and decoded. In a step **410**, one or more video frames **300** of video stream **222** may be received, resized to standard sizes, and decoded. In a step **420**, a video frame **300** may be processed to detect and, if applicable, extract one or more card images, such as card image **310** of FIG. **3**, from video frame **300**. Pursuant to a query **430**, if no valid card image **310** is found in video frame **300**, method **400** may return to step **410** to decode and analyze a different video frame **300**.

(94) If a valid card image **310** has been found, then in a step **440**, video frame **300** may be further processed to localize, extract, and process a detected card image **310** and extract and process text boxes and/or strings of characters embedded in card image **310**. Pursuant to a query **450**, if no valid character string **200** is found in card image **310**, method **400** may return to step **410** to process a new video frame **300**.

(95) If a valid character string **200** is found in card image **310**, method **400** may proceed to a step **460**, in which extracted character string(s) **200** are recognized and interpreted, and corresponding metadata **224** is generated based on the interpretation of information from card image **310**. In various embodiments, the available choices for text interpretation are based on determining the type of card image of card image **310** detected in video frame **300**, and/or on advance knowledge of detected fields present within the particular type of card image applicable to card image **310** detected in video frame **300**.

(96) As indicated previously, detection, localization, and interpretation of embedded text in card images present in television programming content may occur entirely locally on the TV, on a STB, or on a mobile device. Alternatively, it can occur remotely on a remote video server with broadcast video ingestion and streaming capability. Alternatively, any combination of local and remote processing can be used.

(97) Information Card Character Strings Processing: Localization and Extraction

(98) An “Extremal Region” (ER) is an image region whose outer boundary pixels have strictly higher values than the region itself (e.g. L. Neumann, J. Matas, “Real-Time Scene Text Localization and Recognition”, 5th IEEE Conference on Computer Vision and Pattern Recognition, Providence, RI, June 2012). One of the well-known methods used for ER detection in an image uses a so-called maximally stable ER detector, or MSER detector. Additional detection methods allow for testing of a wider range of ERs, while maintaining relatively low computational complexity. When a wider range of ERs are included in the test, a sequential classifier can be introduced which is based on certain features pertinent to the character regions. This classifier can be pre-trained to generate a probability of the presence of a character, which results in multiple probable detected boundaries of a character (i.e., character boundaries **204**). While in the first stage of ER classification, the probability of the presence of a character is estimated; in the second stage, ERs with locally maximal probability are selected. The classification can be further improved by using some more computationally expensive features. Furthermore, in at least one embodiment, a repetitive exhaustive search is applied to detect combinations of characters and to group ERs into words. Such methods also allow for region edges to be included into the consideration of ERs for improved character detection. The final outcome is an ER selected with highest probability of representing character boundaries **204**.

(99) Since the character detector described above generates several regions for the same character, the next step is to disambiguate the detected regions. In at least one embodiment, this disambiguation involves performing multiple comparisons of detected character boundaries **204**, and subsequently purging character boundaries **204**, which may be in the form of character-

bounding boxes, which appear too close to each other. As a result, only one character-bounding box is accepted within a certain perimeter, thus allowing for a correct formation of a character string **200** representing the appropriate text field of card image **310**.

(100) FIG. **5** is a flowchart depicting a method **500** for carrying out, in more detail, the process outlined above. A video frame **300** is selected for processing, or an option is chosen to process each video frame **300** in succession. In a step **510**, card images **310** in video frames **300**, if any are detected, are extracted and resized to a standardized size. Next, in a step **520**, the resized card images are pre-processed by a chain of filters, including for example: contrast increase, bilateral and median filtering for noise reduction, gamma correction, and/or illumination compensation.

(101) In a step **530**, an ER filter with 2-stage classifiers is created, and in a step **540**, this cascade classifier is applied to each image channel of card image **310**. Character groups are detected, and one or more groups of word boxes are extracted for further processing. In a step **550**, character strings **200** with individual character boundaries **204** are analyzed for character boundary disambiguation. Finally, a clean character string **200** is generated, with only one character accepted within each of the perimeters of a location **206** of a character.

(102) FIG. **6** is a flowchart depicting a method **600** of further processing for validation of character boundaries **204**. Method **600** may commence with extraction of character strings **200**, removal of duplicate characters, and final processing and acceptance of character strings **200**, in a step **610**. As depicted, each character within the string of disambiguated characters may be further processed for character image validation.

(103) Thus, in a step **620**, pixel count ratios may be obtained in low and high intensity regions of each character image **202** (or processed character image **203**), for comparison with a predefined contrast ratio between low- and high-intensity pixel counts. In step **620**, for each character image **202** or processed character image **203**, high- and low-intensity level pixels are grouped and counted.

(104) Next, in a step **630**, the ratio of these two counts is computed and subjected to thresholding, such that only character images **202** or processed character images **203** with sufficiently high contrast ratios are retained. Subsequently, in a step **640**, positional bounding box coordinates (i.e., locations **206**) for validated characters are recorded and saved for further use in interpretation of character strings **200**.

(105) In alternative embodiments, the character-bounding box validation described above may precede the character boundary disambiguation, or it may be used in combination with character boundary disambiguation for final character validation.

(106) Information Card Processing for Query Extraction and Recognition

(107) In at least one embodiment, an automated process is performed, including the steps of: receiving a digital video stream, such as video stream **222** pertaining to a highlight **220**; analyzing one or more video frames **300** of the digital video stream for the presence of a card image **310**; extracting card image **310**; localizing character boundaries **204** for characters of character strings **200** within card image **310**; and extracting text residing within the text boxes to create a query string of characters.

(108) FIG. **7** is a flowchart depicting a method **700** of information card query generation according to one embodiment. In a step **710**, card images **310** are extracted from decoded video frames **300**. In a step **720**, card images **310** are processed to identify and extract character strings **200** as described above. In a step **730**, character images **202** are extracted from card images **310** and normalized query images (for example, queries **230**), are generated. In a step **740**, a query infrastructure is populated with normalized query character images (query feature vectors **232**).

(109) In another embodiment, query predictions are generated by first projecting query feature vectors onto a previously developed training set orthogonal basis (for example, orthogonal basis **234**), and then applying the resulting projected query feature vectors to a machine-learned classification model, such as classification model **165**. A string of predicted alphanumeric

characters may be generated in accordance with previously established classification labels, and this predicted alphanumeric string may be passed to an interpretation process for final extraction of text meaning **238**.

(110) FIG. **8** is a flowchart depicting a method **800** containing processing steps for query recognition, leading to query alphanumeric string generation and query interpretation and understanding. In a step **810**, orthogonal basis vectors of orthogonal basis **234** are loaded, spanning the training set vector space. In a step **820**, normalized queries may be projected onto orthogonal basis **234**. In a step **830**, classification model **165**, as previously developed, may be loaded. Classification model **165** may be applied to projected queries. Finally, in a step **840**, a string of predicted alphanumeric characters may be generated, and subsequently used for interpretation and meaning extraction to yield text meaning **238**.

(111) Query Interpretation and Meaning Extraction

(112) In at least one embodiment, one or more character strings **200** residing within card image **310** are identified. Subsequent steps may include localization, size determination, and extraction of each character image **202** in identified character strings **200**. Detected and extracted character images **202** are converted into query feature vectors **232** and projected onto training set orthogonal basis **234**. Subsequently, the projected queries are applied against classification model **165**, to produce a string of predicted alphanumeric characters.

(113) In at least one embodiment, the predicted query alphanumeric characters are routed to an interpretation process that applies previous knowledge and positional understanding of characters residing in a multitude of card images **310**. Next, the meaning is derived for each predicted alphanumeric character positioned in a particular character string **200**, and the extracted information is appended to metadata **224** stored in association with highlight **220**.

(114) FIG. **9** is a flowchart depicting, in more detail, a method **900** for predicted query string interpretation according to one embodiment. Method **900** involves combining consideration of character string length, position and horizontal distance of character boxes, and alphanumeric readings for meaning extraction.

(115) Method **900** starts with a step **910** in which a character count in each processed query for a character string **200** is loaded, together with size **205** and location **206** of the character within character string **200**. The video frame number and/or time, associated with extracted queries **230** to be processed, may also be made available for a reference related to the absolute time. In a step **920**, string length **209**, size **205** of the characters, and/or location **206** of the characters may be considered in the analysis.

(116) Next, in a step **930**, system **100** may proceed through character string **200**, and character string **200** may be interpreted by applying knowledge of field position of the characters, as well as the knowledge of alphanumeric values of the characters. In step **930**, knowledge and understanding of particular card image **310** may also be used to compensate for possible missing front characters. Finally, in a step **940**, the derived meaning is recorded (for example, in text meaning **238**), and corresponding metadata **224** are formed, providing real-time information related to the current sporting event television programming and the current timeline associated with processed embedded card images **310**.

(117) Generation of Machine Learned Classification Model with Application to Recognition of Query Characters Extracted from Embedded Information Cards

(118) In at least one embodiment, classification model generation is performed using convolutional neural networks. In general, neural networks develop their information categorization capabilities through a supervised learning process applied to a training set of character vectors, and with a known (desired) classification outcome. During the training process, the neural network algorithmic structure adjusts its weights and biases to perform accurate classification. One example of a known architecture used for learning internal weights and biases of a neural network during the training process, is a back-propagation neural network architecture, or feed-forward back-

propagation neural network architecture. When such a network is presented with a set of training data, the back-propagation algorithm computes the difference between the actual output and desired output, and feeds back the error to correct the inner network weights and biases that are responsible for error generation. At the classification/inference phase, a neural network structure is first loaded with pre-learned model parameters, weights, and biases, and then a query is fed forward through the network, resulting in one or more identified label(s) at the network output representing query prediction.

(119) In another exemplary system for classification model generation, a multi-class SVM is used. Such SVM classification systems differ radically from comparable approaches such as neural network learning systems, which rely heavily on heuristics to construct various network architectures, and with training processes that do not always end in a global minimum. In contrast, SVMs are mathematically very well defined, and with a training process that consistently finds a global minimum. In addition, with SVMs, there is a relatively simple and clear geometric interpretation of the training process and classification goals, which improve on the intuitive insight into the process of classification model generation. An SVM can be efficiently utilized for classification of data sets that are not linearly separable, and can be extended to multi-label classification tasks. The SVM for classification of data sets that are not linearly separable is characterized by the choice of kernel functions, which help project the data set onto a high-dimensional vector space, where the original data sets become linearly separable. However, the choice of kernel functions is non-trivial, and includes a degree of heuristics and data dependency.

(120) In at least one embodiment, character classification model generation is based on a training set of characters extracted from one or more exemplary card images **310** embedded in sporting event television programming contents. Character boundaries **204** are detected and characters are extracted from a multitude of card images **310**. Such character boundaries **204** contain small character images **202** that may be subsequently normalized to a standard size and illumination to provide processed character images **203**. Feature vectors (or query feature vectors **232**) are formed for character images **202** and/or processed character images **203**, and these feature vectors are then associated with each particular character from a set of character images appearing in embedded card images **310**.

(121) In a structural approach to a character image feature formation, a character feature vector, or query feature vector **232**, is associated with a set of n pixels extracted from a preprocessed character image **202**. These n pixels are formatted into an n-dimensional vector, representing a single point in the n-dimensional feature vector space of training vectors. The main goal of feature selection is to construct a decision boundary in feature space that correctly separates character images **202** of different classes. Hence, in at least one embodiment, the extracted set of character images **202**, representing the training vectors, are further processed to increase uniqueness and mutual metric distance of training vectors, as well as to reduce the dimensionality of the overall vector space of training vectors.

(122) In accordance with the above considerations, in another embodiment, a principal component analysis (PCA) is performed on the training vector set. Thus, orthogonal basis vectors of orthogonal basis **234** are derived from the training set, such that the orthogonal basis vectors are spanning the training vector space. In addition, the dimensionality of the training vector space is reduced by selecting a limited number of orthogonal basis vectors such that only the most important orthogonal vectors, associated with the largest set of singular values (generated by singular value decomposition of the matrix of training vectors) are retained. The selected training set basis vectors are saved for later use in classification model generation with one or more of available algorithmic structures for data set classification, such as an SVM classifier or a CNN classifier.

(123) In various embodiments, the systems and methods described herein provide techniques for extracting individual character images **202** from character strings **200** embedded in card images

310, and for subsequent utilization of character images **202** to generate query feature vectors **232**. In the next processing step, these query feature vectors are projected onto orthogonal basis **234** spanning the training vector space to generate projected queries. Projected queries are subsequently applied to generate query predictions, or predicted queries **236**, as an output of the pre-trained classification model produced by the exemplary SVM (or CNN) classifier. These predicted queries **236** form a string of predicted characters, which is subsequently interpreted to generate text meaning **238**, and finally used to generate metadata **224** for highlights **220**, enriched with real-time information read directly from card images **310**.

(124) FIG. **10** is a flowchart depicting, in more detail, a method **1000** of classification model generation. In at least one embodiment, method **1000** commences with a step **1010** in which an exemplary training set of character images **202** is extracted from a multitude of exemplary card image types. Character images **202** are normalized to a standard size and illumination to form processed character images **203**. Feature vectors are derived, and a labeled training set is generated. In at least one embodiment, in a step **1020**, PCA analysis is performed on the training set by computing orthogonal basis **234** spanning the training vector space. In a step **1030**, a subset of orthogonal training vectors is selected. The selected training set basis vectors may be saved for query processing in a step **1040**. In a step **1050**, classification model **165** may be trained with the subset of orthogonal training vectors. The classification model and the orthogonal basis vectors may be saved, in a step **1060**, for generation of future predicted queries **236**.

(125) FIG. **11** is a flowchart depicting an overall method **1100** of reading and interpreting text fields in cards images **310**, and updating metadata **224** for highlights **220** with in-frame real-time information. In a step **1110**, a field to be processed is selected from character boundaries **204** of the characters present in card image **310**. In a step **1120**, a group of characters is extracted from a line field, and text strings are recognized and interpreted as described above. Finally, in a step **1130**, the card image reading performed on decoded video frame boundaries is embedded in metadata **224** generated for highlight **220**.

(126) The present system and method have been described in particular detail with respect to possible embodiments. Those of skill in the art will appreciate that the system and method may be practiced in other embodiments. First, the particular naming of the components, capitalization of terms, the attributes, data structures, or any other programming or structural aspect is not mandatory or significant, and the mechanisms and/or features may have different names, formats, or protocols. Further, the system may be implemented via a combination of hardware and software, or entirely in hardware elements, or entirely in software elements. Also, the particular division of functionality between the various system components described herein is merely exemplary, and not mandatory; functions performed by a single system component may instead be performed by multiple components, and functions performed by multiple components may instead be performed by a single component.

(127) Reference in the specification to “one embodiment” or to “an embodiment” means that a particular feature, structure, or characteristic, described in connection with the embodiments, is included in at least one embodiment. The appearances of the phrases “in one embodiment” or “in at least one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

(128) Various embodiments may include any number of systems and/or methods for performing the above-described techniques, either singly or in any combination. Another embodiment includes a computer program product comprising a non-transitory computer-readable storage medium and computer program code, encoded on the medium, for causing a processor in a computing device or other electronic device to perform the above-described techniques.

(129) Some portions of the above are presented in terms of algorithms and symbolic representations of operations on data bits within the memory of a computing device. These algorithmic descriptions and representations are the means used by those skilled in the data

processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of steps (instructions) leading to a desired result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical, magnetic or optical signals capable of being stored, transferred, combined, compared and otherwise manipulated. It is convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like. Furthermore, it is also convenient at times, to refer to certain arrangements of steps requiring physical manipulations of physical quantities as modules or code devices, without loss of generality.

(130) It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise, as apparent from the following discussion, it is appreciated that throughout the description, discussions utilizing terms such as “processing” or “computing” or “calculating” or “displaying” or “determining” or the like, refer to the action and processes of a computer system, or similar electronic computing module and/or device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system memories or registers or other such information storage, transmission or display devices.

(131) Certain aspects include process steps and instructions described herein in the form of an algorithm. It should be noted that the process steps and instructions can be embodied in software, firmware and/or hardware, and when embodied in software, can be downloaded to reside on, and be operated from, different platforms used by a variety of operating systems.

(132) The present document also relates to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, or it may comprise a general-purpose computing device selectively activated or reconfigured by a computer program stored in the computing device. Such a computer program may be stored in a computer readable storage medium, such as, but is not limited to, any type of disk, including floppy disks, optical disks, CD-ROMs, DVD-ROMs, magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, flash memory, solid state drives, magnetic or optical cards, application specific integrated circuits (ASICs), or any type of media suitable for storing electronic instructions, and each coupled to a computer system bus. The program and its associated data may also be hosted and run remotely, for example on a server. Further, the computing devices referred to herein may include a single processor or may be architectures employing multiple processor designs for increased computing capability.

(133) The algorithms and displays presented herein are not inherently related to any particular computing device, virtualized system, or other apparatus. Various general-purpose systems may also be used with programs in accordance with the teachings herein, or it may prove convenient to construct a more specialized apparatus to perform the required method steps. The required structure for a variety of these systems will be apparent from the description provided herein. In addition, the system and method are not described with reference to any particular programming language. It will be appreciated that a variety of programming languages may be used to implement the teachings described herein, and any references above to specific languages are provided for disclosure of enablement and best mode.

(134) Accordingly, various embodiments include software, hardware, and/or other elements for controlling a computer system, computing device, or other electronic device, or any combination or plurality thereof. Such an electronic device may include, for example, a processor, an input device such as a keyboard, mouse, touchpad, track pad, joystick, trackball, microphone, and/or any combination thereof, an output device such as a screen, speaker, and/or the like, memory, long-term storage such as magnetic storage, optical storage, and/or the like, and/or network connectivity. Such an electronic device may be portable or non-portable. Examples of electronic devices that may be used for implementing the described system and method include: a desktop computer,

laptop computer, television, smartphone, tablet, music player, audio device, kiosk, set-top box, game system, wearable device, consumer electronic device, server computer, and/or the like. An electronic device may use any operating system such as, for example and without limitation: Linux; Microsoft Windows, available from Microsoft Corporation of Redmond, Washington; Mac OS X, available from Apple Inc. of Cupertino, California; iOS, available from Apple Inc. of Cupertino, California; Android, available from Google, Inc. of Mountain View, California; and/or any other operating system that is adapted for use on the device.

(135) While a limited number of embodiments have been described herein, those skilled in the art, having benefit of the above description, will appreciate that other embodiments may be devised. In addition, it should be noted that the language used in the specification has been principally selected for readability and instructional purposes, and may not have been selected to delineate or circumscribe the subject matter. Accordingly, the disclosure is intended to be illustrative, but not limiting, of scope.

Claims

1. A method for generating a classification model for extracting metadata from a video stream, the method comprising: receiving, by a computing system, at least a portion of a video stream; identifying, by the computing system, one or more card images embedded in one or more video frames of the portion of the video stream; processing, by the computing system, the one or more card images to extract a plurality of character images, each character image comprising a character; generating, by the computing system, a training set of character vectors in a vector space based on the extracted plurality of character images, wherein generating the training set of the character vectors in the vector space based on the extracted plurality of character images includes: formatting, by the computing system, a set of n pixels from the plurality of character images into n -dimensional vectors; reducing, by the computing system, dimensionality of the vector space by selecting a subset of the character vectors in the training set; and generating, by the computing system, a classification model to extract metadata from video streams by training the classification model using at least one of the subset of the character vectors.
2. The method of claim 1, further comprising: normalizing, by the computing system, the plurality of character images to a standard size and/or a standard illumination prior to generating the training set of the character vectors.
3. The method of claim 1, wherein reducing the dimensionality of the vector space by selecting the subset of the character vectors further comprises: performing, by the computing system, a principal component analysis on the training set of the character vectors to determine character vectors that are orthogonal basis vectors; and selecting, by the computing system, the orthogonal basis vectors as the subset of the character vectors.
4. The method of claim 1, wherein reducing the dimensionality of the vector space by selecting the subset of the character vectors further comprises: performing, by the computing system, a principal component analysis on the training set of the character vectors to determine character vectors that are orthogonal basis vectors; and selecting, by the computing system, a limited number of the orthogonal basis vectors as the subset of the character vectors.
5. The method of claim 4, wherein selecting the limited number of the orthogonal basis vectors further comprises: selecting, by the computing system, orthogonal basis vectors that correspond to a largest set of singular values derived from a matrix of the orthogonal basis vectors.
6. The method of claim 1, wherein the video stream is of a sporting event, and wherein the one or more card images include at least one of: a current time within the sporting event; a current phase of the sporting event; a game clock of the sporting event; or a game score of the sporting event.
7. The method of claim 1, wherein the classification model is at least one of a support vector model or a convolutional neural network.

8. A system for generating a classification model for extracting metadata from a video stream, the system comprising: a non-transitory storage medium storing computer program instructions; and at least one processor configured to execute the computer program instructions to perform operations comprising: receiving at least a portion of a video stream; identifying one or more card images embedded in one or more video frames of the portion of the video stream; processing the one or more card images to extract a plurality of character images, each character image comprising a character; generating a training set of character vectors in a vector space based on the extracted plurality of character images, wherein generating the training set of the character vectors in the vector space based on the extracted plurality of character images includes: formatting, by the computing system, a set of n pixels from the plurality of character images into n -dimensional vectors; reducing dimensionality of the vector space by selecting a subset of the character vectors in the training set; and generating a classification model to extract metadata from video streams by training the classification model using at least one of the subset of the character vectors.

9. The system of claim 8, wherein the operations further comprise: normalizing the plurality of character images to a standard size and/or a standard illumination prior to generating the training set of the character vectors.

10. The system of claim 8, wherein reducing the dimensionality of the vector space by selecting the subset of the character vectors further comprises: performing a principal component analysis on the training set of the character vectors to determine character vectors that are orthogonal basis vectors; and selecting the orthogonal basis vectors as the subset of the character vectors.

11. The system of claim 8, wherein reducing the dimensionality of the vector space by selecting the subset of the character vectors further comprises: performing a principal component analysis on the training set of the character vectors to determine character vectors that are orthogonal basis vectors; and selecting a limited number of the orthogonal basis vectors as the subset of the character vectors.

12. The system of claim 11, wherein selecting the limited number of the orthogonal basis vectors further comprises: selecting orthogonal basis vectors that correspond to a largest set of singular values derived from a matrix of the orthogonal basis vectors.

13. The system of claim 8, wherein the video stream is of a sporting event, and wherein the one or more card images include at least one of: a current time within the sporting event; a current phase of the sporting event; a game clock of the sporting event; or a game score of the sporting event.

14. A non-transitory storage medium storing computer program instructions that when executed by at least one processor perform operations comprising: receiving at least a portion of a video stream; identifying one or more card images embedded in one or more video frames of the portion of the video stream; processing the one or more card images to extract a plurality of character images, each character image comprising a character; generating a training set of character vectors in a vector space based on the extracted plurality of character images, wherein generating the training set of the character vectors in the vector space based on the extracted plurality of character images includes: formatting, by the computing system, a set of n pixels from the plurality of character images into n -dimensional vectors; reducing dimensionality of the vector space by selecting a subset of the character vectors in the training set; and generating a classification model to extract metadata from video streams by training the classification model using at least one of the subset of the character vectors.

15. The non-transitory storage medium of claim 14, wherein the operations further comprise: normalizing the plurality of character images to a standard size and/or a standard illumination prior to generating the training set of the character vectors.

16. The non-transitory storage medium of claim 14, wherein reducing the dimensionality of the vector space by selecting the subset of the character vectors further comprises: performing a principal component analysis on the training set of the character vectors to determine character vectors that are orthogonal basis vectors; and selecting the orthogonal basis vectors as the subset of

the character vectors.

17. The non-transitory storage medium of claim 14, wherein reducing the dimensionality of the vector space by selecting the subset of the character vectors further comprises: performing a principal component analysis on the training set of the character vectors to determine character vectors that are orthogonal basis vectors; and selecting a limited number of the orthogonal basis vectors as the subset of the character vectors.
