

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383278
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Chen; Jan-Hung et al.

Left atrial appendage closure device

Abstract

A left atrial appendage closure device may include an expandable framework having a plurality of struts joined at a proximal and distal hub. When the framework is fully constrained in a first position, a first segment of struts extends distally from the distal hub parallel to a central longitudinal axis to a first bend and a second segment of struts extends from the first bend proximally. A first amount of the framework is unconstrained in a second position, where the first segment extends distally from the distal hub parallel to the central longitudinal axis to the first bend, the second segment extends from the first bend proximally and radially outward to a second bend, a third segment of struts extends from the second bend proximally and radially inward to a third bend, and a fourth segment of struts extends from the third bend proximally to within the delivery sheath.

Inventors: Chen; Jan-Hung (St. Paul, MN), Natesan; Harishankar (Shoreview, MN), Chau; Thyna M. (Woodbury, MN)

Applicant: BOSTON SCIENTIFIC SCIMED, INC. (Maple Grove, MN)

Family ID: 1000008751094

Assignee: Boston Scientific Scimed, Inc. (Maple Grove, MN)

Appl. No.: 17/857513

Filed: July 05, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230010024 A1	Jan. 12, 2023

Related U.S. Application Data

us-provisional-application US 63219696 20210708

Publication Classification

Int. Cl.: A61B17/12 (20060101)

U.S. Cl.:

CPC A61B17/12172 (20130101); A61B17/12031 (20130101); A61B17/12122 (20130101); A61B2017/1205 (20130101)

Field of Classification Search

CPC: A61B (17/12109); A61B (17/12113); A61B (17/12118); A61B (17/0057); A61B (2017/00575); A61B (2017/00592); A61B (2017/00632); A61B (17/12172); A61B (17/12031); A61B (17/12122); A61B (2017/1205); A61B (17/12177)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
178283	12/1875	French	N/A	N/A
1967318	12/1933	Monahan	N/A	N/A
3402710	12/1967	Paleschuck	N/A	N/A
3540431	12/1969	Mobin-Uddin	N/A	N/A
3557794	12/1970	Van Patten	N/A	N/A
3638652	12/1971	Kelley	N/A	N/A
3811449	12/1973	Gravlee et al.	N/A	N/A
3844302	12/1973	Klein	N/A	N/A
3874388	12/1974	King et al.	N/A	N/A
4007743	12/1976	Blake	N/A	N/A
4108420	12/1977	West et al.	N/A	N/A
4175545	12/1978	Termanini	N/A	N/A
4309776	12/1981	Berguer	N/A	N/A
4341218	12/1981	Ü	N/A	N/A
4364392	12/1981	Strother et al.	N/A	N/A
4425908	12/1983	Simon	N/A	N/A
4545367	12/1984	Tucci	N/A	N/A
4585000	12/1985	Hershenson	N/A	N/A
4603693	12/1985	Conta et al.	N/A	N/A
4611594	12/1985	Grayhack et al.	N/A	N/A
4619246	12/1985	Molgaard-Nielsen et al.	N/A	N/A
4638803	12/1986	Rand et al.	N/A	N/A
4665906	12/1986	Jervis	N/A	N/A
4681588	12/1986	Ketharanathan et al.	N/A	N/A
4710192	12/1986	Liotta et al.	N/A	N/A
4718417	12/1987	Kittrell et al.	N/A	N/A
4759348	12/1987	Cawood et al.	N/A	N/A
4781177	12/1987	Lebigot	N/A	N/A

4793348	12/1987	Palmaz	N/A	N/A
4827907	12/1988	Tashiro	N/A	N/A
4832055	12/1988	Palestrant	N/A	N/A
4873978	12/1988	Ginsburg	N/A	N/A
4917089	12/1989	Sideris	N/A	N/A
4921484	12/1989	Hillstead	N/A	N/A
4960412	12/1989	Fink	N/A	N/A
4966150	12/1989	Etienne et al.	N/A	N/A
4998972	12/1990	Chin et al.	N/A	N/A
5037810	12/1990	Saliba, Jr.	N/A	N/A
5041090	12/1990	Scheglov et al.	N/A	N/A
5041093	12/1990	Chu	N/A	N/A
5042707	12/1990	Taheri	N/A	N/A
5053009	12/1990	Herzberg	N/A	N/A
5064435	12/1990	Porter	N/A	N/A
5071407	12/1990	Termin et al.	N/A	N/A
5078736	12/1991	Behl	N/A	N/A
5098440	12/1991	Hillstead	N/A	N/A
5108418	12/1991	Lefebvre	N/A	N/A
5108420	12/1991	Marks	N/A	N/A
5108474	12/1991	Riedy et al.	N/A	N/A
5116360	12/1991	Pinchuk et al.	N/A	N/A
5122136	12/1991	Guglielmi et al.	N/A	N/A
5171259	12/1991	Inoue	N/A	N/A
5171383	12/1991	Sagaye et al.	N/A	N/A
5176692	12/1992	Wilk et al.	N/A	N/A
5192301	12/1992	Kamiya et al.	N/A	N/A
5211658	12/1992	Clouse	N/A	N/A
5234458	12/1992	Metais	N/A	N/A
5256146	12/1992	Ensminger et al.	N/A	N/A
5258000	12/1992	Gianturco	N/A	N/A
5258042	12/1992	Mehta	N/A	N/A
5279539	12/1993	Bohan et al.	N/A	N/A
5284488	12/1993	Sideris	N/A	N/A
5304184	12/1993	Hathaway et al.	N/A	N/A
5306234	12/1993	Johnson	N/A	N/A
5312341	12/1993	Turi	N/A	N/A
5329942	12/1993	Gunther et al.	N/A	N/A
5334217	12/1993	Das	N/A	N/A
5344439	12/1993	Otten	N/A	N/A
5350398	12/1993	Pavcnik et al.	N/A	N/A
5350399	12/1993	Erlebacher et al.	N/A	N/A
5353784	12/1993	Nady-Mohamed	N/A	N/A
5366460	12/1993	Eberbach	N/A	N/A
5366504	12/1993	Andersen et al.	N/A	N/A
5370657	12/1993	Irie	N/A	N/A
5375612	12/1993	Cottenceau et al.	N/A	N/A
5397331	12/1994	Himpens et al.	N/A	N/A
5397355	12/1994	Marin et al.	N/A	N/A
5409444	12/1994	Kensey et al.	N/A	N/A

5417699	12/1994	Klein et al.	N/A	N/A
5421832	12/1994	Lefebvre	N/A	N/A
5425744	12/1994	Fagan et al.	N/A	N/A
5427119	12/1994	Swartz et al.	N/A	N/A
5433727	12/1994	Sideris	N/A	N/A
5443454	12/1994	Tanabe et al.	N/A	N/A
5443478	12/1994	Purdy et al.	N/A	N/A
5451235	12/1994	Lock et al.	N/A	N/A
5454365	12/1994	Bonutti	N/A	N/A
5464408	12/1994	Duc	N/A	N/A
5469867	12/1994	Schmitt	N/A	N/A
5490856	12/1995	Person et al.	N/A	N/A
5497774	12/1995	Swartz et al.	N/A	N/A
5499975	12/1995	Cope et al.	N/A	N/A
5499995	12/1995	Teirstein	N/A	N/A
5522790	12/1995	Moll et al.	N/A	N/A
5522822	12/1995	Phelps et al.	N/A	N/A
5522836	12/1995	Palermo	N/A	N/A
5527322	12/1995	Klein et al.	N/A	N/A
5527338	12/1995	Purdy	N/A	N/A
5558093	12/1995	Pomeranz et al.	N/A	N/A
5558652	12/1995	Henke	N/A	N/A
5569204	12/1995	Cramer et al.	N/A	N/A
5591196	12/1996	Marin et al.	N/A	N/A
5614204	12/1996	Cochrum	N/A	N/A
5634936	12/1996	Linden et al.	N/A	N/A
5634942	12/1996	Chevillon et al.	N/A	N/A
5637097	12/1996	Yoon	N/A	N/A
5643282	12/1996	Kieturakis	N/A	N/A
5643292	12/1996	Hart	N/A	N/A
5649953	12/1996	Lefebvre	N/A	N/A
5653690	12/1996	Booth et al.	N/A	N/A
5662671	12/1996	Barbut et al.	N/A	N/A
5669933	12/1996	Simon et al.	N/A	N/A
5681345	12/1996	Euteneuer	N/A	N/A
5681347	12/1996	Cathcart et al.	N/A	N/A
5683411	12/1996	Kavteladze et al.	N/A	N/A
5690671	12/1996	McGurk et al.	N/A	N/A
5693067	12/1996	Purdy	N/A	N/A
5695525	12/1996	Mulhauser et al.	N/A	N/A
5700285	12/1996	Myers et al.	N/A	N/A
5702421	12/1996	Schneidt	N/A	N/A
5704910	12/1997	Humes	N/A	N/A
5709224	12/1997	Behl et al.	N/A	N/A
5709704	12/1997	Nott et al.	N/A	N/A
5709707	12/1997	Lock et al.	N/A	N/A
5722400	12/1997	Ockuly et al.	N/A	N/A
5724975	12/1997	Negus et al.	N/A	N/A
5725512	12/1997	Swartz et al.	N/A	N/A
5725552	12/1997	Kotula et al.	N/A	N/A

5725568	12/1997	Hastings	N/A	N/A
5733294	12/1997	Forber et al.	N/A	N/A
5733302	12/1997	Myler et al.	N/A	N/A
5735290	12/1997	Sterman et al.	N/A	N/A
5749880	12/1997	Banas et al.	N/A	N/A
5749883	12/1997	Halpern	N/A	N/A
5749894	12/1997	Engelson	N/A	N/A
5766219	12/1997	Horton	N/A	N/A
5766246	12/1997	Mulhauser et al.	N/A	N/A
5769816	12/1997	Barbut et al.	N/A	N/A
5776097	12/1997	Massoud	N/A	N/A
5776162	12/1997	Kleshinski	N/A	N/A
5782860	12/1997	Epstein et al.	N/A	N/A
5785679	12/1997	Abolfathi et al.	N/A	N/A
5800454	12/1997	Jacobsen et al.	N/A	N/A
5800457	12/1997	Gelbfish	N/A	N/A
5800512	12/1997	Letnz et al.	N/A	N/A
5807261	12/1997	Benaron et al.	N/A	N/A
5810874	12/1997	Lefebvre	N/A	N/A
5814028	12/1997	Swartz et al.	N/A	N/A
5814029	12/1997	Hassett	N/A	N/A
5814064	12/1997	Daniel	N/A	N/A
5820591	12/1997	Thompson et al.	N/A	N/A
5823198	12/1997	Jones et al.	N/A	N/A
5830228	12/1997	Knapp et al.	N/A	N/A
5833673	12/1997	Ockuly et al.	N/A	N/A
5836913	12/1997	Orth et al.	N/A	N/A
5836968	12/1997	Simon et al.	N/A	N/A
5840027	12/1997	Swartz et al.	N/A	N/A
5843118	12/1997	Sepetka et al.	N/A	N/A
5846260	12/1997	Maahs	N/A	N/A
5846261	12/1997	Kotula et al.	N/A	N/A
5848969	12/1997	Panescu et al.	N/A	N/A
5849005	12/1997	Garrison et al.	N/A	N/A
5851232	12/1997	Lois	N/A	N/A
5853422	12/1997	Huebsch et al.	N/A	N/A
5855597	12/1998	Jayaraman	N/A	N/A
5865791	12/1998	Whayne et al.	N/A	N/A
5865802	12/1998	Yoon et al.	N/A	N/A
5868702	12/1998	Stevens et al.	N/A	N/A
5868708	12/1998	Hart et al.	N/A	N/A
5876367	12/1998	Kaganov et al.	N/A	N/A
5879296	12/1998	Ockuly et al.	N/A	N/A
5879366	12/1998	Shaw et al.	N/A	N/A
5882340	12/1998	Yoon	N/A	N/A
5885258	12/1998	Sachdeva et al.	N/A	N/A
5891558	12/1998	Bell et al.	N/A	N/A
5895399	12/1998	Barbut et al.	N/A	N/A
5902289	12/1998	Swartz et al.	N/A	N/A
5904680	12/1998	Kordis et al.	N/A	N/A

5904703	12/1998	Gilson	N/A	N/A
5906207	12/1998	Shen	N/A	N/A
5910154	12/1998	Tsugita et al.	N/A	N/A
5911734	12/1998	Tsugita et al.	N/A	N/A
5916236	12/1998	Muij Van de Moer et al.	N/A	N/A
5925060	12/1998	Forber	N/A	N/A
5925063	12/1998	Khosravi	N/A	N/A
5925074	12/1998	Gingras et al.	N/A	N/A
5925075	12/1998	Myers et al.	N/A	N/A
5928192	12/1998	Maahs	N/A	N/A
5928260	12/1998	Chin et al.	N/A	N/A
5931818	12/1998	Werp et al.	N/A	N/A
5935145	12/1998	Villar et al.	N/A	N/A
5935147	12/1998	Kensey et al.	N/A	N/A
5935148	12/1998	Villar et al.	N/A	N/A
5941249	12/1998	Maynard	N/A	N/A
5941896	12/1998	Kerr	N/A	N/A
5944738	12/1998	Amplatz et al.	N/A	N/A
5947997	12/1998	Pavcnik et al.	N/A	N/A
5951589	12/1998	Epstein et al.	N/A	N/A
5951599	12/1998	McCrory	N/A	N/A
5954694	12/1998	Sunseri	N/A	N/A
5954767	12/1998	Pajotin et al.	N/A	N/A
5957940	12/1998	Tanner et al.	N/A	N/A
5961545	12/1998	Lentz et al.	N/A	N/A
5976174	12/1998	Ruiz	N/A	N/A
5980514	12/1998	Kupiecki et al.	N/A	N/A
5980555	12/1998	Barbut et al.	N/A	N/A
5989281	12/1998	Barbut et al.	N/A	N/A
5993469	12/1998	McKenzie et al.	N/A	N/A
5993483	12/1998	Gianotti	N/A	N/A
5997557	12/1998	Barbut et al.	N/A	N/A
6004280	12/1998	Buck et al.	N/A	N/A
6004348	12/1998	Banas et al.	N/A	N/A
6007523	12/1998	Mangosong	N/A	N/A
6007557	12/1998	Ambrisco et al.	N/A	N/A
6010517	12/1999	Baccaro	N/A	N/A
6010522	12/1999	Barbut et al.	N/A	N/A
6013093	12/1999	Nott et al.	N/A	N/A
6024751	12/1999	Lovato et al.	N/A	N/A
6024754	12/1999	Engelson	N/A	N/A
6024755	12/1999	Addis	N/A	N/A
6024756	12/1999	Huebsch et al.	N/A	N/A
6027520	12/1999	Tsugita et al.	N/A	N/A
6033420	12/1999	Hahnen	N/A	N/A
6036720	12/1999	Abrams et al.	N/A	N/A
6042598	12/1999	Tsugita et al.	N/A	N/A
6048331	12/1999	Tsugita et al.	N/A	N/A
6051014	12/1999	Jang	N/A	N/A

6051015	12/1999	Maahs	N/A	N/A
6056720	12/1999	Morse	N/A	N/A
6063070	12/1999	Eder	N/A	N/A
6063113	12/1999	Kavteladze et al.	N/A	N/A
6066126	12/1999	Li et al.	N/A	N/A
6068621	12/1999	Balceta et al.	N/A	N/A
6074357	12/1999	Kaganov et al.	N/A	N/A
6076012	12/1999	Swanson et al.	N/A	N/A
6079414	12/1999	Roth	N/A	N/A
6080182	12/1999	Shaw et al.	N/A	N/A
6080183	12/1999	Tsugita et al.	N/A	N/A
6083239	12/1999	Addis	N/A	N/A
6090084	12/1999	Hassett et al.	N/A	N/A
6096052	12/1999	Callister et al.	N/A	N/A
6096053	12/1999	Bates et al.	N/A	N/A
6110243	12/1999	Wnenchak et al.	N/A	N/A
6123715	12/1999	Amplatz	N/A	N/A
6124523	12/1999	Banas et al.	N/A	N/A
6132438	12/1999	Fleischman et al.	N/A	N/A
6135991	12/1999	Muni et al.	N/A	N/A
6136016	12/1999	Barbut et al.	N/A	N/A
6139527	12/1999	Laufer et al.	N/A	N/A
6139573	12/1999	Sogard et al.	N/A	N/A
6152144	12/1999	Lesh et al.	N/A	N/A
6152946	12/1999	Broome et al.	N/A	N/A
6156055	12/1999	Ravenscroft	N/A	N/A
6159195	12/1999	Ha et al.	N/A	N/A
6161543	12/1999	Cox et al.	N/A	N/A
6168615	12/2000	Ken et al.	N/A	N/A
6171329	12/2000	Shaw et al.	N/A	N/A
6179859	12/2000	Bates et al.	N/A	N/A
6193739	12/2000	Chevillon et al.	N/A	N/A
6203531	12/2000	Ockuly et al.	N/A	N/A
6206907	12/2000	Marino et al.	N/A	N/A
6214029	12/2000	Thill et al.	N/A	N/A
6221092	12/2000	Koike et al.	N/A	N/A
6231561	12/2000	Frazier et al.	N/A	N/A
6231589	12/2000	Wessman et al.	N/A	N/A
6235045	12/2000	Barbut et al.	N/A	N/A
6245012	12/2000	Kleshinski	N/A	N/A
6251122	12/2000	Tsukernik	N/A	N/A
6258115	12/2000	Dubrul	N/A	N/A
6267772	12/2000	Mulhauser et al.	N/A	N/A
6267776	12/2000	O'Connell	N/A	N/A
6270490	12/2000	Hahnen	N/A	N/A
6270530	12/2000	Eldridge et al.	N/A	N/A
6270902	12/2000	Tedeschi et al.	N/A	N/A
6277138	12/2000	Levinson et al.	N/A	N/A
6285898	12/2000	Ben-Haim	N/A	N/A
6290674	12/2000	Roue et al.	N/A	N/A

6290708	12/2000	Kugel et al.	N/A	N/A
6312407	12/2000	Zadno-Azizi et al.	N/A	N/A
6319251	12/2000	Tu et al.	N/A	N/A
6328727	12/2000	Frazier et al.	N/A	N/A
6328755	12/2000	Marshall	N/A	N/A
6342062	12/2001	Suon et al.	N/A	N/A
6346116	12/2001	Brooks et al.	N/A	N/A
6346895	12/2001	Lee et al.	N/A	N/A
6361545	12/2001	Macoviak et al.	N/A	N/A
6364895	12/2001	Greenhalgh	N/A	N/A
6368338	12/2001	Kónya et al.	N/A	N/A
6371971	12/2001	Tsugita et al.	N/A	N/A
6375670	12/2001	Greenhalgh	N/A	N/A
6391044	12/2001	Yadav et al.	N/A	N/A
6398803	12/2001	Layne et al.	N/A	N/A
6402746	12/2001	Whayne et al.	N/A	N/A
6402771	12/2001	Palmer et al.	N/A	N/A
6402779	12/2001	Colone et al.	N/A	N/A
6419669	12/2001	Frazier et al.	N/A	N/A
6440152	12/2001	Gainor et al.	N/A	N/A
6443972	12/2001	Bosma et al.	N/A	N/A
6447530	12/2001	Ostrovsky et al.	N/A	N/A
6454775	12/2001	Demarais et al.	N/A	N/A
6458145	12/2001	Ravenscroft et al.	N/A	N/A
6464712	12/2001	Epstein et al.	N/A	N/A
6468291	12/2001	Bates et al.	N/A	N/A
6468301	12/2001	Amplatz et al.	N/A	N/A
6485501	12/2001	Green	N/A	N/A
6488689	12/2001	Kaplan et al.	N/A	N/A
6511496	12/2002	Huter et al.	N/A	N/A
6514280	12/2002	Gilson	N/A	N/A
6517573	12/2002	Pollock et al.	N/A	N/A
6533782	12/2002	Howell et al.	N/A	N/A
6547760	12/2002	Samson et al.	N/A	N/A
6547815	12/2002	Myers	N/A	N/A
6551303	12/2002	Van Tassel et al.	N/A	N/A
6551344	12/2002	Thill	N/A	N/A
6558401	12/2002	Azizi	N/A	N/A
6558405	12/2002	McInnes	N/A	N/A
6558414	12/2002	Layne	N/A	N/A
6562058	12/2002	Seguin et al.	N/A	N/A
6569184	12/2002	Huter	N/A	N/A
6569214	12/2002	Williams et al.	N/A	N/A
6589214	12/2002	McGuckin et al.	N/A	N/A
6589251	12/2002	Yee et al.	N/A	N/A
6599308	12/2002	Amplatz	N/A	N/A
6602271	12/2002	Adams et al.	N/A	N/A
6623508	12/2002	Shaw et al.	N/A	N/A
6641564	12/2002	Kraus	N/A	N/A
6650923	12/2002	Lesh et al.	N/A	N/A

6652555	12/2002	VanTassel et al.	N/A	N/A
6652556	12/2002	VanTassel et al.	N/A	N/A
6666861	12/2002	Grabek	N/A	N/A
6689150	12/2003	Vantassel et al.	N/A	N/A
6699260	12/2003	Dubrul et al.	N/A	N/A
6699276	12/2003	Sogard et al.	N/A	N/A
6702825	12/2003	Frazier et al.	N/A	N/A
6712836	12/2003	Berg et al.	N/A	N/A
6726701	12/2003	Gilson et al.	N/A	N/A
6730108	12/2003	Van Tassel et al.	N/A	N/A
6755812	12/2003	Peterson et al.	N/A	N/A
6827737	12/2003	Hill et al.	N/A	N/A
6837901	12/2004	Rabkin et al.	N/A	N/A
6855153	12/2004	Saadat	N/A	N/A
6911037	12/2004	Gainor et al.	N/A	N/A
6932838	12/2004	Schwartz et al.	N/A	N/A
6942653	12/2004	Quinn	N/A	N/A
6949113	12/2004	Van Tassel et al.	N/A	N/A
6958061	12/2004	Truckai et al.	N/A	N/A
6994092	12/2005	van der Burg et al.	N/A	N/A
7011671	12/2005	Welch	N/A	N/A
7014645	12/2005	Greene, Jr. et al.	N/A	N/A
7037321	12/2005	Sachdeva et al.	N/A	N/A
7044134	12/2005	Khairkhahan et al.	N/A	N/A
7097651	12/2005	Harrison et al.	N/A	N/A
7128073	12/2005	van der Burg et al.	N/A	N/A
7152605	12/2005	Khairkhahan et al.	N/A	N/A
7169164	12/2006	Borillo et al.	N/A	N/A
7179275	12/2006	McGuckin, Jr. et al.	N/A	N/A
7226466	12/2006	Opolski	N/A	N/A
7303526	12/2006	Sharkey et al.	N/A	N/A
7323002	12/2007	Johnson et al.	N/A	N/A
7597704	12/2008	Frazier et al.	N/A	N/A
7678123	12/2009	Chanduszko	N/A	N/A
7695425	12/2009	Schweich et al.	N/A	N/A
7713282	12/2009	Frazier et al.	N/A	N/A
7722641	12/2009	van der Burg et al.	N/A	N/A
7727189	12/2009	VanTassel et al.	N/A	N/A
7735493	12/2009	van der Burg et al.	N/A	N/A
7780694	12/2009	Palmer et al.	N/A	N/A
7799049	12/2009	Ostrovsky et al.	N/A	N/A
7811300	12/2009	Feller, III et al.	N/A	N/A
7811314	12/2009	Fierens et al.	N/A	N/A
7862500	12/2010	Khairkhahan et al.	N/A	N/A
7927365	12/2010	Fierens et al.	N/A	N/A
7972359	12/2010	Kreidler	N/A	N/A
8025495	12/2010	Hardert et al.	N/A	N/A
8043329	12/2010	Khairkhahan et al.	N/A	N/A
8052715	12/2010	Quinn et al.	N/A	N/A
8062282	12/2010	Kolb	N/A	N/A

8080032	12/2010	van der Burg et al.	N/A	N/A
8097015	12/2011	Devellian	N/A	N/A
8100938	12/2011	Figulla et al.	N/A	N/A
8221384	12/2011	Frazier et al.	N/A	N/A
8221445	12/2011	van Tassel et al.	N/A	N/A
8287563	12/2011	Khairkhahan et al.	N/A	N/A
8323309	12/2011	Khairkhahan et al.	N/A	N/A
8388672	12/2012	Khairkhahan et al.	N/A	N/A
8491623	12/2012	Vogel et al.	N/A	N/A
8523897	12/2012	van der Burg et al.	N/A	N/A
8535343	12/2012	van der Burg et al.	N/A	N/A
8562509	12/2012	Bates	N/A	N/A
8663273	12/2013	Khairkhahan et al.	N/A	N/A
8685055	12/2013	VanTassel et al.	N/A	N/A
8728117	12/2013	Janardhan et al.	N/A	N/A
8758389	12/2013	Glimsdale	N/A	N/A
8828051	12/2013	Javois et al.	N/A	N/A
8834519	12/2013	van der Burg et al.	N/A	N/A
8845711	12/2013	Miles et al.	N/A	N/A
9034006	12/2014	Quinn et al.	N/A	N/A
9132000	12/2014	VanTassel et al.	N/A	N/A
9168043	12/2014	van der Burg et al.	N/A	N/A
9211124	12/2014	Campbell et al.	N/A	N/A
9295472	12/2015	Ottma	N/A	N/A
9351716	12/2015	Miles et al.	N/A	N/A
9445895	12/2015	Kreidler	N/A	N/A
9554804	12/2016	Erzberger et al.	N/A	N/A
9554806	12/2016	Larsen et al.	N/A	N/A
9561037	12/2016	Fogarty et al.	N/A	N/A
9561097	12/2016	Kim et al.	N/A	N/A
9592058	12/2016	Erzberger et al.	N/A	N/A
9597088	12/2016	Ottma	N/A	N/A
9629636	12/2016	Fogarty et al.	N/A	N/A
9730701	12/2016	Tischler et al.	N/A	N/A
9750505	12/2016	Miles et al.	N/A	N/A
9763666	12/2016	Wu et al.	N/A	N/A
9795387	12/2016	Miles et al.	N/A	N/A
9808253	12/2016	Li et al.	N/A	N/A
9883936	12/2017	Sutton et al.	N/A	N/A
9913652	12/2017	Bridgeman et al.	N/A	N/A
9943299	12/2017	Khairkhahan et al.	N/A	N/A
9943315	12/2017	Kaplan et al.	N/A	N/A
10071181	12/2017	Penegor et al.	N/A	N/A
10076335	12/2017	Zaver et al.	N/A	N/A
10143458	12/2017	Kreidler	N/A	N/A
10201337	12/2018	Glimsdale	N/A	N/A
10231737	12/2018	Amplatz et al.	N/A	N/A
2001/0000797	12/2000	Mazzocchi	N/A	N/A
2001/0020181	12/2000	Layne	N/A	N/A
2001/0034537	12/2000	Shaw et al.	N/A	N/A

2001/0037141	12/2000	Yee et al.	N/A	N/A
2002/0022860	12/2001	Borillo et al.	N/A	N/A
2002/0035374	12/2001	Borillo et al.	N/A	N/A
2002/0045931	12/2001	Sogard et al.	N/A	N/A
2002/0062133	12/2001	Gilson et al.	N/A	N/A
2002/0082638	12/2001	Porter et al.	N/A	N/A
2002/0082675	12/2001	Myers	N/A	N/A
2002/0099439	12/2001	Schwartz et al.	N/A	N/A
2002/0111647	12/2001	Khairkhahan et al.	N/A	N/A
2002/0138094	12/2001	Borillo et al.	N/A	N/A
2002/0138097	12/2001	Ostrovsky et al.	N/A	N/A
2002/0169475	12/2001	Gainor et al.	N/A	N/A
2002/0177855	12/2001	Greene, Jr. et al.	N/A	N/A
2003/0017775	12/2002	Dong et al.	N/A	N/A
2003/0023262	12/2002	Welch	N/A	N/A
2003/0023266	12/2002	Borillo et al.	N/A	N/A
2003/0057156	12/2002	Peterson et al.	N/A	N/A
2003/0060871	12/2002	Hill et al.	N/A	N/A
2003/0120337	12/2002	Van Tassel et al.	N/A	N/A
2003/0181942	12/2002	Sutton et al.	N/A	N/A
2003/0191526	12/2002	Van Tassel et al.	N/A	N/A
2003/0195555	12/2002	Khairkhahan et al.	N/A	N/A
2003/0204203	12/2002	Khairkhahan et al.	N/A	N/A
2003/0208214	12/2002	Loshakove et al.	N/A	N/A
2003/0220667	12/2002	van der Burg et al.	N/A	N/A
2004/0034366	12/2003	van der Burg et al.	N/A	N/A
2004/0049210	12/2003	VanTassel et al.	N/A	N/A
2004/0093012	12/2003	Cully et al.	N/A	N/A
2004/0098031	12/2003	van der Burg et al.	N/A	N/A
2004/0122467	12/2003	VanTassel et al.	N/A	N/A
2004/0127935	12/2003	VanTassel et al.	N/A	N/A
2004/0158274	12/2003	WasDyke	N/A	N/A
2004/0186486	12/2003	Roue et al.	N/A	N/A
2004/0215230	12/2003	Frazier et al.	N/A	N/A
2004/0220610	12/2003	Kreidler et al.	N/A	N/A
2004/0220682	12/2003	Levine et al.	N/A	N/A
2004/0230222	12/2003	van der Burg et al.	N/A	N/A
2005/0004652	12/2004	van der Burg et al.	N/A	N/A
2005/0015109	12/2004	Lichtenstein	N/A	N/A
2005/0038470	12/2004	van der Burg et al.	N/A	N/A
2005/0049573	12/2004	Van Tassel et al.	N/A	N/A
2005/0070952	12/2004	Devellian	N/A	N/A
2005/0113861	12/2004	Corcoran et al.	N/A	N/A
2005/0125020	12/2004	Meade et al.	N/A	N/A
2005/0177182	12/2004	van der Burg et al.	N/A	N/A
2005/0203568	12/2004	Burg et al.	N/A	N/A
2005/0283186	12/2004	Berrada et al.	N/A	N/A
2005/0288704	12/2004	Cartier et al.	N/A	N/A
2006/0015136	12/2005	Besselink	N/A	N/A
2006/0030877	12/2005	Martinez et al.	N/A	N/A

2006/0052816	12/2005	Bates et al.	N/A	N/A
2006/0100658	12/2005	Obana et al.	N/A	N/A
2006/0155323	12/2005	Porter et al.	N/A	N/A
2007/0066993	12/2006	Kreidler	N/A	N/A
2007/0083227	12/2006	van der Burg et al.	N/A	N/A
2007/0083230	12/2006	Javois	N/A	N/A
2007/0150041	12/2006	Evans et al.	N/A	N/A
2007/0156123	12/2006	Moll et al.	N/A	N/A
2007/0162048	12/2006	Quinn et al.	N/A	N/A
2007/0185471	12/2006	Johnson	N/A	N/A
2008/0275536	12/2007	Zarins et al.	N/A	N/A
2009/0005803	12/2008	Batiste	N/A	N/A
2009/0062841	12/2008	Amplatz et al.	N/A	N/A
2009/0099647	12/2008	Glimsdale et al.	N/A	N/A
2009/0105747	12/2008	Chanduszko et al.	N/A	N/A
2009/0112249	12/2008	Miles et al.	N/A	N/A
2009/0254195	12/2008	Khairkhan et al.	N/A	N/A
2009/0318948	12/2008	Linder et al.	N/A	N/A
2010/0004726	12/2009	Hancock et al.	N/A	N/A
2010/0049238	12/2009	Simpson	N/A	N/A
2010/0106178	12/2009	Obermiller et al.	N/A	N/A
2010/0324585	12/2009	Miles et al.	N/A	N/A
2011/0054515	12/2010	Bridgeman	606/200	A61B 17/12122
2011/0082495	12/2010	Ruiz	N/A	N/A
2011/0098525	12/2010	Kermode et al.	N/A	N/A
2011/0218566	12/2010	van der Burg et al.	N/A	N/A
2011/0301630	12/2010	Hendriksen et al.	N/A	N/A
2012/0029553	12/2011	Quinn et al.	N/A	N/A
2012/0035643	12/2011	Khairkhahan et al.	N/A	N/A
2012/0065662	12/2011	van der Burg et al.	N/A	N/A
2012/0125619	12/2011	Wood et al.	N/A	N/A
2012/0172654	12/2011	Bates	N/A	N/A
2012/0172927	12/2011	Campbell et al.	N/A	N/A
2012/0239077	12/2011	Zaver et al.	N/A	N/A
2012/0239083	12/2011	Kreidler	N/A	N/A
2012/0245619	12/2011	Guest	N/A	N/A
2012/0283585	12/2011	Werneth et al.	N/A	N/A
2012/0283773	12/2011	Van Tassel et al.	N/A	N/A
2012/0323267	12/2011	Ren	N/A	N/A
2013/0006343	12/2012	Kassab et al.	N/A	N/A
2013/0012982	12/2012	Khairkhahan et al.	N/A	N/A
2013/0018413	12/2012	Oral et al.	N/A	N/A
2013/0110154	12/2012	van der Burg et al.	N/A	N/A
2013/0165735	12/2012	Khairkhahan et al.	N/A	N/A
2013/0211492	12/2012	Schneider et al.	N/A	N/A
2013/0331884	12/2012	Van der Burg et al.	N/A	N/A
2014/0005714	12/2013	Quick et al.	N/A	N/A
2014/0018841	12/2013	Peiffer et al.	N/A	N/A
2014/0039536	12/2013	Cully et al.	N/A	N/A

2014/0046360	12/2013	van der Burg et al.	N/A	N/A
2014/0081314	12/2013	Zaver et al.	N/A	N/A
2014/0100596	12/2013	Rudman et al.	N/A	N/A
2014/0135817	12/2013	Tischler et al.	N/A	N/A
2014/0142612	12/2013	Li et al.	N/A	N/A
2014/0148842	12/2013	Khairkhahan et al.	N/A	N/A
2014/0163605	12/2013	VanTassel et al.	N/A	N/A
2014/0188157	12/2013	Clark	N/A	N/A
2014/0214077	12/2013	Glimsdale	N/A	N/A
2014/0296908	12/2013	Ottma et al.	N/A	N/A
2014/0303719	12/2013	Cox et al.	N/A	N/A
2014/0336612	12/2013	Frydlewski et al.	N/A	N/A
2014/0336699	12/2013	van der Burg et al.	N/A	N/A
2015/0005810	12/2014	Center et al.	N/A	N/A
2015/0039021	12/2014	Khairkhahan et al.	N/A	N/A
2015/0080903	12/2014	Dillard et al.	N/A	N/A
2015/0196300	12/2014	Tischler et al.	N/A	N/A
2015/0230909	12/2014	Zaver et al.	N/A	N/A
2015/0238197	12/2014	Quinn et al.	N/A	N/A
2015/0305727	12/2014	Karimov et al.	N/A	N/A
2015/0313604	12/2014	Roue et al.	N/A	N/A
2015/0313605	12/2014	Griffin	N/A	N/A
2015/0327979	12/2014	Quinn et al.	N/A	N/A
2015/0374491	12/2014	Kreidler	N/A	N/A
2016/0015397	12/2015	Figulla et al.	N/A	N/A
2016/0051358	12/2015	Sutton et al.	N/A	N/A
2016/0058539	12/2015	VanTassel et al.	N/A	N/A
2016/0066922	12/2015	Bridgeman et al.	N/A	N/A
2016/0106437	12/2015	van der Burg et al.	N/A	N/A
2016/0192942	12/2015	Strauss et al.	N/A	N/A
2016/0287259	12/2015	Hanson et al.	N/A	N/A
2016/0331382	12/2015	Center et al.	N/A	N/A
2016/0374657	12/2015	Kreidler	N/A	N/A
2017/0007262	12/2016	Amplatz et al.	N/A	N/A
2017/0027552	12/2016	Turkington et al.	N/A	N/A
2017/0042550	12/2016	Chakraborty et al.	N/A	N/A
2017/0056166	12/2016	Ratz et al.	N/A	N/A
2017/0100112	12/2016	van der Burg et al.	N/A	N/A
2017/0119400	12/2016	Amplatz et al.	N/A	N/A
2017/0181751	12/2016	Larsen et al.	N/A	N/A
2017/0224354	12/2016	Tischler et al.	N/A	N/A
2017/0340336	12/2016	Osypka	N/A	N/A
2017/0354421	12/2016	Maguire et al.	N/A	N/A
2018/0064446	12/2017	Figulla et al.	N/A	N/A
2018/0070950	12/2017	Zaver et al.	N/A	N/A
2018/0140412	12/2017	Sutton et al.	N/A	N/A
2018/0140413	12/2017	Quinn et al.	N/A	N/A
2018/0250014	12/2017	Melanson et al.	N/A	N/A
2019/0133563	12/2018	Glimsdale	N/A	N/A
2019/0175185	12/2018	Amplatz et al.	N/A	N/A

2019/0223883	12/2018	Anderson et al.	N/A	N/A
2019/0247053	12/2018	Inouye	N/A	N/A
2021/0059685	12/2020	Groff et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1399571	12/2002	CN	N/A
202143640	12/2011	CN	N/A
104287804	12/2014	CN	N/A
1104352261	12/2014	CN	N/A
106859722	12/2016	CN	N/A
1109464173	12/2018	CN	N/A
10201004476	12/2011	DE	N/A
1523957	12/2004	EP	N/A
1595504	12/2004	EP	N/A
2074953	12/2008	EP	N/A
2481381	12/2011	EP	N/A
2928420	12/2014	EP	N/A
3072461	12/2015	EP	N/A
3372173	12/2017	EP	N/A
3398523	12/2017	EP	N/A
2003532457	12/2002	JP	N/A
2005324019	12/2004	JP	N/A
2007513684	12/2006	JP	N/A
2009160402	12/2008	JP	N/A
2012501793	12/2011	JP	N/A
9313712	12/1992	WO	N/A
9504132	12/1994	WO	N/A
9522359	12/1994	WO	N/A
9601591	12/1995	WO	N/A
9640356	12/1995	WO	N/A
9721402	12/1996	WO	N/A
9726939	12/1996	WO	N/A
9728749	12/1996	WO	N/A
9735522	12/1996	WO	N/A
9802100	12/1997	WO	N/A
9817187	12/1997	WO	N/A
9822026	12/1997	WO	N/A
9823322	12/1997	WO	N/A
9827868	12/1997	WO	N/A
9905977	12/1998	WO	N/A
9907289	12/1998	WO	N/A
9908607	12/1998	WO	N/A
9923976	12/1998	WO	N/A
9925252	12/1998	WO	N/A
9930640	12/1998	WO	N/A
9944510	12/1998	WO	N/A
9959479	12/1998	WO	N/A
0001308	12/1999	WO	N/A

0016705	12/1999	WO	N/A
0027292	12/1999	WO	N/A
0035352	12/1999	WO	N/A
0053120	12/1999	WO	N/A
0067669	12/1999	WO	N/A
0108743	12/2000	WO	N/A
0115629	12/2000	WO	N/A
0121247	12/2000	WO	N/A
0126726	12/2000	WO	N/A
0130266	12/2000	WO	N/A
0130267	12/2000	WO	N/A
0130268	12/2000	WO	N/A
0170119	12/2000	WO	N/A
0215793	12/2001	WO	N/A
0224106	12/2001	WO	N/A
02071977	12/2001	WO	N/A
03007825	12/2002	WO	N/A
03008030	12/2002	WO	N/A
03032818	12/2002	WO	N/A
2004012629	12/2003	WO	N/A
2007044536	12/2006	WO	N/A
2010024801	12/2009	WO	N/A
2010081033	12/2009	WO	N/A
2013060855	12/2012	WO	N/A
2013159065	12/2012	WO	N/A
2014011865	12/2013	WO	N/A
2014018907	12/2013	WO	N/A
2014089129	12/2013	WO	N/A
201406239	12/2013	WO	N/A
2015164836	12/2014	WO	N/A
2016087145	12/2015	WO	N/A
2018017935	12/2017	WO	N/A
2018187732	12/2017	WO	N/A
2019084358	12/2018	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Oct. 25, 2022 for International Application No. PCT/US2022/036092. cited by applicant

International Search Report and Written Opinion dated Aug. 3, 2004 for International Application No. PCT/US2004/008109. cited by applicant

International Search Report and Written Opinion dated Feb. 15, 2000 for International Application No. PCT/US99/26325. cited by applicant

International Search Report dated May 20, 2003 for International Application No. PCT/US02/33808. cited by applicant

Written Opinion dated Nov. 17, 2003 for International Application No. PCT/US/02/33808. cited by applicant

International Search Report and Written Opinion dated Aug. 21, 2018 for International Application No. PCT/US2018/029684. cited by applicant

Cragg et al., "A New Percutaneous Vena Cava Filter," American Journal of Radiology, Sep. 1983, pp. 601-604, vol. 141. cited by applicant

Cragg et al., "Nonsurgical Placement of Arterial Endoprostheses: A New Technique Using Nitinol Wire," *Radiology*, Apr. 1983, pp. 261-263, vol. 147, No. 1. cited by applicant

Lock et al., "Transcatheter Closure of Atrial Septal Defects." *Circulation*, May 1989, pp. 1091-1099, vol. 79, No. 5. cited by applicant

Lock et al., "Transcatheter Umbrella Closure of Congenital Heart Defects," *Circulation*, Mar. 1987, pp. 593-599, vol. 75, No. 3. cited by applicant

Rashkind et al., "Nonsurgical closure of patent ductus arteriosus: clinical application of the Rashkind PDA Occluder System," *Circulation*, Mar. 1987, pp. 583-592, vol. 75, No. 3. cited by applicant

Rosengart et al., "Percutaneous and Minimally Invasive Valve Procedures," *Circulation*, Apr. 1, 2008, pp. 1750-1767, vol. 117. cited by applicant

Ruttenberg, "Nonsurgical Therapy of Cardiac Disorders," *Pediatric Consult*, 1986, Pages not numbered, vol. 5, No. 2. cited by applicant

Sugita et al., "Nonsurgical Implantations of a Vascular Ring Prosthesis Using Thermal Shape Memory Ti/Ni Alloy (Nitinol Wire)," *Trans. Am. Soc. Artif. Intern. Organs*, 1986, pp. 30-34, vol. XXXII. cited by applicant

Wessel et al., "Outpatient Closure of the Patent Ductus Arteriosus," *Circulation*, 1988, pp. 1068-1071, vol. 77, No. 5. cited by applicant

Tung et al., U.S. Appl. No. 61/559,941, filed Nov. 15, 2011. cited by applicant

Yue Yu et al., U.S. Appl. No. 61/557,880, filed Dec. 20, 2011. cited by applicant

Cline, "File: Fish hooks.jpg," Wikipedia foundation , Inc., San Francisco, CA, Jun. 2007; p. 1 of 4; available online at http://en.wikipedia.org/wiki/File:Fish_hooks.jpg; last accessed Oct. 5, 2012. cited by applicant

International Search Report and Written Opinion dated Apr. 22, 2014 for International Application No. PCT/US2013/078454. cited by applicant

Aryana et al., "Incomplete Closure of the Left Atrial Appendage: Implication and Management." *Curr Cardiol Rep.*, 18(9):82, 2016. cited by applicant

Delurgio, "Device-Associated Thrombus and Peri-Device Leak Following Left Atrial Appendage Closure with the Amplatzer Cardiac Plug." *JACC: Cardiovascular Interventions*, 10(4): 400-402, 2017. cited by applicant

University of Minnesota. Atlas of Human Cardiac Anatomy, Left Atrium. Retrieved from <http://www.vhlab.umn.edu/atlas/left-atrium/left-atrial-appendage/index.shtml>. Accessed 2017. Downloaded 2019. cited by applicant

Saw et al., "Incidence and Clinical Impact of Device-Associated Thrombus and Peri-Device Leak following Left Atrial Appendage Closure with the Amplatzer Cardiac Plug." *JACC: Cardiovascular Intervention*. 10(4): 391-399, 2017. cited by applicant

Romero et al., "Left Atrial Appendage Closure Devices," *Clinical Medicine Insights: Cardiology*, vol. 8, pp. 45-52, 2014. cited by applicant

Invitation To Pay Additional Fees And, Where Applicable, Protest Fee, mailed Oct. 13, 2016. cited by applicant

International Search Report and Written Opinion dated Oct. 14, 2019 for International Application No. PCT/US2019/047452. cited by applicant

International Search Report and Written Opinion dated Oct. 27, 2017 for International Application No. PCT/US2017/048150. cited by applicant

International Search Report and Written Opinion dated Jan. 21, 2019 for International Application No. PCT/US2018/051953. cited by applicant

International Search Report and Written Opinion dated Oct. 13, 2016 for International Application No. PCT/US2016/043363. cited by applicant

International Search Report and Written Opinion dated Mar. 17, 2020, for International Application No. PCT/US2019/065243. cited by applicant

International Search Report and Written Opinion dated Sep. 9, 2019 for International Application No. PCT/US2019/033698. cited by applicant
Blackshear et al; "Appendage Obliteration to Reduce Stroke in Cardiac Surgical Patients with Atrial Fibrillation", Ann. Thoracic Surgery, pp. 755-759, 1996. cited by applicant
Lindsay, "Obliteration of the Left Atrial Appendage: A Concept Worth Testing", Ann. Thoracic Surgery, 1996. cited by applicant
Invitation To Pay Additional Fees dated Feb. 22, 2019 for International Application No. PCT/US2018/066163. cited by applicant
International Search Report and Written Opinion dated Oct. 20, 2020 for International Application No. PCT/US2020/042192. cited by applicant
International Search Report and Written Opinion dated Oct. 23, 2020 for International Application No. PCT/US2020/048437. cited by applicant
Watchman FLX™ Left Atrial Appendage Closure Device, Boston Scientific. 5 pages, 2022. cited by applicant

Primary Examiner: David; Shaun L

Assistant Examiner: Geiger; Rachael L

Attorney, Agent or Firm: Seager, Tufte & Wickhem LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of priority of U.S. Provisional Application No. 63/219,696 filed Jul. 8, 2021, the entire disclosure of which is hereby incorporated by reference.

TECHNICAL FIELD

(1) The disclosure relates generally to medical devices and more particularly to medical devices that are adapted for use in percutaneous medical procedures including implantation into the left atrial appendage (LAA) of a heart.

BACKGROUND

(2) The left atrial appendage is a small organ attached to the left atrium of the heart. During normal heart function, as the left atrium constricts and forces blood into the left ventricle, the left atrial appendage constricts and forces blood into the left atrium. The ability of the left atrial appendage to contract assists with improved filling of the left ventricle, thereby playing a role in maintaining cardiac output. However, in patients suffering from atrial fibrillation, the left atrial appendage may not properly contract or empty, causing stagnant blood to pool within its interior, which can lead to the undesirable formation of thrombi within the left atrial appendage.

(3) Thrombi forming in the left atrial appendage may break loose from this area and enter the blood stream. Thrombi that migrate through the blood vessels may eventually plug a smaller vessel downstream and thereby contribute to stroke or heart attack. Clinical studies have shown that the majority of blood clots in patients with atrial fibrillation originate in the left atrial appendage. As a treatment, medical devices have been developed which are deployed to close off the left atrial appendage. Of the known medical devices and methods, each has certain advantages and disadvantages. There is an ongoing need to provide alternative medical devices and introducers as well as alternative methods for manufacturing and using medical devices and introducers.

SUMMARY

(4) In one example, a left atrial appendage closure device may comprise an expandable framework

having a plurality of struts disposed about a central longitudinal axis, the plurality of struts being joined together at a proximal hub and a distal hub. When the expandable framework is fully constrained in a first position by a delivery sheath, a first segment of the plurality of struts extends distally from the distal hub parallel to the central longitudinal axis to a first bend and a second segment of the plurality of struts extends from the first bend proximally. A first amount of the expandable framework is unconstrained by the delivery sheath in a second position. In the second position the first segment of the plurality of struts extends distally from the distal hub parallel to the central longitudinal axis to the first bend, the second segment of the plurality of struts extends from the first bend proximally and radially outward to a second bend, a third segment of the plurality of struts extends from the second bend proximally and radially inward to a third bend, and a fourth segment of the plurality of struts extends from the third bend proximally to within the delivery sheath.

(5) In addition or alternatively to any example disclosed herein, in the second position the first segment and the second segment form an acute angle opening inwardly toward an interior of the expandable framework.

(6) In addition or alternatively to any example disclosed herein, a second amount of the expandable framework greater than the first amount is unconstrained by the delivery sheath in a third position. In the third position the first segment of the plurality of struts extends distally from the distal hub parallel to the central longitudinal axis to the first bend, the second segment of the plurality of struts extends from the first bend radially outward generally perpendicular to the central longitudinal axis to the second bend, the third segment of the plurality of struts extends from the second bend proximally and radially inward to the third bend, and the fourth segment of the plurality of struts extends from the third bend proximally toward the proximal hub disposed within the delivery sheath.

(7) In addition or alternatively to any example disclosed herein, in the third position the second segment and the third segment form an acute angle opening inwardly toward the central longitudinal axis.

(8) In addition or alternatively to any example disclosed herein, in the third position the third segment and the fourth segment form an obtuse angle opening outwardly away from the central longitudinal axis.

(9) In addition or alternatively to any example disclosed herein, a third amount of the expandable framework greater than the second amount is unconstrained by the delivery sheath in a fourth position. In the fourth position the first segment of the plurality of struts extends distally from the distal hub parallel to the central longitudinal axis to the first bend, the second segment of the plurality of struts extends from the first bend distally and radially outward to the second bend, the third segment of the plurality of struts extends from the second bend proximally and radially inward toward the third bend, and the fourth segment of the plurality of struts extends from the third bend proximally toward the proximal hub disposed within the delivery sheath.

(10) In addition or alternatively to any example disclosed herein, in the fourth position the first segment and the second segment form an obtuse angle opening inwardly toward an interior of the expandable framework.

(11) In addition or alternatively to any example disclosed herein, in the fourth position the second segment and the third segment form an acute angle opening inwardly toward the central longitudinal axis.

(12) In addition or alternatively to any example disclosed herein, in the fourth position the third segment and the fourth segment form an obtuse angle opening outwardly away from the central longitudinal axis.

(13) In addition or alternatively to any example disclosed herein, a fourth amount of the expandable framework greater than the third amount is unconstrained by the delivery sheath in a fifth position. In the fifth position the first segment of the plurality of struts extends distally from the distal hub

parallel to the central longitudinal axis to the first bend, the second segment of the plurality of struts extends from the first bend distally and radially outward to the second bend, the third segment of the plurality of struts extends from the second bend proximally to the third bend, and the fourth segment of the plurality of struts extends from the third bend radially inward toward the proximal hub.

(14) In addition or alternatively to any example disclosed herein, in the fifth position the first segment and the second segment form an obtuse angle opening inwardly.

(15) In addition or alternatively to any example disclosed herein, in the fifth position the second segment and the third segment form an acute angle opening inwardly.

(16) In addition or alternatively to any example disclosed herein, in the fifth position the third segment and the fourth segment form an angle of about 90 degrees or less opening inwardly.

(17) In addition or alternatively to any example disclosed herein, the distal hub is disposed proximal of the first bend.

(18) In addition or alternatively to any example disclosed herein, in the second position the distal hub is disposed distal of the second bend.

(19) In addition or alternatively to any example disclosed herein, a left atrial appendage closure device may comprise an expandable framework having a plurality of struts disposed about a central longitudinal axis, the plurality of struts being joined together at a proximal hub and a distal hub. As the expandable framework shifts from fully constrained to fully unconstrained, the expandable framework transitions sequentially through a plurality of positions. In a first position, a first segment of the plurality of struts extends distally from the distal hub parallel to the central longitudinal axis to a first bend and a second segment of the plurality of struts extends from the first bend proximally and generally parallel to the central longitudinal axis. In a second position, the second segment of the plurality of struts, if swept circumferentially around the central longitudinal axis, defines a generally conical shape tapering radially outward in a proximal direction from the first bend toward a second bend.

(20) In addition or alternatively to any example disclosed herein, in the second position, the distal hub is disposed proximal of the first bend and the distal hub is disposed distal of the second bend.

(21) In addition or alternatively to any example disclosed herein, in a third position, the second segment of the plurality of struts, if swept circumferentially around the central longitudinal axis, defines a generally planar shape oriented generally perpendicular to the central longitudinal axis.

(22) In addition or alternatively to any example disclosed herein, in a fourth position, the second segment of the plurality of struts, if swept circumferentially around the central longitudinal axis, defines a generally conical shape tapering radially outward in a distal direction from the first bend toward the second bend.

(23) In addition or alternatively to any example disclosed herein, a left atrial appendage closure device system may comprise a delivery sheath having a lumen extending therein, and a left atrial appendage closure device comprising an expandable framework having a plurality of struts disposed about a central longitudinal axis, the plurality of struts being joined together at a proximal hub and a distal hub. When the expandable framework is disposed within the lumen of the delivery sheath in a first position, a first segment of the plurality of struts extends distally from the distal hub parallel to the central longitudinal axis to a first bend and a second segment of the plurality of struts extends from the first bend proximally. Relative axial translation between the delivery sheath and the expandable framework exposes some of the expandable framework in a second position. In the second position the first segment of the plurality of struts extends distally from the distal hub parallel to the central longitudinal axis to the first bend, the second segment of the plurality of struts extends from the first bend proximally and radially outward to a second bend, a third segment of the plurality of struts extends from the second bend proximally and radially inward to a third bend, and a fourth segment of the plurality of struts extends from the third bend proximally to within the delivery sheath. Relative axial translation between the delivery sheath and the

expandable framework exposes more of the expandable framework in a third position than in the second position. In the third position the first segment of the plurality of struts extends distally from the distal hub parallel to the central longitudinal axis to the first bend, the second segment of the plurality of struts extends from the first bend radially outward generally perpendicular to the central longitudinal axis to the second bend, the third segment of the plurality of struts extends from the second bend proximally and radially inward to the third bend, and the fourth segment of the plurality of struts extends from the third bend proximally toward the proximal hub disposed within the delivery sheath. Relative axial translation between the delivery sheath and the expandable framework exposes more of the expandable framework in a fourth position than in the third position. In the fourth position the first segment of the plurality of struts extends distally from the distal hub parallel to the central longitudinal axis to the first bend, the second segment of the plurality of struts extends from the first bend distally and radially outward to the second bend, the third segment of the plurality of struts extends from the second bend proximally and radially inward toward the third bend, and the fourth segment of the plurality of struts extends from the third bend proximally toward the proximal hub disposed within the delivery sheath. Relative axial translation between the delivery sheath and the expandable framework exposes all of the expandable framework in a fifth position. In the fifth position the first segment of the plurality of struts extends distally from the distal hub parallel to the central longitudinal axis to the first bend, the second segment of the plurality of struts extends from the first bend distally and radially outward to the second bend, the third segment of the plurality of struts extends from the second bend proximally to the third bend, and the fourth segment of the plurality of struts extends from the third bend radially inward toward the proximal hub.

(24) The above summary of some embodiments, aspects, and/or examples is not intended to describe each embodiment or every implementation of the present disclosure. The figures and the detailed description more particularly exemplify aspects of these embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The disclosure may be more completely understood in consideration of the following detailed description in connection with the accompanying drawings, in which:
- (2) FIGS. 1-2 are side views of a left atrial appendage closure device system;
- (3) FIG. 3 illustrates selected aspects of a left atrial appendage closure device;
- (4) FIG. 4 illustrates selected aspects of the left atrial appendage closure device of FIG. 3; and
- (5) FIGS. 5-9 are schematic partial cross-sectional views illustrating selected aspects related to deploying the left atrial appendage closure device of FIGS. 3-4.
- (6) While aspects of the disclosure are amenable to various modifications and alternative forms, examples are shown in the drawings and described herein. It should be understood, however, that the intention is not to limit aspects of the disclosure to the particular embodiments described. On the contrary, the disclosure shall cover all modifications, equivalents, and alternatives falling within the spirit and scope thereof.

DETAILED DESCRIPTION

- (7) The following description should be read with reference to the drawings, which are not necessarily to scale, wherein like reference numerals indicate like elements throughout the several views. The detailed description and drawings are intended to illustrate but not limit the present disclosure. Those skilled in the art will recognize that the various elements described and/or shown may be arranged in various combinations and configurations without departing from the scope of the disclosure. The detailed description and drawings illustrate exemplary aspects of the disclosure. However, in the interest of clarity and ease of understanding, while every feature and/or element

may not be shown in each drawing, the feature(s) and/or element(s) may be understood to be present regardless, unless otherwise specified.

(8) For the following defined terms, these definitions shall be applied, unless a different definition is given in the claims or elsewhere in this specification.

(9) All numeric values are herein assumed to be modified by the term “about,” whether or not explicitly indicated. The term “about”, in the context of numeric values, generally refers to a range of numbers that one of skill in the art would consider equivalent to the recited value (e.g., having the same function or result). In many instances, the term “about” may include numbers that are rounded to the nearest significant figure. Other uses of the term “about” (e.g., in a context other than numeric values) may be assumed to have their ordinary and customary definition(s), as understood from and consistent with the context of the specification, unless otherwise specified.

(10) The recitation of numerical ranges by endpoints includes all numbers within that range, including the endpoints (e.g., 1 to 5 includes 1, 1.5, 2, 2.75, 3, 3.80, 4, and 5).

(11) Although some suitable dimensions, ranges, and/or values pertaining to various components, features and/or specifications are disclosed, one of skill in the art, incited by the present disclosure, would understand desired dimensions, ranges, and/or values may deviate from those expressly disclosed.

(12) As used in this specification and the appended claims, the singular forms “a”, “an”, and “the” include plural referents unless the content clearly dictates otherwise. As used in this specification and the appended claims, the term “or” is generally employed in its sense including “and/or” unless the content clearly dictates otherwise. It is to be noted that in order to facilitate understanding, certain features of the disclosure may be described in the singular, even though those features may be plural or recurring within the disclosed embodiment(s). Each instance of the features may include and/or be encompassed by the singular disclosure(s), unless expressly stated to the contrary. For simplicity and clarity purposes, all elements of the present disclosure are not necessarily shown in each figure or discussed in detail below. However, it will be understood that the following discussion may apply equally to any and/or all of the components for which there are more than one, unless explicitly stated to the contrary. Additionally, not all instances of some elements or features may be shown in each figure for clarity.

(13) Relative terms such as “proximal”, “distal”, “advance”, “retract”, variants thereof, and the like, may be generally considered with respect to the positioning, direction, and/or operation of various elements relative to a user/operator/manipulator of the device, wherein “proximal” and “retract” indicate or refer to closer to or toward the user and “distal” and “advance” indicate or refer to farther from or away from the user. In some instances, the terms “proximal” and “distal” may be arbitrarily assigned in an effort to facilitate understanding of the disclosure, and such instances will be readily apparent to the skilled artisan. Other relative terms, such as “upstream”, “downstream”, “inflow”, and “outflow” refer to a direction of fluid flow within a lumen, such as a body lumen, a blood vessel, or within a device. Still other relative terms, such as “axial”, “circumferential”, “longitudinal”, “lateral”, “radial”, etc. and/or variants thereof generally refer to direction and/or orientation relative to a central longitudinal axis of the disclosed structure or device.

(14) The term “extent” may be understood to mean the greatest measurement of a stated or identified dimension, unless the extent or dimension in question is preceded by or identified as a “minimum”, which may be understood to mean the smallest measurement of the stated or identified dimension. For example, “outer extent” may be understood to mean an outer dimension, “radial extent” may be understood to mean a radial dimension, “longitudinal extent” may be understood to mean a longitudinal dimension, etc. Each instance of an “extent” may be different (e.g., axial, longitudinal, lateral, radial, circumferential, etc.) and will be apparent to the skilled person from the context of the individual usage. Generally, an “extent” may be considered the greatest possible dimension measured according to the intended usage, while a “minimum extent” may be

considered the smallest possible dimension measured according to the intended usage. In some instances, an “extent” may generally be measured orthogonally within a plane and/or cross-section, but may be, as will be apparent from the particular context, measured differently—such as, but not limited to, angularly, radially, circumferentially (e.g., along an arc), etc.

(15) The terms “monolithic” and “unitary” shall generally refer to an element or elements made from or consisting of a single structure or base unit/element. A monolithic and/or unitary element shall exclude structure and/or features made by assembling or otherwise joining multiple discrete structures or elements together.

(16) It is noted that references in the specification to “an embodiment”, “some embodiments”, “other embodiments”, etc., indicate that the embodiment(s) described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it would be within the knowledge of one skilled in the art to effect the particular feature, structure, or characteristic in connection with other embodiments, whether or not explicitly described, unless clearly stated to the contrary. That is, the various individual elements described below, even if not explicitly shown in a particular combination, are nevertheless contemplated as being combinable or arrangeable with each other to form other additional embodiments or to complement and/or enrich the described embodiment(s), as would be understood by one of ordinary skill in the art.

(17) For the purpose of clarity, certain identifying numerical nomenclature (e.g., first, second, third, fourth, etc.) may be used throughout the description and/or claims to name and/or differentiate between various described and/or claimed features. It is to be understood that the numerical nomenclature is not intended to be limiting and is exemplary only. In some embodiments, alterations of and deviations from previously used numerical nomenclature may be made in the interest of brevity and clarity. That is, a feature identified as a “first” element may later be referred to as a “second” element, a “third” element, etc. or may be omitted entirely, and/or a different feature may be referred to as the “first” element. The meaning and/or designation in each instance will be apparent to the skilled practitioner.

(18) The left atrial appendage may be attached to and in fluid communication with a left atrium of a patient's heart. In some patients, the left atrial appendage may have a complex geometry and/or irregular surface area. Those of skill in the art will also recognize that the medical devices and methods disclosed herein may be adapted for various sizes and shapes of the left atrial appendage, as necessary. The left atrial appendage may include a generally longitudinal axis arranged along a depth of a main body of the left atrial appendage. The main body may include a wall and an ostium forming a proximal mouth. In some embodiments, a lateral extent of the ostium and/or the wall may be smaller or less than a depth of the main body along the longitudinal axis, or a depth of the main body may be greater than a lateral extent of the ostium and/or the wall. In some embodiments, the left atrial appendage may include a tail-like element associated with a distal portion of the main body, which element may protrude radially or laterally away from the main body.

(19) The following figures illustrate selected components and/or arrangements of a left atrial appendage closure device, a left atrial appendage closure device system, and/or methods of using the left atrial appendage closure device and/or the left atrial appendage closure device system. It should be noted that in any given figure, some features may not be shown, or may be shown schematically, for simplicity. Additional details regarding some of the components of the implant and/or the system may be illustrated in other figures in greater detail. While discussed in the context of occluding the left atrial appendage, the left atrial appendage closure device and/or the left atrial appendage closure device system may also be used for other interventions and/or percutaneous medical procedures within a patient. Similarly, the devices and methods described herein with respect to percutaneous deployment may be used in other types of surgical procedures,

as appropriate. For example, in some examples, the devices may be used in a non-percutaneous procedure. Devices and methods in accordance with the disclosure may also be adapted and configured for other uses within the anatomy.

(20) FIGS. 1-2 illustrate selected components and/or arrangements of a left atrial appendage closure device system **10** which may be used for occluding a left atrial appendage. It should be noted that in any given figure, some features of the left atrial appendage closure device system **10** may not be shown, or may be shown schematically, for simplicity. Additional details regarding some of the components of the left atrial appendage closure device system **10** may be illustrated in other figures in greater detail.

(21) The left atrial appendage closure device system **10** may include a delivery sheath **40** having a lumen **42** extending from a proximal opening to a distal opening, a core wire **30** slidably disposed within the lumen **42**, and a left atrial appendage closure device **100** for occluding the left atrial appendage. The left atrial appendage closure device **100** may include an expandable framework **110** (e.g., FIG. 3) configured to shift between a fully constrained configuration (e.g., FIG. 1), wherein the left atrial appendage closure device **100** is disposed within the lumen **42** proximate the distal opening in the delivery configuration, and a fully unconstrained configuration (e.g., FIG. 2), wherein the left atrial appendage closure device **100** and/or the expandable framework **110** is configured to shift between the fully constrained configuration and the fully unconstrained configuration as the left atrial appendage closure device **100** is translated relative to the delivery sheath **40**. In at least some embodiments, the expandable framework **110** may be self-biased toward the fully unconstrained configuration.

(22) The left atrial appendage closure device **100** may be disposed at and/or releasably securable to a distal portion of the core wire **30**. The core wire **30** may be slidably and/or rotatably disposed within the lumen **42** of the delivery sheath **40**. In some embodiments, a proximal end of the core wire **30** may extend proximally of a proximal end of the delivery sheath **40** and/or the proximal opening of the lumen **42** for manual manipulation by a clinician or practitioner. In some embodiments, the left atrial appendage closure device **100** may be removably attached, joined, secured, or otherwise connected to a distal end of the core wire **30**. The core wire **30** may be configured to and/or may be capable of axially translating the left atrial appendage closure device **100** relative to the delivery sheath **40**. In one example, the core wire **30** may be advanced distally while the delivery sheath **40** is held in a constant position. In another example, the core wire **30** may be advanced distally while the delivery sheath **40** is retracted proximally. In yet another example, the core wire **30** may be held in a constant position while the delivery sheath **40** is retracted proximally relative to the core wire **30** and/or the left atrial appendage closure device **100**. Other configurations are also contemplated. The delivery sheath **40** and/or the core wire **30** may have a selected level of axial stiffness and/or pushability characteristics while also having a selected level of flexibility to permit navigation through the patient's vasculature.

(23) Some suitable, but non-limiting, examples of materials for the left atrial appendage closure device system **10**, the core wire **30**, the delivery sheath **40**, and/or the left atrial appendage closure device **100**, etc. are discussed below. It is contemplated that any exemplary left atrial appendage closure device disclosed herein may be used in accordance with and/or be associated with the example left atrial appendage closure device system **10** described above.

(24) The left atrial appendage closure device **100** may comprise an expandable framework **110** configured to shift axially and/or radially along a central longitudinal axis between the fully constrained configuration and the fully unconstrained configuration. In the fully constrained configuration, the expandable framework **110** may be axially elongated and/or radially compressed. In the fully unconstrained configuration, the expandable framework **110** may be axially shortened and/or radially expanded.

(25) As seen in FIG. 3, which illustrates selected aspects of the left atrial appendage closure device **100** in the fully unconstrained configuration, the expandable framework **110** may have a plurality

of struts disposed about the central longitudinal axis. In some embodiments, the plurality of struts may define a plurality of cells. In some embodiments, the plurality of cells may be a plurality of closed cells. In some embodiments, the plurality of cells may be a plurality of open cells. In some embodiments, the plurality of cells may include a plurality of open cells and a plurality of closed cells in various combinations and/or arrangements.

(26) The expandable framework **110** may include a proximal hub **112** and a distal hub **114**. In some embodiments, the proximal hub **112** and/or the distal hub **114** may be centered on and/or coaxial with the longitudinal axis. The plurality of struts may be joined together at and/or fixedly attached to the proximal hub **112** and/or the distal hub **114**. The proximal hub **112** may be configured to releasably connect, secure, and/or attach the left atrial appendage closure device **100** and/or the expandable framework **110** to the core wire **30**. In some embodiments, the proximal hub **112** may include internal threads configured to rotatably and/or threadably engage an externally threaded distal end of the core wire **30**. Other configurations for releasably securing the left atrial appendage closure device **100** to the core wire **30** are also contemplated. As noted herein, some features are not shown in every figure to improve clarity.

(27) The expandable framework **110** and/or the plurality of struts may be formed and/or cut from a tubular member. In some embodiments, the expandable framework **110** and/or the plurality of struts may be integrally formed and/or cut from a unitary member. In some embodiments, the expandable framework **110** and/or the plurality of struts may be integrally formed and/or cut from a unitary tubular member and subsequently formed and/or heat set to a desired shape in the fully unconstrained configuration. In some embodiments, the expandable framework **110** and/or the plurality of struts may be integrally formed and/or cut from a unitary flat member or sheet, and then rolled or formed into a tubular structure and subsequently formed and/or heat set to the desired shape in the fully unconstrained configuration. Some exemplary means and/or methods of making and/or forming the expandable framework **110** and/or the plurality of struts include laser cutting, machining, punching, stamping, electro discharge machining (EDM), chemical dissolution, etc. Other means and/or methods are also contemplated.

(28) As would be understood by the skilled person, anatomical features may vary in size and/or shape. In some embodiments, the left atrial appendage may have an irregular (e.g., elongated and/or oblong) cross-sectional shape. In some embodiments, the expandable framework **110** may be compliant and substantially conform to and/or be in sealing engagement with the shape and/or geometry of a lateral wall of a left atrial appendage when deployed and/or expanded therein. In some embodiments, the left atrial appendage closure device **100** may expand to a size, extent, or shape less than or different from the fully unconstrained configuration, as determined by the surrounding tissue and/or lateral wall of the left atrial appendage. In some embodiments, the expandable framework **110** may be configured to shape and/or stretch the tissue of the left atrial appendage such that the lateral wall of the left atrial appendage substantially conforms to an outer shape of the expandable framework **110**. Other configurations are also contemplated.

(29) In some embodiments, the expandable framework **110** may include at least one anchoring member **116** extending radially outward therefrom in the fully unconstrained configuration. In some embodiments, the expandable framework **110** may include at least one anchoring member **116** extending radially outward from the expandable framework **110**. In some embodiments, the expandable framework **110** may include at least one anchoring member **116** extending radially outward from the expandable framework **110** proximate a proximal shoulder of the expandable framework **110**. In some embodiments, the expandable framework **110** may include at least one anchoring member **116** extending radially outward from the expandable framework **110** proximate a midsection of the expandable framework **110**. In some embodiments, the at least one anchoring member **116** may be configured to engage with the lateral wall of the main body of the left atrial appendage. In some embodiments, the at least one anchoring member **116** may be formed as J-shaped hooks having a free end extending in and/or directed toward a proximal direction with

respect to the central longitudinal axis of the left atrial appendage closure device **100** and/or the expandable framework **110**. Other configurations are also contemplated.

(30) In some embodiments, the left atrial appendage closure device **100** may optionally include the occlusive element **120** connected to, disposed on, disposed over, disposed about, and/or disposed radially outward of at least a portion of the expandable framework **110** and/or the plurality of struts, as seen in FIG. 4. In some embodiments, the occlusive element **120** may be attached to the proximal hub **112** and/or may be attached to the expandable framework at the proximal hub **112**. In some embodiments, the occlusive element **120** may extend radially outward from and/or may extend distally from the proximal hub **112**. In some embodiments, the occlusive element **120** may be attached and/or secured to the expandable framework **110** at a plurality of discrete locations. In some embodiments, one of, some of, and/or all of the at least one anchoring member **116** may extend through an occlusive element **120**, where present.

(31) In some embodiments, the occlusive element **120** may include a membrane, a fabric, a mesh, a tissue element, or another suitable construction. In some embodiments, the occlusive element **120** may be porous. In some embodiments, the occlusive element **120** may be non-porous. In some embodiments, the occlusive element **120** may be permeable to selected gases and/or fluids. In some embodiments, the occlusive element **120** may be substantially impermeable to selected gases and/or fluids, such as blood, water, etc. In some embodiments, the occlusive element **120** may be designed, sized, and/or configured to prevent thrombus and/or embolic material from passing out of the left atrial appendage into the left atrium and/or the patient's bloodstream. In some embodiments, the occlusive element **120** may be configured to promote endothelization after implantation, thereby effectively removing the target site (e.g., the left atrial appendage, etc.) from the patient's circulatory system. Some suitable, but non-limiting, examples of materials for the occlusive element **120** are discussed below.

(32) FIGS. 5-9 schematically illustrate selected aspects of the left atrial appendage closure device **100** and/or the left atrial appendage closure device system **10** during deployment of the left atrial appendage closure device **100**. For clarity and ease of understanding, some elements of the left atrial appendage closure device **100** are not shown but shall be understood to be present in accordance and/or consistent with other figures and/or description of the disclosure. FIGS. 5-8 illustrate the left atrial appendage closure device **100** in partial cross-section. FIG. 9 illustrates the left atrial appendage closure device **100** using broken lines to show hidden features as may be understood from other figures. The occlusive element **120** is not shown in FIG. 9. It may be seen in FIGS. 5-9 that as the expandable framework **110** of the left atrial appendage closure device **100** shifts from fully constrained to fully unconstrained, the expandable framework **110** may transition sequentially through a plurality of positions. In some embodiments, the plurality of positions may include a first position, a second position, a third position, a fourth position, and/or a fifth position as described herein. In some embodiments, the plurality of positions may include additional and/or other positions.

(33) Returning now to FIG. 5, in some embodiments, the expandable framework **110** may be fully constrained in a first position by the delivery sheath **40**. In some embodiments, the expandable framework **110** may be disposed within the lumen **42** of the delivery sheath **40** in the first position. In some embodiments, in the first position a first segment **130** of the plurality of struts of the expandable framework **110** may extend distally from the distal hub **114** substantially parallel to the central longitudinal axis to a first bend **132** and a second segment **140** of the plurality of struts of the expandable framework **110** may extend from the first bend **132** proximally. In some embodiments, in the first position the second segment **140** may extend from the first bend **132** proximally and generally parallel to the central longitudinal axis. In the first position, the distal hub **114** may be disposed proximal of the first bend **132**. In some embodiments, the first segment **130** may be secured to the distal hub **114**. In some embodiments, the first segment **130** may be fixedly attached to the distal hub **114**. For example, the first segment **130** may be welded, adhesively

bonded, etc. to the distal hub **114**. Other configurations are also contemplated.

(34) In some embodiments, relative axial translation between the delivery sheath **40** and the expandable framework **110** may expose some of the expandable framework **110** and/or the plurality of struts in a second position, as seen in FIG. **6**. In some embodiments, a first amount of the expandable framework **110** and/or the plurality of struts may be exposed from and/or unconstrained by the delivery sheath **40** in the second position. In some embodiments, the first amount may be less than about 55% of an axial length, a volume, a weight, and/or a surface area of the expandable framework **110** and/or the plurality of struts. In some embodiments, the first amount may be about 15% to about 55% of the axial length, the volume, the weight, and/or the surface area of the expandable framework **110** and/or the plurality of struts. Other configurations and/or ranges are also contemplated. In some embodiments, in the second position, the expandable framework **110** may have a maximum radial extent of about 6 millimeters (mm) to about 10 mm. In some embodiments, in the second position, the expandable framework **110** may have a maximum radial extent of about 8 mm. In some embodiments, in the second position, the maximum radial extent of the expandable framework **110** may be about twice or about 200% of a maximum outer extent of a distal end of the delivery sheath **40**. Other configurations and/or sizes are also contemplated.

(35) In some embodiments, in the second position the first segment **130** of the plurality of struts of the expandable framework **110** may extend distally from the distal hub **114** substantially parallel to the central longitudinal axis to the first bend **132**. In the second position, the second segment **140** of the plurality of struts of the expandable framework **110** may extend from the first bend **132** proximally and radially outward toward and/or to a second bend **142**. In the second position, a third segment **150** of the plurality of struts of the expandable framework **110** may extend from the second bend **142** proximally and radially inward toward and/or to a third bend **152**. In some embodiments, in the second position, a fourth segment **160** of the plurality of struts of the expandable framework **110** may extend from the third bend **152** proximally to within the lumen **42** of the delivery sheath **40**. In some embodiments, in the second position, the fourth segment **160** of the plurality of struts of the expandable framework **110** may extend from the third bend **152** proximally toward the proximal hub **112** disposed within the lumen **42** of the delivery sheath **40**.

(36) In some embodiments, in the second position, the distal hub **114** is disposed proximal of the first bend **132**. In some embodiments, in the second position, the distal hub **114** may be disposed distal of the second bend **142**. For example, in the second position, the distal hub **114** may be positioned distal of a plane extending through, including at least a portion of, and/or tangent to the second bend **142** and oriented perpendicular to the central longitudinal axis. In some embodiments, in the second position, the first segment **130** of the plurality of struts and the second segment **140** of the plurality of struts may form and/or intersect to form an acute angle opening inwardly toward an interior of the expandable framework **110**. In some embodiments, in the second position, the first segment **130** of the plurality of struts and the second segment **140** of the plurality of struts may form and/or intersect to form an acute angle opening radially outwardly from the central longitudinal axis. In some embodiments, in the second position, the second segment **140** of the plurality of struts of the expandable framework **110**, if swept circumferentially around the central longitudinal axis, may define a generally conical shape tapering radially outward in a proximal direction from the first bend **132** toward the second bend **142**.

(37) In some embodiments, relative axial translation between the delivery sheath **40** and the expandable framework **110** may expose more of the expandable framework **110** and/or the plurality of struts in a third position than in the second position, as seen in FIG. **7**. In some embodiments, a second amount of the expandable framework **110** and/or the plurality of struts greater than the first amount may be exposed from and/or unconstrained by the delivery sheath **40** in the third position. In some embodiments, the second amount may be less than about 75% of the axial length, the volume, the weight, and/or the surface area of the expandable framework **110** and/or the plurality of struts. In some embodiments, the second amount may be about 40% to about 75% of the axial

length, the volume, the weight, and/or the surface area of the expandable framework **110** and/or the plurality of struts. Other configurations and/or ranges are also contemplated.

(38) In some embodiments, in the third position the first segment **130** of the plurality of struts of the expandable framework **110** may extend distally from the distal hub **114** substantially parallel to the central longitudinal axis to the first bend **132**. In the third position, the second segment **140** of the plurality of struts of the expandable framework **110** may extend from the first bend **132** radially outward generally perpendicular to the central longitudinal axis toward and/or to the second bend **142**. In the third position, the third segment **150** of the plurality of struts of the expandable framework **110** may extend from the second bend **142** proximally and radially inward toward and/or to the third bend **152**. In some embodiments, in the third position, the fourth segment **160** of the plurality of struts of the expandable framework **110** may extend from the third bend **152** proximally to within the lumen **42** of the delivery sheath **40**. In some embodiments, in the third position, the fourth segment **160** of the plurality of struts of the expandable framework **110** may extend from the third bend **152** proximally toward the proximal hub **112** disposed within the lumen **42** of the delivery sheath **40**.

(39) In some embodiments, in the third position, the distal hub **114** is disposed proximal of the first bend **132**. In some embodiments, in the third position, the first segment **130** of the plurality of struts and the second segment **140** of the plurality of struts may form and/or intersect to form a generally right angle opening toward the interior of the expandable framework **110**. In some embodiments, in the third position, the first segment **130** of the plurality of struts and the second segment **140** of the plurality of struts may form and/or intersect to form a generally right angle opening radially outwardly away from the central longitudinal axis. In some embodiments, in the third position, the second segment **140** of the plurality of struts and the third segment **150** of the plurality of struts may form and/or intersect to form an acute angle opening radially inwardly toward the interior of the expandable framework **110**. In some embodiments, in the third position, the second segment **140** of the plurality of struts and the third segment **150** of the plurality of struts may form and/or intersect to form an acute angle opening radially inwardly toward the central longitudinal axis. In some embodiments, in the third position, the third segment **150** of the plurality of struts and the fourth segment **160** of the plurality of struts may form and/or intersect to form an obtuse angle opening radially outwardly away from the central longitudinal axis. In some embodiments, in the third position, the second segment **140** of the plurality of struts of the expandable framework **110**, if swept circumferentially around the central longitudinal axis, may define a generally planar shape oriented generally perpendicular to the central longitudinal axis.

(40) In some embodiments, relative axial translation between the delivery sheath **40** and the expandable framework **110** may expose more of the expandable framework **110** and/or the plurality of struts in a fourth position than in the third position, as seen in FIG. **8**. In some embodiments, a third amount of the expandable framework **110** and/or the plurality of struts greater than the second amount may be exposed from and/or unconstrained by the delivery sheath **40** in the fourth position. In some embodiments, the third amount may be less than about 95% of the axial length, the volume, the weight, and/or the surface area of the expandable framework **110** and/or the plurality of struts. In some embodiments, the third amount may be about 60% to about 95% of the axial length, the volume, the weight, and/or the surface area of the expandable framework **110** and/or the plurality of struts. Other configurations and/or ranges are also contemplated.

(41) In some embodiments, in the fourth position the first segment **130** of the plurality of struts of the expandable framework **110** may extend distally from the distal hub **114** substantially parallel to the central longitudinal axis to the first bend **132**. In the fourth position, the second segment **140** of the plurality of struts of the expandable framework **110** may extend from the first bend **132** distally and radially outward toward and/or to the second bend **142**. In the fourth position, the third segment **150** of the plurality of struts of the expandable framework **110** may extend from the second bend **142** proximally and radially inward toward and/or to the third bend **152**. In some

embodiments, in the fourth position, the fourth segment **160** of the plurality of struts of the expandable framework **110** may extend from the third bend **152** proximally toward the proximal hub **112** disposed within the lumen **42** of the delivery sheath **40**.

(42) In some embodiments, in the fourth position, the distal hub **114** is disposed proximal of the first bend **132**. In some embodiments, in the fourth position, the first segment **130** of the plurality of struts and the second segment **140** of the plurality of struts may form and/or intersect to form an obtuse angle opening inwardly toward the interior of the expandable framework **110**. In some embodiments, in the fourth position, the second segment **140** of the plurality of struts and the third segment **150** of the plurality of struts may form and/or intersect to form an acute angle opening radially inwardly toward the central longitudinal axis. In some embodiments, in the fourth position, the third segment **150** of the plurality of struts and the fourth segment **160** of the plurality of struts may form and/or intersect to form an obtuse angle opening radially outwardly away from the central longitudinal axis. In some embodiments, in the fourth position, the second segment **140** of the plurality of struts of the expandable framework **110**, if swept circumferentially around the central longitudinal axis, may define a generally conical shape tapering radially outward in a distal direction from the first bend **132** toward the second bend **142**.

(43) In some embodiments, relative axial translation between the delivery sheath **40** and the expandable framework **110** may expose substantially all of the expandable framework **110** and/or the plurality of struts in a fifth position, as seen in FIG. 9. In some embodiments, a fourth amount of the expandable framework **110** and/or the plurality of struts greater than the third amount may be exposed from and/or unconstrained by the delivery sheath **40** in the fifth position. In some embodiments, the fourth amount may be more than about 95% of the axial length, the volume, the weight, and/or the surface area of the expandable framework **110** and/or the plurality of struts. In some embodiments, the fourth amount may be about 100% of the axial length, the volume, the weight, and/or the surface area of the expandable framework **110** and/or the plurality of struts. Other configurations and/or ranges are also contemplated.

(44) In some embodiments, the expandable framework **110** may be in the fully unconstrained configuration in the fifth position. In some embodiments, in the fully unconstrained configuration, the expandable framework may have a maximum radial extent of about 16 millimeters (mm) to about 40 mm. In some embodiments, in the fully unconstrained configuration, the expandable framework may have a maximum radial extent of about 16 mm. In some embodiments, in the fully unconstrained configuration, the expandable framework may have a maximum radial extent of about 20 mm. In some embodiments, in the fully unconstrained configuration, the expandable framework may have a maximum radial extent of about 25 mm. In some embodiments, in the fully unconstrained configuration, the expandable framework may have a maximum radial extent of about 30 mm. In some embodiments, in the fully unconstrained configuration, the expandable framework may have a maximum radial extent of about 35 mm. In some embodiments, in the fully unconstrained configuration, the expandable framework may have a maximum radial extent of about 40 mm. Other configurations and/or sizes are also contemplated.

(45) In some embodiments, in the fifth position the first segment **130** of the plurality of struts of the expandable framework **110** may extend distally from the distal hub **114** substantially parallel to the central longitudinal axis to the first bend **132**. In the fifth position, the second segment **140** of the plurality of struts of the expandable framework **110** may extend from the first bend **132** distally and radially outward toward and/or to the second bend **142**. In the fifth position, the third segment **150** of the plurality of struts of the expandable framework **110** may extend from the second bend **142** proximally and toward and/or to the third bend **152**. In some embodiments, in the fifth position, the third segment **150** of the plurality of struts of the expandable framework **110** may extend from the second bend **142** proximally generally parallel to the central longitudinal axis toward and/or to the third bend **152**. In some embodiments, in the fifth position, the fourth segment **160** of the plurality of struts of the expandable framework **110** may extend from the third bend **152** radially inward

toward and/or to the proximal hub **112**.

(46) In some embodiments, in the fifth position, the distal hub **114** is disposed proximal of the first bend **132**. In some embodiments, in the fifth position, the first segment **130** of the plurality of struts and the second segment **140** of the plurality of struts may form and/or intersect to form an obtuse angle opening inwardly toward the interior of the expandable framework **110**. In some embodiments, in the fifth position, the second segment **140** of the plurality of struts and the third segment **150** of the plurality of struts may form and/or intersect to form an acute angle opening radially inwardly toward the central longitudinal axis. In some embodiments, in the fifth position, the third segment **150** of the plurality of struts and the fourth segment **160** of the plurality of struts may form and/or intersect to form an angle of about 90 degrees or less opening radially inwardly toward the interior of the expandable framework **110**. In some embodiments, in the fifth position, the third segment **150** of the plurality of struts and the fourth segment **160** of the plurality of struts may form and/or intersect to form an angle of about 90 degrees or less opening radially inwardly toward the central longitudinal axis.

(47) A method for occluding the left atrial appendage may comprise advancing the left atrial appendage closure device **100** into the left atrial appendage of the patient's heart. For example, the left atrial appendage closure device **100** may be advanced to the left atrial appendage within the lumen **42** of the delivery sheath **40** in the fully constrained configuration. The method may include deploying the expandable framework **110** from the delivery sheath **40** within the left atrial appendage. The method may further include expanding and/or shifting the expandable framework **110** from the fully constrained configuration toward the fully unconstrained configuration within the left atrial appendage.

(48) As the expandable framework **110** shifts from fully constrained to fully unconstrained, the expandable framework **110** may transition sequentially through a plurality of positions, as described herein. In some embodiments, in the second position, the expandable framework **110** may be moved and/or navigated within the patient's heart, the left atrium, and/or the left atrial appendage. In the second position, the expandable framework **110** may form a generally rounded atraumatic shape. In some embodiments, in the second position, the maximum radial extent of the expandable framework **110** may be about twice or about 200% of a maximum outer extent of a distal end of the delivery sheath **40**. In some embodiments, in the second position, the maximum radial extent of the expandable framework **110** may be about 8 millimeters. Other configurations and/or sizes are also contemplated. In some embodiments, a physician may use the generally rounded atraumatic shape as a navigational tool within the patient's anatomy.

(49) In and/or near the fully unconstrained configuration (e.g., the fifth position), the expandable framework **110** may be urged into contact with, engaged with, and/or anchored to the lateral wall of the main body of the left atrial appendage. In some embodiments, the expandable framework **110** may not fully achieve the fully unconstrained configuration (e.g., the fifth position) due to contact with the wall(s) of the left atrial appendage. However, the inverted shape of the distal portion of the expandable framework **110** (e.g., the first segment **130**, the first bend **132**, the second segment **140**, and the second bend **142**) may prevent the expandable framework **110** from elongating distally, which may compromise locating the left atrial appendage closure device **100** and/or the expandable framework **110** within the left atrial appendage, sealing of the left atrial appendage closure device **100** and/or the expandable framework **110** with respect to the left atrial appendage, and/or anchoring of the left atrial appendage closure device **100** and/or the expandable framework **110** within the left atrial appendage. Instead, compressive force applied against the third segment **150** and/or the second bend **142** may urge the distal hub **114** proximally toward the proximal hub **112**. As such, the final shape of the left atrial appendage closure device **100** and/or the expandable framework **110** may be more predictable and locating and anchoring of the left atrial appendage closure device **100** and/or the expandable framework **110** within the left atrial appendage may be improved.

(50) In at least some embodiments, the left atrial appendage closure device **100** and/or the expandable framework **110** may span across the ostium of the left atrial appendage. In some embodiments, the left atrial appendage closure device **100** and/or the expandable framework **110** may span completely across the ostium of the left atrial appendage, thereby effectively removing the left atrial appendage from the circulatory system of the patient.

(51) When satisfied with the positioning of the left atrial appendage closure device **100** within the left atrial appendage, the core wire **30** may be disconnected from the left atrial appendage closure device **100**, thereby leaving the left atrial appendage closure device **100** disposed at and/or in the left atrial appendage. In some embodiments, disconnecting the core wire **30** from the left atrial appendage closure device **100** may include rotating the externally threaded distal end of the core wire **30** relative to the left atrial appendage closure device **100** and/or the proximal hub **112** to disengage the core wire **30** from the left atrial appendage closure device **100**.

(52) In some embodiments, the delivery sheath **40** and/or the core wire **30** may include a keying structure configured to prevent rotation of the core wire **30** relative to the proximal hub **112**. In such embodiments, the keying structure is disengaged prior to rotating the core wire **30** relative to the left atrial appendage closure device **100** and/or the proximal hub **112**. When the keying structure is engaged, rotation of the core wire **30** may be transmitted to left atrial appendage closure device **100** and/or the expandable framework **110**. In some embodiments, rotation of the left atrial appendage closure device **100** and/or the expandable framework **110** may facilitate positioning and/or orientation of the left atrial appendage closure device **100** and/or the expandable framework **110** relative to the left atrial appendage, for example, with respect to an asymmetrical and/or irregular ostium and/or left atrial appendage. Other configurations, purposes, and/or results are also contemplated.

(53) The materials that can be used for the various components of the system (and/or other elements disclosed herein) and the various components thereof disclosed herein may include those commonly associated with medical devices and/or systems. For simplicity purposes, the following discussion refers to the system. However, this is not intended to limit the devices and methods described herein, as the discussion may be applied to other elements, members, components, or devices disclosed herein, such as, but not limited to, the left atrial appendage closure device, the delivery sheath, the core wire, the expandable framework, the occlusive element, etc. and/or elements or components thereof.

(54) In some embodiments, the system and/or components thereof may be made from a metal, metal alloy, polymer (some examples of which are disclosed below), a metal-polymer composite, ceramics, combinations thereof, and the like, or other suitable material.

(55) Some examples of suitable metals and metal alloys include stainless steel, such as 444V, 444L, and 314LV stainless steel; mild steel; nickel-titanium alloy such as linear-elastic and/or super-elastic nitinol; other nickel alloys such as nickel-chromium-molybdenum alloys (e.g., UNS: N06625 such as INCONEL® 625, UNS: N06022 such as HASTELLOY® C-22®, UNS: N10276 such as HASTELLOY® C276®, other HASTELLOY® alloys, and the like), nickel-copper alloys (e.g., UNS: N04400 such as MONEL® 400, NICKELVAC® 400, NICORROS® 400, and the like), nickel-cobalt-chromium-molybdenum alloys (e.g., UNS: R44035 such as MP35-N® and the like), nickel-molybdenum alloys (e.g., UNS: N10665 such as HASTELLOY® ALLOY B2®), other nickel-chromium alloys, other nickel-molybdenum alloys, other nickel-cobalt alloys, other nickel-iron alloys, other nickel-copper alloys, other nickel-tungsten or tungsten alloys, and the like; cobalt-chromium alloys; cobalt-chromium-molybdenum alloys (e.g., UNS: R44003 such as ELGILOY®, PHYNOX®, and the like); platinum enriched stainless steel; titanium; combinations thereof; and the like; or any other suitable material.

(56) As alluded to herein, within the family of commercially available nickel-titanium or nitinol alloys, is a category designated “linear elastic” or “non-super-elastic” which, although may be similar in chemistry to conventional shape memory and super-elastic varieties, may exhibit distinct

and useful mechanical properties. Linear elastic and/or non-super-elastic nitinol may be distinguished from super elastic nitinol in that the linear elastic and/or non-super-elastic nitinol does not display a substantial “superelastic plateau” or “flag region” in its stress/strain curve like super elastic nitinol does. Instead, in the linear elastic and/or non-super-elastic nitinol, as recoverable strain increases, the stress continues to increase in a substantially linear, or a somewhat, but not necessarily entirely linear relationship until plastic deformation begins or at least in a relationship that is more linear than the super elastic plateau and/or flag region that may be seen with super elastic nitinol. Thus, for the purposes of this disclosure linear elastic and/or non-super-elastic nitinol may also be termed “substantially” linear elastic and/or non-super-elastic nitinol. In some cases, linear elastic and/or non-super-elastic nitinol may also be distinguishable from super-elastic nitinol in that linear elastic and/or non-super-elastic nitinol may accept up to about 2-5% strain while remaining substantially elastic (e.g., before plastically deforming) whereas super-elastic nitinol may accept up to about 8% strain before plastically deforming. Both of these materials can be distinguished from other linear elastic materials such as stainless steel (that can also be distinguished based on its composition), which may accept only about 0.2 to 0.44 percent strain before plastically deforming.

(57) In some embodiments, the linear elastic and/or non-super-elastic nickel-titanium alloy is an alloy that does not show any martensite/austenite phase changes that are detectable by differential scanning calorimetry (DSC) and dynamic metal thermal analysis (DMTA) analysis over a large temperature range. For example, in some embodiments, there may be no martensite/austenite phase changes detectable by DSC and DMTA analysis in the range of about -60 degrees Celsius (° C.) to about 120° C. in the linear elastic and/or non-super-elastic nickel-titanium alloy. The mechanical bending properties of such material may therefore be generally inert to the effect of temperature over this very broad range of temperature. In some embodiments, the mechanical bending properties of the linear elastic and/or non-super-elastic nickel-titanium alloy at ambient or room temperature are substantially the same as the mechanical properties at body temperature, for example, in that they do not display a super-elastic plateau and/or flag region. In other words, across a broad temperature range, the linear elastic and/or non-super-elastic nickel-titanium alloy maintains its linear elastic and/or non-super-elastic characteristics and/or properties.

(58) In some embodiments, the linear elastic and/or non-super-elastic nickel-titanium alloy may be in the range of about 50 to about 60 weight percent nickel, with the remainder being essentially titanium. In some embodiments, the composition is in the range of about 54 to about 57 weight percent nickel. One example of a suitable nickel-titanium alloy is FHP-NT alloy commercially available from Furukawa Techno Material Co. of Kanagawa, Japan. Other suitable materials may include ULTANIUM™ (available from Neo-Metrics) and GUM METAL™ (available from Toyota). In some other embodiments, a superelastic alloy, for example a superelastic nitinol can be used to achieve desired properties.

(59) In at least some embodiments, portions or all of the system and/or other elements disclosed herein may also be doped with, made of, or otherwise include a radiopaque material. Radiopaque materials are understood to be materials capable of producing a relatively bright image on a fluoroscopy screen or another imaging technique during a medical procedure. This relatively bright image aids a user in determining the location of the system and/or other elements disclosed herein. Some examples of radiopaque materials can include, but are not limited to, gold, platinum, palladium, tantalum, tungsten alloy, polymer material loaded with a radiopaque filler, and the like. Additionally, other radiopaque marker bands and/or coils may also be incorporated into the design of the system and/or other elements disclosed herein to achieve the same result.

(60) In some embodiments, a degree of Magnetic Resonance Imaging (MRI) compatibility is imparted into the system and/or other elements disclosed herein. For example, the system and/or components or portions thereof may be made of a material that does not substantially distort the image and create substantial artifacts (e.g., gaps in the image). Certain ferromagnetic materials, for

example, may not be suitable because they may create artifacts in an MRI image. The system or portions thereof, may also be made from a material that the MM machine can image. Some materials that exhibit these characteristics include, for example, tungsten, cobalt-chromium-molybdenum alloys (e.g., UNS: R44003 such as ELGILOY®, PHYNEX®, and the like), nickel-cobalt-chromium-molybdenum alloys (e.g., UNS: R44035 such as MP35-N® and the like), nitinol, and the like, and others.

(61) In some embodiments, the system and/or other elements disclosed herein may be made from or include a polymer or other suitable material. Some examples of suitable polymers may include polytetrafluoroethylene (PTFE), ethylene tetrafluoroethylene (ETFE), fluorinated ethylene propylene (FEP), polyoxymethylene (POM, for example, DELRIN® available from DuPont), polyether block ester, polyurethane (for example, Polyurethane 85A), polypropylene (PP), polyvinylchloride (PVC), polyether-ester (for example, ARNITEL® available from DSM Engineering Plastics), ether or ester based copolymers (for example, butylene/poly(alkylene ether) phthalate and/or other polyester elastomers such as HYTREL® available from DuPont), polyamide (for example, DURETHAN® available from Bayer or CRISTAMID® available from Elf Atochem), elastomeric polyamides, block polyamide/ethers, polyether block amide (PEBA, for example available under the trade name PEBAX®), ethylene vinyl acetate copolymers (EVA), silicones, polyethylene (PE), MARLEX® high-density polyethylene, MARLEX® low-density polyethylene, linear low density polyethylene (for example REXELL®), polyester, polybutylene terephthalate (PBT), polyethylene terephthalate (PET), polytrimethylene terephthalate, polyethylene naphthalate (PEN), polyetheretherketone (PEEK), polyimide (PI), polyetherimide (PEI), polyphenylene sulfide (PPS), polyphenylene oxide (PPO), poly paraphenylene terephthalamide (for example, KEVLAR®), polysulfone, nylon, nylon-12 (such as GRILAMID® available from EMS American Grilon), perfluoro(propyl vinyl ether) (PFA), ethylene vinyl alcohol, polyolefin, polystyrene, epoxy, polyvinylidene chloride (PVdC), poly(styrene-b-isobutylene-b-styrene) (for example, SIBS and/or SIBS 50A), polycarbonates, ionomers, biocompatible polymers, other suitable materials, or mixtures, combinations, copolymers thereof, polymer/metal composites, and the like. In some embodiments the sheath can be blended with a liquid crystal polymer (LCP). For example, the mixture can contain up to about 6 percent LCP.

(62) In some embodiments, the system and/or other elements disclosed herein may include a fabric material disposed over or within the structure. The fabric material may be composed of a biocompatible material, such a polymeric material or biomaterial, adapted to promote tissue ingrowth. In some embodiments, the fabric material may include a bioabsorbable material. Some examples of suitable fabric materials include, but are not limited to, polyethylene glycol (PEG), nylon, polytetrafluoroethylene (PTFE, ePTFE), a polyolefinic material such as a polyethylene, a polypropylene, polyester, polyurethane, and/or blends or combinations thereof.

(63) In some embodiments, the system and/or other elements disclosed herein may include and/or be formed from a textile material. Some examples of suitable textile materials may include synthetic yarns that may be flat, shaped, twisted, textured, pre-shrunk or un-shrunk. Synthetic biocompatible yarns suitable for use in the present disclosure include, but are not limited to, polyesters, including polyethylene terephthalate (PET) polyesters, polypropylenes, polyethylenes, polyurethanes, polyolefins, polyvinyls, polymethylacetates, polyamides, naphthalene dicarboxylene derivatives, natural silk, and polytetrafluoroethylenes. Moreover, at least one of the synthetic yarns may be a metallic yarn or a glass or ceramic yarn or fiber. Useful metallic yarns include those yarns made from or containing stainless steel, platinum, gold, titanium, tantalum or a Ni—Co—Cr-based alloy. The yarns may further include carbon, glass or ceramic fibers. Desirably, the yarns are made from thermoplastic materials including, but not limited to, polyesters, polypropylenes, polyethylenes, polyurethanes, polynaphthalenes, polytetrafluoroethylenes, and the like. The yarns may be of the multifilament, monofilament, or spun types. The type and denier of the yarn chosen may be selected in a manner which forms a biocompatible and implantable prosthesis and, more

particularly, a vascular structure having desirable properties.

(64) In some embodiments, the system and/or other elements disclosed herein may include and/or be treated with a suitable therapeutic agent. Some examples of suitable therapeutic agents may include anti-thrombogenic agents (such as heparin, heparin derivatives, urokinase, and PPACK (dextrophenylalanine proline arginine chloromethylketone)); anti-proliferative agents (such as enoxaparin, angiopeptin, monoclonal antibodies capable of blocking smooth muscle cell proliferation, hirudin, and acetylsalicylic acid); anti-inflammatory agents (such as dexamethasone, prednisolone, corticosterone, budesonide, estrogen, sulfasalazine, and mesalamine); antineoplastic/antiproliferative/anti-mitotic agents (such as paclitaxel, 5-fluorouracil, cisplatin, vinblastine, vincristine, epothilones, endostatin, angiostatin and thymidine kinase inhibitors); anesthetic agents (such as lidocaine, bupivacaine, and ropivacaine); anti-coagulants (such as D-Phe-Pro-Arg chloromethyl ketone, an RGD peptide-containing compound, heparin, anti-thrombin compounds, platelet receptor antagonists, anti-thrombin antibodies, anti-platelet receptor antibodies, aspirin, prostaglandin inhibitors, platelet inhibitors, and tick antiplatelet peptides); vascular cell growth promoters (such as growth factor inhibitors, growth factor receptor antagonists, transcriptional activators, and translational promoters); vascular cell growth inhibitors (such as growth factor inhibitors, growth factor receptor antagonists, transcriptional repressors, translational repressors, replication inhibitors, inhibitory antibodies, antibodies directed against growth factors, bifunctional molecules consisting of a growth factor and a cytotoxin, bifunctional molecules consisting of an antibody and a cytotoxin); cholesterol-lowering agents; vasodilating agents; and agents which interfere with endogenous vasoactive mechanisms.

(65) It should be understood that this disclosure is, in many respects, only illustrative. Changes may be made in details, particularly in matters of shape, size, and arrangement of steps, without exceeding the scope of the disclosure. This may include, to the extent that it is appropriate, the use of any of the features of one example embodiment being used in other embodiments. The disclosure's scope is, of course, defined in the language in which the appended claims are expressed.

Claims

1. A left atrial appendage closure device, comprising: an expandable framework having a plurality of struts disposed about a central longitudinal axis, the plurality of struts being joined together at a proximal hub and a distal hub; wherein when the expandable framework is fully constrained in a first position by a delivery sheath, a first segment of the plurality of struts extends distally from the distal hub to a first bend and a second segment of the plurality of struts extends from the first bend proximally; wherein a first amount of the expandable framework is unconstrained by the delivery sheath in a second position; wherein in the second position the first segment of the plurality of struts extends distally from the distal hub to the first bend, the second segment of the plurality of struts extends from the first bend proximally and radially outward to a second bend, a third segment of the plurality of struts extends from the second bend proximally and radially inward to a third bend, and a fourth segment of the plurality of struts extends from the third bend proximally to within the delivery sheath; wherein a second amount of the expandable framework greater than the first amount is unconstrained by the delivery sheath in a third position; wherein in the third position the first segment of the plurality of struts extends distally from the distal hub to the first bend, the second segment of the plurality of struts extends from the first bend radially outward generally perpendicular to the central longitudinal axis to the second bend, the third segment of the plurality of struts extends from the second bend proximally and radially inward to the third bend, and the fourth segment of the plurality of struts extends from the third bend proximally toward the proximal hub disposed within the delivery sheath; wherein a third amount of the expandable framework greater than the second amount is unconstrained by the delivery sheath in a fourth

position; wherein in the fourth position the first segment of the plurality of struts extends distally from the distal hub to the first bend, the second segment of the plurality of struts extends from the first bend distally and radially outward to the second bend, the third segment of the plurality of struts extends from the second bend proximally and radially inward toward the third bend, and the fourth segment of the plurality of struts extends from the third bend proximally toward the proximal hub disposed within the delivery sheath.

2. The left atrial appendage closure device of claim 1, wherein in the second position the first segment and the second segment form an acute angle opening inwardly toward an interior of the expandable framework.

3. The left atrial appendage closure device of claim 1, wherein in the third position the second segment and the third segment form an acute angle opening inwardly toward the central longitudinal axis.

4. The left atrial appendage closure device of claim 1, wherein in the third position the third segment and the fourth segment form an obtuse angle opening outwardly away from the central longitudinal axis.

5. The left atrial appendage closure device of claim 1, wherein in the fourth position the first segment and the second segment form an obtuse angle opening inwardly toward an interior of the expandable framework.

6. The left atrial appendage closure device of claim 1, wherein in the fourth position the second segment and the third segment form an acute angle opening inwardly toward the central longitudinal axis.

7. The left atrial appendage closure device of claim 1, wherein in the fourth position the third segment and the fourth segment form an obtuse angle opening outwardly away from the central longitudinal axis.

8. The left atrial appendage closure device of claim 1, wherein a fourth amount of the expandable framework greater than the third amount is unconstrained by the delivery sheath in a fifth position; wherein in the fifth position the first segment of the plurality of struts extends distally from the distal hub to the first bend, the second segment of the plurality of struts extends from the first bend distally and radially outward to the second bend, the third segment of the plurality of struts extends from the second bend proximally to the third bend, and the fourth segment of the plurality of struts extends from the third bend radially inward toward the proximal hub.

9. The left atrial appendage closure device of claim 8, wherein in the fifth position the first segment and the second segment form an obtuse angle opening inwardly.

10. The left atrial appendage closure device of claim 8, wherein in the fifth position the second segment and the third segment form an acute angle opening inwardly.

11. The left atrial appendage closure device of claim 8, wherein in the fifth position the third segment and the fourth segment form an angle of about 90 degrees or less opening inwardly.

12. The left atrial appendage closure device of claim 1, wherein the distal hub is disposed proximal of the first bend.

13. The left atrial appendage closure device of claim 1, wherein in the second position the distal hub is disposed distal of the second bend.

14. A left atrial appendage closure device, comprising: an expandable framework having a plurality of struts disposed about a central longitudinal axis, the plurality of struts being joined together at a proximal hub and a distal hub; wherein as the expandable framework shifts from fully constrained to fully unconstrained, the expandable framework transitions sequentially through a plurality of positions; wherein in a first position, a first segment of the plurality of struts extends distally from the distal hub to a first bend and a second segment of the plurality of struts extends from the first bend proximally; wherein in a second position, the second segment of the plurality of struts, if swept circumferentially around the central longitudinal axis, defines a generally conical shape tapering radially outward in a proximal direction from the first bend toward a second bend; wherein

in a third position, the second segment of the plurality of struts, if swept circumferentially around the central longitudinal axis, defines a generally planar shape oriented generally perpendicular to the central longitudinal axis; and wherein in a fourth position, the second segment of the plurality of struts, if swept circumferentially around the central longitudinal axis, defines a generally conical shape tapering radially outward in a distal direction from the first bend toward the second bend.

15. The left atrial appendage closure device of claim 14, wherein in the second position, the distal hub is disposed proximal of the first bend and the distal hub is disposed distal of the second bend.

16. A left atrial appendage closure device system, comprising: a delivery sheath having a lumen extending therein; and a left atrial appendage closure device comprising an expandable framework having a plurality of struts disposed about a central longitudinal axis, the plurality of struts being joined together at a proximal hub and a distal hub; wherein when the expandable framework is disposed within the lumen of the delivery sheath in a first position, a first segment of the plurality of struts extends distally from the distal hub to a first bend and a second segment of the plurality of struts extends from the first bend proximally; wherein relative axial translation between the delivery sheath and the expandable framework exposes some of the expandable framework in a second position; wherein in the second position the first segment of the plurality of struts extends distally from the distal hub to the first bend, the second segment of the plurality of struts extends from the first bend proximally and radially outward to a second bend, a third segment of the plurality of struts extends from the second bend proximally and radially inward to a third bend, and a fourth segment of the plurality of struts extends from the third bend proximally to within the delivery sheath; wherein relative axial translation between the delivery sheath and the expandable framework exposes more of the expandable framework in a third position than in the second position; wherein in the third position the first segment of the plurality of struts extends distally from the distal hub to the first bend, the second segment of the plurality of struts extends from the first bend radially outward generally perpendicular to the central longitudinal axis to the second bend, the third segment of the plurality of struts extends from the second bend proximally and radially inward to the third bend, and the fourth segment of the plurality of struts extends from the third bend proximally toward the proximal hub disposed within the delivery sheath; wherein relative axial translation between the delivery sheath and the expandable framework exposes more of the expandable framework in a fourth position than in the third position; wherein in the fourth position the first segment of the plurality of struts extends distally from the distal hub to the first bend, the second segment of the plurality of struts extends from the first bend distally and radially outward to the second bend, the third segment of the plurality of struts extends from the second bend proximally and radially inward toward the third bend, and the fourth segment of the plurality of struts extends from the third bend proximally toward the proximal hub disposed within the delivery sheath; wherein relative axial translation between the delivery sheath and the expandable framework exposes all of the expandable framework in a fifth position; wherein in the fifth position the first segment of the plurality of struts extends distally from the distal hub to the first bend, the second segment of the plurality of struts extends from the first bend distally and radially outward to the second bend, the third segment of the plurality of struts extends from the second bend proximally to the third bend, and the fourth segment of the plurality of struts extends from the third bend radially inward toward the proximal hub.
