

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12382928
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Chow; Jesse

---

### Pet toy

---

#### Abstract

The present invention relates to the technical field of pet toys, in particular to pet toys for teasing cats and other pets. It comprises a jacking component, a power component, a toy base pad and a deformable connecting wire, wherein the jacking component comprises a reset structure, a rocker base and a rocker member hinged with the rocker base; the rocker member comprises a driven end, and there is a connecting wire actuating arm from the connecting wire to the axis of the hinged joint between the rocker member and the rocker base, where the moment generated by the connecting wire actuating arm causes the rocker member to move away from the rocker base. The present invention can form a prominent protrusion from the rocker base back and forth, thereby attracting the attention of cats and other pets, and teasing cats, etc.

---

<b>Inventors:</b>	<b>Chow; Jesse (Hong Kong, CN)</b>
<b>Applicant:</b>	<b>DAKA INTERNATIONAL LIMITED (Hong Kong, CN)</b>
<b>Family ID:</b>	<b>1000008749133</b>
<b>Assignee:</b>	<b>DAKA INTERNATIONAL LIMITED (Hong Kong, CN)</b>
<b>Appl. No.:</b>	<b>18/487414</b>
<b>Filed:</b>	<b>October 16, 2023</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240164347 A1	May. 23, 2024

#### Foreign Application Priority Data

CN	202211450048.3	Nov. 19, 2022
----	----------------	---------------

---

#### Publication Classification

**Int. Cl.:** A01K15/02 (20060101)

**U.S. Cl.:**

**CPC** A01K15/025 (20130101);

## Field of Classification Search

**CPC:** A01K (15/025); A63H (33/26)

**USPC:** 446/484; 446/486; 446/490

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4627620	12/1985	Yang	482/84	A63B 69/0028

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
213819385	12/2020	CN	N/A

---

*Primary Examiner:* Berona; Kimberly S

*Assistant Examiner:* Aleksic; Nevena

*Attorney, Agent or Firm:* JEEN IP LAW, LLC

---

## Background/Summary

### CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This is a U.S. patent application which claims the priority and benefit of Chinese Patent Application Number 202211450048.3, filed on Nov. 19, 2022, the disclosure of which is incorporated herein by reference in its entirety.

### TECHNICAL FIELD

(2) The present invention relates to the technical field of pet toys, in particular to pet toys for teasing cats and other pets.

### BACKGROUND

(3) CN213819385U discloses a camouflaged mouse cat teasing toy, comprising a main body, which comprises an upper cover, an inner cover and a bottom cover in sequence from the top down. The inner ring of the inner cover is provided with toothed grains, the bottom cover is provided with a motor and also with gears, the gears are matched with the toothed grains, and the inner cover is rotated by clicking to realize the cat teasing function. The side of the bottom cover is provided with a plurality of second rollers, and a plurality of first rollers are provided above the bottom cover, so that the inner cover rotates more smoothly; there are a plurality of rubber foot pads on the bottom of the bottom cover to prevent slipping and swinging during operation. Both ends of the inner cover are provided with a cat teasing rod and a feather connecting rod. The combination of the feather and silicone cat teasing accessories makes the present invention more practical in catering for preferences of different pets compared to products with a single function only in the market,

solving the problem of functional singularity of products effectively.

(4) In summary, at least the following technical problems exist in the prior art:

(5) Firstly, currently, there is no toy in the market that can form a prominent protrusion from the ground to tease cats and other pets through this prominent protrusion.

## SUMMARY

(6) One objective of the present invention is to solve or alleviate the above first technical problem.

(7) The measure taken by the present invention is a pet toy, which comprises a jacking component, a power component, a toy base pad and a deformable connecting wire, wherein the jacking component comprises a reset structure, a rocker base and a rocker member hinged with the rocker base; the rocker member comprises a driven end, and there is a connecting wire actuating arm from the connecting wire to the axis of the hinged joint between the rocker member and the rocker base, where the moment generated by the connecting wire actuating arm causes the rocker member to move away from the rocker base; the reset structure is connected to the rocker member and the rocker base, respectively, so that the driven end has a tendency of approaching the rocker base; the power component comprises a sliding end that can drive the connecting wire to move; the two ends of the connecting wire are a pulling end connected to the driven end and a sliding end connected to the sliding member, respectively.

(8) The effect realized by the present invention is to form a prominent protrusion from the rocker base back and forth, thereby attracting the attention of cats and other pets, and teasing cats, etc.

(9) A further technical solution, further comprising a sheet-shaped toy base pad, a rocker base fixed to the front side of the toy base pad, and a power component fixedly connected to the toy base pad, thereby making the pet toy look like a pad in general for easy use and storage.

(10) A further technical solution, further comprising a covering layer fixed to the front side of the toy base pad, where the connecting wire passes between the covering layer and the toy base pad, so that the connecting wire is not exposed and the reliability of its movement is ensured.

(11) A further technical solution, wherein the reset structure is an elastic sheet fixedly connected to the rocker base, and is integrally connected to the covering layer, thereby facilitating the mass production of the pet toy.

(12) A further technical solution, wherein the power component further comprises a rotating base and a rotating member provided with a bracing part; the rotating member is hinged with the rotating base and has rotational power, and the sliding member is slidably connected to the rotating base, which has a radial vector; when the rotating member rotates, the bracing part braces the sliding member and keeps the sliding member away from the axis of the rotating member.

(13) A further technical solution, wherein there are a plurality of jacking components, connecting wires and sliding members.

(14) A further technical solution, wherein the sliding members are linearly slidably connected to the rotating base; all linear sliding connections between the sliding members and the rotating base point to the axis of the rotating member, so that a plurality of rocker members can be driven by a single power source, thereby simplifying the structure and reducing the cost.

(15) A further technical solution, wherein when viewed from above, the power component is located completely in the toy base pad and among the jacking components.

(16) A further technical solution, wherein when viewed from above, the connecting wires and the rocker members of all jacking components pass through the axis of the rotating member, thereby ensuring that the pulling force of the connecting wires is in the same direction as the sliding direction of the sliding member and that the connecting wires move smoothly.

(17) A further technical solution, wherein all jacking components and sliding members are distributed uniformly around the axis of the rotating member.

(18) A further technical solution, wherein the rotating base is provided with a plurality of connecting wire ports, which are located on one side of the rotating member, and the connecting wires pass through the connecting wire ports, respectively, thereby allowing the power component

to be provided on the edge of the toy base pad and utilizing the toy base pad to a great extent.

(19) A further technical solution, wherein the maximum distance between two jacking components is the maximum distance among the jacking components, the maximum distance between two connecting wire ports is the maximum distance among the connecting wire ports, and the maximum distance among the connecting wire ports is less than the maximum distance among the jacking components, thereby allowing the power component to be connected to part of the edge of the toy base pad only, and further utilizing the toy base to a great extent.

(20) A further technical solution, wherein the rotating base is provided with a steering body, and the connecting wires bypass the steering body respectively to form a before-wheel segment and a steering segment; the steering segment is closer to the sliding member relative to the before-wheel segment, and the connecting wires between the connecting wire ports and the corresponding steering body are parallel to one another, thereby avoiding interference among the connecting wires and ensuring the smooth movement of the connecting wires.

(21) A further technical solution, wherein a rotatable steering wheel fits over the steering body, and the connecting wires bypass the steering wheel, respectively, thereby avoiding interference among the connecting wires and ensuring the smooth movement of the connecting wires.

(22) A further technical solution, wherein the rotating base is fixedly provided with a protective body, which is used to prevent the connecting wires from approaching the steering body, thereby ensuring that the connecting wires move smoothly without being interfered with by one another.

(23) A further technical solution, wherein the reset structure is an elastic sheet fixedly connected to the rocker base, and the rocker member is located between the rocker base and the reset structure.

(24) A further technical solution, wherein all edges of the reset structure are connected to the rocker base, and in a closed shape when viewed from above.

(25) A further technical solution, wherein the rocker base comprises a base sidewall, the rocker member is below or flush with the base sidewall when laid flat, and the reset structure is pressed against the top of the base sidewall.

(26) A further technical solution, wherein the rocker member comprises a hinged end provided with a hinged shaft, the rocker base comprises a protrusion for hinging provided with a hinged groove, and the hinged shaft is inserted into the hinged groove.

(27) A further technical solution, wherein the rocker base is provided with a penetration port, and when viewed from above, there is an overlap between the hinged end and the penetration port, and the hinged groove is provided with an exposed port, and the hinged shaft can move upward and out of the exposed port.

(28) In summary, the present invention can realize the following technical effects: 1) It can form a prominent protrusion from the rocker base back and forth, thereby attracting the attention of cats and other pets, and teasing cats, etc. 2) It can make the pet toy look like a pad in general for easy use and storage. 3) It can further utilize the toy base pad to a great extent.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a three-dimensional schematic diagram of the pet toy in an embodiment of the present invention.
- (2) FIG. 2 is a side view of the pet toy in an embodiment of the present invention.
- (3) FIG. 3 is a top view of the pet toy in an embodiment of the present invention.
- (4) FIG. 4 is a three-dimensional exploded view of the pet toy in an embodiment of the present invention.
- (5) FIG. 5 is another three-dimensional exploded view of the pet toy in an embodiment of the present invention.

- (6) FIG. 6 is a three-dimensional schematic diagram of the jacking component 1 of an embodiment of the present invention; Reset structure 13 is not shown.
- (7) FIG. 7 is a three-dimensional exploded view of the jacking component 1 of an embodiment of the present invention.
- (8) FIG. 8 is a three-dimensional exploded view of the jacking component 1 of an embodiment of the present invention.
- (9) FIG. 9 is a schematic diagram of Section 1; Arrow 1 indicates the direction in which the power component 3 pulls the connecting wire 2 when the reset structure 13 is to be jacked up; Arrow 2 indicates the direction in which the pulling end 21 drives the rocker member 11 to rotate when the reset structure 13 is to be jacked up; Line 1 denotes the hypothetical position of the reset structure 13 after being jacked up by the driven end 111.
- (10) FIG. 10 is a three-dimensional exploded view of exploded state 1 of the power component 3 in an embodiment of the present invention.
- (11) FIG. 11 is another three-dimensional exploded view of exploded state 1 of the power component 3 in an embodiment of the present invention.
- (12) FIG. 12 is a three-dimensional schematic diagram of the power component 3 of an embodiment of the present invention; the upper cover of the shell 39 is not shown.
- (13) FIG. 13 is a three-dimensional exploded view of exploded state 2 of the power component 3 in an embodiment of the present invention; the shell 39 and the connecting wire 2 are not shown.
- (14) FIG. 14 is another three-dimensional exploded view of exploded state 2 of the power component 3 in an embodiment of the present invention; the shell 39 and the connecting wire 2 are not shown.
- (15) FIG. 15 is an upward view of the power component 3 of an embodiment of the present invention; the bottom cover of the shell 39 is not shown; Arrow 3 denotes the rotating direction of the rotating member 31; Arrow 4 denotes the direction in which sliding member 32 is braced by the bracing part 311 of the rotating member 31, and Arrow 1 denotes the direction in which the sliding member 32 pulls the connecting wire 2 to move it.
- (16) FIG. 16 is an enlarged schematic diagram of DTL1 in FIG. 9.
- (17) Section 1; Arrow 1; Arrow 2; Arrow 3; Arrow 4; Line 1; jacking component 1; rocker member 11; driven end 111; pulling end connecting hole 112; large diameter end holding groove 113; hinged end 116; hinged shaft 117; threading hole 118; wire step-down port 119; rocker base 12; penetration port 124; protrusion for hinging 125; hinged groove 126; exposed port 127; base sidewall 128; extension tube seat 129; reset structure 13; maximum distance among the jacking components 15; fixed frame 18; fixed frame protrusion 189; extension tube 19; connecting wire 2; pulling end 21; sliding end 22; height difference segment 23; before-wheel segment 24; steering segment 25; connecting wire actuating arm 29; power component 3; rotating member 31; bracing part 311; rotating member gear 312; motor 313; worm 314; sliding member 32; sliding end connecting hole 329; rotating base 33; connecting wire port 331; steering body 332; steering wheel 333; protective body 334; maximum distance among the connecting wire ports 335; upper base 338; lower base 339; sliding structure 37; sliding groove 371; sliding block 372; electric control device 38; power source 381; switch 382; shell 39; covering layer 8; toy base pad 9.

#### DETAILED DESCRIPTION

- (18) Specific embodiments of the present invention will be described below by reference to the drawings for the specification.
- (19) As a specific embodiment, the pet toy in an embodiment of the present invention comprises a lifting structure of pet toys and a driving structure of pet toys.
- (20) The lifting structure of the pet toy in an embodiment of the present invention comprises a jacking component 1, wherein the jacking component 1 comprises a reset structure 13, a rocker base 12 and a rocker member 11 hinged with the rocker base 12.
- (21) The rocker member 11 comprises a driven end 111, and there is a connecting wire actuating

arm **29** from the connecting wire **2** to the axis of the hinged joint between the rocker member **11** and the rocker base **12**, where the moment generated by the connecting wire actuating arm **29** causes the rocker member **11** to move away from the rocker base **12**.

(22) The reset structure **13** is connected to the rocker member **11** and the rocker base **12**, respectively, so that the driven end **111** has a tendency of approaching the rocker base **12**. For example, the reset structure **13** is a spring, and its two ends are connected to the rocker member **11** and the rocker base **12** through hooks, respectively, and the pulling force provided by the reset structure **13** causes the driven end **111** to have a tendency of approaching the rocker base **12** (FIG. **16**).

(23) The operating principle is as follows: As shown in FIG. **9**, when the connecting wire **2** is driven by the power component **3** described below and retracted into the power component **3**, the driven end **111** is pulled by the connecting wire **2**, causing the driven end **111** to rotate and move away from the rocker base **12**, and protrude prominently from the rocker base **12**, thereby attracting the attention of cats and other pets, and inducing them to press the protruding driven end **111**.

(24) The connecting wire **2** is released by the power component **3**, and the reset structure **13** causes the driven end **111** to approach the rocker base **12** rotatably until it is pressed against or close to the rocker base **12** and laid flat; at the same time, the driven end **111** drives the connecting wire **2** to reset.

(25) It can be seen from above that a prominent protrusion can be formed from the rocker base **12** back and forth, thereby attracting the attention of cats and other pets, and realizing cat teasing, etc.

(26) As one of the specific embodiments, the reset structure **13** is an elastic sheet fixedly connected to the rocker base **12**, and the rocker member **11** is located between the rocker base **12** and the reset structure **13**. For example, the reset structure **13** is an elastic rubber sheet. It should be noted that when there is a gap between the reset structure **13** and the rocker member **11**, the reset structure **13** is connected indirectly to the rocker member **11**.

(27) As one of the specific embodiments, all edges of the reset structure **13** are connected to the rocker base **12**, and in a closed shape when viewed from above, such as circular, square or rectangular. When the driven end **111** jacks up the sheet-shaped reset structure **13**, the reset structure **13** can be bulged (i.e. the cross-section is curved), thereby improving the effect of attracting the attention of cats and other pets.

(28) As one of the specific embodiments, the rocker base **12** comprises a base sidewall **128**, the rocker member **11** is below or flush with the base sidewall **128** when laid flat, and the reset structure **13** is pressed against the top of the base sidewall **128**. For example, the base sidewall **128** is cylindrical in general, and when the rocker member **11** is laid flat, the reset structure **13** has a roughly flat portion other than a slightly protruding bulge, thereby making the bulging effect of the reset structure **13** more prominent.

(29) As one of the specific embodiments, the jacking component **1** also comprises a fixed frame **18**, which is detachably and fixedly connected to the rocker base **12**, and the fixed frame **18** and the rocker base **12** clamp the reset structure **13**, so that the reset structure **13** is fixedly connected to the rocker base **12**, making it easy to fix the reset structure **13**. For example, the fixed frame **18** and the base sidewall **128** hold the reset structure **13**.

(30) As one of the specific embodiments, the fixed frame **18** is provided with a fixed frame protrusion **189** embedded directly or indirectly into the rocker base **12**, making the fixed frame **18** detachably and fixedly connected to the rocker base **12**. For example, the fixed frame protrusion **189** is directly embedded into the rocker base **12** through the reset structure **13**, presses against the reset structure **13** or is embedded indirectly into the rocker base **12** through the reset structure **13**, making it easy to fix the reset structure **13**.

(31) As one of the specific embodiments, the rocker member **11** comprises a hinged end **116** provided with a hinged shaft **117**, the rocker base **12** comprises a protrusion for hinging **125** provided with a hinged groove **126**, and the hinged shaft **117** is inserted into the hinged groove **126**,

so that the rocker member **11** is hinged with the rocker base **12**.

(32) As one of the specific embodiments, the rocker base **12** comprises an extension tube seat **129**, the hinged end **116** is provided with a threading hole **118**, and the inner cavity of the extension tube seat **129** is lower than the threading hole **118**. The connecting wire **2** passes through the wire hole **118** and the inner cavity of the extension tube seat **129** in sequence to form a height difference segment **23**. When the connecting wire **2** is retracted into the power component **3**, the pulling force of the height difference segment **23** generates a moment, causing the driven end **111** to rotate and move away from the rocker base **12**, thereby improving the effect of the connecting wire **2** driving the driven end **111** to rotate.

(33) As one of the specific embodiments, the connecting wire **2** also comprises an extension tube **19**, which is detachably connected to the extension tube seat **129**, so that the inner cavity of the extension tube **19** and the inner cavity of the extension tube seat **129** are on a straight line and connected. For example, the extension tube **19** is embedded into the extension tube seat **129**, making the extension tube **19** detachably connected to the extension tube seat **129**.

(34) As one of the specific embodiments, the rocker base **12** is provided with a penetration port **124**. When viewed from above as shown in FIG. 9, there is an overlap between the hinge end **116** and the penetration port **124**. The hinged groove **126** is provided with an exposed port **127**, and the hinged shaft **117** can move upward (vertically or obliquely upward) to move out of the exposed port **127**. The hinged shaft **117** can be moved out of the hinged groove **126**, and the connecting wire **2** can pass through the extension tube seat **129** and the penetration port **124** in sequence, and then through the threading hole **118** of the rocker member **11** separated from the rocker base **12**, thereby facilitating the assembly of the jacking component **1**, and also ensuring that the hinged shaft **117** is located in the hinged groove **126** when the connecting wire **2** pulls the rocker member **11** with high reliability.

(35) As one of the specific embodiments, the driven end **111** is provided with a pulling end connecting hole **112**, and the connection wire **2** comprises a pulling end **21**, which passes through the pulling end connecting hole **112** from the hinge end **116** (which ignores the physical obstruction of the driven end **111**) and presses against the driven end **111**, so that the pulling end **21** is connected to the driven end **111**. For example, the pulling end **21** is a spherical or cylindrical object with a diameter greater than the pulling end connecting hole **112**, or a ball-like object formed by knotting, making it impossible for the pulling end **21** to pass through the pulling end connecting hole **112**. The connection between the pulling end **21** and the driven end **111** is unidirectional; in other words, the pulling end **21** can freely move from the hinged end **116** to the driven end **111**, but the movement from the driven end **111** to the hinged end **116** is restricted by the pulling end connecting hole **112**, thereby ensuring that when the connecting wire **2** extends, the rocker member **11** is laid flat and fits with the rocker base **12**.

(36) As one of the specific embodiments, the driven end **111** is provided with a large diameter end holding groove **113** connected to the pulling end connecting hole **112**, and the pulling end **21** is located in the large diameter end holding groove **113**.

(37) The driving structure of the pet toy in an embodiment of the present invention comprises a power component **3**, which comprises a rotating base **33**, a sliding member **32** and a rotating member **31** provided with a bracing part **311**.

(38) The rotating member **31** is hinged with the rotating base **33** and has rotational power, and the axis of hinging between the rotating member **31** and the rotating base **33** is referred to as the axis of the rotating member **31**.

(39) The sliding member **32** is slidably connected to the rotating base **33**, which has a radial vector; in other words, in this sliding connection, there is a difference between the distance from the end closer to the axis of the rotating member **31** to the axis of the rotating member **31**, and the distance from the end farther away from the axis of the rotating member **31** to the axis of the rotating member **31**.

(40) When the rotating member **31** rotates, the bracing part **311** braces the sliding member **32** and keeps the sliding member **32** away from the axis of the rotating member **31**.

(41) The sliding member **32** comprises a portion for connecting the connecting wire **2**, and the sliding member **32** has a tendency of approaching the axis of the rotating member **31**. For example, the sliding member **32** is provided with a sliding end connecting hole **329**, and after the connecting wire **2** passes through the sliding end connecting hole **329**, the sliding member **32** is connected to the connecting wire **2** by knotting or connecting the pulling end **21** as mentioned above. For another example, the sliding member **32** has a tendency of approaching the axis of the rotating member **31** through a spring.

(42) As mentioned above, the connecting wire **2** applies a force on the rocker member **11** due to the reset structure **13**, so that the rocker member **11** pulls the sliding member **32**, realizing the tendency of the connecting wire **2** to bring the sliding member **32** close to the axis of the rotating member **31**.

(43) The operating principle is as follows: When the rotating member **31** rotates, the bracing part **311** presses against the sliding member **32**, causing the sliding member **32** to move away from the axis of the rotating member **31**. The sliding member **32** pulls the connecting wire **2**, which is driven by the power component **3** and retracted into the power component **3**, forming a prominent protrusion from the rocker base **12** as mentioned above, thereby attracting the attention of cats and other pets, and realizing cat teasing, etc.

(44) When the bracing part **311** rotates and passes over the sliding member **32**, the connecting wire **2** applies a force on the rocker member **11**, so that the rocker member **11** pulls the sliding member **32** to reset, and the connecting wire **2** is released by the power component **3**.

(45) By rotating the rotating member **31** multiple turns in a single direction, the connecting wire **2** can move back and forth without the need for a complex structure.

(46) It can be seen from above that a simple structure can provide power for the connecting wire **2** to move back and forth.

(47) As one of the specific embodiments, the power component **3** also comprises a motor **313** and a rotating member gear **312** fixedly connected to the rotating member **31**, and the motor **313** drives the rotating member gear **312** to rotate, thereby providing rotational power to the rotating member **31**.

(48) As one of the specific embodiments, the motor **313** is fixed on the rotating base **33**, and the output end of the motor **313** is fixedly provided with a worm **314** engaged with the rotating member gear **312**. The engaging structure of the rotating member gear **312** and the worm **314** has a self-locking effect, and the sliding of the sliding member **32** cannot make the motor **313** rotate, thereby ensuring that the bulging effect of the above reset structure **13** is relatively stable.

(49) As one of the specific embodiments, the motor **313** is fixed on the rotating base **33**, and drives the rotating member gear **312** to rotate in both directions. In other words, the motor **313** can drive the rotating member gear **12** to rotate, and the rotating member gear **312** can also drive the rotating output end of the rotating member gear **312** to rotate. For example, the output end of the motor **313** is fixedly provided with a gear engaged with the rotating member gear **312**, which discharges the worm **314**. The sliding of the sliding element **32** can rotate the motor **313**; when the rocker member **11** and the connecting wire **2** are stepped on accidentally, so that the sliding member **32** moves, the sliding member **32** presses against the bracing part **311**, causing the rotating member gear **312** to rotate without causing the connecting wire **2** to be stretched, thereby reducing or eliminating the risk of the connecting wire **2** being pulled apart.

(50) As one of the specific embodiments, the power component **3** also comprises an electric control device **38** electrically connected to the motor **313**, which is electrically connected to a power source **381** and a switch **382**. The electronic control device **38** is a circuit board or the like used to control the speed and/or starting of the motor **313**.

(51) As one of the specific embodiments, the sliding members **32** are linearly slidably connected to



the rotating base **33**.

(52) As one of the specific embodiments, the power component **3** also comprises a sliding structure **37**, which comprises a sliding groove **371** and a sliding block **372** embedded into the sliding groove **371**; the sliding groove **371** and the sliding block **372** are provided on the rotating base **33** and the sliding member **32**, respectively. For example, the top and bottom ends of the sliding element **32** are provided with a sliding block **372**, and the rotating base **33** comprises an upper base **338** and a lower base **339**, both of which are provided with a sliding groove **371** to ensure the stable sliding of the sliding element **32**. Of course, the sliding member **32** can also be embedded into the sliding groove **371** to realize sliding wheel connection. For another example, the top and bottom ends of the sliding member **32** are provided with a sliding groove **371**.

(53) As one of the specific embodiments, all linear sliding connections between the sliding members **32** and the rotating base **33** point to the axis of the rotating member **31**, and the sliding member **32** are multiple and distributed uniformly around the axis of the rotating member **31**, thereby ensuring that the sliding members **32** have a consistent travel, and that the bulging effect of each reset structure **13** is consistent.

(54) As one of the specific embodiments, the power component **3** also comprises a shell **39**, and a rotating base **33** is provided in the shell **39**.

(55) As a specific embodiment, the pet toy in an embodiment of the present invention comprises a jacking component **1**, a power component **3**, a toy base pad **9** and a deformable connecting wire **2**. For example, the connecting wire **2** is a somewhat flexible steel cable.

(56) The jacking component **1** comprises a reset structure **13**, a rocker base **12** and a rocker member **11** hinged with the rocker base **12**; the rocker member **11** comprises a driven end **111**, and there is a connecting wire actuating arm **29** from the connecting wire **2** to the axis of the hinged joint between the rocker member **11** and the rocker base **12**, where the moment generated by the connecting wire actuating arm **29** causes the rocker member **11** to move away from the rocker base **12**; the reset structure **13** is connected to the rocker member **11** and the rocker base **12**, respectively, so that the driven end **111** has a tendency of approaching the rocker base **12**.

(57) The power component **3** comprises a rotating base **33**, a sliding member **32** and a rotating member **31** provided with a bracing part **311**; the rotating member **31** is hinged with the rotating base **33** and has rotational power, and the sliding member **32** is slidably connected to the rotating base **33**, which has a radial vector; when the rotating member **31** rotates, the bracing part **311** braces the sliding member **32** and keeps the sliding member **32** away from the axis of the rotating member **31**.

(58) The two ends of the connecting wire **2** are a pulling end **21** connected to the driven end **111** and a sliding end **22** connected to the sliding member **32**, respectively.

(59) The pet toy in an embodiment of the present invention can form a prominent protrusion from the rocker base **12** back and forth, thereby attracting the attention of cats and other pets, and realizing cat teasing, etc.

(60) As one of the specific embodiments, the pet toy in an embodiment of the present invention also comprises a sheet-shaped toy base pad **9**, a rocker base **12** fixed to the front side of the toy base pad **9**, and a power component **3** fixedly connected to the toy base pad **9**, such as the edge of the toy base pad **9**, thereby making the pet toy look like a pad in general for easy use and storage.

(61) As one of the specific embodiments, the pet toy in an embodiment of the present invention also comprises a covering layer **8** fixed to the front side of the toy base pad **9**. For example, the covering layer **8** is fixed by fitting with the toy base pad **9**. The connecting wire **2** passes between the covering layer **8** and the toy base pad **9**. It can be easily understood that there is a non-sticking portion between the covering layer **8** and the toy base pad **9**, which corresponds to the connecting wire **2**, thereby preventing the connection wire **2** from being exposed and ensuring the reliability of movement of the connection wire **2**.

(62) As one of the specific embodiments, the reset structure **13** is an elastic sheet fixedly connected

to the rocker base **12**, and is integrally connected to the covering layer **8**. A rubber pad or other sheet can form a reset structure **13** and a covering layer **8**, thereby facilitating the mass production of the pet toy.

(63) As one of the specific embodiments, there are a plurality of jacking components **1**, connecting wires **2** and sliding members **32**.

(64) As one of the specific embodiments, the sliding members **32** are linearly slidably connected to the rotating base **33**; all linear sliding connections between the sliding members **32** and the rotating base **33** point to the axis of the rotating member **31**, so that a plurality of rocker members can be driven by a single power source, thereby simplifying the structure and reducing the cost. For example, as mentioned above, the sliding members **32** are distributed uniformly around the axis of the rotating member **31**, so that the rocker members **11** are lifted uniformly. Of course, the sliding members **32** can also be distributed non-uniformly as necessary to realize the uneven lifting of the rocker members **11**.

(65) As one of the specific embodiments (not shown in the drawing of this embodiment), when viewed from above, the power component **3** is located completely in the toy base pad **9** and among the jacking components **1**. For example, there are two jacking components **1**, and when viewed from above, the power component **3** is located between the two jacking components **1**, so that when viewed from above, the power component **3** is located completely between the jacking components **1**. For example, there are three jacking components **1**, which are connected in sequence to form a triangle. When viewed from above, the power component **3** is located completely in this triangle, so that when viewed from above, the power component **3** is located completely between the jacking components **1**.

(66) As one of the specific embodiments (not shown in the drawing of this embodiment), when viewed from above, the connecting wire **2** and the rocker member **11** of each jacking component **1** pass through the axis of the rotating member **31**. For example, all jacking components **1** and all sliding members **32** are distributed uniformly around the axis of the rotating member **31**, thereby ensuring that the pulling force of the connecting wires **2** is in the same direction as the sliding direction of the sliding member **32** and that the connecting wires **2** move smoothly.

(67) As one of the specific embodiments, as shown in FIG. **15**, the rotating base **33** is provided with a plurality of connecting wire ports **331**, which are located on one side of the rotating member **31**, and the connecting wires **2** pass through the connecting wire ports **331**, respectively, thereby allowing the power component **3** to be provided on the edge of the toy base pad **9** and utilizing the toy base pad **9** to a great extent, so that pets, etc. are not interfered with by the power component **3** when on the toy base pad **9**.

(68) As one of the specific embodiments, the rotating base **33** is provided with a steering body **332**, and the connecting wires **2** bypass the steering body **332** respectively to form a before-wheel segment **24** and a steering segment **25**; the steering segment **25** is closer to the sliding member **32** relative to the before-wheel segment **24**, and the connecting wires **2** between the connecting wire ports **331** and the corresponding steering body **332** are parallel to one another, thereby avoiding interference among the connecting wires **2** and ensuring the smooth movement of the connecting wires **2**.

(69) As one of the specific embodiments, as shown in FIG. **3**, the maximum distance between two jacking components **1** is the maximum distance among the jacking components **15**, the maximum distance between two connecting wire ports **331** is the maximum distance among the connecting wire ports **335**, and the maximum distance among the connecting wire ports **335** is less than the maximum distance among the jacking components **15**. It can be easily understood that the connecting wires **2** between the connecting wire ports **331** and the jacking components **1** face the jacking components **1** because they are pressed against the outer wall of the connecting wire port **331**, thereby allowing the power component **3** to be connected to part of the edge of the toy base pad **9** only, and further utilizing the toy base to a great extent.

(70) As one of the specific embodiments, a rotatable steering wheel 333 fits over the steering body 332, and the connecting wires 2 bypass the steering wheel 333 respectively, thereby avoiding interference among the connecting wires and ensuring the smooth movement of the connecting wires.

(71) As one of the specific embodiments, the rotating base 33 is fixedly provided with a protective body 334, which is used to prevent the connecting wires 2 from approaching the steering body 332, thereby ensuring that the connecting wires 2 move smoothly without being interfered with by one another.

(72) Terms like “first” and “second” as used in the present invention are not intended to indicate any order, quantity or importance, but are used for differentiation only.

(73) Terms like “one” and “one type” as used in the present invention are not intended to indicate any restriction in quantity, but indicate the existence of at least one subject mentioned.

(74) Terms like “top”, “bottom”, “side”, “longitudinal”, “lateral”, “middle”, “center”, “outer”, “inner”, “horizontal”, “vertical”, “left”, “right”, “above” and “below” indicating direction or position as used in the present invention are intended to reflect relative positions rather than absolute positions.

(75) Terms like “rough”, “overall”, “approximate” and “similar” as used in the present invention are restrictive terms intended to indicate the existence of a feature but allow for a certain deviation. The degree of the allowable deviation can vary depending on the specific background; for example, for dimensional deviations, specific backgrounds depended on include but are not limited to national standards on dimensional tolerances.

## Claims

1. A pet toy, comprising a jacking component, a power component, a toy base pad and a deformable connecting wire, wherein the jacking component comprises a reset structure, a rocker base and a rocker member hinged with the rocker base; the rocker member comprises a driven end, and there is a connecting wire actuating arm from the connecting wire to an axis of the hinged joint between the rocker member and the rocker base; the reset structure is connected to the rocker member and the rocker base, respectively, so that the driven end has a tendency of approaching the rocker base; the power component comprises a sliding end; two ends of the connecting wire are respectively a pulling end and a sliding end; the pulling end is connected to the driven end, and the sliding end is connected to the sliding member wherein the rocker member comprises a hinged end provided with a hinged shaft, the rocker base comprises a protrusion for hinging provided with a hinged groove, and the hinged shaft is inserted into the hinged groove.
2. The pet toy according to claim 1, wherein the rocker base is fixed to a front side of the toy base pad, and the power component is fixedly connected to the toy base pad.
3. The pet toy according to claim 2, wherein it further comprises a covering layer fixed to the front side of the toy base pad, where the connecting wire passes between the covering layer and the toy base pad.
4. The pet toy according to claim 3, wherein the reset structure is an elastic sheet fixedly connected to the rocker base, and is connected to the covering layer.
5. The pet toy according to claim 2, wherein the power component further comprises a rotating base and a rotating member provided with a bracing part; the rotating member is hinged with the rotating base and has rotational power, and the sliding member is slidably connected to the rotating base, which has a radial vector; when the rotating member rotates, the bracing part braces the sliding member and keeps the sliding member away from an axis of the rotating member.
6. The pet toy according to claim 5, wherein there are a plurality of jacking components, connecting wires and sliding members.
7. The pet toy according to claim 6, wherein the sliding members are linearly slidably connected to

the rotating base; all linear sliding connections between the sliding members and the rotating base point to the axis of the rotating member.

8. The pet toy according to claim 5, wherein when viewed from above, the connecting wires and the rocker members of all jacking components pass through the axis of the rotating member.

9. The pet toy according to claim 8, wherein all jacking components and sliding members are distributed uniformly around the axis of the rotating member.

10. The pet toy according to claim 7, wherein the rotating base is provided with a plurality of connecting wire ports, which are located on one side of the rotating member, and the connecting wires pass through the connecting wire ports, respectively.

11. The pet toy according to claim 10, wherein a maximum distance between two jacking components is a maximum distance among the jacking components, a maximum distance between two connecting wire ports is a maximum distance among the connecting wire ports, and the maximum distance among the connecting wire ports is less than the maximum distance among the jacking components.

12. The pet toy according to claim 10, wherein the rotating base is provided with a steering body, and the connecting wires between the connecting wire ports and the corresponding steering body are parallel to one another.

13. The pet toy according to claim 12, wherein a rotatable steering wheel fits over the steering body, and the connecting wires bypass the steering wheel respectively.

14. The pet toy according to claim 12, wherein the rotating base is fixedly provided with a protective body, which is configured to prevent the connecting wires from approaching the steering body.

15. The pet toy according to claim 1, wherein the rocker member is located between the rocker base and the reset structure.

16. The pet toy according to claim 1, wherein the rocker base comprises a base sidewall, the rocker member is below or flush with the base sidewall when laid flat, and the reset structure is pressed against a top of the base sidewall.

17. The pet toy according to claim 1, wherein the rocker base is provided with a penetration port, and when viewed from above, there is an overlap between the hinged end and the penetration port, and the hinged groove is provided with an exposed port, and the hinged shaft can move upward and out of the exposed port.

---