

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389378
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Rajendran; Karupaiah et al.

SSB transmission for improving low SINR across network

Abstract

Disclosed is a method of transmitting Synchronization Signal Blocks (SSBs) in a Fifth-Generation (5G) New Radio (NR) cellular telecommunication Radio Access Network (RAN). The method is performed by a Radio Unit (RU) device and includes: transmitting first symbols from a first antenna in a first sector, two or more of the first symbols including a first SSB; transmitting second symbols from a second antenna in a second sector, two or more of the second symbols including a second SSB; and transmitting third symbols from a third antenna in a third sector, two or more of the third symbols including a third SSB. The transmitting is performed during a first time slot and a second time slot. The symbols including the first SSB, the symbols including the second SSB, and the symbols including the third SSB are transmitted during different time periods.

Inventors: Rajendran; Karupaiah (Highlands Ranch, CO), Amaya; Norberto (Littleton, CO)

Applicant: DISH Wireless L.L.C. (Englewood, CO)

Family ID: 1000008748366

Assignee: DISH WIRELESS L.L.C. (Englewood, CO)

Appl. No.: 17/886157

Filed: August 11, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240057041 A1	Feb. 15, 2024

Publication Classification

Int. Cl.: H04W72/04 (20230101); H04W48/08 (20090101); H04W72/044 (20230101); H04W72/23 (20230101)

U.S. Cl.:

CPC **H04W72/044** (20130101); **H04W48/08** (20130101); H04W72/23 (20230101)

Field of Classification Search

CPC: H04W (72/044); H04W (72/0453); H04W (48/08); H04W (56/001); H04W (72/23)

USPC: 370/329

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10305580	12/2018	Lee	N/A	H04L 25/03343
2022/0210844	12/2021	MolavianJazi	N/A	H04W 74/006
2022/0256487	12/2021	Liu	N/A	H04W 56/001
2023/0275628	12/2022	Ge	375/262	H04B 1/401
2023/0388900	12/2022	Sakhnini	N/A	H04W 56/001
2023/0422310	12/2022	Kim	N/A	H04W 72/0453

OTHER PUBLICATIONS

International Search Report and Written Opinion, dated Jan. 9, 2024, for International Patent Application No. PCT/US2023/029764. (20 pages). cited by applicant

3GPP Technical Specification Group Radio Access Network; 3GPP TS 38.211 V17.2.0; 2022; 136 pages. cited by applicant

3GPP Technical Specification Group Radio Access Network; 3GPP TS 38.213 V17.2.0; 2022; 256 pages. cited by applicant

Invitation to Pay Additional Fees, dated Nov. 10, 2023, for International Patent Application No. PCT/US2023/029764. (16 pages). cited by applicant

Primary Examiner: Chang; Jungwon

Attorney, Agent or Firm: Seed IP Law Group LLP

Background/Summary

BACKGROUND

(1) Synchronization Signal Blocks (SSBs) are used in Fifth Generation (5G) New Radio (NR) cellular telecommunication Radio Access Networks (RANs). An SSB occupies 240 subcarriers in the frequency domain and 4 symbols in the time domain. An SSB contains a Primary Synchronization Signal (PSS), a Secondary Synchronization Signal (SSS), and a Physical Broadcast Channel (PBCH). The PSS and SSS represent a Physical Cell Identity (PCI), and the PBCH carries a Master Information Block (MIB). SSBs are transmitted periodically from each cell in a cellular network. SSBs are transmitted by Radio Unit (RU) devices, which are served by a Distributed Unit (DU) device that is governed by a Central Unit (CU) device and can be configured with a periodicity of 5 ms to 160 ms (e.g., 5 ms, 10 ms, 20 ms, 40 ms, 80 ms, 160 ms).

(2) Conventionally, when beamforming is not used, SSBs are transmitted on different cells using

the same time and frequency resources. Therefore, there is a 100% probability of mutual SSB interference from adjacent cells in areas where coverage for those cells overlap. Thus, due to this interference the Signal to Noise Ratio (SNR) of the SSB signal that is received at a User Equipment (UE) device may degrade significantly in regions with coverage overlap from adjacent cells.

BRIEF SUMMARY

(3) According to the present disclosure, transmission of SSBs from adjacent cells is shifted in the time domain or in the frequency domain or in both time and frequency domains. When SSBs from adjacent cells are transmitted at different time slots using frequency resources that do not overlap or minimally overlap, there is a reduction of SSB-to-SSB interference, which results in an increased Signal to Interference Noise Ratio (SINR) at a UE device that is in a location where coverage areas for those adjacent cells overlap. For example, for NR Frequency Range 1 (FR1), SSB indices can be configured per sector such that different sectors use different SSB indices. Thus, SSB transmissions occur on different time slots and the probability of SSB interference in overlap regions decreases. Accordingly, Synchronization Signal (SS)-SINR is improved at receiving UE devices, which can improve user experience by providing improved quality across the cell coverage footprint and reducing the number of dropped calls.

(4) Results have shown that time shifting SSBs according to the present disclosure can result in a 9 dB to 13 dB plus improvement in SS-SINR at receiving UE devices compared to conventional methods of transmitting SSBs. Also, results have shown that frequency shifting SSBs according to the present disclosure can result in a 10 dB improvement in SS-SINR at receiving UE devices compared to conventional methods of transmitting SSBs.

(5) A method of transmitting Synchronization Signal Blocks (SSBs) in a Fifth-Generation (5G) New Radio (NR) cellular telecommunication Radio Access Network (RAN) according to the present disclosure may be characterized as including: transmitting, by a Radio Unit (RU) device, a first plurality of symbols from a first antenna in a first sector during a first time slot, where two or more of the first plurality of symbols include a first SSB; transmitting, by the RU device, a second plurality of symbols from a second antenna in a second sector during the first time slot, where two or more of the second plurality of symbols include a second SSB, and where the second sector is adjacent to the first sector; and transmitting, by the RU device, a third plurality of symbols from a third antenna in a third sector during a second time slot, where two or more of the third plurality of symbols include a third SSB, and where the third sector is adjacent to the second sector. The two or more of the first plurality of symbols that include the first SSB are transmitted during a first time period. The two or more of the second plurality of symbols that include the second SSB are transmitted during a second time period that is different from the first time period. The two or more of the third plurality of symbols that include the third SSB are transmitted during a third time period that is different from the first time period and the second time period.

(6) The first time period, the second time period, and the third time period may not overlap in time. The two or more of the first plurality of symbols that include the first SSB may be transmitted using a first plurality of frequency resources, the two or more of the second plurality of symbols that include the second SSB may be transmitted using a second plurality of frequency resources different from the first plurality of frequency resources, and the two or more of the third plurality of symbols that include the third SSB may be transmitted using a third plurality of frequency resources different from the first plurality of frequency resources and the second plurality of frequency resources. The first plurality of frequency resources, the second plurality of frequency resources, and the third plurality of frequency resources may not overlap in frequency. The first plurality of frequency resources, the second plurality of frequency resources, and the third plurality of frequency resources may partially overlap in frequency.

(7) The first plurality of symbols may be consecutive and the two or more of the first plurality of symbols that include the first SSB may begin at a first offset from a first one of the first plurality of symbols, the second plurality of symbols may be consecutive and the two or more of the second

plurality of symbols that include the second SSB may begin at a second offset from a first one of the second plurality of symbols, the third plurality of symbols may be consecutive and the two or more of the third plurality of symbols that include the third SSB may begin at a third offset from a first one of the third plurality of symbols, a number of symbols included in the first plurality of symbols, a number of symbols included in the second plurality of symbols, and a number of symbols included in the third plurality of symbols may be a same number, and the first offset, the second offset, and the third offset may be different.

(8) The method may further include: transmitting, by the RU device, a fourth plurality of symbols from a fourth antenna in a fourth sector during the first time slot and the second time slot, where two or more of the plurality of fourth symbols include a fourth SSB, where the fourth sector is adjacent to the third sector, and where the two or more of the fourth plurality of symbols that include the fourth SSB are transmitted during a fourth time period that is different from the first time period, the second time period, and the third time period.

(9) A method of transmitting Synchronization Signal Blocks (SSBs) in a Fifth-Generation (5G) New Radio (NR) cellular telecommunication Radio Access Network (RAN) according to the present disclosure may be characterized as including: transmitting, by a Radio Unit (RU) device, a first plurality of symbols from a first antenna in a first sector during a first time slot and a second time slot, where two or more of the first plurality of symbols include a first SSB; transmitting, by the RU device, a second plurality of symbols from a second antenna in a second sector during the first time slot and the second time slot, where two or more of the second plurality of symbols include a second SSB, and where the second sector is adjacent to the first sector; and transmitting, by the RU device, a third plurality of symbols from a third antenna in a third sector during the first time slot and the second time slot, where two or more of the third plurality of symbols include a third SSB, and where the third sector is adjacent to the second sector. The two or more of the first plurality of symbols that include the first SSB are transmitted using a first plurality of frequency resources. The two or more of the second plurality of symbols that include the second SSB are transmitted using a second plurality of frequency resources different from the first plurality of frequency resources. The two or more of the third plurality of symbols that include the third SSB are transmitted using a third plurality of frequency resources different from the first plurality of frequency resources and the second plurality of frequency resources.

(10) The first plurality of frequency resources, the second plurality of frequency resources, and the third plurality of frequency resources may not overlap in frequency.

(11) The first plurality of frequency resources, the second plurality of frequency resources, and the third plurality of frequency resources may partially overlap in frequency.

(12) The first plurality of symbols may be consecutive and the two or more of the first plurality of symbols that include the first SSB may begin at a first offset from a first one of the first plurality of symbols. The second plurality of symbols may be consecutive and the two or more of the second plurality of symbols that include the second SSB may begin at a second offset from a first one of the second plurality of symbols. The third plurality of symbols may be consecutive and the two or more of the third plurality of symbols that include the third SSB may begin at a third offset from a first one of the third plurality of symbols. A number of symbols included in the first plurality of symbols, a number of symbols included in the second plurality of symbols, and a number of symbols included in the third plurality of symbols may be a same number, and the first offset, the second offset, and the third offset may be different.

(13) The method may further include: transmitting, by the RU device, a fourth plurality of symbols from a fourth antenna in a fourth sector during the first time slot and the second time slot, where two or more of the plurality of fourth symbols include a fourth SSB, where the fourth sector is adjacent to the third sector, and where the two or more of the fourth plurality of symbols that include the fourth SSB are transmitted using a fourth plurality of frequency resources different from the first plurality of frequency resources, the second plurality of frequency resources, and the

third plurality of frequency resources.

(14) A method of transmitting Synchronization Signal Blocks (SSBs) in a Fifth-Generation (5G) New Radio (NR) cellular telecommunication Radio Access Network (RAN) according to the present disclosure may be characterized as including: transmitting, by a Radio Unit (RU) device, a first beam including a first plurality of symbols from a first antenna in a first sector during a first time slot and a second time slot, where two or more of the first plurality of symbols include a first SSB; transmitting, by the RU device, a second beam including a second plurality of symbols from the first antenna in the first sector during the first time slot and the second time slot, where two or more of the second plurality of symbols include a second SSB; transmitting, by the RU device, a third beam including a third plurality of symbols from the first antenna in the first sector during the first time slot and the second time slot, where two or more of the third plurality of symbols include a third SSB; transmitting, by the RU device, a fourth beam including a fourth plurality of symbols from a second antenna in a second sector during the first time slot and the second time slot, where two or more of the fourth plurality of symbols include a fourth SSB, and where the second sector is adjacent to the first sector; transmitting, by the RU device, a fifth beam including a fifth plurality of symbols from the second antenna in the second sector during the first time slot and the second time slot, where two or more of the fifth plurality of symbols include a fifth SSB; transmitting, by the RU device, a sixth beam including a sixth plurality of symbols from the second antenna in the second sector during the first time slot and the second time slot, where two or more of the sixth plurality of symbols include a sixth SSB; transmitting, by the RU device, a seventh beam including a seventh plurality of symbols from a third antenna in a third sector during the first time slot and the second time slot, where two or more of the seventh plurality of symbols include a seventh SSB, and where the third sector is adjacent to the second sector; transmitting, by the RU device, an eighth beam including an eighth plurality of symbols from the third antenna in the third sector during the first time slot and the second time slot, where two or more of the eighth plurality of symbols include an eighth SSB; and transmitting, by the RU device, a ninth beam including a ninth plurality of symbols from the third antenna in the third sector during the first time slot and the second time slot, where two or more of the ninth plurality of symbols include a ninth SSB. The two or more of the first plurality of symbols that include the first SSB, the two or more of the fourth plurality of symbols that include the fourth SSB, and the two or more of the seventh plurality of symbols that include the seventh SSB are transmitted during a first time period. The two or more of the second plurality of symbols that include the second SSB, the two or more of the fifth plurality of symbols that include the fifth SSB, and the two or more of the eighth plurality of symbols that include the eighth SSB are transmitted during a second time period that is different from the first time period. The two or more of the third plurality of symbols that include the third SSB, the two or more of the sixth plurality of symbols that include the sixth SSB, and the two or more of the ninth plurality of symbols that include the ninth SSB are transmitted during a third time period that is different from the first time period and the second time period.

(15) The first time period, the second time period, and the third time period may not overlap in time.

(16) Information included in the first SSB may be same as information included in the second SSB, and information included in the third SSB may be same as the information included in the second SSB.

(17) The first plurality of symbols may be consecutive and the two or more of the first plurality of symbols that include the first SSB may begin at a first offset from a first one of the first plurality of symbols, the second plurality of symbols may be consecutive and the two or more of the second plurality of symbols that include the second SSB may begin at a second offset from a first one of the second plurality of symbols, the third plurality of symbols may be consecutive and the two or more of the third plurality of symbols that include the third SSB may begin at a third offset from a first one of the third plurality of symbols, a number of symbols included in the first plurality of

symbols, a number of symbols included in the second plurality of symbols, and a number of symbols included in the third plurality of symbols may be a same number, and the first offset, the second offset, and the third offset may be different.

(18) The two or more of the first plurality of symbols that include the first SSB, the two or more of the fourth plurality of symbols that include the fourth SSB, and the two or more of the seventh plurality of symbols that include the seventh SSB may be transmitted using a first plurality of frequency resources, the two or more of the second plurality of symbols that include the second SSB, the two or more of the fifth plurality of symbols that include the fifth SSB, and the two or more of the eighth plurality of symbols that include the eighth SSB may be transmitted using a second plurality of frequency resources that is different from the first plurality of frequency resources, the two or more of the third plurality of symbols that include the third SSB, the two or more of the sixth plurality of symbols that include the sixth SSB, and the two or more of the ninth plurality of symbols that include the ninth SSB may be transmitted using a third plurality of frequency resources different from the first plurality of frequency resources and the second plurality of frequency resources.

(19) The first plurality of frequency resources, the second plurality of frequency resources, and the third plurality of frequency resources may not overlap in frequency, or may partially overlap in frequency.

(20) The method may further include: transmitting, by the RU device, a tenth beam including a tenth plurality of symbols from the first antenna in the first sector during the first time slot and the second time slot, where two or more of the tenth plurality of symbols include a tenth SSB; transmitting, by the RU device, an eleventh beam including an eleventh plurality of symbols from the second antenna in the second sector during the first time slot and the second time slot, where two or more of the eleventh plurality of symbols include an eleventh SSB; and transmitting, by the RU device, a twelfth beam including a twelfth plurality of symbols from the third antenna in the third sector during the first time slot and the second time slot, where two or more of the ninth plurality of symbols include a twelfth SSB, where the two or more of the tenth plurality of symbols that include the tenth SSB are transmitted during the first time period, where the two or more of the eleventh plurality of symbols that include the eleventh SSB are transmitted during the second time period, and where the two or more of the twelfth plurality of symbols that include the twelfth SSB are transmitted during the third time period.

(21) The method may further include: transmitting, by the RU device, a tenth beam including a tenth plurality of symbols from a fourth antenna in a fourth sector during a first time slot and a second time slot, where two or more of the first plurality of symbols include a tenth SSB, and where the fourth sector is adjacent to the third sector; transmitting, by the RU device, an eleventh beam including an eleventh plurality of symbols from the fourth antenna in the fourth sector during the first time slot and the second time slot, where two or more of the eleventh plurality of symbols include an eleventh SSB; and transmitting, by the RU device, a twelfth beam including a twelfth plurality of symbols from the fourth antenna in the fourth sector during the first time slot and the second time slot, where two or more of the twelfth plurality of symbols include a twelfth SSB, where the two or more of the tenth plurality of symbols that include the tenth SSB are transmitted during the first time period, where the two or more of the eleventh plurality of symbols that include the eleventh SSB are transmitted during the second time period, and where the two or more of the twelfth plurality of symbols that include the twelfth SSB are transmitted during the third time period.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

- (1) Non-limiting and non-exhaustive embodiments are described with reference to the following drawings. In the drawings, like reference numerals refer to like parts throughout the various figures unless otherwise specified.
- (2) For a better understanding of the present disclosure, reference will be made to the following Detailed Description, which is to be read in association with the accompanying drawings.
- (3) FIG. 1 is a block diagram illustrating a communication system in accordance with embodiments described herein.
- (4) FIG. 2 is a diagram for explaining operation of a communication system in accordance with embodiments described herein.
- (5) FIG. 3 is a diagram for explaining operation of a communication system in accordance with embodiments described herein.
- (6) FIG. 4 is a diagram for explaining operation of a communication system in accordance with embodiments described herein.
- (7) FIG. 5 is a diagram for explaining operation of a communication system in accordance with embodiments described herein.
- (8) FIG. 6 is a block diagram illustrating an example of a Radio Unit (RU) device in accordance with embodiments described herein.
- (9) FIG. 7 is a block diagram illustrating an example of a Distributed Unit (DU) device in accordance with embodiments described herein.
- (10) FIG. 8 is a block diagram illustrating an example of a Centralized Unit (CU) device in accordance with embodiments described herein.
- (11) FIG. 9 illustrates a logical flow diagram showing an example of a method of operating a RU device in accordance with embodiments described herein.
- (12) FIG. 10 illustrates a logical flow diagram showing another example of a method of operating a RU device in accordance with embodiments described herein.

DETAILED DESCRIPTION

- (13) FIG. 1 is a block diagram illustrating a communication system **100** in accordance with embodiments described herein. The communication system **100** includes a Centralized Unit (CU) device **102** that controls and coordinates operation of a plurality of Distributed Unit (DU) devices, including a DU device **104a**, a DU device **104b**, and a DU device **104c**.
- (14) The DU device **104a** controls and coordinates operation of a plurality of Radio Unit (RU) devices, including an RU device **106a**, an RU device **106b**, and an RU device **106c**. For example, based on control information received from the CU device **102**, the DU device **104a** provides control information to the RU device **106a**, the RU device **106b**, and the RU device **106c**, which causes the RU device **106a**, the RU device **106b**, and the RU device **106c** to transmit Synchronization Signal Blocks (SSBs) at times or timings indicated by the control information and using frequency resources indicated by the control information.
- (15) In one or more implementations, the DU device **104a** provides control information to the RU device **106a**, the RU device **106b**, and the RU device **106c**, which cause the RU device **106a**, the RU device **106b**, and the RU device **106c** to transmit SSBs according to 3GPP TS 38.213 V17.2.0 (2022-06) using specified Resource Elements (REs) or Physical Resource Blocks (PRBs), which are mentioned in 3GPP TS 38.211 V17.2.0 (2022-06), for example. The contents of 3GPP TS 38.211 V17.2.0 (2022-06) and 3GPP TS 38.213 V17.2.0 (2022-06) are incorporated by reference herein.
- (16) In one or more implementations, control information provided by the DU device **104a** specifies frequency resources for respective SSBs, wherein there is no overlap between the frequency resources for respective SSBs. In one or more implementations, control information provided by the DU device **104a** specifies frequency resources for respective SSBs, wherein there

is some overlap between the frequency resources for respective SSBs. For example, for a 10 MHz system, in which 20 RBs are specified per SSB, out of 52 available RBs, there is a minimum overlap between frequency resources for respective SSBs.

(17) The DU device **104b** controls and coordinates operation of a plurality of RU devices, including an RU device **106d**, an RU device **106e**, and an RU device **106f**. For example, based on control information received from the CU device **102**, the DU device **104a** provides control information to the RU device **106d**, the RU device **106e**, and the RU device **106f**, which causes the RU device **106d**, the RU device **106e**, and the RU device **106f** to transmit SSBs at times or timings indicated by the control information and using frequency resources indicated by the control information.

(18) Also, the DU device **104c** controls and coordinates operation of a plurality of RU devices, including an RU device **106g**, an RU device **106h**, and an RU device **106i**. For example, based on control information received from the CU device **102**, the DU device **104a** provides control information to the RU device **106g**, the RU device **106h**, and the RU device **106i**, which causes the RU device **106g**, the RU device **106h**, and the RU device **106i** to transmit SSBs at times or timings indicated by the control information and using frequency resources indicated by the control information.

(19) In addition, the DU device **104a**, the DU device **104b**, the DU device **104c**, the RU device **106a**, the RU device **106b**, the RU device **106c**, the RU device **106d**, the RU device **106e**, the RU device **106f**, the RU device **106g**, the RU device **106h**, and the RU device **106i** are part of a Radio Access Network (RAN) **100**. In one or more implementations, the CU device **102** part of a 5G Core Network that is implemented in a public cloud environment (e.g., Amazon Web Service).

(20) FIG. 2 is a diagram for explaining operation of a communication system in accordance with embodiments described herein. More particularly, FIG. 2 shows an area **200** that includes a first coverage area **202** in which the RU device **106a** is disposed, and a second coverage area **204** in which the RU device **106d** is disposed. The first coverage area **202** and the second coverage area **204** overlap in an overlap area **206**. A User Equipment (UE) device **208** is located in the overlap area **206**. In one or more implementations, each of the RU device **106a** and the RU device **106d** are part of a 5G NR gNodeB (gNB) device (e.g., base station device).

(21) If the RU device **106a** and the RU device **106d** were to simultaneously transmit SSBs using the same frequency resources (e.g., PRBs) to the UE device **208** would receive the SSBs with a low SINR. Accordingly, the RU device **106a** and the RU device **106d** do not simultaneously transmit SSBs using the same frequency resources (e.g., PRBs) to the UE device **208** in order to improve the SINR at which the SSBs are received at the UE device **208**.

(22) FIG. 3 is a diagram for explaining operation of a communication system in accordance with embodiments described herein. FIG. 3 shows an example of a Radio Frequency (RF) radiation pattern **300**, which can be produced by each of the RU device **106a**, the RU device **106b**, the RU device **106c**, the RU device **106d**, the RU device **106e**, the RU device **106f**, the RU device **106g**, the RU device **106h**, and the RU device **106i** shown in FIG. 1. FIG. 3 includes a first antenna **302**, a second antenna **304**, and a third antenna **306** by which one of the RU device **106a**, the RU device **106b**, the RU device **106c**, the RU device **106d**, the RU device **106e**, the RU device **106f**, the RU device **106g**, the RU device **106h**, and the RU device **106i** shown in FIG. 1 transmits information, including SSBs. The first antenna **302**, the second antenna **304**, and the third antenna **306** are fixed and orientated such that the first antenna **302** transmits RF signals in a first sector **308**, the second antenna **302** transmits RF signals in a second sector **310**, and the third antenna **302** transmits RF signals in a third sector **312**. Each of the first sector **308**, the second sector **310**, and the third sector **312** has a central angle of 120 degrees

(23) As shown in FIG. 3, the first sector **308** is adjacent to the second sector **310** and the third sector **312**. Also, the second sector **310** is adjacent to the first sector **308** and the third sector **312**. In addition, the third sector **312** is adjacent to the first sector **308** and the second sector **310**.

(24) The RF radiation pattern **300** is an example of one of many radiation patterns according to the present disclosure. Radiation patterns according to the present disclosure may include sectors having central angle that are bigger or smaller than 120 degrees. For example, if an additional (i.e., fourth antenna) is used, each of four resulting sectors would a central angle of 90 degrees.

(25) FIG. 4 is a diagram for explaining operation of a communication system in accordance with embodiments described herein. FIG. 4 shows an example of a Radio Frequency (RF) radiation pattern **400**, which can be produced by each of the RU device **106a**, the RU device **106b**, the RU device **106c**, the RU device **106d**, the RU device **106e**, the RU device **106f**, the RU device **106g**, the RU device **106h**, and the RU device **106i** shown in FIG. 1. FIG. 4 includes a first antenna **402**, a second antenna **404**, and a third antenna **406** by which one of the RU device **106a**, the RU device **106b**, the RU device **106c**, the RU device **106d**, the RU device **106e**, the RU device **106f**, the RU device **106g**, the RU device **106h**, and the RU device **106i** shown in FIG. 1 can transmit information, including SSBs. The first antenna **402**, the second antenna **404**, and the third antenna **406** are fixed and orientated such that the first antenna **402** transmits RF signals in a first sector **408**, the second antenna **404** transmits RF signals in a second sector **410**, and the third antenna **406** transmits RF signals in a third sector **412**. Each of the first sector **408**, the second sector **410**, and the third sector **412** has a central angle of 120 degrees.

(26) More particularly, the first antenna **402** uses beamforming techniques to form a first beam **414a**, a second beam **414b**, a third beam **414c**, and a fourth beam **414d**, which are transmitted in the first sector **408**. Each of the first beam **414a**, second beam **414b**, third beam **414c**, and fourth beam **414d** forms a central angle of 30 degrees with an adjacent one of those beams.

(27) The second antenna **404** uses beamforming techniques to form a first beam **416a**, a second beam **416b**, a third beam **416c**, and a fourth beam **416d**, which are transmitted in the second sector **410**. Each of the first beam **416a**, second beam **416b**, third beam **416c**, and fourth beam **416d** forms a central angle of 30 degrees with an adjacent one of those beams.

(28) The third antenna **406** uses beamforming techniques to form a first beam **418a**, a second beam **418b**, a third beam **418c**, and a fourth beam **418d**, which are transmitted in the third sector **412**. Each of the first beam **418a**, second beam **418b**, third beam **418c**, and fourth beam **418d** forms a central angle of 30 degrees with an adjacent one of those beams.

(29) Although FIG. 4 shows each of the antennas **402**, **402**, **404** forming four beams, the antennas **402**, **402**, **404** may form fewer or additional beams without departing from the scope of the present disclosure. Additionally, the RF radiation pattern **400** is an example of one of many radiation patterns according to the present disclosure. Radiation patterns according to the present disclosure may include sectors having central angle that are bigger or smaller than 120 degrees. For example, if an additional (i.e., fourth antenna) is used, each of four resulting sectors would a central angle of 90 degrees.

(30) FIG. 5 is a diagram for explaining operation of a communication system in accordance with embodiments described herein. FIG. 5 shows an example of a transmission **500** of a plurality of symbols **502** (only one of which is labeled in FIG. 5 for illustrative simplicity). The symbols are transmitted during a first slot Slot 0 and a second slot Slot 1, each of which includes fourteen symbols, which are numbered 0 to 13 in FIG. 5. As shown in FIG. 5, a first SSB having an SSB index of 0 (i.e., SSB(0)) can be transmitted during a first time period t_0 using symbols numbered 2 through 5 of the first slot Slot 0, a second SSB having an SSB index of 1 (i.e., SSB(1)) can be transmitted during a second time period t_1 using symbols numbered 8 through 11 of the first slot Slot 0, a third SSB having an SSB index of 2 (i.e., SSB(2)) can be transmitted during a third time period t_1 using symbols numbered 2 through 5 of the second slot Slot 1, and a fourth SSB having an SSB index of 3 (i.e., SSB(3)) can be transmitted using symbols numbered 2 through 5 of the second slot Slot 1.

(31) In one or more implementations, an RU device (e.g., RU device **106a**) causes the first antenna **302** shown in FIG. 3 to transmit the first SSB having the SSB index of 0 (i.e., SSB(0)) using

symbols numbered 2 through 5 of the first slot Slot 0. Also, the RU device causes the second antenna **304** shown in FIG. **3** to transmit the second SSB having the SSB index of 1 (i.e., SSB(1)) using symbols numbered 8 through 11 of the first slot Slot 0. In addition, the RU device causes the third antenna **306** shown in FIG. **3** to transmit the third SSB having the SSB index of 2 (i.e., SSB(2)) using symbols numbered 2 through 5 of the second slot Slot 1. Thus, the SSBs transmitted by the antennas **302**, **304**, and **306** are transmitted at different times. In other words, the SSBs transmitted by the antennas **302**, **304**, and **306** are transmitted during three non-overlapping time periods (e.g., t_0 , t_1 , and t_2). Accordingly, interference at a UE device (e.g., UE device **208**) is reduced compared to conventional techniques in which the SSBs are transmitted at the same time.

(32) In one or more implementations in which beamforming is not used, an RU device (e.g., RU device **106a**) causes the first antenna **402** shown in FIG. **4** to transmit the SSB having the SSB index of 0 (i.e., SSB(0)) using symbols numbered 2 through 5 of the first slot Slot 0. Also, the RU device causes the second antenna **404** shown in FIG. **4** to transmit the SSB having the SSB index of 1 (i.e., SSB(1)) using symbols numbered 8 through 11 of the first slot Slot 0. In addition, the RU device causes the third antenna **406** shown in FIG. **4** to transmit the SSB having the SSB index of 2 (i.e., SSB(2)) using symbols numbered 2 through 5 of the second slot Slot 1.

(33) FIG. **6** is a block diagram illustrating an example of a Radio Unit (RU) device **106** in accordance with embodiments described herein. In some embodiments, one or more special-purpose computing systems may be used to implement the RU device **106**. Accordingly, various embodiments described herein may be implemented in software, hardware, firmware, or in some combination thereof. The RU device **106** may include one or more memory devices **604**, one or more central processing units (CPUs) **610**, I/O interfaces **612**, other computer-readable media **614**, and network connections **616**.

(34) The one or more memory devices **604** may include one or more various types of non-volatile and/or volatile storage technologies. Examples of the one or more memory devices **604** may include, but are not limited to, flash memory, hard disk drives, optical drives, solid-state drives, various types of random access memory (RAM), various types of read-only memory (ROM), other computer-readable storage media (also referred to as processor-readable storage media), or the like, or any combination thereof. The one or more memory devices **604** may be utilized to store information, including computer-readable instructions that are utilized by the one or more CPUs **610** to perform actions, including those of embodiments described herein.

(35) The one or more memory devices **604** may have stored thereon a Radio Unit (RU) module **606**. The Radio Unit (RU) module **606** is configured to implement and/or perform some or all of the functions of the RU device **106** described herein and interface with radio transceiver **618**. The one or more memory devices **604** may also store other programs and data **608**, which may include RU digital certificates, connection recovery algorithms, connection recovery rules, network protocols, O-RAN operating rules, user interfaces, operating systems, etc.

(36) Network connections **616** are configured to communicate with other computing devices including a Distributed Unit (DU) device. In various embodiments, the network connections **616** include transmitters and receivers, a layer 2 (L2) switch and physical network ports (not illustrated) to send and receive data as described herein, and to send and receive instructions, commands and data to implement the processes described herein. The L2 switch plays a role as Ethernet forwarding/transparent bridge in order to support Radio Unit (RU) copy and combine function for O-RAN cascade mode. I/O interfaces **612** may include enhanced Common Public Radio Interface (eCPRI) ports, Antenna Interface Standards Group (AISG) interfaces, other data input or output interfaces, or the like. Other computer-readable media **614** may include other types of stationary or removable computer-readable media, such as removable flash drives, external hard drives, or the like.

(37) The radio transceiver **618** transmits and receives signals in the 5G NR frequency bands, including the Frequency Range 1 (FR1) bands, which includes sub-6 GHz frequency bands, and

Frequency Range 2 bands, which includes frequency bands from 24.25 GHz to 71.0 GHz. In one or more implementations, the radio transceiver **618** transmits and receives information using Multiple Input Multiple Output (MIMO) radio link technology. In one or more implementations, the radio transceiver **618** includes one or more oscillators, radio frequency (RF) filters, amplifiers, beamforming circuitry, and antennas arranged to perform 5G NR communications.

(38) FIG. 7 is a block diagram illustrating an example of a Distributed Unit (DU) device **104** in accordance with embodiments described herein. In some embodiments, one or more special-purpose computing systems may be used to implement the Distributed Unit (DU) device **104**. Accordingly, various embodiments described herein may be implemented in software, hardware, firmware, or in some combination thereof. The DU device **104** may include one or more memory devices **704**, one or more central processing units (CPUs) **710**, I/O interfaces **712**, other computer-readable media **714**, and network connections **716**.

(39) The one or more memory devices **704** may include one or more various types of non-volatile and/or volatile storage technologies. Examples of the one or more memory devices **704** may include, but are not limited to, flash memory, hard disk drives, optical drives, solid-state drives, various types of random access memory (RAM), various types of read-only memory (ROM), other computer-readable storage media (also referred to as processor-readable storage media), or the like, or any combination thereof. The one or more memory devices **704** may be utilized to store information, including computer-readable instructions that are utilized by the one or more CPUs **710** to perform actions, including those of embodiments described herein.

(40) The one or more memory devices **704** may have stored thereon a Distributed Unit (DU) module **706**. The Distributed Unit (DU) module **706** is configured to implement and/or perform some or all of the functions of the Distributed Unit (DU) **702** described herein. The one or more memory devices **704** may also store other programs and data **708**, which may include a Radio Link Control (RLC) module that implements a RLC sublayer of the 7G NR protocol stack, which interfaces to PDCP sublayer from above and MAC sublayer from below, a Media Access Control (MAC) module that implements a MAC sublayer of the 7G NR protocol stack, which interfaces to the RLC sublayer from above and a Physical (PHY) layer from below, and a PHY module that implements the PHY layer for Enhanced Mobile Broadband (eMBB) communications, Machine-Type-Communications (mMTC), and Ultra-Reliable Low Latency Communications (URLLC).

(41) Network connections **716** are configured to communicate with other computing devices including one or more Radio Unit (RU) devices, a Centralized Unit (CU) device, and a RAN Intelligent Controller (MC) device. In various embodiments, the network connections **716** include transmitters and receivers, a layer 3 (L2) switch and physical network ports (not illustrated) to send and receive data as described herein, and to send and receive instructions, commands and data to implement the processes described herein. The L2 switch plays a role as Ethernet forwarding/transparent bridge in order to support Radio Unit (RU) copy and combine function for O-RAN cascade mode. I/O interfaces **712** may include PCI interfaces, PCI-Express interfaces, other data input or output interfaces, or the like. Other computer-readable media **714** may include other types of stationary or removable computer-readable media, such as removable flash drives, external hard drives, or the like.

(42) FIG. 8 is a block diagram illustrating an example of a Centralized Unit (CU) device **102** in accordance with embodiments described herein. In some embodiments, one or more special-purpose computing systems may be used to implement the Centralized Unit (CU) device **102**. Accordingly, various embodiments described herein may be implemented in software, hardware, firmware, or in some combination thereof. The DU device **106** may include one or more memory devices **804**, one or more central processing units (CPUs) **810**, I/O interfaces **812**, other computer-readable media **814**, and network connections **816**.

(43) The one or more memory devices **804** may include one or more various types of non-volatile and/or volatile storage technologies. Examples of the one or more memory devices **804** may

include, but are not limited to, flash memory, hard disk drives, optical drives, solid-state drives, various types of random access memory (RAM), various types of read-only memory (ROM), other computer-readable storage media (also referred to as processor-readable storage media), or the like, or any combination thereof. The one or more memory devices **804** may be utilized to store information, including computer-readable instructions that are utilized by the one or more CPUs **810** to perform actions, including those of embodiments described herein.

(44) The one or more memory devices **804** may have stored thereon a Centralized Unit (CU) module **806**. The Centralized Unit (CU) module **806** is configured to implement and/or perform some or all of the functions of the Centralized Unit (CU) **802** described herein. The one or more memory devices **804** may also store other programs and data **808**, which may include Radio Resource Control (RRC) module that implements an RRC a layer within the 5G NR protocol stack in a control plane of a gNB, a Service Data Adaptation Protocol (SDAP) module that implements a sublayer in a plane in the gNB, and a Packet Data Convergence Protocol (PDCP) module that implements a PDCP layer within the 5G NR protocol stack.

(45) Network connections **816** are configured to communicate with other computing devices including one or more Radio Unit (RU) devices, one or more Distributed Unit (CU) devices, one or more devices that implement Access and Mobility Management Function (AMF) operations, and one or more devices that implement User Plane Function (UPF) operations. In one or more implementations, the network connections **816** includes connections made via N2, N3, F1-C, and F1-U interfaces, for example.

(46) FIG. **9** illustrates a logical flow diagram showing an example of a method **900** of operating an RU device in accordance with embodiments described herein. The method **900** begins at **902**.

(47) At **902**, an RU device transmits a first plurality of symbols from a first antenna in a first sector during a first time slot and a second time slot, wherein two or more of the first plurality of symbols include a first SSB. For example, at **902**, the RU device **106a** causes the first antenna **302** to transmit a first plurality of symbols in the sector **308** shown in FIG. **3**, during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. **5**, wherein SSB(0) is transmitted during the first time period t0 using symbols numbered 2 to 5 of the first time slot Slot 0. The method **900** then proceeds to **904**.

(48) At **904**, the RU device transmits a second plurality of symbols from a second antenna in a second sector during the first time slot and the second time slot, wherein two or more of the second plurality of symbols include a second SSB. For example, at **904**, the RU device **106a** causes the second antenna **304** to transmit a second plurality of symbols in the sector **310** shown in FIG. **3**, during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. **5**, wherein SSB(1) is transmitted during the second time period t1 using symbols numbered 8 to 11 of the first time slot Slot 0. The method **900** then proceeds to **906**.

(49) At **906**, the RU device transmits a third plurality of symbols from a third antenna in a third sector during the first time slot and the second time slot, wherein two or more of the third plurality of symbols include a third SSB. For example, at **906**, the RU device **106a** causes the third antenna **306** to transmit a third plurality of symbols in the sector **312** shown in FIG. **3**, during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. **5**, wherein SSB(2) is transmitted during the third time period t2 using symbols numbered 2 to 5 of the second time slot Slot 1. The method **900** then ends. In one or more implementation, **902**, **904**, and **906** are performed simultaneously.

(50) FIG. **10** illustrates a logical flow diagram showing an example of a method **1000** of operating an RU device in accordance with embodiments described herein. The method begins at **1002**.

(51) At **1002**, an RU device transmits a first beam including a first plurality of symbols from a first antenna in a first sector during a first time slot and a second time slot, wherein two or more of the first plurality of symbols include a first SSB. For example, at **1002**, the RU device **106a** causes the beam **414a** to include a first plurality of symbols and be transmitted from the first antenna **402** in the sector **408** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. **5**,

wherein SSB(0) is transmitted during the first time period t0 using symbols 2 to 5 of the first time slot Slot 0. The method **1000** then proceeds to **1004**.

(52) At **1004**, the RU device transmits a second beam including a second plurality of symbols from the first antenna in the first sector during the first time slot and the second time slot, wherein two or more of the second plurality of symbols include a second SSB. For example, at **1004** the RU device **106a** causes the beam **414b** to include a second plurality of symbols and be transmitted from the first antenna **402** in the sector **408** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(1) is transmitted during the second time period t1 using symbols 8 to 11 of the first time slot Slot 0. The method **1000** then proceeds to **1006**.

(53) At **1006**, the RU device transmits a third beam including a third plurality of symbols from the first antenna in the first sector during the first time slot and the second time slot, wherein two or more of the third plurality of symbols include a third SSB. For example, at **1006**, the RU device **106a** causes the beam **414c** to include a third plurality of symbols and be transmitted from the first antenna **402** in the sector **408** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(2) is transmitted during the third time period t2 using symbols 2 to 5 of the second time slot Slot 1. The method **1000** then proceeds to **1008**.

(54) At **1008**, the RU device transmits a fourth beam including a fourth plurality of symbols from the first antenna in the first sector during the first time slot and the second time slot, wherein two or more of the fourth plurality of symbols include a fourth SSB. For example, at **1008**, the RU device **106a** causes the beam **414c** to include a fourth plurality of symbols and be transmitted from the first antenna **402** in the sector **408** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(2) is transmitted during the fourth time period t3 using symbols 8 to 11 of the second time slot Slot 1. The method **1000** then proceeds to **1010**.

(55) At **1010**, an RU device transmits a fifth beam including a fifth plurality of symbols from a second antenna in a first sector during a first time slot and a second time slot, wherein two or more of the fifth plurality of symbols include a fifth SSB. For example, at **1010**, the RU device **106a** causes the beam **416a** to include a fifth plurality of symbols and be transmitted from the second antenna **404** in the sector **410** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(0) is transmitted during the first time period t0 using symbols 2 to 5 of the first time slot Slot 0. The method **1000** then proceeds to **1012**.

(56) At **1012**, the RU device transmits a sixth beam including a sixth plurality of symbols from the second antenna in the second sector during the first time slot and the second time slot, wherein two or more of the sixth plurality of symbols include a sixth SSB. For example, at **1012** the RU device **106a** causes the beam **416b** to include a sixth plurality of symbols and be transmitted from the second antenna **404** in the sector **410** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(1) is transmitted during the second time period t1 using symbols 8 to 11 of the first time slot Slot 0. The method **1000** then proceeds to **1014**.

(57) At **1014**, the RU device transmits a seventh beam including a seventh plurality of symbols from the second antenna in the second sector during the first time slot and the second time slot, wherein two or more of the seventh plurality of symbols include a seventh SSB. For example, at **1014**, the RU device **106a** causes the beam **416c** to include a seventh plurality of symbols and be transmitted from the second antenna **404** in the sector **410** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(2) is transmitted during the third time period t2 using symbols 2 to 5 of the second time slot Slot 1. The method **1000** then proceeds to **1016**.

(58) At **1016**, the RU device transmits an eighth beam including an eighth plurality of symbols from the second antenna in the second sector during the first time slot and the second time slot, wherein two or more of the eighth plurality of symbols include an eighth SSB. For example, at **1016**, the RU device **106a** causes the beam **416c** to include an eighth plurality of symbols and be transmitted from the second antenna **404** in the sector **410** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(2) is transmitted during the fourth time

period t3 using symbols 8 to 11 of the second time slot Slot 1. The method **1000** then proceeds to **1018**.

(59) At **1018**, an RU device transmits a ninth beam including a ninth plurality of symbols from a third antenna in a third sector during a first time slot and a second time slot, wherein two or more of the ninth plurality of symbols include a ninth SSB. For example, at **1018**, the RU device **106a** causes the beam **418a** to include a ninth plurality of symbols and be transmitted from the third antenna **406** in the sector **412** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(0) is transmitted during the first time period t0 using symbols 2 to 5 of the first time slot Slot 0. The method **1000** then proceeds to **1020**.

(60) At **1020**, the RU device transmits a tenth beam including a tenth plurality of symbols from the third antenna in the third sector during the first time slot and the second time slot, wherein two or more of the tenth plurality of symbols include a tenth SSB. For example, at **1020** the RU device **106a** causes the beam **418b** to include a tenth plurality of symbols and be transmitted from the third antenna **406** in the sector **412** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(1) is transmitted during the second time period t1 using symbols 8 to 11 of the first time slot Slot 0. The method **1000** then proceeds to **1022**.

(61) At **1022**, the RU device transmits an eleventh beam including an eleventh plurality of symbols from the third antenna in the third sector during the first time slot and the second time slot, wherein two or more of the eleventh plurality of symbols include an eleventh SSB. For example, at **1022**, the RU device **106a** causes the beam **418c** to include an eleventh plurality of symbols and be transmitted from the third antenna **406** in the sector **412** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(2) is transmitted during the third time period t2 using symbols 2 to 5 of the second time slot Slot 1. The method **1000** then proceeds to **1024**.

(62) At **1024**, the RU device transmits a twelfth beam including a twelfth plurality of symbols from the third antenna in the third sector during the first time slot and the second time slot, wherein two or more of the twelfth plurality of symbols include a twelfth SSB. For example, at **1024**, the RU device **106a** causes the beam **418c** to include a twelfth plurality of symbols and be transmitted from the third antenna **406** in the sector **412** during the first time slot Slot 0 and the second time slot Slot 1 shown in FIG. 5, wherein SSB(2) is transmitted during the fourth time period t3 using symbols 8 to 11 of the second time slot Slot 1. The method **1000** then ends. In one or more implementation, **1002**, **1004**, **1006**, **1008**, **1010**, **1012**, **1014**, **1016**, **1018**, **1020**, **1022**, and **1024** are performed simultaneously.

(63) The various embodiments described above can be combined to provide further embodiments. Aspects of the embodiments can be modified, if necessary to employ concepts of the various patents, applications and publications to provide yet further embodiments.

(64) These and other changes can be made to the embodiments in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the claims to the specific embodiments disclosed in the specification and the claims, but should be construed to include all possible embodiments along with the full scope of equivalents to which such claims are entitled. Accordingly, the claims are not limited by the disclosure.

Claims

1. A method of transmitting Synchronization Signal Blocks (SSBs) in a Fifth-Generation (5G) New Radio (NR) cellular telecommunication Radio Access Network (RAN), the method comprising: transmitting, by a Radio Unit (RU) device, a first plurality of symbols from a first antenna in a first sector during a first time slot, wherein two or more of the first plurality of symbols include a first SSB; transmitting, by the RU device, a second plurality of symbols from a second antenna in a second sector during the first time slot, wherein two or more of the second plurality of symbols include a second SSB, and wherein the second sector is adjacent to the first sector; and

transmitting, by the RU device, a third plurality of symbols from a third antenna in a third sector during a second time slot, wherein two or more of the third plurality of symbols include a third SSB, and wherein the third sector is adjacent to the second sector, and wherein the second time slot is separate from the first time slot, wherein the two or more of the first plurality of symbols that include the first SSB are transmitted during a first time period within the first time slot, wherein the two or more of the second plurality of symbols that include the second SSB are transmitted during a second time period within the first time slot, wherein the second time period is different from the first time period, and wherein the two or more of the third plurality of symbols that include the third SSB are transmitted during a third time period within the second time slot, wherein the third time period is different from the first time period and the second time period.

2. The method according to claim 1, wherein: the first time period, the second time period, and the third time period do not overlap in time.

3. The method according to claim 2, wherein: wherein the two or more of the first plurality of symbols that include the first SSB are transmitted using a first plurality of frequency resources, wherein the two or more of the second plurality of symbols that include the second SSB are transmitted using a second plurality of frequency resources different from the first plurality of frequency resources, and wherein the two or more of the third plurality of symbols that include the third SSB are transmitted using a third plurality of frequency resources different from the first plurality of frequency resources and the second plurality of frequency resources.

4. The method according to claim 3, wherein: the first plurality of frequency resources, the second plurality of frequency resources, and the third plurality of frequency resources do not overlap in frequency.

5. The method according to claim 3, wherein: the first plurality of frequency resources, the second plurality of frequency resources, and the third plurality of frequency resources partially overlap in frequency.

6. The method according to claim 1, wherein: the first plurality of symbols are consecutive and the two or more of the first plurality of symbols that include the first SSB begin at a first offset from a first one of the first plurality of symbols, the second plurality of symbols are consecutive and the two or more of the second plurality of symbols that include the second SSB begin at a second offset from a first one of the second plurality of symbols, the third plurality of symbols are consecutive and the two or more of the third plurality of symbols that include the third SSB begin at a third offset from a first one of the third plurality of symbols, a number of symbols included in the first plurality of symbols, a number of symbols included in the second plurality of symbols, and a number of symbols included in the third plurality of symbols are a same number, and the first offset, the second offset, and the third offset are different.

7. The method according to claim 1, further comprising: transmitting, by the RU device, a fourth plurality of symbols from a fourth antenna in a fourth sector during the first time slot and the second time slot, wherein two or more of the plurality of fourth symbols include a fourth SSB, and wherein the fourth sector is adjacent to the third sector, wherein the two or more of the fourth plurality of symbols that include the fourth SSB are transmitted during a fourth time period that is different from the first time period, the second time period, and the third time period.

8. A method of transmitting Synchronization Signal Blocks (SSBs) in a Fifth-Generation (5G) New Radio (NR) cellular telecommunication Radio Access Network (RAN), the method comprising: transmitting, by a Radio Unit (RU) device, a first plurality of symbols from a first antenna in a first sector during a first time slot and a second time slot, wherein two or more of the first plurality of symbols include a first SSB; transmitting, by the RU device, a second plurality of symbols from a second antenna in a second sector during the first time slot and the second time slot, wherein two or more of the second plurality of symbols include a second SSB, and wherein the second sector is adjacent to the first sector; and transmitting, by the RU device, a third plurality of symbols from a third antenna in a third sector during the first time slot and the second time slot, wherein two or

more of the third plurality of symbols include a third SSB, and wherein the third sector is adjacent to the second sector, and wherein the second time slot is separate from the first time slot, wherein the two or more of the first plurality of symbols that include the first SSB are transmitted using a first plurality of frequency resources during a first time period, wherein the two or more of the second plurality of symbols that include the second SSB are transmitted using a second plurality of frequency resources during a second time period, wherein the second plurality of frequency resources are different from the first plurality of frequency resources, and wherein the two or more of the third plurality of symbols that include the third SSB are transmitted using a third plurality of frequency resources during a second time period, wherein the third plurality of frequency resources are different from the first plurality of frequency resources and the second plurality of frequency resources.

9. The method according to claim 8, wherein: the first plurality of frequency resources, the second plurality of frequency resources, and the third plurality of frequency resources do not overlap in frequency.

10. The method according to claim 8, wherein: the first plurality of frequency resources, the second plurality of frequency resources, and the third plurality of frequency resources partially overlap in frequency.

11. The method according to claim 8, wherein: the first plurality of symbols are consecutive and the two or more of the first plurality of symbols that include the first SSB begin at a first offset from a first one of the first plurality of symbols, the second plurality of symbols are consecutive and the two or more of the second plurality of symbols that include the second SSB begin at a second offset from a first one of the second plurality of symbols, the third plurality of symbols are consecutive and the two or more of the third plurality of symbols that include the third SSB begin at a third offset from a first one of the third plurality of symbols, a number of symbols included in the first plurality of symbols, a number of symbols included in the second plurality of symbols, and a number of symbols included in the third plurality of symbols are a same number, and the first offset, the second offset, and the third offset are different.

12. The method according to claim 8, further comprising: transmitting, by the RU device, a fourth plurality of symbols from a fourth antenna in a fourth sector during the first time slot and the second time slot, wherein two or more of the plurality of fourth symbols include a fourth SSB, and wherein the fourth sector is adjacent to the third sector, wherein the two or more of the fourth plurality of symbols that include the fourth SSB are transmitted using a fourth plurality of frequency resources different from the first plurality of frequency resources, the second plurality of frequency resources, and the third plurality of frequency resources.
