

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250254958

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Shinohara; Keisuke et al.

---

### **LATERALLY-GATED TRANSISTORS AND LATERAL SCHOTTKY DIODES WITH INTEGRATED LATERAL FIELD PLATE STRUCTURES**

---

#### **Abstract**

Laterally-gated transistors and lateral Schottky diodes are disclosed. The FET includes a substrate, source and drain electrodes, channel, a gate electrode structure, and a dielectric layer. The gate electrode structure includes an electrode in contact with the channel and a lateral field plate adjacent to the electrode. The dielectric layer is disposed between the lateral field plate and the channel. The lateral field plate contacts the dielectric layer and to modulate an electric field proximal to the gate electrode proximal to the drain or source electrodes. Also disclosed is a gate electrode structure with lateral field plates symmetrically disposed relative to the gate electrode. Also disclosed in a substrate with dielectric structures buried in the substrate remote from the gate electrode structure. A lateral Schottky diode having an anode structure includes an anode (A), cathodes (C) and lateral field plates located between the anode and the cathodes.

---

**Inventors:** Shinohara; Keisuke (Thousand Oaks, CA), King; Casey (Newbury Park, CA), Regan; Eric (Moorpark, CA), Urteaga; Miguel (Moorpark, CA)

**Applicant:** Teledyne Scientific & Imaging, LLC (Thousand Oaks, CA)

**Family ID:** 77627517

**Appl. No.:** 19/186107

**Filed:** April 22, 2025

#### **Related U.S. Application Data**

parent US division 18609778 20240319 parent-grant-document US 12310080 child US 19186107  
parent US division 17022521 20200916 parent-grant-document US 11967619 child US 18609778

---

#### **Publication Classification**

**Int. Cl.:** H10D64/00 (20250101); H10D8/60 (20250101); H10D30/47 (20250101)

**U.S. Cl.:**

**CPC** H10D64/112 (20250101); H10D8/60 (20250101); H10D30/47 (20250101);

---

## **Background/Summary**

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a divisional application filed under 35 U.S.C. § 121 of U.S. patent application Ser. No. 18/609,778 entitled “LATERALLY-GATED TRANSISTORS AND LATERAL SCHOTTKY DIODES WITH INTEGRATED LATERAL FIELD PLATE STRUCTURES” filed on Mar. 19, 2024, which claims the benefit under 35 U.S.C. § 121 of U.S. patent application Ser. No. 17/022,521 entitled “LATERALLY-GATED TRANSISTORS AND LATERAL SCHOTTKY DIODES WITH INTEGRATED LATERAL FIELD PLATE STRUCTURES” filed on Sep. 16, 2020, now issued as U.S. Pat. No. 11,967,619. The entire disclosures of which are incorporated herein by reference in their entirety and for all purposes.

### **TECHNICAL FIELD**

[0003] This disclosure relates generally to field-effect transistors (FETs) with lateral field plates. More particularly, this disclosure relates to laterally-gated transistors with lateral field plates to modulate an electric field near a drain-end of a lateral gate in single- or multiple-channel transistors.

### **BACKGROUND**

[0004] In most conventional FETs, the gate electrode is disposed on top of the semiconductor surface to modulate the drain current by a vertical gate electric field. This forms a region at the drain end of the gate where an electric field strength becomes the largest during high voltage operation. This is a main cause of problems for traditional FETs. For example, current collapse caused by electron trapping near the high electric field region degrades power performance of the FET when it is biased at high drain voltages. This degrades RF power performance (output power, efficiency, linearity, gain) of FETs when they are operated to provide a large voltage swing. For GaN-based high electron mobility transistors (HEMTs) with strong piezoelectricity, the high vertical electric field at the drain end of the gate can cause cracks in the epitaxial layers by inducing tensile stress in the top barrier material (so-called “inverse piezoelectric effect”). This effect limits the reliability of GaN-based HEMTs. Other considerations regarding conventional FETs include device breakdown when the electric field strength exceeds the critical field of the materials and degraded device reliability due to defect formation by the high electric field at the drain end of the gate. Similar considerations apply to laterally-gated transistors.

[0005] In a conventional top-gated HEMT with a field plate, a dielectric layer is inserted between the field plate and the channel. The field plate alleviates an electric field near the drain-side of the gate contact. A conventional laterally-gated transistor can contain multiple channels to increase power density and current handling and to decrease transistor's on-resistance for high-power RF and power switching applications. Other transistors that employ lateral gates include FIN FETs, SLC FETs, and BRIDGE HEMT by Teledyne Scientific & Imaging, LLC.

### **SUMMARY**

[0006] In one aspect, the present disclosure provides a field-effect transistor (FET) comprising a substrate, source and drain electrodes on the substrate, a channel layer, a gate electrode structure, and a dielectric layer. The gate electrode structure comprises a gate electrode and a lateral field plate adjacent to the gate electrode. The gate electrode is in contact with the channel layer. The

dielectric layer is disposed between the lateral fieldplate and the channel layer. The lateral field plate is in contact with the dielectric layer and is configured to modulate an electric field proximal to the gate electrode proximal to at least one of or both the drain or source electrodes.

[0007] In another aspect, the present disclosure provides a field-effect transistor (FET) comprising a substrate, source and drain electrodes on the substrate, a channel layer, a gate electrode structure, and a dielectric layer. The gate electrode structure comprises a gate electrode, a first lateral field plate adjacent to one side of the gate electrode, and a second lateral field plate adjacent to an opposite side of the gate electrode. The gate electrode is in contact with the channel. The dielectric layer is disposed between the first and second lateral field plates and the channel layer. The first and second lateral field plates are disposed in a symmetrical arrangement relative to the gate electrode. The first and second lateral field plates are in contact with the dielectric layer and are configured to modulate an electric field proximal to the gate electrode proximal to at least one of or both the drain or source electrodes.

[0008] In another aspect, the present disclosure provides a field-effect transistor (FET) comprising a substrate, source and drain electrodes on the substrate, a channel layer, a gate electrode structure, a dielectric layer, and a dielectric structure buried in the substrate remote from the gate electrode structure. The gate electrode structure comprises a gate electrode and a lateral field plate adjacent to the gate electrode. The gate electrode is in contact with the channel layer. The dielectric layer is disposed between the lateral field plate and the channel layer. The lateral field plate is in contact with the dielectric layer and is configured to modulate an electric field proximal to the gate electrode proximal to at least one of or both the drain or source electrodes.

[0009] In various aspects, the FET may be, buried gate HEMT, FIN FET, or SLC FET.

[0010] In another aspect, the present disclosure provides a lateral Schottky diode, comprising: a substrate comprising a plurality of structures buried in apertures disposed in the substrate; an anode structure comprising: an anode; and lateral field plates; and a cathode located on a top surface of the substrate.

[0011] The foregoing is a summary and thus may contain simplifications, generalizations, inclusions, and/or omissions of detail; consequently, those skilled in the art will appreciate that the summary is illustrative only and is NOT intended to be in any way limiting. Other aspects, features, and advantages of the devices and/or processes and/or other subject matter described herein will become apparent in the teachings set forth herein.

[0012] In one or more various aspects, related systems include but are not limited to circuitry in virtually any combination of hardware to affect the herein-referenced transistors depending upon the design choices of the system designer. In addition to the foregoing, various other aspects are set forth and described in the teachings such as text (e.g., claims and/or detailed description) and/or drawings of the present disclosure.

[0013] Further, it is understood that any one or more of the following-described forms, expressions of forms, examples, can be combined with any one or more of the other following-described forms, expressions of forms, and examples.

[0014] The foregoing summary is illustrative only and is not intended to be in any way limiting. In addition to the illustrative aspects, embodiments, and features described above, further aspects, embodiments, and features will become apparent by reference to the drawings and the following detailed description.

---

## Description

### FIGURES

[0015] The novel features of the described forms are set forth with particularity in the appended claims. The described forms, however, both as to organization and methods of operation, may be

best understood by reference to the following description, taken in conjunction with the accompanying drawings in which:

[0016] FIG. **1** is a cross-sectional view of a top gate HEMT with a gate electrode without a lateral field plate.

[0017] FIG. **2** is a perspective sectional view of a buried gate HEMT with a gate electrode without a lateral field plate.

[0018] FIG. **3** is a cross-sectional view of a top gate HEMT with a gate electrode structure comprising a gate electrode and a single lateral field plate according to at least one aspect of the present disclosure.

[0019] FIG. **4** is a perspective sectional view of a buried gate HEMT with a gate electrode structure comprising a gate electrode and a single lateral field plate arranged in an asymmetric configuration according to at least one aspect of the present disclosure.

[0020] FIG. **5** is a top view of the buried gate HEMT with a gate electrode structure comprising a gate electrode and a single lateral field plate arranged in an asymmetric configuration as shown in FIG. **4** according to at least one aspect of the present disclosure.

[0021] FIG. **6** is a top view of a buried gate HEMT with a gate electrode structure comprising a gate electrode and double lateral field plates arranged in an asymmetric configuration according to at least one aspect of the present disclosure.

[0022] FIG. **7** is a top view of a buried gate HEMT with a gate electrode structure comprising a gate electrode and a single lateral field plate arranged in an asymmetric configuration according to at least one aspect of the present disclosure.

[0023] FIG. **8** is a top view of a buried gate HEMT with a gate electrode structure comprising a gate electrode and a double lateral field plate arranged in an asymmetric configuration according to at least one aspect of the present disclosure.

[0024] FIG. **9** is a top view of a buried gate HEMT with a gate electrode structure comprising a gate electrode and a lateral field plate arranged in a symmetric configuration according to at least one aspect of the present disclosure.

[0025] FIG. **10** is a top view of a buried gate HEMT with a gate electrode structure comprising a gate electrode and double lateral field plates arranged in a symmetric configuration according to at least one aspect of the present disclosure.

[0026] FIG. **11** is a perspective sectional view of a buried gate HEMT with a gate electrode structure comprising a gate electrode and a single lateral field plate and a dielectric structure buried in a substrate remote from the gate electrode structure according to at least one aspect of the present disclosure.

[0027] FIG. **12** is a top view of the buried gate HEMT shown in FIG. **11** according to at least one aspect of the present disclosure.

[0028] FIG. **13** is a top view of a lateral Schottky diode with an anode structure comprising an anode (A) and lateral field plates according to at least one aspect of the present disclosure.

[0029] FIG. **14** is a top view of a lateral Schottky diode with an anode structure comprising an anode (A) and lateral field plates according to at least one aspect of the present disclosure.

[0030] FIG. **15** is a top view of a lateral Schottky diode with an anode structure comprising an anode (A) and lateral field plates according to at least one aspect of the present disclosure.

[0031] FIG. **16** is a top view of a lateral Schottky diode with an anode structure comprising an anode (A) and lateral field plates according to at least one aspect of the present disclosure.

#### DESCRIPTION

[0032] Before explaining various forms of electronic devices in detail, it should be noted that the illustrative forms are not limited in application or use to the details of construction and arrangement of parts illustrated in the accompanying drawings and description. The illustrative forms may be implemented or incorporated in other forms, variations and modifications, and may be practiced or carried out in various ways. Further, unless otherwise indicated, the terms and expressions utilized

herein have been chosen for the purpose of describing the illustrative forms for the convenience of the reader and are not for the purpose of limitation thereof.

[0033] Further, it is understood that any one or more of the following-described forms, expressions of forms, examples, can be combined with any one or more of the other following-described forms, expressions of forms, and examples.

[0034] In one general aspect, this disclosure provides a FET comprising a gate electrode comprising a lateral field plate. In one aspect, the lateral field plate can be integrated in the FET during the fabrication process. This disclosure is applicable to any FET comprising single or multiple current conducting channels.

[0035] In one aspect the FET can be a laterally-gated transistor. In one aspect, the laterally-gated transistor may be a top gate HEMT comprising a lateral field plate and a dielectric layer disposed between the lateral field plate and the single or multiple current conducting channel defining a field plate region where a thickness of the dielectric layer determines a pinch-off voltage in the field plate region. A thickness of the dielectric layer determines the pinch-off voltage in the field plate region. The lateral field plate alleviates the electric field near the drain electrode end of the gate electrode when the device is biased at a high drain voltage, increasing breakdown voltage, and suppressing current collapse. In one aspect, the top-gate HEMT comprises an integrated lateral field plate structure in contact with the substrate and the dielectric layer. The dielectric layer is located on a top layer of the substrate.

[0036] In another aspect, the laterally-gated transistor can be a buried gate HEMT comprising a lateral field plate. The buried gate electrode of the buried gate HEMT contacts laterally with the single or multiple conducting channels and modulates the channel width laterally with gate voltage bias. The lateral field plate is adjacent to the gate electrode with a dielectric layer disposed on sidewalls between the lateral field plate and the single or multiple conducting channel. The lateral field plate is configured to modulate an electric field proximal to a field plate region proximal the gate electrode proximal to at least one of the drain or source electrodes. A thickness of the dielectric layer deposited on the sidewalls is uniform in the depth direction to enable a distance between the lateral field plate and the single or multiple conducting channel to be uniform for the single or multiple channel. In one aspect, the laterally-gated transistor can be a buried gate HEMT comprising a lateral field plate according to the present disclosure may be employed to increase transistor power density and current handling and to decrease the on-resistance of the transistor for both RF and power switching applications.

[0037] Various lateral field plate configurations may be employed depending on the application. The following applications are not limiting. For RF power amplification and power switching device, field plates may be located asymmetrically only on the drain electrode side of the gate electrode where the electric field peaks. For RF switch devices where the gate-to-source and the gate-to-drain voltages are applied equally, symmetric lateral field plates are applicable where the lateral field plate is adjacent to the gate electrode proximal to at least one of or both the drain or source electrodes.

[0038] In one aspect, the laterally gated transistor comprises an integrated lateral field plate structure adjacent to the gate electrode proximal to at least one of or both the drain or source electrodes with a dielectric layer contacting the entire sidewall except where the gate electrode contacts the substrate.

[0039] In another aspect, a laterally gated transistor comprises an integrated lateral field plate structure adjacent to the gate electrode proximal to at least one of the drain or source electrodes with a dielectric layer contacting the entire sidewall except where the gate contacts the substrate. The dielectric layer also contacts the lateral sides of the gate electrode proximal to at least one of or both the drain or source electrodes.

[0040] In yet another aspect, the present disclosure provides a laterally gated transistor comprising an integrated field plate structure adjacent to the gate electrode proximal to at least one of or both

the drain or source electrodes and a field plate is adjacent to the gate on the source-end of the gate. A dielectric layer contacts the sidewall except where the gate electrode contacts the substrate. [0041] In another aspect, the present disclosure provides a laterally gated transistor comprising an integrated field plate structure adjacent to the gate electrode proximal to at least one of or both the drain or source electrodes. A second field plate is adjacent to the first field plate. A dielectric layer contacts the sidewall except where the gate contacts the substrate. A second dielectric layer contacts the first dielectric layer.

[0042] In another aspect, the present disclosure provides a laterally gated transistor comprising an integrated field plate structure adjacent to the gate on the drain-end of the gate. A second field plate is adjacent to the first field plate. A dielectric layer contacts the entire sidewall except where the gate contacts the substrate. The dielectric layer also contacts the gate electrode proximal to at least one of or both the drain or source electrodes. A second dielectric layer contacts the first dielectric layer.

[0043] In yet another aspect, the present disclosure provides a laterally gated transistor comprising a first field plate adjacent to the gate electrode proximal to at least one of or both the drain or source electrodes and a second field plate adjacent to the gate electrode proximal to the at least one of or both the drain or source electrodes. A third field plate adjacent to the gate electrode proximal to at least one of or both the drain or source electrodes and a fourth field plate adjacent to the third field plate proximal to at least one of or both the drain or source electrodes. A dielectric layer contacts the sidewall except where the gate electrode contacts the substrate. A second dielectric layer contacts the first dielectric layer.

[0044] In another aspect, the present disclosure provides a buried nitride structure embedded in the substrate of a laterally gated transistor in addition to an integrated field plate structure contacting laterally with the channels through a gate dielectric layer. The buried nitride structure enhances breakdown voltage and reduces the gate to drain capacitance.

[0045] The lateral field plate modulates the electric field in a field plate region proximal to at least one of or both the drain or source electrodes in one or multiple channels simultaneously. The lateral field plate alleviates electric field strength in the field plate region proximal to at least one of or both the drain or source electrodes. The lateral field plate, due to the alleviated electric field strength at the drain electrode end of the gate electrode, enables increased breakdown voltage, reduced off-state gate leakage current, suppressed current collapse and knee walkout during large-signal operation of the transistors, and suppressed dynamic on-resistance increase during high-voltage switching operation of the transistors.

[0046] The laterally-gated transistors comprising integrated lateral field plate structures according to the present disclosure can be applied to any type of laterally gated transistors made of any type of semiconductor material such as InAlGaAs, InAlN, InGaSb, SiGe/Si, Ga<sub>2</sub>O<sub>3</sub>, or AlGaOx. In addition, the laterally-gated transistors with integrated lateral field plate structures according to the present disclosure may be applicable to a wide range of RF products such as power amplifiers, low-noise amplifiers, low-loss RF switches, power converters with a low-loss and a high-blocking voltage.

[0047] In various aspects, the laterally-gated transistors comprising integrated lateral field plate structures according to the present disclosure may be applicable to RF transistors used in power amplifiers with high output power, high efficiency, high linearity with high reliability at a wide range of frequencies from S-band to W-band. In various aspects, the laterally-gated transistors comprising integrated lateral field plate structures may be applied to reliable RF power amplifiers with an unprecedented combination of output power, efficiency, and linearity. The laterally-gated transistors comprising integrated lateral field plate structures according to the present disclosure also may be applied to robust low noise amplifiers with high linearity.

[0048] In one aspect, the laterally-gated transistors with integrated lateral field plate structures according to the present disclosure may be applicable to RF transistors used in RF switches with

low insertion loss and high isolation. In another aspect, the laterally-gated transistors with integrated lateral field plate structures according to the present disclosure may be applied to power switches with low dynamic on-resistance and breakdown voltages. In yet another aspect, the laterally-gated transistors comprising integrated lateral field plate according to the present disclosure may be applied to low insertion-loss RF switches with high isolation and power handling capability. The laterally-gated transistors comprising integrated lateral field plate structures according to the present disclosure can produce power switches with high power conversion efficiency at high voltages, such as over 600V, for example.

[0049] In one aspect, the laterally-gated transistors with integrated lateral field plate structures according to the present disclosure may be applied to RF transistors used in diodes with a low series resistance and a high breakdown voltage.

[0050] In various aspects, the laterally-gated transistors comprising integrated lateral field plate structures according to the present disclosure may be applied to FinFETs or other type of non-planar transistors, or “3D” transistors, super lattice castellated (SLC) FETs, and buried gate HEMTs.

[0051] Turning now to the figures, where FIG. 1 is cross-sectional views of a top gate HEMT **100** with a gate electrode **108** without a lateral field plate and FIG. 2 is a perspective sectional view of a buried gate HEMT **200** without a lateral field plate. In the conventional planar HEMT shown in FIG. 1, a buffer layer **122**, a channel **110**, and a top barrier layer **120** have been grown on a substrate **102**. Source and drain electrodes **104**, **106** are on a top surface of the substrate **102**, along with a gate electrode **108**. As used herein, the “top surface” of the substrate **102** refers to a surface of the uppermost epitaxial layer that has been grown on the substrate **102**. In operation, in the ON-state, a voltage applied to the gate electrode **108** creates a vertical electric field which affects the depletion of the channel **110**, thereby controlling the current flow between source and drain electrodes **104**, **106**. Drain current is controlled by electron density modulation, with electrons flowing under the foot of the gate electrode **108**. One drawback of this conventional design is that in the OFF-state, there may be a leakage current when the source-drain voltage is high, due to source-drain punch through.

[0052] A dielectric layer **112** is located on the top surface of the substrate **102**. The dielectric layer **112** is in contact with the substrate **102**, the source electrode **104**, and the drain electrode **106**. The gate electrode **108** disposed on the top of the semiconductor substrate **102** modulates the drain current by a vertical gate field. This forms a region **114** at the drain electrode **106** end of the gate electrode **108** where an electric field strength becomes the largest during high voltage operation. The high electric field strength in this region **114** causes current collapse by electron trapping at the semiconductor surface and degrades the power performance of the top gate HEMT **100** when it is biased at high drain voltages.

[0053] FIG. 2 is a perspective sectional view of a buried gate HEMT **200** with a buried gate electrode **208** without a lateral field plate. In this illustrated example, the FET is a buried gate HEMT in which the drain current is carried via a 2DEG plane within a channel **210**. As shown, the channel **210** comprises multiple conducting channels. The buried gate HEMT **200** comprises a substrate **202**, an epitaxial buffer layer **222**, a 2DEG plane within an epitaxial channel **210**, an epitaxial top barrier layer **220**, and source and drain electrodes **204**, **206** on a top surface of the substrate **202**. However, instead of a gate electrode **108** on the surface of the substrate **102** as shown in FIG. 1, here the gate electrode comprises a plurality of buried gate electrode **208**, the tops of which extend above the top surface of the substrate **202** and the bottoms of which are buried to a depth at least equal to that of the bottom of 2DEG plane of the channel **210** between a dielectric layer **212** disposed on the sidewalls of the channel **210**. The buried gate electrode **208** also includes a head portion above (not shown) and not in contact with the top surface of the substrate, which contacts and interconnects all of the buried gate electrode **208**. Thus, the buried gate electrodes **208** contact the 2DEG plane of the channel **210** only from the sides. When so arranged, the drain

current of the FET is controlled by channel width modulation by lateral gating of the 2DEG plane of the channel **210** by the buried gate electrode **208**. The drain current in the ON-state is controlled by channel width modulation, and the device exhibits excellent electrostatic isolation in the OFF-state because the buried gate electrode **208** laterally extend the depletion region under the 2DEG plane of the channel **210**.

[0054] In the example depicted in FIG. 2, the gate electrodes **208** are rectangularly shaped. A dielectric layer **212** is disposed on the inner sidewalls of aperture **236** defined in the substrate **202** where the bottoms of the gate electrode **208** are buried in the substrate **202**. The lateral sides of the bottom of the gate electrode **208** are received in the apertures **236** through gaps **234** defined in the dielectric layer **212** between the elongated sides of the apertures **236**. The dielectric layer **212** surrounds the edge of the aperture **236** containing the gate electrode **208** except where the gaps **234** are defined.

[0055] Electrons flow between the buried gate electrode **208**, with the width of the channels ( $W_{ch}$ ), measured between the buried gate electrode **208** along the width ( $W$ ) of the substrate **202**, controlled by the depletion induced by the lateral sides of the bottom of the buried gate electrode **208**, and by the pitch ("Pg-g") between adjacent buried gate electrode **208**. The preferably nanometer-scale parallel channels reduce self-heating during large signal operation by spatially distributing the heat sources. The width ( $W$ ) is transverse to the length  $L$  of the substrate **202**. The buried gate electrode **208** contact laterally with the channel(s) defined between the gate electrode **208** along the width ( $W$ ) and modulate the channel widths  $W_{ch}$  laterally with the gate bias.

[0056] When the FET is a HEMT **200** as illustrated in FIG. 2, the channel **210** comprises a 2DEG plane. The length of the channel is measured along the length  $L$  of the device. For this type of FET, the bottoms of buried gate electrode **208** should be buried at least to the bottom of the 2DEG plane of the channel **210**. As the 2DEG plane occupies only the upper portion of the channel layer, the bottoms of the buried gate electrode **208** can be within the channel **210**, or even in the buffer layer **222**.

[0057] The depth to which the buried gate electrode **208** should be buried depends on the device type. As noted above, for the HEMT **200** shown in FIG. 2, the bottoms of the buried gate electrode **208** should be buried to a depth at least equal to the bottom of the current-carrying 2DEG plane in the channel **210**. If the device is a MESFET, the buried gate electrode **208** could be buried to a depth at least equal to the bottom of the channel **210**. In general, the buried gate electrode **208** must be buried deep enough so that they contact the current-carrying portion of the channel **210** only from its sides, such that the drain current of the FET is controlled by channel width modulation by lateral gating of the current-carrying layer by the buried gate electrode **208**.

[0058] As noted above, a FET employing buried gate electrode **208** as described herein controls drain current via channel width modulation, by laterally gating the channel **210**. The laterally extended depletion region under the channel **210** enhances electrostatic isolation, and reduces leakage current and drain-induced barrier lowering (DIBL) in the off-state; it also reduces output conductance in on-state, thereby improving transistor gain. Effective source and drain resistances are very small ("1/5 those of planar HEMTs) because the source and drain contact width is wider than the effective channel width, thereby reducing the knee voltage. In addition, having no contact between the top of substrate **202** and the head portion (not shown) suppresses the electron trapping effect during large signal operation, and eliminates the inverse piezoelectric effect.

[0059] The buried gate electrode **208** can have any of a number of shapes. For example, the structures may be cylindrical. They might also be, for example, rectangular, or any other suitable shape.

[0060] As shown in FIG. 2, the plurality of buried gate electrode **208** may lie along a line which is parallel to and between the source and drain electrodes **204**, **206**, though this is not essential. In this example, the buried gate electrode **208** are evenly spaced along said line (i.e., the buried gates have a fixed pitch). As FET characteristics such as threshold voltage vary with pitch, the fixed pitch can



be selected as needed to achieve desired performance characteristics.

[0061] The dielectric layer **212** is in contact with the sidewalls of the channel **210** where the bottoms of the buried gate electrode **208** are buried in the channel **210**. The dielectric layer **212** also is in contact with the top surface of the substrate **202**. The buried gate electrode **208** modulate the drain current by a vertical gate field. This forms a region **214** at the drain electrode **206** end of the buried gate electrode **208** where an electric field strength becomes the largest during high voltage operation. The high electric field strength in this region **214** causes current collapse by electron trapping at the semiconductor surface and degrades the power performance of the top gate HEMT **200** when it is biased at high drain voltages.

[0062] As described hereinbelow, to alleviate the high electric field strength in regions **114**, **214** as shown in FIGS. **1** and **2**, lateral field plate structures are integrated with the gate electrode structures **108**, **208** and a dielectric layer **112**, **212** is inserted in between the lateral field plate structure and the channel **110**, **210**. The thickness of the dielectric layer **112**, **212** determines the pinch-off voltage in the field plate structure region **114**, **214**. The field plate alleviate the electric field in the regions **114**, **214** near the drain electrode **106**, **206** end of the gate electrode structures **108**, **208** when the device is biased at a high drain voltage, increasing breakdown voltage and suppressing current collapse.

[0063] Laterally-gated transistors with multiple channels **210**, as shown in FIG. **2**, for example, increase the power density and current handling of the transistor to decrease the on-resistance of the transistor for both RF and power switching applications. In the laterally-gated transistors, the field lateral field plate structures contacts laterally with the channel(s) **110**, **210** through a gate dielectric layer **112**, **212** (SiN, SiO<sub>2</sub>, SiON, AlN, Al<sub>2</sub>O<sub>3</sub>, AlON, HfO<sub>2</sub>, HfN, HfON, etc.). The thickness of the gate dielectric layer **212** deposited on the sidewalls is made to be the same in the depth direction, enabling the distance between the lateral field plate structure and the channel **210** to be the same for multiple channels.

[0064] Additional description of top gated HEMT and buried gate HEMT devices is provided in commonly owned Publication No. US 2019/0013386 A1, the disclosure of which is herein incorporated by reference in its entirety. Although HEMTs are depicted in the examples shown, the lateral field plate structures described herein could be applied to other FET types, including MESFETs and Metal Insulator Semiconductor FETs (MISFETs), FIN FETS, SLG FETS, among other. Various FET transistors comprising various configurations of lateral field structures are described hereinbelow in connection with FIGS. **3-12**.

[0065] FIG. **3** is a cross-sectional view of a top gate HEMT **300** with a gate electrode structure **307** comprising a gate electrode **308** and a lateral field plate **332** according to at least one aspect of the present disclosure. In the illustrated example, the top gate HEMT **300** HEMT shown in FIG. **1**, a buffer layer **322**, a channel layer **320**, and a top barrier layer **310** have been grown on a substrate **302**. Source and drain electrodes **304**, **306** are on a top surface of the substrate **302**, along with a gate electrode structure **307** comprising a gate electrode **308** and a lateral field plate **332**. As used herein, the “top surface” of the substrate **302** refers to a surface of the uppermost epitaxial layer that has been grown on the substrate **302**. In operation, in the ON-state, a voltage applied to the gate electrode **308** creates a vertical electric field which affects the depletion of the channel layer **320**, thereby controlling the current flow between source and drain electrodes **304**, **306**. Drain current is controlled by electron density modulation, with electrons flowing under the foot of the gate electrode **308**. One drawback of this conventional design is that in the OFF-state, there may be a leakage current when the source-drain voltage is high, due to source-drain punch through.

[0066] A dielectric layer **312** is located on the top surface of the substrate **302**. The dielectric layer **312** is in contact with the substrate **302**, the source electrode **304**, and the drain electrode **306**. The gate electrode **308** disposed on the top of the semiconductor substrate **302** modulates the drain current by a vertical gate field. The dielectric layer **312** is inserted in between the lateral field plate **332** and the channel layer **320**. The thickness of the dielectric layer **312** determines the pinch-off

voltage in the lateral field plate **332** region **314**. The lateral field plate **332** alleviates the electric field near the drain electrode **306** end of the gate electrode **308** when the top gate HEMT **300** is biased at a high drain voltage, increasing breakdown voltage and suppressing current collapse when the electric field strength becomes the largest during high voltage operation. The alleviated electric field region **314** near the lateral field plate **332** prevents current collapse and enhances the power performance of the top gate HEMT **300** when it is biased at high drain voltages.

[0067] FIG. **4** is a perspective sectional view of a buried gate HEMT **400** with a gate electrode structure **407** comprising a gate electrode **408** and a single lateral field plate **432** arranged in an asymmetric configuration and FIG. **5** is a top view of the buried gate HEMT **400** shown in FIG. **4** according to at least one aspect of the present disclosure. In the example illustrated in FIGS. **4** and **5**, the FET is a buried gate HEMT in which the drain current is carried via a 2DEG plane within a channel **410**. As shown, the channel **410** comprises multiple conducting channels. The buried gate HEMT **400** comprises a substrate **402**, an epitaxial buffer layer **422**, a 2DEG plane within an epitaxial channel **410**, an epitaxial top barrier layer **420**, and source and drain electrodes **404**, **406** on a top surface of the substrate **402**. A gate electrode structure **407** on the surface of the substrate **402** comprises a plurality of buried gate electrodes **408** and lateral field plates **432**, the tops of which extend above the top surface of the substrate **402** and the bottoms of which are buried in an aperture **436** disposed in the substrate **402** to a depth at least equal to that of the bottom of 2DEG plane of the channel **410** between a dielectric layer **412** disposed on the sidewalls of the channel **410**. The buried gate electrode structures **407** also includes a head portion above (not shown) and not in contact with the top surface of the substrate, which contacts and interconnects all of the buried gate electrodes **408**. Thus, the buried gate electrodes **408** contact the 2DEG plane of the channel **410** only from the sides. When so arranged, the drain current of the FET is controlled by channel width modulation by lateral gating of the 2DEG plane of the channel **410** by the buried gate electrodes **408**. The drain current in the ON-state is controlled by channel width modulation, and the device exhibits excellent electrostatic isolation in the OFF-state because the buried gate electrodes **408** laterally extend the depletion region under the 2DEG plane of the channel **410**. In the illustrated example, the gate electrode structures **407** are located asymmetrically closer to the source electrode **404** end of the substrate **402**. A plurality of channels **410** are defined between the source electrode **404** and the drain electrode **406** between the gate electrode structures **407**.

[0068] In the example depicted in FIGS. **4** and **5**, the gate electrodes **408** and lateral field plates **432** are rectangularly shaped and arranged in an asymmetric configuration. The buried gate electrodes **408** and the lateral field plates **432** are not limited to the shape in the depicted example. Each gate electrode structure **407** comprises a gate electrode **408** and a lateral field plate **432** extending longitudinally from the gate electrode **408** towards to the drain electrode **406** end along the length (L) of the substrate **402**. The amount of longitudinal extension along the length (L) of the lateral field plate **432** is non-limiting and may be selected for a given application. A dielectric layer **412** is disposed on the inner sidewalls of the aperture **436** where the bottoms of the gate electrodes **408** are buried in the substrate **402**. The lateral sides of the bottom of the gate electrodes **408** are received in the apertures **436** through gaps **434** defined in the dielectric layer **412** disposed along the elongated sides of the apertures **436**. The dielectric layer **412** surrounds the sidewalls of the apertures **436** containing the gate electrode structures **407** except where the gaps **434** are defined. The buried gate electrodes **408** contact laterally with the channel(s) **410** along the width (W) and modulate the channel widths laterally with gate voltage bias. The lateral field plate **432** is located adjacent to the transistor's gate electrode **408** with a dielectric layer **412** in between the lateral field plate **432** and the channel(s) **410**.

[0069] The lateral field plate **432** is adjacent to at least one of the plurality of gate electrodes **408** buried in the substrate **402**. The lateral field plate **432** is in contact with the drain electrode **406** end of the gate electrode **408** along an edge and is in contact with the dielectric **412** sidewall in the lateral width (W) direction. The lateral field plate **432** is configured to modulate an electric field in

the field plate region **414** proximal to the gate electrode **408** proximal to the drain electrode **406** end of at least one of the plurality of gate electrode structures **407** buried in the substrate **402**. Throughout this description, the term “lateral” is defined as the direction along the width (W) of the substrate **402** and “longitudinal” is defined as the direction along the length (L) of the substrate **402**.

[0070] A plurality of channels **410** are located between the source electrode **404** and the drain electrode **406** between the gate electrode structures **407**. The lateral field plate **432** creates an alleviated electric field in the lateral field plate region **414**. The lateral field plate **432** is in electrical contact with a lateral portion of the plurality of channels **410** through the gate dielectric layer **412**. The alleviated electric field in the lateral field plate region **414** is near the drain electrode **406** end of the gate electrode structure **407** and occurs when the device is biased at a high enough drain voltage, increasing breakdown voltage and suppressing current collapse. An alleviated electric field in the lateral field plate region **414** is smaller than an electric field produced without a lateral field plate.

[0071] Electrons flow between the buried gate electrode structures **407**, with the width of the channels (W<sub>ch</sub>), measured between the buried gate electrode structures **407** along the width (W) of the substrate **402**, controlled by the depletion induced by the lateral sides of the bottom of the buried gate electrode structures **407**, and by the pitch (“Pg-g”) between adjacent buried gate electrode structures **407**. The preferably nanometer-scale parallel channels reduce self-heating during large signal operation by spatially distributing the heat sources. The width (W) is transverse to the length (L) of the substrate **402**. The buried gate electrodes **408** contact laterally with the channel(s) defined between the gate electrode structures **407** along the width (W) and modulate the channel widths W<sub>ch</sub> laterally with the gate bias.

[0072] The channel **410** of the buried gate HEMT **400** illustrated in FIG. 4, comprises a 2DEG plane. For this type of FET, the bottoms of buried gate electrode structures **407** should be buried at least to the bottom of the 2DEG plane of the channel **410**. As the 2DEG plane occupies only the upper portion of the channel layer, the bottoms of the buried gate electrode structures **407** can be within the channel **410**, or even in the buffer layer **422**.

[0073] The depth to which the buried gate electrode structures **407** should be buried depends on the device type. The bottoms of the buried gate electrode structures **407** should be buried to a depth at least equal to the bottom of the current-carrying 2DEG plane in the channel **410**. If the device is a MESFET, the buried gate electrode structures **407** could be buried to a depth at least equal to the bottom of the channel **410**. In general, the buried gate electrode structures **407** must be buried deep enough so that they contact the current-carrying portion of the channel **410** only from its sides, such that the drain current of the FET is controlled by channel width modulation by lateral gating of the current-carrying layer by the buried gate electrode structures **407**.

[0074] An FET employing buried gate electrode structures **407** as described herein controls drain current via channel width modulation, by laterally gating the channel **410**. The laterally extended depletion region under the channel **410** enhances electrostatic isolation, and reduces leakage current and drain-induced barrier lowering (DIBL) in the off-state; it also reduces output conductance in on-state, thereby improving transistor gain. Effective source and drain resistances are very small (“ $\frac{1}{5}$  those of planar HEMTs”) because the source and drain contact width is wider than the effective channel width, thereby reducing the knee voltage. In addition, having no contact between the top of substrate **402** and the head portion (not shown) suppresses the electron trapping effect during large signal operation, and eliminates the inverse piezoelectric effect.

[0075] The buried gate electrode structures **407** can have any of a number of shapes. For example, the structures may be cylindrical. They might also be, for example, rectangular, or any other suitable shape.

[0076] As shown in FIG. 4, the plurality of buried gate electrode structures **407** may lie along a line which is parallel to and between the source and drain electrodes **404**, **406**, though this is not

essential. In this example, the buried gate electrode structures **407** are evenly spaced along said line (i.e., the buried gates have a fixed pitch). As FET characteristics such as threshold voltage vary with pitch, the fixed pitch can be selected as needed to achieve desired performance characteristics. [0077] The dielectric layer **412** is in contact with the sidewalls of the channel **410** where the bottoms of the buried gate electrode structures **407** are buried in the substrate **402** down into the channel **410**. The dielectric layer **412** also is in contact with the top surface of the substrate **402**. The buried gate electrode structures **407** modulate the drain current by a vertical gate field. This forms a lateral field plate region **414** at the drain electrode **406** end of the buried gate electrode structures **407** where an electric field strength is alleviated during high voltage operation.

Alleviation of the high electric field strength in this lateral field plate region **414** prevents current collapse by electron trapping at the semiconductor surface and enhances the power performance of the buried gate HEMT **400** when it is biased at high drain voltages.

[0078] To alleviate the high electric field strength in regions **414**, the lateral field plates **432** are integrated with the gate electrode structures **407** and a dielectric layer **412** is inserted in between the lateral field plates **432** and the channel **410**. The thickness of the dielectric layer **412** determines the pinch-off voltage in the lateral field plate region **414**. The lateral field plates **432** alleviate the electric field in the regions **414** near the drain electrode **406** end of the gate electrode structures **407** when the buried gate HEMT **400** is biased at a high drain voltage, increasing breakdown voltage and suppressing current collapse.

[0079] Laterally-gated transistors with multiple channels **410**, as shown in FIGS. **4** and **5**, for example, increase the power density and current handling of the transistor to decrease the on-resistance of the transistor for both RF and power switching applications. In the laterally-gated transistors, the field lateral field plates **432** contacts laterally with the channel(s) **410** through a gate dielectric layer **412** made of SiN, SiO<sub>2</sub>, SiON, AlN, Al<sub>2</sub>O<sub>3</sub>, AlON, HfO<sub>2</sub>, HfN, or HfON, for example. The thickness of the gate dielectric layer **412** deposited on the sidewalls is made to be the same in the depth direction, enabling the distance between the lateral field plates **432** and the channel **410** to be the same for multiple channels.

[0080] FIG. **6** is a top view of a buried gate HEMT **500** with a gate electrode structure **507** comprising a gate electrode **508** and double lateral field plates **532**, **533** arranged in an asymmetric configuration according to at least one aspect of the present disclosure. The buried gate HEMT **500** comprises a substrate **502**, a source electrode **504**, and a drain electrode **506**. The source electrode **504** and the drain electrode **506** are located on a top surface of the substrate **502**. The substrate **502** comprises a plurality of gate electrode structures **507** buried in apertures **536** disposed in the substrate **502** analogous to the apertures **236**, **436** shown in FIGS. **2** and **4**, for example, disposed in the substrates **202**, **402** and extending into the channels **210**, **410**. In the illustrated example, the gate electrode structures **507** are located asymmetrically closer to the source electrode **504** end of the substrate **502**. A plurality of channels extending along the length (L) of the substrate **502** between the source and drain electrodes **504**, **506** are disposed between the gate electrode structures **507**.

[0081] In the example depicted in FIG. **6**, the buried gate electrodes **508** and first and second lateral field plates **532**, **533** are rectangularly shaped and arranged in an asymmetric configuration. The buried gate electrodes **508** and the first and second lateral field plates **532**, **533** are not limited to the shape in the depicted example. The first and second lateral field plates **532**, **533** extend longitudinally from the gate electrodes **508** towards the drain electrode **506** along the length (L) of the substrate **502**. The first and second lateral field plates **532**, **533** extend laterally along the width (W) direction of the substrate **502**.

[0082] A first dielectric layer **512** is disposed on the inner sidewalls of the apertures **536** where the bottoms of the gate electrode structures **507** are buried in the substrate **502** down into the channel(s). A second dielectric layer **550** is disposed over the sidewalls of the first dielectric layers **512**. The lateral sides of the bottoms of the gate electrodes **508** are received within the apertures

**536** through gaps **534** defined in the dielectric layers **512**, **550** along the longitudinal sides of the apertures **536**. The dielectric layers **512**, **550** surround the sidewalls of the apertures **536** containing the gate electrodes **508** except where the gaps **534** are defined in the apertures **536**.

[0083] The buried gate electrodes **508** contact laterally with the channel(s) in the width (W) direction of the substrate **502** and modulate the widths of the channel(s) in the width (W) direction with gate voltage bias. The first lateral field plate **532** is located adjacent to the transistor's gate electrode **508** and the second lateral field plate **533** is located adjacent to the first lateral field plate **532** and extends longitudinally towards the drain electrode **506** along the length (L) direction of the substrate **502**. The first dielectric layer **512** is disposed on the sidewalls of the apertures **536** and the second dielectric layer **550** is disposed on the inner sidewalls of the first dielectric layer **512**.

[0084] To alleviate the high electric field strength in regions proximal to the drain electrode **506**, two lateral field plates **532**, **533** are integrated with each of the gate electrode **508**. The first dielectric layer **512** is inserted in between the first lateral field plate **532** and the channel and the first and second dielectric layers **512**, **550** are inserted in between the second lateral field plate **533** and the channel. For at least one of the gate electrode structures **507**, the first lateral field plate **532** laterally contacts the first dielectric layer **512** and longitudinally contacts the second dielectric layer **550**. The second lateral field plate **533** laterally contacts the second dielectric layer **550**. The first and second lateral field plates **532**, **533** are configured to modulate an electric field proximal to a field plate region proximal to the gate electrode **508** proximal to the drain electrode **506** end of at least one of the plurality of gate electrode structures **507** buried in the substrate **502**. The thickness of the dielectric layers **512**, **550** determine the pinch-off voltage in the lateral field plate region. The lateral field plates **532**, **533** alleviate the electric field in the lateral field plate regions near the drain electrode **506** end of the gate electrodes **508** when the buried gate HEMT **500** is biased at a high drain voltage, increasing breakdown voltage and suppressing current collapse.

[0085] FIG. 7 is a top view of a buried gate HEMT **600** with a gate electrode structure **607** comprising a gate electrode **608** and a single lateral field plate **632** arranged in an asymmetric configuration according to at least one aspect of the present disclosure. The buried gate HEMT **600** comprises a substrate **602**, a source electrode **604**, and a drain electrode **606**. The source electrode **604** and the drain electrode **606** are located on the top surface of the substrate **602**. The substrate **602** comprises a plurality of gate electrode structures **607** buried in apertures **636** disposed in the substrate **602** analogous to the apertures **236**, **436** shown in FIGS. 2 and 4, for example, disposed in the substrates **202**, **402** and extending into the channels **210**, **410**. In the illustrated example, the gate electrode structures **607** are located asymmetrically closer to the source electrode **604** end of the substrate **602**. A plurality of channels extending along the length (L) of the substrate **602** between the source and drain electrodes **604**, **606** are disposed between the gate electrode structures **607**.

[0086] In the example depicted in FIG. 7, the buried gate electrodes **608** and the single lateral field plate **632** are rectangularly shaped and arranged in an asymmetric configuration. The buried gate electrodes **608** and the single lateral field plates **632** are not limited to the shape in the depicted example. The single lateral field plate **632** extends longitudinally from the gate electrode **608** towards the drain electrode **606** along the length (L) of the substrate **602**. The single lateral field plate **632** extends laterally along the width (W) direction of the substrate **602**.

[0087] A dielectric layer **612** is disposed on the inner sidewalls of the apertures **636** where the bottoms of the gate electrode structures **607** are buried in the substrate **602** down into the channel(s). The lateral sides of the bottoms of the gate electrodes **608** are received within the apertures **636** through gaps **634** defined in the dielectric layer **612** along the longitudinal sides of the apertures **636**. The dielectric layer **612** surrounds the sidewalls of the apertures **636** including sidewall portions of the gate electrodes **608** in the lateral direction along the width (W) of the substrate **602** except where the gaps **634** are defined in the apertures **636**.

[0088] The buried gate electrodes **608** contact laterally with the channel(s) in the width (W)

direction of the substrate **602** and modulate the channel widths along the width (W) direction with gate voltage bias. The single lateral field plate **632** is located adjacent to the transistor's gate electrode **608** and extends longitudinally towards the drain electrode **606** along the length (L) direction of the substrate **602**. The dielectric layer **612** is disposed on the sidewalls of the apertures **636** and along the sidewalls of the gate electrode **608** in a lateral direction along the width (W) of the substrate **602**. The single lateral field plate **632** is separated from the gate electrode **608** by a portion **613** of the dielectric layer **612**.

[0089] To alleviate the high electric field strength in regions proximal to the drain electrode **606**, a single lateral field plate **632** is integrated with each the gate electrode **608** and the dielectric layer **612** is inserted in between the single lateral field plate **632** and the channel. For at least one of the gate electrode structures **607**, the lateral field plate **632** laterally contacts the dielectric layer **612** and longitudinally contacts the portion **613** of the dielectric layer **612** between the gate electrode **608** and the lateral field plate **632**. The single lateral field plate **632** is configured to modulate an electric field proximal to a field plate region proximal to the gate electrode **608** proximal to the drain electrode **606** end of at least one of the plurality of gate electrode structures **607** buried in the substrate **602**. The thickness of the dielectric layer **612** determines the pinch-off voltage in the lateral field plate region. The single lateral field plate **632** alleviate the electric field in the lateral field plate regions near the drain electrode **606** end of the gate electrodes **608** when the buried gate HEMT **600** is biased at a high drain voltage, increasing breakdown voltage and suppressing current collapse.

[0090] FIG. **8** is a top view of a buried gate HEMT **700** with a gate electrode structure **707** comprising a gate electrode **708** and a double lateral field plate **732**, **733** arranged in an asymmetric configuration according to at least one aspect of the present disclosure. The buried gate HEMT **700** comprises a substrate **702**, a source electrode **704**, and a drain electrode **706**. The source electrode **704** and the drain electrode **706** are located on the top surface of the substrate **702**. The substrate **702** comprises a plurality of gate electrode structures **707** buried in apertures **736** disposed in the substrate **702** analogous to the apertures **236**, **436** shown in FIGS. **2** and **4**, for example, disposed in the substrates **202**, **402** and extending into the channels **210**, **410**. In the illustrated example, the gate electrode structures **707** are located asymmetrically closer to the source electrode **704** end of the substrate **702**. A plurality of channels extending along the length (L) of the substrate **702** between the source and drain electrodes **704**, **706** are disposed between the gate electrode structures **707**.

[0091] In the example depicted in FIG. **8**, the buried gate electrode **708** and the first and second lateral field plates **732**, **733** are rectangularly shaped and arranged in an asymmetric configuration. The buried gate electrodes **708** and the first and second lateral field plates **732**, **733** are not limited to the shape in the depicted example. The first and second lateral field plates **732**, **733** extend longitudinally from the gate electrode **708** towards the drain electrode **706** end along the length (L) of the substrate **702**. The first and second lateral field plates **732**, **733** extend laterally along the width (W) of the substrate **702**.

[0092] A first dielectric layer **712** is disposed on the inner sidewalls of the apertures **736** where the bottoms of the gate electrode structures **707** are buried in the substrate **702** down into the channel(s). A second dielectric layer **750** is disposed on the inner sidewalls of the first dielectric layers **712**. The lateral sides of the bottoms of the gate electrodes **708** are received within the apertures **736** through gaps **734** defined in the first dielectric layers **712** along the longitudinal sides of the apertures **736**. The first dielectric layers **712** surround the sidewalls of the apertures **736** including the sides of the gate electrodes **708** along the width (W) direction except where the gaps **734** are defined. The second dielectric layers **750** proximal to the source electrode **704** side of the substrate **702** surround the sidewalls of the first dielectric layers **712**. The second dielectric layers **750** proximal to the drain electrode **706** side of the substrate **702** are disposed along the sidewalls of the apertures **736**, about the sidewalls of the second lateral field plate **733**, and in between the

sidewalls of the first and second lateral field plates **732**, **733**.

[0093] The buried gate electrodes **708** contact laterally with the channel(s) in the width (W) direction of the substrate **702** and modulate the widths of the channel(s) in the width (W) direction with gate bias voltage. The first lateral field plate **732** is located adjacent to the transistor's gate electrode **708** and separated by a portion **713** of the first dielectric layer **712** proximal to the drain electrode **706**. The first lateral field plate **732** contacts the first dielectric layer **712** on three sides and contacts the second dielectric layer **750** on the side proximal to the drain electrode **706**. The second lateral field plate **733** is located adjacent to the first lateral field gate **732** is disposed longitudinally from the first lateral field plate **732** toward the drain electrode **706** and contacts the second dielectric layer **750** on all four sides. The second lateral field plate **733** does not contact the first dielectric layer **712**.

[0094] To alleviate the high electric field strength in regions proximal to the drain electrode **706**, two lateral field plates **732**, **733** are integrated with each of the gate electrodes **708**. The first dielectric layer **712** is inserted between the first lateral field plate **732** and the channel(s) and the second dielectric layer **750** is inserted between the second lateral field plate **733** and the first dielectric layer **712** and between the first and second lateral field plates **732**, **733**. For at least one of the gate electrode structures **707**, the first lateral field plate **732** laterally contacts the first dielectric layer **712** and the second lateral field plate **733** laterally contacts the second dielectric layer **750**. The first and second lateral field plates **732**, **733** are configured to modulate an electric field proximal to a field plate region proximal to the gate electrode **708** proximal to the drain electrode **706** end of at least one of the plurality of gate electrode structures **707** buried in the substrate **702**. The thickness of the dielectric layers **712**, **750** determine the pinch-off voltage in the lateral field plate region. The lateral field plates **732**, **733** alleviate the electric field in the lateral field plate regions near the drain electrode **706** end of the gate electrodes **708** when the buried gate HEMT **700** is biased at a high drain voltage, increasing breakdown voltage and suppressing current collapse.

[0095] FIG. **9** is a top view of a buried gate HEMT **800** with a gate electrode structure **807** comprising a gate electrode **808** and lateral field plates **832**, **833** arranged in a symmetric configuration according to at least one aspect of the present disclosure. The buried gate HEMT **800** comprises a substrate **802**, a source electrode **804**, and a drain electrode **806**. The source electrode **804** and the drain electrode **806** are located on a top surface of the substrate **802**. The substrate **802** comprises a plurality of gate electrode structures **807** buried in apertures **836** disposed in the substrate **802** analogous to the apertures **236**, **436** shown in FIGS. **2** and **4**, for example, disposed in the substrates **202**, **402** and extending into the channels **210**, **410**. In the illustrated example, the gate electrode structures **807** are located symmetrically between the source and drain electrodes **804**, **806**. A plurality of channels extending along the length (L) of the substrate **802** between the source and drain electrodes **804**, **806** are disposed between the gate electrode structures **807**.

[0096] In the example depicted in FIG. **9**, the buried gate electrodes **808** and the first and second lateral field plates **832**, **833** are rectangularly shaped and arranged in a symmetric configuration. The buried gate electrodes **808** and the first and second lateral field plates **832**, **833** are not limited to the shape in the depicted example. The first lateral field plate **832** extends longitudinally from the gate electrode **808** towards the source electrode **804** along the length (L) of the substrate **802** and the second lateral field plate **833** extends longitudinally from the gate electrode **808** towards the drain electrode **806** along the length (L) of the substrate **802**. The first and second lateral field plates **832**, **833** extend laterally along the width (W) direction of the substrate **802**.

[0097] A dielectric layer **812** is disposed on the inner sidewalls of the apertures **836** where the bottoms of the gate electrode structures **807** are buried in the substrate **802** down into the channel(s). The lateral sides of the bottoms of the gate electrodes **808** are received within the apertures **836** through gaps **834** defined in the dielectric layers **812** along the longitudinal sides of the apertures **836**. The dielectric layers **812** surround the sidewalls of the apertures **836** containing

the gate electrodes **808** except where the gaps **834** are defined in the apertures **836**.  
[0098] The buried gate electrodes **808** contact laterally with the channel(s) in the width (W) direction of the substrate **802** and modulate the widths of the channel(s) in the width (W) direction with gate voltage bias. The first lateral field plate **832** is located adjacent to the transistor's gate electrode **808** proximal to the source electrode **804** and extends longitudinally towards the source electrode **804** along the length (L) direction of the substrate **802**. The second lateral field plate **833** is located adjacent to the gate electrode **808** proximal to the drain electrode **806** and extends longitudinally towards the drain electrode **806** along the length (L) direction of the substrate **802**. The dielectric layer **812** is disposed on the sidewalls of the apertures **836**.

[0099] To alleviate the high electric field strength in regions proximal to the source and drain electrodes **804**, **806**, two lateral field plates **832**, **833** are integrated symmetrically with each of the gate electrodes **808**. The dielectric layer **812** is inserted in between the first lateral field plate **832** and the channel. For at least one of the gate electrode structures **807**, the first and second lateral field plates **832**, **833** laterally contact the dielectric layer **812**. The first and second lateral field plates **832**, **833** are configured to modulate an electric field proximal to a field plate region proximal to the gate electrode **808** proximal to the source and drain electrodes **804**, **806** end of at least one of the plurality of gate electrode structures **807** buried in the substrate **802**. The thickness of the dielectric layer **812** determines the pinch-off voltage in the lateral field plate region. The lateral field plates **832**, **833** alleviate the electric field in the lateral field plate regions near the source and drain electrodes **804**, **806** end of the gate electrodes **808** when the buried gate HEMT **800** is biased at a high drain voltage, increasing breakdown voltage and suppressing current collapse.

[0100] FIG. **10** is a top view of a buried gate HEMT **900** with a gate electrode structure **907** comprising a gate electrode **908** and double lateral field plates **932**, **933** and **938**, **939** arranged in a symmetric configuration according to at least one aspect of the present disclosure. The buried gate HEMT **900** comprises a substrate **902**, a source electrode **904**, and a drain electrode **906**. The source electrode **904** and the drain electrode **906** are located on a top surface of the substrate **902**. The substrate **902** comprises a plurality of gate electrode structures **907** buried in apertures (not shown) disposed in the substrate **902** analogous to the apertures **236**, **436** shown in FIGS. **2** and **4**, for example, disposed in the substrates **202**, **402** and extending into the channels **210**, **410**. In the illustrated example, the gate electrode structures **907** are located symmetrically between the source and drain electrodes **904**, **906**. A plurality of channels extending along the length (L) of the substrate **902** between the source and drain electrodes **904**, **906** are disposed between the gate electrode structures **907**.

[0101] In the example depicted in FIG. **10**, the buried gate electrodes **907** and the four lateral field plates **932**, **933**, **938**, **939** are rectangularly shaped and arranged in a symmetric configuration. The buried gate electrodes **908** and the four lateral field plates **932**, **933**, **938**, **939** are not limited to the shape in the depicted example. The first and second lateral field plates **932**, **933** extend longitudinally from the gate electrode **908** towards the drain electrode **906** along the length (L) of the substrate **902** and the third and fourth lateral field plates **938**, **939** extend longitudinally from the gate electrode **908** towards the source electrode **904** along the length (L) of the substrate **902**. The four lateral field plates **932**, **933**, **938**, **939** extend laterally along the width (W) direction of the substrate **902**.

[0102] A first dielectric layer **912** is disposed on the inner sidewalls of the apertures where the bottoms of the gate electrode structures **907** are buried in the substrate **902** down into the channel(s). The lateral sides of the bottoms of the gate electrodes **908** are received within the apertures through gaps **934** defined in the first dielectric layers **912** along the longitudinal sides of the apertures. The first dielectric layers **912** surround the sidewalls of the apertures containing the gate electrode structures **907** except where the gaps **934** are defined in the apertures. A second dielectric layer **950** is disposed on the inner sidewalls of the first dielectric layer **912**.



[0103] The buried gate electrodes **908** contact laterally with the channel(s) in the width (W) direction of the substrate **902** and modulate the widths of the channel(s) in the width (W) direction with gate voltage bias. The first lateral field plate **932** is located adjacent to the transistor's gate electrode **908** proximal to the drain electrode **906** and extends longitudinally towards the drain electrode **906** along the length (L) direction of the substrate **902**. The second lateral field plate **938** is located adjacent to the first lateral field plate **932** and also extends longitudinally towards the drain electrode **906** along the length (L) direction of the substrate **902**. The third lateral field plate **938** is located adjacent to the gate electrode **908** proximal to the source electrode **904** and extends longitudinally towards the source electrode **904** along the length (L) direction of the substrate **902**. The fourth lateral field plate **939** is located adjacent to the first lateral field plate **938** and also extends longitudinally towards the source electrode **904** along the length (L) direction of the substrate **902**. The dielectric layer **912** is disposed on the sidewalls of the apertures.

[0104] To alleviate the high electric field strength in regions proximal to the source and drain electrodes **904**, **906**, four lateral field plates **932**, **933**, **938**, **939** are integrated symmetrically with each of the gate electrodes **908**. The first dielectric layer **912** is inserted in between the first and third lateral field plates **932**, **938** and the channel. For at least one of the gate electrode structures **907**, the first and third lateral field plates **932**, **938** laterally contact the first dielectric layer **912** and longitudinally contact the second dielectric layer **950**. The second and fourth lateral field plates **933**, **939** laterally and longitudinally contact the second dielectric layer **950**. The four lateral field plates **932**, **933**, **938**, **939** are configured to modulate an electric field proximal to a field plate region proximal to the gate electrode **908** proximal to the source and drain electrodes **904**, **906** end of at least one of the plurality of gate electrodes **908** buried in the substrate **902**. The thickness of the dielectric layers **912**, **950** determines the pinch-off voltage in the lateral field plate region. The lateral field plates **932**, **933**, **938**, **939** alleviate the electric field in the lateral field plate regions near the source and drain electrodes **904**, **906** end of the gate electrodes **908** when the buried gate HEMT **900** is biased at a high drain voltage, increasing breakdown voltage and suppressing current collapse.

[0105] FIG. **11** is a perspective view of a buried gate HEMT **1000** with a gate electrode structure **1007** comprising a gate electrode **1008** and a single lateral field plate **1032** and a dielectric structure **1040** buried in a substrate **1002** remote from the gate electrode structure **1007** according to at least one aspect of the present disclosure. FIG. **12** is a top view of the buried gate HEMT **1000** shown in FIG. **11** according to at least one aspect of the present disclosure. With reference now to FIGS. **11** and **12**, a buried gate HEMT **1000** is disclosed in which the drain current is carried via a 2DEG plane within a channel **1010**. As shown, the channel **1010** comprises multiple conducting channels. The buried gate HEMT **1000** comprises a substrate **1002**, an epitaxial buffer layer **1022**, a 2DEG plane within an epitaxial channel **1010**, an epitaxial top barrier layer **1020**, and source and drain electrodes **1004**, **1006** on a top surface of the substrate **1002**. A gate electrode structure on the surface of the substrate **1002** comprises a plurality of buried gate electrode structures **1007**, the tops of which extend above the top surface of the substrate **1002** and the bottoms of which are buried in an aperture **1036** disposed in the substrate **1002** to a depth at least equal to that of the bottom of 2DEG plane of the channel **1010** between a dielectric layer **1012** disposed on the sidewalls of the channel **1010**. The buried gate electrode structures **1007** also includes a head portion above (not shown) and not in contact with the top surface of the substrate, which contacts and interconnects all of the buried gate electrode structures **1007**. Thus, the buried gate electrodes **1008** contact the 2DEG plane of the channel **1010** only from the sides. When so arranged, the drain current of the FET is controlled by channel width modulation by lateral gating of the 2DEG plane of the channel **1010** by the buried gate electrodes **1008**. The drain current in the ON-state is controlled by channel width modulation, and the device exhibits excellent electrostatic isolation in the OFF-state because the buried gate electrodes **1008** laterally extend the depletion region under the 2DEG plane of the channel **1010**. In the illustrated example, the gate electrode structures **1007** are located

asymmetrically closer to the source electrode **1004** end of the substrate **1002**. A plurality of channels **1010** are defined between the source electrode **1004** and the drain electrode **1006** between the gate electrode structures **1007**.

[0106] In the example depicted in FIGS. **11** and **12**, the gate electrodes **1008** and the lateral field plate **1032** are rectangularly shaped and arranged in an asymmetric configuration. The buried gate electrodes **1008** and the lateral field plate **1032** are not limited to the shape in the depicted example. Each gate electrode **1008** comprises a lateral field plate **1032** extending longitudinally from the gate electrode **1008** towards to the drain electrode **1006** end along the length (L) of the substrate **1002**. The amount of longitudinal extension along the length (L) of the lateral field plate **1032** is non-limiting and may be selected for a given application. A dielectric layer **1012** is disposed on the inner sidewalls of the aperture **1036** where the bottoms of the gate electrode structures **1007** are buried in the substrate **1002**. The lateral sides of the bottom of the gate electrodes **1008** are received in the apertures **1036** through gaps **1034** defined in the dielectric layer **1012** disposed along the elongated sides of the apertures **1036**. The dielectric layer **1012** surrounds the sidewalls of the apertures **1036** containing the gate electrode structures **1007** except where the gaps **1034** are defined. The buried gate electrodes **1008** contact laterally with the channel(s) **1010** along the width (W) and modulate the channel widths laterally with gate voltage bias. The lateral field plate **1032** is located adjacent to the transistor's gate electrode **1008** with a dielectric layer **1012** in between the lateral field plate **1032** and the channel(s) **1010**.

[0107] The lateral field plate **1032** is adjacent to at least one of the plurality of gate electrodes **1008** buried in the substrate **1002**. The lateral field plate **1032** is in contact with the drain electrode **1006** end of the gate electrode structure **1007** along an edge and is in contact with the dielectric **1012** sidewall in the lateral width (W) direction. The lateral field plate **1032** is configured to modulate an electric field proximal to a field plate region proximal to the gate electrode **1008** proximal to the drain electrode **1006** end of at least one of the plurality of gate electrode structures **1007** buried in the substrate **1002**. Throughout this description, the term “lateral” is defined as the direction along the width (W) of the substrate **1002** and “longitudinal” is defined as the direction along the length (L) of the substrate **402**.

[0108] A plurality of channels **1010** are located between the source electrode **1004** and the drain electrode **1006** between the gate electrode structures **1007**. The lateral field plate **1032** creates an alleviated electric field in the lateral field plate region. The lateral field plate **1032** is in electrical contact with a lateral portion of the plurality of channels **1010** through the gate dielectric layer **1012**. The alleviated electric field in the lateral field plate region is near the drain electrode **1006** end of the gate electrode structure **1007** and occurs when the device is biased at a high enough drain voltage, increasing breakdown voltage and suppressing current collapse. An alleviated electric field in the lateral field plate region is smaller than an electric field produced without a lateral field plate.

[0109] Electrons flow between the buried gate electrode structures **1007**, with the width of the channels (W<sub>ch</sub>), measured between the buried gate electrode structures **1007** along the width (W) of the substrate **1002**, controlled by the depletion induced by the lateral sides of the bottom of the buried gate electrode structures **1007**, and by the pitch (“Pg-g”) between adjacent buried gate electrode structures **1007**. The preferably nanometer-scale parallel channels reduce self-heating during large signal operation by spatially distributing the heat sources. The width (W) is transverse to the length (L) of the substrate **1002**. The buried gate electrodes **1008** contact laterally with the channel(s) defined between the gate electrode structures **1007** along the width (W) and modulate the channel widths W<sub>ch</sub> laterally with the gate bias.

[0110] The channel **1010** of the buried gate HEMT **1000** illustrated in FIG. **11**, comprises a 2DEG plane. For this type of FET, the bottoms of the buried gate electrode structures **1007** should be buried at least to the bottom of the 2DEG plane of the channel **1010**. As the 2DEG plane occupies only the upper portion of the channel layer, the bottoms of the buried gate electrode structures **1007**

can be within the channel **1010**, or even in the buffer layer **1022**.

[0111] The depth to which the buried gate electrode structures **1007** should be buried depends on the device type. The bottoms of the buried gate electrode structures **1007** should be buried to a depth at least equal to the bottom of the current-carrying 2DEG plane in the channel **1010**. If the device is a MESFET, the buried gate electrode structures **1007** could be buried to a depth at least equal to the bottom of the channel **1010**. In general, the buried gate electrode structures **1007** must be buried deep enough so that they contact the current-carrying portion of the channel **1010** only from its sides, such that the drain current of the FET is controlled by channel width modulation by lateral gating of the current-carrying layer by the buried gate electrode structures **1007**.

[0112] An FET employing buried gate electrode structures **1007** as described herein controls drain current via channel width modulation, by laterally gating the channel **1010**. The laterally extended depletion region under the channel **1010** enhances electrostatic isolation, and reduces leakage current and drain-induced barrier lowering (DIBL) in the off-state; it also reduces output conductance in on-state, thereby improving transistor gain. Effective source and drain resistances are very small ( $\frac{1}{5}$  those of planar HEMTs) because the source and drain contact width is wider than the effective channel width, thereby reducing the knee voltage. In addition, having no contact between the top of substrate **1002** and the head portion (not shown) suppresses the electron trapping effect during large signal operation, and eliminates the inverse piezoelectric effect.

[0113] The buried gate electrode structures **1007** can have any of a number of shapes. For example, the structures may be cylindrical. They might also be, for example, rectangular, or any other suitable shape.

[0114] As shown in FIG. **11**, the plurality of buried gate electrode structures **1007** may lie along a line which is parallel to and between the source and drain electrodes **1004**, **1006**, though this is not essential. In this example, the buried gate electrode structures **1007** are evenly spaced along said line (i.e., the buried gates have a fixed pitch). As FET characteristics such as threshold voltage vary with pitch, the fixed pitch can be selected as needed to achieve desired performance characteristics.

[0115] The dielectric layer **1012** is in contact with the sidewalls of the channel **1010** where the bottoms of the buried gate electrode structures **1007** are buried in the substrate **1002** down into the channel **1010**. The dielectric layer **1012** also is in contact with the top surface of the substrate **1002**. The buried gate electrode structures **1007** modulate the drain current by a vertical gate field. This forms a lateral field plate region at the drain electrode **1006** end of the buried gate electrode structures **1007** where an electric field strength is alleviated during high voltage operation. Alleviation of the high electric field strength in this lateral field plate region **1014** prevents current collapse by electron trapping at the semiconductor surface and enhances the power performance of the buried gate HEMT **1000** when it is biased at high drain voltages.

[0116] To alleviate the high electric field strength in regions, the lateral field plates **1032** are integrated with the gate electrodes **1008** and a dielectric layer **1012** is inserted in between the lateral field plates **1032** and the channel **1010**. The thickness of the dielectric layer **1012** determines the pinch-off voltage in the lateral field plate region. The lateral field plates **1032** alleviate the electric field in the regions **1014** near the drain electrode **1006** end of the gate electrodes **1008** when the buried gate HEMT **1000** is biased at a high drain voltage, increasing breakdown voltage and suppressing current collapse. In addition, the substrate **1002** comprises buried dielectric structures **1040** located remote from the gate electrode structures **1007** to enhance breakdown voltage and reduce the gate-to-drain capacitance. The buried dielectric structures **1040** shape the equipotential lines **1042** developed between the dielectric layers **1012** of adjacent gate electrodes **1008** to increase breakdown voltage and suppress current collapse. In one aspect, the buried dielectric structures **1040** are made of nitride.

[0117] Laterally-gated transistors with multiple channels **1010**, as shown in FIGS. **11** and **12**, for example, increase the power density and current handling of the transistor to decrease the on-resistance of the transistor for both RF and power switching applications. In the laterally-gated

transistors, the field lateral field plates **1032** contacts laterally with the channel(s) **1010** through a gate dielectric layer **1012** made of SiN, SiO<sub>2</sub>, SiON, AlN, Al<sub>2</sub>O<sub>3</sub>, AlON, HfO<sub>2</sub>, HfN, or HfON, for example. The thickness of the gate dielectric layer **1012** deposited on the sidewalls is made to be the same in the depth direction, enabling the distance between the lateral field plates **1032** and the channel **1010** to be the same for multiple channels.

[0118] It will be appreciated that any of the gate electrode structures **407, 507, 607, 707, 807, 907, 1007** comprising gate electrodes **408, 508, 608, 708, 808, 908, 1008** adjacent to corresponding lateral field plates **432, 532, 533, 632, 732, 733, 832, 833, 932, 933, 1032** configurations may be implemented in the top gate FET configuration described in connection with FIG. 3. In these implementations, the dielectric layer **312** is inserted in between the lateral field plates **432, 532, 533, 632, 732, 733, 832, 833, 932, 933, 1032** and the channel layer **320**. In a top gate implementation, the gate electrode structures **407, 507, 607, 707, 807, 907, 1007** may be arranged in symmetric or asymmetric configurations relative to the substrate.

[0119] In view of the foregoing description, in various aspects, the dielectric layer material **112, 212, 312, 412, 512, 612, 712, 812, 912, 1012** may be selected from any one of the following materials SiN, SiO<sub>2</sub>, SiON, AlN, Al<sub>2</sub>O<sub>3</sub>, AlON, HfO<sub>2</sub>, HfN, or HfON.

[0120] In view of the foregoing description, in various aspects, the semiconductor substrate material may be selected from any one of the following semiconductor materials SiC, GaN, AlN, GaAs, InP, Ga<sub>2</sub>O<sub>3</sub>, Si.

[0121] In view of the foregoing description, in various aspects, the buffer layer material may be selected from any one of the following materials: GaN, AlGa<sub>N</sub>, AlN, InGa<sub>N</sub>, InAl<sub>N</sub>, GaAs, InGaAs, InAlAs, InP, AlGaAs, InGaO<sub>x</sub>, Ga<sub>2</sub>O<sub>3</sub>, AlGaO<sub>x</sub>, Si, SiGe.

[0122] In view of the foregoing description, in various aspects, the channel layer material may be selected from any one of the following materials: GaN, AlGa<sub>N</sub>, InGa<sub>N</sub>, InAl<sub>N</sub>, GaAs, InGaAs, InAlAs, InP, AlGaAs, InGaO<sub>x</sub>, Ga<sub>2</sub>O<sub>3</sub>, AlGaO<sub>x</sub>, Si, SiGe.

[0123] In view of the foregoing description, in various aspects, the barrier layer material may be selected from any one of the following materials: GaN, AlGa<sub>N</sub>, InGa<sub>N</sub>, InAl<sub>N</sub>, GaAs, InGaAs, InAlAs, InP, AlGaAs, Ga<sub>2</sub>O<sub>3</sub>, AlGaO<sub>x</sub>, Si, SiGe.

[0124] As noted above, the present FET structure may be used to form, for example, HEMTs or MESFETs. HEMTs that might employ the device structure described herein might be disposed from various combinations of substrates and epitaxial layer materials. Several possible material combinations are listed below; other combinations may also be possible. [0125] 1. AlGa<sub>N</sub> barrier/GaN channel/GaN or AlGa<sub>N</sub> buffer on SiC, Si, GaN, AlN, sapphire, or diamond substrate; [0126] 2. AlGaAs barrier/InGaAs channel/GaAs or AlGaAs buffer on GaAs substrate; [0127] 3. InAlAs barrier/InGaAs channel/InP or InAlAs buffer on InP substrate; and [0128] 4. (AlGa)<sub>2</sub>O<sub>3</sub> barrier/Ga<sub>2</sub>O<sub>3</sub> channel/Ga<sub>2</sub>O<sub>3</sub> buffer on Ga<sub>2</sub>O<sub>3</sub> substrate.

[0129] In other aspects, the present disclosure is directed to Schottky diodes comprising lateral contacts. In one aspect, a Schottky diode comprises a lateral contact between the anode metal and a single or multiple 2DEG channel layer or layers. Lateral field plates are added in between the anode and the cathode to laterally pinch off the multiple 2DEG channels simultaneously, leading to an increased breakdown voltage. A single or multiple lateral field plate(s) can be used to establish an electric field between the anode and the cathode.

[0130] Turning now to the figures, FIG. 13 is a top view of a lateral Schottky diode **1100** with an anode structure comprising an anode (A) **1162** and lateral field plates **1132, 1133** according to at least one aspect of the present disclosure. The lateral Schottky diode **1100** comprises a substrate **1102** and cathodes (C) **1160, 1166**. The cathodes **1160, 1166** are located on the top surface of the substrate **1102**. The substrate **1102** comprises a plurality of structures buried in apertures **1136** disposed in the substrate **1102**. The anode **1162** is located symmetrically between the cathodes **1160, 1166**.

[0131] In the example depicted in FIG. 13, the first and second lateral field plates **1132, 1133** are

rectangularly shaped and arranged in a symmetric configuration. The first and second lateral field plates **1132**, **1133** are not limited to the shape in the depicted example. The first lateral field plate **1132** extends longitudinally from the anode **1162** towards the cathode **1160** along length (L) of the substrate **1102**. The second lateral field plate **1133** extends longitudinally from the anode **1162** towards the cathode **1166** along the length (L) of the substrate **1102**. The first and second lateral field plates **1132**, **1133** extend laterally along the width (W) direction of the substrate **1102**.

[0132] A dielectric layer **1112** is disposed on the inner sidewalls of the apertures **1136** where the bottoms of the anode structure are buried in the substrate **1102** down into the channel(s). The lateral sides of the bottoms of the anode **1162** are received within the apertures **1136** through the gaps **1134** defined in the dielectric layers **1112** along the longitudinal sides of the apertures **1136**. The dielectric layers **1112** surround the sidewalls of the apertures **1136** containing the anode **1162** except where the gaps **1134** are defined in the aperture **1136**.

[0133] The first lateral field plate **1132** is located adjacent to the anode **1162** proximal to the cathode **1160** and extends longitudinally towards the cathode along the length (L) direction of the substrate **1102**. The second lateral field plate **1133** is located adjacent to the anode **1162** proximal to the cathode **1166** and extends longitudinally towards the cathode **1166** along the length (L) direction of the substrate **1102**. The dielectric layer **1112** is disposed on the sidewalls of the apertures **1136**.

[0134] The lateral field plates **1132**, **1133** disposed between the anode **1162** and the cathode **1160**, **1166** laterally pinch off the multiple 2DEG channels simultaneously, leading to an increased breakdown voltage. A single or multiple field plate(s) can be used to establish an electric field between the anode **1162** and the cathode **1160**, **1166**. To do so, two lateral field plates **1132**, **1133** are integrated symmetrically with the anode **1162**. The dielectric layer **1112** is disposed between the first lateral field plate **1132** and the channel. For at least one of the anode structures, the first and second lateral field plates **1132**, **1133** are configured to establish an electric field between the anode **1162** and the cathode **1160**. The thickness of the dielectric layer **1112** determines the pinch-off voltage in the lateral field plate region. The lateral field plates **1132**, **1133** establish an electric field in the lateral field plate regions near the cathodes **1160**, **1166**. Along the anode **1162** are the Schottky contacts **1164**.

[0135] FIG. **14** is a top view of a lateral Schottky diode **1200** with an anode structure comprising an anode (A) **1262** and lateral field plates **1232**, **1233** according to at least one aspect of the present disclosure. The lateral Schottky diode **1200** comprises a substrate **1202** and cathodes (C) **1260**, **1266**. The cathodes **1260**, **1266** are located on the top surface of the substrate **1202**. The substrate **1202** comprises a plurality of structures buried in apertures **1236** disposed in the substrate **1202**. The anode **1262** is located symmetrically between the cathodes **1260**, **1266**.

[0136] In the example depicted in FIG. **14**, the first and second lateral field plates **1232**, **1233** are rectangularly shaped and arranged in a symmetric configuration. The first and second lateral field plates **1232**, **1233** are not limited to the shape in the depicted example. The first lateral field plate **1232** is separated from the anode **1262** by a dielectric layer **1212** and extends longitudinally towards the cathode **1260** along length (L) of the substrate **1202**. The second lateral field plate **1233** is separated from the anode **1262** by the dielectric layer **1212** and extends longitudinally towards the cathode **1266** along the length (L) of the substrate **1202**. The first and second lateral field plates **1232**, **1233** extend laterally along the width (W) direction of the substrate **1202**.

[0137] The dielectric layer **1212** is disposed on the inner sidewalls of the apertures **1236** where the bottoms of the anode structure are buried in the substrate **1202** down into the channel(s). The lateral sides of the bottoms of the anode **1262** are received within the apertures **1236** through the gaps **1234** defined in the dielectric layers **1212** along the longitudinal sides of the apertures **1236**. The dielectric layers **1212** surround the sidewalls of the apertures **1236** including sidewall portions of the anode **1236** in the lateral direction along the width (W) of the substrate **1202** except where the gaps **1234** are defined in the apertures **1236**.

[0138] The first lateral field plate **1232** is separated from the anode **1262** by the dielectric layer **1212** and extends longitudinally towards the cathode **1260** along the length (L) direction of the substrate **1202**. The second lateral field plate **1233** is separated from the anode **1262** by the dielectric layer **1212** and extends longitudinally towards the cathode **1266** along the length (L) direction of the substrate **1202**. The dielectric layer **1212** is disposed on the sidewalls of the apertures **1236**.

[0139] The lateral field plates disposed between the anode **1262** and the cathode **1260**, **1266** laterally pinch off the multiple 2DEG channels simultaneously, leading to an increased breakdown voltage. A single or multiple field plate(s) can be used to establish an electric field between the anode **1262** and the cathode **1260**, **1266**. To do so, two lateral field plates **1232**, **1233** are disposed symmetrically on either side of the anode **1262**. The dielectric layer **1212** is disposed between the first lateral field plate **1232** and the channel. For at least one of the anode structures, the first and second lateral field plates **1232**, **1233** are configured to establish an electric field between the anode **1262** and the cathode **1260**, **1266**. The thickness of the dielectric layer **1212** determines the pinch-off voltage in the lateral field plate region. The lateral field plates **1232**, **1233** establish an electric field in the lateral field plate regions near the cathodes **1260**. Along the anode **1262** are the Schottky contacts **1264**.

[0140] FIG. **15** is a top view of a lateral Schottky diode **1300** with an anode structure comprising an anode (A) **1362** and lateral field plates **1332**, **1333**, **1338**, **1339** according to at least one aspect of the present disclosure. The lateral Schottky diode **1300** comprises a substrate **1302** and cathodes (C) **1360**, **1366**. The cathodes **1360**, **1366** are located on the top surface of the substrate **1302**. The substrate **1302** comprises a plurality of structures buried in apertures **1336** disposed in the substrate **1302**. The anode **1362** is located symmetrically between the cathodes **1360**, **1366**.

[0141] In the example depicted in FIG. **15**, the four lateral field plates **1332**, **1333**, **1338**, **1339** are rectangularly shaped and arranged in a symmetric configuration. The four lateral field plates **1332**, **1333**, **1338**, **1339** are not limited to the shape in the depicted example. The first and second lateral field plates **1332**, **1333** extend longitudinally from the anode **1362** towards the cathode **1366** along length (L) of the substrate **1302**. The third and fourth lateral field plates **1338**, **1339** extend longitudinally from the anode **1362** towards the cathode **1360** along the length (L) of the substrate **1302**. The four lateral field plates **1332**, **1333**, **1338**, **1339** extend laterally along the width (W) direction of the substrate **1302**.

[0142] A first dielectric layer **1312** is disposed on the inner sidewalls of the apertures **1336** where the bottoms of the anode structure are buried in the substrate **1302** down into the channel(s). The lateral sides of the bottoms of the anode **1362** are received within the apertures **1336** through the gaps **1334** defined in the first dielectric layer **1312** along the longitudinal sides of the apertures **1336**. The first dielectric layers **1312** surround the sidewalls of the apertures **1336** containing the anode **1362** except where the gaps **1334** are defined in the apertures **1336**. A second dielectric layer **1350** is disposed on the inner sidewalls of the first dielectric layer **1312**.

[0143] The first lateral field plate **1332** is located adjacent to the anode **1362** proximal to the cathode **1366** and extends longitudinally towards the cathode along the length (L) direction of the substrate **1302**. The second lateral field plate **1333** is located adjacent to the first lateral field plate **1332** proximal to the cathode **1366** and extends longitudinally towards the cathode **1366** along the length (L) direction of the substrate **1302**. The third lateral field plate **1338** is located adjacent to the anode **1362** proximal to the cathode **1360** and extends longitudinally towards the cathode **1360** along the length (L) direction of the substrate **1302**. The fourth lateral field plate **1339** is located adjacent to the third lateral field plate **1338** proximal to the cathode **1360** and extends longitudinally towards the cathode **1360** along the length (L) direction of the substrate **1302**. The dielectric layer **1312** is disposed on the sidewalls of the apertures **1336**.

[0144] The lateral field plates disposed between the anode **1362** and the cathode **1360**, **1366** laterally pinch off the multiple 2DEG channels simultaneously, leading to an increased breakdown

voltage. A single or multiple field plate(s) can be used to establish an electric field between the anode and the cathode. To do so, four lateral field plates **1332, 1333, 1338, 1339** are integrated symmetrically with the anode **1362**. The first dielectric layer **1312** is disposed between the first and third lateral field plates **1332, 1338** and the channel. The first and third lateral field plates **1332, 1338** laterally contact the first dielectric layer **1312** and longitudinally contact the second dielectric layer **1350**. The second and fourth lateral field plates **1333, 1339** laterally and longitudinally contact the second dielectric layer **1350**. For at least one of the anode structures, the four lateral field plates **1332, 1333, 1338, 1339** are configured to establish an electric field between the anode **1362** and the cathode **1360, 1366**. The thickness of the dielectric layers **1312, 1350** determines the pinch-off voltage in the lateral field plate region. The lateral field plates **1332, 1333, 1338, 1339** establish an electric field in the lateral field plate regions near the cathodes **1360, 1366**. Along the anode **1362** are the Schottky contacts **1364**.

[0145] FIG. **16** is a top view of a lateral Schottky diode **1400** with an anode structure comprising an anode (A) **1462** and lateral field plates **1432, 1433, 1438, 1439** according to at least one aspect of the present disclosure. The lateral Schottky diode **1400** comprises a substrate **1402** and cathodes (C) **1460, 1466**. The cathodes **1460, 1466** are located on the top surface of the substrate **1402**. The substrate **1402** comprises a plurality of structures buried in apertures **1436** disposed in the substrate **1402**. The anode **1462** is located symmetrically between the cathodes **1460, 1466**.

[0146] In the example depicted in FIG. **16**, the four lateral field plates **1432, 1433, 1438, 1439** are rectangularly shaped and arranged in a symmetric configuration. The four lateral field plates **1432, 1433, 1438, 1439** are not limited to the shape in the depicted example. The first and second lateral field plates **1432, 1433** extend longitudinally from the anode **1462** towards the cathode **1466** along length (L) of the substrate **1402**. The third and fourth lateral field plates **1438, 1439** extend longitudinally from the anode **1462** towards the cathode **1460** along the length (L) of the substrate **1402**. The four lateral field plates **1432, 1433, 1438, 1439** extend laterally along the width (W) direction of the substrate **1402**.

[0147] A first dielectric layer **1412** is disposed on the inner sidewalls of the apertures **1436** where the bottoms of the anode structure are buried in the substrate **1402** down into the channel(s). A second dielectric layer **1450** is disposed on the inner sidewalls of the first dielectric layer **1412**. The lateral sides of the bottoms of the anode **1462** are received within the apertures **1436** through the gaps **1434** defined in the dielectric layers **1412** along the longitudinal sides of the apertures **1436**. The first dielectric layers **1412** surround the sidewalls of the apertures **1436** including the sides of the anode **1462** along the width (W) direction except where the gaps **1434** are defined in the aperture **1436**. A second dielectric layer **1450** is disposed along the sidewalls of the apertures **1436**, about the sidewalls of the second and fourth lateral field plate **1433, 1439**, and in between the sidewalls of the first and second lateral field plates **1432, 1433**, and in between the sidewalls of the third and fourth lateral field plates **1438, 1439**.

[0148] The first lateral field plate **1432** is located adjacent to the anode **1462** separated by a portion of the first dielectric layer **1412** proximal to the cathode **1466** and extends longitudinally towards the cathode **1466** along the length (L) direction of the substrate **1402**. The first lateral field plate **1432** contacts the first dielectric layer **1412** on three sides and contacts the second dielectric layer **1450** on the side proximal to the cathode **1466**. The second lateral field plate **1433** is located adjacent to the first lateral field plate **1432** proximal to the cathode **1466** and extends longitudinally towards the cathode **1466** along the length (L) direction of the substrate **1402** and contacts the second dielectric layer **1450** on all four sides. The second lateral field plate **1432** does not contact the first dielectric layer **1412**. The third lateral field plate **1438** is located adjacent to the anode **1462** separated by a portion of the first dielectric layer **1412** proximal to the cathode **1460** and extends longitudinally towards the cathode **1460** along the length (L) direction of the substrate **1402**. The third lateral field plate **1438** contacts the first dielectric layer **1412** on three sides and contacts the second dielectric layer **1450** on the side proximal to the cathode **1460**. The fourth

lateral field plate **1439** is located adjacent to the third lateral field plate **1438** proximal to the cathode **1460** and extends longitudinally towards the cathode **1460** along the length (L) direction of the substrate **1402** and contacts the second dielectric layer **1450** on all four sides. The fourth lateral field plate **1439** does not contact the first dielectric layer **1412**. The dielectric layer **1412** is disposed on the sidewalls of the apertures **1436**.

[0149] The lateral field plates disposed between the anode **1462** and the cathode **1460**, **1466** laterally pinch off the multiple 2DEG channels simultaneously, leading to an increased breakdown voltage. A single or multiple field plate(s) can be used to establish an electric field between the anode and the cathode. To do so, four lateral field plates **1432**, **1433**, **1438**, **1439** are integrated symmetrically with the anode **1462**. The first dielectric layer **1412** is disposed between the first and third lateral field plate **1432**, **1438** and the channel(s) and the second dielectric layer **1450** is inserted between the second lateral field plate **1433** and the first dielectric layer **1412** and between the first and second lateral field plates **1432**, **1433**, and the second dielectric layer is inserted between the fourth lateral field plate **1439** and the first dielectric layer **1412** and between the third and fourth lateral field plates **1438**, **1439**. For at least one of the anode structures, the first lateral field plate **1432** laterally contacts the first dielectric layer **1412** and the second lateral field plate **1433** laterally contacts the second dielectric layer **1450**, while the third lateral field plate **1438** laterally contacts the first dielectric layer **1412** and the fourth lateral field plate **1439** laterally contacts the second dielectric layer **1450**. The thickness of the dielectric layer **1412**, **1450** determines the pinch-off voltage in the lateral field plate region. The lateral field plates **1432**, **1433**, **1438**, **1439** establish an electric field in the lateral field plate regions near the cathodes **1460**, **1466**. Along the anode **1462** are the Schottky contacts **1464**.

#### EXAMPLES

[0150] Examples of various aspects of end-effectors and surgical instruments of the present disclosure are provided below. An aspect of the end-effector or surgical instrument may include any one or more than one, and any combination of, the examples described below:

[0151] Example 1. A field-effect transistor (FET), comprising a substrate; source and drain electrodes on the substrate; a channel layer; a gate electrode structure comprising: a gate electrode in contact with the channel layer; and a first lateral field plate adjacent to the gate electrode; and a first dielectric layer disposed between the first lateral field plate and the channel layer; wherein the first lateral field plate is in contact with the first dielectric layer and is configured to modulate an electric field proximal to the gate electrode proximal to at least one of or both the drain or source electrodes.

[0152] Example 2. The FET of Example 1, wherein the gate electrode and the first lateral field plate are disposed on a surface of the substrate.

[0153] Example 3. The FET of any one of Examples 1-2, wherein a thickness of the first dielectric layer determines a pinch-off voltage in a field plate region proximal to the gate electrode structure.

[0154] Example 4. The FET of any one of Examples 1-3, wherein the gate electrode and the first lateral field plate comprise top and bottom portions, wherein the bottom portions of the gate electrode and the first lateral field plate are buried in an aperture defined in the substrate to a depth extending to the channel layer and the top portions of the gate electrode and the first lateral field plate extend above a surface of the substrate.

[0155] Example 5. The FET of Example 4, wherein the apertures define sidewalls and the first dielectric layer is disposed on the sidewalls except in lateral gaps disposed in the first dielectric layer configured to receive the bottom portion of the gate electrode such that the gate electrode is in lateral contact with the channel.

[0156] Example 6. The FET of Example 5, wherein the aperture and the gate electrode structure are disposed in an asymmetric arrangement on the substrate between the source and drain electrodes.

[0157] Example 7. The FET of Example 6, wherein the gate electrode structure is disposed in an asymmetric arrangement within the aperture.



[0158] Example 8. The FET of Example 7, wherein the first lateral field plate extends longitudinally from the gate electrode and the bottom portion of the first lateral field plate is in lateral contact with the first dielectric layer.

[0159] Example 9. The FET of any one of Examples 7-8, further comprising: a second dielectric layer disposed on sidewalls defined by the first dielectric layer; and a second lateral field plate disposed adjacent to the first lateral field plate; wherein the first lateral field plate laterally contacts the first dielectric layer and longitudinally contacts the second dielectric layer; wherein the second lateral field plate laterally contacts the second dielectric layer; and wherein a thickness of the first and second dielectric layers determines a pinch-off voltage in the field plate region.

[0160] Example 10. The FET of any one of Examples 7-9, wherein the first dielectric layer is further disposed on sidewalls defined by the bottom portion of the gate electrode in a lateral direction along a width (W) of the substrate and wherein the first lateral field plate is separated from the gate electrode by a portion of the first dielectric layer.

[0161] Example 11. The FET of Example 10, further comprising: a second dielectric layer disposed over the first dielectric layer; and a second lateral field plate adjacent to the first lateral field plate, wherein the second lateral field plate is in lateral contact with the second dielectric layer and is separated from the first lateral field plate by a portion of the second dielectric layer.

[0162] Example 12. A field-effect transistor (FET), comprising: a substrate; source and drain electrodes on the substrate; a channel layer; a gate electrode structure comprising: a gate electrode in contact with the channel; a first lateral field plate adjacent to one side of the gate electrode; and a second lateral field plate adjacent to an opposite side of the gate electrode; wherein the first and second lateral field plates are disposed in a symmetrical arrangement relative to the gate electrode; and a first dielectric layer disposed between the first and second lateral field plates and the channel layer; wherein the first and second lateral field plates are in contact with the first dielectric layer and are configured to modulate an electric field proximal to the gate electrode proximal to at least one of or both the drain or source electrodes.

[0163] Example 13. The FET of Example 12, wherein the gate electrode and the first and second lateral field plates are disposed on a surface of the substrate.

[0164] Example 14. The FET of any one of Examples 12-13, wherein a thickness of the first dielectric layer determines a pinch-off voltage in a field plate region proximal to the gate electrode structure.

[0165] Example 15. The FET of any one of Examples 12-14, wherein the gate electrode and the first and second lateral field plates comprise top and bottom portions, wherein the bottom portions of the gate electrode and the first and second lateral field plates are buried in an aperture defined in the substrate to a depth extending to the channel layer and the top portions of the gate electrode and the first and second lateral field plates extend above a surface of the substrate.

[0166] Example 16. The FET of Example 15, wherein the apertures define sidewalls and the first dielectric layer is disposed on the sidewalls except in lateral gaps disposed in the first dielectric layer configured to receive the bottom portion of the gate electrode such that the gate electrode is in lateral contact with the channel.

[0167] Example 17. The FET of any one of Examples 12-16, further comprising: a second dielectric layer disposed over the first dielectric layer; a third lateral field plate adjacent to the first lateral field plate; and a fourth lateral field plate adjacent to the second lateral field plate; wherein the third and fourth lateral field plates are in lateral contact with the second dielectric layer.

[0168] Example 18. A field-effect transistor (FET), comprising: a substrate; source and drain electrodes on the substrate; a channel layer; a gate electrode structure comprising: a gate electrode in contact with the channel layer; and a first lateral field plate adjacent to the gate electrode; a first dielectric layer disposed between the first lateral field plate and the channel layer; and a dielectric structure buried in the substrate remote from the gate electrode structure; wherein the first lateral field plate is in contact with the first dielectric layer and is configured to modulate an electric field

proximal to the gate electrode proximal to at least one of or both the drain or source electrodes.

[0169] Example 19. The FET of Example 18, wherein the buried dielectric structures shape equipotential lines developed between the first dielectric layer adjacent to the gate electrode structure.

[0170] Example 20. The FET of any one of Examples 18-19, wherein the gate electrode and the first lateral field plate comprise top and bottom portions, wherein the bottom portions of the gate electrode and the first lateral field plate are buried in an aperture defined in the substrate to a depth extending to the channel layer and the top portions of the gate electrode and the first lateral field plate extend above a surface of the substrate, and wherein the first lateral field plate extends longitudinally from the gate electrode and the bottom portion of the first lateral field plate is in lateral contact with the first dielectric layer.

[0171] Example 21. A lateral Schottky diode, comprising: a substrate comprising a plurality of structures buried in apertures disposed in the substrate; an anode structure comprising: an anode; and lateral field plates; and a cathode located on a top surface of the substrate.

[0172] Example 22. The lateral Schottky diode of Example 21, further comprising another cathode wherein the anode is located symmetrically between the cathodes.

[0173] Example 23. The lateral Schottky diode of any one of Examples 21-22, wherein the first and second lateral field plates are rectangularly shaped and arranged in a symmetric configuration.

[0174] Example 24. The lateral Schottky diode of any one of Example 21-23, wherein a first lateral field plate extends longitudinally from the anode towards the cathode along a length (L) of the substrate, a second lateral field plate extends longitudinally from the anode towards the cathode along the length (L) of the substrate, wherein the first and second lateral field plates extend laterally along a width (W) of the substrate.

[0175] Example 25. The lateral Schottky diode of any one of Examples 21-24, further comprising a dielectric layer disposed on inner sidewalls of the apertures, wherein bottom portions of the anode are buried in the substrate.

[0176] Example 26. The lateral Schottky diode of any one of Examples 21-25, wherein the lateral field plates are located between the anode and the cathode.

[0177] While several forms have been illustrated and described, it is not the intention of Applicant to restrict or limit the scope of the appended claims to such detail. Numerous modifications, variations, changes, substitutions, combinations, and equivalents to those forms may be implemented and will occur to those skilled in the art without departing from the scope of the present disclosure. Moreover, the structure of each element associated with the described forms can be alternatively described as a means for providing the function predisposed by the element. Also, where materials are disclosed for certain components, other materials may be used. It is therefore to be understood that the foregoing description and the appended claims are intended to cover all such modifications, combinations, and variations as falling within the scope of the disclosed forms. The appended claims are intended to cover all such modifications,

[0178] One or more components may be referred to herein as “configured to,” “configurable to,” “operable/operative to,” “adapted/adaptable,” “able to,” “conformable/condisposed to,” etc. Those skilled in the art will recognize that “configured to” can generally encompass active-state components and/or inactive-state components and/or standby-state components, unless context requires otherwise.

[0179] The terms “proximal” and “distal” are used herein with reference to a clinician manipulating the handle portion of the surgical instrument. The term “proximal” refers to the portion closest to the clinician and the term “distal” refers to the portion located away from the clinician. It will be further appreciated that, for convenience and clarity, spatial terms such as “vertical”, “horizontal”, “up”, and “down” may be used herein with respect to the drawings. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and/or absolute.

[0180] Those skilled in the art will recognize that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to claims containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations.

[0181] In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that typically a disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms unless context dictates otherwise. For example, the phrase “A or B” will be typically understood to include the possibilities of “A” or “B” or “A and B.”

[0182] With respect to the appended claims, those skilled in the art will appreciate that any recited operations therein may generally be predisposed in any order. Also, although various operational flow diagrams are presented in a sequence(s), it should be understood that the various operations may be perdisposed in other orders than those which are illustrated, or may be perdisposed concurrently. Examples of such alternate orderings may include overlapping, interleaved, interrupted, reordered, incremental, preparatory, supplemental, simultaneous, reverse, or other variant orderings, unless context dictates otherwise. Furthermore, terms like “responsive to,” “related to,” or other past-tense adjectives are generally not intended to exclude such variants, unless context dictates otherwise.

[0183] It is worthy to note that any reference to “one aspect,” “an aspect,” “an exemplification,” “one exemplification,” and the like means that a particular feature, structure, or characteristic described in connection with the aspect is included in at least one aspect. Thus, appearances of the phrases “in one aspect,” “in an aspect,” “in an exemplification,” and “in one exemplification” in various places throughout the specification are not necessarily all referring to the same aspect. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner in one or more aspects.

[0184] Any patent application, patent, non-patent publication, or other disclosure material referred

to in this specification and/or listed in any Application Data Sheet is incorporated by reference herein, to the extent that the incorporated materials is not inconsistent herewith. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

[0185] In summary, numerous benefits have been described which result from employing the concepts described herein. The foregoing description of the one or more forms has been presented for purposes of illustration and description. It is not intended to be exhaustive or limiting to the precise form disclosed. Modifications or variations are possible in light of the above teachings. The one or more forms were chosen and described in order to illustrate principles and practical application to thereby enable one of ordinary skill in the art to utilize the various forms and with various modifications as are suited to the particular use contemplated. It is intended that the claims submitted herewith define the overall scope.

## Claims

1. A lateral Schottky diode, comprising: a substrate comprising a plurality of conductive or semiconductive structures at least partially buried in apertures disposed in the substrate; an anode structure comprising: an anode; and first and second lateral field plates arranged adjacent to the anode; and a first cathode disposed on a top surface of the substrate.
2. The lateral Schottky diode of claim 1, comprising a second cathode wherein the anode is symmetrically disposed between the first and second cathodes.
3. The lateral Schottky diode of claim 1, wherein the lateral field plates comprise a first and second lateral field plate, each having a rectangular shape and arranged symmetrically relative to the anode.
4. The lateral Schottky diode of claim 2, wherein the lateral field plates comprise a first lateral field plate disposed adjacent to the anode and a second lateral field plate adjacent to an opposite side of the anode.
5. The lateral Schottky diode of claim 4, wherein the first lateral field plate extends from the anode towards the first cathode along a longitudinal direction of the substrate; and the second lateral field plate extends from the anode toward the second cathode along the longitudinal direction of the substrate; wherein the both lateral field plates extend laterally across a width (W) of the substrate.
6. The lateral Schottky diode of claim 1, wherein the apertures define sidewalls, and a first dielectric layer is disposed on the sidewalls excluding lateral gaps formed within the apertures.
7. The lateral Schottky diode of claim 1, further comprising a dielectric layer disposed on inner sidewalls of the apertures, wherein a bottom portion of the anode is buried within the substrate.
8. The lateral Schottky diode of claim 1, wherein the lateral field plates comprise a first and second lateral field plate, wherein the first lateral field plate is located between the anode and the first cathode, and the second lateral field plate is disposed on the opposite side of the anode relative to the first lateral field plate.
9. A lateral Schottky diode, comprising: a substrate; a first cathode disposed on a top surface of the substrate; a second cathode disposed on the top surface of the substrate; and an anode structure comprising: an anode; a first lateral field plate adjacent to the anode; and a second lateral field plate adjacent to the anode.
10. The lateral Schottky diode of claim 9, wherein the anode, the first lateral field plate, and the second lateral field plate comprise top and bottom portions, wherein bottom portions of the anode and the first lateral field plate are embedded within an aperture in the substrate, and top portions of the anode and the first lateral field plate extend above a surface of the substrate.

- 11.** The lateral Schottky diode of claim 10, wherein the aperture defines sidewalls and a first dielectric layer disposed along the aperture sidewalls, excluding areas defined as lateral gaps.
- 12.** The lateral Schottky diode of claim 10, comprising a dielectric disposed on sidewalls of the aperture including sidewall portions of the anode along a lateral direction of the substrate, except at locations where lateral gaps are present.
- 13.** The lateral Schottky diode of claim 10, further comprising a dielectric layer disposed on inner sidewalls of the aperture and sidewall portions of the anode.
- 14.** A lateral Schottky diode, comprising: a substrate; a first cathode located on a top surface of the substrate; a second cathode located on the top surface of the substrate; and an anode structure comprising: an anode; a first lateral field plate adjacent to the anode; a second lateral field plate adjacent to the anode; a third lateral field plate adjacent to and laterally outward from the first lateral field plate; and a fourth lateral field plate adjacent to and laterally outward from the second lateral field plate.
- 15.** The lateral Schottky diode of claim 14, wherein the anode and the first lateral field plate comprise top and bottom portions, wherein the bottom portions of the anode and the first lateral field plate are embedded in an aperture defined in the substrate and the top portions of the anode and the first lateral field plate extend above a surface of the substrate.
- 16.** The lateral Schottky diode of claim 15, wherein the aperture defines sidewalls, and a first dielectric layer is disposed thereon, excluding regions of lateral gaps.
- 17.** The lateral Schottky diode of claim 14, comprising: a first dielectric layer disposed between the first and second lateral field plates; and a second dielectric layer disposed between the third and fourth lateral field plates and the first dielectric layer.
- 18.** The lateral Schottky diode of claim 17, wherein the first and second lateral field plates are in lateral contact the first dielectric layer.
- 19.** The lateral Schottky diode of claim 17, wherein the second dielectric layer is disposed on sidewalls defined by the first dielectric layer and is in lateral contact with the third and fourth lateral field plates.
- 20.** The lateral Schottky diode of claim 19, wherein the first dielectric layer is disposed along a sidewall portion of the anode, and the second dielectric layer is disposed between the first and third field plates and between the second and fourth field plates.
-