

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250253628

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Olander; John A.

---

### CABLE POSITIONING ASSEMBLY AND PULLING SYSTEM

---

#### Abstract

A cable pulling system and associated method are shown. Examples include positioning joints that allows a pulling boom to move up or down and side to side, while maintaining alignment of a pulling cable between pulleys. Example methods include positioning a pulling boom within a conduit box and pulling an electrical cable through a conduit into the conduit box.

---

**Inventors:** Olander; John A. (Clayton, WI)

**Applicant:** TT Technologies, Inc. (Aurora, IL)

**Family ID:** 77922444

**Appl. No.:** 19/189704

**Filed:** April 25, 2025

#### Related U.S. Application Data

parent US continuation 18223274 20230718 parent-grant-document US 12288968 child US 19189704

parent US continuation 17223346 20210406 parent-grant-document US 11735894 child US 18223274

us-provisional-application US 63006334 20200407

---

#### Publication Classification

**Int. Cl.:** H02G1/08 (20060101)

**U.S. Cl.:**

**CPC** H02G1/085 (20130101); H02G1/083 (20130101); H02G1/08 (20130101)

---

## Background/Summary

CLAIM OF PRIORITY [0001] This patent application is a continuation of U.S. patent application Ser. No. 18/223,274, filed Jul. 18, 2023, which is a continuation of U.S. patent application Ser. No. 17/223,346, filed Apr. 6, 2021, which claims the benefit of priority, under 35 U.S.C. § 119 (e), to U.S. Provisional Patent Application Ser. No. 63/006,334, entitled “CABLE POSITIONING ASSEMBLY AND PULLING METHOD,” filed on Apr. 7, 2020, which are hereby incorporated by reference herein in their entirety.

### TECHNICAL FIELD

[0002] Embodiments described herein generally relate to pulling cables. Selected specific examples relate to pulling cables through conduit into electrical boxes or other enclosures.

### BACKGROUND

[0003] During construction or maintenance, electrical cables must generally be installed into conduit in order to comply with building codes or other standards. The installation of cables into electrical or conduit boxes is often accomplished by pulling cables through the conduit. A significant amount of force is required due to the weight of the cables, the resistance against the conduit, and the distance to be pulled.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0004] In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. Like numerals having different letter suffixes may represent different instances of similar components. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments discussed in the present document.

[0005] FIG. 1 illustrates an isometric view of a cable positioning assembly and pulling system in accordance with at least one example of the present application.

[0006] FIG. 2 illustrates an isometric view of a lateral positioning joint of the cable positioning assembly and pulling system, in accordance with at least one example of the present application.

[0007] FIG. 3 illustrates an isometric view of a pulling boom of the cable positioning assembly and pulling system, in accordance with at least one example of the present application.

[0008] FIG. 4A illustrates an isometric view of the cable positioning assembly and pulling system in accordance with at least one example of the present application.

[0009] FIG. 4B illustrates an isometric view of the cable positioning assembly and pulling system in accordance with at least one example of the present application.

[0010] FIG. 5 illustrates a perspective view of an example of the cable positioning assembly and pulling system in operation.

[0011] FIG. 6 illustrates a method for using the cable positioning assembly and pulling system in accordance with at least one example of the present application.

### DETAILED DESCRIPTION

[0012] The following description and the drawings sufficiently illustrate specific examples to enable those skilled in the art to practice them. Other examples may incorporate structural, process, or other changes. Portions and features of some examples may be included in, or substituted for, those of other examples. Examples set forth in the claims encompass all available equivalents of those claims.

[0013] A variety of devices and techniques are described in the present disclosure for pulling cables through conduit. Each device or technique can generally involve positioning a power winch, aligning a pulling cable between the power winch and a conduit, including positioning the pulling

cable on various guide pulleys that can be mounted to pulling devices. Precise positioning of the pulling cable is desired in order to allow the winch and pulling devices to pull the cable freely through the conduit with minimal resistance. Additional difficulties arise when cables must be pulled into a conduit terminating inside an electrical box or another type of enclosure.

[0014] The devices and methods of the present disclosure are intended to address current disadvantages of the devices and techniques used in pulling cables through conduit, by providing a cable positioning assembly and pulling system capable of being assembled and positioned in a reduced amount of time. The cable positioning assembly and pulling system disclosed is also capable of pulling cable directly into a conduit terminating inside an electrical box or another type of enclosure.

[0015] FIG. 1 illustrates an isometric view of a cable positioning assembly and pulling system **100** in accordance with at least one example of the present application. The cable positioning assembly and pulling system **100** can include a winch mount **102**, a winch fitting **104**, and a boom mount **106**. The winch mount **102** can include a first pulley **110**. The boom mount **106** can include a second pulley **112**. The winch mount **102** and the boom mount **106** can be pivotably coupled to form a lateral positioning joint **108**. The lateral positioning joint **108** can allow for lateral movement between the winch mount **102** and the boom mount **106**. The winch mount **102** can include the winch fitting **104**. The winch fitting **104** can be configured to couple the winch mount **102** to a power winch.

[0016] The cable positioning assembly and pulling system **100** can include a pulling boom **114** including a first end **116** and a second end **118**. The first end **116** of the pulling boom **114** and the boom mount **106** can be pivotably coupled to form a vertical positioning joint **109**. The vertical positioning joint **109** can allow for vertical movement of the winch mount **102** and the boom mount **106** with respect to the pulling boom **114**. The pulling boom **114** can include a first boom plate **120** and a second boom plate **122**. A length of the pulling boom **114** can define a central axis **A 1**.

[0017] The pulling boom **114** can include a pair of supporting legs **124**. The pulling boom **114** can be supported with the supporting legs **124**. The supporting legs **124** can be height adjustable. The supporting legs **124** can each include a leg base **126**. The leg bases **126** can improve the stability of the pulling boom **114** during a pulling operation. The pulling boom can include one or more handles **128**. The cable positioning assembly and pulling system **100** can be lifted, carried, or otherwise positioned with the handles **128**.

[0018] In the operation of some examples, the cable positioning assembly and pulling system **100** can be used to position a pulling cable coupled to a power winch in preparation for a pulling operation. The lateral positioning joint **108** can allow the first pulley **110** and second pulley **112** to be laterally adjusted with respect to each other to aid in aligning and positioning the pulling cable and pulling boom **114**. The vertical positioning joint **109** can allow the pulling boom to be vertically adjusted to aid in aligning and positioning the pulling cable and the pulling boom **114**.

[0019] The second end **118** of the pulling boom **114** can be positioned within an electrical box or an enclosure. The pulling cable can be run from the power winch to the second end of the pulling boom **114**. The pulling cable can be run into a proximal end of a conduit positioned inside the electrical box, and then through to a distal end of the conduit. Electrical cables can be coupled to the pulling cable at the distal end of the conduit, and the power winch subsequently operated to pull the pulling cable and any attached electrical cables into the electrical box.

[0020] FIG. 2 illustrates an isometric view of a lateral positioning joint **108** of the cable positioning assembly and pulling system **100**, in accordance with at least one example of the present application. The lateral positioning joint **108** can include the winch mount **102**, the winch fitting **104**, the boom mount **106**, the first pulley **110** and the second pulley **112**. The winch mount **102** can further include a first winch mount plate **132** and a second winch mount plate **134**. One or more plate couplers **135** can couple the first winch mount plate **132** to the second winch mount plate **134**.

[0021] The winch mount **102** can include a winch mount first end **136** and a winch mount second

end **138**. The winch mount first end **136** can include a first winch mount knuckle **140**. The first winch mount knuckle **140** can be coupled to the winch mount **102** between the first winch mount plate **132** and the second winch mount plate **134**. The first winch mount knuckle **140** can also be coupled to a plate coupler **135**. The winch mount second end **138** can include a second winch mount knuckle **142**. The second winch mount knuckle **142** can be coupled to the winch mount **102** between the first winch mount plate **132** and the second winch mount plate **134**. The first winch mount knuckle **140** can also be coupled to a plate coupler **135**.

[0022] The boom mount **106** can include a first boom mount plate **144** and a second boom mount plate **146**. One or more of the plate couplers **135** can couple the first boom mount plate **144** to the second boom mount plate **146**. The boom mount **106** can include a boom mount first end **148** and a boom mount second end **150**. The boom mount first end **148** can include a first boom mount knuckle **152**. The first boom mount knuckle **152** can be coupled to the boom mount **106** between the first boom mount plate **144** and the second boom mount plate **146**. The first boom mount knuckle **152** can be also coupled to a plate coupler **135**. The boom mount second end **150** can include a second boom mount knuckle **154**. The second boom mount knuckle **154** can be coupled to the boom mount **106** between the first boom mount plate **144** and the second boom mount plate **146**. The second boom mount knuckle can be also coupled to a plate coupler **135**.

[0023] The first winch mount knuckle **140**, the second winch mount knuckle **142**, the first boom mount knuckle **152**, and the second boom mount knuckle **154** can generally form closed-loop shapes. The first winch mount knuckle **140** can be configured to engage with the first boom mount knuckle **152**. A first hinge pin **156** can be inserted through the first winch mount knuckle **140** and the first boom mount knuckle **152** to form a first hinge **158**. The second winch mount knuckle **142** can be configured to engage with the second boom mount knuckle **154**. A second hinge pin **160** can be inserted through the second winch mount knuckle **142** and the second boom mount knuckle **154** to form a second hinge **162**. The first hinge pin **156** and the second hinge pin **160** can be secured using various types of fasteners. For example, the first hinge pin **156** and the second hinge pin **160** can each include a bore at one end for a retaining pin to be inserted into, or a threaded end to engage with a threaded nut.

[0024] The first hinge **158** and the second hinge **162** can pivotably couple the winch mount **102** to the boom mount **106**. The first hinge **158** and the second hinge **162** can rotate around a vertical axis generally defined by the first hinge pin **156** and the second hinge pin **160**, respectively. The winch mount **102**, the boom mount **106**, the first hinge **158**, and the second hinge **162** can form the lateral positioning joint **108**. The lateral positioning joint **108** can have a 180-degree range of rotational motion. The lateral positioning joint **108** can also have a range of rotational motion between 90 and 160 degrees, 80 and 150 degrees, and 100 and 170 degrees.

[0025] The lateral positioning joint **108**, including the winch mount **102**, the boom mount **106**, the first hinge **158**, and the second hinge **162**, can be robustly constructed to resist operational forces. The winch mount **102** and the boom mount **106** can each include one or more plate couplers **135** coupling the first winch mount plate **132** to the second winch mount plate **134**, and the first boom mount plate **144** to the second boom mount plate **146**, respectively. The plate couplers **135** can act as bracing elements positioned between the first winch mount plate **132** and the second winch mount plate **134**, and between the first boom mount plate **144** and the second boom mount plate **146**, ensuring the winch mount **102** and the boom mount **106** are sufficiently strong and rigid. Additionally, the first hinge **158** and the second hinge **162**, which can couple the winch mount **102** to the boom mount **106**, can be precisely and robustly constructed to ensure that the lateral positioning joint **108** can resist bending, compression, tension, torsion, and shear forces during a pulling operation.

[0026] The first pulley **110** can be coupled to the winch mount **102** with a first pulley axle **164**. The second pulley **112** can be coupled to the boom mount **106** with a second pulley axle **166**. The first pulley **110** and the second pulley **112** can rotate around a lateral axis generally defined by the first

pulley axle **164** and the second pulley axle **166**, respectively. The first pulley **110** and the second **112** pulleys can be configured to have a diameter sufficient to enable the pulleys to accommodate and pull large power cables or other types of cables, such as fiber optic cables. The first pulley axle **164** and the second pulley axle **166** can be bolts that pass laterally through the first boom plate **120** and the second boom plate **122**. The first pulley axle **164** and the second pulley axle **166** can be secured using various types of fasteners. For example, the first pulley axle **164** and the second pulley axle **166** can include a bore at one end for a retaining pin to be inserted into, or a threaded end to engage with a threaded nut.

[0027] FIG. **3** illustrates an isometric view of the pulling boom **114** of the cable positioning assembly and pulling system **100**, in accordance with at least one example of the present application. The pulling boom can include the supporting legs **124**. The supporting legs can each include one or more leg apertures **168**. The supporting legs **124** can be coupled to the pulling boom **114** between the first end **116** and the second end **118**. The pulling boom **114** can include leg mounts **170**. The leg mounts **170** can pivotably couple the supporting legs **124** to the pulling boom **114**. The leg mounts **170** can include each include one or more mount apertures **172**. The leg apertures **168** can engage with the mount apertures **172** to allow the supporting legs **124** to be height adjustable.

[0028] The leg mounts **170** can be configured to allow the supporting legs **124** to pivot around a lateral axis generally defined by the leg mounts **170**, in order to pivot the supporting legs **124** between a transport orientation to an active orientation. In the transport orientation, the supporting legs **124** can extend generally parallel to the central axis **A 1**. This can provide the benefit of transporting the pulling boom **114** more easily. In the active orientation, the supporting legs **124** can extend generally perpendicular to the central axis **A 1**, in order to support and position the pulling boom **114** during a pulling operation.

[0029] The pulling boom **114** can include the handles **128**. The handles **128** can be positioned between the first end **116** and the second end **118** of the pulling boom **114**. One or more of the handles **128** can be positioned on one, or both, of the first boom plate **120** and the second boom plate **122**. The handles **128** can generally comprise plates with gripping slots formed therein. The handles **128** can be coupled to the pulling boom in a fixed position with a variety of types of fasteners. For example, the handles **128** can be coupled to the pulling boom **114** with screws, bolts, or rivets. The handles **128** can also be welded to the pulling boom **114**.

[0030] The handles **128** can also have a generally curved shape that can form a guard surface **174**. The guard surface **174** of each handle **128** can extend substantially over and across a space generally defined between the first boom plate **120** and the second boom plate **122**. The guard surface **174** of each handle **128** can prevent a pulling cable from moving away from the pulling boom **114** in the event of a pulling cable failure. The handles **128** can comprises a single piece of material, such as plate steel, that can provide both the benefits of convenient gripping points for handling the boom, as well as protection for the user against cable recoil.

[0031] The pulling boom **114** can include a third pulley **130**. The third pulley **130** can be positioned at the second end **118** of the pulling boom **114**. The pulling boom **114** can also include a fourth pulley **176**, a fifth pulley **178**, and a sixth pulley **180**. The third pulley **130**, fourth pulley **176**, fifth pulley **178**, and sixth pulley **180** can each be configured to guide a pulling cable. The third **182**, the fourth **184**, the fifth **186**, and the sixth **188** pulley axles can respectively couple the third pulley **130**, the fourth pulley **176**, the fifth pulley **178**, and the sixth pulley **180** to the pulling boom **114**. The third pulley **130**, the fourth pulley **176**, the fifth pulley **178**, and the sixth pulley **180** can each rotate around a lateral axis generally defined by a third **182**, a fourth **184**, a fifth **186**, and a sixth **188** pulley axle, respectively.

[0032] The third pulley **130**, the fourth pulley **176**, the fifth pulley **178**, and the sixth pulley **180** can be arranged at the second end **118** of the pulling boom **114**, or otherwise arranged between the first end **116** and the second end **118** of the pulling boom. The third pulley **130**, the fourth pulley

**176**, the fifth pulley **178**, and the sixth pulley **180** can be configured to be coupled to the pulling boom **114** generally along a curvature of the second end **118** of the pulling boom **114**. The third pulley **130**, the fourth pulley **176**, the fifth pulley **178**, and the sixth pulley **180** can each be configured to have a diameter sufficient to enable the pulleys to accommodate and pull large power cables or other cables types, such as fiber optic cables. The third pulley **130**, the fourth pulley **176**, the fifth pulley **178**, and the sixth pulley **180** can be configured to form a progressive curve having an overall radius sufficient to guide a pulling cable between the first boom plate **120** and the second boom plate **122** of the pulling boom **114**.

[0033] The third **182**, the fourth **184**, the fifth **186**, and the sixth **188** pulley axles can be bolts that pass laterally through the first boom plate **120** and the boom plate second **122**. The third **182**, the fourth **184**, the fifth **186**, and the sixth **188** pulley axles can be secured using various types of fasteners. For example, the third **182**, the fourth **184**, the fifth **186**, and the sixth **188** pulley axles can each include a bore at one end for a retaining pin to be inserted into, or a threaded end to engage with a threaded nut.

[0034] The pulling boom **114** can include a first latch **190** and a second latch **192**. The first latch **190** and the second latch **192** can each include a latch first end **194** and a latch second end **196**. The latch first ends **194** of each of the first latch **190** and the second latch **192** can include latch recesses **198**. The latch recesses **198** can be generally curved recesses formed in the first latch **190** and the second latch **192**. The latch recesses **198** can be configured to engage the second pulley axle **166**. The pulling boom **114** can include two boom recesses **200**. One boom recess **200** can be formed in each of the first boom plate **120** and the second boom plate **122**, at the first end **116** of the pulling boom **114**. The boom recesses **200** can be configured to engage the second pulley axle **166**.

[0035] The second latch ends **196** of each of the first latch **190** and the second latch **192** can be coupled to the pulling boom **114** with a latch fastener **202**. The latch fastener **202** can be various types of fasteners, such as a threaded bolt configured to engage with the first boom plate **120**, the second boom plate **122**, or a threaded nut. The latch fastener **202** can allow the first latch **190** and the second latch **192** to pivot around a lateral axis generally defined by the latch fastener **202**. An oblong slot **203** can also be formed in the second latch end **196** of either the first latch **190** or the second latch **192**.

[0036] The first latch **190** and the second latch **192** can be configured to engage and disengage the second pulley axle **166** by pivoting. The first latch **190** or the second latch **192** can be coupled to a latch spring **204**. A first end of the latch spring **204** can be coupled to a latch second end **196** of either the first latch **190** or the second latch **192**. A second end of the latch spring **204** can be coupled to the first boom plate **120** or the second boom plate **122** of the pulling boom **114**. The latch spring **204** can be configured to bias the first latch **190** or the second latch **192** toward the second pulley axle **166**.

[0037] The winch mount **102**, the winch fitting **104**, the boom mount **106**, the first pulley **110**, the second pulley **112**, the pulling boom **114**, the first boom plate **120**, the second boom plate **122**, the supporting legs **124**, the leg bases **126**, the handles **128**, the third pulley **130**, the first hinge pin **156**, the second hinge pin **160**, the leg mounts **170**, the fourth pulley **176**, the fifth pulley **178**, the sixth pulley **180**, the third pulley axle **182**, the fourth pulley axle **184**, the fifth pulley axle **186**, the sixth pulley axle **188**, the first latch **190**, the second latch **192**, the latch fastener **202**, and the latch springs **204** can each be made from steel, although the invention is not so limited. Other metals such as aluminum, or other metal alloys are also within the scope of the invention.

[0038] FIGS. **4A** and **4B** illustrate isometric views of the cable positioning assembly and pulling system **100** in accordance with at least two examples of the present application. The first latch **190** and the second latch **192** can each have a closed orientation and an open orientation. The first latch **190** and the second latch **192** can pivot between the closed orientation and the open configuration by rotating around a lateral axis generally defined by the latch fastener **202**. When in the closed orientation, the first latch **190** and the second latch **192** can couple the first end **116** of the pulling

boom **114** to the second pulley axle **166** as shown in FIG. 4A. When in the open orientation, the first latch **190** and the second latch **192** can allow the first end **116** of the pulling boom **114** to be de-coupled from the second pulley axle **166**, as shown in FIG. 4B.

[0039] The cable positioning assembly and pulling system **100** can further include a latch retaining feature **206**, and a latch retainer **208**. The latch first ends **194** of either the first latch **190** or the second latch **192** can include the latch retaining feature **206**. The latch retaining feature **206** can be a generally hook shaped projection formed on either the first latch **190** or the second latch **192**. The latch retaining feature **206** can be configured to engage the latch retainer **208**. The latch retainer **208** can be a bolt head, a dowel, or a protrusion extending laterally from first boom plate **120** or the second boom plate **122**, of the pulling boom **114**. The oblong slot **203** formed in the first latch **190** or the second latch **192** latches can allow the latch retaining feature **206** to engage the latch retainer **208**. The oblong slot **203** formed in either of the first latch **190** or the second latch **192** can allow the first latch **190** or the second **192** latch to translate with respect to the latch fastener **202**. When the first latch **190** or the second latch **192** translates, the latch retaining feature **206** can engage the latch retainer **208** to lock and secure the first latch **190**, or the second latch **192**, in the open orientation.

[0040] The latch retaining feature **206** can engage the latch retainer **208** and prevent either the first latch **190** or the second latch **192** from automatically returning to the closed orientation through gravity or from spring pressure from the latch spring **204**. Advantageously, this can allow for a single person to de-couple the boom mount **106** from the pulling boom **114** after a pulling operation, as two persons would be otherwise be required to lift both the first latch **190** and the second latch **192**, while simultaneously moving the boom mount **106** and second pulley axle **166** away from pulling boom **114**.

[0041] In the operation of some examples, the boom mount **106** and the second pulley axle **166** can be inserted into the pulling boom **114**, in a direction generally along the central axis A **1**. The latch first ends **194** of the first latch **190** and the second latch **192** can be shaped and configured to ride up and over a top surface of the second pulley axle **166**, upon contact with the second pulley axle **166**. The first latch **190** and the second latch **192** can be configured to close automatically under spring force generated by the latch spring **204** once the first latch **190** and the second latch **192** ride up and over a top surface of the second pulley axle **166**.

[0042] In one example having one latch **190** that is always biased to a latching position provides enhanced safety while at the same time providing convenience for a single user. If an operator forgets to actuate the latch **190**, it will fail safe (i.e. will stay latched if left unattended). In examples described, by allowing only one latch **192** to be held open while the first latch **190** is fail safe, provides a level of safety while also providing a convenience for a single user.

[0043] FIG. 5 illustrates a perspective view of an example of the cable positioning assembly and pulling system **100** in operation. The example illustrated in FIG. 5 is not necessarily drawn to scale. The second end **118** of the pulling boom **114** can be positioned within an electrical box **210**. A pulling cable **212** can be run from a power winch **214** through the winch fitting **104**, the first pulley **110**, the second pulley **112**, and then along a length of the pulling boom **114** between the first boom plate **120** and the second boom plate **122**, and then through the third pulley **130** at the second end **118** of the pulling boom **114**. The pulling cable **212** can then be run into a proximal end **216** of a conduit **218** terminating inside the electrical box **210**. The pulling cable **212** can then be run to a distal end **220** of the conduit **218**, which can be located below a ground level **222**. Electrical cables can then be coupled to the pulling cable, and the winch subsequently operated to pull the pulling cable **212**, and any attached electrical cables, back through the conduit **212** into the electrical box **210**.

[0044] The lateral positioning joint **108** can allow the pulling boom **114** to be moved laterally when attached to the power winch **214**. The lateral positioning joint **108** can be compact, as a result of the proximity of the first pulley **110** with respect to the second pulley **112**. The lateral positioning joint

**108** can provide the benefit of easily rotating the pulling boom **114** side to side while maintaining the alignment of the pulling cable **212** between the first pulley **110** and the second pulley **112**. Examples shown further include a first hinge and a second hinge, for example first hinge **158** and second hinge **162**. By positioning the first pulley **110** and the second pulley **112** between the first hinge **158** and the second hinge **162**, any bending moments that might be created during a cable pulling operation are countered both above and below the first pulley **110** and the second pulley **112**. This configuration provides a robust joint that resists unwanted bending between the first pulley **110** and the first pulley **112**, yet still allows lateral movement of the lateral positioning joint **108**, all within a compact volume along the boom.

[0045] The vertical positioning joint **109** can allow the pulling boom **114** to be raised or lowered when attached to the power winch **214**. The vertical positioning joint **109** can provide the benefit of easily rotating the pulling boom **114** up or down, while maintaining alignment of the pulling cable **212** between the first pulley **110**, the second pulley **112**, the third pulley **130**, the fourth pulley **176**, the fifth pulley **178**, and the sixth pulley **180**.

[0046] FIG. **6** illustrates a method **300** for using the cable positioning assembly and pulling system, in accordance with at least one example of the present application. The steps or operations of the method **300** are illustrated in a particular order for convenience and clarity; many of the discussed operations can be performed in a different sequence or in parallel without materially impacting other operations. The method **300** as discussed includes operations that can be performed by multiple different actors, devices, and/or systems. It is understood that subsets of the operations discussed in the method **300** can be attributable to a single actor, device, or system could be considered a separate standalone process or method.

[0047] In one or more examples, a first step **302** can be positioning a pulling boom within a conduit box, the pulling boom having a first end and a second end, wherein the first end is coupled to a winch and the second end is positioned over a conduit within the conduit box. In one or more examples, a second step **304** can be running the pulling cable from the winch to a proximal end of the conduit. In one or more examples, a third step **306** can be running the pulling cable through the conduit to a distal end of the conduit. In one or more examples, a fourth step **308** can be coupling an electrical cable to the pulling cable at the distal end of the conduit. In one or more examples, a fifth step **310** can be operating the winch to bring the pulling cable and the attached electrical cable through the conduit into the conduit box.

[0048] In one or more examples, the first step **302** can include positioning the pulling boom further includes positioning a lateral positioning joint, the lateral positioning joint coupling the winch to the pulling boom. In one or more examples, the first step **302** can include positioning the pulling boom further includes positioning a vertical joint, the vertical joint coupling the lateral positioning joint to the pulling boom. In one or more examples, the first step **302** can include positioning adjustable supporting legs coupled to the pulling boom to support the pulling boom over the proximal end of the conduit.

#### NOTES AND EXAMPLES

[0049] The following, non-limiting examples, detail certain aspects of the present subject matter to solve the challenges and provide the benefits discussed herein, among others.

[0050] Example 1 is a cable positioning assembly, comprising: a winch mount having a first end and a second end; a first pulley coupled to the winch mount, the first pulley rotatable about a first lateral axis; a boom mount having a first end and a second end; a second pulley coupled to the boom mount, the second pulley rotatable about a second lateral axis; a first hinge pivotably coupling the first end of the winch mount to the first end of the boom mount; a second hinge pivotably coupling the second end of the of the winch mount to the second end of the boom mount; wherein the first and second hinges form a lateral positioning joint, the lateral positioning joint rotatable about a first vertical axis; and wherein the first and second pulleys are positioned between the first hinge and the second hinge.



[0051] In Example 2, the subject matter of Example 1 optionally includes wherein the winch mount further includes a fitting configured to engage with a winch and couple the cable positioning assembly to the winch.

[0052] In Example 3, the subject matter of any one or more of Examples 1-2 optionally include a vertical joint coupling the boom mount to a pulling boom, the pulling boom having a first end and a second end, wherein the vertical joint is rotatable about a third lateral axis.

[0053] In Example 4, the subject matter of Example 3 optionally includes wherein the pulling boom is curved.

[0054] In Example 5, the subject matter of any one or more of Examples 3-4 optionally include wherein the pulling boom includes adjustable supporting legs.

[0055] In Example 6, the subject matter of Example 5 optionally includes wherein the adjustable supporting legs are positioned between a first end and a second end of the pulling boom.

[0056] In Example 7, the subject matter of any one or more of Examples 3-6 optionally include a third pulley coupled to the second end of the pulling boom.

[0057] In Example 8, the subject matter of any one or more of Examples 3-7 optionally include a plurality of pulleys coupled to the pulling boom between the first end and the second end.

[0058] In Example 9, the subject matter of any one or more of Examples 1-8 optionally include degree range of rotational motion.

[0059] Example 10 is a cable pulling system, comprising: a cable positioning system including: a winch mount having a first end and a second end; a first pulley coupled to the winch mount, the first pulley rotatable about a first lateral axis; a boom mount having a first end and a second end; a second pulley coupled to the boom mount, the second pulley rotatable about a second lateral axis; a first hinge pivotably coupling the first end of the winch mount to the first end of the boom mount; a second hinge pivotably coupling the second end of the of the winch mount to the second end of the boom mount; wherein the first and second hinges form a lateral positioning joint, the lateral positioning joint rotatable about a first vertical axis; wherein the first and second pulleys are positioned between the first hinge and the second hinge; and a pulling boom having a first end to couple the cable positioning assembly to the pulling boom and a second end to deploy over a conduit; wherein the pulling boom is coupled to the boom mount with a vertical joint, the vertical joint rotatable about a third lateral axis.

[0060] In Example 11, the subject matter of Example 10 optionally includes wherein the winch mount further includes a fitting configured to engage with a winch and couple the cable pulling system to the winch.

[0061] In Example 12, the subject matter of any one or more of Examples 10-11 optionally include wherein the pulling boom is curved.

[0062] In Example 13, the subject matter of any one or more of Examples 10-12 optionally include wherein the pulling boom includes adjustable supporting legs.

[0063] In Example 14, the subject matter of any one or more of Examples 10-13 optionally include degree range of rotational motion.

[0064] In Example 15, the subject matter of any one or more of Examples 10-14 optionally include degrees.

[0065] Example 16 is a method for pulling electrical cable into a conduit box, the method comprising: positioning a pulling boom within a conduit box, the pulling boom having a first end and a second end, wherein the first end is coupled to a winch and the second end is positioned over a conduit within the conduit box; running the pulling cable from the winch to a proximal end of the conduit; running the pulling cable through the conduit to a distal end of the conduit; coupling an electrical cable to the pulling cable at the distal end of the conduit; operating the winch to bring the pulling cable and the attached electrical cable through the conduit into the conduit box.

[0066] In Example 17, the subject matter of Example 16 optionally includes wherein positioning the pulling boom further includes positioning a lateral positioning joint, the lateral positioning joint

coupling the winch to the pulling boom.

[0067] In Example 18, the subject matter of any one or more of Examples 16-17 optionally include wherein positioning the pulling boom further includes positioning a vertical joint, the vertical joint coupling the lateral positioning joint to the pulling boom.

[0068] In Example 19, the subject matter of any one or more of Examples 16-18 optionally include wherein positioning the pulling boom further includes positioning adjustable supporting legs coupled to the pulling boom to support the pulling boom over the proximal end of the conduit.

[0069] The above detailed description includes references to the accompanying drawings, which form a part of the detailed description. The drawings show, by way of illustration, specific embodiments in which the invention can be practiced. These embodiments are also referred to herein as “examples.” Such examples can include elements in addition to those shown or described. However, the present inventors also contemplate examples in which only those elements shown or described are provided. Moreover, the present inventors also contemplate examples using any combination or permutation of those elements shown or described (or one or more aspects thereof), either with respect to a particular example (or one or more aspects thereof), or with respect to other examples (or one or more aspects thereof) shown or described herein. In the event of inconsistent usages between this document and any documents so incorporated by reference, the usage in this document controls.

[0070] In this document, the terms “a” or “an” are used, as is common in patent documents, to include one or more than one, independent of any other instances or usages of “at least one” or “one or more.” In this document, the term “or” is used to refer to a nonexclusive or, such that “A or B” includes “A but not B,” “B but not A,” and “A and B,” unless otherwise indicated. In this document, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Also, in the following claims, the terms “including” and “comprising” are open-ended, that is, a system, device, article, composition, formulation, or process that includes elements in addition to those listed after such a term in a claim are still deemed to fall within the scope of that claim. Moreover, in the following claims, the terms “first,” “second,” and “third,” etc. are used merely as labels, and are not intended to impose numerical requirements on their objects.

[0071] The above description is intended to be illustrative, and not restrictive. For example, the above-described examples (or one or more aspects thereof) may be used in combination with each other. Other embodiments can be used, such as by one of ordinary skill in the art upon reviewing the above description. The Abstract is provided to comply with 37 C.F.R. § 1.72 (b), to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. Also, in the above Detailed Description, various features may be grouped together to streamline the disclosure. This should not be interpreted as intending that an unclaimed disclosed feature is essential to any claim. Rather, inventive subject matter may lie in less than all features of a particular disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description as examples or embodiments, with each claim standing on its own as a separate embodiment, and it is contemplated that such embodiments can be combined with each other in various combinations or permutations. The scope of the invention should be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

## Claims

1. A boom arm assembly, comprising: a winch mount; a boom; a lateral positioning joint coupled between the winch mount and the boom, including; a hinge assembly including a top hinge and a bottom hinge that both rotate about a common vertical pivot axis and define a vertical space

between the top hinge and the bottom hinge; a first pulley located between the top hinge and the bottom hinge and coupled to a boom side of the hinge assembly; a second pulley located between the top hinge and the bottom hinge and coupled to a winch side of the hinge assembly; wherein a tangent of the first pulley and a tangent of the second pulley are colinear with each other and colinear with the vertical pivot axis; and a vertical positioning joint coupled between the winch mount and the boom.

**2.** The boom arm assembly of claim 1, wherein the vertical positioning joint is located on the boom side of the hinge assembly.

**3.** The boom arm assembly of claim 2, wherein a rotation axis of the vertical positioning joint is concentric with a rotation axis of the first pulley.

**4.** The boom arm assembly of claim 1, further including a boom release to removably attach the boom to hinge assembly.

**5.** The boom arm assembly of claim 4, wherein the boom release removably connects to a rotation axis of the first pulley.

**6.** The boom arm assembly of claim 1, wherein the boom includes a downward curving boom.

**7.** The boom arm assembly of claim 6, wherein the boom includes a plurality of distal end boom pulleys.

**8.** The boom arm assembly of claim 7, wherein the plurality of distal end boom pulleys define a downward arc at a distal end of the downward curving boom.

**9.** The boom arm assembly of claim 1, further including one or more supporting legs coupled to the boom.

**10.** The boom arm assembly of claim 9, wherein the one or more supporting legs are height adjustable.

**11.** A winch system, comprising: a portable power winch, including; a set of wheels for transportation; a trailer hitch for connection to a tow vehicle; a boom arm assembly, coupled to the portable power winch, including; a winch mount; a boom; a lateral positioning joint coupled between the winch mount and the boom, including; a hinge assembly including a top hinge and a bottom hinge that both rotate about a common vertical pivot axis and define a vertical space between the top hinge and the bottom hinge; a first pulley located between the top hinge and the bottom hinge and coupled to a boom side of the hinge assembly; a second pulley located between the top hinge and the bottom hinge and coupled to a winch side of the hinge assembly; wherein a tangent of the first pulley and a tangent of the second pulley are colinear with each other and colinear with the vertical pivot axis; and a vertical positioning joint coupled between the winch mount and the boom.

**12.** The winch system of claim 11, wherein the vertical positioning joint is located on the boom side of the hinge assembly.

**13.** The winch system of claim 12, wherein a rotation axis of the vertical positioning joint is concentric with a rotation axis of the first pulley.

**14.** The winch system of claim 13, further including a boom release to removably attach the boom to hinge assembly.

**15.** The winch system of claim 14, wherein the boom release removably connects to the rotation axis of the first pulley.

**16.** The winch system of claim 11, further including one or more supporting legs coupled to the boom.

**17.** The winch system of claim 16, wherein the one or more supporting legs are height adjustable.

---