

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386032
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Brown; Adam et al.

Methods and systems for using interference to detect sensor impairment

Abstract

Example embodiments relate to methods and systems for using interference to detect sensor impairment. Radar or another type of sensor on a vehicle may receive radio-frequency (RF) signals propagating in the environment. These RF signals may originate from an external source and a computing device can be used to determine a distance and an angle to the source in order to identify a power level threshold that represents an expected power associated with the RF signals. The computing device may then perform a comparison between a power level of the RF signals and a power level threshold. Based on the comparison, the computing device may decrease a confidence assigned to the radar coupled to the vehicle and control the vehicle based on the decreased confidence assigned to the radar.

Inventors:	Brown; Adam (Mountain View, CA), Clayton; Gary (Torrance, CA)
Applicant:	Waymo LLC (Mountain View, CA)
Family ID:	1000008748242
Assignee:	Waymo LLC (Mountain View, CA)
Appl. No.:	17/823327
Filed:	August 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240069157 A1	Feb. 29, 2024

Publication Classification

Int. Cl.: G01S7/40 (20060101); G01S13/931 (20200101); H04W4/02 (20180101); B60W60/00 (20200101)

U.S. Cl.:

CPC **G01S7/40** (20130101); **G01S7/4039** (20210501); **G01S13/931** (20130101); **H04W4/023** (20130101); B60W60/001 (20200201); B60W2420/408 (20240101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7271880	12/2006	Samukawa	N/A	N/A
7451035	12/2007	Nozawa	N/A	N/A
7486222	12/2008	Matsuoka	N/A	N/A
9958534	12/2017	Chabaud	N/A	N/A
10884120	12/2020	Yu	N/A	N/A
2021/0063546	12/2020	Slobodyanyuk	N/A	N/A
2021/0190899	12/2020	Bolduc	N/A	N/A
2022/0021868	12/2021	Hunt	N/A	N/A
2022/0120845	12/2021	Gulati	N/A	H04W 4/40
2022/0207887	12/2021	Miyazawa	N/A	N/A
2024/0149923	12/2023	Fang	N/A	G06V 20/56

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102016221440	12/2017	DE	N/A
3825727	12/2020	EP	N/A
3825727	12/2020	EP	N/A
2009085920	12/2008	JP	N/A
4321487	12/2008	JP	N/A
2009250640	12/2008	JP	N/A
2010091386	12/2009	JP	N/A
1786039	12/2016	KR	N/A
2022019162	12/2021	WO	N/A
2022055873	12/2021	WO	N/A
2022132608	12/2021	WO	N/A

OTHER PUBLICATIONS

Ryde et al., “Performance of Laser and Radar Ranging Devices in Adverse Environmental Conditions” (2009). cited by applicant

Primary Examiner: Liang; Hongye

Attorney, Agent or Firm: McDonnell Boehnen Hulbert & Berghoff LLP

Background/Summary

BACKGROUND

(1) Advancements in computing, sensors, and other technologies have enabled some vehicles to navigate safely between locations autonomously, i.e., without requiring input from a human driver. By processing sensor measurements of the surrounding environment in real-time, an autonomous vehicle can transport passengers or objects (e.g., cargo) between locations while avoiding obstacles, obeying traffic requirements, anticipating movements of nearby agents, and performing other actions that are typically conducted by a driver. Shifting both decision-making and control of the vehicle over to vehicle systems can allow passengers to devote their attention to tasks other than driving.

SUMMARY

(2) Example embodiments relate to techniques for using interference to detect impairment of radars and other types of vehicle sensors. Sensor data from a vehicle sensor can be impacted by interference that arises when other nearby emitters are also transmitting signals in the direction of the vehicle. Disclosed techniques involve using one or multiple expected properties within detected interference that are derived based on the spatial relationship relative to the external emitter in order to determine if the receiving sensor is potentially experiencing fouling or some other form of impairment. Vehicle systems may further determine if the impairment is local to the vehicle sensor or caused by the emitting sensor based on additional sensor data and/or wireless communication with the external emitter.

(3) In one aspect, an example method is provided. The method involves receiving, at a computing device and from a radar coupled to a vehicle, radio-frequency (RF) signals propagating in an environment of the vehicle, determining a distance and an angle to a source of the RF signals, and performing a comparison between a power level of the RF signals and a power level threshold. The power level threshold depends on the distance and the angle to the source of the RF signals. The method further involves decreasing a confidence assigned to the radar coupled to the vehicle based on the comparison and controlling the vehicle based on the decreased confidence assigned to the radar.

(4) In another aspect, an example system is provided. The system includes a vehicle radar system and a computing device coupled to a vehicle. The computing device is configured to receive, from a radar, radio-frequency (RF) signals propagating in an environment of the vehicle and determine a distance and an angle to a source of the RF signals. The computing device is further configured to perform a comparison between a power level of the RF signals and a power level threshold. The power level threshold depends on the distance and the angle to the source of the RF signals. The computing device is further configured to decrease a confidence assigned to the radar coupled to the vehicle based on the comparison and control the vehicle based on the decreased confidence assigned to the radar.

(5) In yet another example, an example non-transitory computer-readable medium is provided. The non-transitory computer-readable medium is configured to store instructions, that when executed by a computing system comprising one or more processors, causes the computing system to perform operations. The operations involve receiving, from a radar coupled to a vehicle, radio-frequency (RF) signals propagating in an environment of the vehicle, determining a distance and an angle to a source of the RF signals, and performing a comparison between a power level of the RF signals and a power level threshold. The power level threshold depends on the distance and the angle to the source of the RF signals. The operations further involve, based on the comparison, decreasing a confidence assigned to the radar coupled to the vehicle and controlling the vehicle based on the decreased confidence assigned to the radar.

(6) The foregoing summary is illustrative only and is not intended to be in any way limiting. In addition to the illustrative aspects, embodiments, and features described above, further aspects,

embodiments, and features will become apparent by reference to the figures and the following detailed description.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1 is a functional block diagram illustrating a vehicle, according to one or more example embodiments.
- (2) FIG. 2A illustrates a side view of a vehicle, according to one or more example embodiments.
- (3) FIG. 2B illustrates a top view of a vehicle, according to one or more example embodiments.
- (4) FIG. 2C illustrates a front view of a vehicle, according to one or more example embodiments.
- (5) FIG. 2D illustrates a back view of a vehicle, according to one or more example embodiments.
- (6) FIG. 2E illustrates an additional view of a vehicle, according to one or more example embodiments.
- (7) FIG. 3 is a simplified block diagram for a computing system, according to one or more example embodiments.
- (8) FIG. 4 depicts a system that enables wireless communication between a vehicle and computing devices, according to one or more example embodiments.
- (9) FIG. 5 depicts a scenario for using interference to detect sensor impairment, according to one or more example embodiments.
- (10) FIG. 6 depicts another scenario showing a vehicle using interference caused by sensors on another vehicle in order to analyze potential onboard sensor impairment, according to one or more example embodiments.
- (11) FIG. 7 is a flow chart of a method for using interference to detect sensor impairment, according to example embodiments.
- (12) FIG. 8 is a schematic diagram of a computer program, according to example implementations.

DETAILED DESCRIPTION

- (13) In the following detailed description, reference is made to the accompanying figures, which form a part hereof. In the figures, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, figures, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the scope of the subject matter presented herein. It will be readily understood that the aspects of the present disclosure, as generally described herein, and illustrated in the figures, can be arranged, substituted, combined, separated, and designed in a wide variety of different configurations, all of which are explicitly contemplated herein.
- (14) Sensor measurements from vehicle sensors can allow vehicle systems to perform various operations for autonomous or semi-autonomous navigation. For instance, vehicle systems can use sensor data to detect and avoid obstacles, to measure road conditions and locate road boundaries, to locate and anticipate movements of nearby agents (e.g., other vehicles, pedestrians), to determine changes in traffic signals and signs, and to estimate weather conditions. In general, sensor data enables vehicle systems to gain an understanding of the surrounding environment in order to determine and perform a control strategy for autonomous navigation to a destination.
- (15) The types, quantity, and arrangement of vehicle sensors used by an autonomous or semi-autonomous vehicle can vary within example embodiments. Some vehicles include a vehicle radar system, which is configured to detect nearby objects by transmitting electromagnetic signals (radar signals) and analyzing the backscattered signals that reflect off from the objects and other surfaces in the environment. The vehicle radar system can detect objects by transmitting short pulses and/or coded waveforms, such as a pulsed Doppler radar that involves a coherent burst of short pulses of a certain carrier frequency. In some applications, electromagnetic energy is concentrated to a

particular spatial sector in the form of a beam via a parabolic reflector or an array of antenna elements associated with a radar unit coupled to the vehicle. As such, received reflections can be used by a radar processing system (e.g., a computing device) to generate two dimensional (2D) and/or three dimensional (3D) measurements that represent measurements of the environment, such as the positions, orientations, and movements of nearby objects and other surfaces occupying the environment near the radar system. In some cases, radar is used to generate range data, Doppler data, azimuth data, and/or elevation data for objects and other surfaces in the surrounding environment.

(16) When multiple radars or other types of electromagnetic emitting sensors (e.g., lidar) are operating in the same general location, interference can arise between the different sensors. In particular, interference may be detected by a processing system within the sensor data received from a sensor when signals emitted by an external emitter are also received by the sensor. These external signals can be received in addition to the desired reflections of signals originally transmitted by the vehicle sensor and can produce undesired artifacts that can impact processing and subsequent use of the sensor data.

(17) By way of an example, interference can occur when multiple radars positioned in relatively close proximity are operating on the same frequency or frequencies (or similar frequencies). This can cause negative effects that impact radar reflection processing for both of the radar systems and can even temporarily limit the use of the radar data by each radar system until the interference decreases. In practice, a radar system may fail to distinguish between reflections of its own transmitted signals and other signals produced by other emitters in the surrounding environment when the signals share similarities, such as operating at similar frequencies and waveforms. The resulting interference is noise that can disrupt and temporarily decrease the processor's ability to accurately measure aspects of the surrounding environment based on the radar data. Lidar and other types of vehicle sensors can experience similar interference when operating nearby sensors that emit signals with similar properties.

(18) With the number of vehicles incorporating sensors for navigation continuing to increase overall, vehicle sensor systems are more likely to encounter interference during navigation within various environments, especially within city limits and other RF-dense areas that typically have more vehicles navigating in multiple directions within close proximity.

(19) Example embodiments presented herein advantageously use signal interference to detect sensor impairments for sensors operating onboard a vehicle. In practice, the signal interference caused by signals from external emitters can be evaluated by vehicle systems to detect when the receiving radar or another type of sensor is potentially impaired by fouling or another issue. By performing disclosed techniques, real-time knowledge of sensor performance impairments can be generated and used to estimate relative and/or absolute sensor performance degradation. Vehicle systems can then update sensor-specific models and/or other downstream models (e.g., perception or behavior) based on the estimations, thereby improving vehicle performance during navigation.

(20) Disclosed techniques can involve evaluating interference based on the spatial relationship between a receiving sensor and the external emitter of the source signals that caused the interference. The spatial relationship and an interference model can indicate when the receiving sensor is potentially experiencing impairment. In some embodiments, vehicle systems may use additional sensor data and/or wireless communication with one or multiple external emitters to further analyze the potential impairments detected for onboard vehicle sensors. For instance, additional sensor data from a potentially impaired sensor, sensor data from other sensors, and/or wireless communication with the source of interfering signals can enable vehicle systems to increase or decrease confidence assigned to the onboard vehicle sensor that is potentially impaired. In some cases, vehicle systems may determine that the sensor initially appeared impaired due to issues associated with the external emitter and/or atmospheric loss and can then continue to use sensor data from the sensor (e.g., increase a confidence assigned to the sensor).

(21) In some embodiments, disclosed techniques are used to estimate the level of impairment experienced by a sensor, which can indicate the subsequent confidence that can be assigned to sensor data from the sensor. In some cases, vehicle systems may determine that a sensor requires some form of maintenance, which may trigger an alert notification and the avoidance of subsequent use of the sensor until the maintenance is performed. In some instances, a vehicle may even temporarily refrain from navigation until a particular sensor impairment is resolved. In other examples, vehicle systems may initiate one or multiple cleaning techniques to try to resolve the impairment experienced by a sensor. As such, vehicle systems can iteratively perform disclosed techniques to test individual sensors positioned on the vehicle.

(22) By way of an example, a vehicle computing device may receive RF signals propagating in a vehicle's environment from a radar located on the vehicle and then determine the RF signals have properties (e.g., frequency and waveform) that indicate the RF signals originated from another nearby emitter, such as from the radar system of a nearby vehicle. In practice, the sensor data provided by the radar may appear to have interference caused by the external RF signals. As such, based on the spatial relationship between the receiving radar and the source of these RF signals, the computing device may determine expected properties for the interference that includes the RF signals, which then can be compared to one or multiple properties measured from the RF signals. For instance, the computing device may use an interference model that articulates expected properties for the interference based on the location and angle of the emitter relative to the receiving sensor. As such, when the comparison yields an identifiable difference between measured properties and expected properties, this may signal that the sensor located onboard the vehicle that received the RF signals is potentially experiencing fouling or another issue that impaired performance (i.e., the reception of the external signals). For example, when the power level of the interference caused by the RF signals is below a threshold power level determined based on the distance and the angle of the emitter, the decreased power may be due to fouling on the radome of the radar, which may require cleaning or replacement to increase performance of the radar.

(23) Because atmospheric loss and/or operations by the external emitter may have contributed to the difference detected during the comparison, the computing device may use further sensor data from the radar and/or other sensors to further analyze the potential impairment in some cases. Subsequent performance by the radar and/or sensor data from other sensors can enable the computing device to further evaluate if the radar is impaired. In some instances, the radar may produce quality radar data when the interference diminishes, which may indicate that the initially detected impairment is not attributable to the performance of the radar or the impairment was temporary. In some examples, the computing device may also communicate with the external emitter to determine if the apparent impairment temporarily associated with the radar may have been caused by the external emitter and/or atmospheric loss. The external emitter may provide information that indicates the external emitter is experiencing fouling or some other issue that resulted in the difference identified during the comparison. In addition, vehicle systems can also test the potentially impaired sensor based on subsequent interference that occurs with another external emitter to validate the performance of the sensor. When the sensor appears impaired again, this may signal that the sensor is actually impaired and requires cleaning and/or some form of maintenance or calibration.

(24) Disclosed techniques can involve anticipating interference properties based on the spatial relationship between the sensor that received the signals emitted by an external source and the external source. In particular, the spatial relationship allows a computing device to evaluate the interference and may involve using the received external signals, other sensor data, and/or wireless communication with the external emitter to estimate the distance and the angle to the emitter. The computing device may then use the distance and the angle to determine properties expected for the interference, which may involve using an interference model that represents expected properties for different spatial relationships between an onboard receiving sensor and an external emitter. For

instance, the computing device may determine a power level threshold or a power range that should be measured within the received RF interference based on the distance and angle to the source. The interference model can specify the power level threshold or power range. As such, the expected power level can be higher or lower pending on the angle and the distance between the emitter and the receiving radar. In practice, the expected power level can be lower when the distance between the emitter and the sensor is farther. The computing device can also analyze other properties of the RF interference by comparing them to expected values for the properties.

(25) Evaluation of the properties of detected interference can indicate if the receiving radar is potentially experiencing some form of impairment, such as fouling on the radome. In practice, when the measured power of the received signals is lower than the expected power level, this may indicate that fouling is impairing the radar that received the RF signals. Fouling can occur when dirt, precipitation, or other physical material covers a sensor's covering (e.g., a radar's radome) and partially impacts the ability for the sensor to receive signals. In some cases, physical damage can also hinder the sensor's ability to receive signals. The lower measured power relative to the expected power could also indicate that the emitter of the RF interference is operating at an unexpected power transmission level and/or is experiencing some form of sensor impairment. In some cases, atmospheric loss can also contribute to the detected difference between expected power level (e.g., a power threshold level) and the measured power. As such, additional sensor data and/or wireless communication with the external emitter may be used to further analyze the condition of the receiving sensor.

(26) In some cases, when the measured power of received interference is lower than the expected power, this can indicate that the receiving sensor, the emitting sensor, and/or both sensors are experiencing some impairment. Atmospheric losses can also influence the comparison in some situations. As such, vehicle systems can perform additional operations to determine if the receiving sensor positioned locally on the vehicle is the cause of the lower measured power. In some embodiments, vehicle systems may communicate with the source of the interference signals. For instance, vehicle systems may communicate with the nearby vehicle to determine information that can be used to determine if the radar that received the RF interference signals is experiencing impairment due to fouling. The vehicles may both operate within a fleet and can share encrypted data within the fleet when performing disclosed techniques.

(27) Wireless communication between vehicles can help each vehicle determine if any sensors are experiencing fouling that may hinder performance. For instance, a pair of vehicles may communicate location information to enable each vehicle to discern if radars have fouling present that may impact performance. As an example, a computing device onboard a vehicle may identify if the power radiated by another fleet vehicle is within its expected range based on the distance and angle between the receiving sensor and the sensor that emitted the RF signals. When low power is detected, it can indicate fouling is present on one or both of the radars. Additional sensor data can also be used to determine if the vehicle's sensor is impaired. Through additional measurements obtained via the sensor and/or other sensors, the severity of fouling on each individual sensor can be determined, along with sensitivity impacts. The vehicle may then make adjustments based on the severity of the fouling.

(28) In some examples, vehicle systems may use independent calibration devices to perform disclosed techniques. For instance, a vehicle can position itself relative to calibration device. The calibration device may emit signals toward the sensors positioned on the vehicle. Vehicle systems can use the fixed location of the calibration device and transmission parameters provided by the calibration device to detect if any of the receiving sensors located onboard the vehicle are performing less than optimal.

(29) In some embodiments, a vehicle radar system may use multiple receive apertures (antennas) to receive electromagnetic waves radiating in the vehicle's environment, such as using a linear array of antennas on one or more radar units coupled to the vehicle to receive radiating electromagnetic

waves in the area that originated from one or more external emitters. By using multiple receive apertures, a processing unit may analyze the received electromagnetic waves to determine a line of bearing to the emitter. For example, the processing unit may use a Frequency Difference of Arrival (FDOA) process and/or a Time Difference of Arrival (TDOA) process to determine a location of the external emitter (e.g., another vehicle) that transmitted the electromagnetic energy relative to the vehicle's position, which can then be factored as part of the navigation strategy.

(30) The following detailed description may be used with one or more radar units having one or multiple antenna arrays. The one or multiple antenna arrays may take the form of a single-input single-output (SISO), single-input, multiple-output (SIMO), multiple-input single-output (MISO), multiple-input multiple-output (MIMO), and/or synthetic aperture radar (SAR) radar antenna architecture. In some embodiments, example radar unit architecture may include a plurality of “dual open-ended waveguide” (DOEWG) antennas. The term “DOEWG” may refer to a short section of a horizontal waveguide channel plus a vertical channel that splits into two parts. Each of the two parts of the vertical channel may include an output port configured to radiate at least a portion of electromagnetic waves that enters the radar unit. Additionally, in some instances, multiple DOEWG antennas may be arranged into one or more antenna arrays.

(31) Some example radar systems may be configured to operate at an electromagnetic wave frequency in the W-Band (e.g., 77 Gigahertz (GHz)). The W-Band may correspond to electromagnetic waves on the order of millimeters (e.g., 1 mm or 4 mm). Such antennas may be compact (typically with rectangular form factors), efficient (i.e., with little of the 77 GHz energy lost to heat in the antenna or reflected back into the transmitter electronics), low cost and easy to manufacture (i.e., radar systems with these antennas can be made in high volume).

(32) An antenna array may involve a set of multiple connected antennas that can work together as a single antenna to transmit or receive signals. By combining multiple radiating elements (i.e., antennas), an antenna array may enhance the performance of the radar unit used in some embodiments. In particular, a higher gain and narrower beam may be achieved when a radar unit is equipped with one or more antenna arrays. Antennas on a radar unit may be arranged in one or more linear antenna arrays (i.e., antennas within an array are aligned in a straight line, arranged in planar arrays (i.e., antennas arranged in multiple, parallel lines on a single plane), and/or multiple planes resulting in a three dimensional array. A radar unit may also include multiple types of arrays (e.g., a linear array on one portion and a planar array on another portion).

(33) In some examples, a radar unit may use an antenna arranged into antenna channels. Each channel may have its own amplifier and/or analogue-to-digital converter (ADC) and can be operated independently from the other antenna channels. The antennas in each channel may also be referred to as radiating apertures and can be aligned in a specific arrangement, such as a linear array. For instance, a radar unit may include 20 or more antenna channels with each channel consisting of four to 10 antennas arranged in a linear array. The radiating apertures in the channel can then be power combined passively and connected to either an amplifier or ADC.

(34) Referring now to the figures, FIG. 1 is a functional block diagram illustrating vehicle **100**, which represents a vehicle capable of operating fully or partially in an autonomous mode. More specifically, vehicle **100** may operate in an autonomous mode without human interaction through receiving control instructions from a computing system (e.g., a vehicle control system). As part of operating in the autonomous mode, vehicle **100** may use sensors (e.g., sensor system **104**) to detect and possibly identify objects of the surrounding environment to enable safe navigation. In some example embodiments, vehicle **100** may also include subsystems that enable a driver (or a remote operator) to control operations of vehicle **100**.

(35) As shown in FIG. 1, vehicle **100** includes various subsystems, such as propulsion system **102**, sensor system **104**, control system **106**, one or more peripherals **108**, power supply **110**, computer system **112**, data storage **114**, and user interface **116**. The subsystems and components of vehicle **100** may be interconnected in various ways (e.g., wired or secure wireless connections). In other

examples, vehicle **100** may include more or fewer subsystems. In addition, the functions of vehicle **100** described herein can be divided into additional functional or physical components, or combined into fewer functional or physical components within implementations.

(36) Propulsion system **102** may include one or more components operable to provide powered motion for vehicle **100** and can include an engine/motor **118**, an energy source **119**, a transmission **120**, and wheels/tires **121**, among other possible components. For example, engine/motor **118** may be configured to convert energy source **119** into mechanical energy and can correspond to one or a combination of an internal combustion engine, one or more electric motors, steam engine, or Stirling engine, among other possible options. For instance, in some implementations, propulsion system **102** may include multiple types of engines and/or motors, such as a gasoline engine and an electric motor.

(37) Energy source **119** represents a source of energy that may, in full or in part, power one or more systems of vehicle **100** (e.g., engine/motor **118**). For instance, energy source **119** can correspond to gasoline, diesel, other petroleum-based fuels, propane, other compressed gas-based fuels, ethanol, solar panels, batteries, and/or other sources of electrical power. In some implementations, energy source **119** may include a combination of fuel tanks, batteries, capacitors, and/or flywheel.

(38) Transmission **120** may transmit mechanical power from the engine/motor **118** to wheels/tires **121** and/or other possible systems of vehicle **100**. As such, transmission **120** may include a gearbox, a clutch, a differential, and a drive shaft, among other possible components. A drive shaft may include axles that connect to one or more wheels/tires **121**.

(39) Wheels/tires **121** of vehicle **100** may have various configurations within example implementations. For instance, vehicle **100** may exist in a unicycle, bicycle/motorcycle, tricycle, or car/truck four-wheel format, among other possible configurations. As such, wheels/tires **121** may connect to vehicle **100** in various ways and can exist in different materials, such as metal and rubber.

(40) Sensor system **104** can include various types of sensors, such as Global Positioning System (GPS) **122**, inertial measurement unit (IMU) **124**, one or more radar units **126**, laser rangefinder/LIDAR unit **128**, camera **130**, steering sensor **123**, and throttle/brake sensor **125**, among other possible sensors. In some implementations, sensor system **104** may also include sensors configured to monitor internal systems of the vehicle **100** (e.g., O.sub.2 monitors, fuel gauge, engine oil temperature, condition of brakes).

(41) GPS **122** may include a transceiver operable to provide information regarding the position of vehicle **100** with respect to the Earth. IMU **124** may have a configuration that uses one or more accelerometers and/or gyroscopes and may sense position and orientation changes of vehicle **100** based on inertial acceleration. For example, IMU **124** may detect a pitch and yaw of the vehicle **100** while vehicle **100** is stationary or in motion.

(42) Radar unit **126** may represent one or more systems configured to use radio signals to sense objects (e.g., radar signals), including the speed and heading of the objects, within the local environment of vehicle **100**. As such, radar unit **126** may include one or more radar units equipped with one or more antennas configured to transmit and receive radar signals as discussed above. In some implementations, radar unit **126** may correspond to a mountable radar system configured to obtain measurements of the surrounding environment of vehicle **100**. For example, radar unit **126** can include one or more radar units configured to couple to the underbody of a vehicle.

(43) Laser rangefinder/LIDAR **128** may include one or more laser sources, a laser scanner, and one or more detectors, among other system components, and may operate in a coherent mode (e.g., using heterodyne detection) or in an incoherent detection mode. Camera **130** may include one or more devices (e.g., still camera or video camera) configured to capture images of the environment of vehicle **100**.

(44) Steering sensor **123** may sense a steering angle of vehicle **100**, which may involve measuring an angle of the steering wheel or measuring an electrical signal representative of the angle of the

steering wheel. In some implementations, steering sensor **123** may measure an angle of the wheels of the vehicle **100**, such as detecting an angle of the wheels with respect to a forward axis of the vehicle **100**. Steering sensor **123** may also be configured to measure a combination (or a subset) of the angle of the steering wheel, electrical signal representing the angle of the steering wheel, and the angle of the wheels of vehicle **100**.

(45) Throttle/brake sensor **125** may detect the position of either the throttle position or brake position of vehicle **100**. For instance, throttle/brake sensor **125** may measure the angle of both the gas pedal (throttle) and brake pedal or may measure an electrical signal that could represent, for instance, the angle of the gas pedal (throttle) and/or an angle of a brake pedal. Throttle/brake sensor **125** may also measure an angle of a throttle body of vehicle **100**, which may include part of the physical mechanism that provides modulation of energy source **119** to engine/motor **118** (e.g., a butterfly valve or carburetor). Additionally, throttle/brake sensor **125** may measure a pressure of one or more brake pads on a rotor of vehicle **100** or a combination (or a subset) of the angle of the gas pedal (throttle) and brake pedal, electrical signal representing the angle of the gas pedal (throttle) and brake pedal, the angle of the throttle body, and the pressure that at least one brake pad is applying to a rotor of vehicle **100**. In other embodiments, throttle/brake sensor **125** may be configured to measure a pressure applied to a pedal of the vehicle, such as a throttle or brake pedal.

(46) Control system **106** may include components configured to assist in navigating vehicle **100**, such as steering unit **132**, throttle **134**, brake unit **136**, sensor fusion algorithm **138**, computer vision system **140**, navigation/pathing system **142**, and obstacle avoidance system **144**. More specifically, steering unit **132** may be operable to adjust the heading of vehicle **100**, and throttle **134** may control the operating speed of engine/motor **118** to control the acceleration of vehicle **100**. Brake unit **136** may decelerate vehicle **100**, which may involve using friction to decelerate wheels/tires **121**. In some implementations, brake unit **136** may convert kinetic energy of wheels/tires **121** to electric current for subsequent use by a system or systems of vehicle **100**.

(47) Sensor fusion algorithm **138** may include a Kalman filter, Bayesian network, or other algorithms that can process data from sensor system **104**. In some implementations, sensor fusion algorithm **138** may provide assessments based on incoming sensor data, such as evaluations of individual objects and/or features, evaluations of a particular situation, and/or evaluations of potential impacts within a given situation.

(48) Computer vision system **140** may include hardware and software operable to process and analyze images in an effort to determine objects, environmental objects (e.g., stop lights, road way boundaries, etc.), and obstacles. As such, computer vision system **140** may use object recognition, Structure from Motion (SFM), video tracking, and other algorithms used in computer vision, for instance, to recognize objects, map an environment, track objects, estimate the speed of objects, etc.

(49) Navigation/pathing system **142** may determine a driving path for vehicle **100**, which may involve dynamically adjusting navigation during operation. As such, navigation/pathing system **142** may use data from sensor fusion algorithm **138**, GPS **122**, and maps, among other sources to navigate vehicle **100**. Obstacle avoidance system **144** may evaluate potential obstacles based on sensor data and cause systems of vehicle **100** to avoid or otherwise negotiate the potential obstacles.

(50) As shown in FIG. 1, vehicle **100** may also include peripherals **108**, such as wireless communication system **146**, touchscreen **148**, microphone **150**, and/or speaker **152**. Peripherals **108** may provide controls or other elements for a user to interact with user interface **116**. For example, touchscreen **148** may provide information to users of vehicle **100**. User interface **116** may also accept input from the user via touchscreen **148**. Peripherals **108** may also enable vehicle **100** to communicate with devices, such as other vehicle devices.

(51) Wireless communication system **146** may securely and wirelessly communicate with one or more devices directly or via a communication network. For example, wireless communication

system **146** could use 3G cellular communication, such as CDMA, EVDO, GSM/GPRS, or 4G cellular communication, such as WiMAX or LTE. Alternatively, wireless communication system **146** may communicate with a wireless local area network (WLAN) using WiFi or other possible connections. Wireless communication system **146** may also communicate directly with a device using an infrared link, Bluetooth, or ZigBee, for example. Other wireless protocols, such as various vehicular communication systems, are possible within the context of the disclosure. For example, wireless communication system **146** may include one or more dedicated short-range communications (DSRC) devices that could include public and/or private data communications between vehicles and/or roadside stations.

(52) Vehicle **100** may include power supply **110** for powering components. Power supply **110** may include a rechargeable lithium-ion or lead-acid battery in some implementations. For instance, power supply **110** may include one or more batteries configured to provide electrical power. Vehicle **100** may also use other types of power supplies. In an example implementation, power supply **110** and energy source **119** may be integrated into a single energy source.

(53) Vehicle **100** may also include computer system **112** to perform operations, such as operations described therein. As such, computer system **112** may include at least one processor **113** (which could include at least one microprocessor) operable to execute instructions **115** stored in a non-transitory computer readable medium, such as data storage **114**. In some implementations, computer system **112** may represent a plurality of computing devices that may serve to control individual components or subsystems of vehicle **100** in a distributed fashion.

(54) In some implementations, data storage **114** may contain instructions **115** (e.g., program logic) executable by processor **113** to execute various functions of vehicle **100**, including those described above in connection with FIG. 1. Data storage **114** may contain additional instructions as well, including instructions to transmit data to, receive data from, interact with, and/or control one or more of propulsion system **102**, sensor system **104**, control system **106**, and peripherals **108**.

(55) In addition to instructions **115**, data storage **114** may store data such as roadway maps, path information, among other information. Such information may be used by vehicle **100** and computer system **112** during the operation of vehicle **100** in the autonomous, semi-autonomous, and/or manual modes.

(56) Vehicle **100** may include user interface **116** for providing information to or receiving input from a user of vehicle **100**. User interface **116** may control or enable control of content and/or the layout of interactive images that could be displayed on touchscreen **148**. Further, user interface **116** could include one or more input/output devices within the set of peripherals **108**, such as wireless communication system **146**, touchscreen **148**, microphone **150**, and speaker **152**.

(57) Computer system **112** may control the function of vehicle **100** based on inputs received from various subsystems (e.g., propulsion system **102**, sensor system **104**, and control system **106**), as well as from user interface **116**. For example, computer system **112** may utilize input from sensor system **104** in order to estimate the output produced by propulsion system **102** and control system **106**. Depending upon the embodiment, computer system **112** could be operable to monitor many aspects of vehicle **100** and its subsystems. In some embodiments, computer system **112** may disable some or all functions of the vehicle **100** based on signals received from sensor system **104**.

(58) The components of vehicle **100** could be configured to work in an interconnected fashion with other components within or outside their respective systems. For instance, in an example embodiment, camera **130** could capture a plurality of images that could represent information about a state of an environment of vehicle **100** operating in an autonomous mode. The state of the environment could include parameters of the road on which the vehicle is operating. For example, computer vision system **140** may be able to recognize the slope (grade) or other features based on the plurality of images of a roadway. Additionally, the combination of GPS **122** and the features recognized by computer vision system **140** may be used with map data stored in data storage **114** to determine specific road parameters. Further, radar unit **126** may also provide information about the

surroundings of the vehicle.

(59) In other words, a combination of various sensors (which could be termed input-indication and output-indication sensors) and computer system **112** could interact to provide an indication of an input provided to control a vehicle or an indication of the surroundings of a vehicle.

(60) In some embodiments, computer system **112** may make a determination about various objects based on data that is provided by systems other than the radio system. For example, vehicle **100** may have lasers or other optical sensors configured to sense objects in a field of view of the vehicle. Computer system **112** may use the outputs from the various sensors to determine information about objects in a field of view of the vehicle, and may determine distance and direction information to the various objects. Computer system **112** may also determine whether objects are desirable or undesirable based on the outputs from the various sensors. In addition, vehicle **100** may also include telematics control unit (TCU) **160**. TCU **160** may enable vehicle connectivity and internal passenger device connectivity through one or more wireless technologies.

(61) Although FIG. **1** shows various components of vehicle **100**, i.e., wireless communication system **146**, computer system **112**, data storage **114**, and user interface **116**, as being integrated into the vehicle **100**, one or more of these components could be mounted or associated separately from vehicle **100**. For example, data storage **114** could, in part or in full, exist separate from vehicle **100**. Thus, vehicle **100** could be provided in the form of device elements that may be located separately or together. The device elements that make up vehicle **100** could be communicatively coupled together in a wired and/or wireless fashion.

(62) FIGS. **2A**, **2B**, **2C**, **2D**, and **2E** illustrate different views of a physical configuration of vehicle **100**. The various views are included to depict example sensor positions **202**, **204**, **206**, **208**, **210** on vehicle **100**. In other examples, sensors can have different positions on vehicle **100**. Although vehicle **100** is depicted in FIGS. **2A-2E** as a van, vehicle **100** can have other configurations within examples, such as a truck, a car, a semi-trailer truck, a motorcycle, a bus, a shuttle, a golf cart, an off-road vehicle, robotic device, or a farm vehicle, among other possible examples.

(63) As discussed above, vehicle **100** may include sensors coupled at various exterior locations, such as sensor positions **202-210**. Vehicle sensors include one or more types of sensors with each sensor configured to capture information from the surrounding environment or perform other operations (e.g., communication links, obtain overall positioning information). For example, sensor positions **202-210** may serve as locations for any combination of one or more cameras, radar units, LIDAR units, range finders, radio devices (e.g., Bluetooth and/or 802.11), and acoustic sensors, among other possible types of sensors.

(64) When coupled at the example sensor positions **202-210** shown in FIGS. **2A-2E**, various mechanical fasteners may be used, including permanent or non-permanent fasteners. For example, bolts, screws, clips, latches, rivets, anchors, and other types of fasteners may be used. In some examples, sensors may be coupled to the vehicle using adhesives. In further examples, sensors may be designed and built as part of the vehicle components (e.g., parts of the vehicle mirrors).

(65) In some implementations, one or more sensors may be positioned at sensor positions **202-210** using movable mounts operable to adjust the orientation of one or more sensors. A movable mount may include a rotating platform that can rotate sensors so as to obtain information from multiple directions around vehicle **100**. For instance, a sensor located at sensor position **202** may use a movable mount that enables rotation and scanning within a particular range of angles and/or azimuths. As such, vehicle **100** may include mechanical structures that enable one or more sensors to be mounted on top the roof of vehicle **100**. Additionally, other mounting locations are possible within examples. In some situations, sensors coupled at these locations can provide data that can be used by a remote operator to provide assistance to vehicle **100**.

(66) FIG. **3** is a simplified block diagram exemplifying computing device **300**, illustrating some of the components that could be included in a computing device arranged to operate in accordance with the embodiments herein. Computing device **300** could be a client device (e.g., a device

actively operated by a user (e.g., a remote operator)), a server device (e.g., a device that provides computational services to client devices), or some other type of computational platform. In some embodiments, computing device **300** may be implemented as computer system **112**, which can be located on vehicle **100** and perform processing operations related to vehicle operations. For example, computing device **300** can be used to process sensor data received from sensor system **104**, develop control instructions, enable wireless communication with other devices, and/or perform other operations. Alternatively, computing device **300** can be located remotely from vehicle **100** and communicate via secure wireless communication. For example, computing device **300** may operate as a remotely positioned device that a remote human operator can use to communicate with one or more vehicles.

(67) In the example embodiment shown in FIG. 3, computing device **300** includes processor **302**, memory **304**, input/output unit **306** and network interface **308**, all of which may be coupled by a system bus **310** or a similar mechanism. In some embodiments, computing device **300** may include other components and/or peripheral devices (e.g., detachable storage, sensors, and so on).

(68) Processor **302** may be one or more of any type of computer processing element, such as a central processing unit (CPU), a co-processor (e.g., a mathematics, graphics, or encryption co-processor), a digital signal processor (DSP), a network processor, and/or a form of integrated circuit or controller that performs processor operations. In some cases, processor **302** may be one or more single-core processors. In other cases, processor **302** may be one or more multi-core processors with multiple independent processing units. Processor **302** may also include register memory for temporarily storing instructions being executed and related data, as well as cache memory for temporarily storing recently-used instructions and data.

(69) Memory **304** may be any form of computer-usable memory, including but not limited to random access memory (RAM), read-only memory (ROM), and non-volatile memory. This may include flash memory, hard disk drives, solid state drives, rewritable compact discs (CDs), rewritable digital video discs (DVDs), and/or tape storage, as just a few examples. Computing device **300** may include fixed memory as well as one or more removable memory units, the latter including but not limited to various types of secure digital (SD) cards. Thus, memory **304** can represent both main memory units, as well as long-term storage. Other types of memory may include biological memory.

(70) Memory **304** may store program instructions and/or data on which program instructions may operate. By way of example, memory **304** may store these program instructions on a non-transitory, computer-readable medium, such that the instructions are executable by processor **302** to carry out any of the methods, processes, or operations disclosed in this specification or the accompanying drawings.

(71) As shown in FIG. 3, memory **304** may include firmware **314A**, kernel **314B**, and/or applications **314C**. Firmware **314A** may be program code used to boot or otherwise initiate some or all of computing device **300**. Kernel **314B** may be an operating system, including modules for memory management, scheduling and management of processes, input/output, and communication. Kernel **314B** may also include device drivers that allow the operating system to communicate with the hardware modules (e.g., memory units, networking interfaces, ports, and busses), of computing device **300**. Applications **314C** may be one or more user-space software programs, such as web browsers or email clients, as well as any software libraries used by these programs. In some examples, applications **314C** may include one or more neural network applications and other deep learning-based applications. Memory **304** may also store data used by these and other programs and applications.

(72) Input/output unit **306** may facilitate user and peripheral device interaction with computing device **300** and/or other computing systems. Input/output unit **306** may include one or more types of input devices, such as a keyboard, a mouse, one or more touch screens, sensors, biometric sensors, and so on. Similarly, input/output unit **306** may include one or more types of output

devices, such as a screen, monitor, printer, speakers, and/or one or more light emitting diodes (LEDs). Additionally or alternatively, computing device **300** may communicate with other devices using a universal serial bus (USB) or high-definition multimedia interface (HDMI) port interface, for example. In some examples, input/output unit **306** can be configured to receive data from other devices. For instance, input/output unit **306** may receive sensor data from vehicle sensors.

(73) As shown in FIG. 3, input/output unit **306** includes GUI **312**, which can be configured to provide information to a remote operator or another user. GUI **312** may have one or more display interfaces, or another type of mechanism for conveying information and receiving inputs. In some examples, the representation of GUI **312** may differ depending on a vehicle situation. For example, computing device **300** may provide GUI **312** in a particular format, such as a format with a single selectable option for a remote operator to select from.

(74) Network interface **308** may take the form of one or more wireline interfaces, such as Ethernet (e.g., Fast Ethernet, Gigabit Ethernet, and so on). Network interface **308** may also support communication over one or more non-Ethernet media, such as coaxial cables or power lines, or over wide-area media, such as Synchronous Optical Networking (SONET) or digital subscriber line (DSL) technologies. Network interface **308** may additionally take the form of one or more wireless interfaces, such as IEEE 802.11 (Wifi), BLUETOOTH®, global positioning system (GPS), or a wide-area wireless interface. However, other forms of physical layer interfaces and other types of standard or proprietary communication protocols may be used over network interface **308**. Furthermore, network interface **308** may comprise multiple physical interfaces. For instance, some embodiments of computing device **300** may include Ethernet, BLUETOOTH®, and Wifi interfaces. In some embodiments, network interface **308** may enable computing device **300** to connect with one or more vehicles to allow for remote assistance techniques presented herein.

(75) In some embodiments, one or more instances of computing device **300** may be deployed to support a clustered architecture. The exact physical location, connectivity, and configuration of these computing devices may be unknown and/or unimportant to client devices. Accordingly, the computing devices may be referred to as “cloud-based” devices that may be housed at various remote data center locations. In addition, computing device **300** may enable the performance of embodiments described herein, including efficient assignment and processing of sensor data.

(76) FIG. 4 depicts system **400** for wireless communication between computing devices and a vehicle, according to one or more example embodiments. In the example embodiment, system **400** includes vehicle **402**, remote computing device **404**, and server **406** communicating wirelessly via network **408**. System **400** may include other components not shown within other embodiments, such as additional vehicles, computing devices, servers, firewalls, and multiple networks, among others.

(77) System **400** may enable performance of disclosed techniques described herein. For instance, vehicle **402** may be configured to autonomously (or semi-autonomously) transport passengers or objects (e.g., cargo) between locations and can have the form of any one or more of the vehicles discussed above, including passenger vehicles, cargo shipping vehicles (e.g., trucks), farming and manufacturing vehicles, and dual-purpose vehicles, among others. When operating in an autonomous mode, vehicle **402** may safely navigate to pick up and drop off passengers (or cargo) between different locations by using sensor measurements to detect and understand the surrounding environment. In some embodiments, vehicle **402** can operate as part of a fleet of vehicles, which may be managed by a central system (e.g., remote computing device **404** and/or other computing devices not shown in FIG. 4).

(78) Remote computing device **404** may represent any type of computing device or multiple devices configured to perform operations, including but not limited to those described herein. The position of remote computing device **404** relative to vehicle **402** can vary within examples. For instance, remote computing device **404** may have a remote position from vehicle **402**, such as operating inside a building. In other cases, remote computing device **404** can be a passenger device

located within vehicle **402**, such as a smartphone or a specialized computing device. In some implementations, operations described herein that are performed by remote computing device **404** may be additionally or alternatively performed by vehicle **402** (i.e., by any system(s) or subsystem(s) of vehicle **100**). In addition, operations described herein can be performed by any of the components communicating via network **408**. For instance, remote computing device **404** may determine operations for vehicle **402** to execute using information (e.g., sensor data) provided by vehicle **402**, server **406**, and/or other sources. In some embodiments, remote computing device **404** may use a GUI to convey information and display selectable options for review by a remote operator.

(79) Server **406** may wirelessly communicate information with remote computing device **404** and vehicle **402** via network **408** (or perhaps directly with remote computing device **404** and/or vehicle **402**). Server **406** may represent any computing device configured to receive, store, determine, and/or send information relating to vehicle **402** and the remote assistance thereof. Some implementations of wireless communication related to remote assistance may utilize server **406**, while others may not.

(80) Network **408** represents infrastructure that can enable wireless communication between computing devices, such as vehicle **402**, remote computing device **404**, and server **406**. For example, network **408** can correspond to a wireless communication network, such as the Internet or a cellular wireless communication network. In some embodiments, vehicle **402** may communicate with remote computing device **404** and/or server **406** via network **408** to receive and/or provide information related to sensor fouling techniques described herein. For instance, server **406** or remote computing device **404** may communicate an interference model to vehicle **402** for subsequent use during performance of disclosed techniques.

(81) FIG. 5 depicts scenario **500** showing vehicles using interference to detect sensor impairment. In the example embodiment, scenario **500** represents an example situation involving vehicle **502**, vehicle **504**, and vehicle **506** navigating relative to an intersection and in the same general environment. As shown in scenario **500**, vehicle **502** is slowing down to stop at the intersection in accordance with stop sign **508**, while vehicle **504** is stopped on the other side of the intersection relative to vehicle **502** and vehicle **506** is also shown located nearby vehicle **502**. With vehicles **502-506** operating near each other, signal interference can arise between the sensors (e.g., radar, lidar) operating on different vehicles. By evaluating measured signal interference relative to expected properties, one or multiple vehicles **502-506** may perform sensor fouling detection techniques disclosed herein.

(82) To further illustrate performance of disclosed techniques from the perspective of vehicle **502**, one or multiple sensors on vehicle **502** may receive electromagnetic energy emitted by an external source. For instance, a forward-facing radar positioned on vehicle **502** may capture radar measurements that are impacted by interference caused by RF signals emitted by one or multiple forward-facing radars positioned on vehicle **504**. An onboard computing system of vehicle **502** may perform disclosed techniques to diagnose the performance of the forward-facing radar experiencing the interference, which may involve analyzing the interference detected within radar returns relative to expected properties for interference. For instance, the computing device may compare a power level of the measured RF signals with a power level threshold that depends on the distance and the angle between vehicle **502** and vehicle **504** as represented by spatial relationship **510**. The power level threshold can be determined based on an interference model that represents power levels based on spatial relationship **510** between the receiving sensor and the source of the interference. The comparison may indicate if the forward-facing radar positioned on vehicle **502** is potentially impaired by fouling or another issue.

(83) The computing device may further use additional sensor data from one or multiple sensors on vehicle **502** and/or wireless communication with vehicle **504** to determine if the impairment is local to the forward-facing radar on vehicle **502** and/or the emitter on vehicle **504** is the cause. As

shown, in order to evaluate the RF interference, vehicle **502** may initially identify the source of the RF signals and then determine spatial relationship **510** relative to the source. For instance, vehicle **502** may determine that the source of the RF signals is vehicle **504** based on the reception angle of the RF signals and the position and orientation of the radar that received the RF signals.

(84) Vehicle **502** may also use wireless communication to identify the source (e.g., vehicle **504**). Determining the spatial positioning relative to a source of a signal (e.g., a sensor) can differ within examples. In some examples, the position and orientation of the receiving sensor can indicate where incoming signals may have originated. Additional sensor data can further be used to determine the spatial positioning. In addition, the onboard computing device may communicate with vehicle **504** to obtain transmission information. For instance, vehicle **504** and vehicle **502** can share transmission parameters and location information to enable performance of disclosed techniques by the other vehicle.

(85) Determination of spatial relationship **510** can allow the computing device onboard vehicle **502** to identify expected properties that can be used to evaluate the interference and determine if the receiving radar is experiencing some form of impairment. For instance, the computing device may identify a power level threshold that should be measured within the received RF interference based on the distance and angle to the source as represented by spatial relationship **510**. The expected power level can be higher or lower pending on the angle and the distance between the emitter and the receiving radar. For instance, the expected power level can be lower when the distance between the emitter and the sensor is farther. The computing device can also analyze other properties of the RF interference by comparing them to expected values for the properties.

(86) Evaluation of the properties of the interference can indicate if the receiving radar is potentially experiencing some form of impairment, such as fouling on the radome. In particular, when the measured power of the received signals is lower than the expected power level, this may indicate that fouling is impairing the radar that received the RF signals. Fouling occurs when dirt, precipitation, or other physical material covers a sensor's covering (e.g., a radar's radome) and partially impacts the ability for the sensor to receive signals. In some cases, physical damage can also hinder the sensor's ability to receive signals. The lower measured power relative to the expected power could also indicate that the emitter of the RF interference is operating at an unexpected power transmission level and/or is experiencing some form of sensor impairment. Vehicle **502** may decrease confidence associated with the receiving sensor based on the results of disclosed techniques. The decreased confidence can be temporary in some cases, such as when additional sensor data shows that the impairment is no longer impacting the particular sensor. In some examples, vehicle **502** may further evaluate the performance of the potentially impaired radar (or other type of sensor) based on interference with vehicle **506**.

(87) In some embodiments, a central system may perform disclosed techniques based on information received from multiple vehicles. For instance, the central system may receive information from multiple vehicles **502-506** that indicates orientation, position, and operation parameters for sensors and use the information to perform disclosed techniques. The central system can perform the disclosed techniques and relay results to the different vehicles **502-506** and/or share the information for onboard vehicle systems to perform disclosed techniques.

(88) FIG. **6** depicts another scenario **600** showing vehicle **602** using interference caused by sensors on vehicle **604** in order to analyze potential onboard sensor impairment. As shown in the example embodiment, vehicle **602** and vehicle **604** are traveling in opposite directions on road **610**. The spatial relationship between vehicles **602-604** is shown for illustration purposes and can differ in real-world applications. In particular, the distance between vehicles **602-604** can be greater while vehicles **602-604** can still perform disclosed techniques to detect potential sensor impairments. In addition, vehicle **602** and vehicle **604** may operate as part of the same fleet in some examples. In such cases, vehicles **602-604** may share information with each other and/or a central management system.

(89) In scenario **600**, vehicle **602** may detect interference within sensor returns from one or multiple types of sensors. For instance, radar and/or lidar positioned on vehicle **602** may experience interference within returns due to sensor signals emitted by sensors positioned on vehicle **604**. A computing system on vehicle **602** may use the detected interference to analyze the operation condition of one or multiple sensors.

(90) As an example, FIG. **6** shows vehicle **602** performing disclosed techniques based on a forward-facing radar positioned near a front bumper of vehicle **602**. The forward-facing radar may receive RF signals that originated from a forward-facing radar positioned on vehicle **604**. Based on the pattern of the returns produced by the radar on vehicle **602**, the computing system may determine that interference is present and subsequently determine a spatial relationship with the source of the interference. In practice, vehicle **602** may anticipate interference based on the proximity of vehicle **604** and/or communication with vehicle **604**. For instance, vehicle **602** and vehicle **604** may communicate wirelessly and share information (e.g., location and transmission data) to perform disclosed techniques.

(91) In order to evaluate potential impairment at the radar, the computing system on vehicle **602** may estimate the spatial relationship relative to the emitting sensor positioned on vehicle **604**. As shown, the computing system may determine distance **606** and angle **608** between the radar located onboard vehicle **602** and the emitting radar positioned on vehicle **604**. The spatial relationship can be determined based on sensor data, communication between vehicles **602-604**, and/or other factors (e.g., vehicle position and transmission information from a central system).

(92) In some examples, the computing system on vehicle **602** may perform a comparison between a power level of the RF signals and a power level threshold that depends on the distance and the angle to the source of the RF signals (e.g., the radar positioned on vehicle **604**). For instance, the computing system may use an interference model and/or communication with vehicle **604** to determine an expected power level (e.g., a power level threshold) for the radar returns impacted by the interference. When the actual power level within the radar returns differs, this may indicate that the receiving radar on vehicle **602** is potentially impaired. In some cases, the computing system on vehicle **602** may then decrease a confidence assigned to the radar coupled to the vehicle based on the comparison and subsequently control the vehicle based on the decreased confidence assigned to the radar. For instance, the computing system may rely on sensor measurements from other sensors until validating the potential impairment of the analyzed radar.

(93) Vehicle **602** may further communicate with vehicle **604** in some examples. Further communication may enable vehicle **602** to determine if the onboard radar is impaired or if the emitting radar on vehicle **604** is potentially the source of the difference detected within the comparison. For instance, the communication between vehicles **602-604** may reveal that the emitting radar on vehicle **604** is experiencing fouling or some other impairment and/or atmospheric loss may have contributed to the difference detected between the measured interference and expected interference by vehicle **602**. In some examples, vehicle **602** may use additional sensor data from the radar and/or other sensors to further analyze the potential impairment of the forward-facing radar. In some cases, radar data from the forward-facing radar may show that the radar is operating properly without any impairment. In addition, vehicle **604** may also perform disclosed techniques in a manner similar to vehicle **602** in some examples.

(94) FIG. **7** is a flowchart of example method **700** for operating a radar system, according to one or more embodiments. Method **700** may include one or more operations, functions, or actions, as depicted by one or more of blocks **702**, **704**, **706**, **708**, and **710**, each of which may be carried out by any of the systems shown in prior figures, among other possible systems.

(95) Those skilled in the art will understand that the flow charts described herein illustrate functionality and operation of certain implementations of the present disclosure. In this regard, each block of the flowchart may represent a module, a segment, or a portion of program code, which includes one or more instructions executable by one or more processors for implementing

specific logical functions or steps in the process. The program code may be stored on any type of computer readable medium, for example, such as a storage device including a disk or hard drive. (96) In addition, each block may represent circuitry that is wired to perform the specific logical functions in the process. Alternative implementations are included within the scope of the example implementations of the present application in which functions may be executed out of order from that shown or discussed, including substantially concurrent or in reverse order, depending on the functionality involved, as would be understood by those reasonably skilled in the art.

(97) Block **702** of method **700** involves receiving radio-frequency (RF) signals propagating in an environment of the vehicle. For instance, a vehicle computing device or another type of computing system may receive the RF signals from one or multiple radars positioned on the vehicle during navigation. In other cases, the computing device can receive other types of sensor signals propagating in the environment.

(98) Block **704** of method **700** involves determining a distance and an angle to a source of the RF signals. For instance, the computing device may determine the RF signals originating from a second vehicle positioned in the environment and estimate a distance and an angle to the second vehicle. In some cases, the computing device may estimate the distance and the angle to the second vehicle based on wireless communication with the second vehicle. In other cases, the computing device may estimate the distance and the angle to the second vehicle based on sensor data from one or more vehicle sensors.

(99) In some examples, the computing device may identify one or more parameters of the RF that indicate the RF signals originate from an external emitter based on receiving the RF signals. For instance, the computing device may perform a comparison between first parameters corresponding to RF signals transmitted by the radar coupled to the vehicle and second parameters corresponding to the RF signals propagating in the environment. Based on the comparison between the first parameters and the second parameters, the computing device may identify at least one parameter in the second parameter that indicates the RF signals originate from the external emitter. Example parameters that can be used to distinguish the received RF signals from reflections of signals emitted by the radar include the polarization, the waveform, the timing, the Doppler dimension, and other aspects of the RF signals.

(100) Block **706** of method **700** involves performing a comparison between a power level of the RF signals and a power level threshold. The power level threshold depends on the distance and the angle to the source of the RF signals.

(101) In some examples, the computing device may identify, using an interference model, the power level threshold based on determining the distance and the angle to the source of the RF signals. The interference model can represent respective power level thresholds for multiple spatial relationships between the vehicle and the source of the RF signals. Each spatial relationship depends on a given distance and a given angle between the vehicle and the given source of the RF signals.

(102) Block **708** of method **700** involves decreasing a confidence assigned to the radar coupled to the vehicle based on the comparison. For instance, the computing device may determine the power level of the RF signals is below the power level threshold based on the comparison. The computing device may decrease the confidence assigned to the radar based on determining if the power level of the RF signals is below the power level threshold. In some cases, the computing device may determine fouling is present on a radome of the radar.

(103) In some examples, the computing device may trigger a cleaning process for the radar based on the comparison. For instance, the comparison may convey that the radome of the radar is likely experiencing fouling and perform a cleaning process on the radome to try to reduce the fouling. The computing device may then evaluate subsequent performance by the radar based on triggering the cleaning process for the radar. The computing device can then adjust the confidence assigned to the radar based on evaluating subsequent performance by the radar.

(104) Block **710** of method **700** involves controlling the vehicle based on the decreased confidence assigned to the radar. The computing device or another computing system on the vehicle may control the vehicle based on sensor data from one or more vehicle sensors. For instance, the computing device may use other sensors.

(105) In some examples, method **700** further involves communicating with the source of the RF signals and increasing the confidence assigned to the radar based on communicating with the source of the RF signals. In some examples, method **700** further involves receiving radar data from the radar coupled to the vehicle and increasing the confidence assigned to the radar based on the radar data. In some cases, the vehicle may initiate one or more cleaning techniques and reanalyze performance of the sensor after.

(106) In some examples, the vehicle is a first vehicle and the source of the RF signals is a radar coupled to a second vehicle, and the second vehicle is configured to wirelessly communicate transmission parameters and location information to the first vehicle. As such, the computing device can be further configured to determine the distance and the angle to the second vehicle based on the location information. The computing device may also perform the comparison between the power level of the RF signals and the power level threshold, where the power level threshold is further based on the transmission parameters.

(107) FIG. **8** is a schematic illustrating a conceptual partial view of an example computer program product that includes a computer program for executing a computer process on a computing device, arranged according to at least some embodiments presented herein. In some embodiments, the disclosed methods may be implemented as computer program instructions encoded on a non-transitory computer-readable storage media in a machine-readable format, or on other non-transitory media or articles of manufacture.

(108) In one embodiment, example computer program product **800** is provided using signal bearing medium **802**, which may include one or more programming instructions **804** that, when executed by one or more processors may provide functionality or portions of the functionality described above with respect to FIGS. **1-7**. In some examples, the signal bearing medium **802** may encompass a non-transitory computer-readable medium **806**, such as, but not limited to, a hard disk drive, a Compact Disc (CD), a Digital Video Disk (DVD), a digital tape, memory, etc. In some implementations, signal bearing medium **802** may encompass a computer recordable medium **808**, such as, but not limited to, memory, read/write (R/W) CDs, R/W DVDs, etc. In some implementations, the signal bearing medium **802** may encompass a communications medium **810**, such as, but not limited to, a digital and/or an analog communication medium (e.g., a fiber optic cable, a waveguide, a wired communications link, a wireless communication link, etc.). Thus, for example, the signal bearing medium **802** may be conveyed by a wireless form of the communications medium **810**.

(109) One or more programming instructions **804** may be, for example, computer executable and/or logic implemented instructions. In some examples, a computing device such as the computer system **112** of FIG. **1** may be configured to provide various operations, functions, or actions in response to the programming instructions **804** conveyed to the computer system **112** by one or more of the computer readable medium **806**, the computer recordable medium **808**, and/or the communications medium **810**. Other devices may perform operations, functions, or actions described herein.

(110) The non-transitory computer readable medium could also be distributed among multiple data storage elements, which could be remotely located from each other. The computing device that executes some or all of the stored instructions could be a vehicle, such as vehicle **100** illustrated in FIGS. **1-2E**. Alternatively, the computing device that executes some or all of the stored instructions could be another computing device, such as a server.

(111) The above detailed description describes various features and functions of the disclosed systems, devices, and methods with reference to the accompanying figures. While various aspects

and embodiments have been disclosed herein, other aspects and embodiments will be apparent. The various aspects and embodiments disclosed herein are for purposes of illustration and are not intended to be limiting, with the true scope being indicated by the following claims.

(112) It should be understood that arrangements described herein are for purposes of example only. As such, those skilled in the art will appreciate that other arrangements and other elements (e.g. machines, apparatuses, interfaces, functions, orders, and groupings of functions, etc.) can be used instead, and some elements may be omitted altogether according to the desired results. Further, many of the elements that are described are functional entities that may be implemented as discrete or distributed components or in conjunction with other components, in any suitable combination and location.

Claims

1. A method comprising: receiving, at a computing device and from a radar coupled to a vehicle, radio-frequency (RF) signals propagating in an environment of the vehicle; determining a distance and an angle to a source of the RF signals, wherein the source of the RF signals is a vehicle radar system used by a second vehicle operating in the environment of the vehicle; performing a comparison between a power level of the RF signals and a power level threshold, wherein the power level threshold depends on the distance and the angle to the source of the RF signals; based on the comparison indicating the power level of the RF signals is below the power level threshold, decreasing a confidence assigned to the radar coupled to the vehicle; and controlling, by the computing device, the vehicle according to a strategy generated based on the decreased confidence assigned to the radar.
2. The method of claim 1, further comprising: based on receiving the RF signals, identifying one or more parameters of the RF signals that indicate the RF signals originate from the vehicle radar system used by the second vehicle.
3. The method of claim 2, wherein identifying one or more parameters of the RF signals that indicate the RF signals originate from the vehicle radar system used by the second vehicle comprises: performing a comparison between first parameters corresponding to RF signals transmitted by the radar coupled to the vehicle and second parameters corresponding to the RF signals propagating in the environment; and based on the comparison between the first parameters and the second parameters, identifying at least one parameter in the second parameters that indicates the RF signals originate from the vehicle radar system used by the second vehicle.
4. The method of claim 1, wherein determining the distance and the angle to the source of the RF signals comprises: determining the RF signals originate from the vehicle radar system used by the second vehicle positioned in the environment; and estimating a distance and an angle to the second vehicle.
5. The method of claim 4, wherein estimating the distance and the angle to the second vehicle comprises: communicating via wireless communication with the second vehicle; and estimating the distance and the angle to the second vehicle based on information received during the wireless communication with the second vehicle.
6. The method of claim 4, wherein estimating the distance and the angle to the second vehicle comprises: estimating the distance and the angle to the second vehicle based on sensor data from one or more vehicle sensors.
7. The method of claim 1, further comprising: communicating with the source of the RF signals; and based on communicating with the source of the RF signals, increasing the confidence assigned to the radar.
8. The method of claim 1, further comprising: receiving radar data from the radar coupled to the vehicle; and based on the radar data, increasing the confidence assigned to the radar.
9. The method of claim 1, further comprising: based on determining the distance and the angle to

the source of the RF signals, identifying, using an interference model, the power level threshold, wherein the interference model represents respective power level thresholds for a plurality of spatial relationships between the vehicle and a given source of the RF signals, and wherein each spatial relationship depends on a distance and an angle between the vehicle and the given source of the RF signal.

10. The method of claim 1, further comprising: based on the comparison, triggering a cleaning process for the radar.

11. The method of claim 10, further comprising: evaluating subsequent performance by the radar based on triggering the cleaning process for the radar; and adjusting the confidence assigned to the radar based on evaluating subsequent performance by the radar.

12. The method of claim 1, wherein decreasing the confidence assigned to the radar comprises: disregarding radar data obtained via the radar during subsequent navigation of the vehicle.

13. The method of claim 1, wherein decreasing the confidence assigned to the radar coupled to the vehicle comprises: determining fouling is present on a radome of the radar.

14. The method of claim 1, wherein controlling the vehicle based on the decreased confidence assigned to the radar comprises: controlling the vehicle based on sensor data from one or more vehicle sensors, wherein the one or more vehicle sensors differ from the radar.

15. The method of claim 1, wherein controlling the vehicle according to the strategy generated based on the decreased confidence assigned to the radar comprises: selecting a set of vehicle sensors coupled to the vehicle based on the decreased confidence assigned to the radar, wherein the set of vehicle sensors differ from the radar; and controlling the vehicle using sensor data from the set of vehicle sensors.

16. A system comprising: a first vehicle radar system coupled to a vehicle; a computing device coupled to the vehicle and configured to: receive, from a radar of the first vehicle radar system, radio-frequency (RF) signals propagating in an environment of the vehicle; determine a distance and an angle to a source of the RF signals, wherein the source is a second vehicle radar system used by a second vehicle operating in the environment of the vehicle; perform a comparison between a power level of the RF signals and a power level threshold, wherein the power level threshold depends on the distance and the angle to the source of the RF signals; based on the comparison indicating the power level of the RF signals is below the power level threshold, decrease a confidence assigned to the radar coupled to the vehicle; and control the vehicle according to a strategy generated based on the decreased confidence assigned to the radar.

17. The system of claim 16, wherein the vehicle is a first vehicle, and wherein the second vehicle is configured to wirelessly communicate transmission parameters and location information to the first vehicle.

18. The system of claim 17, wherein the computing device is further configured to: determine the distance and the angle to the second vehicle based on the location information.

19. The system of claim 18, wherein the computing device is further configured to perform the comparison between the power level of the RF signals and the power level threshold, wherein the power level threshold is further based on the transmission parameters.

20. A non-transitory computer-readable medium configured to store instructions, that when executed by a computing system comprising one or more processors, causes the computing system to perform operations comprising: receiving, from a radar coupled to a vehicle, radio-frequency (RF) signals propagating in an environment of the vehicle; determining a distance and an angle to a source of the RF signals, wherein the source of the RF signals is a vehicle radar system used by a second vehicle operating in the environment of the vehicle; performing a comparison between a power level of the RF signals and a power level threshold, wherein the power level threshold depends on the distance and the angle to the source of the RF signals; based on the comparison indicating the power level of the RF signals is below the power level threshold, decreasing a

confidence assigned to the radar coupled to the vehicle; and controlling the vehicle according to a strategy generated based on the decreased confidence assigned to the radar.
