

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250258300

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

MacGougan; Glenn D. et al.

SYSTEMS AND METHODS FOR SHARED ANTENNA TUNING

Abstract

This disclosure is directed to shared antenna tuning. An electronic device may receive a global navigation satellite system (GNSS) tune request to tune a shared antenna to a GNSS signal frequency. The electronic device may then tune the antenna to the GNSS signal frequency and enable a GNSS receiver. The electronic device may also receive a cellular tune request to tune the antenna to a cellular frequency. The electronic device may tune the antenna to a cellular frequency and may deactivate the GNSS receiver or blank the GNSS receiver. In some embodiments, the electronic device may also communicate with a Low Earth Orbit (LEO) satellite. During LEO satellite communication, the electronic device may transmit a signal to blank a GNSS L1 receiver to avoid signal interference with the LEO satellite communication, and activate a GNSS L5 receiver to receive GNSS signals.

Inventors: MacGougan; Glenn D. (San Jose, CA), Srivastava; Aditya N. (Fremont, CA), Shirahatti; Harsha (Santa Clara, CA), Chaudhary; Madhusudan (Campbell, CA), Ekici; Ozgur (Ottawa, CA), Sane; Sachin J. (San Jose, CA), Bencze; William J. (Half Moon Bay, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 1000008572146

Appl. No.: 19/055349

Filed: February 17, 2025

Related U.S. Application Data

parent US continuation 17321171 20210514 ABANDONED child US 17668828

parent US division 17668828 20220210 parent-grant-document US 12228655 child US 19055349

Publication Classification

Int. Cl.: G01S19/23 (20100101); **G01S19/20** (20100101); **G01S19/24** (20100101); **H01Q1/24** (20060101)

U.S. Cl.:

CPC G01S19/235 (20130101); **G01S19/20** (20130101); **G01S19/24** (20130101); **H01Q1/241** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a divisional application of U.S. patent application Ser. No. 17/668,828, entitled “SYSTEMS AND METHODS FOR SHARED ANTENNA TUNING”, filed Feb. 10, 2022, which is a continuation of U.S. application Ser. No. 17/321,171, entitled “SYSTEMS AND METHODS FOR SHARED ANTENNA TUNING,” filed May 14, 2021, now abandoned, each of which is incorporated by reference in its entirety for all purposes.

BACKGROUND

[0002] The present disclosure relates generally to systems and methods for shared antenna tuning in a wireless communication device, and more specifically to controlling transmitters and/or receivers in response to tuning requests received by the wireless communication device.

[0003] In a wireless communication device (e.g., a smartphone), one or more antennas may be tuned to desired frequencies based upon tune requests received by the wireless communication device. The wireless communication device may then send or receive signals using a transmitter or receiver coupled to the one or more antennas. In this manner, different signals of different frequencies may be sent from or received by the wireless communication device. However, these sent or received signals may be negatively impacted by attenuation at certain frequencies due to multiple signaling operations being conducted concurrently by the wireless communication device.

SUMMARY

[0004] A summary of certain embodiments disclosed herein is set forth below. It should be understood that these aspects are presented merely to provide the reader with a brief summary of these certain embodiments and that these aspects are not intended to limit the scope of this disclosure. Indeed, this disclosure may encompass a variety of aspects that may not be set forth below.

[0005] In one embodiment, an electronic device includes multiple antennas, a cellular transceiver that sends and receives cellular signals via one or more antennas of the multiple antennas, and a global navigation satellite system (GNSS) receiver that receives GNSS signals via the one or more antennas. The electronic device also includes one or more processors that receive a GNSS tune request to receive the GNSS signals via the one or more antennas at a GNSS signal frequency, and in response to receiving the GNSS tune request, receive the GNSS signals via the one or more antennas at the GNSS signal frequency. The one or more processors also receive a cellular tune request to send or receive the cellular signals via the one or more antennas at a cellular frequency, and, in response to receiving the cellular tune request, deactivate the GNSS receiver, and send or receive, using the cellular transceiver, the cellular signals via the one or more antennas at the cellular frequency.

[0006] In another embodiment, an electronic device includes multiple antennas and a first global navigation satellite system (GNSS) receiver that receives GNSS signals via a first set of the antennas of the multiple antennas on a first GNSS frequency band, and a second GNSS receiver that receives GNSS signals via a second set of the antennas of the multiple antennas on a second

GNSS frequency band. The electronic device also includes a Low Earth Orbit (LEO) satellite transceiver that sends and receives LEO satellite signals via a third set of antennas of the multiple antennas. The electronic device further includes one or more processors that receive an LEO satellite tune request to send or receive the LEO satellite signals via the third set of antennas at a LEO satellite signal frequency, and, in response to receiving the LEO satellite tune request, blank or deactivate the first GNSS receiver, activate the LEO satellite transceiver, and enable the second GNSS receiver. Additionally, the one or more processors receive an indication that the LEO satellite is out of range, and, in response, to receiving the indication that the LEO satellite is out of range, deactivate the LEO satellite transceiver and enable the first GNSS receiver.

[0007] In yet another embodiment, a method includes receiving, at processing circuitry of an electronic device, a global navigation satellite system (GNSS) tune request to receive GNSS signals via one or more antennas of multiple antennas at a GNSS signal frequency and, in response to receiving the GNSS tune request, receiving, using a GNSS receiver of the electronic device, the GNSS signals via the one or more antennas at the GNSS signal frequency. Additionally, the method includes receiving, by the processing circuitry, a cellular tune request to send or receive the cellular signals via the one or more antennas at a cellular frequency. In response to receiving the cellular tune request deactivating the GNSS receiver, and sending or receiving, using a cellular transceiver of the electronic device, cellular signals via the one or more antennas at the cellular frequency.

[0008] Various refinements of the features noted above may exist in relation to various aspects of the present disclosure. Further features may also be incorporated in these various aspects as well. These refinements and additional features may exist individually or in any combination. For instance, various features discussed below in relation to one or more of the illustrated embodiments may be incorporated into any of the above-described aspects of the present disclosure alone or in any combination. The brief summary presented above is intended only to familiarize the reader with certain aspects and contexts of embodiments of the present disclosure without limitation to the claimed subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Various aspects of this disclosure may be better understood upon reading the following detailed description and upon reference to the drawings described below in which like numerals refer to like parts.

[0010] FIG. 1 is a block diagram of an electronic device, according to embodiments of the present disclosure;

[0011] FIG. 2 is a functional diagram of the electronic device of FIG. 1, according to embodiments of the present disclosure;

[0012] FIG. 3 is a schematic diagram of a transmitter of the electronic device of FIG. 1, according to embodiments of the present disclosure;

[0013] FIG. 4 is a schematic diagram of a receiver of the electronic device of FIG. 1, according to embodiments of the present disclosure;

[0014] FIG. 5 is a schematic diagram of communication circuitry of the electronic device of FIG. 1, according to embodiments of the present disclosure;

[0015] FIG. 6 is a flowchart for tuning an antenna shared by a cellular transceiver and a Global Navigation Satellite System (GNSS) receiver as shown in FIG. 5, according to embodiments of the present disclosure;

[0016] FIG. 7 is a flowchart for tuning an antenna shared by the cellular transceiver and the GNSS receiver of FIG. 5 based on a cellular operation, according to embodiments of the present disclosure;

[0017] FIG. 8 is a flowchart for tuning an antenna shared by the cellular transceiver and the GNSS receiver of FIG. 5 by delaying tuning to the GNSS receiver, according to embodiments of the present disclosure;

[0018] FIG. 9 is a flowchart for tuning an antenna shared by a Low Orbit Satellite (LEO) transceiver and a GNSS receiver as shown in FIG. 5, according to embodiments of the present disclosure; and

[0019] FIG. 10 is a flowchart for deactivating a LEO transceiver of FIG. 5 based on a location of the electronic device of FIG. 1, according to embodiments of the present disclosure.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

[0020] One or more specific embodiments will be described below. In an effort to provide a concise description of these embodiments, not all features of an actual implementation are described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

[0021] When introducing elements of various embodiments of the present disclosure, the articles “a,” “an,” and “the” are intended to mean that there are one or more of the elements. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. Additionally, it should be understood that references to “one embodiment” or “an embodiment” of the present disclosure are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. Use of the term “approximately,” “near,” “about,” “close to,” and/or “substantially” should be understood to mean including close to a target (e.g., design, value, amount), such as within a margin of any suitable or contemplable error (e.g., within 0.1% of a target, within 1% of a target, within 5% of a target, within 10% of a target, within 25% of a target, and so on).

[0022] This disclosure is directed to antenna tuning for various signal types in electronic devices (e.g., radio frequency communication devices). The electronic device may include one or more shared antennas that may each receive cellular signals and satellite signals in multiple frequency bands. For example, the one or more shared antennas may receive a global navigation satellite system (GNSS) signal transmitted by a GNSS satellite in L1 frequency bands (e.g., centered at 1575.42 MHz) and/or L5 frequency bands (e.g., centered at 1176.45 MHz). In some cases, the shared one or more antennas may be tuned to a cellular frequency, and the GNSS signals in some/all frequency bands may be severely attenuated as a result. For example, the one or more shared antenna may periodically be tuned to cellular bands for cellular paging operations even when there is no cellular operation. This periodic antenna de-tune from GNSS operation to cellular paging operations (e.g., periodic requests (e.g., every 1.28 second) for cellular tuning for a duration of 1 millisecond (ms) to 10 ms may introduce noise into and degrade the GNSS signals. In particular, the GNSS signals may be 20 decibels (dB) below a noise floor of cellular operations without additional de-tuning or de-sensing due to antenna tuning away from a GNSS frequency band. Thus, GNSS processing may be unnecessary and result in unneeded power expenditure without any user benefit.

[0023] Additionally, the electronic device may receive low earth orbit (LEO) satellite signals on a LEO transmit frequency band (e.g., 1610-1618.725 megahertz (MHz)) that may interfere with the L1 band for GNSS signal reception. This may result in interference with the GNSS signals received by the one or more antennas on the L1 band. Additionally, governmental bodies and other

regulatory bodies may implement restrictions on LEO satellite communication according to certain geographical areas, such as requiring that the electronic device deactivate a LEO transceiver and halt LEO satellite communication in the certain geographical areas.

[0024] Embodiments herein provide various apparatuses and techniques to reduce GNSS signal attenuation and unnecessary GNSS receiver power output during shared antenna tuning with cellular operations. To do so, the embodiments disclosed herein include GNSS receiver architecture that enables independent power control for signals received at one or more GNSS receivers. In particular, a GNSS receiver may be deactivated and/or blanked (e.g., the received signals may be “blanked” or replaced with “dummy” signals, such as a signals having only zeroes) when the shared antenna is detuned (e.g., with respect to GNSS) for cellular requests. In this way, attenuation of GNSS signals during cellular operation using the shared antenna may be mitigated or avoided. Moreover, blanking the GNSS receiver, as opposed to deactivating the GNSS receiver, may enable faster activation of the GNSS receiver, thus reducing latency time and excess power output associated with deactivating and activating the GNSS receiver multiple times over short time durations.

[0025] Additionally, to address LEO satellite transmission interference with the GNSS signals in the L1 band, the electronic device may deactivate (e.g., shut off or depower) a GNSS L1 receiver during LEO satellite transmissions. That is, the electronic device may determine that a LEO satellite transmission signal is to be received, and deactivate the GNSS L1 receiver for a period of time that the electronic device receives the LEO satellite transmissions. The electronic device may also enable a GNSS L5 receiver so that GNSS signals may continue to be received and processed by the electronic device in the L5 frequency band, which may not interfere with the LEO satellite transmission signal. The electronic device may also enable periodic tracking and updating of a location of the electronic device (e.g., relative to geographical areas where LEO satellite transmissions are not permitted based on territory regulations). The electronic device may initially determine a distance the device is to an area where LEO satellite communication is restricted (e.g., geographical areas where the LEO transceiver of the electronic device should be deactivated). The electronic device may periodically determine the location of the device via receiving GNSS L5 signals, and may increase the frequency of location determination based on the distance to the restricted LEO satellite area decreasing. Accordingly, the electronic device may increase frequency of location determination as the electronic device approaches the restricted LEO use area, and may deactivate the LEO transceiver when the electronic device is within the restricted LEO use area.

[0026] With the foregoing in mind, FIG. 1 is a block diagram of an electronic device 10, according to embodiments of the present disclosure. The electronic device 10 may include, among other things, one or more processors 12 (collectively referred to herein as a single processor for convenience, which may be implemented in any suitable form of processing circuitry), memory 14, nonvolatile storage 16, a display 18, input structures 22, an input/output (I/O) interface 24, a network interface 26, and a power source 29. The various functional blocks shown in FIG. 1 may include hardware elements (including circuitry), software elements (including machine-executable instructions) or a combination of both hardware and software elements (which may be referred to as logic). The processor 12, memory 14, the nonvolatile storage 16, the display 18, the input structures 22, the input/output (I/O) interface 24, the network interface 26, and/or the power source 29 may each be communicatively coupled directly or indirectly (e.g., through or via another component, a communication bus, a network) to one another to transmit and/or receive data between one another. It should be noted that FIG. 1 is merely one example of a particular implementation and is intended to illustrate the types of components that may be present in electronic device 10.

[0027] By way of example, the electronic device 10 may include any suitable computing device, including a desktop or notebook computer (e.g., in the form of a MacBook®, MacBook® Pro, MacBook Air®, iMac®, Mac® mini, or Mac Pro® available from Apple Inc. of Cupertino,

California), a portable electronic or handheld electronic device such as a wireless electronic device or smartphone (e.g., in the form of a model of an iPhone® available from Apple Inc. of Cupertino, California), a tablet (e.g., in the form of a model of an iPad® available from Apple Inc. of Cupertino, California), a wearable electronic device (e.g., in the form of an Apple Watch® by Apple Inc. of Cupertino, California), and other similar devices. It should be noted that the processor **12** and other related items in FIG. **1** may be generally referred to herein as “data processing circuitry.” Such data processing circuitry may be embodied wholly or in part as software, hardware, or both. Furthermore, the processor **12** and other related items in FIG. **1** may be a single contained processing module or may be incorporated wholly or partially within any of the other elements within the electronic device **10**. The processor **12** may be implemented with any combination of general-purpose microprocessors, microcontrollers, digital signal processors (DSPs), field programmable gate array (FPGAs), programmable logic devices (PLDs), controllers, state machines, gated logic, discrete hardware components, dedicated hardware finite state machines, or any other suitable entities that may perform calculations or other manipulations of information. The processors **12** may perform the various functions described herein and below. [0028] In the electronic device **10** of FIG. **1**, the processor **12** may be operably coupled with a memory **14** and a nonvolatile storage **16** to perform various algorithms. Such programs or instructions executed by the processor **12** may be stored in any suitable article of manufacture that includes one or more tangible, computer-readable media. The tangible, computer-readable media may include the memory **14** and/or the nonvolatile storage **16**, individually or collectively, to store the instructions or routines. The memory **14** and the nonvolatile storage **16** may include any suitable articles of manufacture for storing data and executable instructions, such as random-access memory, read-only memory, rewritable flash memory, hard drives, and optical discs. In addition, programs (e.g., an operating system) encoded on such a computer program product may also include instructions that may be executed by the processor **12** to enable the electronic device **10** to provide various functionalities.

[0029] In certain embodiments, the display **18** may facilitate users to view images generated on the electronic device **10**. In some embodiments, the display **18** may include a touch screen, which may facilitate user interaction with a user interface of the electronic device **10**. Furthermore, it should be appreciated that, in some embodiments, the display **18** may include one or more liquid crystal displays (LCDs), light-emitting diode (LED) displays, organic light-emitting diode (OLED) displays, active-matrix organic light-emitting diode (AMOLED) displays, or some combination of these and/or other display technologies.

[0030] The input structures **22** of the electronic device **10** may enable a user to interact with the electronic device **10** (e.g., pressing a button to increase or decrease a volume level). The I/O interface **24** may enable electronic device **10** to interface with various other electronic devices, as may the network interface **26**. In some embodiments, the I/O interface **24** may include an I/O port for a hardwired connection for charging and/or content manipulation using a standard connector and protocol, such as the Lightning connector provided by Apple Inc. of Cupertino, California, a universal serial bus (USB), or other similar connector and protocol. The network interface **26** may include, for example, one or more interfaces for a personal area network (PAN), such as a BLUETOOTH® network, for a local area network (LAN) or wireless local area network (WLAN), such as a network employing one of the IEEE 802.11x family of protocols (e.g., WI-FI®), and/or for a wide area network (WAN), such as any standards related to the Third Generation Partnership Project (3GPP), including, for example, a 3.sup.rd generation (3G) cellular network, universal mobile telecommunication system (UMTS), 4.sup.th generation (4G) cellular network, long term evolution (LTE®) cellular network, long term evolution license assisted access (LTE-LAA) cellular network, 5.sup.th generation (5G) cellular network, and/or New Radio (NR) cellular network, a satellite network, and so on. In particular, the network interface **26** may include, for example, one or more interfaces for using a Release-15 cellular communication standard of the 5G specifications

that include the millimeter wave (mmWave) frequency range (e.g., 24.25-300 gigahertz (GHz)). The network interface **26** of the electronic device **10** may allow communication over the aforementioned networks (e.g., 5G, Wi-Fi, LTE-LAA, and so forth).

[0031] The network interface **26** may also include one or more interfaces for, for example, broadband fixed wireless access networks (e.g., WIMAX®), mobile broadband Wireless networks (mobile WIMAX®), asynchronous digital subscriber lines (e.g., ADSL, VDSL), digital video broadcasting-terrestrial (DVB-T®) network and its extension DVB Handheld (DVB-H®) network, ultra-wideband (UWB) network, alternating current (AC) power lines, and so forth.

[0032] As illustrated, the network interface **26** may include a transceiver **30**. In some embodiments, all or portions of the transceiver **30** may be disposed within the processor **12**. The transceiver **30** may support transmission and receipt of various wireless signals via one or more antennas. The power source **29** of the electronic device **10** may include any suitable source of power, such as a rechargeable lithium polymer (Li-poly) battery and/or an alternating current (AC) power converter. In certain embodiments, the electronic device **10** may take the form of a computer, a portable electronic device, a wearable electronic device, or other type of electronic device.

[0033] FIG. **2** is a functional diagram of the electronic device **10** of FIG. **1**, according to embodiments of the present disclosure. As illustrated, the processor **12**, the memory **14**, the transceiver **30**, the transmitter **52**, the receiver **54**, and/or the antennas **55** (illustrated as **55A-55N**, collectively an antenna **55**) may be communicatively coupled directly or indirectly (e.g., through or via another component, a communication bus, a network) to one another to transmit and/or receive data between one another.

[0034] The electronic device **10** may include the transmitter **52** and/or the receiver **54** that respectively enable transmission and reception of data between the electronic device **10** and a remote location via, for example, a network or direction connection associated with the electronic device **10** and an external transceiver (e.g., in the form of a cell, eNB (E-UTRAN Node B or Evolved Node B), base stations, and the like. As illustrated, the transmitter **52** and the receiver **54** may be combined into the transceiver **30**. The electronic device **10** may also have one or more antennas **55A-55N** electrically coupled to the transceiver **30**. The antennas **55A-55N** may be configured in an omnidirectional or directional configuration, in a single-beam, dual-beam, or multi-beam arrangement, and so on. Each antenna **55** may be associated with a one or more beams and various configurations. In some embodiments, multiple antennas of the antennas **55A-55N** of an antenna group or module may be communicatively coupled a respective transceiver **30** and each emit radio frequency signals that may constructively and/or destructively combine to form a beam. The electronic device **10** may include multiple transmitters, multiple receivers, multiple transceivers, and/or multiple antennas as suitable for various communication standards.

[0035] The transmitter **52** may wirelessly transmit packets having different packet types or functions. For example, the transmitter **52** may transmit packets of different types generated by the processor **12**. The receiver **54** may wirelessly receive packets having different packet types. In some examples, the receiver **54** may detect a type of a packet used and process the packet accordingly. In some embodiments, the transmitter **52** and the receiver **54** may transmit and receive information via other wired or wireline systems or means.

[0036] As illustrated, the various components of the electronic device **10** may be coupled together by a bus system **56**. The bus system **56** may include a data bus, for example, as well as a power bus, a control signal bus, and a status signal bus, in addition to the data bus. The components of the electronic device **10** may be coupled together or accept or provide inputs to each other using some other mechanism.

[0037] FIG. **3** is a schematic diagram of the transmitter **52** (e.g., transmit circuitry), according to embodiments of the present disclosure. As illustrated, the transmitter **52** may receive outgoing data **60** in the form of a digital signal to be transmitted via the one or more antennas **55**. A digital-to-analog converter (DAC) **62** of the transmitter **52** may convert the digital signal to an analog signal,

and a modulator **64** may combine the converted analog signal with a carrier signal to generate a radio wave. A power amplifier (PA) **66** receives the modulated signal from the modulator **64**. The power amplifier **66** may amplify the modulated signal to a suitable level to drive transmission of the signal via the one or more antennas **55**. A filter **68** (e.g., filter circuitry and/or software) of the transmitter **52** may then remove undesirable noise from the amplified signal to generate transmitted data **70** to be transmitted via the one or more antennas **55**. The filter **68** may include any suitable filter or filters to remove the undesirable noise from the amplified signal, such as a bandpass filter, a bandstop filter, a low pass filter, a high pass filter, and/or a decimation filter. Additionally, the transmitter **52** may include any suitable additional components not shown, or may not include certain of the illustrated components, such that the transmitter **52** may transmit the outgoing data **60** via the one or more antennas **55**. For example, the transmitter **52** may include a mixer and/or a digital up converter. As another example, the transmitter **52** may not include the filter **68** if the power amplifier **66** outputs the amplified signal in or approximately in a desired frequency range (such that filtering of the amplified signal may be unnecessary).

[0038] FIG. **4** is a schematic diagram of the receiver **54** (e.g., receive circuitry), according to embodiments of the present disclosure. As illustrated, the receiver **54** may receive received data **80** from the one or more antennas **55** in the form of an analog signal. A low noise amplifier (LNA) **82** may amplify the received analog signal to a suitable level for the receiver **54** to process. A filter **84** (e.g., filter circuitry and/or software) may remove undesired noise from the received signal, such as cross-channel interference. The filter **84** may also remove additional signals received by the one or more antennas **55** which are at frequencies other than the desired signal. The filter **84** may include any suitable filter or filters to remove the undesired noise or signals from the received signal, such as a bandpass filter, a bandstop filter, a low pass filter, a high pass filter, and/or a decimation filter. A demodulator **86** may remove a radio frequency envelope and/or extract a demodulated signal from the filtered signal for processing. An analog-to-digital converter (ADC) **88** may receive the demodulated analog signal and convert the signal to a digital signal of incoming data **90** to be further processed by the electronic device **10**. Additionally, the receiver **54** may include any suitable additional components not shown, or may not include certain of the illustrated components, such that the receiver **54** may receive the received data **80** via the one or more antennas **55**. For example, the receiver **54** may include a mixer and/or a digital down converter.

[0039] As discussed above, the electronic device **10** may include one or more antennas **55** that may receive cellular signals and/or satellite signals in multiple frequency bands. A global navigation satellite signal (GNSS) signal may be transmitted by a GNSS satellite in an L1 frequency bands (e.g., 1575.42 MHz) and L5 frequency bands (e.g., 1,176.45 MHz) and be received by the shared one or more antennas. In some cases, the shared one or more antennas are tuned to a cellular frequency and the GNSS signals in some/all frequency bands may be severely attenuated as a result of antenna tuning operations corresponding to cellular connected modes (e.g., Voice over Long-Term Evolution (VoLTE) calls, video streaming) and/or cellular paging operations. That is, the GNSS signals may have signal quality values below a GNSS receiver' acquisition and/or tracking threshold signal quality values (e.g., signal quality values used to determine a location of the electronic device **10**). Thus, GNSS processing may be unnecessary and result in unneeded power expenditure without any user benefit.

[0040] With the foregoing in mind, FIG. **5** is a schematic diagram of communication circuitry **100** of the electronic device **10**, according to embodiments of the present disclosure. The electronic device **10** may include a LEO transceiver **102** that enables sending and receiving LEO signals, a cellular transceiver **104** that enables sending and receiving cellular signals, a GNSS L1 receiver **106** that enables receiving GNSS signals on the L1 band, and a GNSS L5 receiver **108** that enables receiving GNSS signals on the L5 band. The communication circuitry **100** may include a baseband processor **114** that utilizes radio frequency (RF) control software **110** to control the one or more receivers and transceivers and an antenna tuner **112** based on one or more tune requests received at

the baseband processor **114**. The baseband processor **114** may be in the form of the processor **12** described above.

[0041] The GNSS L1 receiver **108** and the GNSS L5 receiver **106** may include the components of the receiver **54** discussed in FIG. **4** to receive GNSS L1 band signals and GNSS L5 band signals, respectively. The cellular transceiver **104** may include the components of the transceiver **30** described in FIG. **2**, including those of the transmitter **52** and the receiver **54** of FIGS. **3** and **4**, to transmit and receive cellular signals. The LEO transceiver **102** may also include the components of the transceiver described in FIG. **2**, including those of the transmitter **52** and the receiver **54** of FIGS. **3** and **4**, to transmit and receive LEO satellite signals. The receivers **106**, **108** and the transceivers **102**, **104** described above may be coupled to one or more antenna tuners **112** (collectively an antenna tuner **112**). The baseband processor **114** may send one or more control signals to the antenna tuner **112** to cause the antenna tuner **112** to tune a resonant frequency of the one or more antennas **55** to send or receive signals efficiently at a desired frequency. The antenna tuner **112** may include any suitable device that may tune the frequency of the one or more antennas **55** to a desired frequency, such as an aperture tuner, an impedance tuner, and so on. The baseband processor **114** may include or execute RF control software **110** that may receive and/or process tune requests (e.g., a cellular tune request **118**, a GNSS tune request **120**, and a LEO tune request **122**) and determine and/or send control instructions to the antenna tuner **112**, the transceivers **102**, **104**, and/or the receivers **106**, **108** based on the received tune requests.

[0042] For example, the baseband processor **114** may receive a cellular tune request **118** and a GNSS tune request **120** (e.g., from an application processor, such as the processor **12**) along with additional information regarding the tune request (e.g., duration information, cellular operation information). The RF control software **110** may determine that the cellular tune request **118** is for a cellular operation (e.g., Voice over Long-Term Evolution (VOLTE), video streaming) based on the tune request information. Performing the cellular operation may cause GNSS signals received at the shared antenna **55** to be severely attenuated. If in operation, the GNSS L1 and L5 receivers **108**, **106** may expend excessive power in an effort to process the attenuated GNSS signals. Accordingly, the RF control software **110** may deactivate or blank (e.g., replace the received GNSS signals with “dummy” signals, such as a signals having only zeroes) the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106** when operating the cellular transceiver **104** (e.g., as indicated by receiving the cellular tune request **118**). In some embodiments, the RF control software **110** may determine a cellular frequency for the cellular tune request **118**, and determine whether the cellular frequency interferes with GNSS L1 and/or GNSS L5 band signals. If so, the RF control software **110** may deactivate or blank the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106** when operating the cellular transceiver **104**. The RF control software **110** may cause the antenna tuner **112** to tune to a desired cellular frequency and cause the cellular transceiver **104** to send or receive cellular signals over the desired cellular frequency when operating the cellular transceiver **104**. The RF control software **110** may also cause the antenna tuner **112** to tune to a desired L1 and/or L5 frequency and cause the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106** to receive GNSS signals when operating the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106**. The RF control software **110** may thus operate the antenna tuner **112**, the cellular transceiver **104**, and/or the GNSS L1 receiver **108**, the GNSS L5 receiver **106** based on tune requests received at the baseband processor **114**. In particular, the RF control software **110** may send instructions to these components to deactivate the components, activate the components, blank signals received by the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106**, or the like.

[0043] In some embodiments, the baseband processor **114** may receive a cellular tune request **118**, but no GNSS tune request **120**. Therefore, the baseband processor **114** may utilize the RF control software **110** to cause the antenna tuner **112** to tune to a desired cellular frequency and cause the cellular transceiver **104** to send or receive cellular signals over the desired cellular frequency, but would not cause the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106** to receive GNSS

signals, because no GNSS tune request **120** was received at the baseband processor **114**, and therefore no processing of the GNSS signals is required. In some embodiments, one or more of the receivers **106**, **108** and transceivers **102**, **104** shown in FIG. 5 may not be included in the communication circuitry **100**. For example, in one embodiment, the communication circuitry **100** may include only the cellular transceiver **104** and a single GNSS receiver (e.g., either the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106**). In another embodiment, the communication circuitry **100** may include only the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106** and the LEO transceiver **102**. That is, it should be understood that the communication circuitry **100** may include any combination of the receiver **106**, **108** and transceiver **102**, **104** components depicted in FIG. 5.

[0044] Based on the foregoing, FIG. 6 is a flowchart of a method **130** for tuning an antenna **55** shared by the cellular transceiver **104** and a GNSS receiver (e.g., **106**, **108**) as shown in FIG. 6, according to an embodiment of the present disclosure. Any suitable device (e.g., a controller) that may control components of the electronic device **10**, such as the processor **12** (e.g., the baseband processor **114**), may perform the method **130**. In some embodiments, the method **130** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the memory **14** or storage **16**, using the processor **12**. For example, the method **130** may be performed at least in part by one or more software components, such as an operating system of the electronic device **10**, one or more software applications of the electronic device **10**, and the like. As a specific example, the method **130** may be performed at least in part by the processor **12** executing the RF control software **110**. While the method **130** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0045] In process block **132**, the processor **12** receives a GNSS tune request **120** for antenna tuning of the shared antenna **55** (e.g., an antenna that is capable of receiving at least GNSS signals and cellular signals) to an L1 band frequency (e.g., 1575.42 MHz) and/or an L5 band frequency (e.g., 1176.45 MHz). In particular, the processor **12**, in the form of the baseband processor **114**, may receive the GNSS tune request **120** from an application processor of the electronic device **10**. In some embodiments, the processor **12** may determine a frequency or frequency band (e.g., the L1 band or the L5 band) for receiving GNSS signals based on the GNSS tune request **120**.

[0046] In process block **134**, the processor **12** tunes the shared antenna **55** to the GNSS L1 band or L5 band frequency. The processor **12** may also activate (e.g., turn on) the GNSS L1 receiver **108** and/or the GNSS L5 receiver, such that the GNSS L1 receiver **108** and/or GNSS L5 receiver may receive and/or process GNSS signals (e.g., from a GNSS satellite).

[0047] In process block **136**, the processor **12** receives a cellular tune request **118** for antenna tuning of the shared antenna (e.g., to a specified cellular frequency). In particular, the processor **12** may receive the cellular tune request **118** from an application processor of the electronic device **10**. In some embodiments, the processor **12** may determine a cellular frequency for the cellular tune request **118**, and determine whether the cellular frequency interferes with GNSS L1 and/or GNSS L5 band signals. For example, the processor **12** may determine, based on the cellular frequency associated with the cellular tune request, that the cellular frequency would severely attenuate the L1 band signals received at the shared antenna. That is, the processor may determine that a signal quality of the attenuated GNSS L1 band signal is below GNSS L1 receiver **108** acquisition and/or tracking threshold values.

[0048] In process block **138**, the processor **12** tunes the shared antenna **55** to the specified cellular frequency and enables the cellular transceiver **104**. The processor **12** may also deactivate or blank the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106**, for example, based on the determined signal interference. That is, the processor **12** may determine to deactivate or blank the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106** based on the cellular tune request information (e.g.,

type of cellular request, duration of request).

[0049] In this manner, unnecessary power output due to processing attenuated GNSS signals received by the GNSS L1 receiver **108** and/or the GNSS L5 receiver **106** may be mitigated by deactivating and/or blanking the GNSS L1 receiver **108** and/or GNSS L5 receiver **106** when tuning the shared antenna **55** to perform cellular tune requests **118**.

[0050] With the foregoing in mind, FIG. 7 is a flowchart of method **140** for tuning an antenna **55** shared by the cellular transceiver **104** and the GNSS receiver (e.g., **106**, **108**) as shown in FIG. 5 based on a cellular operation, according to an embodiment of the present disclosure. Any suitable device (e.g., a controller) that may control components of the electronic device **10**, such as the processor **12** (e.g., baseband processor **114**), may perform the method **140**. In some embodiments, the method **140** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the memory **14** or storage **16**, using the processor **12**. For example, the method **140** may be performed at least in part by one or more software components, such as an operating system of the electronic device **10**, one or more software applications of the electronic device **10**, and the like. As a specific example, the method **140** may be performed at least in part by the processor **12** executing the RF control software **110**. While the method **140** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0051] In process block **142**, the processor **12** receives a cellular tune request **118** for antenna tuning of the shared antenna **55** (e.g., an antenna that is capable of receiving at least GNSS signals and cellular signals) to a cellular frequency. In particular, the processor **12**, in the form of the baseband processor **114**, may receive the cellular tune request **118** from an application processor of the electronic device **10**. In some embodiments, the processor **12** may determine the cellular frequency or frequency band based on the cellular tune request **118**.

[0052] In decision block **144**, the processor **12** determines whether the cellular tune request **118** corresponds to a paging operation. For example, when the electronic device **10** is in a cellular idle state (e.g., performing GNSS operations), the cellular transceiver **104** may perform periodic paging operations on a cadence of every few seconds (e.g., 1.28 sec) to monitor for paging messages from base stations or cellular network operators to determine whether there is incoming data from the cellular network. These periodic paging operations may result in periodic detuning of the GNSS receivers **106**, **108** at the shared antenna **55** for a short duration (e.g., 1-10 ms).

[0053] If the processor **12** determines that the request is a paging operation, the processor **12**, at process block **146**, blanks the GNSS L1 receiver **108** and/or GNSS L5 **106** receiver. In some embodiments, the processor **12** blanks the GNSS L1 receiver **108** and/or GNSS L5 receiver **106** based on determining whether the cellular frequency interferes with the GNSS frequency (e.g., the L1 band and/or the L5 band). In particular, the processor **12** may blank a GNSS receiver **106**, **108** by replacing received GNSS signals with “dummy” signals, such as “zeroing out” the signals by replacing the GNSS L1 receiver **108** and/or GNSS L5 receiver **106** with signals having only zeroes. As such, the GNSS signals may be processed by a GNSS receiver **106**, **108** with little or no additional power output from RF and/or digital components of the GNSS receiver **106**, **108**.

[0054] If the processor **12** determines, at process block **148**, that the cellular tune request **118** is not a paging operation (e.g., that the cellular tune request **118** corresponds to a long duration cellular operation), the processor **12** deactivates the GNSS L1 receiver **108** and/or the GNSS L5 **106** receiver. It should be understood that the paging operation is an example of a short duration cellular operation, and any suitable operation may be substituted for or added to the paging operation. For example, the paging operation may be substituted with any cellular operation that takes at least 2 seconds to complete, 1 second to complete, 100 ms to complete, 10 ms to complete, 5 ms to complete, 1 ms to complete, 0.5 ms to complete, and so on.

[0055] At process block **150**, the processor **12** enables the cellular transceiver **104** to send and/or

receive and/or process the cellular signals received by the shared antenna **55**. Blanking a GNSS receiver **106**, **108** based on short duration cellular operations (e.g., the paging operation) may prevent latency and excess power output in the GNSS receiver **106**, **108** during short duration cellular tune requests.

[0056] In some embodiments, a first cellular tune request **118** may be received, the corresponding cellular operation may be completed, and then, after a short time duration (e.g., greater than 1 picosecond, greater than 1 nanosecond, greater than 1 ms, between 1 ms and 10 seconds), a second cellular tune request **118** may be received again at the processor **12** after the short duration. In some cases, a GNSS tune request **120** may be received by the processor **12** during performance of the first cellular tune request **118** (e.g., and thus may be queued) or during the short duration (e.g., when no cellular tune request **118** is received). This may result in the shared antenna **55** being tuned to the GNSS frequency and activation of the GNSS receivers **106**, **108** for the short duration, only to have to disable the GNSS receivers **106**, **108**, after the short duration due to the second cellular tune request **118**. Unnecessary or excessive power may be output due to activating and deactivating the GNSS receivers **106**, **108** for such short time periods over the short time durations.

[0057] Based on the discussions above, FIG. **8** is a flowchart of a method **160** for tuning an antenna **55** shared by the cellular transceiver **104** and the GNSS receiver **106**, **108** of FIG. **5** by delaying tuning to the GNSS receiver **106**, **108**, according to an embodiment of the present disclosure. Any suitable device (e.g., a controller) that may control components of the electronic device **10**, such as the processor **12** (e.g., baseband processor **114**), may perform the method **160**. In some embodiments, the method **160** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the memory **14** or storage **16**, using the processor **12**. For example, the method **160** may be performed at least in part by one or more software components, such as an operating system of the electronic device **10**, one or more software applications of the electronic device **10**, and the like. As a specific example, the method **160** may be performed at least in part by the processor **12** executing the RF control software **110**. While the method **160** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0058] In process block **162**, the processor **12** receives a GNSS tune request **120** for antenna tuning of the shared antenna **55** (e.g., an antenna that is capable of receiving at least GNSS signals and cellular signals) to the L1 band frequency (e.g., 1575.42 MHz) and/or L5 band frequency (e.g., 1,176.45 MHz) and concurrently receives a cellular tune request **118** for shared antenna tuning to a cellular frequency. In particular, the processor **12**, in the form of the baseband processor **114**, may receive the cellular tune request **118** and the GNSS tune request **120** from an application processor of the electronic device **12**. In some embodiments, the processor **12** may determine the cellular frequency or frequency band based on the cellular tune request **118**.

[0059] In process block **164**, the processor **12** tunes the one or more shared antennas **55** of the communication circuitry **100** to the cellular frequency. In some embodiments, the processor **12** may also blank and/or deactivate the GNSS L1 receiver **108** and/or GNSS L5 receiver based on determining whether the cellular frequency interferes with the GNSS frequency (e.g., the L1 band and/or the L5 band).

[0060] In decision block **166**, the processor **12** determines if the cellular tune request **118** has stopped (e.g., whether a cellular operation associated with the cellular tune request **118** has been completed) or if the cellular tune request **118** has continued. If the processor **12** continues to receive the cellular tune request **118** from an application processor of the electronic device **10**, the processor **12**, at process block **164**, continues to tune the shared antenna **55** to the cellular frequency.

[0061] If the processor **12** determines that the cellular tune request **118** has stopped, in decision

block **168**, the processor **12** determines if an additional cellular tune request **118** has been received. If the processor **12** determines that an additional cellular tune request **118** has been received, at process block **164**, the processor **12** tunes the shared antenna **55** to the cellular frequency that corresponds to the additional cellular tune request **118**.

[0062] If the processor **12** determines that no additional cellular tune request **118** has been received, at decision block **170**, the processor **12** determines if a specified delay time period has elapsed. The delay time period to any suitable time period that may avoid unnecessary and/or excessive power output due to activating and deactivating the cellular transceiver **104** and/or the GNSS receiver **106**, **108** during the time period, such as the time for cellular paging (e.g., between 1 ms and 10 ms). The delay time period may also be determined by the quality of GNSS L1 signals and/or GNSS L5 signals received at the shared one or more antennas **55**. For example, the cellular tune frequency may not cause interference and result in a degraded signal for both the GNSS L1 band signal and the GNSS L5 band signal. In this case, since both signals are generally unaffected by the shared antenna **55** tuning to the cellular frequency, the delay time period may be extended because the GNSS signals may still be processed and location of the electronic device **10** determined during cellular tuning operations. In another case, both the GNSS L1 signal and the GNSS L5 signal may be degraded due to the cellular tune frequency at the shared antenna **55**. In this case the delay time period may be shorter, such that the location of the electronic device **10** may be obtained more rapidly during cases where cellular tuning is not necessary.

[0063] If the processor **12** determines that the delay period of time has not elapsed without an additional cellular tune request **118** being received, at decision block **168**, the processor **12** continues to monitor if an additional cellular tune request **118** has been received by the processor **12**. If the processor **12** determines that the delay period of time has elapsed without an additional cellular tune request **118** being received, the processor **12**, at process block **172**, tunes the shared antenna **55** to the GNSS frequency and activates and/or enables the GNSS L1 receiver **108** and/or GNSS L5 **106** receiver.

[0064] The method **160** may be implemented to mitigate unnecessary tuning and/or activation of the GNSS receiver **106**, **108** for short durations. For example, the electronic device **10** may be utilized to stream music via cellular operation and provide route directions via GNSS operation. As such, the electronic device **10** may tune the shared antenna **55** according to the cellular tune request **118** to stream music on the electronic device **10**. The electronic device **10** may stop transmitting the cellular tune request **118** during short time periods, such as when a user of the electronic device **10** may be selecting an additional song, and may resume streaming music after the short time period. To prevent unnecessary tuning of the shared antenna **55** to a GNSS frequency during the short time period, only to return to tuning to a cellular frequency after the short time period and mitigate unnecessary power output for short term activation and deactivation of the GNSS L1 receiver **108** and/or GNSS L5 receiver **106**, the electronic device **10** may implement the delay period for shared antenna tuning.

[0065] As mentioned above, the electronic devices **10** may receive low earth orbit (LEO) satellite signals on a LEO satellite transmit frequency band (e.g., 1610-1618.725 megahertz (MHz)) that may interfere with the L1 band for GNSS signal reception. This may result in interference with the GNSS signals received by one or more antennas **55** tuned to the L1 band. Additionally, governmental bodies and other regulatory bodies may implement restrictions on LEO satellite communication according to certain geographical areas, such as requiring that the electronic device **10** deactivate a LEO transceiver **102** and halt LEO satellite communication in the certain geographical areas.

[0066] With the foregoing in mind, FIG. **9** is a flowchart of method **180** for tuning an antenna shared by a Low Orbit Satellite (LEO) transceiver **102** and a GNSS receiver **106**, **108** as shown in FIG. **5**, according to an embodiment of the present disclosure. Any suitable device (e.g., a controller) that may control components of the electronic device **10**, such as the processor **12** (e.g.,

baseband processor **114**), may perform the method **180**. In some embodiments, the method **180** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the memory **14** or storage **16**, using the processor **12**. For example, the method **180** may be performed at least in part by one or more software components, such as an operating system of the electronic device **10**, one or more software applications of the electronic device **10**, and the like. As a specific example, the method **180** may be performed at least in part by the processor **12** executing the RF control software **110**. While the method **180** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0067] In process block **182**, the processor **12** receives a LEO satellite tune request **122** for antenna tuning of the one or more antenna **55** (e.g., an antenna that is capable of receiving at least LEO signals) to a LEO satellite frequency (e.g., 2483.5-2500 MHZ). In particular, the processor **12**, in the form of the baseband processor **114**, may receive the LEO satellite tune request **122** from an application processor of the electronic device **10**. Additionally, in response to receiving the LEO satellite tune request **122**, the processor **12** may receive GNSS signals via the one or more antennas **55** tuned to the GNSS L1 band and/or the GNSS L5 band, to determine an initial time and local oscillator frequency offset for acquiring the LEO satellite signal.

[0068] In process block **184**, the processor **12** blanks the GNSS L1 receiver **108** (e.g., in response to receiving LEO satellite tune request **122**). The GNSS L1 receiver **108** may be blanked to mitigate receiving and/or processing degraded GNSS L1 signals resulting from high power LEO satellite transmissions causing interference with the L1 band for GNSS signal reception. That is, the processor **12** may replace the GNSS L1 signals with a dummy signal (e.g., zeroes), such that the GNSS L1 receiver **108** receives the dummy signal instead of the degraded GNSS L1 signals. In some embodiments, the processor **12** may deactivate or turn off the GNSS L1 receiver **108** instead of blanking the GNSS L1 receiver **108**. In process block **186**, the processor **12** enables and/or activates the LEO transceiver **102** to receive the LEO satellite signals.

[0069] In process block **188**, the processor **12** may enable and/or activate the GNSS L5 receiver **106** to allow for GNSS signal processing for the electronic device **10**. In some embodiments, the processor **12** may send instructions to a secondary device (e.g., a smartphone, a smartwatch, a laptop, a tablet, and so on) associated with or communicatively coupled to the electronic device **10** to cause a GNSS receiver of the secondary device to receive GNSS signals and transmit the GNSS signals to the electronic device **10**. Additionally, the electronic device **10** may transmit the initial time and local oscillator frequency offset calculated based on the GNSS signals to the LEO satellite. The LEO satellite may utilize the initial time and local oscillator frequency offset to progressively degrade time and frequency uncertainties based on clock stability parameters. In some embodiments, the GNSS L5 receiver **106** may receive GNSS signals on the L5 frequency band on a first set of antennas of the one or more antennas **55**, the GNSS L1 receiver **108** may receive GNSS signals on the L1 frequency band on a second set of antennas of the one or more antennas **55**, and the LEO transceiver **102** may send and receive LEO satellite signals on a third set of antennas of the one or more antennas **55**, where the first set, second set, and third set of antennas include different antennas. However, in some embodiments, the second set of antennas used to receive the GNSS signals on the L1 frequency band may be the same as the third set of antennas used to send and receive LEO satellite signals.

[0070] In decision block **190**, the processor **12** determines whether the LEO satellite is out of range (e.g., for communications to be performed with the LEO satellite). In some embodiments, the processor **12** may determine whether a signal received from the LEO satellite is weak, nonexistent, or has a signal quality or power below a threshold signal quality or power. In additional or alternative embodiments, the electronic device **10** may store a map of LEO satellite trajectories, and may determine whether a location of the electronic device **10** (e.g., based on the received

GNSS signals) is not within range of a LEO satellite. If the processor **12** determines that the LEO satellite is out of range, at process block **192**, the processor **12** enables the GNSS L1 receiver **108** based on the LEO satellite no longer transmitting to the electronic device **10**. That is, the processor **12** may stop blanking the GNSS L1 signals or replacing the GNSS L1 signals with a dummy signal (e.g., zeroes), and thus enable the GNSS L1 receiver **108** to receive the GNSS L1 signals. In embodiments where the processor **12** deactivates or turns off the GNSS L1 receiver **108** (e.g., in process block **184**), then the processor **12** may activate or turn on the GNSS L1 receiver **108**. The processor **12** may also deactivate the LEO transceiver **102**. If the processor **12** determines that the LEO satellite is still within a communication range, at process block **188**, the processor **12** continues to enable the GNSS L5 receiver **106** or the GNSS receiver of the secondary device. In this manner the GNSS L1 receiver **108** may avoid unnecessary power output due to processing a noisy GNSS L1 signal caused by LEO satellite communication interference, which may result in a loss of GNSS L1 signal tracking due to degraded signal quality.

[0071] With the foregoing in mind, FIG. **10** is a flowchart of method **200** for deactivating the LEO transceiver **102** of FIG. **5** based on a location of the electronic device of FIG. **1**, according to embodiments of the present disclosure. Any suitable device (e.g., a controller) that may control components of the electronic device **10**, such as the processor **12** (e.g., baseband processor), may perform the method **200**. In some embodiments, the method **200** may be implemented by executing instructions stored in a tangible, non-transitory, computer-readable medium, such as the memory **14** or storage **16**, using the processor **12**. For example, the method **200** may be performed at least in part by one or more software components, such as an operating system of the electronic device **10**, one or more software applications of the electronic device **10**, and the like. As a specific example, the method **200** may be performed at least in part by the processor **12** executing the RF control software **110**. While the method **200** is described using steps in a specific sequence, it should be understood that the present disclosure contemplates that the described steps may be performed in different sequences than the sequence illustrated, and certain described steps may be skipped or not performed altogether.

[0072] In process block **202**, the processor **12** determines an initial location of the electronic device **10**. In particular, the processor **12** may receive GNSS signals using a GNSS receiver **106**, **108**, and determine the initial location of the electronic device **10** based on the received GNSS signals. At process block **204**, the processor **12** enables the LEO transceiver **102** to send and receive LEO satellite signals. In some embodiments, the processor **12** may enable the LEO transceiver **102** after determining that the electronic device **10** is within communication range of the LEO satellite, as described in decision block **190** of method **180** in FIG. **9**. Additionally or alternatively, the processor **12** may determine that LEO satellite communication may be performed by the electronic device **10** according to satellite transmission regulations corresponding to the initial location of the electronic device **10**.

[0073] In process block **206**, the processor **12** determines a distance to one or more geographical areas from the initial location where the LEO transceiver **102** is to be deactivated based on territory and/or country regulations for LEO satellite transmissions. As discussed above, governmental bodies and other regulatory bodies may implement restrictions on LEO satellite communication according to certain geographical areas, such as requiring that the electronic device **10** deactivate a LEO transceiver **102** and halt LEO satellite communication in the certain geographical areas. The processor **12** may store the geographical areas in the memory **14** to track when the electronic device **10** may be approaching a restricted LEO satellite area.

[0074] In decision block **208**, the processor **12** may determine whether the electronic device **10** is within a first threshold distance to the geographical areas where LEO satellite use is restricted. That is, the processor **12** may determine a shortest distance that the electronic device **10** is to a restricted LEO satellite area, and determine whether that distance is within the first threshold distance. In particular, the processor **12** may utilize GNSS L5 signals due to LEO satellite transmission signal

interferences with the GNSS L1 band. During operation of the LEO transceiver **102**, the GNSS L5 receiver **106** may be enabled initially to determine location information. The first threshold distance may include any suitable distance that may be indicative of the electronic device **10** being sufficiently close enough to a restricted LEO satellite area to warrant regular checking or tracking the electronic device **10** to see if the electronic device **10** has entered the restricted LEO satellite area. For example, the first threshold distance may be greater than 100 meters (m), 200 m, 500 m, 1 kilometer (km), 2 km, 5 km, 10 km, and so on. During LEO satellite communication, the GNSS L5 receiver **106** may implement a duty cycle (e.g., deactivate GNSS L5 receiver **106** for certain periods of time) to save power after initial location is determined. Duty cycle of the GNSS L5 tracking may be based on time and frequency uncertainty propagation and pull-in range of the LEO satellite transceiver **102**. The stability of the clock (e.g., 1 parts per million (ppm) stable clock) enables a time duration of four minutes to stay within ± 250 microseconds of time uncertainty necessary to maintain L5 tracking capability. The LEO satellite time/frequency lock (e.g., when LEO satellite is tracking) may further increase duration of the duty cycle depending on the LEO satellite capabilities.

[0075] If the processor **12** determines that the LEO satellite is within the first threshold distance to the restricted LEO satellite areas, then, at process block **210**, the processor **12** increases the GNSS L5 tracking duty cycle to a greater frequency and/or increase the frequency of received GNSS signals from the secondary device. This may be to ensure that the electronic device **10** does not enter restricted LEO areas. The increased frequency of the GNSS signals received at the processor **12** may be determined based on the first threshold distance to the restricted LEO satellite area. For example, the frequency of GNSS signals received at the processor **12** may be a frequency less than 1 second (sec), 5 sec, 10 sec, 1 minute (min), 5 min, 10 min, and so on. The frequency determined by the processor **12** may be based on the first threshold distance, such that a greater first threshold distance to the restricted LEO area may result in a lesser frequency (e.g., a determined first threshold distance of 2 km may correspond to a frequency of 10 min and a determined first distance of 200 m corresponds to a frequency interval of 1 min). The first frequency may be any suitable frequency that can receive GNSS signals at intervals that correspond to less than the time estimate to the shortest distance to reach the restricted LEO satellite areas from the first threshold distance. If the processor **12** determines that the electronic device **10** is not within the first threshold distance based on the GNSS signals, at process block **206**, the processor **12** decreases the frequency of the GNSS L5 tracking duty cycle due and/or frequency of received secondary device GNSS signals due to distance to the LEO satellite restricted areas from the electronic device **10** increasing. That is, because the electronic device **10** is not sufficiently close enough to a restricted LEO satellite area to warrant regular checking or tracking the electronic device **10** to see if the electronic device **10** has entered the restricted LEO satellite area, checking or tracking the electronic device **10** may be performed less frequently (e.g., at a lower duty cycle).

[0076] In decision block **212**, the processor **12** determines if the electronic device **10** is within a second threshold distance less than the first distance to the geographical areas where LEO satellite use is restricted. That is, the processor **12** may determine a shortest distance that the electronic device **10** is to a restricted LEO satellite area, and determine whether that distance is within the second threshold distance. The second threshold distance may be less than the first threshold distance, and may include any suitable distance that may be indicative of having to increase the frequency of checking or tracking the electronic device **10** to see if the electronic device **10** has entered the restricted LEO satellite area, as the electronic device **10** is near or sufficiently close to the restricted LEO satellite area. For example, the first threshold distance may be less than 10 km, 5 km, 2 km, 1 km, 500 m, 200 m, 100 m, and so on. If the processor **12** determines that the LEO satellite is within the second threshold distance to the restricted LEO satellite areas the processor **12**, at process block **214**, increases the GNSS L5 tracking duty cycle to a second frequency greater than the first frequency, based on the electronic device **10** approaching the restricted area for LEO

satellite signal communication. As discussed, above the second frequency may be a greater frequency than the first frequency. For example, the second frequency may be a frequency greater than 1 sec, 5 sec, 10 sec, 1 min, 5 min, 10 min, and so on based on the first frequency value determined and the second threshold distance. The second frequency may be any suitable frequency that can enable the processor **12** to receive GNSS signals at intervals that correspond to less than the time estimate to the shortest distance to reach the restricted LEO satellite areas from the second threshold distance. If the processor **12** determines that the electronic device **10** is not within the second threshold distance, at decision block **208**, the processor **12** determines the distance of the electronic device **10** relative to the first threshold (e.g., based on receiving GNSS signals).

[0077] In decision block **216**, the processor **12** determines if the electronic device **10** is within a geographical area where the LEO satellite communication is restricted. If the processor **12** determines that the electronic device **10** is within the restricted area, the processor **12**, at process block **218**, deactivates the LEO transceiver **102**. If the processor **12** determines that the electronic device **10** is not within the within the restricted area, the processor **12** returns to decision block **212** and determines the distance of electronic device **10** relative to the second threshold.

[0078] The method **200** enables the electronic device **10** to monitor the device location relative to geographical areas that restrict LEO satellite access based on regulatory requirements, and increases the frequency of checking the device location using the GNSS L5 receiver **106** to ensure that the electronic device **10** does not enter the geographical areas while the LEO transceiver **102** is active. The method may also reduce unnecessary power output by decreasing the frequency of checking the device location using the GNSS L5 receiver **106** when the electronic device **10** is further away from a restricted area. Additionally, the average duty cycle implemented by the GNSS L5 receiver **106** in the disclosed embodiments may enable between 5 and 15 milliamperes of current draw savings for the electronic device **10**.

[0079] The specific embodiments described above have been shown by way of example, and it should be understood that these embodiments may be susceptible to various modifications and alternative forms. It should be further understood that the claims are not intended to be limited to the particular forms disclosed, but rather to cover all modifications, equivalents, and alternatives falling within the spirit and scope of this disclosure.

[0080] The techniques presented and claimed herein are referenced and applied to material objects and concrete examples of a practical nature that demonstrably improve the present technical field and, as such, are not abstract, intangible or purely theoretical. Further, if any claims appended to the end of this specification contain one or more elements designated as “means for [perform]ing [a function] . . .” or “step for [perform]ing [a function] . . .,” it is intended that such elements are to be interpreted under 35 U.S.C. 112(f). However, for any claims containing elements designated in any other manner, it is intended that such elements are not to be interpreted under 35 U.S.C. 112(f).

Claims

1. (canceled)
2. An electronic device comprising: a cellular transceiver configured to communicate with a satellite; a satellite receiver configured to receive location signals from a satellite network; and processing circuitry configured to receive a request to communicate with the satellite using the cellular transceiver, blank the satellite receiver based on the request, and communicate with the satellite using the cellular transceiver while the satellite receiver is blanked.
3. The electronic device of claim 2, wherein the processing circuitry is configured to receive a second request to communicate with the satellite network using the satellite receiver.
4. The electronic device of claim 3, wherein the processing circuitry is configured to communicate with the satellite network using the satellite receiver based on the second request.

5. The electronic device of claim 2, wherein the satellite comprises a low Earth orbit satellite.
 6. The electronic device of claim 2, wherein the satellite network comprises a global navigation satellite system.
 7. The electronic device of claim 2, comprising one or more antennas coupled to the cellular transceiver and the satellite receiver.
 8. The electronic device of claim 7, wherein the request is associated with tuning the one or more antennas to communicate with the satellite using the cellular transceiver.
 9. A method comprising: receiving a request to communicate with a satellite using a cellular transceiver of an electronic device, blanking a satellite receiver of the electronic device based on the request, and communicating with the satellite using the cellular transceiver while the satellite receiver is blanked.
 10. The method of claim 9, wherein blanking the satellite receiver comprises replacing a signal received by the satellite receiver with a dummy signal.
 11. The method of claim 10, wherein the signal received by the satellite receiver comprises a frequency in an L1 frequency band.
 12. The method of claim 10, wherein the signal received by the satellite receiver comprises a frequency in an L5 frequency band.
 13. The method of claim 9, comprising receiving one or more global navigation satellite system (GNSS) signals from a second electronic device.
 14. The method of claim 13, comprising sending time or frequency information associated with the one or more GNSS signals to the satellite using the cellular transceiver.
 15. The method of claim 9, comprising stopping blanking of the satellite receiver based on an inability to communicate with the satellite.
 16. The method of claim 15, comprising determining the inability to communicate with the satellite based on comparing signal quality or signal power associated with the satellite to a threshold.
 17. One or more tangible, non-transitory, computer-readable media storing instructions that, when executed by processing circuitry, cause the processing circuitry to receive a request to communicate with a satellite using a cellular transceiver of an electronic device, and blank a satellite receiver of the electronic device based on the request, and communicate with the satellite using the cellular transceiver while the satellite receiver is blanked.
 18. The one or more tangible, non-transitory, computer-readable media of claim 17, wherein the instructions cause the processing circuitry to communicate with the satellite using the cellular transceiver by sending or receiving signals having frequencies between 1610 megahertz and 1618.725 megahertz.
 19. The one or more tangible, non-transitory, computer-readable media of claim 17, wherein the instructions cause the processing circuitry to receive a second request to communicate with a satellite network using the satellite receiver.
 20. The one or more tangible, non-transitory, computer-readable media of claim 19, wherein the instructions cause the processing circuitry to communicate with the satellite network using the satellite receiver based on the second request.
 21. The one or more tangible, non-transitory, computer-readable media of claim 19, wherein the instructions cause the processing circuitry to communicate with the satellite network using the satellite receiver by receiving signals having frequencies in an L1 frequency band or an L5 frequency band.
-