

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250255383

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Swigart; John F. et al.

ARTICLE OF FOOTWEAR WITH CLOSURE SYSTEM

Abstract

An article of footwear with an upper, a sole assembly connected to the upper, and a flap coupled to the article of footwear proximate the bite line. The article of footwear includes a closure system comprising a lace configured to engage the flap. The closure system is adjustable to secure the flap to the upper or to release the flap from the upper.

Inventors: Swigart; John F. (Plymouth, MA), Teeter; Paul O. (Pembroke, MA)

Applicant: Acushnet Company (Fairhaven, MA)

Family ID: 1000008571843

Assignee: Acushnet Company (Fairhaven, MA)

Appl. No.: 19/195770

Filed: May 01, 2025

Related U.S. Application Data

parent US continuation 18503228 20231107 parent-grant-document US 12310458 child US 19195770

parent US continuation 17517274 20211102 parent-grant-document US 11844401 child US 18503228

us-provisional-application US 63115162 20201118

Publication Classification

Int. Cl.: A43C11/16 (20060101); A43C1/00 (20060101); A43C7/02 (20060101); A43C11/00 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a Continuation of U.S. patent application Ser. No. 18/503,228 filed on Nov. 7, 2023, which is a Continuation of U.S. patent application Ser. No. 17/517,274 filed on Nov. 2, 2021 (issued as U.S. Pat. No. 11,844,401), which claims the benefit of and priority to U.S. Provisional Patent Application No. 63/115,162 filed on Nov. 18, 2020, each of which is incorporated herein by reference in its entirety for all purposes.

FIELD OF THE DISCLOSURE

[0002] The disclosure relates generally to the field of footwear. More specifically, the disclosure relates to the field of footwear with a closure system and a flap for stability.

SUMMARY

[0003] The following presents a summary of the disclosure in order to provide a basic understanding of some aspects of the disclosure. This summary is not an extensive overview of the disclosure. It is not intended to identify critical elements of the disclosure or to delineate the scope of the disclosure. Its sole purpose is to present some concepts of the disclosure in a simplified form as a prelude to the more detailed description that is presented elsewhere.

[0004] In one embodiment, an article of footwear may comprise a flexible upper, a sole having an outsole and a midsole, a bite line, a heel region, and a forefoot region. The article of footwear may have a medial side extending from the forefoot region to the heel region. The article of footwear may have a lateral side extending from the forefoot region to the heel region, the lateral side being opposite to and generally parallel the medial side. The article of footwear may further have a closure system for securing the article of footwear which may be tightened and loosened. The article of footwear may further comprise at least one flap coupled to the article of footwear proximate the bite line. The closure system may be configured to interact with the flap, and, when tightened, the closure system may be configured to secure the flap to the upper.

[0005] In another embodiment, an article of footwear may comprise a flexible upper, a sole having an outsole and a midsole, a bite line, a heel region, and a forefoot region. The article of footwear may have a medial side extending from the forefoot region to the heel region. The article of footwear may have a lateral side extending from the forefoot region to the heel region, the lateral side being opposite to and generally parallel the medial side. The article of footwear may further comprise a closure system having laces and lace guides, wherein the laces are threaded through at least one lace guide located proximate the bite line. The article of footwear may further comprise at least one flap coupled to the article of footwear proximate the bite line.

[0006] In yet another embodiment, an article of footwear may comprise a flexible upper, a sole having an outsole and a midsole, a bite line, a heel region, and a forefoot region. The article of footwear may have a medial side extending from the forefoot region to the heel region. The article of footwear may have a lateral side extending from the forefoot region to the heel region, the lateral side being opposite to and generally parallel the medial side. The article of footwear may further comprise an adjustable closure system and a flap. The flap may have a forefoot end, a heel end, and an uppermost point. The flap may be coupled to the article of footwear proximate the bite line. The flap may be variable between an engaged position and a relaxed position. In the engaged position, the flap may provide lateral support to a midfoot region of the article of footwear.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Illustrative embodiments of the present disclosure are described in detail below with reference to the attached drawing and figures, wherein:

[0008] FIG. **1** is a side view of an article of footwear according to one embodiment;

[0009] FIG. **2** is a side view of the article of footwear according to another embodiment;

[0010] FIG. **3** is a side view of the article of footwear according to another embodiment;

[0011] FIG. **4** is a side view of the article of footwear according to another embodiment;

[0012] FIG. **5** is a bottom view of the article of footwear according to one embodiment;

[0013] FIG. **6** is a side view of the article of footwear according to one embodiment;

[0014] FIG. **7** is a side view of the article of footwear according to another embodiment;

[0015] FIG. **8** is a top perspective view of the article of footwear according to one embodiment;

[0016] FIG. **9** is a top perspective view of the article of footwear according to another embodiment;

[0017] FIG. **10** is a rear view of the article of footwear according to one embodiment; and

[0018] FIG. **11** is a perspective view of the article of footwear according to one embodiment.

DETAILED DESCRIPTION

[0019] The present invention now will be described more fully in reference to the accompanying figures, in which embodiments of the invention are shown. However, this invention should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. In the drawings, like numbers refer to like elements throughout. Thicknesses and dimensions of some components may be exaggerated for clarity.

[0020] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

[0021] It will be understood that when an element is referred to as being “attached,” “coupled” or “connected” to another element, it can be directly attached, coupled or connected to the other element or intervening elements may also be present. In contrast, when an element is referred to as being “directly attached,” “directly coupled” or “directly connected” to another element, there are no intervening elements present.

[0022] It is noted that any one or more aspects or features described with respect to one embodiment may be incorporated in a different embodiment although not specifically described relative thereto. That is, all embodiments and/or features of any embodiment can be combined in any way and/or combination. Applicant reserves the right to change any originally filed claim or file any new claims accordingly, including the right to be able to amend any originally filed claim to depend from and/or incorporate any feature of any other claim although not originally claimed in that manner. These and other objects and/or aspects of the present invention are explained in detail in the specification set forth below.

[0023] An article of footwear **10** is shown in FIGS. **1-10** and includes a flexible upper **100** and a sole **110**. As shown in FIG. **1**, the article of footwear **10** may further include a heel region **130**, a forefoot region **140**, a closure system **150**, and a flap **160**.

[0024] The heel region **130** may generally correspond with the rear portions of a foot, namely, the area surrounding and below the Achilles tendon, the posterior of the heel, and the talus and calcaneus bones. A forefoot region **140** may generally correspond with a front of a foot, namely, the toes and metatarsal, phalange, and sesamoid bones. A midfoot region **135** may generally correspond with a middle of the foot, namely, the arch and the navicular, cuboid, and cuneiform bones. It is understood that the heel region **130**, midfoot region **135**, and forefoot region **140** are

intended to represent general areas of footwear and not demarcate precise areas.

[0025] The article of footwear **10** may have a medial side that extends from a forefoot region **140** to a heel region **130** and a lateral side that extends from a forefoot region **140** to a heel region **130**. The lateral side and the medial side may be opposite one another. In some embodiments, the lateral side and medial side may be generally parallel to one another. The lateral side may generally correspond to an outside area of a foot and a surface that faces away from a user's other foot. The medial side may generally correspond with an inside area of a foot and a surface that faces toward a user's other foot.

[0026] The upper **100** may have an interior surface **102** and an exterior surface **104**. The interior surface **102** may partially define an area configured to receive a user's foot. The upper **100** may be configured to extend over a user's foot, along the medial and lateral sides of the foot, and around a forefoot region and a heel region of the foot. The area configured to receive a user's foot may be accessed from an ankle opening defined by a collar **106**.

[0027] The upper **100** may be constructed from any appropriate material now known or later developed, including, but not limited to, leather, suede, fabric, canvas, weaves, knits, man-made polymer fibers, nylon, polyester, or cotton. The upper **100** may be elastic. Alternately, at least a portion of the upper **100** may be elastic. In other embodiments, the upper **100** may be inelastic. The upper **100** at least a portion that is inflexible and is rigid or semi-rigid.

[0028] The upper **100** may further include a heel counter **132** at the heel region **130**. The heel counter **132** may reinforce the upper **100** and limit movement of a user's heel. The heel counter **132** may wrap around the heel region **130** and extend forward along both the lateral side and the medial side.

[0029] The sole **110** may include an outsole **112**, a midsole **114**, and an insole **116**. The sole **110** may be coupled to the upper **100** at a bite line **105**. The sole **110** may be configured to attenuate forces or provide support or cushioning. In some embodiments, the midsole **114** may be formed from a compressible material that provides cushioning. In other embodiments, the midsole **114** may comprise plates or be formed from dense materials to increase stability.

[0030] The outsole **112** may be below the midsole **114** and may be designed to interact with a ground surface. The outsole **112** may be designed to impart traction. In some embodiments, spikes, cleats, or other devices for additional traction may be coupled to the outsole **112**. Such devices may be releasably coupled to the outsole **112**. In other embodiments, such devices may be fixedly coupled to the outsole **112**. In some embodiments the outsole **112** may be comprised of multiple pads or ridges, as is shown in FIG. 5.

[0031] The insole **116** may be designed to provide cushioning or comfort for a user. The insole **116** may be removable and may be above the midsole **114** when in use. In some embodiments, the insole **116** may be designed to provide support. The insole **116** may be flexible, semi-rigid, or rigid.

[0032] The article of footwear **10** may include a closure system **150**. The closure system **150** may be any appropriate closure system known in the art or later developed. In one embodiment, the closure system **150** may include shoelaces for securing the upper **100** around a user's foot. In other embodiments the closure system **150** may further include at least one elastic gore so that a user can pull the upper **100** proximate a vamp **120** and the collar **106** and enlarge the ankle opening to facilitate placement of a foot within the upper **100** the article of footwear **10**.

[0033] In yet other embodiments, the closure system **150** may include an adjustable lacing system that uses at least one lace **152**, an adjustable dial **154**, and lace guides **156**. For example, the closure system **150** may be a lacing system as described in US Pat No. 10,070,695 and incorporated herein by reference in its entirety. In other embodiments, the closure system **150** does not utilize an adjustable dial **154** to control the tension of the lace **152**, and such tension may be increased or decreased by other means. Increasing the tension may result in a tightening of the lace **152** and decreasing the tension may result in a loosening of the lace **152**. The lace **152** may be secured in any way now known or later developed. In some embodiments, the lace **152** may be secured by

tying ends of the lace **152** to one another.

[0034] The lace **152** may be a tensile lace. In some embodiments, the lace **152** is a wire. When a tension of the lace **152** is increased, the lace **152** may secure the upper **100** around a user's foot. The lace **152** may be selectively adjusted using the adjustable dial **154**. The tension of the lace **152** may be decreased using the adjustable dial **154** to allow a user to place its foot at least partially within the upper **100**. A user may use the adjustable dial **154** to increase tension to the lace **152** in order to tighten the lace **152** and secure the upper **100** around a user's foot.

[0035] The lace guides **156** may be loops that allow the lace **152** to slide through the loop when tension is increased or decreased using the adjustable dial **154**. In some embodiments, the lace guides **156** are low friction. The lace guides **156** may be coupled to the upper **100** at strategic points that enable a user to secure the upper **100** to its foot. The lace guides **156** may be strategically placed such that when tightened the lace **152** does not cause a user discomfort. The placement of the lace guides **156** may assist in stabilizing the foot. In some of the embodiments, the closure system **150** and placement of the lace guides **156** may attenuate forces acting on a user's foot such as pressure, shear force, ground forces, or the ability for flexion or movement.

[0036] As shown in FIGS. **1-4**, in some embodiments the lace **152** may be above the upper **100** and configured to interact with the outer surface of the upper. The lace **152** may be entirely or partially visible. In other embodiments, the lace guides **156** may be placed such that the lace **152** is not in direct contact with the upper **100**.

[0037] In other embodiments, the lace **152** may be between an exterior surface **104** of the upper and an interior surface **102** of the upper. In such embodiments there may be a channel for the laces between the exterior surface **104** of the upper and the interior surface **102** of the upper. The lace guides **156** may also be positioned between the exterior surface **104** of the upper and the interior surface **102** of the upper.

[0038] In some embodiments, a portion of the lace **152** may be between an exterior surface **104** of the upper and an interior surface **102** of the upper, and a portion of the lace **152** may be above an exterior surface **104** of the upper.

[0039] In embodiments where at least a portion of the lace **152** is above an exterior surface **104** of the upper, the upper **100** may optionally have grooves (not shown herein) for facilitating the placement of the lace **152** when the adjustable dial **154** is tightened. The grooves may secure the lace **152** when the adjustable dial **154** is tightened and prevent the lace **152** from slipping or being tightened at an undesired location that may affect forces acting on the article of footwear or a user's foot. The grooves may also provide a reliable position for the lace **152** such that a user would not need to readjust the lace **152**.

[0040] As shown in FIG. **10**, the adjustable dial **154** may be at a rear of the article of footwear **10** at the heel region **130**. In some embodiments, the adjustable dial may be generally halfway between the collar **106** and the bite line **105**. The placement of the adjustable dial **154** at the rear of the article of footwear **10** may be beneficial due to the forces exerted when adjusting the tension of the lace **152**. Placement of the adjustable dial **154** at the heel region **130** may provide increased stability of the article of footwear **10**.

[0041] The placement of the adjustable dial **154** may provide increased stability when downward pressure is applied to the sole **110**. The placement of the adjustable dial **154** may also increase freedom of movement when the downward pressure is lifted. The strategic placement of the lace guides **156** may provide increased stability when downward pressure is applied to the sole **110** and increased freedom of movement when the downward pressure is lifted. In some embodiments, the lace **152** may be crossed in an X pattern proximate the forefoot region. The X pattern configuration may provide greater mechanical advantage. In some embodiments, the combination of the adjustable dial **154** at the heel region **130** and the strategic placement of the lace guides **156** may provide increased stability when downward pressure is applied to the sole and increased freedom of movement when the downward pressure is lifted and/or a forefoot region **140** is flexed. The flexion

in the forefoot region **140** may be a dorsal flexion.

[0042] The lifting of the downward pressure may introduce slack into the lace **152** when there is flexion in the forefoot region **140**. In some embodiments, slack may be introduced without the need to further adjust the tension of the closure system **150**. The tension may thus be automatically adjusted using the lacing configuration such that slack is introduced when there is flexion in the forefoot region **140** and the lace **152** is pulled taut when downward pressure is applied to the sole **110**. Downward pressure applied to the sole **110**, such as when a user plants its foot, may increase the tightness of the laces **152** and thereby further stabilize the article of footwear **10**. The taut laces **152** may engage a flap **160** as further described below, thereby adding stability for a lateral load. This may result in an article of footwear **10** that has increased stability when a user's foot is planted, and increased freedom of motion when the downward pressure is lifted and the forefoot is flexed. Such an article of footwear **10** may be comfortable for a user to walk in or engage in other ambulatory activities, while still providing increased stability when a user's foot is planted.

[0043] In some embodiments, the adjustable dial **154** may be coupled to the upper **100** proximate an eyestay **122**. In other embodiments, the adjustable dial may be coupled to the upper **100** at a quarter of the article of footwear **10**.

[0044] In some embodiments, and as is shown in FIG. **8**, at least one lace guide **156** may be placed proximate the eyestay **122**. In some embodiments, two lace guides **156** may be placed proximate a medial eyestay and one lace guide **156** may be placed proximate a lateral eyestay.

[0045] The lace **152** may be coupled at a first end to the adjustable dial **154** and at a second end to a lace anchor **158**. The lace anchor **158** may be coupled to the article of footwear **10** proximate the bite line **105**. In some embodiments, the lace anchor **158** is fixedly coupled to the article of footwear **10**. In some embodiments, the lace guides **156** may be coupled at the bite line **105** adjacent the flap **160**. In some embodiments, the lace guides **156** and/or lace anchor **158** may be coupled anywhere to the flap **160**. For example, the lace guides **156** and lace anchor **158** may be coupled to the flap **160** at an upper, middle or lower region of the flap. The positions of the lace guides **156** and lace anchor **158** are independent from one another and need not be in the same region.

[0046] The article of footwear **10** may include at least one flap **160**. In some embodiments, each shoe in a pair of shoes may have a flap **160**. The flap **160** may provide a benefit for the user by further stabilizing at least a portion of the footwear **10** to reduce the effects of shear forces during wear. When engaged, the flap **160** produces a cinching action that stabilizes a region of the footwear **10** and distributes the applied pressure over a desired area of the footwear.

[0047] The flap **160** may be rigid or semi-rigid. The amount of stabilization provided by the flap **160** may vary depending on its rigidity, wherein increased rigidity may provide higher stabilization effects. In some embodiments, the flap **160** may have a non-uniform rigidity. For example, the flap **160** may have regions of increased rigidity, such as the region at and near the bite line. In some embodiments, the flap may have a rigidity gradient, wherein the most rigid point is near the bite line and the least rigid point is at the uppermost point **162**. Rigidity may be varied by increasing the thickness of the material (e.g., applying additional layers of material) at areas where increased rigidity is desired. In some embodiments, the flap **160** may be flexible.

[0048] The flap **160** may be formed from leather, fabric, carbon fiber, thermosets, thermoplastics, or any appropriate material now known or later developed with suitable rigidity. In some embodiments, the flap **160** comprises a self-reinforced polymer composite material. Self-reinforced polymer composites are generally known in the composite industry and refer to fiber-reinforced composites comprising reinforcing fibers and a polymer matrix, where the highly oriented reinforcing fibers are made from the same polymer in which the matrix is made. For example, a polypropylene matrix can be reinforced with polypropylene fibers. Different thermoplastic polymers can be used including, for example, polypropylene, polyethylene terephthalate, polymethyl methacrylate, liquid crystal polymers, polylactic acid, and polyamides. Self-reinforced

polymer composites are commercially available and sold, for example, under the trademarks of Pure® (DIT BV and Milliken USA (formerly Lankhorst Pure Composites, The Netherlands); Armordon® (Don & Low, Ltd., Scotland, UK); and Curv® (Propex Furnishing Solutions GmbH&Co. KG (Gronau, Germany)).

[0049] Self-reinforced composites can be made using various technologies including hot compaction and co-extrusion methods. In general, hot-compaction refers to a method by which highly oriented polymer tapes are heated. The heating allows a small percentage of the polymer tapes to melt. When pressure is applied, this molten polymer flows through the lattice work of the tapes to form a continuous matrix. The sheet is then cooled while still under pressure to solidify the matrix. The fiber-drawing process provides higher stiffness as the surface facings of the fibers are melted. The melted skin is re-crystallized to form the polymer matrix and a highly stiff, smooth composite sheet is produced. This rigid sheet can then be thermoformed into a flap constructed according to one or more embodiments as described herein.

[0050] In a co-extrusion process, a high melting point grade of the polymer is used to extrude highly oriented polymer tapes. During this process, a low-melting point grade of the same polymer family is extruded on the surface of the tape. These tapes can then be woven to form a fabric. During post-processing into shaped parts and articles, the outer layer of the tape melts before the inner core of the oriented polymer. Under pressure, the low melt grade polymer flows throughout the fabric. On cooling, this low melt grade polymer re-solidifies to form the composite matrix and a composite sheet is produced.

[0051] These self-reinforced composites are lightweight and have high strength. Other advantageous properties include, for example, a high stiffness, high tensile strength, and outstanding impact resistance. Because the reinforcement fibers and matrix are made of the same polymer, they are chemically compatible and there is low interfacial failure.

[0052] In particular, these self-reinforced composites have low density, preferably less than about 1.0 g/cm³ and more preferably less than 0.95 g/cm³ (as measured according to ISO1183). The combination of highly oriented tapes and matrix made of the same polymer helps provide a lightweight material with good physical properties such as strength, toughness, and modulus.

[0053] The composites also have high impact strength. The Charpy Impact strength is greater than 90 kJ/m.^{sup.2}, more preferably greater than 100 kJ/m.^{sup.2}, and even more preferably greater than 110 kJ/m.^{sup.2} (as measured according to EN ISO 179/2). The Tensile Strain to Failure (as measured according to DIN EN ISO 527) is preferably at least 10%. The Compression strength (flat wise) (as measured according to EN ISO 604) is preferably greater than 200 MPa and more preferably greater than 250 MPa.

[0054] The composites are ductile material that stay ductile at low temperatures. That is, these composites maintain their toughness and do not become brittle at cold temperatures. Furthermore, these composites can be recycled easily since the reinforcing material is made of the same polymer as the polymer matrix. The composites are made entirely of thermoplastic so the component part can be broken down, re-melted and then re-granulated so that it can be used to make new components.

[0055] These self-reinforced polymer composite materials and methods of manufacturing are described in the patent literature including, for example, Ward et al., U.S. Pat. Nos. 9,873,239; 8,871,333; 8,268,439; 8,052,913; and 8,021,592 (Propex) and Loos et al., U.S. Pat. No. 7,318,961 (Lankhurst); and Nair et al., U.S. Pat. No. 7,960,024 and Callaway, U.S. Pat. No. 7,300,691 (Milliken).

[0056] The polypropylene self-reinforced composite, Curv®, available from (Propex Furnishing Solutions GmbH&Co. KG (Gronau, Germany) is a particularly preferred material. The Curv® composite material is based on highly drawn tapes made of polypropylene homopolymer. During a precisely controlled heating process, the polypropylene tapes are heated so that only a thin outer layer of the tapes is melted. The outer melted material bonds the tapes together while the tapes

maintain their orientation through most of their thickness. The Curv® composite material can be molded to form the base using a thermoforming process. The Curv® composite material has a relatively high stiffness even at molding temperatures so moderate pressure is needed to shape the material. In one process, a sheet of Curv® composite material is heated to a moderate temperature, where the shrinkage of the sheet is kept low. The Curv® composite material is molded by moderate pressure compression molding. Because of the Curv® composite material's high stiffness, vacuum thermoforming is not used.

[0057] The flap **160** may be any shape. As is shown in FIGS. **1-4**, the flap **160** may have a substantially semi-circular shape. It is contemplated that the flap **160** may be substantially semi-circular, triangular, ovular, or rectangular. In some embodiments, it is anticipated that the flap **160** may have an irregular shape. The flap **160** may have rounded edges or sharp edges. The flap **160** may have an uppermost point **162**, a heel end **164**, and a forefoot end **166**. In some embodiments the flap **160** is entirely within the midfoot region **135**. In other embodiments the heel end **164** may extend into the heel region **130** or the forefoot end **166** may extend into the forefoot region **140**. In other embodiments, the forefoot end **166** is generally posterior to a forefoot flexion area. The flap **160** may have a width that is generally uniform throughout the flap. Alternately, the flap **160** may have a variable width to provide increased stability. In some embodiments, the width of the flap **160** may be thicker proximate the bite line **105** and taper as it extends toward an uppermost point **162**. The flap **160** may have grooves to facilitate proper placement of the laces **152**.

[0058] The flap **160** may be configured to provide lateral support when downward pressure is applied to the sole **110**. The closure system **150** may engage the flap **160** by pushing or pulling the flap **160** toward a center of an article of footwear **10**. If the flap **160** is coupled on the medial side, the closure system **150** may push or pull the flap **160** inwardly toward the lateral side. If the flap **160** is coupled on the lateral side, the closure system **150** may push or pull the flap inwardly toward the medial side. Engaging the flap **160** prevents the upper **100** from twisting around the user's foot and the foot from linearly sliding medio-laterally within the footwear **10**.

[0059] The flap **160** may provide stability for various types of biomechanical movements. For example, the biomechanics associated with swinging a golf club call for a rapid shift of weight from back foot to front foot. Shear forces are applied to both feet through the swing. During the backswing, the back foot must remain stable. Improperly shifting weight at the back foot may result in improper contact with the ball. Further, due to biomechanics, the back foot may be susceptible to being rolled to the lateral outside or slipping from the initial foot placement. Weight transfer may thus be diminished and rotation may be lost. On the downswing, weight is shifted to the front foot, which must now remain relatively stable. Increasing foot stability may result in increasing the efficacy and quality of a golf swing.

[0060] When the flaps **160** of a pair of shoes are engaged, the feet remain further secured within their respective shoe and are prevented from shifting while swinging the golf club. Thus, the feet are also more easily planted in position when the flap **160** is engaged. During a backswing, the flap **160** stabilizes the trail foot by reducing abduction and external rotation. Reducing abduction and external rotation of the back foot enables the user to place more load on the back hip leg muscle thereby enabling increased separation between the hips and shoulders prior to the downswing.

[0061] It is contemplated that the flap **160** may stabilize a desired portion of the foot for a variety of activities, and there is no intention to limit the usefulness of the current disclosure. For example, the flap **160** may stabilize at least a portion of a medial midfoot region.

[0062] As is shown in FIG. **11**, the flap **160** may be coupled to the article of footwear **10** at the bite line **105**. In these embodiments, the flap **160** reduces the effect of medio-lateral shear forces generated between a footwear traction system and a substratum when worn by a user by adding lateral rigidity to the bite line area when the flap **160** is engaged. In some embodiments, the flap **160** may be coupled to the upper **100**. In some embodiments, the flap **160** is configured to be coupled to a lateral side of a back foot as described above. In some embodiments the lace **152** may

overlay the flap **160**.

[0063] The flap **160** may be unattached to the upper **100**. In some embodiments when the flap **160** is only attached at the bite line **105** an attachment point may be a hinged connection and the flap **160** may be able to partially rotate outwardly and downwardly. In other embodiments, a hinged connection may not be necessary as the coupling of the flap **160** to the bite line **105** may allow the flap **160** may to partially rotate outwardly and downwardly about the bite line **105**, as is shown in FIG. **11**. Yet, in alternative embodiments, the flap **160** may be attached near the upper **100** using various means known in the art including sewing or adhering. For example, the flap **160** may be a rigid layer wrapped around the upper **100** wherein the uppermost point **162** of the upper is still free to be pulled across the upper **100**.

[0064] The flap **160** may be variable between two general positions. The flap **160** may have a relaxed position in which the flap is not tightly held or pulled to the upper **100**, which is shown in FIG. **11**. The flap **160** may be in the relaxed position when a downward pressure is released from the sole **110**, when there is a flexion in a forefoot region **140**, or when the closure system **150** is not tightened. The flap **160** may also have an engaged position wherein the flap **160** is not secured to the upper.

[0065] In the relaxed position, a portion of the flap **160** may not be in contact with the upper **100**. The flap **160** may be configured to slide against the upper **100** as opposed to applying continuous support. In some embodiments, the closure system **150** crosses over the flap **160**. When the lace **152** of the closure system is tightened, the flap **160** may be held tight and secured to the upper **100** in the engaged position. This may provide increased lateral stability. However, if the flap **160** was to always provide the increased stability, the article of footwear **10** may be rendered rigid and uncomfortable. It may be painful to engage in prolonged ambulatory movement with the flap **160** in the engaged position. Therefore, when the lace **152** is slack, the flap **160** may arc laterally outward from the upper **100**. The release of the flap **160** may provide increased comfort and improve the flexibility of the article of footwear **10**.

[0066] In some embodiments, there may be a secondary closure system **170** proximate the vamp **120** as can be seen in FIGS. **2**, **4**, **7**, and **9**. The secondary closure system may include shoelaces **172** and a tongue **174**. There may be eyelets **176** in an eyerow proximate the eyestay configured to receive the shoelaces **172**. The shoelaces **172** may be inelastic or resiliently elastic. The shoelaces **172** may have a first end and a second end, and each end may further have an aglet. The shoelaces **172** may be threaded through the eyelets **176** such that when pulled taut, the upper **100** and tongue **174** secure a user's foot within the upper **100**.

[0067] It will be appreciated that the secondary closure system may also include a variety of fastening mechanisms, such as bands with hook and loop closures, buckles, buttons, hooks, snaps, or any other fastening device now known or later developed.

[0068] The article of footwear **10** may have three general embodiments offering varying levels of stability and ease of use. The first embodiment may relate to an article of footwear **10** having a flap **160** and a closure system **150**. The first embodiment may also have a secondary closure system **170**. The flap **160** may be coupled to the article of footwear **10** at the bite line **105** but is otherwise moveable and configured to be adjustably tightened to the upper **100** using the closure system **150**. There may be at least one lace guide **156** proximate the bite line **105** at the midfoot region **135**. There may also be at least one lace guide **156** in the forefoot region **140**. The lace guide **156** in the forefoot region may be proximate the bite line **105** or may be above the bite line **105** and on the outer surface of the upper. The laces may be hidden by view by the use of a fabric tubing channel or other means. In some embodiments, the lace **152** may cross in an X pattern at the vamp **120** in the forefoot region **140**. Alternately, the lace **152** may be crossed in an X pattern in the midfoot region **135**. This may provide increased stability, strength, and tension due to the length of the closure system from the forefoot region **140** to the heel region **130**.

[0069] A lateral load of a foot may be relatively low proximate the bite line **105**. The lace guides

156 may be coupled at or proximate the bite line **105**. A lacing configuration employing lace guides **156** proximate the bite line **105** reduces excess pressure at the vamp **120** and the midfoot region **135**. In contrast, typical closure systems, such as shoelaces and eyelets, apply excess downward pressure resulting in lace bite. If the lateral load is stabilized above the bite line **105**, a foot may still roll or be misplaced. Thus, if the lateral load is stabilized at the bite line **105**, it provides increased stability. The lateral load is stabilized at the bite line **105** when the flap **160** is in the engaged position. In some embodiments, the lace guides **156** and/or lace anchor **158** may be coupled to other areas of the flap **160**. For example, the lace guides **156** and/or lace anchor **158** may be coupled to the top of the flap **160** to place the flap **160** in tension along the inferior/superior length of the article of footwear **10**. In these embodiments, the flap **160** preferably still remains pivotably attached to the bite line **105**.

[0070] The X pattern may further promote the increase and decrease in a tension of the lace **152**. The lace **152** may be tightened when a downward force is applied to the sole **110**. The tightened lace **152** may secure the flap **160** proximate the upper **100**. The tension in the lace **152** may thus be activated automatically. When there is flexion in the forefoot region **140**, the article of footwear **10** may be move such that slack may be introduced to the lace **152**. The slack lace **152** may permit the flap **160** to transition from an engaged position to a relaxed position.

[0071] The second embodiment may relate to an article of footwear **10** having a flap **160** and a closure system **150**. The closure system **150** may be more similar to a typical shoelace system and at least one lace guide **156** may be proximate the eyestay **122**. The tension in the laces **152** may be activated automatically, but the article of footwear **10** may have a decrease in stability when compared to the lacing configuration employing the X pattern due to a lacing configuration that may not as tightly secure the flap **160** to the upper **100**.

[0072] The third embodiment may relate to an article of footwear **10** having a flap **160**, a closure system **150**, and a secondary closure system **170**. The secondary closure system **170** may act as the primary closure system, and the closure system **150** may be designed to be adjusted and tightened such that the flap **160** provides increased stability before an increased stability is desired. For example, in use, a user may manually increase the tension before swinging a golf ball to increase lateral foot support. The article of footwear **10** may otherwise be secured, but the closure system **150** may activate the flap **160**. Once the increased stability is no longer desired, the closure system **150** may be adjusted to decrease the tension of the laces **152** such that the flap **160** may not be tightened to the upper. For example, upon completing a golf swing and anticipating walking to the next shot, a user may decrease the tension before beginning to walk. In some embodiments, slack in the laces **152** may not be automatically transferred upon release of a downward pressure on the sole **110**. Therefore, the closure system **150** may need to be adjusted each time increased or decreased stability from the flap **160** is desired.

[0073] Many different arrangements of the various components depicted, as well as components not shown, are possible without departing from the spirit and scope of the present disclosure. Embodiments of the present disclosure have been described with the intent to be illustrative rather than restrictive. Alternative embodiments will become apparent to those skilled in the art that do not depart from its scope. A skilled artisan may develop alternative means of implementing the aforementioned improvements without departing from the scope of the present disclosure.

[0074] It will be understood that certain features and subcombinations are of utility and may be employed without reference to other features and subcombinations and are contemplated within the scope of the claims.

Claims

1. An article of footwear comprising: an upper; a sole; a bite line; a heel region, a midfoot region, and a forefoot region; a medial side and a lateral side extending between the forefoot region and the

heel region; a flap positioned entirely along the midfoot region on the medial or lateral side of the article of footwear, wherein the flap has an upper region and a lower region with a different thickness and rigidity than the upper region; and a closure system comprising a lace with a first end coupled to an adjustable dial positioned in the heel region and a second end coupled to the lower region of the flap, wherein the lace is configured to cross over an outer surface portion of the flap to engage a lace guide or a lace anchor provided on the outer surface portion of the flap, wherein the closure system is configured to (i) secure the flap to the medial or lateral side of the upper when the lace is tightened and (ii) release the flap from the medial or lateral side of the upper when the lace is loosened.

2. The article of footwear of claim 1, wherein the flap comprises one or more layers of a rigid or semi-rigid material.

3. The article of footwear of claim 2, wherein the one or more layers of material comprise a composite material, a carbon fiber material, a thermoset material, or a thermoplastic material.

4. The article of footwear of claim 2, wherein the flap includes one or more additional layers of material provided along or adjacent to the bite line to increase a stiffness or a rigidity of the lower region of the flap.

5. The article of footwear of claim 2, wherein the flap includes areas in which additional layers of material are applied to provide higher stabilization effects.

6. The article of footwear of claim 1, wherein the flap has a thickness that varies between the upper region of the flap and the lower region of the flap.

7. The article of footwear of claim 1, wherein the flap has a width that tapers along a length of the flap from the bite line to the upper region of the flap.

8. The article of footwear of claim 1, wherein the flap has a semi-circular shape with a rounded edge portion and a sharp edge portion.

9. The article of footwear of claim 1, wherein the flap includes one or more grooves configured to receive the lace.

10. The article of footwear of claim 1, wherein the flap is moveable between a relaxed position and an engaged position.

11. The article of footwear of claim 10, wherein the flap is configured to transition to the engaged position when the lace is pulled taut.

12. The article of footwear of claim 11, wherein the lace is pulled taut when a downward pressure is applied to the sole or when the forefoot region is not under flexion.

13. The article of footwear of claim 10, wherein the flap is configured to transition to the relaxed position when slack is introduced to the lace.

14. The article of footwear of claim 13, wherein said slack is introduced to the lace when a downward pressure is lifted from the sole or when there is flexion in the forefoot region.

15. The article of footwear of claim 13, wherein the lace is configured to release at least a forefoot end of the flap when said slack is introduced to the lace.

16. The article of footwear of claim 10, wherein the flap is configured to arc outwards and away from the upper as the flap transitions from the engaged position to the relaxed position.

17. The article of footwear of claim 10, wherein the lace remains attached or secured to the lace guide or the lace anchor when the flap is in the relaxed position.

18. The article of footwear of claim 1, wherein the second end of the lace is attached or coupled to the lace anchor.

19. The article of footwear of claim 1, wherein the lace is configured to engage both the lace guide and the lace anchor.

20. The article of footwear of claim 19, wherein the lace guide and the lace anchor are provided on different parts of the flap.
