



US012383405B2

(12) **United States Patent**
Dees, Jr. et al.

(10) **Patent No.:** **US 12,383,405 B2**
(45) **Date of Patent:** ***Aug. 12, 2025**

(54) **ANATOMICAL MOTION HINGED PROSTHESIS**

(56) **References Cited**

(71) Applicant: **Smith & Nephew, Inc.**, Memphis, TN (US)

U.S. PATENT DOCUMENTS
3,748,662 A 7/1973 Helfet
3,774,244 A 11/1973 Walker
(Continued)

(72) Inventors: **Roger Ryan Dees, Jr.**, Senatobia, MS (US); **Paul Charles Crabtree, Jr.**, Nesbit, MS (US); **Jonathan Kirk Nielsen**, Dana Point, CA (US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Smith & Nephew, Inc.**, Memphis, TN (US)

CN 1087506 A 6/1994
CN 101484094 A 7/2009
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 885 days.

OTHER PUBLICATIONS

This patent is subject to a terminal disclaimer.

Canadian Patent Office, Second Office Action dated Dec. 4, 2017, 4 pages.

(Continued)

(21) Appl. No.: **17/573,802**

Primary Examiner — Melanie R Tyson

Assistant Examiner — Melissa A Hoban

(22) Filed: **Jan. 12, 2022**

(74) *Attorney, Agent, or Firm* — KDW Firm PLLC

(65) **Prior Publication Data**

US 2022/0133485 A1 May 5, 2022

Related U.S. Application Data

(60) Continuation of application No. 16/684,801, filed on Nov. 15, 2019, now abandoned, which is a division of (Continued)

(51) **Int. Cl.**
A61F 2/38 (2006.01)

(52) **U.S. Cl.**
CPC **A61F 2/385** (2013.01); **A61F 2/384** (2013.01); **A61F 2/38** (2013.01); **A61F 2/3859** (2013.01)


(58) **Field of Classification Search**
None

See application file for complete search history.

(57) **ABSTRACT**

A hinged knee prosthesis comprises a tibial component and a femoral component. The tibial component is configured to attach to a tibia. The tibial component has a bearing surface. The femoral component is configured to hingedly attach to the tibial component and rotate relative to the tibial component. The femoral component comprises a medial condyle and a lateral condyle. The medial and lateral condyles have an eccentric sagittal curvature surface configured to rotate and translate on the bearing surface of the tibial component. A method of rotating a hinged knee through a range of flexion is provided. The method fixedly attaches a femoral component to a tibial component. Axial rotation of the femoral component is induced relative to the tibial component when the hinged knee is flexed.

14 Claims, 21 Drawing Sheets



Related U.S. Application Data

application No. 15/676,024, filed on Aug. 14, 2017, now Pat. No. 10,779,949, which is a continuation of application No. 13/964,306, filed on Aug. 12, 2013, now Pat. No. 9,730,799, which is a continuation of application No. 12/307,102, filed as application No. PCT/US2007/072611 on Jun. 30, 2007, now Pat. No. 8,523,950.

- (60) Provisional application No. 60/806,383, filed on Jun. 30, 2006.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,798,679 A	3/1974	Ewald	5,098,436 A	3/1992	Ferrante et al.
3,816,855 A	6/1974	Saleh	5,100,409 A	3/1992	Coates et al.
3,824,630 A	7/1974	Johnston	5,104,824 A	4/1992	Clausen, Jr. et al.
3,837,009 A	9/1974	Walker	5,107,824 A	4/1992	Rogers et al.
3,869,731 A	3/1975	Waugh et al.	5,116,375 A	5/1992	Hofmann
3,924,277 A	12/1975	Freeman et al.	5,122,144 A	6/1992	Bert et al.
3,934,272 A	1/1976	Wearne et al.	5,129,909 A	7/1992	Sutherland
3,958,278 A	5/1976	Lee et al.	5,133,758 A	7/1992	Hollister
4,016,606 A	4/1977	Murray et al.	5,133,759 A	7/1992	Turner
4,178,641 A	12/1979	Grundei et al.	5,147,405 A	9/1992	Van Zie et al.
4,207,627 A	6/1980	Cloutier	5,147,406 A	9/1992	Houston et al.
4,209,861 A	7/1980	Walker et al.	5,176,710 A	1/1993	Hahn et al.
4,213,209 A	7/1980	Insall et al.	5,181,925 A	1/1993	Houston et al.
4,249,270 A	2/1981	Bahler et al.	5,201,881 A	4/1993	Evans
4,262,368 A	4/1981	Lacey	5,203,807 A	4/1993	Evans et al.
4,301,553 A	11/1981	Noiles	5,219,362 A	6/1993	Tuke et al.
4,309,778 A	1/1982	Buechel et al.	5,226,916 A	7/1993	Goodfellow et al.
4,340,978 A	7/1982	Buechel et al.	5,228,459 A	7/1993	Caspari et al.
4,353,135 A	10/1982	Forte et al.	5,234,433 A	8/1993	Bert et al.
4,358,859 A	11/1982	Schurman et al.	5,236,432 A	8/1993	Matsen, III et al.
4,462,120 A	7/1984	Rambert et al.	5,236,461 A	8/1993	Forte
4,474,177 A	10/1984	Whiteside	5,250,050 A	10/1993	Poggie et al.
4,524,766 A	6/1985	Petersen	5,263,498 A	11/1993	Caspari et al.
4,538,305 A	9/1985	Engelbrecht et al.	5,282,803 A	2/1994	Lackey
4,568,348 A	2/1986	Johnson et al.	5,282,867 A	2/1994	Mikhail
4,586,933 A	5/1986	Shoji et al.	5,282,870 A	2/1994	Moser et al.
4,653,488 A	3/1987	Kenna	5,304,181 A	4/1994	Caspari et al.
4,659,331 A	4/1987	Matthews	5,314,481 A	5/1994	Bianco
4,662,889 A	5/1987	Zichner et al.	5,314,482 A	5/1994	Goodfellow et al.
4,703,751 A	11/1987	Pohl	5,326,358 A	7/1994	Aubriot et al.
4,711,639 A	12/1987	Grundei	5,330,532 A	7/1994	Ranawat
4,714,472 A	12/1987	Averill et al.	5,330,533 A	7/1994	Walker
4,714,473 A	12/1987	Bloebaum	5,330,534 A	7/1994	Herrington et al.
4,721,104 A	1/1988	Kaufman	5,336,267 A	8/1994	Kubein-Meesenburg et al.
4,722,330 A	2/1988	Russell et al.	5,358,527 A	10/1994	Forte
4,731,086 A	3/1988	Whiteside et al.	5,358,529 A	10/1994	Davidson
4,770,663 A	9/1988	Hanslik et al.	5,358,531 A	10/1994	Goodfellow et al.
4,787,383 A	11/1988	Kenna	5,370,699 A	12/1994	Hood et al.
4,822,365 A	4/1989	Walker et al.	5,370,701 A	12/1994	Finn
4,834,758 A	5/1989	Lane	5,405,398 A	4/1995	Buford, III et al.
4,865,606 A	9/1989	Rehder	5,411,555 A	5/1995	Nieder
4,926,847 A	5/1990	Luckman	5,413,604 A	5/1995	Hodge
4,936,853 A	6/1990	Fabian et al.	5,413,607 A	5/1995	Engelbrecht et al.
4,938,769 A	7/1990	Shaw	5,417,694 A	5/1995	Marik et al.
4,944,757 A	7/1990	Martinez et al.	5,454,816 A	10/1995	Ashby
4,950,297 A	8/1990	Elloy et al.	5,470,354 A	11/1995	Hershberger et al.
4,950,298 A	8/1990	Gustilo et al.	5,480,443 A	1/1996	Elias
4,963,152 A	10/1990	Hofmann et al.	5,480,446 A	1/1996	Goodfellow et al.
4,979,949 A	12/1990	Matsen, III et al.	5,507,820 A	4/1996	Pappas
5,002,547 A	3/1991	Poggie et al.	5,514,143 A	5/1996	Bonutti et al.
5,007,933 A	4/1991	Sidebotham et al.	5,520,695 A	5/1996	Luckman
5,011,496 A	4/1991	Forte et al.	5,549,684 A	8/1996	Amino et al.
5,021,061 A	6/1991	Wevers et al.	5,549,686 A	8/1996	Johnson et al.
5,032,134 A	7/1991	Lindwer	5,549,688 A	8/1996	Ries et al.
5,047,057 A	9/1991	Lawes	5,549,689 A	8/1996	Epstein et al.
5,053,037 A	10/1991	Lackey	5,556,432 A	9/1996	Kubein-Meesenburg et al.
5,062,852 A	11/1991	Dorr et al.	5,609,645 A	3/1997	Vinciguerra
5,071,438 A	12/1991	Jones et al.	5,611,802 A	3/1997	Samuelson et al.
5,080,675 A	1/1992	Lawes et al.	5,639,279 A	6/1997	Burkinshaw et al.
5,092,869 A	3/1992	Waldron	5,658,342 A	8/1997	Draganich et al.
			5,658,344 A	8/1997	Hurlburt
			5,667,511 A	9/1997	Vendrely
			5,681,354 A	10/1997	Eckhoff
			5,682,886 A	11/1997	Delp et al.
			5,690,635 A	11/1997	Matsen, III et al.
			5,690,637 A	11/1997	Wen et al.
			5,702,458 A	12/1997	Burstein et al.
			5,702,466 A	12/1997	Pappas
			5,723,016 A	3/1998	Minns et al.
			5,728,162 A	3/1998	Eckhoff
			5,755,801 A	5/1998	Walker et al.
			5,755,803 A	5/1998	Haines et al.
			5,755,804 A	5/1998	Schmotzer et al.
			5,766,257 A	6/1998	Goodman et al.
			5,776,200 A	7/1998	Johnson et al.
			5,782,921 A	7/1998	Colleran et al.
			5,782,925 A	7/1998	Collazo et al.
			5,800,552 A	9/1998	Forte
			5,810,827 A	9/1998	Haines et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,824,096	A	10/1998	Pappas et al.	7,048,741	B2	5/2006	Swanson
5,824,100	A	10/1998	Kester et al.	7,077,867	B1	7/2006	Pope et al.
5,824,102	A	10/1998	Buscayret	7,104,996	B2	9/2006	Bonutti
5,824,105	A	10/1998	Ries et al.	7,141,053	B2	11/2006	Rosa et al.
5,871,545	A	2/1999	Goodfellow et al.	7,153,327	B1	12/2006	Metzger
5,871,546	A	2/1999	Colleran et al.	7,160,330	B2	1/2007	Axelsson, Jr. et al.
5,879,392	A	3/1999	McMinn	7,297,165	B1	11/2007	Kriek
5,906,643	A	5/1999	Walker	7,326,252	B2	2/2008	Otto et al.
5,935,173	A	8/1999	Roger et al.	7,371,240	B2	5/2008	Pinczewski et al.
5,954,770	A	9/1999	Schmotzer et al.	7,572,292	B2	8/2009	Crabtree et al.
5,997,577	A	12/1999	Herrington et al.	7,625,407	B2	12/2009	Akizuki et al.
6,019,794	A	2/2000	Walker	7,658,767	B2	2/2010	Wyss
6,039,764	A	3/2000	Pottenger et al.	7,871,442	B2	1/2011	Servidio
6,056,779	A	5/2000	Noyer et al.	2001/0001121	A1	5/2001	Lombardo et al.
6,059,788	A	5/2000	Katz	2001/0018615	A1	8/2001	Biegun et al.
6,068,658	A	5/2000	Insall et al.	2001/0043918	A1	11/2001	Masini et al.
6,080,195	A	6/2000	Colleran et al.	2002/0032450	A1	3/2002	Trudeau et al.
6,099,570	A	8/2000	Livet et al.	2002/0055784	A1	5/2002	Burstein et al.
6,120,543	A	9/2000	Kubein-Meesenburg et al.	2002/0058997	A1	5/2002	O Connor et al.
6,132,468	A	10/2000	Mansmann	2002/0103541	A1	8/2002	Meyers et al.
6,139,581	A	10/2000	Engh et al.	2002/0107576	A1	8/2002	Meyers et al.
6,143,034	A	11/2000	Burrows	2002/0120340	A1	8/2002	Metzger et al.
6,165,223	A	12/2000	Metzger et al.	2002/0161447	A1	10/2002	Salehi et al.
6,171,340	B1	1/2001	McDowell	2002/0173852	A1	11/2002	Felt et al.
6,190,415	B1	2/2001	Cooke et al.	2002/0177852	A1	11/2002	Chervitz et al.
6,197,064	B1	3/2001	Haines et al.	2002/0177853	A1	11/2002	Chervitz et al.
6,203,576	B1	3/2001	Afriat et al.	2003/0009228	A1	1/2003	Meyers et al.
6,206,926	B1	3/2001	Pappas	2003/0009230	A1	1/2003	Gundlapalli et al.
6,210,443	B1	4/2001	Marceaux et al.	2003/0028196	A1	2/2003	Bonutti
6,235,060	B1	5/2001	Kubein-Meesenburg et al.	2003/0055494	A1	3/2003	Bezuidenhout et al.
6,264,696	B1	7/2001	Reigner et al.	2003/0055501	A1	3/2003	Fell et al.
6,264,697	B1	7/2001	Walker	2003/0055509	A1	3/2003	McCue et al.
6,306,172	B1	10/2001	O Neil et al.	2003/0060882	A1	3/2003	Fell et al.
6,325,828	B1	12/2001	Dennis et al.	2003/0060883	A1	3/2003	Fell et al.
6,361,564	B1	3/2002	Marceaux et al.	2003/0060884	A1	3/2003	Fell et al.
6,379,388	B1	4/2002	Ensign et al.	2003/0060885	A1	3/2003	Fell et al.
6,406,497	B2	6/2002	Takei	2003/0069591	A1	4/2003	Carson et al.
6,413,279	B1	7/2002	Metzger et al.	2003/0093156	A1	5/2003	Metzger et al.
6,428,577	B1	8/2002	Evans et al.	2003/0100953	A1	5/2003	Rosa et al.
6,436,145	B1	8/2002	Miller	2003/0130665	A1	7/2003	Pinczewski et al.
6,443,991	B1	9/2002	Running	2003/0153977	A1	8/2003	Suguro et al.
6,475,241	B2	11/2002	Pappas	2003/0153978	A1	8/2003	Whiteside
6,485,519	B2	11/2002	Meyers et al.	2003/0153979	A1	8/2003	Hughes et al.
6,494,917	B1	12/2002	McKellop et al.	2003/0163201	A1	8/2003	McMinn
6,500,208	B1	12/2002	Metzger et al.	2003/0220697	A1	11/2003	Justin et al.
6,506,215	B1	1/2003	Letot et al.	2003/0225410	A1	12/2003	Chervitz et al.
6,554,838	B2	4/2003	McGovern et al.	2003/0225458	A1	12/2003	Donkers et al.
6,558,426	B1	5/2003	Masini	2004/0006393	A1	1/2004	Burkinshaw
6,569,202	B2	5/2003	Whiteside	2004/0030387	A1	2/2004	Landry et al.
6,575,980	B1	6/2003	Robie et al.	2004/0034432	A1	2/2004	Hughes et al.
6,589,283	B1	7/2003	Metzger et al.	2004/0044414	A1	3/2004	Nowakowski
6,620,198	B2	9/2003	Burstein et al.	2004/0102852	A1	5/2004	Johnson et al.
6,623,526	B1	9/2003	Lloyd	2004/0122522	A1	6/2004	Kubein-Meesenburg et al.
6,645,251	B2	11/2003	Salehi et al.	2004/0143339	A1	7/2004	Axelsson, Jr. et al.
6,695,848	B2	2/2004	Haines	2004/0153066	A1	8/2004	Coon et al.
6,702,821	B2	3/2004	Bonutti	2004/0153164	A1	8/2004	Sanford et al.
6,730,128	B2	5/2004	Burstein	2004/0162620	A1	8/2004	Wyss
6,755,864	B1	6/2004	Brack et al.	2004/0186584	A1	9/2004	Keller
6,764,516	B2	7/2004	Pappas	2004/0193280	A1	9/2004	Webster et al.
6,770,097	B2	8/2004	Leclercq	2004/0199249	A1	10/2004	Fell
6,770,099	B2	8/2004	Andriacchi et al.	2004/0199250	A1	10/2004	Fell
6,773,461	B2	8/2004	Meyers et al.	2004/0204766	A1	10/2004	Siebel
6,811,568	B2	11/2004	Minamikawa	2004/0249467	A1	12/2004	Meyers et al.
6,827,723	B2	12/2004	Carson	2004/0249468	A1	12/2004	Suguro et al.
6,846,329	B2	1/2005	McMinn	2004/0267363	A1	12/2004	Fell et al.
6,866,683	B2	3/2005	Gerbac et al.	2005/0021147	A1	1/2005	Tarabichi
6,866,684	B2	3/2005	Fell et al.	2005/0033424	A1	2/2005	Fell
6,887,276	B2	5/2005	Gerbac et al.	2005/0055102	A1	3/2005	Tornier
6,893,467	B1	5/2005	Bercovy	2005/0107886	A1	5/2005	Crabtree et al.
6,911,044	B2	6/2005	Fell	2005/0125069	A1	6/2005	Naegerl et al.
6,916,234	B2	7/2005	Suwabe	2005/0143832	A1	6/2005	Carson
6,916,340	B2	7/2005	Metzger et al.	2005/0171604	A1	8/2005	Michalow
6,984,249	B2	1/2006	Keller	2005/0197710	A1	9/2005	Naegerl
6,986,791	B1	1/2006	Metzger	2005/0209701	A1	9/2005	Suguro et al.
7,018,418	B2	3/2006	Amrich et al.	2005/0246028	A1	11/2005	Pappas et al.
				2005/0267363	A1	12/2005	Duchon et al.
				2005/0267476	A1	12/2005	Chervitz et al.
				2006/0015109	A1	1/2006	Haines
				2006/0015115	A1	1/2006	Haines

(56)

References Cited**U.S. PATENT DOCUMENTS**

2006/0015116	A1	1/2006	Haines
2006/0015117	A1	1/2006	Haines
2006/0030853	A1	2/2006	Haines
2006/0030854	A1	2/2006	Haines
2006/0030855	A1	2/2006	Haines
2006/0030944	A1	2/2006	Haines
2006/0052875	A1	3/2006	Bernero et al.
2006/0058882	A1	3/2006	Haines
2007/0078517	A1	4/2007	Engh et al.
2008/0119940	A1	5/2008	Otto et al.
2008/0154270	A1	6/2008	Haines et al.
2008/0161918	A1	7/2008	Fankhauser et al.
2008/0167722	A1	7/2008	Metzger et al.
2009/0076514	A1	3/2009	Haines
2009/0088860	A1	4/2009	Romeis et al.
2009/0125114	A1	5/2009	May et al.
2009/0143866	A1	6/2009	Servidio
2009/0210066	A1	8/2009	Jasty
2009/0319048	A1	12/2009	Shah et al.
2009/0319049	A1	12/2009	Shah et al.
2010/0016977	A1	1/2010	Masini
2010/0042224	A1	2/2010	Otto et al.
2010/0076567	A1	3/2010	Justin et al.
2010/0100192	A1	4/2010	Haines et al.
2010/0185203	A1	7/2010	Haines
2011/0082559	A1	4/2011	Hartdegen et al.
2011/0125280	A1	5/2011	Otto et al.
2011/0125281	A1	5/2011	Otto et al.
2011/0125282	A1	5/2011	Otto et al.
2011/0125283	A1	5/2011	Otto et al.
2011/0130841	A1	6/2011	Otto et al.
2011/0130842	A1	6/2011	Otto et al.
2011/0130843	A1	6/2011	Otto et al.
2011/0137426	A1	6/2011	Otto et al.
2011/0137427	A1	6/2011	Otto et al.
2011/0137619	A1	6/2011	Otto et al.

FOREIGN PATENT DOCUMENTS

DE	3022668	A	12/1981
DE	3314038	A	10/1983
DE	4102509	A	7/1992
DE	19529824	A	2/1997
DE	19915053	A	10/1999
DE	10012059	A	9/2001
DE	102005015598	A	9/2006
EP	69683	A	1/1983
EP	121142	A	10/1984
EP	189253	A	7/1986
EP	194326	A	9/1986
EP	243109	A	10/1987
EP	327249	A	8/1989
EP	336774	A	10/1989
EP	380451	A	8/1990
EP	381352	A	8/1990
EP	420460	A	4/1991
EP	466659	A	1/1992
EP	472475	A	2/1992
EP	472975	A	3/1992
EP	510299	A	10/1992
EP	538153	A	4/1993
EP	553585	A	8/1993
EP	555003	A	8/1993
EP	653194	A	5/1995
EP	716839	A	6/1996
EP	724868	A	8/1996
EP	791338	A	8/1997
EP	806920	A	11/1997
EP	916321	A	5/1999
EP	923916	A	6/1999
EP	925766	A	6/1999
EP	941719	A	9/1999
EP	970667	A	1/2000
EP	988840	A	3/2000
EP	1038286	A	9/2000

EP	1285638	A	2/2003
EP	1447060	A	8/2004
EP	1477143	A	11/2004
EP	1721584	A	11/2006
EP	1721585	A	11/2006
EP	2213262	A	8/2010
FR	2508793	A1	1/1983
FR	2635675	A1	3/1990
FR	2664157	A1	1/1992
FR	2701387	A1	8/1994
FR	2710258	A1	3/1995
FR	2710835	A1	4/1995
FR	2760352	A1	9/1998
FR	2776919	A1	10/1999
GB	296443	A1	10/1929
GB	1363018	A1	8/1974
GB	1409150	A1	10/1975
GB	2007980	A1	5/1979
GB	2296443	A1	1/1997
GB	2324249	A1	10/1998
GB	2335145	A1	9/1999
JP	61170453	A1	8/1986
JP	62133948	A1	6/1987
JP	62254750	A1	11/1987
JP	4297254	A1	10/1992
JP	6237941	A1	8/1994
JP	8500992	A1	2/1996
JP	UP8224263	A1	9/1996
JP	10501155	A1	2/1998
JP	11504226	A1	4/1999
JP	11313845	A1	11/1999
JP	2000116682	A1	4/2000
JP	2000201955	A1	7/2000
JP	2000312691	A1	11/2000
JP	2001524349	A1	12/2001
JP	2002224149	A1	8/2002
JP	04951797	A1	6/2012
RU	2121319	A1	11/1998
WO	WO1991010408	A1	7/1991
WO	WO1993003681	A1	3/1993
WO	WO1993022990	A1	11/1993
WO	WO1993025157	A1	12/1993
WO	WO1994005212	A1	3/1994
WO	WO1994009730	A1	5/1994
WO	WO1994022397	A1	10/1994
WO	WO1994028812	A1	12/1994
WO	WO1995003003	A1	2/1995
WO	WO1995032623	A1	12/1995
WO	WO1996001087	A1	1/1996
WO	WO1996001588	A1	1/1996
WO	WO1996003939	A1	2/1996
WO	WO1996023460	A1	8/1996
WO	WO1996024311	A1	8/1996
WO	WO1997029703	A1	8/1997
WO	WO1997029704	A1	8/1997
WO	WO1998020817	A1	5/1998
WO	WO1999027872	A1	6/1999
WO	WO1999030649	A1	6/1999
WO	WO2001013825	A1	3/2001
WO	WO2003059203	A1	7/2003
WO	WO2004100839	A1	11/2004
WO	WO2009056836	A1	5/2009

OTHER PUBLICATIONS

Response dated Nov. 5, 2007 in related U.S. Appl. No. 10/499,047.
Office Action dated Jan. 24, 2008 in related U.S. Appl. No. 10/499,047.
Response dated Apr. 24, 2008 in related U.S. Appl. No. 10/499,047.
Office Action dated May 13, 2008 in related U.S. Appl. No. 10/499,047.
Response dated Aug. 13, 2008 in related U.S. Appl. No. 10/499,047.
Notice of Allowance dated Oct. 8, 2008 in related U.S. Appl. No. 10/499,047.
International Search Report for International Application No. PCT/US2007/072611, mailed Nov. 23, 2007, 4 pages.
First Office Action for Chinese Application No. 20780025036.3, mailed Dec. 7, 2010, 8 pages.

(56)

References Cited**OTHER PUBLICATIONS**

- Communication Pursuant to Article 94(3) EPC for European Application No. 07799226.1, mailed Jul. 8, 2010, 4 pages.
- International Search Report for International Application No. PCT/US02/41221, mailed Oct. 10, 2003, 3 pages.
- English-Language Translation of EP472475, translated on May 23, 2012, with certification of translation, 11 pages.
- Notice of Reasons for Rejection for Japanese Application No. 2009-518598, mailed Jun. 26, 2012.
- Office Action for U.S. Appl. No. 12/307,102, mailed Aug. 9, 2012.
- Communication Pursuant to Article 96(2) EPC for European Application No. 02798579.5, mailed Mar. 15, 2005.
- International Preliminary Report on Patentability for International Application No. PCT/US2007/072611, mailed Jan. 6, 2009.
- Office Action for Canadian Application No. 2,656,359, mailed Nov. 8, 2013.
- Patent Examination Report No. 2 for Australian Application No. 2007269203, mailed Feb. 12, 2014.
- Notice of Reasons for Rejection for Japanese Application No. 2013-096941, mailed Apr. 7, 2014.
- Office Action in Canadian Application No. 2,656,359, mailed Jul. 8, 2014.
- Gschwend, N., "GSB Knee Joint," Clinical Orthopaedics and Related Research, No. 132, May 1978, pp. 170-176.
- Communication Pursuant to Article 94(3) EPC for European Application No. 07799226.1, mailed Aug. 29, 2014.
- "S-ROM® Noiles™ Rotating Hinge: Surgical Technique and Reference Guide," © 2002 DePuy Orthopaedics, Inc.
- First Office Action for Chinese Application No. 201210471063.6, mailed Aug. 29, 2014, with English-language summary.
- Second Office Action for Chinese Application No. 201210471063.6, mailed Apr. 16, 2015, with English-language summary.
- Office Action for Canadian Application No. 2,656,359, mailed Nov. 13, 2015.
- European Hospital . . . The European Forum for Those in the Business of Making Healthcare Work, 12(5/03):1-24 (Oct./Nov. 2003).
- Freeman Samuelson, Total Knee Systems, Biomet, Inc., 1994, attached as Exhibit F, 60 pages.
- Freeman, M.A.R., and Samuelson, K.M., Protek® Mark II Total Knee Replacement System, published 1985, 32 pages, attached as Exhibit G.
- Protek F/S Modular Total Knee Replacement System, published by Protek, Jan. 1991, pp. 1-58, attached as Exhibit H.
- Engh, G.A., et al., "The AMK Total Knee System, Design Rationale and Surgical Procedure," Published by DePuy, 1989, Bates No. DEP00004153-DEP00004201, 50 pages.
- Chapman, Michael W., ed., "Primary Total Knee Arthroplasty," Operative Orthopaedics, vol. 1, published by J.B. Lippincott Co., Philadelphia, 1988, pp. 719-725 and p. 86, Bates No. DEP000004236-DEP00004247.
- Crossett, L.S., et al., "AMK Congruency Instrument System, Surgical Technique," published by DePuy, 1997, Bates No. DEP00004252-DEP00004267, 17 pages.
- Engh, G.A., et al., "AMK Surgical Technique," published by DePuy, 1989, Bates No. DEP00004299-DEP00004329, 32 pages.
- Desjardins, D., et al., "Interax Total Knee Operative Technique," Interax, 1993, Bates No. DEP00004412-DEP00004432, 22 pages.
- Desjardins, D., et al., "Interax Operative Techniques," Interax, 1994, Bates No. DEP00004391-DEP00004411, 22 pages.
- Baird, et al., "LCS Uni: Unicompartamental Knee System with Porocoat," published by DePuy, 1991, Bates No. DEP0000452-DEP00004462, 12 pages.
- Oxford Meniscal Knee Phase II Unicompartamental Replacement, published by Biomet prior to Jun. 7, 1994, Bates No. DEP00004509-DEP00004515, 8 pages.
- Buechel, FF, et al., "Low Contact Stress Meniscal Bearing Unicompartamental Knee Replacement: Long-Term Evaluation of Cemented and Cementless Results," Journal of Orthopaedic Rheumatology, presented at the 57th Annual American Academy of Orthopaedic Surgeons Meeting, New Orleans, LA, Feb. 11, 1990, Bates No. DEP00004096-DEP00004107, 13 pages.
- N. J. Unicompartamental Knee, Sep. 15, 1989, Bates No. DEP00004108-DEP00004116, 10 pages.
- Buechel, FF, "NJLCS Unicompartamental Knee System with Porocoat: Surgical Procedure," Oct. 24, 1994, Bates No. DEP00004117-DEP00004130, 15 pages.
- Buechel, FF, "NJLCS Unicompartamental Knee System with Porocoat," 1994, Bates No. DEP00004142-DEP00004152, 11 pages.
- Scott, R.D., et al., "P.F.C. Signa Uni-compartmental Knee System," published by Johnson & Johnson, 1998, Bates No. DEP00004531-DEP00004539, 10 pages.
- Scott, R.D. et al., "Unicondylar Unicompartamental Replacement for Osteoarthritis of the Knee," Journal of Bone and Joint Surgery, vol. 63-A, No.4, Apr. 1, 1981, pp. 536-544, Bates No. DEP-00004764-DEP00004775.
- Uvehammer, J., et al., "In vivo Kinematics of Total Knee Arthroplasty," The Journal of Bone & Joint Surgery (Br), vol. 82-B, No. 4, May 2000, pp. 499-50.
- Whiteside Ortholoc Total Knee System: Surgical Procedure, Dow Corning Wright, pp. WMT000001-WMT000040, Jun. 1985.
- Zimmer, Insall/Burstein II Constrained Condylar: Modular Knee System, Surgical Technique, copyright 1989.
- Exhibits 4, 5 and 8 from *Hudson Surgical Design, Inc. v. Zimmer Holdings, Inc.*, Zimmer Inc., Rush System for Health and Rush University Medical Center, Hudson Surgical Design, Inc.'s Opening Brief on Claim Construction Case No. 1 :08-cv-01566, Civil Action No. 08C1566, Document No. 83, filed Nov. 17, 2008, 6 pages.
- Hudson Surgical Design v. Zimmer Holdings, Inc., et al.*, Revised Final Claim Construction Chart, filed Mar. 11, 2009, 18 pages.
- Haines et al., Accelerated Examination Search Statement and Support Document for Femoral Prosthetic Implant from U.S. Appl. No. 12/638,692, dated Dec. 15, 2009, 85 pages.
- Haines et al., Corrected Accelerated Examination Search Statement and Support Document for Femoral Prosthetic Implant from U.S. Appl. No. 12/757,778, dated Apr. 9, 2010, 104 pages.
- Advertisement for Protek Mark II PCR Total Knee Replacement System, Journal of Bone and Joint Surgery, vol. 69-B, No. Two Mar. 1987, Bates No. DEP00004202-DEP00004230, 29 pages.
- Parts Brochure for Mark II Protek, published by Protek, 1987, Bates No. DEP00004231-DEP00004235, 4 pages.
- American Academy of Orthopaedic Surgeons, Flyer from the 57th Annual American Academy of Orthopaedic Surgeons Meeting, Feb. 13, 1990, Bates No. DEP00004248-DEP00004267, 4 pages.
- Campbell's Operative Orthopaedics, A.H. Crenshaw, ed., 4th Edition, vol. 1, 1963, pp. 29-30, Bates No. DEP00004330-DEP00004333.
- "Duraconcept: Design Concepts of the Duracon Total Knee System," published by Howmedica, 1993, Bates No. DEP00004337, 1 page.
- Howmedica 1994 Product Catalog, Bates No. DEP00004374-DEP00004375, 2 pages.
- Massarella, Antony, "Interax Bulletin No. 6, Tibial Intramedullary Alignment Surgical Techniques," Interax, Feb. 23, 1994, Bates No. DEP00004387-DEP00004390, 4 pages.
- New Jersey LCS Total Knee System, FDA PMA-Premarket Approval, 1991, reprinted from <http://www.accessdata.fda.gov/scripts/cdrh/cfdocs/cfPMA/pma.cfm?id=3357> on Apr. 8, 2010, Bates No. DEP00004434, 1 page.
- Freeman, M.A.R., et al., "Mark II Total Knee Replacement System," published by Protek, 1985, Bates No. DEP00004463-DEP00004492, 30 pages.
- Buechel, F.F., "NJ LCS Unicompartamental Knee System with Porocoat," © Biomedical Engineering Trust, South Orange, NJ, 1994, Bates No. DEP00004493-DEP00004503, 11 pages.
- Freeman, M.A.R., et al., "F/S Modular Total Knee Replacement System," published by Protek, 1990, Bates No. DEP00004540-DEP00004596, 57 pages.
- Broughton, N.S., et al., "Unicompartamental Replacement and High Tibial Osteotomy for Osteoarthritis of the Knee," Journal of Bone and Joint Surgery, vol. 68-B, No. 3, May 1, 1986, pp. 447-452, Bates No. DEP00004752-DEP00004763.

(56)

References Cited

OTHER PUBLICATIONS

Thornhill, Thomas S., "Unicompartmental Knee Arthroplasty," Clinical Orthopaedics and Related Research, No. 205, Apr. 1, 1986, pp. 121-131, Bates No. DEP00004776-DEP00004791, 16 pages.

Forst, V.R., et al., "A Special jig for Tibial Resection for the Implantation of GSB-Knee-Prostheses in Problematic Cases," Jun. 1, 1984, pp. 162-166, Bates No. DEP00004838-DEP00004842.

Ingillis, A.E., et al., "Revision Total Knee Replacement," Techniques in Orthopaedics, vol. 5, No. 1, Apr. 1, 1990, pp. 67-73, Bates No. DEP00005583-DEP00005592.

Brochure entitled Aesculap EnduRo Gekoppelte Knieendoprothese Aesculap Orthopaedics B/Braun Sharing Expertise, 8 pages, known prior to Jul. 16, 2010.

Brochure entitled Aesculap EnduRo Gekoppelte Knieendoprothese Operationstechnik Aesculap Orthopaedics B/Braun Sharing Expertise, 56 pages, known prior to Jul. 16, 2010.

Brochure entitled Aesculap EnduRo Rotating Hinge Knee Endoprothesis Manual Surgical Procedure B/Braun Sharing Expertise, 1 page, known prior to Jul. 16, 2010.

Photograph of Aesculap-B Braun EnduRo Knee—rotating hinge (known prior to Jul. 16, 2010).

Office Action dated May 4, 2007 in related U.S. Appl. No. 10/499,047.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22






FIG. 23






FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41

1

ANATOMICAL MOTION HINGED PROSTHESIS

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of pending U.S. patent application Ser. No. 16/684,801, filed Nov. 15, 2019, which is a division of U.S. patent application Ser. No. 15/676,024, filed Aug. 14, 2017, now U.S. Pat. No. 10,779,949, issued Sep. 22, 2020, which is a continuation of U.S. patent application Ser. No. 13/964,306, filed Aug. 12, 2013, now U.S. Pat. No. 9,730,799, issued Aug. 15, 2017, which is a continuation of U.S. patent application Ser. No. 12/307,102, filed Feb. 3, 2010, now U.S. Pat. No. 8,523,950, issued Sep. 3, 2013, which is a U.S. National Phase of International Application No. PCT/US2007/072611, filed Jun. 30, 2007, which claims the benefit of U.S. Provisional Application No. 60/806,383, filed Jun. 30, 2006. Each of the prior applications is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

This application relates generally to knee prostheses and, more particularly, the application relates to hinged knee prostheses.

2. Related Art

Most hinged-knee prostheses only provide a mechanical means to restore the joint in a hinge-like function. Other hinged-knee prostheses provide for more kinematically-correct prostheses; however, they rely mostly on remaining soft tissue to restore normal kinematics to the joint. In most cases, the remaining soft tissue has been compromised and/or missing/removed during surgery. Thus, the soft tissue cannot contribute significantly to restoring normal kinematics, particularly anterior/posterior (A/P) translation or normal axial rotation including rotation to the 'screw-home' position. Moreover, the remaining soft tissue may be damaged when restoring normal kinematics by forcing motion of the prostheses.

In prosthetic systems that address axial rotation, current systems address rotation by allowing a rotating platform. Generally, one of the two articulating prostheses (usually the tibial insert or construct) is allowed rotational freedom. This allows the soft tissues to rotate the joint in a more normal fashion. However, most soft tissue has been compromised and cannot reproduce normal or near normal rotation.

A/P translation is a motion that is seldom addressed. In those prostheses that do address A/P translation, a cam mechanism against the joint-linking mechanism (usually a post) or against the tibial articular geometry is used to force the tibia anteriorly relative to the distal femur as the knee flexes. This method of A/P translation is common in a primary total knee arthroplasty (TKA) by the use of a cam and post method in which the cam is on the femoral articulating prosthesis and the post is found on the tibial articulating prosthesis. This is commonly referred to as a posterior or cruciate stabilized knee implant. These hinged knees generally focus forces on a small area (such as a cam with point and/or line contact and post), which may increase wear and decrease the life span of the implant.

In U.S. Pat. Nos. 5,358,527 and 5,800,552, A/P translation is allowed through flexion, yet the hinged knee does not

2

control and/or maintain a constant limit on A/P translation. In other words, the femoral can be flexed and can translate posteriorly when contact to the tibial bearing surface is not maintained. Thus, the femoral component does not maintain contact with the tibial component when A/P translation occurs.

There remains a need in the art for kinematically-correct prostheses including A/P translation and/or normal axial rotation. In addition, there remains a need for kinematically-correct prostheses that reduce wear on the prosthesis and reduce forces on the remaining soft tissue.

SUMMARY

The disclosure provides a hinged knee prosthesis comprising a tibial component and a femoral component. The tibial component is configured to attach to a tibia. The tibial component has a bearing surface. The femoral component is configured to hingedly attach to the tibial component and rotate relative to the tibial component. The femoral component comprises a medial condyle and a lateral condyle. The medial and lateral condyles have a sagittal curvature surface configured to induce axial rotation on the bearing surface of the tibial component.

The medial and lateral condyles may have a plurality of eccentric sagittal curvature surfaces configured to rotate on the bearing surface of the tibial component.

The bearing surface of the tibial component is configured with an anterior portion and a posterior portion. The posterior portion of the bearing surface has a portion configured to guide the medial and lateral condyles of the femoral component. Contact points between the femoral component and the tibial component translate in the anterior/posterior direction and rotate axially.

The hinged knee may further comprise an axle hinge pin. The axle hinge pin is located transversely between the medial and lateral condyles. The eccentric sagittal curvature surface has a center of rotation not aligned with the axle hinge pin.

The hinged knee prosthesis may further comprise a post configured to extend from the tibial component to the femoral component. A proximal portion of the post is configured to attach to the axle hinge pin.

The center of rotation of a portion of the eccentric sagittal curvature surface of the medial condyle may not be aligned with the center of rotation of a portion of the eccentric sagittal curvature surface of the lateral condyle. The medial and lateral condyles direct axial rotation of the femoral component relative to the tibial component.

The center of rotation of a portion of the eccentric sagittal curvature surface of the medial condyle may be aligned with the center of rotation of a portion of the eccentric sagittal curvature surface of the lateral condyle, wherein the medial and lateral condyles direct anterior/posterior translation of the femoral component relative to the tibial component.

The medial condyle of the femoral component may further comprise a concentric sagittal curvature surface. The center of rotation of the concentric sagittal curvature surface of the medial condyle is not aligned with the center of rotation of a portion of the eccentric sagittal curvature surface of the lateral condyle. The medial and lateral condyles direct axial rotation of the femoral component relative to the tibial component.

The center of rotation of a first eccentric sagittal curvature surface of the medial condyle may not be aligned with the center of rotation of a first eccentric sagittal curvature surface of the lateral condyle. The medial and lateral con-

3

dyles direct axial rotation and anterior/posterior translation of the femoral component relative to the tibial component when the first eccentric sagittal curvature surfaces contact the tibial component. The center of rotation of a second eccentric sagittal curvature surface of the medial condyle is aligned with the center of rotation of a second eccentric sagittal curvature surface of the lateral condyle, wherein the medial and lateral condyles direct anterior/posterior translation of the femoral component relative to the tibial component when the second eccentric sagittal curvature surfaces contact the tibial component.

The hinged knee prosthesis may comprise a sleeve configured to receive the post. The sleeve is configured to allow axial rotation of the femoral component relative to the tibial component.

The disclosure provides a method of rotating a hinged knee through a range of flexion. The method fixedly attaches a femoral component to a tibial component. Axial rotation of the femoral component is induced relative to the tibial component when the hinged knee is flexed.

The method may further comprise the step of inducing translation of the femoral component in an anterior/posterior direction relative to the tibial component when the hinged knee is flexed.

The inducing translation step and the inducing axial rotation steps may occur simultaneously.

The inducing axial rotation step may occur through a portion of the range of flexion of the prosthetic knee.

The inducing axial rotation step may occur through a first portion of the range of flexion of the prosthetic knee and a second portion of the range of flexion of the prosthetic knee.

The first portion of the range of flexion may not be adjacent to the second portion of the range of flexion.

The inducing axial rotation step may occur at varying angular velocities as the hinged knee passes through the range of flexion of the knee.

The fixedly attaching step may include connecting a sleeved post to the tibial insert such that a sleeved portion of the sleeved post and a post portion of the sleeved post axially rotate relative to each other. Further the fixedly attaching step may include fixing an axial hinge pin to the sleeved post such that the axial hinge pin transversely connects a medial condyle of the femoral component to the lateral condyle of the femoral component.

The method may further comprise the step of fixing the sleeved portion of the sleeved post to a stem in the tibial component.

The method may further comprise the step of axially displacing the sleeved portion of the sleeved post relative to the post portion of the sleeved post when the hinged knee is flexed.

Thus, kinematically-correct prostheses including A/P translation and/or normal axial rotation may be achieved by the structures in the disclosure. These kinematically-correct prostheses may reduce wear on the prosthesis and reduce forces on the remaining soft tissue. Further features, aspects, and advantages of the present invention, as well as the structure and operation of various embodiments of the present invention, are described in detail below with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and form a part of the specification, illustrate embodiments and together with the description, serve to explain the principles of the invention. In the drawings:

4

FIG. 1 is an isometric view of an embodiment of a hinged knee;

FIG. 2 is a cutaway view of the embodiment of FIG. 1;

FIG. 3 is a side view of the embodiment of FIG. 1;

FIG. 4 is a cutaway view of the embodiment of FIG. 3;

FIG. 5 is an isometric view of an embodiment of a hinged knee;

FIG. 6 is a cutaway view of the embodiment of FIG. 5;

FIG. 7 is a side view of the embodiment of FIG. 5;

FIG. 8 is a cutaway view of the embodiment of FIG. 7;

FIG. 9 is an isometric view of an embodiment of a tibial insert;

FIG. 10 is a top view of the tibial insert of FIG. 9;

FIG. 11 is a side view of an embodiment of femoral component of a hinged knee;

FIGS. 12 and 13 are a side view and an isometric view, respectively, of an embodiment of a hinged knee at extension;

FIGS. 14 and 15 are a side view and an isometric view, respectively, of the hinged knee of FIG. 12 at 20 degrees flexion;

FIGS. 16 and 17 are a side view and an isometric view, respectively, of the hinged knee of FIG. 12 at 40 degrees flexion;

FIGS. 18 and 19 are a side view and an isometric view, respectively, of the hinged knee of FIG. 12 at 90 degrees flexion;

FIGS. 20 and 21 are a side view and an isometric view, respectively, of the hinged knee of FIG. 12 at 120 degrees flexion;

FIGS. 22 and 23 are a side view and an isometric view, respectively, of the hinged knee of FIG. 12 at 150 degrees flexion;

FIGS. 24-26 are a side view, an isometric view, and a top view, respectively, of an embodiment of a hinged knee at extension;

FIGS. 27-29 are a side view, an isometric view, and a top view, respectively, of the hinged knee of FIG. 27 at 20 degrees flexion;

FIGS. 30-32 are a side view, an isometric view, and a top view, respectively, of the hinged knee of FIG. 27 at 40 degrees flexion;

FIGS. 33-35 are a side view, an isometric view, and a top view, respectively, of the hinged knee of FIG. 27 at 90 degrees flexion;

FIGS. 36-38 are a side view, an isometric view, and a top view, respectively, of the hinged knee of FIG. 27 at 120 degrees flexion; and

FIGS. 39-41 are a side view, an isometric view, and a top view, respectively, of the hinged knee of FIG. 27 at 150 degrees flexion.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Referring to the accompanying drawings in which like reference numbers indicate like elements, FIGS. 1-4 show views of an embodiment of a hinged knee.

Turning now to FIG. 1, FIG. 1 is an isometric view of an embodiment of a hinged knee 10. The hinged knee 10 includes a femoral component 14, a tibial component 16, a pin sleeve 18 and a pin 20. The tibial component 16 includes a tibial insert 24 and a tibial base 26. The femoral component 14 includes a medial condyle 30 and a lateral condyle 32. The pin 20 connects the condyles 30 and 32 to the sleeve 18. The sleeve 18 connects to the tibial component through a sleeved post (discussed below).

5

As the knee flexes, the femoral component **14** rotates relative to the tibial component **16**. The femoral component **14** rotates about the pin **20**. Axial rotation and anterior/posterior (A/P) translation of the femoral component **14** is urged by the shape of the tibial insert **24** and the condyles **30** and **32**. The axial rotation and anterior/posterior (A/P) translation of the femoral component **14** may occur because the pin **20** is able to axial rotate and be axially translated relative to the post and sleeve of the hinged knee **10**.

The femoral component **14** and the tibial component **16** are connected to the femur and tibia, respectively. Stems **36** are inserted into the femur and tibia to fix the femoral component and tibial component to the bones. The length and thickness of these stems may be adjusted based upon required fixation, size of the bones, and size of the intramedullary canals in the bones.

Turning now to FIG. 2, FIG. 2 is a cutaway view of the embodiment of FIG. 1. The cutaway is taken in a sagittal plane between the femoral condyles. FIG. 2 shows the pin **20** in the sleeve **18**. The sleeve **18** is attached to a post sleeve **40** which surrounds a post **42**. The post **42** is attached to the tibial base **26**, and may be attached asymmetrically to the tibial base **26**. The post sleeve **40** may be axially rotated and axially translated relative to the post **42**. The sleeve **18** (and thus the pin **20**) may rotate axially and translate axially relative to the tibial component **16**. The rotation and translation allow for the femoral component **14** to axially rotate and to translate in the A/P direction. The A/P translation may be accomplished by the condyle surface having a curvature with a center of rotation outside the pin **20**. As the femoral component **14** rotates, a bushing **46** stops hyper extension so that the knee may not overextend.

Turning now to FIG. 3, FIG. 3 is a side view of the embodiment of FIG. 1. The pin **20** is located posterior to the center of the knee **10**. The curve **50** of the condyle **32** is eccentric with respect to the center of rotation of the femoral component **14**, which is the pin **20**. With respect to the tibial component **16**, the pin **20** axially rotates and axially translates as the knee flexes.

Turning now to FIG. 4, FIG. 4 is a cutaway view of the embodiment of FIG. 3. The cutaway is taken along the same sagittal plane of the cutaway in FIG. 2. The cutaway shows the post sleeve **40** and post **42** of the hinged knee **10**. A screw **56** fixes a post receiver **58** to the post to lock the post sleeve **40** on the post **42**. The post sleeve **40** and pin sleeve **18** then may rotate and translate axially without pulling off the post **42**.

Turning now to FIGS. 5-8, these FIGs. show views of another embodiment of a hinged knee **70**. Turning now to FIG. 5, FIG. 5 is an isometric view of an embodiment of the hinged knee **70**. The hinged knee **70** includes a femoral component **74**, a tibial component **76**, a pin sleeve **78** and a pin **80**. The tibial component **76** includes a tibial insert **84** and a tibial base **86**. The femoral component **74** includes a medial condyle **90** and a lateral condyle **92**. The pin **80** connects the condyles **90** and **92** to the sleeve **78**. The sleeve **78** connects to the tibial component through a sleeved post.

As the knee flexes, the femoral component **74** rotates relative to the tibial component **76**. The femoral component **74** rotates about the pin **80**. Axial rotation and anterior/posterior (A/P) translation of the femoral component **74** is urged by the shape of the tibial insert **84** and the condyles **90** and **92**. The axial rotation and anterior/posterior (A/P) translation of the femoral component **74** may occur because the pin **80** is able to axially rotate and be axially translated relative to the post and sleeve of the hinged knee **70**.

6

The femoral component **74** and the tibial component **76** are connected to the femur and tibia, respectively. Stems **96** are inserted into the femur and tibia to fix the femoral component and tibial component to the bones. The length and thickness of these stems may be adjusted based upon required fixation, size of the bones, and size of the intramedullary canals in the bones.

Turning now to FIG. 6, FIG. 6 is a cutaway view of the embodiment of FIG. 5. The cutaway is taken in a sagittal plane between the femoral condyles. FIG. 6 shows the pin **80** in the sleeve **78**. The sleeve **78** is attached to a post **100** which is inserted into a post sleeve **102**. The post sleeve **102** is attached to the tibial base **86**. The post **100** may be axially rotated and axially translated relative to the post sleeve **102**. The pin sleeve **78** (and thus the pin **80**) may rotate axially and translate axially relative to the tibial component **76**. The rotation and translation allow for the femoral component **74** to axially rotate and to translate in the A/P direction. The A/P translation may be accomplished by the condyle surface having a curvature with a center of rotation outside the pin **80**. As the femoral component **74** rotates, a bushing **106** stops hyper extension so that the knee may not overextend.

Turning now to FIG. 7, FIG. 7 is a side view of the embodiment of FIG. 5. The pin **80** is located posterior to the center of the knee **70**. The curve **110** of the condyle **92** is eccentric with respect to the center of rotation of the femoral component **74**, which is the pin **80**. With respect to the tibial component **76**, the pin **80** axially rotates and axially translates as the knee flexes.

Turning now to FIG. 8, FIG. 8 is a cutaway view of the embodiment of FIG. 7. The cutaway is taken along the same sagittal plane of the cutaway in FIG. 6. The cutaway shows the post **100** and post sleeve **102** of the hinged knee **70**. An enlarged portion **106** of the post **100** fixes the post **100** to the femoral component **74** so that when the post **100** is inserted in the post sleeve **102**, the femoral component **74** is aligned and held in place relative to the tibial component **76**. The post **100** and pin sleeve **78** then may rotate and translate axially without pulling the femoral component **74** off the tibial base **76**.

Turning now to FIGS. 9 and 10, these FIGs. show views of a tibial insert **120**. FIG. 9 is an isometric view of an embodiment of a tibial insert **120** and FIG. 10 is a top view of the tibial insert **120** of FIG. 9. The tibial insert **120** includes a post hole **124** for receiving the post from either the tibial base or the femoral component. Direction lines **126** on a bearing surface **128** show the lines the femoral component articulates on the tibial insert **120**. As the femoral component rotates on the insert **120**, the position on the line **126** travels posteriorly. The posterior portion of the tibial insert **120** slopes to axially rotate and translate the femoral component posteriorly. Together in conjunction with the curvature of the condyles, the tibial insert **120** cause A/P translation and axial rotation of the femoral component.

Turning now to FIG. 11, FIG. 11 is a side view of an embodiment of femoral component **130** of a hinged knee. The curvature of a condyle **131** includes a first distal portion **132** having a first center of rotation **134**, a second posterior portion **136** having a second center of rotation **138** concentric with a pin hole **140**, and a third proximal portion **142** having a third center of rotation **144**. The centers of rotation **134** and **144** are eccentric to the pin hole **140**. As the knee rotates, the contact point between the femoral component **130** and the tibial insert produces a force normal to the femoral component **130** and aligned with the center of rotation for that section of the curvature. While the contact point is within the distal portion of the curvature, the normal

force points toward the center of rotation **134**. At the interface between the distal portion **132** and the posterior portion **136**, the normal force is collinear with the centers of rotation **134** and **138**. Similarly, at the interface between the posterior portion **136** and the proximal portion **142**, the normal force is collinear with the centers of rotation **138** and **144**. Thus, the contact points do not jump during rotation but smoothly move.

The eccentricity of the curvatures allows for the lateral forces at the contact points to control axial rotation and A/P translation. Because the forces are normal to the tibial and femoral surfaces, reactive forces at the contact points induce A/P motion and axial rotation. The pins, sleeves, and posts of the hinged knee allow for the translation and rotation of the femoral component **130** with respect to the tibial component.

Turning now to FIGS. **12-23**, the FIGs. show side views and isometric views of an embodiment of a hinged knee in different angles of flexion. FIGS. **12** and **13** are a side view and an isometric view, respectively, of an embodiment of a hinged knee at extension. A contact point **150** anterior to the pin axis is the contact point between a femoral component **152** and a tibial component **154**. The tibial component is posteriorly distal sloped at the contact point **150** so there is a reactive contact force attempting to push the femoral component backwards. FIG. **13** shows the position of the femoral component **152** at extension.

Turning now to FIGS. **14** and **15**, FIGS. **14** and **15** are a side view and an isometric view, respectively, of the hinged knee of FIG. **12** at 20 degrees flexion. As the knee flexes, the contact point **150** moves posteriorly. Additionally, as shown in FIG. **15**, the femoral component **152** has rotated relative to the tibial component **154**. The axial rotation is urged by a differential between the moments created by the reactive forces at the medial and lateral condyles.

Turning now to FIGS. **16** and **17**, FIGS. **16** and **17** are a side view and an isometric view, respectively, of the hinged knee of FIG. **12** at 40 degrees flexion. The contact point **150** has shifted posteriorly and the femoral component has continued to rotate axially. This change in contact point shows the A/P translation of the femoral component as the knee rotates. While most of the motion during early knee flexion is axial rotation, some A/P translation occurs. This "rollback" and rotation is similar to normal joint kinematics. These movements are urged by the shapes of the tibial and femoral component. This minimizes shear forces on the patella which may otherwise try to force these movements of the femoral components. Generation of the shear forces in the patella may cause pain or prosthetic failure.

The contact force **150** is directed through the center of the pin hole as the curvature of the condyle transitions from the distal eccentric portion to the posterior concentric portion discussed with reference to FIG. **11**.

Turning now to FIGS. **18** and **19**, FIGS. **18** and **19** are a side view and an isometric view, respectively, of the hinged knee of FIG. **12** at 90 degrees flexion. While flexion continues through the concentric portion, the A/P translation and axial rotation stops. The distance to the center of the pin hole remains constant as the center of curvature for the posterior portion of the condyle is concentric with the pin hole.

Turning now to FIGS. **20** and **21**, FIGS. **20** and **21** are a side view and an isometric view, respectively, of the hinged knee of FIG. **12** at 120 degrees flexion. The contact force **150** is directed through the center of the pin hole as the curvature of the condyle transitions from the posterior concentric portion of the curvature to the proximal eccentric portion discussed with reference to FIG. **11**. As the contact

force **150** moves posterior the center of the pin hole, the distance from the contact point to the center of the pinhole lessens.

Turning now to FIGS. **22** and **23**, FIGS. **22** and **23** are a side view and an isometric view, respectively, of the hinged knee of FIG. **12** at 150 degrees flexion. As the hinged knee continues to rotate, the contact force generally creates A/P translation, and little axial rotation. Again, this is generally consistent with normal knee kinematics. While this embodiment has described A/P translation and axial rotation by surface characteristics of the tibial and femoral components **154** and **152**, other embodiments may accomplish these motions in other ways.

The additional embodiments generally try to control lateral forces between the femoral and tibial components. For example, differences in the lateral forces between condyles may create motion. Additionally keeping lateral forces on one side small or zero while controlling the forces on the other side can control axial rotation. For more rotation, forces may be opposite in direction to increase axial rotation. Because rotation is controlled by moments, another method of controlling rotation is to control the moment arms.

Another embodiment may create contact points with corresponding tibial articulation of the femoral articulating surfaces to vary from a plane perpendicular to the transverse axle hinge pin. Generally, the plane would extend through a medial/lateral and/or lateral/medial direction. As the knee moves through the range of motion of the knee, the corresponding insert articulating geometry remains parallel or varies from the same plane creating an axial rotation through whole, in part, and/or various ranges of the range of motion of the joint.

In another embodiment, a concentric sagittal curvature of the medial or lateral femoral condyle's articular surface relative to the transverse hinge pin location and the opposite femoral condyle's articular surface may have eccentric curvature sagittally to the hinge pin location. This shifts the contact with the tibial articulation medial/lateral or lateral/medial at least in part through a range of motion. The tibial articulating surfaces correspond to femoral curvatures and induce axial rotation through whole, in part, and/or various ranges of the range of motion of the joint.

Alternatively, a concentric sagittal curvature of the medial or lateral condyle's articular surface relative to the transverse hinge pin location and the opposite condyle's articular surface having eccentric curvature sagittally to the hinge pin location may create the motion. The tibial articulating surfaces corresponds to femoral curvatures where the corresponding eccentric medial or lateral compartment follows a predetermined path relative to multiple angles of flexion and its corresponding contact points movement. The radial translation of these contact points around the axial rotation around the tibial post/sleeve axis and the corresponding concentric medial or lateral compartment follows a predetermined path relative to multiple angles of flexion and its corresponding contact point's movement around the axial rotation around the tibial post/sleeve axis. This induces an axial rotation through whole, in part, and/or various ranges of the range of motion of the joint.

Another embodiment includes a femoral prosthesis with eccentric sagittal curvature for both of the medial and lateral articulating condylar portions of the femoral prosthesis relative to the transverse axle pin position. A tibial insert with the corresponding articulating geometry, either inclining and/or declining as the eccentric contact points of the femoral articulation translates, shift in a medial/lateral and/

or lateral/medial direction to induce an axial rotation through whole, in part, and/or various ranges of the range of motion of the joint.

In another embodiment, a concentric sagittal curvature of the medial or lateral condyle's articular surface relative to the transverse hinge pin location and the opposite condyle's articular surface having eccentric curvature sagittally to the hinge pin location. The tibial articulating surfaces correspond to femoral curvatures where the corresponding eccentric medial or lateral compartment follows a predetermined path relative to multiple angles of flexion and its corresponding contact points movement and the radial translation of these contact points around the axial rotation around the tibial post/sleeve axis. The corresponding concentric medial or lateral compartment follows a predetermined inclining and/or declining path relative to multiple angles of flexion and its corresponding contact points movement around the axial rotation around the tibial post/sleeve axis which induces an axial rotation through whole, in part, and/or various ranges of the range of motion of the joint.

Alternatively, a femoral prosthesis with concentric sagittal curvature for both of the medial and lateral articulating condylar portions of the femoral prosthesis relative to the transverse pin position. A tibial insert with the corresponding articulating geometry, either inclining and/or declining, form an axial rotating path relative to the femoral articulating surfaces. Translational/rotational freedom allows the transverse pin to rotate and translate the femoral prosthesis.

Turning now to FIGS. 24-41, the FIGs. Show side views, isometric views, and top views of an embodiment of a hinged knee in different angles of flexion. FIGS. 24-26 are a side view, an isometric view, and a top view, respectively, of an embodiment of a hinged knee at extension. A femoral component 180 rotates about a pin 182 relative to a tibial component 184. Contact areas 200 show the area in which a tibial insert 186 may contact the femoral component 180. The contact areas 200 in FIGS. 24-41 show how the femoral component 180 rotates and translates along the tibial insert 186.

Turning now to FIGS. 27-29, FIGS. 27-29 are a side view, an isometric view, and a top view, respectively, of the hinged knee of FIG. 27 at 20 degrees flexion. The femoral component 180 continues to rotate about the pin 182 relative to the tibial component 184. The contact areas 200, particularly the lateral contact area, have rolled back. The roll back of the lateral contact area corresponds to axial rotation of the femoral component 180 relative to the tibial component 184.

Turning now to FIGS. 30-32, FIGS. 30-32 are a side view, an isometric view, and a top view, respectively, of the hinged knee of FIG. 27 at 40 degrees flexion. The femoral component 180 continues to rotate about the pin 182 relative to the tibial component 184. The contact areas 200 have continued to roll back, and again the lateral contact area has translated farther posteriorly compared to the medial condyle. This corresponds to more axial rotation.

Turning now to FIGS. 33-35, FIGS. 33-35 are a side view, an isometric view, and a top view, respectively, of the hinged knee of FIG. 27 at 90 degrees flexion. The femoral component 180 continues to rotate about the pin 182 relative to the tibial component 184. From 40 degrees to 90 degrees of flexion, the rotation and translation are minimized as the rotation continues through the concentric portion of the curvature.

Turning now to FIGS. 36-38, FIGS. 36-38 are a side view, an isometric view, and a top view, respectively, of the hinged knee of FIG. 27 at 120 degrees flexion. The femoral component 180 continues to rotate about the pin 182 relative to

the tibial component 184. Similar to the flexion between 40 and 90 degrees, from 90 degrees to 120 degrees of flexion, the rotation and translation are minimized as the rotation continues through the concentric portion of the curvature.

Turning now to FIGS. 39-41, FIGS. 39-41 are a side view, an isometric view, and a top view, respectively, of the hinged knee of FIG. 27 at 150 degrees flexion. The femoral component 180 continues to rotate about the pin 182 relative to the tibial component 184. As the flexion continues from 120 to 150 degrees, the contact areas 200 translate and have little axial rotation.

Thus, as the knee flexes, the rotation allows for the patella to slide along the patellar groove without generating forces in the patella. Additionally, with movement approximating the natural movement, the hinged knee does not generate forces in the soft tissue. This may help preserve soft tissue that is initially damaged by surgery. Moreover, some soft tissue is removed during surgery, and thus the remaining soft tissue must work harder to complete tasks. Reducing the forces on soft tissue can reduce swelling, pain and additional stresses on the soft tissue after surgery.

In view of the foregoing, it will be seen that the several advantages of the invention are achieved and attained.

The embodiments were chosen and described in order to best explain the principles of the invention and its practical application to thereby enable others skilled in the art to best utilize the invention in various embodiments and with various modifications as are suited to the particular use contemplated.

As various modifications could be made in the constructions and methods herein described and illustrated without departing from the scope of the invention, it is intended that all matter contained in the foregoing description or shown in the accompanying drawings shall be interpreted as illustrative rather than limiting. Thus, the breadth and scope of the present invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims appended hereto and their equivalents.

The invention claimed is:

1. A knee prosthesis comprising:

- a tibial component configured to attach to a patient's tibia, the tibial component including a bearing surface with a posterior portion, the posterior portion including medial and lateral posterior portions each having a contour that slopes medially in a posterior direction, the tibial component having a superior-inferior axis; and
- a femoral component configured to attach to a patient's femur, the femoral component being hingeably coupled to the tibial component so that the femoral component translates in an anterior/posterior (A/P) direction relative to the tibial component and axially rotates relative to the tibial component about the superior-inferior axis, the femoral component comprising:

- a medial condyle and a lateral condyle, wherein the medial condyle includes a concentric sagittal curvature surface, the lateral condyle including an eccentric sagittal curvature surface, and a center of rotation of the concentric sagittal curvature surface of the medial condyle is not aligned with the center of rotation of a portion of the eccentric sagittal curvature surface of the lateral condyle.

2. The knee prosthesis of claim 1, wherein the medial condyle and the bearing surface define a medial contact surface where the medial condyle contacts the bearing surface and the lateral condyle and the bearing surface

11

define a lateral contact surface where the lateral condyle contacts the bearing surface; and

wherein, in use, the lateral contact surface rolls back to a greater extent than the medial contact surface so that the lateral condyle translates to a greater extent posteriorly relative to the medial condyle.

3. The knee prosthesis of claim 1, further comprising an insert positioned between the tibial component and the femoral component, the insert including the bearing surface.

4. The knee prosthesis of claim 1, further comprising a pin, the femoral component rotates about the pin relative to the tibial component.

5. The knee prosthesis of claim 4, wherein the pin is arranged and configured to axially rotate and axially translate in the A/P direction to enable rotation and translation of the femoral component relative to the tibial component.

6. The knee prosthesis of claim 4, wherein the femoral component includes a pin sleeve, the pin being positioned within the pin sleeve for coupling the pin sleeve to the medial and lateral condyles.

7. The knee prosthesis of claim 6 further comprising a post passing through a portion of the pin sleeve and into the tibial component.

12

8. The knee prosthesis of claim 7, wherein the pin sleeve includes an opening formed therein, the post passing through the opening for coupling the pin sleeve to the tibial component.

9. The knee prosthesis of claim 8, wherein the post extends from the tibial component.

10. The knee prosthesis of claim 8, wherein the post is asymmetrically positioned relative to the tibial component.

11. The knee prosthesis of claim 8, further comprising a post sleeve for coupling the post to the pin sleeve, the post sleeve being positioned between the post and the opening formed in the pin sleeve.

12. The knee prosthesis of claim 11, wherein the post sleeve is arranged and configured to rotate and translate relative to the post.

13. The knee prosthesis of claim 12, wherein the pin is arranged and configured to rotate and translate relative to the post and the post sleeve.

14. The knee prosthesis of claim 4, wherein the pin is positioned posteriorly relative to a center of the knee prosthesis.

* * * * *