



US 20250256866A1

(19) **United States**

(12) **Patent Application Publication**
Schuster et al.

(10) **Pub. No.: US 2025/0256866 A1**

(43) **Pub. Date: Aug. 14, 2025**

(54) **SYSTEMS FOR HUMAN WASTE
COLLECTION AND PROCESSING**

Publication Classification

(51) **Int. Cl.**
B64G 1/60 (2006.01)
A47K 11/02 (2006.01)
(52) **U.S. Cl.**
CPC **B64G 1/60** (2013.01); **A47K 11/02**
(2013.01)

(71) Applicant: **Hamilton Sundstrand Space Systems
International, Inc.**, Windsor Locks, CT
(US)

(72) Inventors: **Ashley Rose Himmelmann Schuster**,
Chicago, IL (US); **Beakal Teshome
Woldemariam**, South Windsor, CT
(US); **Thao Hoang**, Arlington, WA
(US); **Timothy Monson**, Winnebago, IL
(US); **Kevin Litton**, Houston, TX (US);
Thomas Gay, Enfield, CT (US); **Casey
Myers**, Parker, CO (US); **Liana J. He**,
West Hartford, CT (US)

(21) Appl. No.: **18/734,368**


(22) Filed: **Jun. 5, 2024**

Related U.S. Application Data

(60) Provisional application No. 63/552,255, filed on Feb.
12, 2024.

(57) **ABSTRACT**

Waste collection and processing systems for use in low-gravity environments include a toilet having a bowl and a lid; a waste tank having an inlet and an outlet, with the bowl fluidly coupled to the inlet of the waste tank; a first valve arranged between the bowl and the waste tank and selectively operable to allow fluid connection between the bowl and the waste tank; a second valve arranged at a first outlet of the waste tank and selectively operable to allow for solid waste and liquid waste within the waste tank to be directed to a waste outlet; and a third valve arranged at a second outlet of the waste tank and selectively operable to allow for gases to be removed from the waste tank and directed to at least one of an occupied space, an external environment, or a waste reclamation system.






FIG. 1





FIG. 2



മെ




FIG. 4




FIG. 5





FIG. 6

**FIG. 7**




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

SYSTEMS FOR HUMAN WASTE COLLECTION AND PROCESSING

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Patent Application No. 63/552,255 filed Feb. 12, 2024, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

[0002] The subject matter disclosed herein generally relates to systems for collection and processing of human waste and, more particularly, to various systems and collection devices for processing human waste in low-gravity and/or space environments.

[0003] When humans reside in relatively closed spaces or environments (e.g., on ships, aircraft, spacecraft, stations, habitats, etc.), or in remote locations or the like, human waste must be managed to avoid contamination or disease and to ensure sanitary conditions for human safety. If conventional plumbing is not required or possible, or there are environmental impacts to plumbing functionality, specific or uniquely designed systems may be required to manage human waste. For example, when in low, micro, or no gravity environments (e.g., in space or on non-Earth celestial bodies), a lack of gravity or reduced gravity may prevent conventional plumbing from being employed, as such systems may rely upon gravity for operation thereof. Further, due to a lack of gravitational force, containment of liquids and solids is an important consideration, particularly for containment of waste that can pose health or other hazards or risks. Additionally, due to the limitations of closed-system environments, particularly in spacecraft, processing of waste and reclamation of water may be important for reducing the total consumable load of the platform.

[0004] In current space-based applications, four systems (i.e., a toilet, a urine processor assembly, a brine processor assembly, and a fecal processor assembly) are required to most thoroughly collect, store, and process human waste. For use of these systems, the toilet requires separate collection of urine (liquid) and non-urine waste (liquid, solid, etc.). Requiring separate collection of urine and non-urine waste streams results in complex requirements and design constraints on the space toilet solution including separate urine and non-urine waste collection ports, which may not be intuitive or as user-friendly as terrestrial designs, particularly for women. Separate urine and non-urine waste collection ports minimizes the ability to reuse hardware and system configurations from terrestrial applications, such as components used for aircraft lavatories or the like. Accordingly, improved systems for waste capture and processing may be advantageous in a variety of applications, including systems that are used in low-gravity environments (e.g., in space).

SUMMARY

[0005] Embodiments of the present disclosure are directed to waste collection and processing systems and related methods of use. The systems described herein may be implemented and installed and used for space-based applications, such as in low-gravity environments, zero-gravity environments, low-gravity surface environments, and the

like. Embodiments of the present disclosure provide for improved systems that may reduce weight and complexity while improving system efficiency related to recapture of air and/or water from human waste.

[0006] According to some embodiments, waste collection and processing systems for use in low-gravity environments are provided. The waste collection and processing system include a toilet having a bowl and a lid; a waste tank having an inlet and an outlet, wherein the bowl of the toilet is fluidly coupled to the inlet of the waste tank; a first valve arranged between the bowl and the waste tank, the first valve selectively operable to allow fluid connection between the bowl and the waste tank; a second valve arranged at a first outlet of the waste tank, the second valve selectively operable to allow for solid waste and liquid waste within the waste tank to be directed to a waste outlet; and a third valve arranged at a second outlet of the waste tank, the third valve selectively operable to allow for gases to be removed from the waste tank and directed to at least one of an occupied space, an external environment, or a waste reclamation system.

[0007] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include a fan arranged to pull air and waste gases through the bowl, into and through the waste tank, and through the third second outlet of the waste tank.

[0008] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include a filter assembly arranged downstream from the second outlet of the waste tank, the filter assembly configured to remove odor and moisture from the gases received from the waste tank.

[0009] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include that the occupied space is part of a spacecraft.

[0010] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include that the occupied space is part of a space station.

[0011] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include a controller configured to control operation of the first valve, the second valve, and the third valve.

[0012] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include a switch configured to be actuated to activate the controller.

[0013] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include that the switch is integrated with the toilet and actuated by opening and closing of the lid.

[0014] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include that the waste reclamation system includes a condenser arranged to cool a flow of gases received from the waste tank and condense moisture from the flow of gases; a settling tank arranged to receive an output from the condenser and separate the condensed moisture from gases received from the condenser; and a gas processing system arranged to

process gases received from the settling tank, the gas processing system configured to direct treated air into the occupied space.

[0015] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include that the waste reclamation system further comprises a liquid processing system configured to generate treated liquid and direct the treated liquid to a liquid outlet.

[0016] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include at least one fluid injector arranged to inject at least one of water, cleaning fluid, and waste treatment fluid into at least one of the bowl and a flow path between the bowl and the waste tank.

[0017] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include a de-mister arranged at the second outlet of the waste tank and upstream from the third valve, the de-mister configured to remove moisture from a flow of gas exiting the waste tank through the second outlet.

[0018] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include that the waste tank fluidly connected to the toilet is a first waste tank and the toilet and the first waste tank define a solid waste collection system of the waste collection and processing system. The waste collection and processing system further includes a liquid waste collection system having a liquid waste receptacle; a second waste tank fluidly connected to the liquid waste receptacle; and a fourth valve arranged between the liquid waste receptacle and the second waste tank, wherein gases removed from the second waste tank are directed to at least one of the occupied space, the external environment, or the waste reclamation system.

[0019] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include a fifth valve arranged at a first outlet of the second waste tank between the second waste tank and a second waste outlet; and a sixth valve at a second outlet of the second waste tank and configured to control of flow of gases from the second waste tank through the second outlet of the second waste tank.

[0020] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include a de-mister arranged at the second outlet of the second waste tank and upstream from the sixth valve, the de-mister configured to remove moisture from a flow of gas exiting the second waste tank through the second outlet of the second waste tank.

[0021] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include at least one fluid injector arranged to inject at least one of water, cleaning fluid, and waste treatment fluid into at least one of the liquid waste receptacle and a flow path between the liquid waste receptacle and the second waste tank.

[0022] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include that

the waste tank is a first waste tank configured to receive solid waste, the waste collection and processing system further includes a urine capture element arranged within the bowl of the toilet; and a second waste tank fluidly connected to the urine capture element.

[0023] In addition to one or more of the features described herein, or as an alternative, further embodiments of the waste collection and processing systems may include a heater operably connected to the waste tank to provide heating thereto.

[0024] According to some embodiments, methods of waste collection and processing in low-gravity environments are provided. The methods include receiving human waste in a toilet having a bowl and a lid; collecting and directing the human waste from the bowl into a waste tank that is fluidly connected to the bowl by opening a first valve arranged between the bowl and an inlet to the waste tank; capturing liquid waste and solid waste within the waste tank; directing the liquid waste and solid waste to a waste outlet by opening a second valve arranged between a first outlet of the waste tank and the waste outlet; and directing air and gaseous waste out of the waste tank by opening a third valve, the air and gaseous waste being directed to at least one of an occupied space, an external environment, or a waste reclamation system.

[0025] In addition to one or more of the features described herein, or as an alternative, further embodiments of the methods may include that treating the air and gaseous waste prior to directing treated air to the occupied space.

[0026] The foregoing features and elements may be combined in various combinations without exclusivity, unless expressly indicated otherwise. These features and elements as well as the operation thereof will become more apparent in light of the following description and the accompanying drawings. It should be understood, however, that the following description and drawings are intended to be illustrative and explanatory in nature and non-limiting.

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] The subject matter is particularly pointed out and distinctly claimed at the conclusion of the specification. The foregoing and other features, and advantages of the present disclosure are apparent from the following detailed description taken in conjunction with the accompanying drawings in which:

[0028] FIG. 1 is a schematic illustration of a first illustrative configuration of a waste collection and processing system in accordance with the present disclosure;

[0029] FIG. 2 is a schematic illustration of a second illustrative configuration of a waste collection and processing system in accordance with the present disclosure;

[0030] FIG. 3 is a schematic illustration of a third illustrative configuration of a waste collection and processing system in accordance with the present disclosure;

[0031] FIG. 4 is a schematic illustration of a fourth illustrative configuration of a waste collection and processing system in accordance with the present disclosure;

[0032] FIG. 5 is a schematic illustration of a fifth illustrative configuration of a waste collection and processing system in accordance with the present disclosure;

[0033] FIG. 6 is a schematic illustration of a sixth illustrative configuration of a waste collection and processing system in accordance with the present disclosure;

[0034] FIG. 7 is a schematic illustration of a seventh illustrative configuration of a waste collection and processing system in accordance with the present disclosure;

[0035] FIG. 8 is a schematic illustration of an eighth illustrative configuration of a waste collection and processing system in accordance with the present disclosure;

[0036] FIG. 9 is a schematic illustration of a ninth illustrative configuration of a waste collection and processing system in accordance with the present disclosure;

[0037] FIG. 10 is a schematic illustration of a tenth illustrative configuration of a waste collection and processing system in accordance with the present disclosure;

[0038] FIG. 11 is a schematic illustration of an eleventh illustrative configuration of a waste collection and processing system in accordance with the present disclosure; and

[0039] FIG. 12 is a schematic illustration of a twelfth illustrative configuration of a waste collection and processing system in accordance with the present disclosure.

DETAILED DESCRIPTION

[0040] When humans reside in relatively closed spaces or environments (e.g., on ships, aircraft, spacecraft, bases, habitats, etc.), or in remote locations or the like, human waste must be managed to avoid contamination and/or disease and to ensure proper sanitation. If conventional plumbing is not required or possible or there are environmental impacts to plumbing functionality, specific or uniquely designed systems may be required to manage human waste. For example, when in low, micro, or no gravity (e.g., in space), a lack of gravity prevents conventional plumbing from being employed. Further, due to the lack of gravity, containment of liquids and solids is an important consideration. Additionally, due to the limited closed-system environments, particularly in spacecraft, processing of waste and reclamation of water may be important for reducing the total consumable load of the platform. As used herein, the terms “low-gravity” and “low-gravity environment(s)” refer to non-Earth based environments that have a gravity less than the gravity of Earth (e.g., less than 1 g). These terms are thus intended to be inclusive of low-gravity (e.g., asteroids, moons, Mars, etc.) and zero-gravity (e.g., onboard spacecraft traveling between celestial bodies, craft and stations in orbit, etc.), and similar environments and is inclusive of artificial gravity applications.

[0041] In current space-based or low-gravity applications, waste collection and processing is typically achieved using four systems (e.g., a toilet, a urine processor assembly, a brine processor assembly, and a fecal processor assembly). These four systems may be required to provide a thorough and complete collection, storage, and processing of human waste. For use of these systems, the toilet requires separate collection of urine and non-urine waste. Requiring separate collection of urine and non-urine waste streams results in complex requirements and design constraints on the space toilet solution. For example, separate urine and non-urine waste collection ports may be required, which may not be intuitive or user-friendly as conventional terrestrial designs, particularly for women. Additionally, the use of separate urine and non-urine waste collection ports minimizes the ability to reuse hardware from terrestrial (or Earth-based) applications, such as components used for aircraft applications or the like. Such systems may also require the inclusion of a pre-treat mechanism, which is a waste treatment fluid that controls microbial growth and prevents solids from

forming or ammonia off-gassing during processing. Accordingly, improved systems for waste capture and processing may be advantageous in a variety of applications.

[0042] In current waste collection systems used in low-gravity environments, (e.g., onboard spacecraft), the waste collection systems enable collection of human waste and reclamation of water present in the waste. The necessary functions of waste collection and storage, along with reclamation of water from such waste, can drive the design of such systems to be complex and special-purpose, requiring unique or special-made components. The low-gravity environments that may require unique waste collection systems, beyond spacecraft applications, includes, without limitation, space stations (e.g., orbit), deep space exploration (e.g., space travel), and non-Earth surface operations (e.g., on the surface of the Moon, Mars, asteroids, and other relatively low-gravity bodies). Some such applications may not require toilets that are compatible with a zero or no-gravity environments, but may require systems that are lighter, smaller, more reliable and provide longer life, and require fewer consumables than conventional (e.g., Earth-based) toilet and processing solutions. That is, for some space surface applications, the complexity and features necessary for zero-gravity applications are not as strict, and thus such space surface application toilets may allow for less complexity than zero-gravity applications.

[0043] In view of the above and other considerations, some embodiments of the present disclosure are directed to space and/or space surface applications that incorporate a vacuum for providing motive force within a waste collection system, such as a human waste collection and processing system. In accordance with such embodiments, a commode or toilet with waste storage features that leverages a vacuum system is adapted for use in space. Such systems are capable of use in environments imposed by Deep Space applications (e.g., reduced gravity, increased radiation, etc.). In some embodiments, radiation tolerant electronics and/or redundant and maintainable radiation tolerance strategies may be implemented. Furthermore, such waste collection and processing systems may be used for non-surface operations, such as onboard spacecraft or stations that provide artificial gravity.

[0044] In accordance with some of the space surface applications described herein, some hardware from aircraft applications may be employed. However, because such systems are intended for use under the gravity of Earth, application to low-gravity environments may require modifications or complete rework of certain features and/or systems to enable functional operation in low-gravity environments. For example, application to low-gravity environments may require a need for reclamation from waste (e.g., water and/or air) and/or water/air loss minimization. As such, modifications of conventional aircraft systems is required for consideration of application to low-gravity environments. In accordance with some embodiments of the present disclosure, a single source (e.g., all types of human waste) or separate source waste collection (e.g., urine versus non-urine human waste), with options for rinse and/or waste treatment mechanisms are provided. In some embodiments, an optional vacuum generation or motive force may be achieved by exposure to the vacuum of space (or low atmospheric pressure environment) or use of a vacuum pump may be employed to generate a motive force on the waste to drive the waste through the system without the aid

of gravity. In accordance with some embodiments, the total complexity and cost of the system may be reduced by relying upon manual maintenance and cleaning (e.g., at a given interval) as compared to powered cleaning and/or maintenance systems. In other embodiments, an automated or automatic rinse mechanism or other cleaning mechanism may be implemented. In still other embodiments, disposable bowls, cups, collectors, or other consumables (e.g., liners or the like) may be used, thereby reducing or eliminating the need for direct cleaning of a bowl or other structure used to receive human waste.

[0045] Referring now to FIG. 1, a schematic diagram of a waste collection and processing system 100 in accordance with an embodiment of the present disclosure is shown. The waste collection and processing system 100 may be configured to collect and process human waste (e.g., urine, feces, menses), and is configured to be implemented, used, and operated in low-gravity environments. The waste collection and processing system 100 includes a toilet 102 having a bowl 104 and a lid 106. In use, a user will open the lid 106 and deposit waste into the bowl 104 where the waste will be collected and processed within the waste collection and processing system 100, as described herein. In some embodiments, the lid 106 may be configured to sealingly engage with a surface or rim of the bowl 104. The waste that is deposited into the toilet 102 may have liquid and solid components, and reclamation of water from the waste may be desirable for users of systems in low-gravity environments (e.g., space stations, spacecraft, non-Earth stations, etc.). Accordingly, the waste collection and processing system 100 is configured to extract the water content from the waste deposited into the toilet 102.

[0046] As shown, the toilet 102 is configured with a first valve 108 that is operated to allow for waste within the bowl 104 of the toilet 102 to be pulled into a waste tank 110. In a closed state, the first valve 108 prevents fluid communication from the bowl 104 to the waste tank 110. The first valve 108 may be selectively opened to provide fluid coupling or connection between an interior of the bowl 104 and an interior of the waste tank 110. In some embodiments, the first valve 108 may be operably controlled by a controller 112 of the waste collection and processing system 100. In other embodiments, the first valve 108 may be manually controlled with a lever, foot pedal, or the like. The controller 112 may include various processors, memory, input/output components, and the like, as will be appreciated by those of skill in the art. In other configurations, the controller 112 may be a more basic controller, receiving input and output and causing opening and/or closing of valves, without programmed control (e.g., operable like a switch for on/off or open/closed). The waste collection and processing system 100 may include a switch 114 to cause operation of the waste collection and processing system 100. For example, activation or operation of the switch 114 may cause the first valve 108 to open and/or close. In some configurations, the switch 114 may be a manually operated switch that is toggled by a user after depositing waste into the toilet 102. In other embodiments, the switch 114 may be integrated into the bowl 104 and/or lid 106 such that when the lid 106 is closed on the bowl 104, the switch 114 is actuated or operated to cause the first valve 108 to open and transfer any deposited waste within the bowl 104 into the waste tank 110.

[0047] As shown, one or more optional fluid injectors 116, 118 may be provided to inject water, cleaning fluid, waste

treatment fluid, or the like, directly into the bowl 104 and/or to be mixed with the waste as it is transferred from the bowl 104 to the waste tank 110 (e.g., within the first valve 108 or upstream or downstream therefrom). The fluid injectors 116, 118 can provide for an optional first processing step that is initialized at the time a user completes their deposit of waste into the toilet 102. The injected fluids or chemicals provided by the fluid injectors 116, 118 may initiate a waste treatment and processing and/or may provide for cleaning of surfaces of the lid 106, the bowl 104, the first valve 108, and/or the piping and conduits connecting the bowl 104 to the waste tank 110.

[0048] The waste is then collected within the waste tank 110. The waste tank 110 may be an enclosure for receiving human waste. The waste tank 110 may, in some embodiments, include bags, filters, disposable components, or the like, for the purpose of waste capture and treatment, with considerations made for ensuring liquids and/or solids do not escape the tank 110 and enter a space, room, or area that is occupied by humans (e.g., cabin or the like of a spacecraft). The first valve 108 is arranged at an inlet of the waste tank 110 and, in this configuration, the waste tank 110 may have two outlets each with a respective valve. For example, as shown, a second valve 120 may be controlled to selectively open to allow for waste within the waste tank 110 to be directed to a waste outlet 122, which may include an optional pump for providing a motive force to move the waste from the waste tank 110 to the waste outlet 122. The waste outlet 122 may be configured to receive solid waste, liquid waste, or a combination of solid and liquid waste, depending on the specific application and configuration of the system. The waste outlet 122 may define a flow path for waste to travel to storage or additional processing locations, such as plumbing.

[0049] At the second outlet of the waste tank 110, a third valve 124 is provided. The third valve 124 may be configured to allow for gas extraction from the waste tank 110. As such, the third valve 124 may be configured to permit, at most, liquids and gases, but may be configured to prevent solid waste to pass therethrough. The third valve 124 may be configured as part of an air and/or water reclamation system that directs airflow from the waste tank 110 through various systems, and may be configured to recycle treated gas (e.g., air) back into an occupied space 126 (e.g., spacecraft cabin) or direct treated or untreated gases to an external environment 128 (e.g., space, low-pressure atmosphere, etc.). In some embodiments, and as shown, an optional de-mister 130 may be provided at an outlet of the waste tank 110 and upstream from the third valve 124 (i.e., between the waste tank 110 and the third valve 124). In other embodiments, the de-mister may be arranged downstream from the third valve 124. The optional de-mister 130 may be a passive or active device for causing moisture from an airflow passing from the waste tank 110 to be removed. In some configurations, the de-mister 130 may be configured as a tortuous flow path with baffles or the like that are impinged upon by the airflow, causing moisture to condense out of the air. As such, the de-mister 130 may be included to generate a relatively dry air that is output from the waste tank 110. In configurations where the extracted air is to be supplied back into the occupied space 126, the airflow may be passed through an air filter assembly 132. The air filter assembly 132 can include odor and/or bacterial filters and the like to remove any odors or bacteria that may still be carried on the flow of

air from the waste tank 110. Such treated air may be supplied into the occupied space 126, such as a spacecraft cabin or the like.

[0050] In some configurations, a pump 134, such as a vacuum pump, may be configured to induce a motive force to drive the air from the waste tank 100, through the de-mister 130, the third valve 124, and the air filter assembly 132 to generate treated air that can be directed into the occupied space 126. In some configurations, the pump 134 may be controllable or selectively operated by the controller 112 or another controller associated with the waste collection and processing system 100. In embodiments where the air from the waste tank 110 is to be directed to the exit at the external environment 128, the external environment 128 itself may provide the vacuum or motive force for pulling the airflow from the waste tank 110. It will be appreciated that although both fluid paths are illustrated (e.g., to the occupied space 126 and the external environment 128), in other embodiments, only one of these two fluid paths may be present. Further, in some embodiments, a valve or the like may be arranged at the junction/split to the two exits, which may be manually or automatically controlled (e.g., by controller 112).

[0051] The airflow paths downstream from the third valve 124 may include additional components and the like, as will be appreciated by those of skill in the art. For example, and without limitation, in some embodiments, the flow paths to either exit may include various dehumidification hardware such as desiccant bed(s), condensing heat exchanger(s), additional passive or active de-mister systems, and the like. Further, at the waste outlet 122, additional processing may be employed to further process the waste after the waste is removed from the waste tank 110, such as water reclamation or the like.

[0052] In accordance with some embodiments of the present disclosure, the waste collection and processing system 100 may be configured for operation in three modes. A first mode of operation may be referred to as a system reset operation, a second mode of operation may be referred to as a waste deposit operation, and a third mode of operation may be referred to as a waste removal operation. The various operational modes may be controlled, at least in part, by the controller 112.

[0053] In the first operational mode (System Reset Operation), the controller 112 will cause both the first valve 108 and the second valve 120 to enter a closed state (if not already in a closed state). The controller 112 will then cause the third valve 124 to open. If the system 100 is configured to vent to vacuum or low pressure atmosphere (e.g., external environment 128), air in the waste tank 110 is vented to the external atmosphere, and the waste tank 110 is brought to a low pressure state (e.g., lower than ambient pressure within the occupied space 126, inclusive of vacuum pressure). If the system 100 is configured to return air back to a cabin or the like (e.g., occupied space 126), the controller 112 may be configured to activate the pump 134, which will cause air within the waste tank 110 to be extracted therefrom and the waste tank 110 may be brought to a low pressure state. As noted above, the configuration illustrated in FIG. 1 is merely schematic and a system in accordance with the present disclosure may include only one of the two airflow paths that exit from the waste tank 110 and/or the third valve 124 may be configured to selectively direct an airflow into one of the two distinct flow paths (e.g., to the external environment 128

or to the occupied space 126). With the waste tank 110 brought to a low pressure state, the third valve 124 will then be closed (resulting in all three valves 108, 120, 124 being closed). At this point, the waste collection and processing system 100 is ready to be used.

[0054] In the second operational mode (Waste Deposit Operation), airflow, gravity, or combinations thereof may be employed to direct human waste deposited by the user into the toilet 102 to be directed into the waste tank 110. In such an operational mode, opening of the lid 106 may optionally actuate a mechanical switch (e.g., the switch 114) which can activate the controller 112. In other embodiments, a user may toggle or actuate the switch 114 to initiate the waste deposit operation. Due to the fact that the systems of the present disclosure may be implemented onboard spacecraft, and such spacecraft may be exposed to radiation, consideration of the effects of such radiation on the system may be important. For example, radiation effects scale with duty cycle, and the inclusion of a switch 114 that is tied to opening/closing of the lid 106 may minimize the duration in which the controller 112, and potentially any other associated electronics, is powered on, resulting in minimizing the impact of radiation exposure to the electronic components.

[0055] In the second mode of operation, a user will deposit human waste into the bowl 104, similar to toilet use in terrestrial applications. When the user has completed use of the toilet 102, a 'flush' is activated by operation of the switch 114, such as by manual actuation of the switch 114 by the user after closing the lid 106 or by the actuation of the switch 114 by closing the lid 106. When the 'flush' is activated, the controller 112 directs the first valve 108 to open. During use (e.g., depositing waste), the toilet 102 will be exposed to the surrounding ambient atmosphere (e.g., ambient pressure of the occupied space 126), and thus the bowl will have a pressure that is about at atmospheric pressure. When the first valve 108 is opened, the volume of the toilet 102 will be exposed to the low pressure state within the waste tank 110 that is generated during the first operational mode. It is noted that the opening of the first valve 108 may be tied to the lid 106 in some manner to ensure that the first valve 108 does not open when the lid 106 is open. With the lid 106 closed and the first valve 108 opened, the pressure differential between the toilet 102 and the waste tank 110 will create a suction force and cause the waste within the bowl 104 to flow into the waste tank 110.

[0056] Before, during, or after the second mode of operation, an optional cleaning or treatment step may be performed. For example, before or during the opening of the first valve 108, a first fluid injector 116 may be operated to direct water, cleaning fluid, or waste treatment fluids into the bowl 104, and/or a second fluid injector 118 may be operated to direct similar fluids into the first valve 108 or within or along a flow pipe/path that connects the bowl 104 to the waste tank 110. The fluids injected by the fluid injectors 116, 118 may be pulled into the waste tank 110 along with the waste. Once the waste (and optional treatment and/or cleaning fluids) has been pulled into the waste tank 110, the first valve 108 may be closed, fluidly sealing the connection between the toilet 102 and the waste tank 110. The controller 112 may then perform the first operational mode (System Reset Operation), as described above, resetting the system 100 for another user. This sequence of the first and second

operational modes may be performed until the waste tank 110 reaches capacity or when the third operational mode is initiated.

[0057] In the third operational mode (Waste removal), waste is removed from the waste collection and processing system 100 by opening the second valve 120 and either pumping waste out (pump not shown) or using gravity to remove waste from the waste tank 110. As discussed above, the resetting operation will cause removal of gases from the waste tank 110. However, the solid and liquid waste deposited within the waste tank 110 will be held in the waste tank 110. During the waste removal operation, the waste is removed from the waste tank 110 and directed to the waste outlet 122. In some configurations, and during the waste removal operation, a rinsing operation may be performed within the waste tank 110 to clean or remove any waste that may be attached to the sides of the waste tank 110 and/or such fluid may aid in removing the waste from the waste tank 110. During the waste removal operation, the waste may be directed into a waste processing system or the like, where water extraction and/or reclamation and/or other waste processing may be performed. In some embodiments, the waste tank 110 may be configured with rinsing capabilities that are initiated and operated at the completion of the third operational mode. Such rinsing operations may include one or more additional fluid injectors arranged to inject fluids (e.g., water, cleaning fluids, disinfectants, etc.) into the waste tank 110.

[0058] It will be appreciated that various sensors, detectors, monitors, and the like may be arranged throughout the waste collection and processing system 100. For example, various configurations may include sensors for lid state (e.g., open/closed), air flow rates, air pressure, liquid and/or solid levels within the toilet 102 and/or waste tank 110, weight, or other sensors to detect fill level within the waste tank, valve state sensors (e.g., open/closed), temperature sensors, moisture sensors, and the like. Each of the sensors may be in arranged operable communication with the controller 112 to provide feedback and/or to enable automation of various aspects described herein. It will be appreciated that such sensors may be implemented with any of the herein described embodiments and such sensors are not merely limited to the embodiment and configuration shown and described with respect to FIG. 1.

[0059] Referring now to FIG. 2, a schematic diagram of a waste collection and processing system 200 in accordance with another embodiment of the present disclosure is shown. The waste collection and processing system 200 may be similar to the configuration shown in FIG. 1, but with differences as shown and described herein. The waste collection and processing system 200 may be used aboard spacecraft or on a base or other structure on the surface of a non-Earth body (i.e., in low-gravity environments). Similar to the configuration shown in FIG. 1, the waste collection and processing system 200 includes a toilet 202 with a bowl 204 and a lid 206. Waste from the toilet 202 may be selectively directed from the bowl 204 into a first waste tank 210 (e.g., a solid waste tank) through a first valve 208 that is controlled by a controller 212. A switch 214 may be employed for control functionality, as described above. Similarly, one or more optional fluid injectors 216, 218 may be provided to inject water, cleaning fluid, waste treatment

fluid, or the like, directly into the bowl 204 and/or to be mixed with the waste as it is transferred from the bowl 204 to the first waste tank 210.

[0060] Waste may be collected from the first waste tank 210 through a second valve 220 that selectively controls fluid connection between the first waste tank 210 and a first waste outlet 222, similar to that described above. In some configurations, the first waste tank 210 may be fluidly connected to an occupied space 226 (e.g., spacecraft cabin) via a flow path having a third valve 224 arranged thereon. In other embodiments, the first waste tank 210, in combination with the third valve 224, may be configured to direct treated or untreated gases to an external environment 228 (e.g., space, low-pressure atmosphere, etc.). In still further configurations, such as shown in FIG. 2, the system 200 may be configured to allow selective fluid to either or both of the occupied space 226 and the external environment 228. An optional de-mister 230 may be provided along the flow path exiting the first waste tank 210, as described above. In configurations or operations where air is to be directed back into the occupied space 226, the air may pass through a filter assembly 232 and a motive force may be provided by a pump 234, such as a vacuum pump.

[0061] The waste collection and processing system 100 of FIG. 1 is a combined collection system. However, in contrast, the waste collection and processing system 200 of FIG. 2 provides for two separate collection mechanisms or systems. The toilet 202 of the waste collection and processing system 200 of FIG. 2 may be configured to receive solid waste, or non-urine waste, although such solid waste deposit may include urine as well. However, if a user intends to only deposit liquid waste (e.g., urine), the waste collection and processing system 200 includes a dedicated system for such waste. As shown, the waste collection and processing system 200 includes a liquid waste collection system 236 which is arranged as a parallel system with the solid waste collection provided by the toilet 202.

[0062] The liquid waste collection system 236, as shown, includes a liquid waste receptacle 238 or other receiving device which is fluidly connected to a second waste tank 240 (e.g., a liquid waste tank). A fourth valve 242 is arranged between the liquid waste receptacle 238 and the second waste tank 240 (e.g., along a hose, conduit, or the like). The second waste tank 240 may be configured similar to that of the first waste tank 210, but may be configured to receive only liquid waste. As shown, the fourth valve 242 is arranged at an inlet to the second waste tank 240, and a fifth valve 244 is arranged between the second waste tank 240 and a second waste outlet 246. Further, as shown, a sixth valve 248 may be provided at an outlet from the second waste tank 240 to enable extraction of gases from the second waste tank 240, and may include an optional de-mister 250 at the outlet thereof, similar to the configuration of the first waste tank 210.

[0063] Similar to the configuration of FIG. 1, the waste collection and processing system 200 has three operating modes.

[0064] In a first operational mode (e.g., System Reset Operation), the controller 212 will control the first valve 208, the second valve 220, the fourth valve 242, and fifth valve 244 to be closed. The controller 212 will then control the third valve 230 and the sixth valve 248 to open (either separately or simultaneously). By opening only the third valve and/or the sixth valve 248, the respective waste tanks

210, 240 may be vented and reduced in pressure for subsequent use of the system 200. In configurations or operations where the waste collection and processing system 200 is configured to vent to vacuum or a low pressure atmosphere (e.g., external environment 229), air in the waste tanks 210, 240 is vented to external atmosphere and the waste tanks 210, 240 are brought to low pressure (or vacuum). If the waste collection and processing system 200 is configured to return the air to the occupied space 226, the controller 212 will activate the pump 234 to draw the air through the filter assembly 232, and the waste tanks 210, 240 are brought to low pressure (or vacuum). The controller 212 will then close the third valve 230 and the sixth valve 248. At this point, in either venting operation, the pressure within the waste tanks 210, 240 is lower than ambient pressure within the occupied space 226, and the system 200 is ready for use.

[0065] In a second operational mode (e.g., Waste Deposit Operation), airflow, gravity, or combinations thereof may be used to direct human waste deposited from user into the respective waste tanks 210, 240. As noted above, optionally, opening the lid 206 or, in this configuration, taking up the liquid waste receptacle 238, can actuate the switch 214 to activate the controller 212. This responsive action thus only activates the controller 212 and the system 200 as a whole, when a user will be depositing waste, thus reducing the duty cycle of the electronic components of the system 200. A user will make a deposit, similar to toilet use in terrestrial applications but with separate means of collection for urine (liquid waste receptacle 238) and non-urine waste (toilet 202). In the second operational mode, the fourth valve 242 can optionally be partially opened to provide a limited amount of air flow to assist with urine capture at the liquid waste receptacle 238. When a user has completed their waste deposit, a 'flush' action is activated, such as by a switch, toggle, foot pedal, or closing of the lid 206 or replacing the liquid waste receptacle 238 to a stowed location. When the 'flush' action is activated, the controller 212 will cause the first valve 208 and the fourth valve 242 to open, either individually or simultaneously. In some embodiments, only the valve 208, 242 that is associated with the location of the waste deposit will be opened. During the waste deposit, the bowl 204 and the liquid waste receptacle 238 will be exposed to atmospheric pressure (e.g., the occupied space 226). When the 'flush' is activated, the toilet 202 and/or the liquid waste receptacle 238 will be exposed to vacuum or low pressure in the respective waste tanks 210, 240. This will create a suction force, moving the waste into the respective waste tanks 210, 240. In some configurations, at the respective valves 208, 242 or within the respective bowl 204 or liquid waste receptacle 238, optional water, cleaning fluid, or waste treatment can be injected using fluid injectors 216, 218, 252. Once the waste has been moved into the respective waste tanks 210, 240, the first and fourth valves 208, 242 are closed and the controller 212 initiates the first operational mode (e.g., System Reset Operation). In some configurations of the waste collection and processing system 200, the system can also be operated in a way that collects urine and non-urine deposits at different times, or independently, with a different valve opening and closing procedure, without departing from the scope of the present disclosure.

[0066] In a third operational mode (e.g., Waste removal), waste is removed from the system 200. The waste removal operation may be controlled by the controller 212. In a first step, the second valve 220 and/or the fifth valve 244 are

opened, and waste within the waste tanks 210, 240 may be pumped out (pump not shown) or the waste may exit the respective waste tanks 210, 240 by means of gravity. The waste collected at the respective waste outlets 222, 246 can be directed to waste reclamation hardware. The waste reclamation hardware may include, but is not limited to, urine processor(s), fecal waste processing bag(s), urine processing bag(s), heaters, evaporators, phase separators (e.g., solid, liquid, gas), or the like. In some embodiments, the waste tanks 210, 240 may be configured with rinsing capabilities that are initiated and operated at the completion of the third operational mode.

[0067] Referring to FIG. 3, a schematic diagram of a waste collection and processing system 300 in accordance with another embodiment of the present disclosure is shown. The waste collection and processing system 300 may be similar to the configurations shown in FIGS. 1-2, but with differences as shown and described herein. The similar features that are illustrated will not be described in detail again for brevity and clarity of differences, but it will be appreciated that unless otherwise stated, embodiments and aspects of the waste collection and processing system 300 may be substantially similar to or even identical to the above described embodiments.

[0068] The waste collection and processing system 300 is a dual-stream configuration, similar to that shown and described with respect to FIG. 2, but having only one waste collection component (i.e., a toilet 302). In this configuration, the toilet 302 includes a bowl 304 and a lid 306 with a urine capture element 308 arranged within the bowl 304. The urine capture element 308 is arranged to ensure separation of liquid waste (urine) from solid or other human waste which will be collected in the bowl 304. Once the urine is deposited into the urine capture element 308 and other waste is deposited into the bowl 304, the operational modes described with respect to FIG. 2 are substantially the same, and thus description thereof will not be repeated. That is, the solid and/or non-urine waste may be collected into and processed from a first waste tank 310 (e.g., solid waste tank) and the urine waste may be collected into and processed from a second waste tank 312 (e.g., liquid waste tank).

[0069] Referring to FIG. 4, a schematic diagram of a waste collection and processing system 400 in accordance with another embodiment of the present disclosure is shown. The waste collection and processing system 400 may be similar to the configurations shown in FIGS. 1-3, but with differences as shown and described herein. The similar features that are illustrated will not be described in detail again for brevity and clarity of differences, but it will be appreciated that unless otherwise stated, embodiments and aspects of the waste collection and processing system 400 may be substantially similar to or even identical to the above described embodiments. The primary features shown and labeled in FIG. 4 are related to a waste reclamation system 402 that is incorporated into the waste collection and processing system 400. The waste reclamation system 402 may be provided to process waste deposited into the system 400 by a user and enable reclamation of portions of the waste (e.g., breathable air, water, etc.).

[0070] Similar to the above described configurations, the waste collection and processing system 400 includes a waste tank 404 that is selectively fluidly connected to the waste reclamation system 402 by a valve 406. The waste reclamation

mation system **402** includes a condenser **408** (e.g., a condensing heat exchanger) that is thermally coupled to a coolant loop **410**, or the like. The condenser **408** is arranged to cool a fluid flow received from the waste tank **404** as it flows through the waste reclamation system **402**. The condenser **408** will cool the fluid and condense moisture (e.g., water) from the fluid flow. The cooled flow, which may include both gases and liquid water or other liquids, may then be directed into a settling tank **412**, where the liquid and gas components may separate. The settling tank **412**, in some configurations, may be replaced by or arranged in connection with a phase separator or similar component, as will be appreciated by those of skill in the art. However, use of the settling tank **412** along may provide for a low complexity, passive system for separation of liquid and gases output from the waste tank **404**.

[0071] Dry air may be passed from the settling tank **412** through an air scrubber **414** (or other gas processing system/apparatus) and then the treated air may be directed by a fan **416** into an occupied space **418**, or the like. The liquid portion (e.g., water) may be pulled out of the settling tank **412** by a pump **420** and the liquid is passed through a liquid scrubber **422** (or other liquid processing system/apparatus) and then the treated liquid may be directed through a liquid outlet **424**. The liquid outlet **424** may be connected to a water storage tank or other water-based system onboard a spacecraft or the like. It will be appreciated that the air scrubber **414** and/or the liquid scrubber **422** may be configured with filters, chemical processing hardware, or the like. When the waste reclamation system **402** is not operated or used, the system **400** provides for fluid connection between the waste tank **404** and a return flow to the occupied space **418** or to an external environment, as described above.

[0072] As shown in FIG. 4, an optional heater **426** may be operably connected to the waste tank **404** to provide heating thereto. The application of heat to the waste tank **404** may increase an efficiency of the waste reclamation system **402** by evaporating liquid within the waste tank **404** prior to drawing the gases from the waste tank **404** into the waste reclamation system **402**. Although the waste reclamation system **402** is illustratively shown as receiving an airflow from the waste tank **404**, it will be appreciated that a similar waste reclamation system may be provided at a waste outlet **428** that is output from the waste tank **404**. In other configurations, the output at the waste outlet **428** may be directly connected to the same waste reclamation system **402** as that which receives the air to be treated for water reclamation, as described above. As such, in some embodiments, the waste reclamation system **402** may be configured to process both gaseous output and solid/liquid output from the waste tank **404**.

[0073] In the above described embodiments, a pump or other low pressure or vacuum source may be arranged to generate a low pressure within the waste tanks. This low pressure is used to pull waste from a toilet bowl or other receptacle and cause gas, liquid, and solid waste to be pulled from the receptacle into one or more waste tanks. It will be appreciated that, in some embodiments, such pump may not be necessary, such as by exposing the waste tank(s) to a low pressure atmosphere or vacuum of space.

[0074] In accordance with some embodiments of the present disclosure, waste collection and processing systems may be arranged as single stream collection commodes with waste storage and processing capability. In use, waste may

be collected from the user with an assisting airflow to pull the waste into the respective receptacle, and, in some embodiments, may be assisted by bowl geometry or the like. The waste may then be separated using various materials, structure, and/or membrane configurations, where solid and liquid waste are captured and gases are allowed to pass through the material/structure/membrane, within the respective waste tank. In some configurations, the waste tank(s) may be configured with heaters or other mechanisms to evaporate water from the collected waste and enable reclamation of the water from the waste. The heating operation may also prepare solid waste remnants (e.g., after gases and liquids have been extracted) for safe storage or disposal. Some such configurations may include an alternating processing chamber architecture to treat and/or remove gases, liquids, and solids. Such systems may be capable of use in environments imposed by Low Earth Orbit and Deep Space applications (e.g., low or no gravity, increased radiation, etc.). In accordance with some embodiments, simultaneous waste stream collection (e.g., liquids and solids) with intuitive human interface may be provided, such as with modified receptacles, or the like. Accordingly, systems of the present disclosure may reduce required crew interaction relative to conventional systems, thus increasing safety and cleanliness. Furthermore, some embodiments of the present disclosure allow for water recapture from all forms of human waste (e.g., urine, feces, vomit, menses, etc.). In accordance with some embodiments, separate waste collection and/or water recapture may be employed with various configurations shown and described herein. For example, and without limitation, such separate waste collection and/or water recapture may be incorporated as shown in FIGS. 2-3.

[0075] Referring now to FIG. 5, a schematic diagram of a waste collection and processing system **500** in accordance with another embodiment of the present disclosure is shown. The waste collection and processing system **500** includes a controller **502**, a switch **504**, and a toilet **506** having a bowl **508** and a lid **510**, similar to that shown and described above, and thus the details of which will not be repeated again. At the outlet of the bowl **508** is a selectively operable first valve **512** that is configured to be controlled by the controller **502**. As shown, a fluid injector **514** may be provided to inject water, cleaning fluid, waste treatment fluid, or the like, directly into the bowl **508** and/or to be mixed with the waste as it is transferred from the bowl **508** to a waste tank of a pair of waste tanks **516**, **518**. Although two waste tanks **516**, **518** are illustratively shown, it will be appreciated that more than two waste tanks may be employed without departing from the scope of the present disclosure.

[0076] The waste tanks **516**, **518** are configured to be selectively operated between a reclamation operation and a collection or containment operation. In the system **500**, one of the waste tanks **516**, **518** may be operated in a reclamation mode of operation while the other waste tank **516**, **518** is operated in a collection or containment mode of operation. In the illustrative configuration, a first waste tank **516** is shown in the reclamation mode of operation and a second waste tank **518** is shown in the collection mode of operation. As noted, the operational state of the two waste tanks **516**, **518** may be selectively switched, such that the first waste tank **516** may be operated in the collection mode of operation and the second waste tank **518** may be operated in the reclamation mode of operation.

[0077] When the first waste tank **516** is in the reclamation mode, and as shown in FIG. **5**, a second valve **520** arranged between the first valve **512** and the first waste tank **516** is closed, thus preventing fluid communication between the toilet **506** and the first waste tank **516**. When the second waste tank **518** is in the collection mode, and as shown in FIG. **5**, a third valve **522** is open, allowing for waste from the toilet **506** to be directed into the second waste tank **518**. In some embodiments, the second and third valves **520**, **522** may be replaced by a directional three-way valve, and the distinct valve arrangement illustrated herein is intended only for explanatory purposes, and is not intended to be limiting to the valve configurations that may be used with embodiments of the present disclosure. The controller **502** may be configured to control operation of the valves **512**, **520**, **522**. In this configuration, each of the waste tanks **516**, **518** includes a waste bag **524** arranged within the respective waste tank **516**, **518**. The waste bags **524** are configured to capture liquid and solid waste, but is permeable to gases that are part of the waste that is deposited into the waste bags **524**. As such, the gasses of the waste may be extracted, reclaimed, and recycled for use. In some embodiments, the waste bags **524** may be configured as a multi-membrane bladder or the like.

[0078] Each of the waste tanks **516**, **518** may include an optional heater **526** that is arranged to promote extraction of gases, and potentially water, from the waste in the waste bags **524** within the respective waste tanks **516**, **518**. In various embodiments, the optional heaters **526** may be placed on the outside of the respective waste tanks **516**, **518**, inside the waste tanks **516**, **518**, upstream of the waste tanks **516**, **518** on a fluid line between the toilet **506** and the waste tanks **516**, **518**, and/or on or at air inlets or pressure relief valves **528** that are associated with the waste tanks **516**, **518**. Further, it will be appreciated that multiple separate heaters may be arranged at multiple locations to ensure desired heating of the waste stream or captured waste. In some configurations, and as shown, air from an occupied space (or from a dedicated supply) may be passed or forced through the waste tanks **516**, **518** from the respective air inlets **528**. In some embodiments, the air supplied through the air inlets **528** may be openings that are always open, thus allowing constant flow of air to pass through the waste tanks **516**, **518**. In other configurations, the air inlets **528** may include operation valves (e.g., pressure relieve valves, controllable orifices, etc.) that are selectively operated to allow air to enter and flow through the respective waste tanks **516**, **518**, depending on the mode of operation and the specific configuration of the waste collection and processing system **500**.

[0079] The waste bags **524** may be removable from the respective waste tanks **516**, **518**, and replaceable. In some embodiments, the waste bags **524** are a consumable or disposable element, and in other embodiments, the waste bags **524** may be processed and reused, depending on the specification configuration and application of the system **500**. The waste bags **524** can be removed from the waste tanks **516**, **518** to remove collected solid and/or liquid wastes for disposal outside of the waste collection and processing system **500**. The removal of the waste bags **524** may be based on a fill level of the waste bags **524** or based on a schedule, or some other reason.

[0080] As shown, downstream from the waste tanks **516**, **518** is an air filter assembly **530** for treating air pulled from

the waste tanks **516**, **518**. A fan **532** may be used to provide a motive force to pull air from the surrounding environment or space in which the waste collection and processing system **500** into and through the system **500**. The air pulled through the system **500** by the fan **532** may enter through the toilet **506** (e.g., when the lid **510** is open and the first valve **512** is open) and through the waste tanks **516**, **518**. In some embodiments, such as shown, that include the air inlets **528** on the waste tanks **516**, **518**, air may be pulled through such air inlets **528** and through the respective waste tanks **516**, **518**. In either configurations, the air and any gases that mix with the airflow within the waste tanks **516**, **518** may be directed into and through the air filter assembly **530** to generate treated air. The treated air may then be provided into a moisture capture system for water reclamation and/or other processing equipment and/or may be directed back into an occupied space as indicated at system outlet **534**.

[0081] The waste collection and processing system **500** provides for waste collection, similar to that described above, along with additional processing functionality built into the system **500**. The toilet **506** may be configured similar to that shown and described above with respect to FIGS. **1-4**. The toilet **506** may have a geometry designed for directing airflow into and through the bowl **508** and direct waste (gases, liquids, solids) from the human user into the bowl **508** and the rest of the system **500**. The first valve **512**, arranged at an outlet of the bowl **508**, is operable to isolate the toilet **506** from the remainder of the system, which may be provided to enable the various modes of operation, as described herein. The system **500** can include features to enable injection of waste treatment fluid(s) or water for waste treatment and system rinse (e.g., fluid injectors **514**). Various other features may also be implemented in this and the other embodiments described, particularly for systems that incorporate waste bags. The waste bags **524**, as noted above, are selected to be permeable to gas, but are impermeable to liquids and solids, thus allowing for capture of liquid/solid waste, and enabling recapture of gases. In some embodiments, the waste bags **524** may be pretreated bags or containers with chemicals and/or coatings for containing, processing, and otherwise handling waste deposited into the waste bags **524**. In some configurations, treatment of waste at the outlet of the bowl **508** and prior to depositing into the waste tanks **516**, **518** may include a flow over pearls, fluid injection between the bowl **508** and the waste tanks **516**, **518**, and/or fluid injection at the bowl **508** itself as a bowl rinsing mechanism. Other treatments and/or pre-treatment applications and operations may be performed without departing from the scope of the present disclosure.

[0082] In addition to the waste collection, described above, the waste collection and processing system **500** also provides for waste storage and recycling functionality. As shown and noted above, two or more waste tanks **516**, **518** are provided that each contain respective waste bags **524**. The waste bags **524** allow for the capture of solid and liquid waste, but flow-through of gases (e.g., air and humidity). The waste tanks **516**, **518** may be configured to operate on a cycle that is manually controlled or may be controlled by the controller **502**. The operational cycle of the operational states of the waste tanks **516**, **518** is designed such that the functions of each waste tank **516**, **518** is interchanged at an interval that allows for one or more of the waste tanks **516**, **518** (or one or more waste bags **524**) to be collecting waste while the other waste tanks **516**, **518** (or waste bags **524**) in

the system 500 are used to reclaim water and other byproducts from the waste and prepare the waste for storage once the waste bag is filled and/or removed from the respective waste tank 516, 518. Water reclamation is performed by passing air over or through the waste bags 524, which allow gaseous water to move through the material of the waste bags 524 and enter into an air stream that flows through the system 500 (e.g., from the bowl 508 and/or the air inlets 528). The water extracted from the waste may then be removed from the air stream. The waste bags 524 may be removable, and may be configured to be sealable when the waste bags 524 are removed from the respective waste tanks 516, 518. Once removed, new or empty replacement waste bags 524 may be installed to replace a removed (e.g., filled) waste bag 524.

[0083] In some embodiments, the optional heaters 526 may be used to apply heat to the air stream, the waste bags 524, and/or the waste tanks 516, 518 to reduce the time required to reclaim water from waste. That is, application of heat from the heaters 526 can cause evaporation of gases and water from the waste collected within the waste bags 524.

[0084] The waste tanks 516, 518 may be designed for manual or automated removal of the waste bags 524 after stabilization and water recapture from waste within the waste bags 524. In some configurations, the waste tanks 516, 518 may include optional secondary filters and waste capture hardware 536 at the outlet of the respective waste tank 516, 518. Furthermore, the waste tanks 516, 518 may include optional valves 538 at the outlet thereof, which may be selectively closed to fluidly isolate the respective waste tank 516, 518.

[0085] Downstream from the waste tanks 516, 518, the waste collection and processing system 500 can include an optional air and humidity processing system or assembly. For example, as shown, the filter assembly 530 may be arranged immediately downstream from the waste tanks 516, 518. The filter assembly 530 is configured to condition or otherwise treat air as it leaves the waste tanks 516, 518. The fan 532 is provided to create a motive force of a flow of air through the system 500. In accordance with various embodiments, the 532 530 may be a variable speed fan, a step speed fan, a single speed fan, or multiple fans of one or more types. Additional hardware at the outlet of the system 500 can be added to reclaim moisture from the air. For example, moisture reclamation systems may include regenerative heat exchangers, heat exchangers that interface with other cooling source(s)/systems, phase separators for use in low-gravity environments to separate condensate from dry air, filters, membranes, chemical beds, or other hardware for air and/or water processing, or the like as will be appreciated by those of skill in the art.

[0086] In the system 500, during a waste deposit operation, airflow, generated by the fan 532, pulls the waste into an active or operational waste tank (in this illustration, second waste tank 518). During the waste deposit operation, and as illustratively shown, the second waste tank 518 is active and open for waste collection, and the first waste tank 516 is closed and able to perform reclamation operations for waste that may be contained in a waste bag 524 within the first waste tank 516. As such, a flow path of waste and gases will be from the bowl 508, into the active second waste tank 518, and then out of the active second waste tank 518, and inactive first waste tank 516 is isolated from such a flow.

[0087] The active second waste tank 518 is open to the flow because the third valve 522 is open. In contrast, the closed first waste tank 516 is isolated because the second valve 520 is closed. With the first waste tank 516 isolated from the flow, the first waste tank 516 may be operated in a reclamation mode of operation, where waste contained within a waste bag 524 within the first waste tank 516 is treated or processed to extract and reclaim water and/or air, while preparing the waste for storage or disposal. In some configurations, the act of opening the lid 510 for use will actuate the switch 504 to activate the controller 502, thus limiting the duration that electronics are operated in an ON state.

[0088] The controller 502 is configured to direct the first valve 512 and the third valve 522 to open and to operate the fan 532 to generate a flow of air through the toilet 506, through the second waste tank 518, and to the system outlet 534. In some embodiments, the fan 532 may be a single speed fan or the like, with an on and off state. In other embodiments, the fan 532 may be a multi-speed or variable speed fan, having at least a low speed operation and a high speed operation. When the fan 532 is operated, air flow will cause a flow of air to be directed into and through the active containment tank (i.e., second waste tank 518). The user will deposit waste into the bowl 508, and the deposit is captured by the airflow within the bowl 508. The airflow will carry or cause the waste to move through the first valve 512 and the third valve 522 to enter the active containment tank (i.e., second waste tank 518), where waste is captured by the waste bag 524 within the second waste tank 518. The airflow continues to flow through the second waste tank 518 and toward an outlet of the system 500. The air will exit the active waste tank and be processed or treated in the filter assembly 530 and to the system outlet 534. Once a user has completed the waste deposit, the lid 510 is closed. When the lid 510 is closed, an optional rinse operation is performed to clean and/or rinse the bowl 508 of the toilet 506. The rinse fluid can be water, waste treatment fluid(s), cleaning fluid(s), sanitizing or disinfecting fluids, or the like. After closure of the lid 510, and after an optional rise operation, the waste and rinse fluids may be pulled out of the toilet 506. Once the waste and fluids are removed from the toilet 506, such as after a preset run time for the fan 532, the first valve 512 and the third valve 522 are closed, and the fan 532 is powered down or set to a low flow state.

[0089] In a waste recycle or reclamation mode of operation of the system 500, airflow is provided over an optionally heated waste bag 524 in a waste tank 516, 518. In some configurations, the waste recycle operation may be performed simultaneously with the waste deposit operation, but performed on the inactive waste tank. The waste recycle operation may be performed to collect moisture from waste and/or cleaning fluids from the waste bags 524. In the waste recycle operation, the fan 532 is powered on (either by the controller 502 or a fan specific controller) to pull air through the waste tank that is in the reclamation mode of operation. In this operation, the second valve 520 is closed (i.e., no fluid connection between the toilet 506 and the first waste tank 516. Further, in some configurations of this operation, the third valve 522 may also be closed, resulting in no fluid communication between the toilet 506 and both waste tanks 516, 518. The air inlet 528 on the waste tank 516, 518 that is reclamation mode (or both tanks if not in active use such as during waste deposit) open to allow air flow over the

waste bag(s) **524** within the waste tanks **516, 518**. It will be appreciated that the air inlet **528** on the waste tanks **516, 518** may be configured as valves, pressure relief valves, solenoid valves, variable orifices, or the like to allow for air to be pulled into and through the waste tanks **516, 518** to capture moisture that is extracted from waste in the waste bags **524**. In some embodiments, the air inlets **528** may be configured as one-way airflow permeable vents or inlets to allow airflow to constantly be pulled through the respective waste tanks **516, 518**. Alternatively, or in addition thereto, during the reclamation mode of operation, one or more of the valves **512, 520, 522** may be opened (fully or partially) to increase the airflow through the waste bag(s) **524** during the reclamation mode of operation. In some such configurations, the toilet **506** may include vents or the like to allow for an airflow from the toilet **506** to pass through the waste tanks **516, 518**.

[0090] As noted above, the optional heaters **526** may be provided on the waste tanks **516, 518**, and/or directly to the waste bags **524**, and/or at the air inlets **528**, and/or at other locations within the system **500**. Application of heat from the heaters **526** may expedite water evaporation from waste within the waste bags **524** and may also provide a mechanism to sanitize the waste contained within the waste bags **524**. As the fan **532** is operated, the induced air flow will carry moisture from the waste through the elements **536, 538** at the outlet of waste tanks **516, 518**, through the filter assembly **530**, and then out of the system **500** at the system outlet **534** (e.g., reintroduced into an occupied space or into moisture capture hardware).

[0091] When full, the waste bags **524** may be removed and replaced with an empty bag. It will be appreciated that being full is not a requirement for removal, as a less-than-full waste bag **524** may also be removed, such as based on a schedule, escaping odors, a maintenance operation, for other reasons or at other appropriate time. When the waste bags **524** are to be removed and replaced with an empty bag, the designated waste tank **516, 518** may be opened to allow for the removal of the waste bag **524** and any collected/captured waste therein. The waste may be at least partially treated by fluids (e.g., from fluid injector **514**) and/or application of heat from the heaters **526**. That is, the fluids provided from the fluid injector(s) **514** may include chemicals that are selected to kill bacteria, breakdown solids, reduce odor generation, or the like, and thus the fluids may be used both for cleaning/rinsing, and for treating collected waste. Further, as noted above, the heaters **526** may provide sanitizing functionality and/or other thermal processing of the waste within the waste bags **524**. The opening of the waste tanks **516, 518** may be achieved through manually opening a door or the like, electromechanically operating a door or performing a removal operation, electronically controlling elements or functions of the waste tanks **516, 518** by the controller **502**, or the like. In some configurations, the waste bags **524** may be configured to automatically seal upon removal from the respective waste tank **516, 518**. In some embodiments, an automated process may be employed where a filled waste bag **524** is closed up and dropped into a collection bin or the like, and an empty bag is moved into place within the respective waste tank **516, 518**. As such, direct human interaction with filled waste bags may be avoided. In some waste bag removal operations, the fan **532** may be operated to reduce stagnant air and pull any potential resulting odors through the filter assembly **530** during removal of the waste

bag **524** from the waste tank **516, 518**. Once removed, a new waste bag **524** may be installed in the respective waste tank **516, 518**.

[0092] As discussed above, one waste tank **516, 518** will be operated in an active or collection mode and the other waste tank **516, 518** will be operated in a reclamation mode. In some configurations, the waste tank that is operated in the active or collection mode may be operated in such mode until the waste bag therein reaches a predetermined capacity or is considered full. During this time, the active/collection mode waste tank may also perform reclamation operations when not being used for waste deposit. In some embodiments, the two (or more) waste tanks may be cycled in a pattern, such as after a use, the tanks will change operation, such that waste is deposited into each of the bags in sequence. This operational scheme may provide for improved waste processing and reclamation by increasing the amount of time that a given waste tank is in the reclamation mode of operation, and may prevent build up of untreated waste within a given waste tank. It will be appreciated that other operational schemes may be employed without departing from the scope of the present disclosure.

[0093] Referring now to FIG. 6, a schematic diagram of a waste collection and processing system **600** in accordance with another embodiment of the present disclosure is shown. The waste collection and processing system **600** includes a controller **602**, a switch **604**, and a toilet **606** having a bowl **608** and a lid **610**, similar to that shown and described above. Similar to the embodiment of FIG. 5, at the outlet of the bowl **608** is a selectively operable first valve **612** that is configured to be controlled by the controller **602**. A fluid injector **614** is arranged to inject water, cleaning fluid, waste treatment fluid, or the like, directly into the bowl **608** and/or to be mixed with the waste as it moves from the bowl **608** to a set of waste tanks **616, 618** (which may be two or more waste tanks). In this illustrative configuration, at the inlet to the first waste tank **616** is a second valve **620**, and at the inlet to the second waste tank **618** is a third valve **622**. Each waste tank **616, 618** has a respective (removable/replaceable) waste bag **624** and a heater **626** associated therewith, as described above. Similarly, air inlets **628** may be provided on each waste tank **616, 618** to enable air throughflow, as described above, which may be configured as vents, valves, or the like. The waste tanks **616, 618** may be configured to alternate operational modes, such as described with respect to FIG. 5, and thus a described of the operational modes will not be repeated. However, it will be appreciated that in operation, one waste tank **616, 618** may be operated in an active/collection mode, and the other waste tank **616, 618** may be operated in a reclamation mode. Downstream from the waste tanks **616, 618** is a filter assembly **630**, a first fan **632**, and an outlet **634**. At the outlet **634**, the system may include moisture capture, air quality treatment and processing, or the like, for redirecting air into an occupied space, or may be vented or otherwise used onboard a craft, as described above with respect to FIG. 5.

[0094] In the waste collection and processing system **600** of FIG. 6, the system **600** includes a two-stage airflow configuration for providing a motive airflow for waste capture at/in the toilet **606** and a motive airflow for drawing waste (solid, liquid, gas) from the toilet **606** and through the waste tanks **616, 618** as described above. In this configuration, a relatively low airflow may be induced through the waste tanks **616, 618** during collection of waste while a

relatively higher airflow is induced within or at the human interface where waste is deposited (e.g., at the toilet 606). The waste collection and processing system 600 includes waste capture airflow system 636 which includes a second fan 638. The waste capture airflow system 636 is integrated with the toilet 606 such that the second fan 638 can generate a flow of air through the bowl 608 in a direction of the first valve 612 to aid in capturing and directing human waste from a user into the system for capture, collection, and processing. A relatively higher or increased airflow rate may be required to direct and/or waste during the waste deposit/capture phase. In contrast, during the reclamation phase, airflow is only required to ensure relatively dry air is provided and supplied into contact with the waste and/or waste bag within the waste tanks 616, 618. In accordance with some embodiments, the lower flow rate of the reclamation phase may be significantly lower than that of the deposit/capture phase. However, it will be appreciated that in some embodiments, a relatively high airflow rate may be employed during reclamation (i.e., a single speed fan or the like). In such configurations, the higher flow rate of the reclamation may result in higher power requirements and more noise (e.g., single speed fan capable of deposit/capture), which may be undesirable. Therefore, higher airflow rates are typically reserved for when such flow rates are functionally required (i.e., during capture/deposit). For example, and without limitation, the capture airflow rate may be 2-10 times greater than the reclamation airflow rate. In some non-limiting embodiments, the capture/deposit airflow rate may be about 15-30 cubic feet per minute (CFM) and the reclamation airflow rate may be about 5 CFM.

[0095] When using the waste collection and processing system 600 during a waste deposit operation, airflow from the waste capture airflow system 636 directs human waste from the user toward an outlet of the bowl 608 and into the currently active waste tank 616, 618 (i.e., the one in active or collection mode), while the other waste tank 616, 618 may be operated in the reclamation mode of operation. For example, by opening the lid 610, the switch 604 may be activated to activate the controller 602 which in turn may activate the waste capture airflow system 636. The controller 602 may be configured to direct the first valve 612 and the third valve 622 (to the active waste tank) to remain closed or only open slightly. The controller 602 activates the second fan 638 (of the waste capture airflow system 636) to generate a capture airflow 640. For example, the second fan 638 may be operated a high flow state or an on state, if it is a single speed fan, to generate the capture flow 640. The capture airflow generated by the second fan 638 will capture and/or direct waste toward the active waste tank 616, 618. For example, a user will make a waste deposit, and the waste is captured by the capture airflow 640 within the bowl 608, thus preventing waste from splashing or otherwise leaving the bowl 604 at the opening with the lid 610. The capture airflow 640 carries the waste toward an outlet of the bowl 608 (e.g., proximate the first valve 612). The user will then close the lid 610. As an optional step, a rinse operation may be performed to rinse the bowl 608 and direct any waste stuck to the bowl 608 to be collected and directed to the waste tank(s) 616, 618. The rinse operation may include rinsing with water, a waste treatment fluid, a sanitation or cleaning solution, or the like. After the lid 610 is closed, and the optional rinse is performed, the first valve 612 and the third valve 622 are opened. The second valve 620 remains

closed due to the first waste tank 616 is operated in the reclamation mode. With the valves 612, 622 open, the second fan 638 of the airflow capture system 636 may be powered down or transitioned into a low flow state, and the first fan 632 is powered on. Airflow induced through the waste collection and processing system 600 by the first fan 632, and optionally the second fan 638, will direct the waste to the active waste tank 618 (in this case). Once the waste is collected in the waste bag 624 of the second waste tank 618, the first and third valves 612, 622 are closed, and both fans 632, 638 are powered down.

[0096] In a waste recycle operation of the waste collection and processing system 600, airflow is directed over an optionally heated waste bag 624 in the first waste tank 616 which is in the reclamation mode of operation. It is noted that both waste tanks 616, 618 may be operated in the reclamation mode simultaneously, although individual or separate operation is also possible. It is noted that the reclamation mode may be stopped and one waste tank transitioned into active mode when a user opens the lid 610 or otherwise begins use of the system 600. The airflow induced by the fans 632, 638 will cause moisture and gases from waste in the waste bag(s) 624 to be drawn out of the waste bag(s) 624 such that water may be recaptured. In example of such operation, the first fan 632 is powered on (either by the controller 602 or a fan-specific controller). The second and third valves 620, 622 are closed, such that airflow cannot be pulled through or from the toilet 606. As such, in this specific example, the second fan 638 may not be operated during this operation. The air inlets 628 on the waste tanks 616, 618 provide an inlet for air to enter the respective waste tanks 616, 618, even with the valves 620, 622 being closed. The air drawn through the air inlets 628 will flow over the waste bag(s) 624 within the waste tanks 616, 618. This airflow will pass over the waste bags 624 and pull moisture and air therefrom. In some configurations, the optional heaters 626 may be activated to expedite water evaporation from waste and sanitize waste within the waste bag(s) 624. In some configurations, the air inlets 628 on the waste tanks 616, 618 may be selectively operable (e.g., open and closed) to allow for moisture capture from only one tank at a time. Thus, in some configurations, the air inlets 628 may be configured as solenoid valves or some other active element that can control air to flow into and through the waste tank(s) 616, 618. The induced airflow by the first fan 632 will carry the moist air to the outlet 634 of the system 600 (for recirculation and/or moisture recapture).

[0097] In a removal and replacement operation of the waste bags 624, the waste tanks 616, 618 may be opened to allow for the removal of the waste bag(s) that contain processed waste. The processed waste is waste that has been collected within the waste bags 624 and had air pulled through to extract gases and moisture therefrom. In some embodiments, the waste may be heated by the heaters 626 to promote evaporation of any water in the waste, and thus the waste bags 624 may contain substantially dehydrated human waste (i.e., the processed waste). In some configurations, the waste bags 624 may be configured to automatically seal upon removal from a respective waste tank 616, 618. During the waste bag removal process, one or both of the fans 632, 638 may be operated to reduce stagnant air and any potential resulting odors during removal of the waste bags 624 from the waste tanks 616, 618. After removal of a used or filled waste bag 624, a new or empty waste bag 624 may be

installed. The waste tank **616**, **618**, with the newly installed waste bag **624**, may be switched to the active collection mode of operation, and the other waste tank **616**, **618** may be operated in the reclamation mode of operation.

[0098] Referring now to FIG. 7, a schematic diagram of a waste collection and processing system **700** in accordance with another embodiment of the present disclosure is shown. The waste collection and processing system **700** is similar to that shown and described above with respect to FIGS. 5-6, and thus like features will not be described again. It will be appreciated that features of the configuration of FIG. 7 may also be implemented in combination with features of other embodiments described herein, such as that shown and described with respect to FIGS. 1-4. As such, the specific configuration illustrated in FIG. 7 is not intended to be limited to the arrangement and components as shown and described, but rather such illustration is for explanatory purposes. In the waste collection and processing system **700**, the system **700** may be used with single use waste bags as opposed to a single large collection bag within each containment/processing tank. That is, each single use waste bag, in this configuration, may be used by a user for depositing waste into the waste bag while allowing for capture and reclamation of gases and liquid (e.g., water).

[0099] As shown in FIG. 7, a single-use waste bag **702** is shown arranged within a toilet **704** of the system **700**. In this configuration, during waste deposit, a user will place the single-use waste bag **702** into the toilet **704** and deposit waste therein. The waste collection and processing system **700** may include an airflow capture system similar to that shown and described with respect to FIG. 6. For example, a system or arrangement similar to the waste capture airflow system **636** of system **600** may be provided to generate a forced airflow into and through the toilet **704** to aid in collection and processing of moisture and/or air, while the solid and liquid human waste may be captured and contained within the single-use waste bag **702**. In some such embodiments, the reusable waste bag **702** may be configured to be used without the toilet **704**. That is, the reusable waste bag **702** may be configured to couple to a valve **703** or other fluid connection interface of the system **700**. In such a configuration, a fan **705** arranged at an outlet **707** of the system **700**, similar to that described above, may provide a motive force to pull the waste and gases from the waste bag **702** and into/through the system **700**. In still other embodiments, the bowl of the toilet **704** may be designed to assist a user with holding the single-use waste bag **702** during a waste deposit, such as providing a housing or frame that supports or holds the single-use waste bag **702**.

[0100] Due to the implementation of the single-use waste bag **702**, waste bags are not required to be installed within waste tanks **706**, **708** of the system **700**. Rather, the waste tanks **706**, **708** may be configured to receive and process captured moisture and ensure separation of air and liquids for recapture and recycling. In other embodiments, each of the waste tanks **706**, **708** may include a removable waste bag similar to the embodiments described above, with such waste bags being used to capture any waste that is not captured by the single-use waste bag **702**. In this illustrative configuration, the waste tanks **706**, **708** are configured with multiple outlets **710**, as compared to the illustrated single outlet configurations shown above. The inclusion of multiple outlets on the waste tanks **706**, **708** can ensure that airflow and fluid flow through the waste tanks **706**, **708** is not

obstructed by waste that may make it into the respective waste tanks **706**, **708**. This may be particularly useful for systems that do not include waste bags within the waste tanks. However, it will be appreciated that the multiple outlet configuration shown in FIG. 7 may be used in any of the illustrative embodiments of the present disclosure. For example, in any of the systems of FIGS. 1-6, the waste tanks may include multiple fluid outlets to ensure desired airflow, moisture capture, and redundancy to avoid blockage of fluid paths by waste or debris that may not be captured by the waste bags within the waste tanks. Accordingly, the use of multiple outlets on the waste tanks is not limited to the single-use waste bag configuration illustrated in FIG. 7. Although shown with two outlets on each waste tank **706**, **708**, it will be appreciated that any number of outlets may be provided without departing from the scope of the present disclosure.

[0101] Furthermore, it will be appreciated that in the system **700** of FIG. 7, the waste tanks **706**, **708** may be operated similar to embodiments that include waste bags therein. For example, the waste tanks **706**, **708** may be operated in the above described modes of operation, with an active collection waste tank and a reclamation waste tank, and swapping between these modes. Furthermore, the waste tanks **706**, **708** may be arranged with heaters for causing evaporation of moisture for collection and reuse. Additionally, fluid cleaning, rinsing, and/or sanitation may be used within the bowl **704** and/or the waste tanks **706**, **708**. Downstream from the waste tanks **706**, **708** may be a filter assembly **712** that is configured to filter gases and moisture pulled from the waste tanks **706**, **708**. At the outlet **707** of the system **700** may be various other systems, such as moisture capture systems and hardware and/or an opening to an occupied space (e.g., for circulating breathable air back to a cabin or the like).

[0102] Referring now to FIG. 8, a schematic diagram of a waste collection and processing system **800** in accordance with another embodiment of the present disclosure is shown. The waste collection and processing system **800** is similar to that shown and described above with respect to, for example, FIGS. 5-6, and thus like features will not be described again. Furthermore, the operation of the waste collection and processing system **800** may be similar to any previously described embodiment, including the various modes of operation. The system **800** includes a toilet **802** and associated electronics including a controller **804**. The toilet **802** is arranged to capture and direct human waste through the system **800**. Downstream from the toilet **802** are waste tanks **806**, **808**, which can include optional heaters **810** and air inlets **812**. A fluid injector **814** may be provided to inject water, cleaning fluids, sanitation fluids, or the like, as described above. Air and moisture may be pulled through the system **800**, and waste may be captured within waste bags within the waste tanks **806**, **808**. A fan **816** may be configured to pull air and moisture through a filter assembly **818** and then the treated air and/or moisture may be directed to a system outlet **820** (e.g., additional processing systems and/or circulated back into an occupied space).

[0103] In contrast to the previously described embodiments, in this illustrative configuration, a venting system **822** is provided. The venting system **822** includes one or more fluid connections between the waste tanks **806**, **808** and a low pressure or vacuum pressure system, indicated at vent **824**. In some embodiments, the vent **824** may be an

inlet or entry to a stringent air filtration hardware system that is used to aid in performing a sanitization cycle of the system **800**. Such a sanitization cycle may be performed after reclamation is completed. That is, after waste has been captured and processed, the sanitation cycle may be used to ensure that waste, odors, bacteria, and the like are managed in a sanitary fashion.

[0104] In this configuration, the venting system **822** includes respective venting valves **826** on the waste tanks **806**, **808**, which provide a second outlet flow path for air through the system **800**, different from the flow path to the system outlet **820**. For example, when the venting valves **826** are open, a high pressure differential is imposed on the respective waste tank(s) **806**, **808** due to low pressure (e.g., vacuum of space, a vacuum pump, or other low pressure/vacuum assembly). In some embodiments, the venting valves **826** may be controlled by the controller **804**. In other embodiments, a dedicated controller for venting operations may be provided separate from the controller **804** of the reset of the system **800**. In still other configurations, the venting valves **826** may be manually opened. When the venting valves **826** are opened, various other valves may be closed to fluidly isolate the waste tanks **806**, **808** such that when exposed to vacuum, air from a surrounding environment (e.g., occupied space) is not pulled through the system and evacuated from a spacecraft or the like. As such, additional valves, not shown, may be arranged at all inlets/outlets of the waste tanks **806**, **808** to ensure that only the waste tanks **808**, **806** are exposed to the low pressure or vacuum when the venting valves **826** are opened.

[0105] In one example operation of the venting system **822**, the controller **804** will operate the heaters **810** to bring the waste tank(s) **806**, **808** up to an elevated sanitization temperature for a duration of time to stabilize the waste within the respective waste tank(s) **806**, **808**. This operation may cause release of various gases from the waste in the waste tank(s) **806**, **808** and/or gases that may be released by evaporation of chemicals or the like that are used during a rinse operation or the like. It will be appreciated that any gasses from this portion of the process may need to be vented or undergo additional filtration, as high sanitization temperatures can result in unique hazards being added to the air. As such, by performing the sanitation and venting steps, harmful gases may be vented and removed without risk of such gases being introduced into an occupied space. It will be appreciated that the venting system **822** of system **800** may be incorporated to any of the other configurations and arrangements described herein, or with other systems based thereon. In some embodiments, the sanitation operation may be omitted, and the venting operation may be performed without pre-heating the material within the waste tanks.

[0106] Referring now to FIG. 9, a schematic diagram of a waste collection and processing system **900** in accordance with another embodiment of the present disclosure is shown. The waste collection and processing system **900** is similar to that shown and described above, and thus like features will not be described again and various elements are not shown for clarity of illustration. Further, the operation of the waste collection and processing system **900** may be similar to the previously described embodiments. The system **900** includes a toilet **902** fluidly connected to multiple waste tanks **904**, **906** through a fluid connection having one or more valves, fluid injectors, and the like. The operation of

the waste tanks **904**, **906** may be substantially similar to the operational modes described above.

[0107] In this illustrative configuration, the waste collection and processing system **900** includes a recapture system **908**. The recapture system **908** is arranged downstream from the waste tanks **904**, **906** of the system **900**. In operation, humid or moist air may be extracted from the waste tanks **904**, **906** by operation of a fan **910** (similar to the above described operations). In this configuration, the air pulled from the waste tanks **904**, **906** will be directed through the recapture system **908**. The air first passes through a condenser **912**, which will reduce the temperature of the air and cause water to condense into water droplets that are carried on the air. The air carrying the water droplets is then directed into a phase separator **914** which is configured to separate the water content from the air, thus generating dry air and liquid water as outputs from the phase separator **914**. The dry air is then passed through an air filter system **916** and may be recycled back into an occupied space or otherwise stored or used (or vented). The liquid portion (e.g., water) is directed from the phase separator **914** to a liquid filter system **918** and may be driven by a pump **920**. The processed water may then be recaptured, recycled, or otherwise reused and/or stored. It will be appreciated that the recapture system **908** may be implemented with any of the embodiments described herein, such that a similar recapture system may be provided downstream from the waste tanks of the other embodiments described herein, and may be provided in combination with a venting system, such as described with respect to FIG. 8.

[0108] Referring now to FIG. 10, a schematic diagram of a waste collection and processing system **1000** in accordance with another embodiment of the present disclosure is shown. The waste collection and processing system **1000** is similar to that shown and described above, and thus like features may not be shown or described again. The operation of the waste collection and processing system **1000** may be similar to the previously described embodiments. The system **1000** includes a toilet **1002** fluidly connected to multiple waste tanks **1004**, **1006** through a fluid connection having one or more valves, fluid injectors, and the like. The operation of the waste tanks **1004**, **1006** may be substantially similar to the operational modes described above.

[0109] In this illustrative configuration, the waste collection and processing system **1000** includes a recapture system **1008**. The recapture system **1008** is arranged downstream from the waste tanks **1004**, **1006** of the system **1000**. In operation, humid or moist air may be extracted from the waste tanks **1004**, **1006** by operation of a fan **1010** (similar to the above described operations). The recapture system **1008** of FIG. 10 may be similar to the system described with respect to FIG. 9, having a condenser **1012**, a phase separator **1014**, an air filter system **1016**, a liquid filter system **1018**, and a pump **1020** for pumping the liquid portion from the phase separator **1014**.

[0110] In this configuration, downstream from the fan **1010**, and along the air outlet/output from the phase separator **1014**, is a recirculation junction **1022**. The recirculation junction **1022** has a controllable valve **1024** associated therewith. The recirculation junction **1022** is arranged to selectively direct at least a portion of dry air that has been processed through the recapture system **1008** back into the system **1000**. For example, dry and conditioned air may be recirculated from the recapture system **1008** back to the

waste tanks **1004**, **1006**. The recirculated air may be used to provide an airflow through the waste tanks **1004**, **1006**, and may provide similar functionality to the air inlets on the waste tanks that is described with respect to other embodiments herein. Further, in some configurations, a combination of air inlets (e.g., FIGS. 5-6) and recirculated dry air (e.g., FIG. 10) may be employed without departing from the scope of the present disclosure.

[0111] In some embodiments, and as shown in FIG. 10, the system **1000** includes an optional regenerative heat exchanger **1026** arranged along the recirculation loop from the phase separator **1014** back to the waste tanks **1004**, **1006**. The regenerative heat exchanger **1026** may be arranged to provide a thermal exchange between the treated, dry air, and the output humid airflow that exits the waste tanks **1004**, **1006**. The regenerative heat exchanger **1026** may be provided to increase an efficiency of the system **1000**. For example, the dry air may pick up heat from the humid air output from the waste tanks **1004**, **1006**, which may have been heated using heaters, as described above. As the dry air picks up heat, it will cause a reduction in temperature of the humid air that is passed into the condenser **1012** and the phase separator **1014**. Accordingly, the power and operational requirements of the condenser **1012** and/or the phase separator **1014** may be reduced. In some embodiments, the regenerative heat exchanger **1026** may replace the condenser **1012**, and provide the pre-cooling to the humid air before entering the phase separator **1014**. Additionally, the warmed, dry air that is recirculated back to the waste tanks **1004**, **1006** may improve water pickup in the waste tanks **1004**, **1006**, which can result in increased reclamation rates.

[0112] Referring now to FIG. 11, a schematic diagram of a waste collection and processing system **1100** in accordance with another embodiment of the present disclosure is shown. The waste collection and processing system **1100** is similar to that shown and described above, and thus like features may not be shown or described again. Furthermore, the operation of the waste collection and processing system **1100** may be similar to the previously described embodiments. The system **1100** includes a toilet **1102** fluidly connected to a first waste tank **1104** and a liquid waste collection system **1106** fluidly connected to a second waste tank **1108** and a third waste tank **1110**. The fluid connections may include one or more valves, fluid injectors, and the like, as described above. The operation of the waste tanks **1104**, **1108**, **1110** may be substantially similar to the operational modes described above.

[0113] In this illustrative configuration, the waste collection and processing system **1100** includes separate waste capture mechanisms, such as similar to the embodiment of FIG. 2. In this configuration, the toilet **1102** is fluidly connected with a single waste tank **1104** for solid waste collection, which may be functionally similar to various embodiments described herein. The liquid waste collection system **1106** is provided in parallel with the solid waste collection. The liquid waste collection system **1106** is configured similar to the dual waste tank systems shown and described above, but with the dual waste tank system applied to liquid waste capture and processing rather than all waste (e.g., compare with FIGS. 5-9). The liquid waste collection system **1106** includes a second waste tank **1108** and a third waste tank **1110** which may be alternated in operational modes (e.g., between active/capture and reclamation), as described above. The liquid waste capture of the liquid

waste collection system **1106** may be by a funnel, hose, or the like (e.g., as shown in FIG. 2) or may be a feature integrated into and/or part of the toilet **1102** (e.g., as shown in FIG. 3). In the hose configuration, as shown, a liquid waste receptacle **1112** may be used which is structurally separate from the toilet **1102**. In other configurations that incorporate a urine capture element as part of the toilet **1102** (e.g., as shown in FIG. 3), a hose or conduit may be arranged to receive the liquid waste and direct it to the waste tanks **1108**, **1110** (e.g., similar to the fluid connection between the liquid waste receptacle **308** and the waste tank **312** shown in FIG. 3).

[0114] It will be appreciated that the toilet **1102** may be configured with dual waste tanks, as shown and described above. In such a configuration, the system may include four (or more) separate waste tanks, with at least two for each waste stream (liquid and all other waste). Furthermore, in some embodiments, a two-stage airflow system may be implemented within the toilet **1102** and/or the liquid waste receptacle **1112** of the liquid waste collection system **1106**, such as shown and described with respect to FIG. 6 (waste capture airflow system **636**). Further, in some embodiments, single bag or single-use bag configurations are possible, with the waste bags used similarly as shown and described with respect to FIG. 7. In such a configuration, the waste tanks **1104**, **1108**, **1110** may be provided with multiple outlets to ensure that the outflow from the respective waste tanks **1104**, **1108**, **1110** does not clog with waste material.

[0115] In some applications, the waste collection and processing systems of the present disclosure may be configured for short duration operations/flights. During short duration operations/flights, the considerations of waste management may be different. For example, waste recycling and recapture may not be a primary focus, as the limited resource availability may not be as impactful on relatively short missions and/or where resupply is readily available. Examples of short duration operations may be missions that last about a month or less, and longer duration operations may be missions of one month or longer.

[0116] Referring now to FIG. 12, a schematic diagram of a waste collection and processing system **1200** in accordance with another embodiment of the present disclosure is shown. As illustrated, the waste collection and processing system **1200** includes a controller **1202**, a switch **1204**, and a toilet **1206** having a bowl **1208** and a lid **1210**, similar to that shown and described above, and thus the details of which will not be repeated again. At the outlet of the bowl **1208** is a selectively operable first valve **1212** that is configured to be controlled by the controller **1202**. As shown, in this configuration, a single waste tank **1214** with a waste bag **1216** is provided. The system **1200** may include fluid injectors within the bowl **1208** and/or along a flow path from the bowl **1208** to the waste tank **1214**, as shown and described above.

[0117] The system **1200** includes a second valve **1218** that is arranged at an outlet of the waste tank **1214**. Similar to the systems described above, a fan **1220** may be used to pull air through the waste tank **1214** and the waste bag **1216** to extract moisture and/or air from the waste tank **1214**. The extracted air is then pulled (or pushed) through an air filter assembly **1222**, which may include various filters, separators, and the like for removing odors and/or moisture. The fan **1220** may then direct the treated air back to an occupied space **1224** (e.g., cabin or the like) or the treated air may be

recycled or redirected back into the bowl **1208** and/or the waste tank **1216** to provide dry, moving air for waste capture and/or waste processing within the waste tank **1214** and waste bag **1216**. In some embodiments, the fan **1220** may be operated only during a waste deposit or reclamation operation (i.e., when in use). However, in other embodiments, the valves **1212**, **1218** may be kept open (or partially open) for continuous cycling of air through the system **1200**. The partial open state of the valves **1212**, **1218** may be selected to allow continuous airflow without providing a strong airflow therethrough, such as to minimize power consumption and/or to minimize release of odors or the like. In some such configurations, when a waste deposit is being made, the fan **1220** may be operated at a high flow rate to pull waste into the bowl **1208** and/or waste tank **1214**, and when not in use by a user, the fan **1220** may be operated at a low flow rate for continuous dry air circulation. In some such configurations, the lid **1210** may be sealed to the bowl **1208**, and the continuous airflow may be substantially closed loop, or air may be pulled into the system **1200** through an air inlet **1226**, as described above. Further, in some configurations, single-use waste bags may be employed, which may be used within or in combination with the toilet **1206**. In such a configuration, the waste tank **1214** may include multiple outlets to ensure blockage does not occur, such as shown FIG. 7.

[0118] It will be appreciated that the system **1200** of FIG. 12 may also be used for longer duration missions/operations, although such systems may include reclamation, recapture, and recycling components, such as those shown and described above. Further, it will be appreciated that the waste collection and processing systems described herein can be adjusted to perform for a specific mission or operation. For example, a craft may be configured with one of the more complex systems described herein, but not all components may need to be operated at all times.

[0119] As discussed throughout the present disclosure, and in view of the teachings herein, it will be readily appreciated that various features from the specifically described embodiments may be combined with features from other embodiments, or may incorporate features not specifically shown and described. For example, each of the above described configurations may be implemented with disposable waste bags, reusable waste bags, or may be used with single-use waste bags. Furthermore, for example, water reclamation may be implemented in any of the above described embodiments. As such, it will be appreciated that the specific embodiments described herein are for illustrative and explanatory purposes and are not intended to be limited to the specific set of components and arrangements thereof, as illustrated and described.

[0120] Advantageously, embodiments described herein provide for improved waste collection and processing systems. In accordance with some embodiments of the present disclosure, waste collection and processing systems are provided with various mechanisms for waste capture, collection, treatment, processing, and the like, as described herein. Embodiments of the present disclosure provide for improved and more user-friendly waste collection and processing systems that are operable in low-gravity environments, for both short duration and long duration mission. The systems described herein enable reclamation, processing, recycling, and recapture of usable resources that can be extracted from human waste. For example, embodiments of

the present disclosure may be configured to recycle or capture moisture from human waste, and thus water supplies may be replenished or the amount of water to be carried may be reduced. Furthermore, advantageously, embodiments of the present disclosure may reduce costs and complexity of human waste management systems for space-based and low-gravity environment applications.

[0121] Further advantages of the present systems may include elimination of the need for pretreating. In current solutions/systems, the addition of pretreating includes a chemical that is added to urine to make the mixed fluid compatible with downstream systems and storage. Such pretreat chemicals may reduce ammonia off-gassing of the waste and solidification of salts and other urine constituents that could harm rotating machinery or block flow paths. The pretreat chemicals may be highly acidic chemicals that are considered a toxic fluid, and thus may drive additional safety considerations and complications. Additionally, pretreating operations and the hardware required to inject/apply the pretreat chemicals may add to the maintenance/operating mass required for the system. Accordingly, advantageously, by eliminating the pretreating of conventional systems, embodiments of the present disclosure may minimize the complexity, mass, volume, and power of the system. Moreover, embodiments of the present disclosure can reduce the amount of human interaction at each step of operation, thus improving sanitation and safety. Additionally, the quantity of consumables associated human waste in low-gravity environments may be reduced through use of the waste tanks, as described herein. These and other advantages and benefits of the systems and processes disclosed herein will be apparent to those of skill in the art in view of the above discussion and description.

[0122] The use of the terms “a”, “an”, “the”, and similar references in the context of description (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or specifically contradicted by context. The modifier “about” used in connection with a quantity is inclusive of the stated value and has the meaning dictated by the context (e.g., it includes the degree of error associated with measurement of the particular quantity). All ranges disclosed herein are inclusive of the endpoints, and the endpoints are independently combinable with each other.

[0123] While the present disclosure has been described in detail in connection with only a limited number of embodiments, it should be readily understood that the present disclosure is not limited to such disclosed embodiments. Rather, the present disclosure can be modified to incorporate any number of variations, alterations, substitutions, combinations, sub-combinations, or equivalent arrangements not heretofore described, but which are commensurate with the scope of the present disclosure. Additionally, while various embodiments of the present disclosure have been described, it is to be understood that aspects of the present disclosure may include only some of the described embodiments. Accordingly, the present disclosure is not to be seen as limited by the foregoing description, but is only limited by the scope of the appended claims.

What is claimed is:

1. A waste collection and processing system for use in low-gravity environments, the waste collection and processing system comprising:

a toilet having a bowl and a lid;

- a waste tank having an inlet and an outlet, wherein the bowl of the toilet is fluidly coupled to the inlet of the waste tank;
 - a first valve arranged between the bowl and the waste tank, the first valve selectively operable to allow fluid connection between the bowl and the waste tank;
 - a second valve arranged at a first outlet of the waste tank, the second valve selectively operable to allow for solid waste and liquid waste within the waste tank to be directed to a waste outlet; and
 - a third valve arranged at a second outlet of the waste tank, the third valve selectively operable to allow for gases to be removed from the waste tank and directed to at least one of an occupied space, an external environment, or a waste reclamation system.
2. The waste collection and processing system of claim 1, further comprising a fan arranged to pull air and waste gases through the bowl, into and through the waste tank, and through the third second outlet of the waste tank.
3. The waste collection and processing system of claim 1, further comprising a filter assembly arranged downstream from the second outlet of the waste tank, the filter assembly configured to remove odor and moisture from the gases received from the waste tank.
4. The waste collection and processing system of claim 1, wherein the occupied space is part of a spacecraft.
5. The waste collection and processing system of claim 1, wherein the occupied space is part of a space station.
6. The waste collection and processing system of claim 1, further comprising a controller configured to control operation of the first valve, the second valve, and the third valve.
7. The waste collection and processing system of claim 6, further comprising a switch configured to be actuated to activate the controller.
8. The waste collection and processing system of claim 7, wherein the switch is integrated with the toilet and actuated by opening and closing of the lid.
9. The waste collection and processing system of claim 1, wherein the waste reclamation system comprises:
- a condenser arranged to cool a flow of gases received from the waste tank and condense moisture from the flow of gases;
 - a settling tank arranged to receive an output from the condenser and separate the condensed moisture from gases received from the condenser; and
 - a gas processing system arranged to process gases received from the settling tank, the gas processing system configured to direct treated air into the occupied space.
10. The waste collection and processing system of claim 9, wherein the waste reclamation system further comprises a liquid processing system configured to generate treated liquid and direct the treated liquid to a liquid outlet.
11. The waste collection and processing system of claim 1, further comprising at least one fluid injector arranged to inject at least one of water, cleaning fluid, and waste treatment fluid into at least one of the bowl and a flow path between the bowl and the waste tank.
12. The waste collection and processing system of claim 1, further comprising a de-mister arranged at the second outlet of the waste tank and upstream from the third valve, the de-mister configured to remove moisture from a flow of gas exiting the waste tank through the second outlet.
13. The waste collection and processing system of claim 1, wherein the waste tank fluidly connected to the toilet is a first waste tank and the toilet and the first waste tank define a solid waste collection system of the waste collection and processing system, the waste collection and processing system further comprising:
- a liquid waste collection system comprising:
 - a liquid waste receptacle;
 - a second waste tank fluidly connected to the liquid waste receptacle; and
 - a fourth valve arranged between the liquid waste receptacle and the second waste tank, wherein gases removed from the second waste tank are directed to at least one of the occupied space, the external environment, or the waste reclamation system.
14. The waste collection and processing system of claim 13, further comprising:
- a fifth valve arranged at a first outlet of the second waste tank between the second waste tank and a second waste outlet; and
 - a sixth valve at a second outlet of the second waste tank and configured to control of flow of gases from the second waste tank through the second outlet of the second waste tank.
15. The waste collection and processing system of claim 14, further comprising a de-mister arranged at the second outlet of the second waste tank and upstream from the sixth valve, the de-mister configured to remove moisture from a flow of gas exiting the second waste tank through the second outlet of the second waste tank.
16. The waste collection and processing system of claim 13, further comprising at least one fluid injector arranged to inject at least one of water, cleaning fluid, and waste treatment fluid into at least one of the liquid waste receptacle and a flow path between the liquid waste receptacle and the second waste tank.
17. The waste collection and processing system of claim 1, wherein the waste tank is a first waste tank configured to receive solid waste, the waste collection and processing system further comprising:
- a urine capture element arranged within the bowl of the toilet; and
 - a second waste tank fluidly connected to the urine capture element.
18. The waste collection and processing system of claim 1, further comprising a heater operably connected to the waste tank to provide heating thereto.
19. A method of waste collection and processing in low-gravity environments, the method comprising:
- receiving human waste in a toilet having a bowl and a lid;
 - collecting and directing the human waste from the bowl into a waste tank that is fluidly connected to the bowl by opening a first valve arranged between the bowl and an inlet to the waste tank;
 - capturing liquid waste and solid waste within the waste tank;
 - directing the liquid waste and solid waste to a waste outlet by opening a second valve arranged between a first outlet of the waste tank and the waste outlet; and
 - directing air and gaseous waste out of the waste tank by opening a third valve, the air and gaseous waste being directed to at least one of an occupied space, an external environment, or a waste reclamation system.

20. The method of claim **19**, further comprising treating the air and gaseous waste prior to directing treated air to the occupied space.

* * * * *