United States Patent Application Publication	20250256739
Kind Code	A1
Publication Date	August 14, 2025
Inventor(s)	MITA; Ryota

SIGNAL PROCESSING DEVICE

Abstract

Provided is a signal processing device capable of more surely keeping a vehicle-to-vehicle distance between a leading vehicle and a host vehicle in traveling by following, by more accurately determining a cause for losing track of the leading vehicle by an external environment sensor as compared to conventional signal processing devices. The integration unit **12** performs integration processing of the external environment information acquired by the external environment sensor **1** mounted on the host vehicle V and the host vehicle travel information acquired by the vehicle sensor **6**. The behavior prediction unit **9** predicts the behavior at a future time of the host vehicle V and another vehicle detected by the external environment sensor **1**, based on the integration result from the integration unit **12**. The road shape acquisition unit **10** obtains the road shape information (gradient information) on the traveling road surface of the host vehicle V and the other vehicle at the future time. The departure determination unit **11** determines whether the other vehicle departs from the detection range of the external environment sensor **1** at the future time, based on the behavior prediction result of the host vehicle V and the other vehicle and the road shape information (gradient information). The integration unit **12** uses the behavior prediction result for the integration processing in accordance with the determination result from the departure determination unit **11**.

Inventors:	**MITA; Ryota (Hitachinaka-shi, Ibaraki, JP)**
Applicant:	**Hitachi Astemo, Ltd.** (Hitachinaka-shi, Ibaraki, JP)
Family ID:	**1000008618617**
Assignee:	**Hitachi Astemo, Ltd. (Hitachinaka-shi, Ibaraki, JP)**
Appl. No.:	**18/702398**
Filed (or PCT Filed):	**August 24, 2022**
PCT No.:	**PCT/JP2022/031910**

Publication Classification

Int. Cl.: **B60W60/00** (20200101); **B60W30/16** (20200101); **B60W40/076** (20120101)

U.S. Cl.:

CPC   **B60W60/0027** (20200201); **B60W30/16** (20130101); **B60W40/076** (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present invention relates to a signal processing device for a vehicle.

BACKGROUND ART

[0002] Recently, autonomous driving of a vehicle (also referred to as an autonomous driving vehicle) with a vehicle control device for autonomous driving mounted thereon has been in practical use. In relation to this, vehicle control has been known in which for example, an autonomous driving vehicle travels by following another vehicle (hereinafter, also referred to as a leading vehicle) driving ahead while acquiring information on the leading vehicle from an external environment sensor so as to keep the vehicle-to-vehicle distance from the leading vehicle.

[0003] Further, Patent Literature 1 discloses an autonomous driving control device in which when the external environment sensor of the host vehicle has lost track of the leading vehicle, it is determined whether the leading vehicle is present on a route of the host vehicle based on route candidates of the leading vehicle obtained from map information, and when it is determined that the leading vehicle is present on the route of the host vehicle, the acceleration of the host vehicle is controlled to be limited.

CITATION LIST

Patent Literature

[0004] Patent Literature 1: JP 2016-103131 A

SUMMARY OF INVENTION

Technical Problem

[0005] In traveling of an autonomous driving vehicle (hereinafter, also referred to as a host vehicle), traveling an overpass or a sag with continuous ascending and descending gradients is also presumed.

[0006] For example, when the host vehicle travels an overpass by following a leading vehicle so as to keep the vehicle-to-vehicle distance therebetween, in a scene where the leading vehicle is positioned outside a detection range of an external environment sensor of the host vehicle due to a large difference in gradient of the road surface where the host vehicle and the leading vehicle are traveling, a phenomenon occurs in which leading vehicle information from the eternal environment sensor is temporarily lost (hereinafter, also referred to as a temporary loss).

[0007] As described above, when the host vehicle accelerates or the leading vehicle decelerates due to the temporary loss of the leading vehicle information from the external environment sensor despite the presence of the leading vehicle ahead of the host vehicle on a travel route, the vehicle-to-vehicle distance having been kept so far is reduced. Further, immediately afterwards, when the

leading vehicle information from the external environment sensor is recovered, the host vehicle recognizes as if the leading vehicle suddenly appears, which could pose a danger of the host vehicle and the leading vehicle rapidly approaching or colliding against each other.

[0008] Prior art of Patent Literature 1 first calculates, from the external environment sensor and map information, the route where the host vehicle travels and candidates for a route where the leading vehicle is traveling from now. Next, based on the relation among the route of the host vehicle, the candidates for the route of the leading vehicle, and the detection range of the external environment sensor, the timing when the leading vehicle is lost is computed for each candidate for the route of the leading vehicle. Then, the timing at which the leading vehicle is lost in the calculated route candidate and the timing at which the leading vehicle has been actually lost by the external environment sensor are compared for consistency to determine which route the leading vehicle has actually selected, so that a cause for the temporary loss of the leading vehicle can be accurately identified.

[0009] Herein, traveling an overpass in Patent Literature 1 will be studied. First, a general overpass has only one straight route as a route. Further, on the overpass, there are few occasions in which a vehicle decelerates to safely make a turn, for example, as in a route with left and right turns at an intersection, and the vehicle speed is likely to be relatively increased. Thus, on the overpass, particularly, the host vehicle and the leading vehicle are more likely to rapidly become closer to each other. However, Patent Literature 1 does not address traveling a single straight route, and lacks consideration for gradients, despite the fact that the gradients on the traveling road surface cause the temporary loss of the leading vehicle on the overpass.

[0010] The method for determining the cause for the temporary loss from the route candidates for the leading vehicle, as in Patent Literature 1, has a problem in that the temporary loss in traveling an overpass or a sag cannot be accurately determined.

[0011] The present invention has been made in view of the aforementioned problem, and provides a signal processing device capable of more surely keeping a vehicle-to-vehicle distance between a leading vehicle and a host vehicle in traveling by following, by more accurately determining a cause for losing track of the leading vehicle by an external environment sensor as compared to conventional signal processing devices.

Solution to Problem

[0012] To achieve the aforementioned object, the present invention is a signal processing device including: an integration unit that performs integration processing of external environment information acquired by an external environment sensor mounted on a host vehicle and host vehicle travel information acquired by a vehicle sensor; and a behavior prediction unit that predicts behavior at a future time of the host vehicle and another vehicle detected by the external environment sensor, based on an integration result from the integration unit, in which the behavior prediction unit includes: a road shape acquisition unit that obtains road shape information on a traveling road surface of the host vehicle and the other vehicle at the future time; and a departure determination unit that determines whether the other vehicle departs from a detection range of the external environment sensor at the future time, based on a behavior prediction result of the host vehicle and the other vehicle and the road shape information, and the integration unit uses the behavior prediction result for the integration processing in accordance with a determination result from the departure determination unit.

Advantageous Effects of Invention

[0013] According to the present invention, it is possible to provide a signal processing device capable of more surely keeping a vehicle-to-vehicle distance between a leading vehicle and a host vehicle in traveling by following, by more accurately determining a cause for losing track of the leading vehicle by an external environment sensor as compared to conventional signal processing devices.

[0014] Problems, configurations, and advantageous effects other than those described above will be clarified by the description of the following embodiments.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0015] FIG. **1** is a configurational diagram showing a vehicle control device AD**1** of an autonomous driving vehicle according to the present invention.

[0016] FIG. **2** is a configurational view showing an example of an external environment sensor **1** of FIG. **1**.

[0017] FIG. **3** is a flowchart of processing performed by a behavior prediction unit **9** of FIG. **1**.

[0018] FIG. **4** shows a scene at a current time t**1**, and explanatory views of an integration result FU**1** and a behavior prediction result CA**1** in an embodiment 1.

[0019] FIG. **5** is a flowchart of processing performed by an integration unit **12** of FIG. **1**.

[0020] FIG. **6** shows a scene at a current time t**2**, and explanatory views of an integration result FU**2** and an integration result FU**3** in the embodiment 1.

[0021] FIG. **7** shows a scene at a current time t**101**, and explanatory views of an integration result FU**101** and an integration result FU**102** in an embodiment 2.

DESCRIPTION OF EMBODIMENTS

[0022] Hereinafter, a signal processing device according to some embodiments will be described in detail with reference to the drawings. It should be noted that the present embodiments are mere examples for embodying the present invention and do not limit the technical scope of the present invention. Common components in the drawings are assigned the same reference signs.

Embodiment 1

[0023] FIG. **1** is a configurational diagram of the vehicle control device AD**1** mounted on an autonomous driving vehicle (host vehicle V). The vehicle control device AD**1** includes a signal processing device **7**, an autonomous driving control unit **17**, an external environment sensor **1**, a map unit **5**, a vehicle sensor **6**, and a vehicle drive unit **20**.

[0024] The signal processing device **7**, the autonomous driving control unit **17**, and the map unit **5** acquire, from the vehicle sensor **6**, operation amounts of an engine **21**, a brake **22**, and steering **23** that are controlled by the vehicle drive unit **20**.

[0025] The external environment sensor **1** includes a camera sensor **2** and a radar sensor **3**. The camera sensor **2** acquires object information (external environment information) detected from an image of the surrounding of the host vehicle V and outputs the acquired object information to the signal processing device **7**. The radar sensor **3** acquires object information (external environment information) detected from a distance to a predetermined location in the surrounding of the host vehicle V and outputs the acquired object information to the signal processing device **7**. Note that the object information includes the size, position, speed, acceleration, orientation, type, detected state, and the like of the detected object.

[0026] The map unit **5** includes an antenna **4**. The antenna **4** receives a satellite reception signal (hereinafter, a GNSS signal) in a Global Navigation Satellite System (hereinafter, a GNSS). The map unit **5** includes a map database and a locator. The map unit **5** computes host vehicle positional information by means of the locator based on the received GNSS signal, selects the surrounding map information from the map database, and outputs the host vehicle positional information and the surrounding map information to the signal processing device **7**. Note that the map information includes detailed information necessary for autonomous driving, such as roads, signs, and terrestrial objects.

[0027] The vehicle sensor **6** acquires host vehicle travel information, such as operating information on the engine **21**, operating information on the brake **22**, and operating information on the steering

23, and outputs the acquired host vehicle travel information to the signal processing device **7**, the autonomous driving control unit **17**, and the map unit **5**.

[0028] Herein, the signal processing device **7** includes a processor **13**, a memory **8**, an I/O interface **15**, an I/O interface **16**, and an auxiliary storage device **14**. The I/O interface **15** is connected to the external environment sensor **1**, the map unit **5**, and the vehicle sensor **6**, and the I/O interface **16** is connected to the autonomous driving control unit **17**. The I/O interface **15** and the I/O interface **16** are connected to the external environment sensor **1**, the map unit **5**, the vehicle sensor **6**, and the autonomous driving control unit **17** via a LAN (Local Area Network) or a CAN (Controller Area Network).

[0029] The auxiliary storage device **14** is configured with a nonvolatile storage medium and retains programs, tables, and the like.

[0030] The integration unit **12** and the behavior prediction unit **9** are loaded as programs on the memory **8** and are executed by the processor **13**. Note that the behavior prediction unit **9** includes a road shape acquisition unit **10** and a departure determination unit **11**.

[0031] The integration unit **12** receives external environment information from the external environment sensor **1**, receives host vehicle positional information, surrounding map information, and preset planned travel route information from the map unit **5**, and receives host vehicle travel information from the vehicle sensor **6**. The integration unit **12** merges the host vehicle travel information into the surrounding map information based on the host vehicle positional information. The integration unit **12** closely examines the external environment information and removes inaccurate information such as a detection error made by the sensor, and then, generates accurate object information to merge the object information into the surrounding map information. The integration unit **12** generates an integration result in which the host vehicle travel information and the object information are merged (integrated) into the surrounding map information (also referred to as integration processing). The integration unit **12** outputs the integration result to the behavior prediction unit **9**, and the integration result and the planned travel route information to the autonomous driving control unit **17**.

[0032] The behavior prediction unit **9** receives the integration result from the integration unit **12** and calculates the positional relation between the host vehicle V and the surrounding object at a future time or the like, and generates a behavior prediction result in which the host vehicle travel information and the object information at the future time that are obtained by the calculation are merged into the surrounding map information. The behavior prediction unit **9** stores and reads the generated behavior prediction result and outputs the behavior prediction result to the integration unit **12**, as necessary.

[0033] The road shape acquisition unit **10** extracts a leading vehicle LV from the behavior prediction result and acquires gradient information on a traveling road surface of the leading vehicle LV at the future time. Further, the road shape acquisition unit **10** acquires gradient information on a traveling road surface of the host vehicle V at the future time from the behavior prediction result. Note that the gradient information on the traveling road surface is a gradient value acquired from the surrounding map information based on the positional information on the host vehicle V and the leading vehicle LV in the behavior prediction result.

[0034] Note that the gradient information on the traveling road surface may be directly acquired from the surrounding map information when the gradient value is included in the surrounding map information or the gradient value may be calculated from information on road coordinate points (latitude, longitude, altitude) that define the road shape included in the surrounding map information to be acquired.

[0035] The departure determination unit **11** acquires the gradient information on the traveling road surface of each of the host vehicle V and the leading vehicle LV at the future time from the road shape acquisition unit **10** and determines whether the leading vehicle LV departs from a detection range of the external environment sensor **1** at the future time.

[0036] An autonomous driving determination unit **18** of the autonomous driving control unit **17** receives the integration result and the planned travel route information from the integration unit **12** and the host vehicle travel information from the vehicle sensor **6**, and calculates the behavior, route, speed, or the like necessary for autonomous driving. The vehicle control unit **19** of the autonomous driving control unit **17** receives the calculation result from the autonomous driving determination unit **18** and controls (autonomous driving control) the vehicle drive unit **20** (engine **21**, brake **22**, steering **23**).

[0037] Next, FIG. **2** is a view showing the configuration of the external environment sensor **1** in the autonomous driving vehicle (host vehicle V). One camera sensor **2** and two radar sensors **3** are provided on the front side of the host vehicle V. A detection range SR**1** of the camera sensor **2** is set facing the front, a detection range SR**2** of the radar sensor **3** on the front-left side is set slightly facing the left, and a detection range SR**3** of the radar sensor **3** on the front-right side is set slightly facing the right, and with the detection ranges overlapping with each other, the external environment sensor **1** obtains a wide detection range. An origin a of coordinates of the host vehicle V is defined at the rear end at the center of the vehicle, and an advancing direction is represented by an x-direction, a lateral direction by a y-direction, and a height direction by a z-direction.

[0038] Hereinafter, description will be made using an example of traveling a road (overpass) ascending and continuously descending.

[0039] Upon executing the autonomous driving by the vehicle control device AD**1**, the integration unit **12**, the behavior prediction unit **9**, the road shape acquisition unit **10**, and the departure determination unit **11** start processing.

[0040] FIG. **3** is a flowchart of processing performed by the behavior prediction unit **9**, and FIG. **5** is a flowchart of processing performed by the integration unit **12**. Hereinafter, the flowchart of processing performed by the behavior prediction unit **9** will be described.

[0041] First, in step S**101**, the behavior prediction unit **9** acquires the integration result FU**1** at the current time t**1** from the integration unit **12**.

[0042] Herein, FIG. **4** shows a scene at the current time t**1**, and views of the integration result FU**1** and the behavior prediction result CA**1**.

[0043] The scene at the current time t**1** of FIG. **4** is a scene in which the host vehicle V is traveling an overpass by following the leading vehicle LV. The host vehicle V is traveling at a speed decelerated from a predetermined speed set by the host vehicle V, in order to keep a vehicle-to-vehicle distance from the leading vehicle LV. It is perceived from the scene that the host vehicle V and the leading vehicle LV are traveling an ascending gradient on the overpass, and the external environment sensor **1** is detecting the leading vehicle LV, which is positioned within the detection ranges SR**1**, SR**2**, SR**3** of the external environment sensor **1** of the host vehicle V.

[0044] The integration result FU**1** of FIG. **4** is the integration result generated by the integration unit **12** by merging the host vehicle travel information and the object information at the current time t**1** into the surrounding map information. For the description, FIG. **4** shows a traffic lane of the road, host vehicle information V**1** indicating the position and the size of the host vehicle V, and leading vehicle information LV**1** indicating the position and the size of the leading vehicle LV, in a grid in the x-y directions. Regarding the positions of the host vehicle information V**1** and the leading vehicle information LV**1**, the positions of an origin a**1** of coordinates of the host vehicle V and an origin b**1** of coordinates of the leading vehicle LV are computed from the host vehicle travel information and the object information in the integration result, and the sizes of the vehicles are defined in the surrounding map information on the basis of these origins.

[0045] The description of the steps of FIG. **3** will be resumed.

[0046] In step S**102**, the behavior prediction unit **9** generates the behavior prediction result CA**1** at a future time t**2**. The future time t**2** may be a time preset relative to the current time t**1** or may be a time set in accordance with the information on the host vehicle V and the leading vehicle LV, such as the speed, acceleration, advancing direction, traveling traffic lane, and surrounding traffic

environment.

[0047] The behavior prediction result CA**1** of FIG. **4** shows the behavior prediction result generated such that the behavior prediction unit **9** computes positions of an origin a**2** of coordinates of the host vehicle V and an origin b**2** of coordinates of the leading vehicle LV at the future time t**2**, and the sizes of the vehicles are defined in the surrounding map information on the basis of these origins.

[0048] The origin a**2** of coordinates and the origin b**2** of coordinates are calculated using the information on the host vehicle V and the leading vehicle LV, such as the speed, acceleration, advancing direction, and traveling traffic lane, from the host vehicle travel information, the object information, and the surrounding map information in the integration result FU**1**.

[0049] In the behavior prediction result CA**1**, host vehicle information V**2** and leading vehicle information LV**2** indicate a vehicle-to-vehicle relation in the coordinate system with x-y directions and host vehicle information GV**2** and leading vehicle information GLV**2** indicate a gradient relation in the coordinate system with x-y directions.

[0050] In step S**103**, the road shape acquisition unit **10** of the behavior prediction unit **9** acquires, from the surrounding map information, the gradient values as road shape information (gradient information) on the traveling road surface of the host vehicle V and the leading vehicle LV at the future time t**2**, based on the positions of the host vehicle information GV**2** and the leading vehicle information GLV**2**. The actual gradient of the overpass differs depending on the roads, but as an example here, the gradient value in the host vehicle information GV**2** is assumed to be +5% and the gradient value in the leading vehicle information GLV**2** is assumed to be −5%.

[0051] In step S**104**, the departure determination unit **11** of the behavior prediction unit **9** determines whether the leading vehicle LV departs from the detection range of the external environment sensor **1** at the future time t**2**. The departure determination unit **11** compares the gradient value of the host vehicle V and the gradient value of the leading vehicle LV that are acquired in step S**103** to compute the difference (difference in gradient) therebetween, and proceeds to step S**105** when the difference is equal to or greater than a specified value (step S**104**: YES), and ends the flow when the difference is less than the specified value (step S**104**: NO).

[0052] In the following example, since the difference in gradient between the host vehicle V and the leading vehicle LV is greater than the specified value, the determination in step S**104** is YES (departure is determined).

Gradient value of host vehicle V: +5%   (a)

Gradient value of leading vehicle LV: −5%   (b)

Difference in gradient (a−b): 10%   (c)

Specified value: 7%   (d) [0053] Determination in S**104** (c≥d?): YES (departure is determined)

[0054] In traveling the overpass, as the difference in gradient between the host vehicle V and the leading vehicle LV increases, the external environment sensor **1** is more likely to fail to detect the leading vehicle LV because the leading vehicle LV is positioned outside the detection range of the external environment sensor **1** or enters a dead angle of an ascending gradient. The departure determination unit **11** utilizes such a phenomenon. That is, the difference in gradient with which the external environment sensor **1** cannot perform the detection is set in advance as the specified value, and when the difference in gradient of the traveling road surface between the host vehicle V and the leading vehicle LV is significant to be equal to or greater than the specified value, the departure determination unit **11** acknowledges that the leading vehicle LV is positioned outside the detection ranges SR**1**, SR**2**, SR**3** of the external environment sensor **1** and determines the departure. Note that in the present example, for the description, the specified value of the gradient is set at 7%, but

may be set at the optimum value considering the actual vehicle shape, the attachment position of the external environment sensor, and the like.

[0055] In step S**105**, the behavior prediction unit **9** stores the behavior prediction result CA**1** at the future time t**2** in the memory **8** and ends the flow.

[0056] Next, the flowchart of the processing performed by the integration unit **12** will be described.

[0057] In step S**201**, the integration unit **12** acquires the external environment information from the external environment sensor **1**, the host vehicle positional information and the surrounding map information from the map unit **5**, and the host vehicle travel information from the vehicle sensor **6** at the current time t**2** (corresponding to the future time t**2** in steps S**102**, S**103**, S**104**, S**105** of the behavior prediction unit **9**).

[0058] Herein, FIG. **6** shows a scene at the current time t**2**, and views of the integration result FU**2** and the regenerated integration result FU**3**.

[0059] In FIG. **6**, the scene at the current time t**2** illustrates the host vehicle V traveling the overpass by following the leading vehicle LV, and the time proceeds from the current time t**1** described in FIG. **4**. The host vehicle V is traveling an ascending gradient of the overpass, while the leading vehicle LV is traveling a descending gradient of the overpass. It is perceived from the scene that at the current time t**2**, the leading vehicle LV departs from the detection ranges SR**1**, SR**2**, SR**3** of the external environment sensor **1** of the host vehicle V, and the external environment sensor **1** has lost track of the leading vehicle LV.

[0060] In step S**202**, the integration unit **12** generates the integration result FU**2** at the current time t**2** based on the information acquired in step S**201**. Since the external environment sensor **1** has lost track of the leading vehicle LV, the integration result FU**2** has host vehicle information V**3**, but no leading vehicle information.

[0061] As described above, despite the presence of the leading vehicle LV ahead of the host vehicle V, if the integration result FU**2** without the leading vehicle information is output to the autonomous driving control unit **17** in the subsequent step, the vehicle-to-vehicle distance between the host vehicle V and the leading vehicle LV is reduced, which could put them in danger. That is, if the autonomous driving determination unit **18** determines from the integration result FU**2** that the leading vehicle LV as a target vehicle to be followed has disappeared and the vehicle control unit **19** performs acceleration control of the host vehicle V so as to return the speed to a predetermined speed, the vehicle-to-vehicle distance between the host vehicle V and the leading vehicle LV, which has been kept so far, is reduced.

[0062] In step S**203**, the integration unit **12** determines whether the leading vehicle information is lost at the current time t**2**. The integration unit **12** monitors how the state detected by the external environment sensor **1** has changed between the current time t**2** and the time before the current time t**2**, and proceeds to step S**204** when a detected state has changed to an undetected state and the leading vehicle information is lost (step S**203**: YES), and proceeds to step S**205** in other cases (step S**203**: NO).

[0063] In step S**204**, the integration unit **12** acquires, from the behavior prediction unit **9**, the stored behavior prediction result CA**1** at the future time t**2** (corresponding to the current time t**2**). The integration unit **12** compares the integration result FU**2** and the behavior prediction result CA**1**, and makes an origin a**3** of coordinates of the host vehicle information V**3** and the origin a**2** of coordinates of the host vehicle information V**2** consistent with each other. The integration unit **12** calculates the positional relation between the origin a**3** of coordinates of the host vehicle information V**3** and the origin b**2** of coordinates of the leading vehicle information LV**2** and computes the position of the origin b**2** of coordinates of the leading vehicle information LV**2** in the integration result FU**2**. The integration unit **12** defines the origin b**2** of coordinates in the integration result FU**2** and defines the size of the leading vehicle LV based on the origin b**2** of coordinates to regenerate the integration result FU**2** as the integration result FU**3**.

[0064] That is, even if the external environment sensor **1** actually loses track of the leading vehicle

LV at the current time t**2**, the integration unit **12** uses the behavior prediction result CA**1** computed and stored in advance in the behavior prediction unit **9** to merge the leading vehicle information LV**2** into the integration result FU**2**, so that the integration result FU**2** can be regenerated (integration processing) as the integration result FU**3** matching the actual situation.

[0065] In step S**205**, the integration unit **12** outputs, to the autonomous driving control unit **17**, the planned travel route information and the integration result generated in step S**202** or the integration result regenerated in step S**204**.

[0066] With the aforementioned processing, in the signal processing device **7** of the vehicle control device AD**1**, the behavior prediction unit **9** generates and stores the behavior prediction result CA**1** at the future time t**2** of the host vehicle V and the leading vehicle LV and the road shape acquisition unit **10** acquires the road shape information (gradient information) on the traveling road surface of the host vehicle V and the leading vehicle LV at the future time t**2**, so that the departure determination unit **11** can determine whether the leading vehicle LV departs from the detection ranges SR**1**, SR**2**, SR**3** of the external environment sensor **1** at the future time t**2**.

[0067] Further, in the signal processing device **7** of the vehicle control device AD**1**, when the leading vehicle LV actually departs from the detection ranges SR**1**, SR**2**, SR**3** of the external environment sensor **1** at the current time t**2** (corresponding to the future time t**2**), the integration unit **12** acquires the behavior prediction result CA**1** corresponding to the current time t**2** (instead of the external environment information acquired by the external environment sensor **1**), and can regenerate the integration result FU**3** in which the leading vehicle information LV**2** is merged into the integration result FU**2** (in other words, the integration result FU**2** interpolated with the leading vehicle information LV**2**).

[0068] Further, in the signal processing device **7** of the vehicle control device AD**1**, when the leading vehicle information acquired by the external environment sensor **1** is temporarily lost at the current time t**2**, the integration unit **12** outputs the planned travel route information and the integration result FU**3** to the autonomous driving control unit **17**, so that the autonomous driving control unit **17** performs vehicle control using the leading vehicle information LV**2** in the integration result FU**3**, thus suppressing a phenomenon in which the host vehicle V accelerates due to losing track of the leading vehicle LV as a target to be followed. As a result, the host vehicle V and the leading vehicle LV can safely travel keeping an adequate vehicle-to-vehicle distance therebetween.

[0069] That is, the signal processing device **7** includes the integration unit **12** and the behavior prediction unit **9**, and the behavior prediction unit **9** includes the road shape acquisition unit **10** and the departure determination unit **11**. The integration unit **12** performs integration processing of the external environment information acquired by the external environment sensor **1** mounted on the host vehicle V and the host vehicle travel information acquired by the vehicle sensor **6**. The behavior prediction unit **9** predicts the behavior at a future time of the host vehicle V and another vehicle detected by the external environment sensor **1**, based on the integration result from the integration unit **12**. The road shape acquisition unit **10** obtains the road shape information (gradient information) on the traveling road surface of the host vehicle V and the other vehicle at the future time. The departure determination unit **11** determines whether the other vehicle departs from the detection range of the external environment sensor **1** at the future time, based on the behavior prediction result of the host vehicle V and the other vehicle and the road shape information (gradient information). The integration unit **12** uses the behavior prediction result for the integration processing in accordance with the determination result from the departure determination unit **11**.

[0070] According to the present embodiment, a cause for losing track of the leading vehicle LV by the external environment sensor **1** can be more accurately determined as compared to the conventional signal processing devices, so that it is possible to provide the signal processing device **7** capable of more surely keeping a vehicle-to-vehicle distance between the leading vehicle LV and

the host vehicle V in traveling by following.

Embodiment 2

[0071] Next, an example of traveling a road (sag) descending and continuously ascending will be described in an embodiment 2.

[0072] Note that the embodiment 2 is an example of traveling a sag in place of the travel road of the embodiment 1, and the configurations of the vehicle control device AD**1** (including the signal processing device **7**) described in FIG. **1** and the external environment sensor **1** described in FIG. **2**, and the flowcharts of the processing performed by the behavior prediction unit **9** and the integration unit **12** described in FIG. **3** and FIG. **5**, respectively, are the same as those of the embodiment 1 and thus, the description will be omitted.

[0073] FIG. **7** shows a scene at the current time t**101**, and views of the integration result FU**101** and the regenerated integration result FU**102**.

[0074] In FIG. **7**, the scene at the current time t**101** is a scene in which the host vehicle V is traveling a sag by following the leading vehicle LV. The host vehicle V is traveling at a speed decelerated from a predetermined speed set by the host vehicle V, in order to keep a vehicle-to-vehicle distance from the leading vehicle LV. The host vehicle V is traveling a descending gradient of the sag, while the leading vehicle LV is traveling an ascending gradient of the sag. It is perceived from the scene that at the current time t**101**, the leading vehicle LV departs from the detection ranges SR**1**, SR**2**, SR**3** of the external environment sensor **1** of the host vehicle V and the external environment sensor **1** has lost track of the leading vehicle LV.

[0075] Hereinafter, the processing performed by the integration unit **12** will be described using the flowchart.

[0076] In step S**202**, the integration unit **12** generates the integration result FU**101** at the current time t**101** based on the information acquired in step S**201**. Since the external environment sensor **1** has lost track of the leading vehicle LV, the integration result FU**101** has host vehicle information V**101**, but no leading vehicle information.

[0077] As described above, despite the presence of the leading vehicle LV ahead of the host vehicle V, if the integration result FU**101** without the leading vehicle information is output to the autonomous driving control unit **17** in the subsequent step, the vehicle-to-vehicle distance between the host vehicle V and the leading vehicle LV is reduced, which could put them in danger. That is, if the autonomous driving determination unit **18** determines from the integration result FU**101** that the leading vehicle LV as a target vehicle to be followed has disappeared and the vehicle control unit **19** performs acceleration control of the host vehicle V so as to return the speed to a predetermined speed, the vehicle-to-vehicle distance between the host vehicle V and the leading vehicle LV, which has been kept so far, is reduced.

[0078] In step S**203**, the integration unit **12** determines whether the leading vehicle information is lost at the current time t**101**. The integration unit **12** monitors how the state detected by the external environment sensor **1** has changed between the current time t**101** and the time before the current time t**101**, and proceeds to step S**204** when a detected state has changed to an undetected state and the leading vehicle information is lost (step S**203**: YES), and proceeds to step S**205** in other cases (step S**203**: NO).

[0079] In step S**204**, the integration unit **12** acquires, from the behavior prediction unit **9**, the stored behavior prediction result (not shown) at the future time t**101** (corresponding to the current time t**101**). The integration unit **12** compares the integration result FU**101** and the behavior prediction result, and makes an origin a**101** of coordinates of the host vehicle information V**101** and an origin (not shown) of coordinates of the host vehicle information in the behavior prediction result consistent with each other. The integration unit **12** calculates the positional relation between the origin a**101** of coordinates of the host vehicle information V**101** and an origin b**100** of coordinates of the leading vehicle information LV**100** in the behavior prediction result and computes the position of the origin b**100** of coordinates of the leading vehicle information LV**100** in the

integration result FU**101**. The integration unit **12** defines the origin b**100** of coordinates in the integration result FU**101** and defines the size of the leading vehicle LV based on the origin b**100** of coordinates to regenerate the integration result FU**101** as the integration result FU**102**.

[0080] That is, even if the external environment sensor **1** actually loses track of the leading vehicle LV at the current time t**101**, the integration unit **12** uses the behavior prediction result computed and stored in advance in the behavior prediction unit **9** to merge the leading vehicle information LV**100** into the integration result FU**101**, so that the integration result FU**101** can be regenerated (integration processing) as the integration result FU**102** matching the actual situation.

[0081] In step S**205**, the integration unit **12** outputs, to the autonomous driving control unit **17**, the planned travel route information and the integration result generated in step S**202** or the integration result regenerated in step S**204**.

[0082] With the aforementioned processing, in the signal processing device **7** of the vehicle control device AD**1**, the behavior prediction unit **9** generates and stores the behavior prediction result at the future time t**101** of the host vehicle V and the leading vehicle LV and the road shape acquisition unit **10** acquires the road shape information (gradient information) on the traveling road surface of the host vehicle V and the leading vehicle LV at the future time t**101**, so that the departure determination unit **11** can determine whether the leading vehicle LV departs from the detection ranges SR**1**, SR**2**, SR**3** of the external environment sensor **1** at the future time t**101**.

[0083] Further, in the signal processing device **7** of the vehicle control device AD**1**, when the leading vehicle LV actually departs from the detection ranges SR**1**, SR**2**, SR**3** of the external environment sensor **1** at the current time t**101** (corresponding to the future time t**101**), the integration unit **12** acquires the behavior prediction result corresponding to the current time t**101** (instead of the external environment information acquired by the external environment sensor **1**), and can regenerate the integration result FU**102** in which the leading vehicle information LV**100** is merged into the integration result FU**101** (in other words, the integration result FU**101** interpolated with the leading vehicle information LV**100**).

[0084] Further, in the signal processing device **7** of the vehicle control device AD**1**, when the leading vehicle information acquired by the external environment sensor **1** is temporarily lost at the current time t**101**, the integration unit **12** outputs the planned travel route information and the integration result FU**102** to the autonomous driving control unit **17**, so that the autonomous driving control unit **17** performs vehicle control using the leading vehicle information LV**100** in the integration result FU**102**, thus suppressing a phenomenon in which the host vehicle V accelerates due to losing track of the leading vehicle LV as a target to be followed. As a result, the host vehicle V and the leading vehicle LV can safely travel keeping an adequate vehicle-to-vehicle distance therebetween.

[0085] According to the present embodiment 2, as with the aforementioned embodiment 1, a cause for losing track of the leading vehicle LV by the external environment sensor **1** can be more accurately determined as compared to the conventional signal processing devices, so that it is possible to provide the signal processing device **7** capable of more surely keeping a vehicle-to-vehicle distance between the leading vehicle LV and the host vehicle V in traveling by following.

[0086] Note that the present invention is not limited to the aforementioned embodiments and includes various modifications. For example, the aforementioned embodiments have been described in detail for easier understanding of the present invention and are not necessarily limited to those including all the described configurations. Further, it is possible to replace a portion of the configuration of one embodiment with that of another embodiment, or it is also possible to add the configuration of one embodiment to the configuration of another embodiment. Further, for a part of the configuration of each embodiment, addition and deletion of or replacement with another configuration may be applicable individually or in combination.

[0087] First, in the aforementioned embodiments, acquiring the gradient information on the traveling road surface from the surrounding map information has been described, but the gradient

value of the leading vehicle LV may be computed using the road shape that can be acquired from the external environment information from the external environment sensor **1** or the moving amount in the height direction of the leading vehicle LV, instead of using the surrounding map information, or the gradient value of the host vehicle V may be computed from an inclination of the host vehicle V that can be acquired from the vehicle sensor **6**.

[0088] Further, in the aforementioned embodiments, acquiring the gradient information (gradient value) on the traveling road surface as the road shape information to determine the departure has been described, but altitude information or the like may be acquired in place of or together with the gradient information.

[0089] Next, in the aforementioned embodiments, calculating the origin a**2** of coordinates and the origin b**2** of coordinates from the host vehicle travel information, the object information, and the surrounding map information in the integration result FU**1** has been described, but in this respect, the calculation may be performed further accurately by using the behavior of the host vehicle V and the leading vehicle LV immediately before, a database of empirical knowledge in the past, and the surrounding traffic environment information.

[0090] Next, in the aforementioned embodiments, outputting the planned travel route information and the integration result FU**3** regenerated in step S**204** to the autonomous driving control unit **17**, in step S**205** performed by the integration unit **12**, has been described, but for the purpose of clarifying the origin of the integration result FU**3**, information indicating that the integration result FU**3** is a result regenerated based on the behavior prediction result CA**1** may also be additionally output to the autonomous driving control unit **17**.

[0091] Further, the components described above may be in part or entirely configured with hardware or may be implemented by a processor executing programs. Furthermore, the illustrated control and information lines are those considered necessary for the description, but do not necessarily indicate all of those in a product. Almost all the components may be considered actually connected with one another.

REFERENCE SIGNS LIST

[0092] **1** External environment sensor [0093] **6** Vehicle sensor [0094] **7** Signal processing device [0095] **9** Behavior prediction unit [0096] Road shape acquisition unit [0097] **11** Departure determination unit [0098] **12** Integration unit [0099] **17** Autonomous driving control unit [0100] **20** Vehicle drive unit [0101] AD**1** Vehicle control device [0102] CA**1** Behavior prediction result [0103] FU**1** Integration result [0104] FU**2** Integration result [0105] FU**3** Integration result [0106] LV Leading vehicle [0107] V Host vehicle

Claims

1. A signal processing device comprising: an integration unit that performs integration processing of external environment information acquired by an external environment sensor mounted on a host vehicle and host vehicle travel information acquired by a vehicle sensor; and a behavior prediction unit that predicts behavior at a future time of the host vehicle and another vehicle detected by the external environment sensor, based on an integration result from the integration unit, wherein the behavior prediction unit includes: a road shape acquisition unit that obtains road shape information on a traveling road surface of the host vehicle and the other vehicle at the future time; and a departure determination unit that determines whether the other vehicle departs from a detection range of the external environment sensor at the future time, based on a behavior prediction result of the host vehicle and the other vehicle and the road shape information, and the integration unit uses the behavior prediction result for the integration processing in accordance with a determination result from the departure determination unit.

2. The signal processing device according to claim 1, wherein the road shape information is gradient information.

3. The signal processing device according to claim 1, wherein when it is determined that the other vehicle departs from the detection range of the external environment sensor at the future time, based on the behavior prediction result of the host vehicle and the other vehicle, and the road shape information, the behavior prediction unit stores the behavior prediction result.

4. The signal processing device according to claim 1, wherein the departure determination unit compares gradient values on the traveling road surface of the host vehicle and the other vehicle at the future time and determines whether the other vehicle departs from the detection range of the external environment sensor at the future time.

5. The signal processing device according to claim 1, wherein when the other vehicle actually departs from the detection range of the external environment sensor at a current time, the integration unit acquires the behavior prediction result corresponding to the current time and regenerates the integration result from the integration unit.

6. The signal processing device according to claim 1, wherein the road shape acquisition unit obtains the road shape information based on map information on the traveling road surface of the host vehicle and the other vehicle at the future time.

7. The signal processing device according to claim 1, wherein the road shape acquisition unit obtains the road shape information based on a road shape that can be acquired from the external environment information from the external environment sensor.

8. The signal processing device according to claim 1, wherein the road shape acquisition unit obtains the road shape information based on a moving amount in a height direction of the other vehicle.

9. The signal processing device according to claim 1, wherein the road shape acquisition unit obtains the road shape information based on an inclination of the host vehicle that can be acquired from the vehicle sensor.