




US 20250258342A1

(19) **United States**(12) **Patent Application Publication**
Higley et al.(10) **Pub. No.: US 2025/0258342 A1**(43) **Pub. Date: Aug. 14, 2025**(54) **FIBER OPTIC FERRULE AND FIBER OPTIC
FERRULE RECEIVER**(71) Applicant: **US Conec Ltd.**, Hickory, NC (US)(72) Inventors: **Jason Higley**, Hickory, NC (US);
Darrell R. Childers, Hickory, NC
(US); **Craig M. Conrad**, Hickory, NC
(US)(21) Appl. No.: **19/196,010**(22) Filed: **May 1, 2025****Related U.S. Application Data**(60) Division of application No. 18/444,680, filed on Feb.
17, 2024, now Pat. No. 12,321,017, which is a con-
tinuation of application No. 17/918,058, filed on Oct.
10, 2022, filed as application No. PCT/US2021/
028925 on Apr. 23, 2021, now Pat. No. 11,914,195.(60) Provisional application No. 63/014,491, filed on Apr.
23, 2020, provisional application No. 63/047,657,
filed on Jul. 2, 2020.**Publication Classification**(51) **Int. Cl.**
G02B 6/38 (2006.01)(52) **U.S. Cl.**CPC **G02B 6/3821** (2013.01); **G02B 6/3831**
(2013.01); **G02B 6/3857** (2013.01); **G02B**
6/3869 (2013.01); **G02B 6/387** (2013.01);
G02B 6/3885 (2013.01)(57) **ABSTRACT**

A fiber optic ferrule receiver includes a main body that has an opening extending between the front end and the rear end and being defined at least by a portion of internal surfaces of the four sides. A first side in the opening has first tapered surface and a second tapered surface, the first tapered surface reducing the opening between the rear end and a first position and the second tapered surface increasing the opening between the first position and the front end. There is also a second side in the opening and across the opening from the first side, the second side has a third tapered surface and a fourth tapered surface, the third tapered surface reducing the opening between the rear end and a second position and the second tapered surface increasing the opening between the second position and the front end. There is also a first projection extending into the opening from the first side to engage a first portion of the fiber optic ferrule at the first position, and a second projection extending into the opening from second side to engage a second portion of the fiber optic ferrule at the second position.






Fig. 2




Fig. 1




Fig. 3




Fig. 4




Fig. 5




Fig. 6





Fig. 7






Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 12A




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 20




Fig. 22




Fig. 21




Fig. 23






Fig. 24






Fig. 27




Fig. 28





Fig. 29






Fig. 32




Fig. 33A




Fig. 33




Fig. 34




Fig. 35




Fig. 36




Fig. 37




Fig. 38




Fig. 39

FIBER OPTIC FERRULE AND FIBER OPTIC FERRULE RECEIVER

REFERENCE TO RELATED CASE

[0001] This application claims priority under 35 U.S.C. § 119 (e) to U.S. provisional application No. 63/014,491 filed on Apr. 23, 2020, and to U.S. provisional application No. 63/047,657 filed on Jul. 2, 2020, and under 35 U.S.C. § 120 to U.S. patent application Ser. No. 17/918,058, filed on Oct. 10, 2022, and also to U.S. patent application Ser. No. 18/444,680, filed on Feb. 17, 2024, the contents of which are hereby incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

[0002] Transceivers interface with various duplex LC connectors with one optical link for the transmitter and another for the receiver. Duplex LC connectors are also used in non-transceiver interfaces, which have tight space requirements. Many such LC duplex connectors interface with transceivers having a footprint according to various industry multisource agreements (MSAs). Two of these include the Quad Small Form-factor Pluggable (QSFP) or the Small Form-factor Pluggable (SFP) MSAs and are defined by specifications associated with these MSAs. These connectors are used in communications applications with speeds up to 400 GBps, with higher speeds currently in research and development. One such duplex connector with a housing and a push-pull boot is illustrated in Applicant's WIPO patent application publication WO 2019/195652, filed Apr. 5, 2019.

[0003] By definition, duplex connectors can only accommodate two optical fiber ferrules (and hence, two optical fibers). This also provides a limitation on how many channels may be interfaced with the transceiver. Conventional non-duplex multi-fiber ferrules, such as the ubiquitous MT-ferrule, has a footprint that allows only one MT-ferrule to interface with the transceiver. For example, the MT-ferrule has shoulder(s) at the back that help the MT ferrule seat inside a typical MPO connector housing, in which the ferrule is used. The shoulder contributes to a larger footprint of the MT-ferrule that has a typical height of 3 mm, a length of 8 mm, and a width of 7 mm. Further, molding such ferrules to simply reduce the footprint is challenging with current multi-fiber ferrule designs. Accordingly, at this time, only one MT ferrule in an MPO connector housing footprint meets the space requirements of an SFP/QSFP footprint transceiver interface. Accordingly, Applicant provides a multi-fiber ferrule that allows for a plurality of duplex connector housings to fit in a footprint matching that of a QSFP/SFP footprint transceiver interface, and supporting more than two optical fibers (e.g., 16 optical fibers). As a result, two or more of such MT-like ferrules within respective housings can be interfaced with an SFP/QSFP transceiver interface.

[0004] In order to use the new higher density fiber optic ferrule, there needs to be a new housing that can receive the new fiber optic ferrule and mate to the transceiver or other assembly.

SUMMARY OF THE INVENTION

[0005] According to one aspect, the present invention is directed to a fiber optic ferrule receiver to receive a fiber optic ferrule therein that includes a main body extending

between a front end and a rear end and having four sides, the main body having an opening extending between the front end and the rear end and being defined at least by a portion of internal surfaces of the four sides, a first side in the opening having a first tapered surface and a second tapered surface, the first tapered surface reducing the opening between the rear end and a first position and the second tapered surface increasing the opening between the first position and the front end, a second side in the opening and across the opening from the first side, the second side having a third tapered surface and a fourth tapered surface, the third tapered surface reducing the opening between the rear end and a second position and the second tapered surface increasing the opening between the second position and the front end, a first projection extending into the opening from the first side to engage a first portion of the fiber optic ferrule at the first position, and a second projection extending into the opening from second side to engage a second portion of the fiber optic ferrule at the second position.

[0006] In some embodiments, there is at least one tab extending from the rear end, the tab having opposing cut-outs to form legs.

[0007] In some embodiments, the rear end has a rear surface, the rear surface being non-perpendicular to a longitudinal axis extending through the opening from the front end to the rear end.

[0008] In some embodiments, a configuration of the rear end of the main body corresponds to the location of the first projection and the second projection in the opening of the fiber optic ferrule receiver.

[0009] In some other embodiments, the tab has a rearmost portion, the rear most portion having a surface that is orthogonal to a longitudinal axis extending through the opening from the front end to the rear end.

[0010] In some embodiments, the main body has a plurality of shoulders extending from the front end to the rear end to align the fiber optic ferrule receiver with an adapter.

[0011] In some embodiments, each of the first projection and the second projection have a length, the length of the first projection is less than the second projection.

[0012] In some embodiments, the first projection and the second projection provide a keying function for the fiber optic ferrule.

[0013] In some embodiments, the first and second tapered surfaces on both the first side and the second side are connected to one another across at least a portion of the opening.

[0014] In some embodiments, the second tapered surface of the first side comprises two second tapered surfaces and the first projection is disposed between the two second tapered surfaces.

[0015] In other embodiments, the fourth tapered surface of the second side comprises two fourth tapered surfaces and the second projection is disposed between the two fourth tapered surfaces.

[0016] It is to be understood that both the foregoing general description and the following detailed description of the present embodiments of the invention are intended to provide an overview or framework for understanding the nature and character of the invention as it is claimed. The accompanying drawings are included to provide a further understanding of the invention, and are incorporated into and constitute a part of this specification. The drawings illustrate various embodiments of the invention and,

together with the description, serve to explain the principles and operations of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] FIG. 1 is a top perspective view of one embodiment of a multi-fiber ferrule according to the present invention;
 [0018] FIG. 2 is a bottom perspective view of the multi-fiber ferrule in FIG. 1;
 [0019] FIG. 3 is a rear elevational view of the multi-fiber ferrule in FIG. 1;
 [0020] FIG. 4 is front elevational view of the multi-fiber ferrule in FIG. 1;
 [0021] FIG. 5 is a cross sectional view from the rear of the multi-fiber ferrule in FIG. 1;
 [0022] FIG. 6 is a cross sectional view of the multi-fiber ferrule in FIG. 1;
 [0023] FIG. 7 is a front elevational view of the multi-fiber ferrule in FIG. 1;
 [0024] FIG. 8 is a perspective view of one embodiment of a fiber optic connector according to the present invention from the top left and using the multi-fiber ferrule in FIG. 1;
 [0025] FIG. 9 is a perspective view of the fiber optic connector in FIG. 8 from the bottom right and using the multi-fiber ferrule in FIG. 1;
 [0026] FIG. 10 is an exploded view of the fiber optic connector in FIG. 8;
 [0027] FIG. 11 is a left side perspective view of one embodiment of a fiber optic ferrule receiver/cap with the multi-fiber ferrule of FIG. 1 disposed therein;
 [0028] FIG. 12 is a cross-sectional view of the fiber optic ferrule receiver/cap of FIG. 1;
 [0029] FIG. 12A is an elevational view of a cross section of the fiber optic ferrule receiver/cap of FIG. 1;
 [0030] FIG. 13 is a front elevational view of the fiber optic ferrule receiver/cap of FIG. 11;
 [0031] FIG. 14 is a rear perspective view of the fiber optic ferrule receiver/cap of FIG. 11;
 [0032] FIG. 15 is a perspective view from the bottom left of a cross-section of the fiber optic connector of FIG. 8;
 [0033] FIG. 16 is a left side elevational view of the fiber optic connector in FIG. 8;
 [0034] FIG. 17 is a left side elevational view of the fiber optic connector in FIG. 8 with fiber optic ferrule receiver/cap of FIG. 11 removed;
 [0035] FIG. 18 is a perspective view of the housing of the fiber optic connector in FIG. 8 from the top rear;
 [0036] FIG. 19 is a perspective view of the housing of the fiber optic connector in FIG. 8 from the bottom left side;
 [0037] FIG. 20 is a perspective view of a cross section of the housing in FIG. 18 with the second portion of the rear section removed;
 [0038] FIG. 21 is a front elevational view of the housing of the fiber optic connector in FIG. 8;
 [0039] FIG. 22 is a perspective view of the housing of the fiber optic connector in FIG. 8 from the rear;
 [0040] FIG. 23 is a rear elevational view of the housing of the fiber optic connector in FIG. 8;
 [0041] FIG. 24 is an exploded view of a cross section of the housing of the fiber optic connector in FIG. 8 with the second portion on the left side;
 [0042] FIG. 25 is an elevational view of a cross section of the fiber optic connector in FIG. 8 with a push-pull boot and connector latch installed thereon;

[0043] FIG. 26 an elevational view of a cross section of the fiber optic connector in FIG. 8 with a push-pull boot and connector latch installed thereon and at a different position within the connector;

[0044] FIG. 27 is a perspective view of the fiber optic connector in FIG. 25 from the top left;

[0045] FIG. 28 is an elevational view of a cross section of a portion of the fiber optic connector in FIG. 25;

[0046] FIG. 29 is a perspective view of another embodiment of a fiber optic connector according to the present invention;

[0047] FIG. 30 is a front elevational view of the housing in the fiber optic connector in FIG. 29;

[0048] FIG. 31 is a perspective view of a cross section of the housing in FIG. 30;

[0049] FIG. 32 is an elevational view of a cross section view of the fiber optic connector in FIG. 29;

[0050] FIG. 33 is a perspective view of the fiber optic ferrule receiver/cap used with the fiber optic connector in FIG. 29;

[0051] FIG. 33A is a left side elevational view of the fiber optic ferrule receiver/cap in FIG. 29;

[0052] FIG. 34 is a cross section of the fiber optic ferrule receiver/cap of FIG. 33 with a multi-fiber ferrule installed therein;

[0053] FIG. 35 is a perspective view of another embodiment of a combination of a fiber optic ferrule receiver/cap and housing according to the present invention;

[0054] FIG. 36 illustrates the multi-fiber ferrule and the spring disposed within the opening of the housing in FIG. 35;

[0055] FIG. 37 is a perspective view of a cross section of the housing in FIG. 35 showing the front end thereof;

[0056] FIG. 38 is a perspective view of the housing in FIG. 35 without the multi-fiber ferrule installed;

[0057] FIG. 39 is an exploded perspective view of another embodiment of a housing according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0058] Reference will now be made in detail to the present preferred embodiment(s) of the invention, examples of which are illustrated in the accompanying drawings. Whenever possible, the same reference numerals will be used throughout the drawings to refer to the same or like parts.

[0059] Illustrated in FIGS. 1-6 is one embodiment of a multi-fiber ferrule 100 according to the present invention. The multi-fiber ferrule 100 has a main body 102 having a top portion 104 and a bottom portion 106. There is a first side portion 108 that extends between the top portion 104 and the bottom portion 106. There is also a second side portion 110 extending between the top portion 104 and the bottom portion 106 on opposites sides of the main body 102. The main body 102 also has an end face 112 at a front end 114 of the main body 102 and a rear face 116 at a rear end 118 of the main body 102. The multi-fiber ferrule 100 is significantly smaller than the conventional MT-ferrule and has typical dimensions of 1.25 mm height, 4 mm length (between the front end 114 and the rear end 118), and a width of 6.4 mm between the first side portion 108 and the second side portion 110.

[0060] Applicant notes that the term “front” or “forward” means that direction where the fiber optic ferrule would meet with another fiber optic ferrule or device, while the

term “rear” or “rearward” is used to mean the direction from which the optical fibers enter into the fiber-optic ferrule or fiber optic connector. In the present application, the multi-fiber ferrule and the fiber optic connector will therefore have a front and a rear, the front will be inserted into an adapter, sleeve or other receptacle. Thus, in FIG. 1, the “front” of the multi-fiber ferrule is on the left side of the figure and pointing out of the figure. The “rear” or “back” is that part of multi-fiber ferrule is on the right side of FIG. 1 and “rearward” and “backward” is toward the right and into the page. The same is true with the fiber optic connector as illustrated in FIG. 8—the front is to the left and out, while rear is to the right and back.

[0061] As seen in FIG. 3, the multi-fiber ferrule 100 has a rear central opening 120 extending into the main body 102 from the rear face 116 and configured to receive at least three optical fibers (not shown). The multi-fiber ferrule 100 also has a plurality of fiber support structures 122 to support the optical fibers. See also FIG. 5. The fiber support structures 122 are in communication with the rear central opening 120 and extending through the main body 102 to the end face 112. Along the length of the fiber support structures 122 there may be chamfered portions 124 that assist in insertion of the optical fibers into the multi-fiber ferrule 100 without the skiving of the front ends of the optical fibers. The fiber support structures 122 may be fiber openings or fiber bores, but may alternatively be groove structures, or the combination or both. The main body 102 may also include two guide pin holes 126, which extend between the end face 112 and the rear face 116. The guide pin holes 126 provide a reference point with respect to the main body 102 and other structures to which the multi-fiber ferrule 100 is mated. As noted below, the guide pin holes 126 are outside the area of cutouts to allow for enough material in the main body 102 to allow for the guide pin holes 126. The end face 112 may have a rectangular profile, although a trapezoidal profile (as shown) may also be provided as an alternative.

[0062] The top portion 104 has a top cut-out 130 that forms a first forward facing surface 132. The first forward facing surface 132 is used as a stop surface in conjunction with a housing for a connector, e.g., an SFP/QSFP connector. There may also be a number of other surfaces formed by the top cut-out 130. For example there is a second, slanted surface 134 on both sides of the top cut-out 130 that assist in the location of the multi-fiber ferrule 100 in the housing for a connector. The second, slanted surfaces 134 assist in moving the multi-fiber ferrule 100 in a side-to-side manner relative to the housing. There are also laterally facing surfaces 136 on each side that form the last part of the cut-out 130 and extend to the end face 112 from the second, slanted surfaces 134. As illustrated in the figures, the top cut-out 130 does not extend all of the way to the rear end 118, but stops short at the first forward facing surface 132. However, a portion of the top cut-out 130 could extend all the way to the back of the multi-fiber ferrule 100. For example, a cutout in the shape of a “T” with a thin narrow section going all the way to the back would work as well, as long as there is at least one forward facing surface adjacent to such a variation of the top cut-out 130. This applies to a bottom cut-out 150 as well, described below.

[0063] The top portion 104 has a first surface 140 that lies in a first plane A and the cut-out 130 forms a second surface 142 that lies in a second plane B. See FIG. 4. Planes A and B are preferably parallel to one another but off set, with

plane B being closer to a longitudinal axis E passing through the center of the main body 102 and through the rear central opening 120 between the front end 114 and the rear end 118. See also FIG. 5. It should also be noted that the cut-out portion 130 does not extend into the rear central opening 120 or the fiber support structures 122.

[0064] Similarly, the bottom portion 104 has the bottom cut-out 150 that forms a second forward facing surface 152. The second forward facing surface 152 is also used as a stop surface in conjunction with a housing for a connector. The bottom cut-out 150 also has two laterally facing surfaces 154 that form a portion thereof. The bottom cut-out 150 extends from the end face 112 towards the rear end 118, but does not reach the rear end 118. It may reach the same distance toward the rear end 118 from the end face 112 as does the top cut-out 130, but it may stop short of or beyond where the top cut-out 130 stops at forward facing surface 132.

[0065] The bottom portion 104 has a first surface 160 that lies in a third plane C and the bottom cut-out 150 forms a fourth surface 162 that lies in a fourth plane D. See FIGS. 4 and 5. The Planes C and D are preferably parallel to one another but off set, with plane D being closer to the longitudinal axis E passing through the center of the main body 102 and through the rear central opening 120 between the front end 114 and the rear end 118. It should also be noted that the bottom cut-out 150 does not extend into the rear central opening 120 or the fiber support structures 122.

[0066] It should be noted that the thickness of the main body 102 varies across a width and a depth. As seen in FIGS. 4 and 6, the thickness of the main body 102 is least where the two cut-outs 130, 150 are located. This is seen in FIG. 4 and represented by the distance between planes B and D. The thickness of the main body 102 is greatest where there are no cut-outs, which corresponds to the distance between the planes A and C.

[0067] Returning to the main body 102, there is first side portion 108 that extends between the top portion 104 and the bottom portion 106. There is also a second side portion 110 extending between the top portion 104 and the bottom portion 106 on opposites sides of the main body 102. The first side portion 108 and the second side portion 110 are smooth between the front end 114 and the rear end 118. Additionally, there is no shoulder with multi-fiber ferrule 100 making the profile from the back to the front the same as the front to the back—and also the same at the end face 112 and the rear face 116. That is, the multi-fiber ferrule 100 is shoulder-less. The term shoulder-less referring to a lack of any protrusions or other features on the first side portion 108 and the second side portion 110 that may be used to engage the multi-fiber ferrule 100 with a receptacle or an adapter. There are also no sharp edges along the length of the multi-fiber ferrule 100 at the junction of the side portions 108, 110 to the top and bottom portions 104, 106. See, e.g., FIGS. 1 and 2. It should also be noted that the top portion 104 may be wider than the bottom portion. That is, the distance across the top portion 104 may be greater than the distance across the bottom portion 106 between the side portions. That is, W1 may be greater than W2 as illustrated in FIG. 3. Alternatively, W1 equals W2.

[0068] It should also be noted that the rear surface 116 at the rear end 118 may also be used as a reference surface for any work that may be done to the multi-fiber ferrule 100. For example, the rear surface 116 may be used as a reference surface for polishing the end face 112 of the main body 102.

The use of the rear surface **116** is in addition to the first forward facing surface **132** and/or the second forward facing surface **152**. Preferably, the wider of the first forward facing surface **132** and the second forward facing surface **152** would be used as a reference datum surface for polishing and interferometry. The end face **112** may be angle-polished (i.e., at an angle relative to the rear face **116**). Alternatively, the end-face **112** may be flat polished. The top cut-out **130** may have a different width than the bottom cut-out **150**. This may act as a polarity indication and/or may cause the ferrule to be oriented in a specific direction when received inside a receptacle or an adapter for mating with another ferrule. Alternatively, the top cut-out **130** may have a same width as the bottom cut-out **150**.

[0069] An alternative embodiment of a multi-fiber ferrule **100'** is illustrated in FIG. 7. In this embodiment, the top portion **104'** has two top cut-outs **130'** that form two first forward facing surfaces **132'**. The two top cut-outs **130'** are separated by a continuation **104a'** of the top portion **104'**. The continuation **104a'** of the top portion **104'** acts as a key for the multi-fiber ferrule **100'**. This is in addition to the top cut-out **130'** having a different width than the bottom cut-out **150'**. Thus the continuation **104a'** may act as a polarity key or wedge. In an alternative aspect, the continuation **104a'** may be presented only partially separate the two top cutouts **130'**. Otherwise, the multi-fiber ferrule **100'** is the same as noted above with regard to multi-fiber ferrule **100**.

[0070] Moving to FIGS. 8-16, there is one embodiment of a fiber optic ferrule receiver **200** to receive a fiber optic ferrule **100** according to the present invention. The fiber optic ferrule receiver **200** can be used in a number of different connectors and assemblies. As illustrated in FIGS. 8 and 9, the fiber optic ferrule receiver **200** is a part of a fiber optic connector **400**. Additionally and as discussed in more detail below, the elements of the fiber optic ferrule receiver **200** may be found in other receivers as well. For example, the features of the fiber optic ferrule receiver **200** may be included in an adapter, into which the fiber optic ferrule **100** would be directly inserted.

[0071] Now turning to FIG. 10, the components of the fiber optic connector **400** will be described, moving in a front to rear direction (or left to right in the figure). The fiber optic ferrule receiver **200** is on the far left, with the multi-fiber ferrule **100** that will be inserted into the fiber optic ferrule receiver **200** next in line. While the multi-fiber ferrule **100** is illustrated, the invention may apply to other fiber optic ferrules as well. Behind the multi-fiber ferrule **100** is a guide pin keeper or spacer **402**. A spring **404** (or other elastic element) is disposed in front end of a housing **406** (and is described in more detail below) to bias the multi-fiber ferrule **100** in a forward direction with the fiber optic ferrule receiver **200**. A crimp ring **408** is used to secure the strength members associated with the optical fibers (not shown) to the housing **406**. Finally, a push-pull boot **410** is attached to the housing **406**.

[0072] The fiber optic ferrule receiver **200** includes a main body **202** extending between a front end **204** and a rear end **206**. See FIGS. 11 and 12. The main body **202** has four sides **208, 210, 212, 214**, and an opening **216** extending between the front end **204** and the rear end **206** and being defined at least by a portion of internal surfaces of the four sides **208, 210, 212, 214**. As illustrated, the first side **208** and the second side **210** are on opposite sides of the opening **216**, while the third side **212** and the fourth side **214** are each

connected to the first side **208** and the second side **210** and are opposite each other about the opening **216**. The third side **212** and the fourth side **214** have internal surfaces that are preferably flat and linear, but they may have tapering features like the internal surfaces of first side **208** and second side **210**, discussed in detail below. In one aspect of this disclosure, the third side **212** may include a polarity step or a polarity mark to indicate orientation of the fiber optic ferrule receiver **200** and hence, the fiber optic ferrule **100**. See also FIG. 13.

[0073] The first side **208** has a first tapered surface **208a** in the opening **216** as well as a second tapered surface **208b**, the first tapered surface **208a** reducing the opening **216** between the rear end **206** and a first position **220**, and the second tapered surface **208b** increasing the opening **216** between the first position **220** and the front end **204**. As illustrated in FIG. 12, the first tapered surface **208a** may have a number of ramped and flat portions. The first tapered surface **208a** is to prevent the front end **114** of the main body **102** of the multi-fiber ferrule **100** from encountering any surface that causes damage to the front end **114** or causes the multi-fiber ferrule **100** from catching as it is inserted into the opening **216**.

[0074] The second side **210** also has a third tapered surface **210a** in the opening **216** as well as a fourth tapered surface **210b**, the third tapered surface **210a** reducing the opening **216** between the rear end **206** and a second position **222**, and the fourth tapered surface **210b** increasing the opening **216** between the second position **222** and the front end **204**. As can be seen in FIG. 12, the first position **220** and the second position **222** are directly across the opening **216** from each other. However, depending on the configuration of the cut-outs in the multi-fiber ferrule, the first position **220** and the second position **222** may be off set from one another along a longitudinal axis F through the fiber optic ferrule receiver **200**. The first portion **220** and the second portion **222** can be thought of as a line that extends across the opening **416** between the third side **212** and the fourth side **214** and on the first side **208** and the second side **210**, respectively. Alternatively, the first position **220** and/or the second position **222** may be a flat surface, e.g., parallel to the first side **208** and the second side **210**. That is, there may be a flat surface formed at a junction of the first tapered surface **208a** and the second tapered surface **208b**. Likewise, there may be another flat surface formed at a junction of the third tapered surface **210a** and the fourth tapered surface **210b**.

[0075] The fiber optic ferrule receiver **200** has a first projection **230** extending into the opening **216** from the first side **208** to engage the multi-fiber ferrule **100** at the first position **220**. Preferably the first projection **230** engages the first forward facing surface **132** of the multi-fiber ferrule **100**. However, as noted above, the first projection **230** could engage any appropriate structure on the multi-fiber ferrule **100**. The projection **230** preferably has a rearward facing surface **232** to engage the first forward facing surface **132** of the multi-fiber ferrule **100**. Additionally, the first projection **230** extends across the opening **216** in the appropriate location and width for that engagement. The first projection **230** preferably has a ramp surface **234** that extends from the first position **220** towards the front end **204**. While the ramp surface **234** extends all of the way to the front end **204**, it could stop short thereof. Alternatively, the first projection

230 may have other configurations, such as a flat plateau like profile, instead of a ramp to engage the multi-fiber ferrule **100**.

[0076] Similarly, the ferrule receiver **200** has a second projection **240** extending into the opening **216** from the second side **210** to engage the multi-fiber ferrule **100** at the second position **222**. Preferably the second projection **240** engages the second forward facing surface **152** of the multi-fiber ferrule **100**. However, as noted above, the second projection **240** could engage any appropriate structure on the multi-fiber ferrule **100**. The second projection **240** preferably has a rearward facing surface **242** to engage the second forward facing surface **152** of the multi-fiber ferrule **100**. Additionally, the second projection **240** extends across the opening **216** in the appropriate location and width for that engagement with the fiber optic ferrule receiver **200**. As is clear in FIG. 13 (showing the view from the front of the ferrule receiver **200**), the first projection **230** is not as wide as the second projection **240** so that the multi-fiber ferrule **100** can only be inserted into the fiber optic ferrule receiver **200** in one way. The second projection **240** also preferably has a ramp surface **244** that extends from the second position **222** towards the front end **204**. While the ramp surface **244** extends all of the way to the front end **204**, it could stop short thereof. Alternatively, similar to the first projection **230**, the second projection **240** may have other configurations, such as a flat plateau like profile, instead of a ramp to engage the multi-fiber ferrule **100**.

[0077] The configuration of the first projection **230** and the second projection **240**, particularly with the ramp surfaces **234,244** cause the second and fourth tapered surfaces **208b, 210b** to be split into two sections—one on each side of the projections **230, 240**. See FIG. 13. At those locations, the first tapered surface **208a** and the second tapered surface **208b**, as well as the third tapered surface **210a** and the fourth tapered surface **210b**, are connected to one another about the first position **220** and second position **222**, respectively. Such a connection, as noted above, may be along a line or along a flat plane.

[0078] The rear end **206** of the main body **202** is not orthogonal to the longitudinal axis **F** extending through the main body **202**. See, e.g., FIG. 11. Rather, it has an angle that matches the angle at the front of the housing **406**. One will be able to discern from this angled surface, where the first projection **230** and the second projection **240** are within the main body **202**. This will allow for the multi-fiber ferrule **100** to be inserted so that the first projection **230** and the second projection **240** engage correct ones of the forward facing surfaces **132, 152** in the multi-fiber ferrule **100**. See, e.g., FIGS. 12 and 15.

[0079] Extending from the rear end **206**, and away from the main body **202**, are two tabs **250**, one is mounted on side **208** and the other on side **210**. The two tabs **250** each have a shape of the letter “T”. The tabs **250** have cut-outs **252** which form legs **254**. The tabs **250** and the legs **254** are able to flex outward from the opening **216** and engage the housing **406** as described below. See also FIGS. 15 and 16. The tabs **250** have a rear surface **256** that is perpendicular to the longitudinal axis **F**. The cut-outs **252** between the tab **205** and the legs **254** are not rectangular, but are trapezoidal, allowing the rear end **206** to be angled, while still having the rear surface **256** and the front end **204** perpendicular to the longitudinal axis **F**.

[0080] The main body **202** of the fiber optic ferrule receiver **200** has a plurality of shoulders **260** that extending from the front end **204** to the rear end **206**. The shoulders are generally at the corners of the main body **202**, where the sides **208,210, 212,214** meet. These shoulders **260** act as a guide to align the fiber optic connector **400** with another receptacle, such as an adapter.

[0081] The housing **406** will now be described with reference to FIGS. 18-28. The housing **406** has a main body **420** that extends between a front end **422** and a rear end **424** and generally has three sections. The housing **406** also has an opening **426** that extends between the front end **422** and the rear end **424**. The first section **428** is a front section that receives an elastic member such as spring **404**. As noted above, the elastic member or spring **404** is to engage, directly or indirectly, the rear end of the multi-fiber ferrule **100** and bias it in a forward direction. The spring **404** engages forward facing surfaces **430** that extend into the opening **426** from the interior surface **432** and function as an integral spring stop. Referring to FIG. 20, in the cross-section, two of the forward facing surfaces **430** are illustrated, each continuing around one side of the housing **406** internally (see also FIG. 21) on the other half of the main body **420** that is not visible. Alternatively, there could preferably be four of the forward facing surfaces **430**, two for the half shown in FIG. 20, and two more for the half of the housing **406** that has been cut in the cross-section of FIG. 20. See also FIGS. 25 and 26. The front end **422** has a chamfered surface **434** that assists in inserting the spring **404** during the initial insertion as well as movement of the spring **404** during use of the housing **406** in the fiber optic connector **400**. The opening **426** is illustrated as being oval in cross section, but it could have other configurations as needed (e.g., an elliptical configuration). The spring **404** is accordingly shaped to be received inside the opening **426**, and engage and seat at the forward facing surfaces **430**.

[0082] Also at the front end **422** and on first side **440** and on opposing second side **442** are depressions **444** to receive the tab **250** and legs **254** from the fiber optic ferrule receiver **200** to removably secure the fiber optic ferrule receiver **200** to the main body **420**. See, FIG. 19 and FIG. 21 showing a front view of the housing **406**.

[0083] The main body **420** of the housing **406** has a plurality of shoulders **460** that extending from the front end **422** to the rear end **424**. The shoulders are generally at the corners of the main body **420**, where first side **440** meets with top side **462** and bottom side **464** and second side **442** meets with top side **462** and bottom side **464**. These shoulders **460** act as a guide to align the fiber optic connector **400** with another receptacle, such as an adapter. The shoulders **460** also match with the shoulders **260** on the fiber optic ferrule receiver **200** to form a continuous shoulder at each corner.

[0084] The second or middle section **470** provides an area for the optical fibers **300** to transition from a flat ribbon to a grouping that can be protected by a round fiber optic cable covering. Referring to FIG. 26, the optical fibers **300** extend from the multi-fiber ferrule **100** in a flat configuration, the middle section **470** allows for them to be grouped together to pass out the rear end **424** in circular configuration and in a cable sheath **302**. As is known in the art, the optical fibers **300** cannot be bent beyond their bend radius without damaging the optical fibers **300**. This transition area **470** assists in preventing such damage. The transition area **470** is

dimensioned to maintain a safe bend radius for the individual optical fibers 300 as these optical fibers 300 transition from a ribbon form to a fiber optic cable form with loose fibers therein.

[0085] The third or rear section 480 is used to finalize the configuration of the optical fibers 300 from the transition area in the middle section 470 to the cable format. The rear section 480 has an outer surface 482 to engage the crimp ring 408. The outer surface 482 is on a circular extension or crimp body 486 that extends from the rear end 424. Additionally, the crimp body 486 is preferably made from two portions, a first portion 490 that is integral with the main body 420 and a second portion 492 that is removable from the main body 420 and the first portion 490. See FIGS. 19-20 and 23-24. The second portion 492 has a rear section 494 that is a half cylinder and a forward section 496 that mates with the main body 420 to close the middle section 470. The rear portion 494 mates with the first portion 490 to form the cylindrical shape that can accept the crimp ring 408. The rear section 494 mates with the first portion 490 with a series of projections 500 and recesses 502. As illustrated in the figures, the projections 500 are on the first portion 490 and the recesses 502 are on the second portion 492. However, the projections and recesses could be reversed or mixed with regard to their positions on the first portion 490 and the second portion 492. The projections 500 preferably frictionally engage the recesses 502 and then once the crimp ring 408 is secured around the crimp body 486, the two portions 490, 492 will not move relative to one another.

[0086] The forward section 496 of the second portion 492 mates with the main body 420 of the housing 406. The main body 420 has an extra portion 504 that has been cut out to allow for more optical fibers and larger groups of optical fibers to pass through the opening 426. This makes the opening 426 at the forward section 496 larger than on the opposing side. The larger opening 426 allows the housing 406 to be installed onto the cable and slid down the cable and out of the way during termination and polishing of the ferrule 100. That is when viewed straight into the opening 426 from the rear section 494, or even from the front end 422, the opening 426 is asymmetrical due to the presence of the first portion 490 and the extra portion 504. See FIGS. 22, 23. The forward section 496 of the crimp body 486 has a tab 506 that extends into the extra portion 504 to close it off when the two portions 490, 492 are mated.

[0087] The housing 406 also has a number of latches 520 that extend from the main body 420 to engage a push-pull boot 410 and more specifically two latches 522 on the push-pull boot. See FIGS. 9, 10, 24, and 27. As illustrated, the latches 522 on the push-pull boot can slide in the area 524 between two latches 520 on each side of the housing 406. See FIG. 27. When the push-pull boot 410 is pulled, the latches 522 slide within the area 524 until they reach the end of the latches 520 and at this point, the force is transferred to the latches 520 and the housing 406 to remove the fiber optic connector from its receiver. To insert the fiber optic connector 400, the push-pull boot 410 is pushed until the latches 522 engage the front end of the area 524, which then transfers to the housing 406 and moves the fiber optic connector in a forward direction to secure it within a receptacle.

[0088] It is also possible, as an alternative to this configuration, whereby at least one of the latches is molded on the second portion. Referring to FIG. 39, there is a housing 406a

that has a second portion 492a of a crimp body 486a and a latch 520a molded thereon. The housing 406a has the same components as the housing discussed above, as well as the extra portion 504' that has been cut out to allow for more optical fibers and larger groups of optical fibers to be used with this housing 406a.

[0089] Another embodiment of a housing 406' and a fiber optic ferrule receiver 200' according to the present invention are illustrated in FIGS. 29-34. First, it should be noted that the fiber optic ferrule that is used in these figures corresponds to multi-fiber ferrule 100 discussed above, but another fiber optic ferrule could also be used.

[0090] This embodiment of a fiber optic ferrule receiver 200' includes a main body 202' extending between a front end 204' and a rear end 206'. As in the prior embodiment, the main body 202' also has four sides 208', 210', 212', 214', and an opening 216' extending between the front end 204' and the rear end 206' and being defined at least by a portion of internal surfaces of the four sides 208', 210', 212', 214'. The fiber optic ferrule receiver 200' also includes two tabs 250' that extend rearwardly from the rear end 206'. The two tabs 250' each have a projection 252' that extend outwardly and away from each other. The projections 252' are designed to engage an opening 444' on each side of the housing 406', as described in more detail below. The two tabs 250' are somewhat flexible in that they can flex inward to be inserted into the housing 406' and subsequently return, at least partially, to their pre-flexed configuration. This allows the fiber optic ferrule receiver 200' to be retained in the housing 406'.

[0091] Turning to FIG. 33A, the length of fiber optic ferrule receiver 200' (the distance between the front end 204' and the rear end 206') is shorter than that of fiber optic ferrule receiver 200. The housing 406' is therefore longer so that the combination of the housing 406' and the fiber optic ferrule receiver 200' are preferably the same overall length. It is also clear from FIG. 33A that the rear end 206' of the a fiber optic ferrule receiver 200' and the front end of the housing 406' are slanted as in the previous embodiment for the purposes of polarity.

[0092] The opening 216' of the fiber optic ferrule receiver 200' has the same general configuration of a fiber optic ferrule receiver 200. That is, first side 208' and second side 210' are on opposite sides of the opening 216', while third side 212' and fourth side 214' are each connected to the first side 208' and the second side 210' and are opposite each other about the opening 216'. Third side 212' and fourth side 214' have internal surfaces that are preferably flat and linear, but they may have tapering features discussed above.

[0093] First side 208' has a first tapered surface 208a' in the opening 216' as well as a second tapered surface 208b', the first tapered surface 208a' reducing the opening 216' between the rear end 206' and a first position 220', and the second tapered surface 208b' increasing the opening 216' between the first position 220' and the front end 204'. See FIG. 34. The first tapered surface 208a' may have a number of ramped and flat portions. The first tapered surface 208a' is to prevent the front end 114 of the main body 102 of the multi-fiber ferrule 100 from encountering any surface that causes damage to the front end 114 or causes the multi-fiber ferrule 100 from catching as it is inserted into the opening 216'.

[0094] Second side 210' also has a third tapered surface 210a' in the opening 216' as well as a fourth tapered surface

210b', the third tapered surface 210a' reducing the opening 216' between the rear end 206' and a second position 222', and the fourth tapered surface 210b' increasing the opening 216' between the second position 222' and the front end 204'. As can be seen in FIG. 34, the first position 220' and the second position 222' are directly across the opening 216' from each other. However, depending on the configuration of the cut-outs in the multi-fiber ferrule 100, the first position 220' and the second position 222' may be off set from one another. The first portion 220' and the second portion 222' can be thought of as a line (that may have a number of thicknesses) that extends across the opening 416' between the third side 212' and the fourth side 214' and on the first side 208' and the second side 210', respectively. However, as described with respect to the embodiments above, the first portion 220' and the second portion 222' can also be a plane rather than a line.

[0095] As with the prior embodiment, the fiber optic ferrule receiver 200' has a first projection 230' extending into the opening 216' from the first side 208' to engage the multi-fiber ferrule 100 at the first position 220'. Preferably the first projection 230' engages the first forward facing surface 132 of the multi-fiber ferrule 100. The ferrule receiver 200' has a second projection 240' extending into the opening 216' from the second side 210' to engage the multi-fiber ferrule 100' at the second position 222'. Preferably the second projection 240' engages the second forward facing surface 152 of the multi-fiber ferrule 100.

[0096] Turning to FIGS. 28-31, the other embodiment of the housing 406' will be explained. The housing 406' has a main body 420' that extends between a front end 422' and a rear end 426' and generally has three sections. The first section 428' is a front section that receives an elastic member such as spring 404. The second or middle section 470' provides an area for the optical fibers 300 to transition from a flat ribbon to a grouping that can be protected by a round fiber optic cable covering. The third or rear section 480' is used to finalize the configuration of the optical fibers from the transition area in the middle section 470' to the cable format. Except for the first section 428', the other sections are the same as discussed above and will not be repeated here.

[0097] The housing 406' also has an opening 426' that extends between the front end 422' and the rear end 424'. The first section 428' receives an elastic member such as spring 404. As noted above, the elastic member or spring 404 is to engage, directly or indirectly, the rear end of the multi-fiber ferrule 100 and bias it in a forward direction. The spring 404 engages forward facing surfaces 430' that extend into the opening 426' from the interior surface 432' and function as an integral spring stop. Referring to FIG. 31, two of the forward facing surfaces 430' are illustrated. The front end 422' has a chamfered surface 434' that assists in inserting the spring 404 during the initial insertion as well as movement of the spring 404 during use of the housing 406' in a fiber optic connector 400. The opening 426' is illustrated as being oval in cross section, but it could have other configurations as needed.

[0098] The main body 420' of the housing 406' has a plurality of shoulders 460' that extending from the front end 422' to the rear end 424'. The shoulders are generally at the corners of the main body 420', where first side 440' meets with top side 462' and bottom side 464' and second side 442' meets with top side 462' and bottom side 464'. These

shoulders 460' act as a guide to align the fiber optic connector 400 with another receptacle, such as an adapter. The shoulders 460' also match with the shoulders on the both of the embodiments of fiber optic ferrule receiver to form a continuous shoulder at each corner.

[0099] At the front end 422' of the main body 420' and on both first side 440' and second side 442' is a depression 448' that also has the opening 444' to receive the projections 252' from the tabs 250' when the fiber optic ferrule receiver 200' is inserted into the opening 426'. There are also two pockets 436' that are closest to the top side 462' and bottom side 464' to receive a part of the ferrule and/or the guide pin keeper or spacer 402. See FIGS. 30 and 32.

[0100] Illustrated in FIGS. 35-38 is an embodiment of a combination of a housing and a fiber optic ferrule receiver according to the present invention. The housing 600 has a front section 602 that incorporates the features of the fiber optic ferrule receiver 200,200' above. The housing 600 has a front end 604 and a rear end 606 with an opening 608 extending therebetween. The housing 600 has a rear section 610 that receives the spring 404 from the rear end 606. As with other housings, the spring 404 engages the back of the multi-fiber ferrule 100, either directly or indirectly to bias it to the front of the housing 600.

[0101] The front section 602 has a first side 612 that has a first tapered surface 612a in the opening 608 as well as a second tapered surface 612b. See FIG. 37. As with the prior embodiments, the first tapered surface 612a reduces the opening 608 between the rear end 606 and a first position 614, and the second tapered surface 612b increasing the opening 608 between the first position 614 and the front end 604.

[0102] The front section 602 has a second side 616 that has a third tapered surface 616a in the opening 608 as well as a fourth tapered surface 616b. As with the prior embodiments, the third tapered surface 616a reduces the opening 608 between the rear end 606 and a second position 618, and the fourth tapered surface 616b increasing the opening 608 between the second position 618, and the front end 604.

[0103] The front section 602 also includes a first projection 620 that extends into the opening 608 from the first side 612 to engage the multi-fiber ferrule 100 at the first position 614. It also includes a second projection 622 that extends into the opening 608 from the second side 616 to engage the multi-fiber ferrule 100 at the second position 618. Thus, the elements of the fiber optic ferrule receiver have been incorporated into the housing and could, by extension, be added to other structures as well.

[0104] It will be apparent to those skilled in the art that various modifications and variations can be made to the present invention without departing from the spirit and scope of the invention. Thus it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

We claim:

1. A fiber optic ferrule receiver to receive a fiber optic ferrule therein, the fiber optic ferrule receiver comprising:
 - a main body extending between a front end and a rear end and having four sides, the main body having an opening extending between the front end and the rear end and being defined at least by a portion of internal surfaces of the four sides;

- a plurality of tapered surfaces of the internal surfaces of the main body and within the opening, the plurality of tapered surfaces configured such that the opening is wider at the rear end and reduces moving internally from the rear end into the opening;
 - a first projection extending into the opening from adjacent one of the plurality of tapered surfaces, the first projection configured to engage a first forward facing surface of the fiber optic ferrule, wherein the first projection has a first length; and
 - a second projection extending into the opening from adjacent another one of the plurality of tapered surfaces, the second projection configured to engage a second forward facing surface of the fiber optic ferrule, wherein the second projection has a second length different from the first length, each of the first length and the second length being in a direction perpendicular to a longitudinal axis from the front end to the rear end,
- wherein the first projection and the second projection are separated from each other by a portion of the opening.
2. The fiber optic ferrule receiver according to claim 1, wherein the first projection and the second projection provide a keying function for a correct orientation of an engagement the fiber optic ferrule with the main body.
 3. The fiber optic ferrule receiver according to claim 1, wherein the plurality of tapered surfaces include tapered surfaces from the front end to the first projection and the second projection, wherein the opening is wider at the front end and reduces moving internally from the front end into the opening and is narrowest at the first projection and the second projection.
 4. The fiber optic ferrule receiver according to claim 1, wherein the main body has a plurality of shoulders extending rearwardly from the front end to align the fiber optic ferrule receiver with an adapter.
 5. The fiber optic ferrule receiver according to claim 1, wherein the plurality of tapered surfaces do not contact a front end of the fiber optic ferrule.
 6. A fiber optic ferrule receiver to receive a fiber optic ferrule therein, the fiber optic ferrule receiver comprising:
 - a main body extending between a front end and a rear end and having four sides, the main body having an opening extending between the front end and the rear end and being defined at least by a portion of internal surfaces of the four sides;
 - at least two tapered surfaces inside the main body and within the opening, the at least two tapered surfaces configured such that the opening is wider at the rear end and reduces moving internally from the rear end into the opening;
 - a first projection extending into the opening from adjacent one of the at least two tapered surfaces, the first projection configured to engage a first forward facing surface of the fiber optic ferrule, wherein the first projection has a first length; and
 - a second projection extending into the opening from adjacent another one of the at least two tapered surfaces, the second projection configured to engage a second forward facing surface of the fiber optic ferrule, wherein the second projection has a second length, each of the first length and the second length being in

- a direction perpendicular to a longitudinal axis, the longitudinal axis is in a direction from the front end to the rear end,
 - wherein the first projection and the second projection are separated from each other on opposite sides of the opening.
7. The fiber optic ferrule receiver of claim 6, wherein the at least two tapered surfaces includes a first tapered surface rearward of the first projection.
 8. The fiber optic ferrule receiver of claim 7, wherein the at least two tapered surfaces includes a second tapered surface forward of the first projection.
 9. The fiber optic ferrule receiver of claim 8, first tapered surface and the second tapered surface never contact a front end of the fiber optic ferrule.
 10. The fiber optic ferrule receiver of claim 6, wherein the at least two tapered surfaces includes a first tapered surface rearward of the first projection, a second tapered surface forward of the first projection, a third tapered surface rearward of the second projection and a fourth tapered surface forward of the second projection.
 11. The fiber optic ferrule receiver of claim 10, wherein none of the first tapered surface, the second tapered surface, the third tapered surface and the fourth tapered surface contact a front end of the fiber optic ferrule.
 12. The fiber optic ferrule receiver of claim 6, wherein the first length is different from the second length.
 13. The fiber optic ferrule receiver of claim 6, wherein the main body is part of a housing of a fiber optic connector.
 14. The fiber optic ferrule receiver of claim 13, wherein the main body has a plurality of shoulders extending rearwardly from the front end to align the main body with an adapter.
 15. The fiber optic ferrule receiver of claim 6, wherein the main body has a plurality of shoulders extending rearwardly from the front end to align the fiber optic ferrule receiver with an adapter.
 16. The fiber optic ferrule receiver of claim 15, wherein each of the plurality of shoulders is disposed at a respective junction of two of the four sides.
 17. A fiber optic ferrule receiver to receive a fiber optic ferrule therein, the fiber optic ferrule receiver comprising:
 - a main body extending between a front end and a rear end and having four sides, the main body having an opening extending between the front end and the rear end and being defined at least by a portion of internal surfaces of the four sides;
 - a plurality of tapered surfaces of the internal surfaces of the main body and within the opening, the plurality of tapered surfaces configured such that the opening is wider at the rear end and reduces moving internally from the rear end into the opening;
 - a first projection extending into the opening from adjacent one of the plurality of tapered surfaces, the first projection configured to engage a first forward facing surface of the fiber optic ferrule, wherein the first projection has a first length; and
 - a second projection extending into the opening from adjacent another one of the plurality of tapered surfaces, the second projection configured to engage a second forward facing surface of the fiber optic ferrule, wherein the second projection has a second length different from the first length, each of the first length

and the second length being in a direction perpendicular to a longitudinal axis from the front end to the rear end,

wherein the opening is narrowest at each of the first projection and the second projection to seat a shoulder-less miniature MT-ferrule.

18. The fiber optic ferrule receiver of claim 17, wherein the first projection and the second projection are separated from each other on opposite sides of the opening inside the main body.

19. The fiber optic ferrule receiver of claim 17, wherein the first projection and the second projection provide a keying function for a single correct orientation of an engagement the fiber optic ferrule with the main body.

20. The fiber optic ferrule receiver of claim 17, wherein the plurality of tapered surfaces do not contact a front end of the shoulder-less miniature MT-ferrule.

* * * * *