

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250256659

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Mora; Fernando et al.

---

### Fixed Angle Car Mount for a Mobile Device

---

#### Abstract

A mount for a mobile device on a fixed feature of an automobile. A platform has a device side attachment surface. The housing also has an attachment extension to couple to the fixed feature such that the device side attachment surface has a permanently fixed orientation relative to the attachment extension. A wireless charger may be coupled to the platform and a first arrangement of magnetic material. The magnetic material exposes a pattern of magnetic fields at the device side attachment surface. The attachment extension maintains the surface at a fixed angle relative to the feature to which it is attached.

---

**Inventors:** Mora; Fernando (Reseda, CA), Baca; Alejandro (Sherman Oaks, CA), Islam; Mydul R. (Los Angeles, CA), Vuong; Kevin H. (Baldwin Park, CA)

**Applicant:** 1Lss, Inc. (Los Angeles, CA)

**Family ID:** 1000008224654

**Assignee:** 1Lss, Inc. (Los Angeles, CA)

**Appl. No.:** 18/937397

**Filed:** November 05, 2024

#### Related U.S. Application Data

parent US continuation 18441992 20240214 parent-grant-document US 12157421 child US 18937397

---

#### Publication Classification

**Int. Cl.:** B60R11/00 (20060101); B60R11/02 (20060101); B60R16/03 (20060101); G06F1/16 (20060101); H02J7/00 (20060101); H02J50/10 (20160101)

## U.S. Cl.:

CPC **B60R11/00** (20130101); **B60R16/03** (20130101); **H02J7/0044** (20130101); **H02J50/10** (20160201); B60R2011/0003 (20130101); B60R2011/0005 (20130101); B60R2011/0077 (20130101); B60R11/0241 (20130101); G06F1/1607 (20130101)

---

## Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 18/441,992 filed Feb. 14, 2024 entitled Fixed Angle Car Mount for a Mobile Device which is a continuation of U.S. application Ser. No. 17/545,362 filed Dec. 8, 2021 entitled Fixed Angle Car Mount for a Mobile Device now U.S. Pat. No. 11,945,371.

### BACKGROUND

#### Technological Field

[0002] Embodiments of the invention relate to a mount for a mobile device. More specifically embodiments of the invention relate to a car mount to maintain a mobile device in a fixed orientation.

#### Background

[0003] Numerous car mounts for a mobile device exist. Various commercial products clamp to surfaces, adhere to surfaces or for example engage vent systems. Some mounts include wireless charging capacity. Generally, such systems have an articulating joint that allows the orientation of the face of the mobile phone to be user adjusted.

[0004] Increasingly, cars include a display screen that is not integrated into the dashboard but has a fixed relation with the steering wheel. For example, the Tesla® Model 3 includes a discrete touch screen through which many functions of the car are controlled. Various models of articulating car mounts are designed to clamp to that screen. The phone screen is then repositioned using the articulating joint to face in a desired direction.

[0005] Recently, Apple Inc. of Cupertino California promulgated a “MagSafe®” specification for magnetic coupling to its iPhones®. Many state of the art smart phones enable wireless charging. Typically, the smart phone includes a receive Qi coil and supporting electronics. When the phone is placed in proximity to a Qi charger, the Qi transmit coil in the Qi charger induces a current in the receive coil that in turn charges the phone. To induce sufficient current to charge the phone, the distance between the transmit and receive coils should be as small as possible. Apple sells a Qi charger compatible with its MagSafe® specification that couples to MagSafe® compliant mobile devices. To charge the phones, the Qi charger couples magnetically directly to the MagSafe® interface on the phone or its compatible MagSafe® case. Various vendors offer MagSafe® compliant car mount chargers.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0006] Embodiments of the invention are illustrated by way of example and not by way of limitation in the figures of the accompanying drawings in which like references indicate similar elements. It should be noted that different references to “an” or “one” embodiment in this disclosure are not necessarily to the same embodiment, and such references mean at least one.

[0007] FIG. 1 is an exploded view of a car mount according to the embodiment of the invention.

[0008] FIG. 2 is a plan view of a back portion of a housing of the car mount of FIG. 1.

[0009] FIG. 3 is a plan view of the car mount of FIG. 1 with a front portion of the housing

removed.

[0010] FIGS. **4A-4C** are front, top, and rear views of the car mount of FIG. **1** installed on a display screen.

[0011] FIG. **5** is a schematic view of an interior of a vehicle with the car mount installed.

[0012] FIG. **6** is a block diagram of an internal mount charging system according to one embodiment of the invention.

#### DETAILED DESCRIPTION

[0013] Embodiments of the invention provide a fixed angle car mount that provides wireless charging capability. Some embodiments have no moving parts to reduce the risk of distracted driving while ensuring the front facing camera of the device with a view of the user's face. Many newer phones require face recognition to unlock. By fixing the view of the front facing camera, hands free unlock is enabled. Moreover, as increased automation pervades the automobile market other functionality such as video conferencing is enabled with the same orientation.

[0014] FIG. **1** is an exploded view of a car mount according to the embodiment of the invention. Car mount **100** once assembled has no moving parts. That is, the car mount **100** once installed will have a single defined fixed angle at which it maintains a mobile device couple thereto.

[0015] Car mount **100** has a housing, that in the shown embodiment is formed as three constituent pieces: a back portion **102**, a chassis **104** and a front cover **106**. In some embodiments, the housing can be formed of more or fewer pieces. In one embodiment, front cover **106** is elastomeric. For example, front cover **106** may be formed of silicone rubber. Elastomeric materials tend to have favorable frictional characteristics with the materials of mobile devices and the cases therefor. The relatively high coefficient of friction adds additional retaining force to the magnetic coupling discussed below.

[0016] In one embodiment, chassis **104** is injection molded out of a synthetic resin. It is desirable to select a resin that once cured will remain stable when local temperatures exceed 70° C. Polycarbonate has been found suitable. Alternatively, chassis **104** could be milled or cast from a metal such as aluminum or the like. In one embodiment, chassis **104** defines one or more arcuately arranged recesses **134-1**, **134-2** (generically recesses **134**) dimensioned to receive a first arrangement of magnetic material **152**, **154**, **156**, **158**. The first arrangement is described in greater detail below. Recesses **134** are distributed about the circumference of a circular space in the chassis **104** dimensioned to receive a Qi transmit coil **108**. Transmit coil **108** resided within the circular space and is supported by one or more shelves **132** that form a partial floor of the circular space. In some embodiments, the shelves form less than 70% of the floor of the circular space.

[0017] In one embodiment, the first arrangement of magnetic material is such that an inner arc **152**, **158** exposes a first polarity magnetic field and an outer arc of magnetic material **154**, **156** exposes an opposite polarity magnetic field. For example, inner arc **152**, **158** may expose a south polarity field and outer arc **154**, **156** may expose a north polarity field, or vice versa. This arrangement ensures axial alignment between an attached device having a complementary magnetic arrangement. In some embodiments, inner arc **152**, **158** and outer arc **154**, **156** are arranged to be Magsafe® compliant.

[0018] In an alternative embodiment, inner arc **158** may expose the same polarity as outer arc **154** and outer arc **156** may expose the same polarity as inner arc **152**. This arrangement would force a single orientation of the attached device. While the first arrangement is shown as only partially surrounding the coil **108**, embodiments in which the arrangement surrounds the entire circumference are deemed within the scope of the invention. Furthermore, embodiments in which recesses **134** are uniformly distributed around the circular space are also contemplated.

[0019] Chassis **104** may also have molded therein a linear recess **136** dimensioned to receive a second arrangement of magnets **162-1**, **162-2**, **162-3** (generically magnets **163**). In some embodiments more or fewer than three magnets **163** may be used. For example, some embodiments may use two magnets or five magnets **163**. Adjacent regions of the arrangement expose different

polarities. For example, magnets **162-1** and **162-3** may expose a south polarity and magnet **162-2** may expose a north polarity, or vice versa. Preferably rare earth magnets are used for both the first and second arrangements of magnetic material. In some embodiments, the first and second arrangements of magnetic materials collectively force a particular orientation of an attached mobile device.

[0020] The recesses **134**, **136** and the shelves **132** are molded such that when magnets **162**, **152**, **154**, **156** and **158** as well as coil **108** reside within the chassis they are substantially flush with an upper surface of the chassis. This provides a substantially flat surface to which front cover **106** can be attached. In some embodiments, front cover **106** is attached to the chassis with a heat stable adhesive such as 9495MP commercially available from 3M Company. In other embodiments it may snap fit or pressure fit over the chassis. Front cover **106** is selected to be of a thickness that ensures sufficient magnetic field to retain the mobile device in the context of forces expected to be encountered during normal driving and also thin enough to enable effective wireless charging. Thickness in the range of 0.5 mm to 0.8 mm have been found satisfactory.

[0021] Chassis **104** may also be molded to define a plurality of countersunk screw ports to facilitate the coupling of the chassis **104** to back portion **102**. Alternatively, screw holes may be omitted and the chassis can be coupled to the back portion with an appropriate adhesive.

[0022] Back portion **102** is preferably milled or cast from a conductive metal such as aluminum. In one embodiment, back portion **102** has a gross geometry with a roughly triangular cross section which provides the fixed angle of the car mount **100** as described in greater detail below. Back portion **102** may include screw holes **126** to align with the screw holes **138** of the chassis **104**. Back portion **102** provides a platform **124** on which to mount a printed circuit board (PCB) **106**. PCB **106** may have mounted thereon a Qi transmit controller **142** and a power controller **144**. These may be instantiated as one or more microcontrollers, one or more ASICs or the like. A power cable **112** electrically couples to the PCB **106** with a vehicle power source. In some embodiments, power cable **112** may terminate in a USB connector **114** or the like. In some embodiments, power controller **144** provides current and/or voltage modulation to allow the charger to source power from different power sources within the vehicle. For example, some embodiments can operate on either five volts from a USB-C connection or 12 volts from a typical automobile auxiliary connection.

[0023] Back portion **102** acts as a heat sink for the PCB **106**. Additionally, back portion **102** has assembly posts **122** that have the dual purpose of facilitating alignment of the chassis **104** on the back portion **102** and providing additional floor coverage for the circular space. When assembled the assembly posts **122** reside in conductive contact with the Qi coil **108** and act as a heat sink for the coil **108**. In some embodiments, the contact between the assembly posts **122** represents greater than 30% of the surface area of a contacting side of the coil **108**.

[0024] Back portion also includes an attachment extension **120**. Attachment extension **120** has a display screen coupling surface with an arcuate contour to match an attachment edge of an intended display. In some embodiments, the coupling surface is shaped to conform to at least part of a corner of a specific display, such as for the Tesla® model **3**. The corner conformance improves stability of the mount **100** when attached. An adhesive insert **110** is applied to the attachment extension **120**. Adhesive insert **110** aggressively adheres and conforms to the coupling surface such that substantially the entire coupling surface is capable of adhesion to the display.

[0025] FIG. **2** is a plan view of a back portion of a housing of the car mount of FIG. **1**. In addition to the PCB platform **124** and the attachment posts **122**, back portion defines a cord channel **202**. Cord channel **202** runs from the PCB (not shown in this view) to immediately adjacent to the attachment extension **120**. By laterally shifting the cord, to exit the housing at the attachment extension, the power cable will largely reside behind the display screen and provide a neater look to the installed device.

[0026] FIG. **3** is a plan view of the car mount of FIG. **1** with a front portion of the housing

removed. Chassis **104** is coupled to the back portion (not shown) but assembly screws **302**. Magnet material, **162**, **154**, **152** are seated in their respective recesses as described with reference to FIG. **1**. Transmit Qi coil **108** similarly resides in the circular space in contact with the assembly posts of the back portion. Adhesive insert **110** exposes an aggressive adhesive over substantially its entire surface.

[0027] FIGS. **4A-4C** are front, top, and rear views of the car mount of FIG. **1** installed on a display screen. In FIG. **4A** the mount **100** is coupled to display **400**. The active screen **402** is not occluded by the mount. Additionally, the cable **112** runs behind the screen **400**. In FIG. **4B** the coupling surface can be seen extending around the side edge **404** and on to the back **408** of the display **400**. By wrapping the edge **408** and extending onto the back sufficient adhesive contact is achieved to securely retain a mobile device. In FIG. **4C** attachment extension **120** can be seen wrapping over a portion of upper edge **408** of display **400**. This provides some vertical support and reduces the stress on the adhesive coupling between the mount **100** and display **400**. Once coupled the display **400** the front surface of mount **100** defines a fixed acute angle  $\theta$  relative to the plane in which the screen **402** resides. Angle  $\theta$  is preferably in the range of 2.7-12.7 degrees. In one embodiment,  $\theta$  is approximately 7.7 degrees. By having a fixed angle, the field of view of an attached device is always the same. By appropriately selecting the angle  $\alpha$  view of the driver is assured, and there is never a need for the driver to be distracted by adjusting the positioning of the mobile device.

[0028] FIG. **5** is a schematic view of an interior of a vehicle with the car mount installed. Display **400** is shown with car mount **100** coupled thereto. A mobile device **502** such as a smart phone magnetically couples to one or more of the magnetic arrangements within car mount **100**. As a result of the fixed angle  $\theta$ , the front side camera of mobile device **502** has a field of view **504** that is guaranteed to include the driver's face **506**. As used herein "front side" camera is the camera whose field of view is on the same side as a display screen of the mobile device **502**. The fixed position of the mount **100** and the magnetic coupling ensures that the attached mobile device **502** will not occlude the active display screen of display **400** and that the view **504** will not be occluded by the steering wheel **508**. By ensuring the driver's face **506** will be in the field of view **502**, hands free unlocking of the phone is enabled. Additionally, as improvements in autonomous driving accelerate other functionality such as video conferencing is enabled.

[0029] FIG. **6** is a block diagram of an internal mount charging system according to one embodiment of the invention. A Qi transmit coil **606** is coupled to a Qi transmit controller **604**. Transmit controller **604** drives Qi transmit coil **606** to induce a current in the Qi receiving interface of an attached mobile device (not shown). Transmit controller modulates the amount of current in the coil **606**. The induced current wirelessly charges the mobile device. A power source **600** may be an automobile auxiliary power port, a USB port or the like. Power source **600** is electrically coupled to power controller **602**. Power controller **602** modulates the supply of current to the Qi transmit controller. The transmit controller **604** and the power controller **602** may be instantiated as one or more microcontrollers, one or more ASICs or the like.

[0030] In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes can be made thereto without departing from the broader spirit and scope of the invention as set forth in the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

## Claims

1. An apparatus for mounting a mobile device to fixed feature of an automobile, the apparatus comprising: a mounting platform having a device side attachment surface and a back surface, the mounting platform further having an attachment extension to couple to the fixed feature, the device side attachment surface having a permanently fixed orientation relative to the attachment extension;

a first arrangement of magnetic material coupled to the mounting platform to expose a pattern of magnetic fields at the device side attachment surface; and wherein the attachment extension once coupled to the fixed feature maintains the fixed orientation of the attachment surface relative to a cabin of the automobile.

**2.** The apparatus of claim 1 further comprising: a wireless charger coupled to the mounting platform such that the first arrangement of magnetic material aligns the mobile device for wireless charging.

**3.** The apparatus of claim 1 wherein the attachment surface forms an angle in the range of 2.7-12.7 degrees relative to a plane substantially parallel to a dashboard of the automobile when installed on the fixed feature.

**4.** The apparatus of claim 1 wherein the attachment surface forms an angle such that the driver is substantially centered in a view of a front facing camera of a phone when the phone is mounted to the apparatus.

**5.** The apparatus of claim 2 wherein the wireless charger comprises: a transmit Qi coil; and a Qi controller to drive the transmit Qi coil responsive to proximity of a Qi receive coil.

**6.** The apparatus of claim 1 further comprising: a power cable to couple the charger to a power source within the automobile.

**7.** The apparatus of claim 1 wherein the device side attachment surface is formed of a molded synthetic material.

**8.** The apparatus of claim 7 where in the material is elastomeric.

**9.** The apparatus of claim 1 further comprising: an adhesive insert covering substantially all of the display screen coupling surface, the adhesive stable at least to temperatures of 50° C.

**10.** The apparatus of claim 1 further comprising: a second arrangement of magnetic material coupled to the mounting platform to expose a pattern of magnetic fields at the device side attachment surface.

**11.** The apparatus of claim 10 wherein the second arrangement is substantially linear and immediately adjacent regions of magnetic material expose opposite polarity magnetic fields at the device side attachment surface.

**12.** The apparatus of claim 1 wherein the pattern of magnetic fields exposed by the first arrangement forces the mobile device into exactly one orientation on the device side attachment surface.

**13.** The apparatus of claim 10 where in the magnetic fields of the first and second arrangements collectively limit possible orientations of the mobile device on the attachment surface to no more than four orientations.

---