

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250250920
Kind Code	A1
Publication Date	August 07, 2025
Inventor(s)	Sandou; Yoshiyuki et al.

Engine Device

Abstract

An exhaust gas purification device including: a first case communicating with an exhaust manifold of an engine and internally including a first exhaust gas purification body for removing a carbon compound; and a second case communicating with an exhaust outlet of the first case and internally including second exhaust gas purification bodies for removing a nitrogen compound. The first case and the second case are arranged above the engine and in an L-shape to respectively extend along two side surfaces of the engine, the two side surfaces being adjacent to each other.

Inventors: Sandou; Yoshiyuki (Osaka, JP), Naganawa; Hiroaki (Osaka, JP), Sugimoto; Kazuma (Osaka, JP)

Applicant: Yanmar Power Technology Co., Ltd. (Osaka, JP)

Family ID: 59625178

Assignee: Yanmar Power Technology Co., Ltd. (Osaka, JP)

Appl. No.: 19/183869

Filed: April 20, 2025

Foreign Application Priority Data

JP	2016-030016	Feb. 19, 2016
JP	2016-030017	Feb. 19, 2016

Related U.S. Application Data

parent US continuation 18125128 20230323 parent-grant-document US 12297763 child US 19183869

parent US continuation 17376107 20210714 parent-grant-document US 11643960 child US 18125128

parent US continuation 16901122 20200615 parent-grant-document US 11092056 child US 17376107

Publication Classification

Int. Cl.: **F01N3/28** (20060101); **F01N3/021** (20060101); **F01N3/023** (20060101); **F01N3/035** (20060101); **F01N3/20** (20060101); **F01N13/00** (20100101)

U.S. Cl.:

CPC **F01N3/2882** (20130101); **F01N3/021** (20130101); **F01N3/023** (20130101); **F01N3/035** (20130101); **F01N3/2066** (20130101); **F01N3/2892** (20130101); **F01N13/009** (20140601); **F01N2240/20** (20130101); **F01N2470/02** (20130101); **F01N2590/08** (20130101); **F01N2610/02** (20130101)

Background/Summary

CROSS REFERENCES TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 18/125,128 filed Mar. 23, 2023, which is a continuation of U.S. application Ser. No. 17/376,107 filed Jul. 14, 2021, which is a continuation of U.S. application Ser. No. 16/901,122 filed Jun. 15, 2020, which is a continuation of U.S. application Ser. No. 15/999,653 filed Aug. 20, 2018, which is a national stage application pursuant to 35 U.S.C. § 371 of International Application No. PCT/JP2017/005597, filed on Feb. 15, 2017, which claims priority under 35 U.S.C. § 119 to Japanese Patent Application Nos. 2016-030016 and 2016-030017, both filed on Feb. 19, 2016, the disclosures of which are hereby incorporated by reference in their entireties.

DESCRIPTION

Technical Field

[0002] The present invention relates to an engine device, such as a diesel engine, to be mounted in, e.g., an agricultural machine (a tractor, a combine harvester) or a construction machine (a bulldozer, a hydraulic excavator, a loader), and specifically to an engine device equipped with an exhaust gas purification device for removing, e.g., a particulate matter (soot, particulates) contained in the exhaust gas or a nitrogen oxide (NO_x) contained in the exhaust gas.

Background Art

[0003] Traditionally, there have been known techniques for purifying an exhaust gas from a diesel engine by introducing the exhaust gas into an exhaust gas purification device (an exhaust gas aftertreatment device) disposed in an exhaust gas path of the diesel engine, the exhaust gas purification device being constituted by a case internally including a diesel particulate filter (hereinafter, such a case will be referred to as a DPF case) and a case internally including a urea selective reduction catalyst (hereinafter, such a case will be referred to as a selective catalytic reduction (SCR) case) (see, e.g., Patent Literatures 1 and 2 (hereinafter, referred to as PTLs 1 and 2)).

CITATION LIST

[0004] PTL 1: Japanese Patent No. 5543563 [0005] PTL 2: Japanese Patent No. 5244334

[0006] In a configuration as those in PTL 1 in which an exhaust gas purification device constituted by a DPF case and an SCR case disposed in parallel is attached to an engine, an area required for mounting the exhaust gas purification device on the engine device is large. This leads to upsizing of the engine device, which is disadvantageous. In addition, in a configuration in which the above-

described exhaust gas purification device is mounted above the engine device, a height of the engine device increases by a height of the exhaust gas purification device.

[0007] PTL 2 discloses a configuration including a DPF case, a connecting pipe having an inserted portion which is inserted into the DPF case and on which a plurality of through-holes is provided, and a urea water injection nozzle disposed at an end of the connecting pipe, wherein urea water and an exhaust gas are mixed together. In this configuration, the connecting pipe needs to have an adequate length. Otherwise, the urea and the exhaust gas are not mixed adequately, which leads to a reduction in purification effect and to upsizing of the exhaust gas purification device, disadvantageously.

[0008] Some aspects of the present invention have an object to provide an engine device that has been improved as a result of study of the circumstances described above.

SUMMARY OF INVENTION

[0009] In order to attain the above object, an engine device according to an aspect of the present invention is an engine device including an exhaust gas purification device including a first case communicating with an exhaust manifold of an engine and internally including a first exhaust gas purification body for removing a carbon compound and a second case communicating with an exhaust outlet of the first case and internally including a second exhaust gas purification body for removing a nitrogen compound, wherein the first and second cases are arranged above the engine in an L-shape to respectively extend along two side surfaces of the engine, the two side surfaces being adjacent to each other.

[0010] The engine device described above may be configured such that a turbocharger is interposed between the first case and the exhaust manifold, and the first case and the turbocharger are connected to each other in series above the exhaust manifold disposed close to, among the two side surfaces of the engine, a first side surface.

[0011] The engine device described above may be configured such that a flywheel housing is disposed close to, among the two side surfaces of the engine, a second side surface intersecting the first side surface, and the second case is disposed above the flywheel housing.

[0012] The engine device described above may be configured such that the second case is disposed below the first case, and the first case and the second case are connected to each other via a urea mixing tube in a position in which the first case and the second case overlap each other in a plan view.

[0013] The engine device described above may be configured such that a urea-water injection body for injecting urea water into the first case is fixed to a portion of an outer peripheral surface of the first case, the portion being in the position in which the first case and the second case overlap each other in a plan view, the portion being not a portion of the first case through which the urea mixing tube is inserted into the first case. The engine device described above may be configured such that a part of the second exhaust gas purification body is a selective catalytic reduction filter made of a particulate-matter collection filter to which a catalytic component for urea selective catalytic reduction is applied.

[0014] The engine device described above may be configured such that a urea-water injection body for injecting urea water into a urea mixing tube is disposed in a portion of the first case that is close to the exhaust outlet of the first case, and the urea mixing tube has both ends respectively inserted into the exhaust outlet of the first case and an exhaust inlet of the second case to allow the first case and the second case to communicate with each other.

[0015] The engine device described above may be configured such that the urea mixing tube has a first inserted portion that is inserted into the first case, the first inserted portion extending toward the urea-water injection body, the first inserted portion having a tube wall on which an exhaust introduction opening is bored, the exhaust introduction opening allowing an exhaust gas having passed through the first exhaust gas purification body to be introduced into the urea mixing tube.

[0016] The engine device described above may be configured such that the urea mixing tube has a

second inserted portion that is inserted into the second case, the second inserted portion having a distal end that is tapered, the second inserted portion extending to a position apart from an inner wall surface of the second case.

[0017] The engine device described above may be configured such that a mixer for stirring and mixing urea water with an exhaust gas is internally included in a second inserted portion of the urea mixing tube, the second inserted portion being inserted into the second case.

[0018] The engine device described above may be configured such that a mixer for stirring and mixing urea water with an exhaust gas is disposed in the first inserted portion of the urea mixing tube, the first inserted portion being inserted into the first case.

[0019] The engine device described above may be configured such that the second case is disposed below the first case, and the first case and the second case are connected to each other via the urea mixing tube in a position in which the first case and the second case overlap each other in a plan view.

[0020] According to the aspect of the present invention, the first and second cases are arranged in an L-shape above the engine. Thus, the first and second cases can be arranged dispersedly in a space above the engine. Consequently, the top surface side of the engine device can be made low. Thus, upsizing of the engine device including the exhaust gas purification device can be suppressed or reduced, and the engine device having a compact size can be mounted in a limited space of an engine room of, e.g., a work machine.

[0021] According to the aspect of the present invention, the turbocharger and the first case can be compactly disposed above the exhaust manifold. Consequently, the top surface side of the engine device can be made low. In addition, a passage from an outlet of the exhaust manifold to the first case can be made shorter. Furthermore, the turbocharger and the first case can be rigidly supported at a side surface of the engine via the exhaust manifold.

[0022] According to the aspect of the present invention, the second case is disposed above the flywheel housing. Consequently, the second case can also be disposed compactly in the space above the flywheel housing. Thus, upsizing of the engine device including the exhaust gas purification device can be suppressed or reduced.

[0023] According to the aspect of the present invention, the second case is disposed below the first case, and the first case and the second case are connected to each other via the urea mixing tube in the position in which the first case and the second case overlap each other in a plan view. Consequently, the connected portion between the first case and the second case can be made shorter. This makes it possible to suppress or reduce the phenomenon that an exhaust gas passing through the urea mixing tube is influenced by a temperature of outside air, thereby making it possible to reduce the phenomenon that a crystal lump of a urea component is formed in the exhaust gas purification device. Consequently, it is possible to easily prevent an increase in exhaust resistance in the exhaust gas purification device that may otherwise be caused by, e.g., growth of the urea crystal lump.

[0024] According to the aspect of the present invention, the urea-water injection body is mounted in the first case, so that the urea-water injection body and the first case can be constituted as a single unit. This makes it easier to perform an assembling work for mounting the exhaust gas purification device onto the engine device.

[0025] According to the aspect of the present invention, the second case is provided with the SCR filter. Thus, the collecting filter can be omitted from the first case. Accordingly, the first case can be downsized. Consequently, the engine device including the exhaust gas purification device can be made compact.

[0026] According to the aspect of the present invention, the urea-water injection body is mounted in the first case, so that the urea-water injection body and the first case can be constituted as a single unit. This makes it easier to perform an assembling work for mounting the exhaust gas purification device onto the engine device. In addition, according to the aspect of the present

invention, both the ends of the urea mixing tube are respectively inserted into the first and second cases. Consequently, the inside of the urea mixing tube can be maintained at a high temperature by a temperature atmosphere of the exhaust gas. This makes it possible to suppress or reduce crystallization of a urea component in urea water having been injected into the urea mixing tube.

[0027] According to the aspect of the present invention, the exhaust introduction opening is provided on the tube wall of the urea mixing tube. Consequently, a flow velocity of an exhaust gas flowing through the urea mixing tube can be made uniform, and thus urea water sprayed from the urea-water injection body toward the inside of the urea mixing tube is more likely to be stirred and dispersed. This improves the evaporability of the urea component at a low temperature, and also enhances the reaction efficiency between the exhaust gas and the urea component.

[0028] According to the aspect of the present invention, the outlet-side end of the urea mixing tube has a squeezed shape. Consequently, urea water is caused to collide with an inner wall surface of the outlet-side end of the urea mixing tube. This allows evaporation of an unreacted urea component, thereby making it possible to facilitate a reaction between the exhaust gas and the urea component in the second case. In addition, due to the configuration in which the outlet-side end of the urea mixing tube is apart from the second case, it is possible to prevent the urea component from reaching an inner wall surface of the second case, thereby making it possible to suppress or reduce the phenomenon that a crystal lump is formed on the inner wall surface of the second case.

[0029] According to the aspect of the present invention, the mixer internally included in the urea mixing tube is positioned in the first case or the second case. This makes it possible to suppress or reduce a temperature drop in the mixer. In addition, since the exhaust gas whose flow velocity has been made uniform in the urea mixing tube flows into the mixer, a rotation performance of the mixer is made uniform. This facilitates mixing of the urea water with the exhaust gas, thereby making it possible to enhance the evaporability of the urea component. Thus, it is possible to prevent crystallization of the urea component at the mixer. Not only this, it is also possible to facilitate a reaction between the exhaust gas and the urea component, and to suppress or reduce the phenomenon that the urea water in the form of droplets enters the second case.

[0030] According to the aspect of the present invention, the second case is disposed below the first case, and the first case and the second case are connected to each other via the urea mixing tube in the position in which the first case and the second case overlap each other in a plan view. Consequently, the connected portion between the first case and the second case can be made shorter. This makes it possible to suppress or reduce the phenomenon that an exhaust gas passing through the urea mixing tube is influenced by a temperature of outside air, thereby making it possible to reduce the phenomenon that a crystal lump of a urea component is formed in the exhaust gas purification device. Consequently, it is possible to easily prevent an increase in exhaust resistance in the exhaust gas purification device that may otherwise be caused by, e.g., growth of the urea crystal lump.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0031] FIG. 1 illustrates a right side view of a diesel engine according to a first embodiment.

[0032] FIG. 2 illustrates a left side view of the diesel engine according to the first embodiment.

[0033] FIG. 3 illustrates a plan view of the diesel engine according to the first embodiment.

[0034] FIG. 4 illustrates a back view of the diesel engine according to the first embodiment.

[0035] FIG. 5 illustrates an explanatory diagram showing a cross-section of an exhaust gas purification device according to the first embodiment, taken in a right side.

[0036] FIG. 6 illustrates an explanatory diagram showing a cross-section of the exhaust gas purification device according to the first embodiment, taken in a back side.

[0037] FIG. 7 illustrates an explanatory diagram showing a cross-section of an exhaust gas purification device including a urea mixing tube according to a first modification, taken in a right side.

[0038] FIG. 8 illustrates an explanatory diagram showing a cross-section of the exhaust gas purification device including the urea mixing tube according to the first modification, taken in a back side.

[0039] FIG. 9 illustrates an explanatory diagram showing a cross-section of an exhaust gas purification device including a urea mixing tube according to a second modification, taken in a right side.

[0040] FIG. 10 illustrates an explanatory diagram showing a cross-section of the exhaust gas purification device including the urea mixing tube according to the second modification, taken in a back side.

[0041] FIG. 11 illustrates a right side view of a diesel engine according to a second embodiment.

[0042] FIG. 12 illustrates a plan view of the diesel engine according to the second embodiment.

[0043] FIG. 13 illustrates a back view of the diesel engine according to the second embodiment.

[0044] FIG. 14 illustrates an explanatory diagram showing a cross-section of an exhaust gas purification device according to the second embodiment, taken in a back side.

[0045] FIG. 15 illustrates a side view of a work vehicle in which the diesel engine is mounted.

[0046] FIG. 16 illustrates a plan view of the work vehicle.

[0047] FIG. 17 illustrates a back view of a diesel engine according to a third embodiment.

[0048] FIG. 18 illustrates a left side view of a tractor in which the diesel engine is mounted.

[0049] FIG. 19 illustrates a plan view of the tractor.

DESCRIPTION OF EMBODIMENTS

[0050] With reference to the drawings (FIGS. 1 to 6), the following will describe a first embodiment in which the present invention is implemented. FIG. 1 is a right side view of a diesel engine 1, showing a right side on which an exhaust manifold 6 is disposed. FIG. 2 is a left side view of the diesel engine 1, showing a left side on which an intake manifold 3 is disposed. FIG. 3 is a plan view of the diesel engine 1, showing a side on which a cylinder head cover 12 is disposed. FIG. 4 is a back view of the diesel engine 1, showing a side on which a flywheel housing 8 is disposed. The side of the diesel engine 1 on which the exhaust manifold 6 is disposed is referred to as a right side of the diesel engine 1. The side of the diesel engine 1 on which the intake manifold 3 is disposed is referred to as a left side of the diesel engine 1. The side of the diesel engine 1 on which a cooling fan 24 is disposed is referred to as a front side of the diesel engine 1.

[0051] Next, with reference to FIGS. 1 to 4, a configuration of the whole of the diesel engine 1 will be described. The diesel engine 1 includes a cylinder head 2 having one side surface on which the intake manifold 3 is disposed. The cylinder head 2 is mounted above a cylinder block 5 including an engine output shaft 4 (crankshaft) and pistons (not illustrated). The cylinder head 2 has another side surface on which the exhaust manifold 6 is disposed. Front and rear ends of the engine output shaft 4 respectively protrude from front and back side surfaces of the cylinder block 5.

[0052] The cylinder block 5 has a back surface to which the flywheel housing 8 is fixedly attached. In the flywheel housing 8, a flywheel 9 is disposed. The flywheel 9 is pivotally supported at a rear end of the engine output shaft 4. A driving force of the diesel engine 1 is taken via the flywheel 9. The cylinder block 5 has a lower surface on which an oil pan 11 is disposed. The cylinder head cover 12 is disposed adjacent to an upper surface of the cylinder head 2.

[0053] The intake manifold 3 is provided with an exhaust gas recirculation (EGR) device 15 for taking in an exhaust gas that is to be recirculated. An air cleaner (not illustrated) is connected to the intake manifold 3 via a compressor case 25 of a turbocharger 17. External air having been subjected to dust removal and purification by the air cleaner is sent to the intake manifold 3 through the compressor case 25, and is then supplied to cylinders of the diesel engine 1. With the configuration described above, part of an exhaust gas emitted from the diesel engine 1 to the

exhaust manifold **6** is recirculated into the cylinders of the diesel engine **1** from the intake manifold **3** through the exhaust gas recirculation device **15**. Consequently, a combustion temperature of the diesel engine **1** drops. Accordingly, an amount of nitrogen oxide (NO_x) emitted from the diesel engine **1** is reduced, and fuel efficiency of the diesel engine **1** is enhanced.

[0054] Above the exhaust manifold **6**, the turbocharger **17** is disposed. The turbocharger **17** includes the compressor case **25** including a built-in blower wheel and a turbine case **26** including a built-in turbine wheel. The exhaust manifold **6** has an outlet connected to an exhaust intake side of the turbine case **26**. The turbine case **26** has an exhaust emission side connected to an exhaust intake side of the exhaust gas purification device **27**. Namely, an exhaust gas emitted from the cylinders of the diesel engine **1** to the exhaust manifold **6** is discharged to the outside through components such as the turbocharger **17** and the exhaust gas purification device **27**.

[0055] A coolant pump **21** by which coolant is caused to recirculate in the cylinder block **5** and a radiator **19** (see FIG. **16**) is provided. The coolant pump **21** is disposed close to the side of the diesel engine **1** on which the cooling fan **24** is disposed. The coolant pump **21** and the cooling fan **24** are connected to the engine output shaft **4** via, e.g., a V-belt **22**. With this configuration, the coolant pump **21** and the cooling fan **24** are driven. The coolant is sent from the coolant pump **21** into the cylinder block **5** via an EGR cooler **18** of the exhaust gas recirculation device **15**, and cooling air is supplied from the cooling fan **24**. Consequently, the diesel engine **1** is cooled.

[0056] As the exhaust gas purification device **27** for purifying an exhaust gas emitted from the cylinders of the diesel engine **1**, a first exhaust gas purification case **28** (hereinafter, referred to as a first case **28**) that is a oxidation catalyst (DOC) for removing particulate matters in the exhaust gas from the diesel engine **1** and a second exhaust gas purification case **29** (hereinafter, referred to as a second case **29**) that is a urea selective catalytic reduction filter (SCR) system for removing a nitrogen oxide in the exhaust gas from the diesel engine **1** are provided.

[0057] The first case **28**, which is a DOC case, internally includes an oxidation catalyst **30** as an exhaust gas purification body. For example, the oxidation catalyst **30** is made of a wall-through type ceramic honeycomb or a metal mesh on which a catalytic component (e.g., platinum (Pt) and/or palladium (Pd)) for facilitating an oxidation reaction of carbon monoxide (CO) and/or hydrocarbon (HC) is carried. Thus, by causing an exhaust gas from the diesel engine **1** to pass through the first case **28**, carbon monoxide (CO) and/or hydrocarbon (HC) in the exhaust gas is reduced.

[0058] The second case **29**, which is an SCR case, internally includes, as an exhaust gas purification body, an SCR filter **31** for urea selective catalytic reduction, an SCR catalyst **32** for urea selective catalytic reduction, and an ammonia slip catalyst (ASC) **33**. The SCR filter **31** is made of, e.g., a particulate-matter (PM) collection filter to which an SCR catalyst component is applied. For example, the SCR filter **31** is made of a wall-flow type ceramic honeycomb on which a catalytic component (SCR catalyst component) for facilitating NO_x selective catalytic reduction is carried. For example, the SCR catalyst **32** is made of a wall-through type ceramic honeycomb, a metal mesh, or the like on which a SCR catalyst component is carried. The ammonia slip catalyst **33** is an oxidation catalyst for oxidizing ammonia not reacted in the SCR filter **31** and the SCR catalyst **32**. Thus, by causing an exhaust gas from the diesel engine **1** to pass through the second case **29**, a nitrogen oxide (NO_x) in the exhaust gas is reduced.

[0059] The first case **28** has an elongated cylindrical shape extending in parallel to the output shaft (crankshaft) **4** of the diesel engine **1** in a plan view. The second case **29** has an elongated cylindrical shape extending in a direction orthogonal to the output shaft **4** of the diesel engine **1** in a plan view. Namely, the exhaust gas purification device **27** includes the first case **28** and the second case **29** each of which has an elongated cylindrical shape and which are arranged in an L-shape in a plan view to extend along an outer periphery of the cylinder head **2** of the diesel engine **1**.

[0060] The first case **28** has an exhaust gas inlet connected to an exhaust gas outlet of the turbine case **26** in the turbocharger **17**, and also has a longitudinal intermediate portion connected to the

cylinder head 2 via a case support bracket 34. The first case 28 is disposed adjacent to one side (right side) of the cylinder head 2, and is linearly aligned with the turbocharger 17 at a height substantially identical to that of the turbocharger 17. Namely, the first case 28 and the turbocharger 17 are connected in series above the exhaust manifold 6. Consequently, even in a case where the first case 28 of the exhaust gas purification device 27 is mounted in the diesel engine 1, the height of the diesel engine 1 can be made low. Thus, the diesel engine 1 can be mounted even in an engine room having a limited space.

[0061] The second case 29 is fixed above the flywheel housing 8 via a case support bracket 35. The second case 29 is positioned at a lower position than the first case 28. The first case 28 and the second case 29 are arranged in an L-shape such that a part 28a downstream in an exhaust gas traveling direction (hereinafter, such a part will be referred to as an exhaust-gas downstream part 28a) of the first case 28 and a part 29a upstream in the exhaust gas traveling direction (hereinafter, such a part will be referred to as an exhaust-gas upstream part 29a) of the second case 29 overlap each other in a top-and-bottom direction. The first case 28 and the second case 29 are connected to each other via an exhaust communicating tube 36 at the exhaust-gas downstream part 28a and the exhaust-gas upstream part 29a, which overlap each other in the top-and-bottom direction. A urea-water injection body 76 for injecting urea water into the first case 28 is fixed to a portion of an outer peripheral surface of the first case 28. This portion of an outer peripheral surface of the first case 28 is in the position in which the first case 28 and the second case 29 overlap each other in a plan view, and is not a portion of the first case 28 to which the exhaust communicating tube 36 is attached.

[0062] The first case 28 is rigidly supported, by the turbocharger 17 and the case support bracket 34, at a side surface (right side surface) of the diesel engine 1, the side surface being close to the exhaust manifold 6. Meanwhile, the second case 29 is rigidly supported, by the first case 28 and the case support bracket 35, at a side surface (back surface) of the diesel engine 1, the side surface being close to the flywheel housing 8. Consequently, the exhaust gas purification device 27 can be rigidly supported in a space adjacent to an outer periphery of the cylinder head 2 and above the exhaust manifold 6 and the flywheel housing 8. In addition, the diesel engine 1 provided with the exhaust gas purification device 27 can be made compact.

[0063] The first case 28 has a shape reduced toward a downstream side in the exhaust gas traveling direction such that a cross-section of the exhaust-gas downstream part 28a is smaller than that of a part 28b in which the exhaust gas purification body is mounted (hereinafter, such a part will be referred to as an exhaust-gas-purification-body mounted part 28b). The first case 28 is configured such that the exhaust-gas downstream part 28a is disposed closer to the center of the first case 28 than is the exhaust-gas-purification-body mounted part 28b. Consequently, an outer peripheral surface of the exhaust-gas downstream part 28a is closer to the center of the first case 28 than is an outer peripheral surface of the exhaust-gas-purification-body mounted part 28b. This can create, in the vicinity of the outer peripheral surface of the exhaust-gas downstream part 28a, a space in which the urea-water injection body 76 can be mounted.

[0064] The second case 29 has a shape reduced toward an upstream side in the exhaust gas traveling direction such that a cross-section of the exhaust-gas upstream part 29a is smaller than that of a part 29b in which the exhaust gas purification bodies 31 to 33 are mounted (hereinafter, such a part will be referred to as an exhaust-gas-purification-body mounted part 29b). The second case 29 is configured such that lower ends of exhaust-gas upstream part 29a and the exhaust-gas-purification-body mounted part 29b are positioned at substantially identical heights. This provides a sufficient space between the exhaust-gas downstream part 28a of the first case 28 and the exhaust-gas upstream part 29a of the second case 29, which are disposed to overlap each other in different positions in the top-and-bottom direction. Consequently, a urea mixing tube 39, which is internally included in the exhaust communicating tube 36 connecting the exhaust-gas downstream part 28a and the exhaust-gas upstream part 29a, achieves a length allowing urea water and an

exhaust gas to be mixed together adequately.

[0065] Injectors (not illustrated) in the respective cylinders of the diesel engine **1** are provided with a fuel pump **42** and a common rail **43** connected to a fuel tank **45** illustrated in FIG. **15** (FIG. **16**). The cylinder head **2** has a side on which the intake manifold **3** is disposed, and the common rail **43** and a fuel filter **44** are disposed adjacent to that side of the cylinder head **2**. The fuel pump **42** is provided to the cylinder block **5**, which is located below the intake manifold **3**. Each of the injectors has a fuel injection valve (not illustrated) of an electromagnetically-controlled opening and closing type.

[0066] A fuel in a fuel tank **45** is sucked into the fuel pump **42** through the fuel filter **44**.

Meanwhile, a discharge side of the fuel pump **42** is connected to the common rail **43**, and the common rail **43**, which has a cylindrical shape, is connected to the injectors of the diesel engine **1**. A surplus of the fuel forcibly fed from the fuel pump **42** to the common rail **43** is returned to the fuel tank **45**. Then, the high-pressure fuel is temporarily stored in the common rail **43**, and the high-pressure fuel in the common rail **43** is supplied into the cylinders of the diesel engine **1**.

[0067] With the configuration described above, the fuel in the fuel tank **45** is forcibly fed to the common rail **43** by the fuel pump **42**, and the high-pressure fuel is stored in the common rail **43**. In addition, the fuel injection valves of the injectors are controlled to be opened and closed, so that the high-pressure fuel in the common rail **43** is injected to the cylinders of the diesel engine **1**. Namely, by electronically controlling the fuel injection valves of the injectors, it is possible to control a fuel injection pressure, a fuel injection timing, and a fuel injection period (fuel injection amount) with high accuracy. Consequently, it is possible to reduce a nitrogen oxide (NO_x) emitted from the diesel engine **1**.

[0068] Next, with reference to FIGS. **5** and **6**, a configuration of the exhaust gas purification device **27** will be described in detail. As illustrated in FIGS. **5** and **6**, the exhaust gas purification device **27** includes the first case **28** having a double-tube structure constituted by a first inner case **37** and a first outer case **38**, the second case **29** having a double-tube structure constituted by a second inner case **40** and a second outer case **41**, and the exhaust communicating tube **36** via which the first case **28** and the second case **29** are connected to each other. The oxidation catalyst **30** is disposed inside the first inner case **37** that is made of a heat-resistant metallic material and has a substantially cylindrical shape, and the first inner case **37** is disposed inside the first outer case **38** that is made of a heat-resistant metallic material and has a substantially cylindrical shape. The SCR filter **31**, the SCR catalyst **32**, and the ammonia slip catalyst **33** are disposed inside the second inner case **40** that is made of a heat-resistant metallic material and has a substantially cylindrical shape, and the second inner case **40** is disposed inside the second outer case **41** that is made of a heat-resistant metallic material and has a substantially cylindrical shape.

[0069] As illustrated in FIG. **5**, the first case **28** is configured such that the first inner case **37** externally covers, via a heat insulating material **49** that is in the shape of a mat and is made of ceramic fiber, the oxidation catalyst **30** that is a first exhaust gas purification body. Namely, the heat insulating material **49** is pressed into between the oxidation catalyst **30** and the first inner case **37** to protect the oxidation catalyst **30**. In addition, the first outer case **38** externally covers the first inner case **37** with, e.g., a ring-shaped spacer (not illustrated) fitted between the first outer case **38** and the first inner case **37** so that an outer peripheral surface of the first inner case **37** and an inner peripheral surface of the first outer case **38** are apart from each other.

[0070] As illustrated in FIG. **6**, the second case **29** is configured such that the second inner case **40** externally covers, via heat insulating materials **50** to **52** each of which is in the shape of a mat and is made of ceramic fiber, the SCR filter **31**, the SCR catalyst **32**, and the ammonia slip catalyst **33** that are a second exhaust gas purification body. Namely, the heat insulating materials **50** to **52** are respectively pressed into between the SCR filter **31** and the second inner case **40**, between the SCR catalyst **32** and the second inner case **40**, and between the ammonia slip catalyst **33** and the second inner case **40** to protect the SCR filter **31**, the SCR catalyst **32**, and the ammonia slip catalyst **33**. In

addition, the second outer case **41** externally covers the second inner case **40** with, e.g., a ring-shaped spacer (not illustrated) fitted between the second outer case **41** and the second inner case **40** so that an outer peripheral surface of the second inner case **40** and an inner peripheral surface of the second outer case **41** are apart from each other.

[0071] As illustrated in FIGS. 5 and 6, the first case **28** is configured such that the exhaust-gas downstream part **28a**, which is downstream of the oxidation catalyst **30** in the exhaust gas traveling direction, has a smaller diameter than that of the exhaust-gas-purification-body mounted part **28b**, in which the oxidation catalyst **30** is mounted. Namely, parts of the first inner case **37** and the first outer case **38** corresponding to the exhaust-gas downstream part **28a** respectively have smaller diameters than those of parts of the first inner case **37** and the first outer case **38** corresponding to the exhaust-gas-purification-body mounted part **28b**. The parts of the first inner case **37** and the first outer case **38** corresponding to the exhaust-gas downstream part **28a** have through-holes **53** to **56** arranged in the top-and-bottom direction.

[0072] Through the through-holes **53** and **54** respectively provided in upper portions of the first inner case **37** and the first outer case **38**, an injection-body mounting case **57** to which the urea-water injection body **76** is fixed is inserted. The injection-body mounting case **57** is fixed in upper portions of the parts of the first inner case **37** and the first outer case **38** corresponding to the exhaust-gas downstream part **28a** such that an outer peripheral surface of the injection-body mounting case **57** is in contact with inner peripheries of the through-holes **53** and **54** of the first inner case **37** and the first outer case **38**. With this configuration, it is possible to guide urea water from the urea-water injection body **76** into the first inner case **37**, and to prevent intrusion of urea water and/or an exhaust gas into a space between the first inner case **37** and the first outer case **38**.

[0073] Through the through-hole **55** of the first inner case **37**, the urea mixing tube **39** is inserted. Through the through-hole **56** of the first outer case **38**, the urea mixing tube **39** and an exhaust communicating tube **36**, which covers an outer surface of the urea mixing tube **39**, are inserted. The exhaust communicating tube **36** is fixed in lower portions of the parts of the first inner case **37** and the first outer case **38** corresponding to the exhaust-gas downstream part **28a**. Specifically, an upstream end of the exhaust communicating tube **36** in the exhaust gas traveling direction is in contact with a portion of the outer peripheral surface of the first inner case **37**, the portion being outward from the through-hole **55**. In addition, an outer peripheral surface of the exhaust communicating tube **36** is in contact with an inner periphery of the through-hole **56** of the first outer case **38**. An outer peripheral surface of the urea mixing tube **39** is in contact with and fixed to an inner periphery of the through-hole **55** of the first inner case **37**. In addition, an upstream end of the urea mixing tube **39** in the exhaust gas traveling direction is inserted to reach the injection-body mounting case **57**. Consequently, a connected portion between the first case **28** and the second case **29** can achieve a double-tube structure having a high heat insulating property. Furthermore, it is possible to prevent intrusion of urea water and/or an exhaust gas into the space between the first inner case **37** and the first outer case **38**.

[0074] The first inner case **37** and the first outer case **38** have respective exhaust-outlet-side ends to which an exhaust-outlet-side inner lid **58** shaped in a circular disc is fixedly attached. In addition, an exhaust-outlet-side outer lid **59** is fixed to face an outer surface of the exhaust-outlet-side inner lid **58**. The oxidation catalyst **30** has an end surface on a downstream side in the exhaust gas traveling direction, and this end surface of the oxidation catalyst **30** is apart from the exhaust-outlet-side inner lid **58** by a certain distance. Consequently, an upstream-side urea mixing chamber **60** is created between the oxidation catalyst **30** and the exhaust-outlet-side inner lid **58** inside the part of the first inner case **37** corresponding to the exhaust-gas downstream part **28a**. The upstream-side urea mixing chamber **60** receives the urea mixing tube **39** externally inserted thereinto.

[0075] As illustrated in FIGS. 5 and 6, the second case **29** is configured such that the exhaust-gas upstream part **29a**, which is upstream of the SCR filter **31** in the exhaust gas traveling direction, has a smaller diameter than that of the exhaust-gas-purification-body mounted part **29b**, in which

the SCR filter **31**, the SCR catalyst **32**, and the ammonia slip catalyst **33** are mounted. Namely, parts of the second inner case **40** and the second outer case **41** corresponding to the exhaust-gas upstream part **29a** respectively have smaller diameters than those of parts of the second inner case **40** and the second outer case **41** corresponding to the exhaust-gas-purification-body mounted part **29b**. Through-holes **61** and **62** are respectively provided in upper portions of the parts of the second inner case **40** and the second outer case **41** corresponding to the exhaust-gas upstream part **29a**. An exhaust inlet tube **63** is disposed on the outer peripheral surface of the second inner case **40**. An exhaust outlet side of the exhaust inlet tube **63** covers the through-hole **61**, and an exhaust inlet side of the exhaust inlet tube **63** protrudes outward from the through-hole **62** of the second outer case **41**.

[0076] Into the through-hole **61** of the second inner case **40**, the urea mixing tube **39** is inserted. Into the exhaust inlet tube **63**, the urea mixing tube **39** and the exhaust communicating tube **36**, which covers the outer surface of the urea mixing tube **39**, are inserted. The exhaust communicating tube **36** is fixed in upper portions of the parts of the second inner case **40** and the second outer case **41** corresponding to the exhaust-gas upstream part **29a**. Specifically, a downstream end of the exhaust communicating tube **36** in the exhaust gas traveling direction is in contact with a portion of the outer peripheral surface of the second inner case **40**, the portion being outward from the through-hole **61**. In addition, the outer peripheral surface of the exhaust communicating tube **36** is in contact with an inner periphery of the exhaust inlet of the exhaust inlet tube **63**. The outer peripheral surface of the urea mixing tube **39** is in contact with and fixed to an inner periphery of the through-hole **61** of the second inner case **40**. In addition, a downstream end of the urea mixing tube **39** in the exhaust gas traveling direction is inserted to reach the inside of the second inner case **40**. Consequently, a connected portion between the first case **28** and the second case **29** can achieve a double-tube structure having a high heat insulating property. Furthermore, it is possible to prevent intrusion of urea water and/or an exhaust gas into a space between the second inner case **40** and the second outer case **41**.

[0077] The second inner case **40** and the second outer case **41** have respective exhaust-inlet-side ends to which an exhaust-inlet-side inner lid **64** shaped in a circular disc is fixedly attached. In addition, an exhaust-inlet-side outer lid **65** is fixed to face an outer surface of the exhaust-inlet-side inner lid **64**. The SCR filter **31** has an end surface on an upstream side in the exhaust gas traveling direction, and this end surface of the SCR filter **31** is apart from the exhaust-inlet-side inner lid **64** by a certain distance. Consequently, a downstream-side urea mixing chamber **66** is created between the SCR filter **31** and the exhaust-inlet-side inner lid **64** inside the part of the second inner case **40** corresponding to the exhaust-gas upstream part **29a**. The downstream-side urea mixing chamber **66** receives the urea mixing tube **39** externally inserted therinto.

[0078] As illustrated in FIGS. 5 and 6, the urea-water injection body **76** is attached, via an injection seat **77**, to the injection-body mounting case **57** disposed in the exhaust-gas downstream part **28a** of the first case **28**. The urea-water injection body **76** sprays an aqueous urea solution into the upstream-side urea mixing chamber **60** in the first inner case **37**. The urea-water injection body **76** has a urea-water injection valve **78** protruding downward to be inserted into a nozzle mounting hole **79** provided in the injection seat **77**. The urea-water injection body **76** is disposed on the injection-body mounting case **57** such that the position of the nozzle mounting hole **79** penetrating through the injection seat **77** coincides with the position of a urea-water guide hole **80** penetrating through the injection-body mounting case **57**. Consequently, urea water injected from the urea-water injection valve **78** of the urea-water injection body **76** is guided, through the nozzle mounting hole **79** and the urea-water guide hole **80**, into the urea mixing tube **39** disposed inside the upstream-side urea mixing chamber **60**.

[0079] As illustrated in FIGS. 5 and 6, the urea mixing tube **39** has a mixing tube inlet **81** at an upper end of the urea mixing tube **39**, and also has a mixing tube outlet **82** at a lower end of the urea mixing tube **39**. The mixing tube inlet **81** is inserted into the upstream-side urea mixing

chamber **60** created near the exhaust outlet of the first case **28**, whereas the mixing tube outlet **82** is inserted into the downstream-side urea mixing chamber **66** created near the exhaust inlet of the second case **29**. The urea mixing tube **39** has an intermediate portion between the first case **28** and the second case **29**, and an outer peripheral surface of the intermediate portion is covered with the exhaust communicating tube **36**, which is connected to the first case **28** and the second case **29**. Thus, the urea mixing tube **39** is covered with the first case **28**, the second case **29**, and the exhaust communicating tube **36**. This provides a heat insulating layer over the outer peripheral surface of the urea mixing tube **39**. Consequently, the inside of the urea mixing tube **39** can be maintained at a high temperature. This makes it possible to suppress or reduce the phenomenon that a crystal lump of a urea component is formed in the urea mixing tube **39**.

[0080] The urea mixing tube **39** has the end serving as the mixing tube inlet **81** with a obliquely-cut shape (a obliquely-cut circular cylinder shape). Specifically, the mixing tube inlet **81** of the urea mixing tube **39** has a tube wall becoming lower from a side close to the oxidation catalyst **30** (i.e., the oxidation catalyst **30** side) toward a side close to the exhaust-outlet-side inner lid **58**. Namely, the mixing tube inlet **81** of the urea mixing tube **39** is configured such that a portion of the tube wall on the oxidation catalyst **30** side is in contact with a portion of an inner peripheral surface of the injection-body mounting case **57**, the portion being outward from the urea-water guide hole **80**. Consequently, the mixing tube inlet **81** of the urea mixing tube **39** is configured to have a closed space on the oxidation catalyst **30** side. Meanwhile, the mixing tube inlet **81** of the urea mixing tube **39** is opened toward the exhaust-outlet-side inner lid **58**. An inner peripheral surface of the mixing tube inlet **81** of the urea mixing tube **39** is located outward from the urea-water guide hole **80** of the injection-body mounting case **57**. The tube wall of the urea mixing tube **39** has an inserted portion that is inserted into the first case **28**. This inserted portion has a plurality of exhaust introduction holes **83** and thus is porous.

[0081] As described above, the tube wall of the mixing tube inlet **81** of the urea mixing tube **39** has a height increasing toward the oxidation catalyst **30**. Due to such a shape of the mixing tube inlet **81**, most of an exhaust gas having passed through the oxidation catalyst **30** makes a detour and is introduced into the urea mixing tube **81** from the exhaust-outlet-side inner lid **58** side. Thus, the obliquely-cut opening and the exhaust introduction holes **83** of the mixing tube inlet **81** each function as an exhaust introduction opening allowing an exhaust gas to be introduced into the urea mixing tube **39**. Consequently, a flow velocity of the exhaust gas introduced into the urea mixing tube **39** can be made uniform. As a result, urea water sprayed from the urea-water injection valve **78** toward the mixing tube inlet **81** of the urea mixing tube **39** becomes more likely to be stirred and dispersed. This improves the evaporativity of the urea component at a low temperature, and also enhances the reaction efficiency between the exhaust gas and the urea component.

[0082] The urea mixing tube **39** has the end serving as the mixing tube outlet **82** and being narrowed (tapered) toward a distal end thereof. Namely, a diameter of the mixing tube outlet **82** is reduced toward the distal end. In addition, the mixing tube outlet **82** extends toward a portion of an inner wall surface of the second case **29**, the portion being opposite to the exhaust inlet tube **63**. Although the mixing tube outlet **82** of the urea mixing tube **39** extends into the second inner case **40** of the second case **29**, the mixing tube outlet **82** is located apart from an inner wall surface of the second inner case **40**.

[0083] As described above, the mixing tube outlet **82** of the urea mixing tube **39** is squeezed toward the distal end. Due to such a shape of the mixing tube outlet **82**, urea water is caused to collide with an inner wall surface of the mixing tube outlet **82** at the distal end. Thus, the exhaust gas and an unreacted urea component are caused to collide with the mixing tube outlet **82**, so as to be evaporated. This facilitates a reaction between the exhaust gas and the urea component in the downstream-side urea mixing chamber **66** in the second case **29**. Furthermore, it is possible to prevent the urea component from reaching the inner wall surface of the second inner case **40**, thereby suppressing or reducing the phenomenon that a crystal lump is formed on the inner wall

surface of the second inner case **40**.

[0084] The urea mixing tube **39** internally includes, at a location downstream of the portion in which the exhaust introduction holes **83** are bored, a mixer **84** for facilitating mixing of the urea water and the exhaust gas together. For example, the mixer **84** includes a plurality of blades arranged radially in point symmetry with respect to a central axis of the urea mixing tube **39**. The mixer **84** causes the urea water to be mixed and dispersed in the exhaust gas. The mixer **84** is disposed at a location from which the urea mixing tube **39** is inserted into the second case **29** (i.e., a location near the through-holes **61** and **62**). Thus, the mixer **84** is fixed at a location upstream of the mixing tube outlet **82** of the urea mixing tube **39** when viewed in the exhaust gas traveling direction.

[0085] As described above, the mixer **84** is disposed inside the second case **29**, which has a high heat-insulating property. Consequently, it is possible to suppress or reduce a temperature drop in the mixer **84**. In addition, since the exhaust gas whose flow velocity has been made uniform at the mixing tube inlet **81** flows into the mixer **84**, the mixer **84** achieves rotatability free from fluctuations. This facilitates mixing of the urea water with the exhaust gas, thereby making it possible to enhance the evaporability of the urea component. Thus, the above configuration can prevent crystallization of the urea component in the mixer **84**. Not only this, the above configuration can facilitate a reaction between the exhaust gas and the urea component, and can suppress or reduce the phenomenon that the urea water in the form of droplets enters the second case **29**. In addition, due to the configuration in which the mixing tube outlet **82** downstream of the mixer **84** has a tapered shape, the urea water having passed through the mixer **84** and being in the form of droplets is caused to collide with the mixing tube outlet **82**. This prevents the urea component from reaching the inner wall surface of the second inner case **40**.

[0086] Next, with reference to FIGS. **7** and **8**, a first modification of the urea mixing tube **39** will be described. In the present modification, as illustrated in FIGS. **7** and **8**, a mixing tube inlet **81** of a urea mixing tube **39** has a bell-mouth shape. In addition, the mixing tube inlet **81** has an expanded distal end and is in contact with a portion of an injection-body mounting case **57**, the portion being outward from a urea-water guide hole **80** of the injection-body mounting case **57**. The urea mixing tube **39** has an inserted portion that is inserted into a first case **28**. A tube wall of the inserted portion of the urea mixing tube **39** is partially bent toward the inside of the urea mixing tube **39**, and the bent part of the tube wall functions as a urea collision plate **85**. As a result of cutting the tube wall of the urea mixing tube **39** to yield the urea collision plate **85**, an opening is created. This opening functions as an exhaust introduction opening **86** allowing an exhaust gas having passed through an oxidation catalyst **30** to be introduced into the urea mixing tube **39**.

[0087] The urea mixing tube **39** includes a plurality of urea collision plates **85** that are bent parts of the tube wall of the urea mixing tube **39**. Each of the urea collision plates **85** extends in a direction toward the center of the urea mixing tube **39** and away from a urea-water injection valve **78**. The urea mixing tube **39** has the exhaust introduction openings **86** each opened downward from a position at which a respective one of the urea collision plates **85** is bent. Consequently, the urea mixing tube **39** has a reduced diameter, i.e., is narrowed (squeezed) at a location in which the urea collision plates **85** are provided. The urea mixing tube **39** has a shape whose cross-section is continuously increased toward a downstream side (downward) from the location at which the urea collision plates **85** are provided.

[0088] Due to the configuration in which the mixing tube inlet **81** of the urea mixing tube **39** has a bell-mouth shape, a urea component from the urea-water injection valve **78** is hardly adhered to the tube wall of the urea mixing tube **39**. Furthermore, due to the configuration in which the inserted portion of the urea mixing tube **39** that is inserted into the first case **28** is squeezed at the location in which the exhaust introduction openings **86** are provided, it is possible to increase a flow velocity of an exhaust gas introduced through the exhaust introduction openings **86**, thereby facilitating a temperature increase in the tube wall of the urea mixing tube **39**. Moreover, due to the

configuration in which the tube wall of the urea mixing tube **39** is gradually expanded toward lower through-holes **55** and **56** of the first case **28**, it is possible to suppress or reduce a temperature drop in the tube wall of the urea mixing tube **39**. Consequently, it is possible to reduce the phenomenon that a crystal lump of a urea component is formed on an inner wall surface of the urea mixing tube **39**, thereby making it possible to easily prevent an increase in exhaust resistance in the urea mixing tube **39** that may otherwise be caused by, e.g., growth of the urea crystal lump.

[0089] Due to the configuration in which the urea mixing tube **39** includes the urea collision plates **85** located downstream (downward) of the urea-water injection valve **78**, urea water injected from the urea-water injection valve **78** is caused to collide with the urea collision plates **85**.

Consequently, the urea water can be easily made into fine particles. This facilitates a reaction between the urea component and the exhaust gas. With a greater inclination angle (an angle at which the urea water collides with each of the urea collision plates **85**) of each of the urea collision plates **85** with respect to a direction in which the urea water is injected from the urea-water injection valve **78**, the urea water hardly forms a liquid membrane on the parts of the tube wall corresponding to the urea collision plates **85**. Consequently, it is possible to suppress or reduce formation of a crystal lump of the urea component.

[0090] In addition, due to the configuration in which the urea collision plates **85** are made of the parts of the tube wall of the urea mixing tube **39** and the exhaust introduction openings **86** are provided in the tube wall of the urea mixing tube **39**, the urea collision plates **85** are exposed to the exhaust gas having a high temperature and accordingly the temperatures of the urea collision plates **85** can be increased. Consequently, even in a case where the urea water injected from the urea-water injection valve **78** collides with the urea collision plates **85**, it is possible to suppress or reduce the phenomenon that a crystal lump of the urea component is formed on the urea collision plates **85**.

[0091] In addition, the inserted portion of the urea mixing tube **39** that is inserted into the first case **28** is squeezed at a location downstream of the mixing tube inlet **81**, and the urea collision plates **85** are provided at the squeezed location. This configuration makes it possible to increase a flow velocity of the exhaust gas at the location in which the urea collision plates **85** are provided. This facilitates heat exchange between the urea collision plates **85** and the exhaust gas. Consequently, it is possible to effectively increase the temperatures of the urea collision plates **85**.

[0092] Next, with reference to FIGS. **9** and **10**, a second modification of the urea mixing tube **39** will be described. In the present modification, as illustrated in FIGS. **9** and **10**, a mixing tube outlet **82** of a urea mixing tube **39** has an outer peripheral surface provided with a plurality of heat exchange fins **87** protruding outwardly. Due to the heat exchange fins **87** provided to the mixing tube outlet **82**, it is possible to suppress or reduce, by a temperature atmosphere in a second case **29**, a temperature drop in a tube wall of an inserted portion of the mixing tube outlet **82**, the inserted portion having been inserted into a downstream-side urea mixing chamber **66**.

Consequently, it is possible to improve the evaporability of a urea component that collides with the tube wall of the mixing tube outlet **82**, thereby facilitating a reaction between the urea component and an exhaust gas. Note that the present modification can be combined with the configuration of the first modification.

[0093] With reference to the drawings (FIGS. **11** to **14**), the following will describe a second embodiment in which the present invention is implemented. FIG. **11** is a right side view of a diesel engine **1**, showing a right side on which an exhaust manifold **6** is disposed. FIG. **12** is a plan view of the diesel engine **1**, showing a side on which a cylinder head cover **12** is disposed. FIG. **13** is a back view of the diesel engine **1**, showing a side on which a flywheel housing **8** is disposed. Note that components and parts/portions of an engine device of the present embodiment identical to those of the engine device of the first embodiment are given identical reference signs, and detailed description thereof is omitted.

[0094] With reference to FIGS. **11** to **14**, the following will describe a connection structure of an

exhaust gas purification device **27** according to the present embodiment. As illustrated in FIGS. **11** to **14**, in the exhaust gas purification device **27** of the present embodiment, a urea-water injection body **76** is fixed to a portion of an outer peripheral surface of an exhaust-gas downstream part **28a** of a first case **28**, the portion being located inward (i.e., closer to the cylinder head cover **12**) from the top of the first case **28**.

[0095] Parts of a first inner case **37** and a first outer case **38** of the first case **28** corresponding to the exhaust-gas downstream part **28a** respectively have through-holes **53** and **54** located leftward of the top of the first case **28** (i.e., closer to the cylinder head cover **12**). An injection-body mounting case **57** is mounted through the through-holes **53** and **54** in the first case **28** such that the injection-body mounting case **57** extends obliquely toward the lower right. Consequently, a surface of the injection-body mounting case **57** on which the urea-water injection body **76** is to be mounted is inclined toward the cylinder head cover **12** (to the left). Thus, the urea-water injection body **76** is mounted inclined. As a result, the urea-water injection body **76** is supported at a low position above the diesel engine **1**. Thus, the top surface side of the diesel engine **1** can be made low.

[0096] The urea mixing tube **39** is inserted into the first case **28** from a lower portion of the first case **28**, the lower portion being outside of and lateral to (at the right side of) the engine device. In addition, a mixing tube inlet **81** of the urea mixing tube **39** extends toward the urea-water injection body **76** (toward the upper left). Namely, the mixing tube inlet **81** of the urea mixing tube **39** is inserted into the first inner case **37** through through-holes **55** and **56** located in the lower portion of the first case **28**, the lower portion being outside of and lateral to (at the right side of) the engine device. The urea mixing tube **39** has an intermediate portion that is bent in a second case **29** so that a mixing tube outlet **82** is inserted into the second case **29** orthogonally to a longitudinal direction of the second case **29**.

[0097] An exhaust communicating tube **36** is obliquely disposed such that the exhaust communicating tube **36** is inclined toward the cylinder head **2** (toward the left) relative to a direction orthogonal (vertical) to the longitudinal direction of the second case **29**. Via the exhaust communicating tube **36**, an exhaust inlet tube **63** protruded from a second outer case **41** and the through-hole **56** of the first outer case **38** communicate with each other. In addition, the exhaust communicating tube **36** covers an outer peripheral surface of the intermediate portion of the urea mixing tube **39**. The bent portion of the urea mixing tube **39** is located in the vicinity of through-holes **61** and **62** of the second case **29**, and is covered with the exhaust communicating tube **36** and the exhaust inlet tube **63**. Due to the configuration in which the bent portion of the urea mixing tube **39** is located inside the second case **29**, a temperature of the tube wall of the bent portion can be increased to a high temperature. Consequently, it is possible to suppress or reduce crystallization of a urea component that collides with an inner wall surface of the exhaust communicating tube **36**.

[0098] A mixer **84** is disposed in an inserted portion of the urea mixing tube **39** that is inserted into the first case **28**. The mixer **84**, which facilitates mixing of urea water and an exhaust gas together, is internally included in the urea mixing tube **39**, and is located downstream of a portion of the urea mixing tube **39** in which exhaust introduction holes **83** are bored. In the present embodiment, the mixer **84** is located in the vicinity of the lower through-holes **55** and **56** of the first case **28**. By placing the mixer **84** inside the first case **28**, the mixer **84** can be under an environment of a high-temperature exhaust gas. Consequently, it is possible to improve evaporation performance achieved with the mixer **84**. Not only this, it is possible to suppress or reduce formation of a crystal lump of a urea component, thereby facilitating a reaction between the urea component and an exhaust gas.

[0099] In the present embodiment, the mixer **84** is disposed inside the first case **28**, and thus a distance between the mixer **84** and the mixing tube outlet **82** in the urea mixing tube **39** is long. Thanks to this, the mixing tube outlet **82** can emit the exhaust gas in which the urea component is adequately stirred and mixed. In the above configuration, the mixing tube outlet **82** of the urea mixing tube **39** inserted into the second case **29** is squeezed to be tapered, in a similar manner to the first embodiment. However, in view of the above effect, the urea mixing tube **82** may have a

shape whose tube diameter is constant to its distal end. In the present embodiment, a portion of the urea mixing tube **39** close to the mixing tube inlet **81** may have a similar shape to that of the first modification of the first embodiment. Also, a portion of the urea mixing tube **39** close to the mixing tube outlet **82** may be provided with a heat exchange fin **87** in a similar manner to the second modification of the first embodiment.

[0100] With reference to FIGS. **15** and **16**, the following will describe a configuration of an excavator **100** in which the diesel engine **1** according to the first or second embodiment is mounted. As illustrated in FIGS. **15** and **16**, the excavator **100** includes a crawler-type traveling device **102** having a pair of left and right traveling crawlers **103** and a slewing body **104** provided above the traveling device **102**. The slewing body **104** is horizontally turnable in all directions of 360° by a hydraulic motor (not illustrated) for slewing. The slewing body **104** has a front left portion in which a cabin (operation unit) **106** is mounted. The slewing body **104** has a front center portion in which a work unit **110** provided with a boom **111** and a bucket **113** each used for an excavation work is mounted. The slewing body **104** has a rear portion in which a radiator **19** and the diesel engine **1** are mounted. The slewing body **104** has a right side portion in which a fuel tank **45** and a urea water tank **71** are mounted.

[0101] In the cabin **106**, an operator's seat on which an operator sits and a lever or a switch used as an operation means for operating an output of, e.g., the diesel engine **1** and/or an operation means for the work unit **110** are disposed. The boom **111**, which is a component of the work unit **110**, is provided with a boom cylinder **112** and a bucket cylinder **114**. The boom **111** has a distal end at which a bucket **113** that is an attachment for excavation is pivotably attached such that the bucket **113** is turnable for scooping. By actuating the boom cylinder **112** or the bucket cylinder **114**, the bucket **113** is actuated to perform an earthwork (a ground work such as furrowing).

[0102] The slewing body **104** has a rear left portion in which the radiator **19** is mounted. On the right side of the radiator **19**, the diesel engine **1** is mounted such that a cooling fan **24** of the diesel engine **1** faces the radiator **19**. The diesel engine **1** is disposed such that the side on which the exhaust manifold **6** is mounted faces the cabin **106** and the work unit **110**. In addition, the top surface of the diesel engine **1** is covered with a hood **115**. The first case **28** of the exhaust gas purification device **27** is disposed behind the work unit **110**, and the second case **29** of the exhaust gas purification device **27** extends rearward from the connected portion between the first case **28** and the second case **29**. The tail pipe **116**, which is connected to the exhaust outlet of the second case **29**, protrudes upward from a rear portion of the hood **115**.

[0103] The fuel tank **45** and the urea water tank **71**, which are disposed in the right side portion of the slewing body **104**, are arranged side by side in a front-and-rear direction. The fuel tank **45** and the urea water tank **71** are respectively provided with a fuel inlet **46** and a water inlet **72** each protruding toward the right. In addition, a urea water injection pump **73** for forcibly feeding an aqueous urea solution in the urea water tank **71** is interposed between the urea water tank **71** and the first case **28**. Consequently, urea water pipe arrangement for connecting the urea-water injection body **76** fixed to the first case **28** and the urea water pump **73** to each other can be made shorter. Furthermore, urea water pipe arrangement for connecting the urea water tank **71** and the urea water pump **73** to each other can also be made shorter.

[0104] With reference to the drawings (FIGS. **17** to **19**), the following will describe a third embodiment in which the present invention is implemented. Note that components and parts/portions of an engine device of the present embodiment identical to those of the engine device of the second embodiment are given identical reference signs, and detailed description thereof is omitted.

[0105] As illustrated in FIG. **17**, a diesel engine **1** of the present embodiment includes an exhaust gas purification device **27** including a first case **28** disposed on a top surface of the diesel engine **1** and a second case **29** disposed remotely from the diesel engine **1**. An exhaust outlet of the first case **28** and an exhaust inlet of the second case **29** communicate with each other via an exhaust

connecting tube **177** having an L-shape. In addition, the exhaust connecting tube **177** internally includes a urea mixing tube **176**. Consequently, a connected portion between the first case **28** and the second case **29** has a double-tube structure.

[0106] Similarly to the second embodiment, the urea mixing tube **176** has a mixing tube inlet **81** inserted into an exhaust-gas downstream part **28a** of the first case **28**. Similarly to the second embodiment, the mixing tube inlet **81** of the urea mixing tube **176** is configured to have an end that is obliquely cut, to have exhaust introduction holes **83**, and to internally include a mixer **84** (see FIG. 6).

[0107] In addition, similarly to the second embodiment, the urea mixing tube **176** has a mixing tube outlet **82** inserted into an exhaust-gas upstream part **29a** of the second case **29**. Similarly to the second embodiment, the mixing tube inlet **81** of the urea mixing tube **176** has a distal end that is squeezed. Note that, similarly to the first and second embodiments, the configurations of the urea mixing tubes **176** according to the first and second modifications may be applied to the urea mixing tube **176** of the present embodiment.

[0108] With reference to FIGS. **17** to **19**, the following will describe a tractor **151** in which the diesel engine **1** of the third embodiment is mounted. As illustrated in FIGS. **17** to **19**, a tractor **151** for an agricultural work that is a work vehicle includes: a carriage **152** supported by a pair of left and right front wheels **153** and a pair of left and right rear wheels **154**; and the diesel engine **1** mounted in a front portion of the carriage **152**. The diesel engine **1** is driven to drive the rear wheels **154** and the front wheels **153** to cause the tractor **151** to run forward or backward. The top surface and the left and right side surfaces of the diesel engine **1** are covered with a hood **156** that is openable.

[0109] In addition, a cabin (operation unit) **157** on which an operator is to ride is mounted on a portion of a top surface of the carriage **152**, the portion being behind the hood **156**. The cabin **157** includes, in its inside, an operator's seat **158** on which the operator is to sit and a steering instrument such as a steering wheel **159** that is a steering means. In addition, a pair of left and right steps **160**, which can be used when the operator gets in or off the cabin **157**, are provided outside of left and right sides of the cabin **157**, respectively. In a space inward from the steps **160** and below a bottom of the cabin **157**, a fuel tank **45** from which a fuel is supplied to the diesel engine **1** is disposed.

[0110] The carriage **152** includes a transmission case **161** for changing an output from the diesel engine **1** and transmitting the output to the rear wheels **154** (the front wheels **153**). The transmission case **161** has a rear portion to which a machine such as a tilling machine (not illustrated) is connected, e.g., via a lower link **162**, a top link **163**, and a lift arm **164** in such a manner that the tilling machine can be raised and lowered. In addition, a power take-off (PTO) shaft **165** for driving, e.g., the tilling machine is disposed in a rear side surface of the transmission case **161**. The carriage **152** of the tractor **151** includes, e.g., the diesel engine **1**, the transmission case **161**, and a clutch case **166** by which the diesel engine **1** and the transmission case **161** are connected to each other.

[0111] In addition, the second case **29** is attached to a right corner portion in a front surface of the cabin **157** so that the second case **29** is upright and vertically long. A tail pipe **178** is disposed upright to extend from the exhaust outlet side of the second case **29**. Namely, at the right corner portion in the front surface of the cabin **157**, the tail pipe **178** and the second case **29** are arranged in series in the top-and-bottom direction. The exhaust inlet tube **63** of the second case **29** is connected to the exhaust outlet of the first case **28** under the hood **156** via the exhaust connecting tube **177** having, in its intermediate portion, a bellows-tube type flexible tube **179**.

[0112] The urea water tank **71** is disposed at a portion of the front surface of the cabin **157**, the portion corresponding to a left side of the hood **156** and being opposite to the right side on which the tail pipe **178** is disposed. Namely, the urea water tank **71** is mounted on a portion of the carriage **152** (e.g., on a portion of a bottom frame of the cabin **157**), the portion corresponding to a rear left

portion of the hood **156**. To a lower left portion of the front surface of the cabin **157**, the fuel inlet **46** of the fuel tank **45** and the water inlet **72** of the urea water tank **71** are disposed adjacent to each other. The tail pipe **178** is disposed in a portion of the front surface of the cabin **157** on the right side, through which the operator seldom gets in and off the cabin **157**. Meanwhile, the fuel inlet **46** and the water inlet **72** are disposed in a portion of the front surface of the cabin **157** on the left side, through which the operator often gets in and off the cabin **157**. Note that the cabin **157** is configured such that the operator can get to and leave the operator's seat **158** through either of the left side and the right side of the cabin **157**.

[0113] In addition, the urea water injection pump **73** for forcibly feeding an aqueous urea solution in the urea water tank **71** is interposed between the urea water tank **71** and the first case **28**.

Consequently, urea water pipe arrangement for connecting the urea-water injection body **76** fixed to the first case **28** and the urea water injection pump **73** to each other can be made shorter.

Furthermore, urea water pipe arrangement for connecting the urea water tank **71** and the urea water injection pump **73** to each other can also be made shorter. Thus, efficient urea water pipe arrangement can be achieved. Consequently, it is possible to simplify a piping work and a maintenance work. Not only this, it is possible to reduce influences given by an external environment on the urea water pipe arrangement, thereby suppressing or reducing crystallization of urea water in the urea water pipe arrangement.

[0114] Note that the configurations of the parts/portions of the present invention are not limited to those in the illustrated embodiments, and can be modified and changed in various ways unless such modifications and changes depart from the scope of the present invention. For example, the configurations of the embodiments described above may be applied to an exhaust gas processing device including: a first case that is a DPF case including an oxidation catalyst and a soot filter as a first exhaust gas purification body; and a second case that is an SCR case including an SCR catalyst and an ammonia slip catalyst as a second exhaust gas purification body. In the embodiments described above, the mixer includes the blades that are fixed. Alternatively, a mixer including rotatable blades may be employed.

REFERENCE SIGNS LIST

TABLE-US-00001 REFERENCE SIGNS LIST 1, diesel engine 27, exhaust gas purification device 28, first case 29, second case 30, oxidation catalyst 31, SCR filter 32, SCR catalyst 33, ammonia slip catalyst 36, exhaust communicating tube 37, first inner case 38, first outer case 39, urea mixing tube 40, second inner case 41, second outer case 76, urea-water injection body 78, urea-water injection valve 79, nozzle mounting hole 80, urea-water guide hole 81, mixing tube inlet 82, mixing tube outlet 83, exhaust introduction hole 84, mixer 85, urea collision plate 86, exhaust introduction opening 87, heat exchange fin

Claims

- 1:** An engine device comprising: an exhaust gas purification device including: a first case; and a second case, wherein the first case and the second case are connected via a tube; and a urea-water injection body for injecting urea water into the tube is placed above the first case.
- 2:** The engine device according to claim 1, wherein the urea-water injection body is provided above an exhaust outlet of the first case.
- 3:** The engine device according to claim 2, wherein a straight portion of the tube is provided downstream of the urea-water injection body in a direction of exhaust gas flow.
- 4:** The engine device according to claim 1, wherein a flow direction of the exhaust gas changes between an upstream side and a downstream side of the urea-water injection body.
- 5:** The engine device according to claim 1, wherein at least a portion of the tube extends vertically.
- 6:** The engine device according to claim 1, wherein one of the cases is placed on a top surface of the engine, and the other is placed on a side surface of the engine.

- 7: The engine device according to claim 1, wherein the second case is positioned lower than the first case vertically.
- 8: The engine device according to claim 1, wherein the second case is disposed above a flywheel housing.
-