



US012383072B2

(12) **United States Patent**
Moon et al.

(10) **Patent No.:** **US 12,383,072 B2**

(45) **Date of Patent:** **Aug. 12, 2025**

(54) **MATTRESSES INCLUDING GEL CUSHIONS OVER COILS**

(71) Applicant: **Purple Innovation, LLC**, Lehi, UT (US)

(72) Inventors: **Shawn David Moon**, Cedar Hill, UT (US); **Lars C. Hamilton**, Carmel, IN (US); **Tanner R. Wheadon**, Washington, UT (US)

(73) Assignee: **Purple Innovation, LLC**, Lehi, UT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/121,549**

(22) Filed: **Mar. 14, 2023**

(65) **Prior Publication Data**

US 2023/0218089 A1 Jul. 13, 2023

Related U.S. Application Data

(63) Continuation of application No. 17/142,147, filed on Jan. 5, 2021, now Pat. No. 11,602,227, which is a continuation of application No. 15/662,934, filed on Jul. 28, 2017, now Pat. No. 10,881,217.

(51) **Int. Cl.**
A47C 27/06 (2006.01)
A47C 27/045 (2006.01)
A47C 27/05 (2006.01)

(52) **U.S. Cl.**
CPC **A47C 27/064** (2013.01); **A47C 27/0453** (2013.01); **A47C 27/053** (2013.01)

(58) **Field of Classification Search**

CPC . A47C 27/064; A47C 27/0453; A47C 27/053; A47C 31/006; A47C 27/15; A47C 27/06

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

174,344	A	3/1876	Andrews	
698,529	A	4/1902	Marshall	
2,615,180	A *	10/1952	Woller	A47C 27/064 5/720

(Continued)

FOREIGN PATENT DOCUMENTS

CN	2272697	Y	1/1998
CN	200970040	Y	11/2007

(Continued)

OTHER PUBLICATIONS

Baltex, "Spacer Fabric and 3D Spacer Fabrics," <http://www.baltex.co.uk/spacerfabrics>, Jun. 30, 2017.

(Continued)


Primary Examiner — Fredrick C Conley

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(57) **ABSTRACT**

A mattress assembly includes a base core layer and an inner core located over the base core layer. The inner core includes coil springs. The mattress assembly also includes a side panel assembly located around a perimeter of the inner core. The side panel assembly includes a spacer fabric located over and transverse to the base core layer. The spacer fabric includes a first knit layer, a second knit layer, and an inner fibrous material located therebetween. Methods of forming the mattress assembly are disclosed.

20 Claims, 3 Drawing Sheets



(56)	References Cited			2009/0062432 A1 *	3/2009	Doesburg	C08G 18/8051 524/425
	U.S. PATENT DOCUMENTS			2009/0100606 A1	4/2009	An	
				2009/0246449 A1	10/2009	Jusiak	
3,512,192 A	5/1970	Simon		2009/0261518 A1	10/2009	Defranks et al.	
4,092,752 A	6/1978	Dougan		2009/0288259 A1	11/2009	Lean et al.	
4,213,214 A	7/1980	Gilhooly		2009/0320209 A1	12/2009	McCain	
4,234,981 A	11/1980	Hanson		2010/0005595 A1	1/2010	Gladney et al.	
4,369,284 A	1/1983	Chen		2010/0115703 A1	5/2010	Kluft	
4,469,739 A	9/1984	Gretzinger et al.		2010/0146709 A1	6/2010	Lafleche et al.	
4,471,020 A	9/1984	McCarthy		2010/0192299 A1	8/2010	Schermel et al.	
4,504,991 A	3/1985	Klancnik		2010/0227091 A1 *	9/2010	Pearce	B32B 3/08 428/36.1
4,685,727 A	8/1987	Cremer et al.					
4,866,799 A	9/1989	Glackin		2010/0237082 A1	9/2010	Fernandez	
5,107,558 A	4/1992	Luck		2010/0319137 A1	12/2010	Witherell et al.	
5,179,742 A	1/1993	Oberle		2011/0173757 A1 *	7/2011	Rensink	A47C 27/15 5/655.5
5,327,596 A	7/1994	Wallace et al.					
5,613,257 A	3/1997	Graebe		2011/0179579 A1	7/2011	Henderson et al.	
5,749,111 A *	5/1998	Pearce	B29C 48/11 428/137	2011/0197363 A1	8/2011	Kokenes et al.	
				2011/0197367 A1	8/2011	Mossbeck	
5,994,450 A	11/1999	Pearce		2011/0302721 A1	12/2011	Khambete et al.	
6,026,527 A	2/2000	Pearce		2011/0314613 A1	12/2011	Haffner et al.	
6,243,900 B1	6/2001	Gladney et al.		2013/0025070 A1	1/2013	Ruehlmann et al.	
6,397,418 B1	6/2002	Stjerna		2013/0043628 A1 *	2/2013	Pearce	A47C 7/02 267/153
6,413,458 B1	7/2002	Pearce					
6,490,744 B1 *	12/2002	Schulz, Jr.	A47C 27/063 5/716	2013/0152305 A1	6/2013	Lall	
				2013/0174344 A1	7/2013	Klancnik et al.	
6,523,812 B1	2/2003	Spinks et al.		2013/0205509 A1	8/2013	Chen	
6,701,557 B2	3/2004	Barman		2014/0130265 A1	5/2014	Lauer et al.	
7,076,822 B2	7/2006	Pearce		2014/0165292 A1	6/2014	Gladney	
7,581,271 B2	9/2009	Gladney et al.		2014/0208517 A1	7/2014	Gross et al.	
7,640,611 B1	1/2010	Kluft		2014/0325763 A1	11/2014	Mason	
7,730,566 B2	6/2010	Flick et al.		2014/0359939 A1	12/2014	Carlitz	
7,757,322 B2	7/2010	An		2014/0373281 A1	12/2014	Mossbeck et al.	
7,964,664 B2	6/2011	Pearce		2014/0373282 A1	12/2014	Mossbeck et al.	
8,006,360 B2	8/2011	Richmond et al.		2015/0026897 A1	1/2015	Chunglo	
8,353,072 B2	1/2013	Klancnik		2015/0067967 A1	3/2015	Tyree	
8,429,776 B2	4/2013	Klancnik et al.		2015/0096121 A1	4/2015	Scarleski	
8,434,748 B1	5/2013	Pearce et al.		2015/0217534 A1	8/2015	Rancourt et al.	
8,607,387 B2	12/2013	Flick et al.		2015/0223622 A1	8/2015	Mobley et al.	
8,628,067 B2	1/2014	Pearce et al.		2015/0231007 A1	8/2015	Vrzalik et al.	
8,784,982 B2	7/2014	Pearce et al.		2015/0305515 A1	10/2015	Arendoski et al.	
8,832,888 B2	9/2014	Chunglo		2016/0235212 A1	8/2016	Krtek et al.	
8,910,334 B2	12/2014	Lafleche et al.		2016/0262561 A1	9/2016	Pearce et al.	
8,918,934 B2	12/2014	Roma et al.		2017/0189238 A1	7/2017	Andrews	
8,919,750 B2	12/2014	Pearce et al.		2017/0251825 A1	9/2017	Pearce	
8,932,692 B2	1/2015	Pearce		2017/0251838 A1 *	9/2017	Whatcott	A47C 31/105
8,997,279 B1	4/2015	McKay et al.		2018/0049559 A1	2/2018	Jewett et al.	
9,032,571 B2	5/2015	Rancourt et al.		2018/0168361 A1	6/2018	Patmore et al.	
9,066,794 B2	6/2015	Jusiak et al.		2018/0368584 A1	12/2018	Jewett et al.	
9,345,334 B2	5/2016	Mossbeck et al.		2019/0150629 A1 *	5/2019	Pearce	A47C 27/16
9,427,090 B2	8/2016	Mossbeck et al.		2019/0390025 A1	12/2019	Sakaguchi et al.	
10,357,113 B2	7/2019	Gladney		2023/0127744 A1	4/2023	McGuire et al.	
10,582,793 B1	3/2020	McMahan et al.					
10,807,811 B2	10/2020	Whatcott					
10,881,217 B2 *	1/2021	Moon	A47C 27/053	FOREIGN PATENT DOCUMENTS			
11,317,733 B2	5/2022	Pearce et al.		CN	200976985 Y	11/2007	
11,571,075 B2	2/2023	Stojanovic et al.		CN	101568281 A	10/2009	
11,602,227 B2	3/2023	Moon et al.		CN	201346046 Y	11/2009	
2002/0184712 A1	12/2002	Gladney et al.		CN	102613836 A	8/2012	
2003/0096899 A1	5/2003	Pearce		CN	102802468 A	11/2012	
2003/0135930 A1	7/2003	Varese et al.		CN	202604240 U	12/2012	
2004/0133988 A1 *	7/2004	Barber	A47C 27/064 5/716	CN	204292709 U	4/2015	
				CN	204734212 U	11/2015	
2004/0148706 A1	8/2004	Visser et al.		CN	204838771 U	12/2015	
2004/0226098 A1	11/2004	Pearce		CN	205321883 U	6/2016	
2005/0223667 A1	10/2005	McCann et al.		CN	105747678 A	7/2016	
2006/0030644 A1	2/2006	Hairston et al.		CN	106213886 A	12/2016	
2006/0030645 A1	2/2006	Hairston et al.		CN	206565654 U	10/2017	
2007/0050905 A1 *	3/2007	Fowkes	A47K 3/12 4/579	CN	109793391 A	5/2019	
				EP	2186447 A1	5/2010	
2007/0135878 A1	6/2007	Lachenbruch et al.		GB	2413111 A	10/2005	
2007/0246157 A1	10/2007	Mason et al.		JP	S57201261 U	12/1982	
2007/0261173 A1	11/2007	Schlusless		JP	S6134951 U	3/1986	
2008/0229507 A1	9/2008	Healy		JP	2003235687 A	8/2003	
2009/0013476 A1	1/2009	Rinchetti		JP	2004016341 A	1/2004	
2009/0056030 A1	3/2009	Bolden		JP	2008307120 A	12/2008	
				JP	2010530764 A	9/2010	

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2010284425 A	12/2010
JP	5216250 B2	6/2013
WO	2009048209 A1	4/2009
WO	2011072022 A1	6/2011

OTHER PUBLICATIONS

Springs Creative, "What is Spacer Fabric?" <http://www.springscreative.com/products/spacerfabric>, Jun. 29, 2017.

Apex Mills, Apex Mills Textiles, <http://www.apexmills.com/textile/testile-type/3d-spacers/3/?act=textile>, Jun. 30, 2017.

IP Australia, "Examination Report No. 1," Australian Application No. 2018307218, Jun. 11, 2020.

Canadian Intellectual Property Office, "Commissioner's Notice—Application Found Allowable," Canadian Application No. 3,070,066, Dec. 3, 2021.

Canadian Intellectual Property Office, "Examiner's Report," Canadian Application No. 3,070,066, Apr. 8, 2021.

China National Intellectual Property Administration, "First Office Action," Chinese Application No. 201810800237.6, Sep. 1, 2020.

China National Intellectual Property Administration, "Second Office Action," Chinese Application No. 201810800237.6, May 6, 2021.

European Patent Office, "Supplementary European Search Report," European Application No. 18838906.8, Feb. 12, 2021.

IP Australia, "Notice of grant for patent," Australian Application No. 2018307218, Oct. 7, 2021.

Japan Patent Office, "Notice of Allowance," Japanese Application No. 2020-504409, Oct. 19, 2021.

Japan Patent Office, "Notice of Reasons for Rejection," Japanese Patent Application No. 2020-504409, Mar. 5, 2021.

Korean Intellectual Property Office, "Notice of Allowance," Korean Application No. 10-2020-7003012, May 28, 2021.

Korean Intellectual Property Office, "Reasons for Rejection," Korean Application No. 10-2020-7003012, Nov. 27, 2020.

Taiwan Intellectual Property Office, "Office Action," Taiwan Application No. 107126144, Mar. 18, 2019.

Taiwan Intellectual Property Office, "Office Action," Taiwan Application No. 108126616, Nov. 18, 2021.

USPTO as International Searching Authority, "International Search Report and Written Opinion," International Application No. PCT/US2018/042331, Nov. 26, 2018.

Taiwan Intellectual Property Office, "Office Action," Taiwan Application No. 111128185, Jun. 30, 2023.

Tempur Sealy International, Inc., "Defendants and Counterclaim Plaintiffs Tempur Sealy International, Inc.'s, Sealy Technology LLC's and Sealy Mattress Manufacturing Co., LLC's Preliminary Invalidity Contentions and applicable exhibits," *Purple Innovation, LLC vs. Tempur Sealy International, Inc.*, U.S. District Court for the Middle District of North Carolina, Case No. 1:23-CV-00257-CCE-LPA, Dec. 4, 2023.

Tempur Sealy International, Inc., "Petition for Inter Partes Review of U.S. Pat. No. 11,317,733," *Tempur Sealy International, Inc. v. Purple Innovation, LLC*, USPTO PTAB IPR Case No. 2024-00482, Feb. 14, 2024.

Klancik, Alvin Roy, "Declaration of Alvin Roy Klancik," Exhibit 1006 to "Petition for Inter Partes Review of U.S. Pat. No. 11,317,733," *Tempur Sealy International, Inc. v. Purple Innovation, LLC*, USPTO PTAB IPR Case No. 2024-00482, Feb. 14, 2024.

Storey, Robson F., "Declaration of Robson F. Storey, Ph. D.," Exhibit 1007 to "Petition for Inter Partes Review of U.S. Pat. No. 11,317,733," *Tempur Sealy International, Inc. v. Purple Innovation, LLC*, USPTO PTAB IPR Case No. 2024-00482, Feb. 14, 2024.

Purple Innovation, LLC, "Purple Innovation, LLC's Answer and Affirmative Defenses to Tempur Sealy International, Inc., Sealy Technology LLC, and Sealy Mattress Manufacturing Co., LLC's Counterclaims," Aug. 21, 2023, Exhibit 1011 to "Petition for Inter

Partes Review of U.S. Pat. No. 11,317,733," *Tempur Sealy International, Inc. v. Purple Innovation, LLC*, USPTO PTAB IPR Case No. 2024-00482, Feb. 14, 2024.

Tempur Sealy International, Inc., "Tempur Sealy International, Inc.'s, Sealy Technology LLC's, and Sealy Mattress Manufacturing Co., LLC's Answer, Affirmative Defenses, and Counter Claims," Jul. 31, 2023, Exhibit 1012 to "Petition for Inter Partes Review of U.S. Pat. No. 11,317,733," *Tempur Sealy International, Inc. v. Purple Innovation, LLC*, USPTO PTAB IPR Case No. 2024-00482, Feb. 14, 2024.

Leggett & Platt Bedding Group, "ComfortCore(R)," <https://beddingcomponents.com/comfortcore> [<https://web.archive.org/web/20171022185929/https://beddingcomponents.com/comfortcore>], Oct. 22, 2017, Exhibit 1015 to "Petition for Inter Partes Review of U.S. Pat. No. 11,317,733," *Tempur Sealy International, Inc. v. Purple Innovation, LLC*, USPTO PTAB IPR Case No. 2024-00482, Feb. 14, 2024.

Merriam-Webster, "Definition of innerspring," merriam-webster.com Dictionary, Jan. 2, 2017, <https://www.merriam-webster.com/dictionary/innerspring> [<https://web.archive.org/web/201710102194529/https://www.merriam-webster.com/dictionary/innerspring>], Exhibit 1016 to "Petition for Inter Partes Review of U.S. Pat. No. 11,317,733," *Tempur Sealy International, Inc. v. Purple Innovation, LLC*, USPTO PTAB IPR Case No. 2024-00482, Feb. 14, 2024.

European Sleep Design European Mattress Systems, "Why is your coil fabric polypropylene instead of natural cotton?," <https://www.sleepdesign.com/Why-Is-Your-Coil-Fabric-Polypropylene-Instead-Of-Natural-Cotton>, Jun. 8, 2016, Exhibit 1017 to "Petition for Inter Partes Review of U.S. Pat. No. 11,317,733," *Tempur Sealy International, Inc. v. Purple Innovation, LLC*, USPTO PTAB IPR Case No. 2024-00482, Feb. 14, 2024.

Kushner, Leslie J., "Petitioners Tempur Sealy International, Inc., Sealy Technology, LLC, and Sealy Mattress Manufacturing Co., LLC's Attorney Declaration," Exhibit 1021 to "Petition for Inter Partes Review of U.S. Pat. No. 11,317,733," *Tempur Sealy International, Inc. v. Purple Innovation, LLC*, USPTO PTAB IPR Case No. 2024-00482, Feb. 14, 2024.

Taiwan Intellectual Property Office, "Office Action," Taiwanese Application No. 111128185, Jan. 26, 2024.

Canadian Intellectual Property Office, "Commissioner's Notice—Application Found Allowable," Canadian Application No. 3,084,510, Oct. 17, 2022.

Canadian Intellectual Property Office, "Examiner's Requisition," Canadian Application No. 3,084,510, Feb. 4, 2022.

Canadian Intellectual Property Office, "Examiner's Requisition," Canadian Application No. 3,084,510, Jun. 25, 2021.

China National Intellectual Property Administration, "Third Office Action," Chinese Application No. 201810811684.1, Dec. 30, 2021.

China National Intellectual Property Administration, "Certificate of Patent," Chinese Application No. 201810811684.1, Mar. 10, 2023.

China National Intellectual Property Administration, "Decision on Rejection," Chinese Application No. 201810811684.1, Jul. 4, 2022.

China National Intellectual Property Administration, "Notification of Granting Invention Patent Right," Chinese Application No. 201810811684.1, Dec. 5, 2022.

China National Intellectual Property Administration, "First Office Action," Chinese Application No. 201810811684.1, Sep. 24, 2020.

China National Intellectual Property Administration, "Second Office Action," Chinese Application No. 201810811684.1, Jul. 5, 2021.

European Patent Office as International Searching Authority, International Search Report and Written Opinion, International application No. PCT/US2018/060680, Dec. 20, 2018.

European Patent Office, "Communication Pursuant to Article 94(3) EPC," European Application No. 18812494.5, Nov. 22, 2022.

European Patent Office, "Communication Pursuant to Article 94(3)," European Application No. 18812494.5, May 3, 2021.

European Patent Office, "Communication Under Rule 71(3) EPC," European Application No. 18812494.5, Aug. 18, 2023.

European Patent Office, "Communication Under Rule 71(3) EPC," European Application No. 18812494.5, Jan. 29, 2024.

International Preliminary Report on Patentability, International Application No. PCT/US2018/060680, May 19, 2020.

(56)

References Cited

OTHER PUBLICATIONS

IP Australia, "Examination Report No. 1," Australian Application No. 2018368359, Jan. 20, 2021.

Japan Patent Office, "Notice of Allowance," Japanese Application No. 2020-527078, Jan. 16, 2022.

Japan Patent Office, "Notice of Reasons for Rejection," Japanese Application No. 2020-527078, Aug. 13, 2021.

Korean Intellectual Property Office, "Decision on Rejection," Korean Application No. 10-2020-7016996, Sep. 10, 2021.

Korean Intellectual Property Office, "Notice of Allowance," Korean Application No. 10-2020-7016996, Apr. 22, 2022.

Tempur Sealy International, LLC, et al., Images Showing a Scrim Fabric on a Gel Cushioning Element from a Purple Mattress (circa 2015, provided to Applicant's counsel on Jul. 31, 2023).

Taiwan Intellectual Property Office, "Notice of Allowance," Taiwanese Patent Application No. 111128185, May 20, 2024.

European Patent Office, "Communication pursuant to Article 94(3) EPC," European Patent Application No. 18 838 906.8, Jul. 5, 2024.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4

1

MATTRESSES INCLUDING GEL CUSHIONS OVER COILS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/142,147, filed on Jan. 5, 2021 and titled MATTRESSES INCLUDING SPACER FABRIC AND RELATED METHODS (“the ’147 Application”), now U.S. Pat. No. 11,602,227, issued Mar. 14, 2023, which is a continuation of U.S. patent application Ser. No. 15/662,934, filed on Jul. 28, 2017 and titled MATTRESSES INCLUDING SPACER FABRIC AND RELATED METHODS (“the ’934 Application”), now U.S. Pat. No. 10,881,217, issued Jan. 5, 2021. The entire disclosures of the ’147 Application and the ’934 Application are hereby incorporated herein.

TECHNICAL FIELD

Embodiments of the disclosure relate generally to cushioning elements such as mattresses including spacer fabrics, and to methods of making such mattresses.

BACKGROUND

Cushioning materials have a variety of uses, such as for mattresses, seating surfaces, shoe inserts, packaging, medical devices, etc. Cushioning materials may be formulated and/or configured to reduce peak pressure on a cushioned body, which may increase comfort for humans or animals, and may protect objects from damage. Cushioning materials may be formed of materials that deflect or deform under load, such as polyethylene or polyurethane foams (e.g., convoluted foam), vinyl, rubber, springs, natural or synthetic fibers, fluid-filled flexible containers, etc. Different cushioning materials may have different responses to a given pressure, and some materials may be well suited to different applications. Cushioning materials may be used in combination with one another to achieve selected properties. For example, mattresses may include pocketed coils in combination with layers of foam, elastomer gels, etc. in order to achieve desired results in the cushioning materials.

In mattresses, springs (e.g., coil springs) may be preferable to foam for their durability and ability to withstand compression. Springs may also impart a feel that may be more desirable to users than that of foam. Despite these advantages, springs may not provide a positive aesthetic and/or tactile experience if they are seen or felt through side panels of the mattress, prompting manufacturers to conceal the feel of springs on the sides of mattresses. One solution includes a wire frame around the edge of the mattress to provide structure to a cover of the mattress. However, the metal of the wire frame may be felt through the cover of the mattress. In addition, such a wire frame may not be particularly suited to handle compression during use and to packing mattresses for shipping and/or storage, such as direct-to-consumer mattresses that are shipped in logs, boxes, etc.

An alternative to conceal the feel and/or visual appearance of springs may be to encase the springs in a foam layer around the perimeter of an inner core of the mattress. While the foam layer may mask the feel of the springs, variations in chemistry and/or manufacturing of the foam may affect quality. In addition, the foam layer may be more susceptible to compression over time due to the foam deteriorating more rapidly than springs. Further, foam encasements may bulge and/or fold during use toward a user’s legs, creating both a

2

gap between the materials as well as an undesirable feel along the side panel of the mattress. Alternatively, manufacturers have utilized thicker and/or stiffer side paneling on mattress covers to conceal the feel of springs. However, such side paneling may not entirely cover the springs and may be aesthetically and/or texturally undesirable.

SUMMARY

In some embodiments, a mattress assembly may include a base core layer and an inner core located over the base core layer. The inner core may include coil springs. The mattress assembly may also include a side panel assembly located around at least a portion of a perimeter of the inner core. The side panel assembly may include a spacer fabric located over and extending transverse to the base core layer. The spacer fabric may include a first knit layer, a second knit layer, and an inner fibrous material located therebetween.

In other embodiments, a mattress assembly may include a base core layer and an inner core located over the base core layer, the inner core comprising one or more coil springs. The mattress assembly may also include a side panel assembly located around at least a portion of a lateral perimeter of the inner core. The side panel assembly may include a spacer fabric including a first knit layer, a second knit layer, and an inner fibrous material between the first knit layer and the second knit layer.

In further embodiments, a method of forming a mattress assembly may include providing a base core layer as a substrate for a mattress and disposing a plurality of coil springs positioned within individual casings in an inner core located over the base core layer. The method may include disposing a spacer fabric around a perimeter of the inner core. The spacer fabric may define at least a portion of a side panel assembly of the mattress and the spacer fabric may be positioned over the base core layer. The spacer fabric may include a first knit layer, a second knit layer, and an inner fibrous material located therebetween.

BRIEF DESCRIPTION OF THE DRAWINGS

While the specification concludes with claims particularly pointing out and distinctly claiming what are regarded as embodiments of the present disclosure, various features and advantages of embodiments of the disclosure may be more readily ascertained from the following description of example embodiments of the disclosure when read in conjunction with the accompanying drawings, in which:

FIG. 1 is a top perspective view of a mattress assembly according to the present disclosure;

FIG. 2 is an end view illustrating a portion of the mattress assembly shown in FIG. 1 including a spacer fabric coupled with other cushioning elements;

FIG. 3 is a cross-sectional side view illustrating a portion of the mattress assembly shown in FIG. 1; and

FIG. 4 is a cross-sectional top view illustrating a portion of the mattress assembly shown in FIG. 1.

DETAILED DESCRIPTION

The following description provides specific details, such as material types, manufacturing processes, uses, and structures in order to provide a thorough description of embodiments of the disclosure. However, a person of ordinary skill in the art will understand that the embodiments of the disclosure may be practiced without employing these specific details. Indeed, the embodiments of the disclosure may

be practiced in conjunction with conventional manufacturing techniques and materials employed in the industry.

In the following detailed description, reference is made to the accompanying drawings, which form a part hereof, and in which is shown, by way of illustration, specific embodiments in which the disclosure may be practiced. These embodiments are described in sufficient detail to enable a person of ordinary skill in the art to practice the disclosure. However, other embodiments may be utilized, and structural, procedural, and other changes may be made without departing from the scope of the disclosure. The illustrations presented herein are not meant to be actual views of any particular system, device, structure, or process, but are idealized representations that are employed to describe the embodiments of the disclosure. The drawings presented herein are not necessarily drawn to scale. Similar structures or components in the various drawings may retain the same or similar numbering for the convenience of the reader; however, the similarity in numbering does not mean that the structures or components are necessarily identical in size, composition, configuration, or other property.

As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

As used herein, the term “substantially” in reference to a given parameter, property, or condition means and includes to a degree that one skilled in the art would understand that the given parameter, property, or condition is met with a small degree of variance, such as within acceptable manufacturing tolerances. For example, a parameter that is substantially met may be at least about 90% met, at least about 95% met, or even at least about 99% met.

As used herein, any relational term, such as “first,” “second,” “top,” “bottom,” “upper,” “lower,” “front,” “back,” “above,” “below,” “horizontal,” “vertical,” “over,” “on,” etc., is used for clarity, consistency of terminology, and convenience in understanding the disclosure and accompanying drawings and does not connote or depend on any specific preference, orientation, or order, except where the context clearly indicates otherwise. For example, the disclosure includes cushioning elements (e.g., mattresses) that may be rotated or flipped in use such that the top thereof faces down and the bottom thereof faces up, and/or the front faces away from the user and the back faces toward the user. Thus, while one example orientation of mattresses is used herein for clarity, other possible orientations are contemplated by and included in the disclosure.

As used herein, the term “cushioning element” means and includes any deformable device intended for use in cushioning one body (e.g., a person, animal, or object) relative to another. As a non-limiting example, cushioning elements (e.g., mattresses, mattress toppers, seat cushions, etc.) include materials intended for use in cushioning a person, animal, or object relative to another object (e.g., a chair seat) that might otherwise abut against the person, animal or object.

As used herein, the term “elastomeric material” means and includes elastomeric polymers and mixtures of elastomeric polymers with plasticizers and/or other materials. Elastomeric materials are elastic (i.e., capable of recovering size and shape after deformation). Elastomeric materials include, without limitation, materials referred to in the art as “elastomeric cushion members,” “elastomer gels,” “gelatinous elastomers,” or simply “gels.”

In some embodiments, a spacer fabric may include material having two separate fabrics, joined by microfilament yarn, to create a breathable, 3D “microclimate” between layers. Spacer fabrics may include uncut pile fabrics includ-

ing at least two layers of fabric knitted independently that are interconnected by a separate spacer yarn.

In some embodiments, a knitted or knit material may include a fabric formed by interlocking loops of threads or yarns. Such knitted fabrics may be porous and stretchable even when formed of non-stretchable fibers, because the threads can shift within a matrix of loops.

The illustrations presented herein are not actual views of any particular material or device, but are merely idealized representations employed to describe embodiments of the present disclosure. Elements common between figures may retain the same numerical designation.

Embodiments of the present disclosure describes mattresses including a spacer fabric (i.e., 3D fabric having multiple layers of varying materials in a sandwiched configuration) located in and/or defining a side panel assembly thereof. The spacer fabric can be of a sufficient thickness and having suitable compressive properties (e.g., resilience and/or resistance) for providing some cushioning effect when used in conjunction with a mattress, mattress topper, or other cushioning element having side panels. The spacer fabric may alleviate problems associated with cushioning materials (e.g., springs) being felt or seen through the side panels of the mattress. In particular, the spacer fabric located in the side panel assembly may reduce local buckling toward a user's legs during use, and thus a mattress utilizing such spacer fabric may be more comfortable and/or visually attractive to the user. In addition, use of the spacer fabric in the side panel assembly of a mattress as disclosed herein may allow compression in a particular direction (e.g., vertical) in order to facilitate packing of the mattress for shipping and/or storage.

FIG. 1 shows a top perspective view of a mattress assembly **100**. For ease of illustration, the mattress assembly **100** of FIG. 1 is shown in a cutaway view in which various portions of the cushioning materials have been removed to reveal internal components thereof. The mattress assembly **100** may include a base core layer **102** having generally planar top and bottom surfaces and a side panel assembly **104** located over (e.g., on, above, directly over) and extending in a plane generally transverse (e.g., perpendicular) to the base core layer **102** (e.g., extending around the lateral or horizontal sides of the mattress assembly **100**). The base core layer **102** may be formed of a polyurethane foam, for example, although other foams may be utilized. The side panel assembly **104** may include a spacer fabric **106**, which may be located proximate (e.g., at or near) an outer perimeter of the base core layer **102**. The base core layer **102** may also support one or more coil springs **108**. Individual coil springs **108** (e.g., steel coils) may be encased in respective casings **110** (e.g., polypropylene socks) in which the casings **110** may form a pocket for each of the individual coil springs **108**, commonly referred to as “pocketed coils.” Individual casings **110** including respective coil springs **108** may be positioned proximate one another and may be located within an inner core **111** of the mattress assembly **100**. The coil springs **108** may be aligned vertically (i.e., generally transverse to the base core layer **102**) to provide cushioning support. In some embodiments, the casings **110** including the coil springs **108** may be further configured (e.g., encased, joined, etc.) to function as a single body in the inner core **111**. An upper foam layer **112** having generally planar top and bottom surfaces may be located over the inner core **111** and thus over upper ends of the casings **110** including the coil springs **108**. In some embodiments, a lower surface of the upper foam layer **112** may be located in direct physical contact with an upper surface of the casings **110**. In some

5

embodiments, the upper foam layer **112** may be located over and at least partially extended over an upper surface of the spacer fabric **106**. The upper foam layer **112** may or may not be attached or adhered (e.g., sewn, glued, etc.) to the spacer fabric **106**.

The spacer fabric **106** may include a spacer layer and, in some embodiments, may be utilized to transport moisture vapor and heat away while allowing air flow in addition to providing cushioning support. For example, the spacer fabric **106** may include at least two adjacently stacked layers of three-dimensional material. In some embodiments, the spacer fabric **106** may include a non-crush, three-dimensional (3D) fabric, such as a knit, cloth, polymeric film, foam, and extruded woven fibers. Further, the spacer fabric **106** may include a material having fibers having lateral flexibility for reducing shear forces by providing a degree of lateral flexing during movement. For example, materials of the spacer fabric **106** may be configured to facilitate bending and transverse movement thereof while resisting applied forces in a direction normal to the spacer fabric **106**. The spacer fabric **106** may include such 3D materials (e.g., AIRSKIN® spacer fabrics) commercially available through Springs Creative Products Group, LLC of Rock Hill, SC, to provide cushioning support in at least a portion of the side panel assembly **104**.

As shown in FIG. 1, one or more elastomeric cushion members **116** may be located over an upper surface of the upper foam layer **112**. The elastomeric cushion member **116** may include a flexible, resilient, gel cushioning media having shape memory. Such gels may be used for cushioning and/or temperature management. Gels may provide cushioning because the gels may hydrostatically flow to the shape of a cushioned object and may tend to relieve pressure peaks and/or gels may reduce stresses from shear. For example, the elastomeric material may increase comfort for a user of the cushioning elements, or may decrease resistance to shear forces which can in turn help prevent decubitus ulcers in medical patients. Such elastomeric cushion members **116** are summarized in U.S. Pat. No. 8,784,982, issued Jul. 22, 2014 to Pearce et al., the disclosure of which is incorporated herein in its entirety by this reference. In addition, the elastomeric cushion members **116** may include interconnected buckling walls summarized in U.S. Pat. No. 8,919,750, issued Dec. 30, 2014 to Pearce et al., which is assigned to the Assignee of the present disclosure, the disclosure of which is incorporated herein in its entirety by this reference.

The elastomeric cushion member **116** may include a stabilizing material **114** on at least a bottom surface thereof. The stabilizing material **114** may include a relatively thin material (e.g., cotton spandex “scrim”) and may be used to provide a surface for adhering (e.g., gluing) the elastomeric cushion member **116** to surrounding materials, such as another elastomeric cushion member **116** and/or an upper surface of the upper foam layer **112**. In some embodiments, the stabilizing material **114** may comprise a scrim fabric (e.g., a woven or non-woven fabric material) and portions of the elastomeric cushion member **116** may seep through (e.g., be melt-fused into, bleed through, push through, leak through, pass through, etc.) the scrim fabric of the stabilizing material **114**. For example, when the elastomeric cushion member **116** includes a gel material, portions of the gel material may be heat fused through the stabilizing material **114**. The portions of the elastomeric cushion member **116** that extend through the scrim fabric of the stabilizing material **114** may create a non-slip surface or reduced slip surface on a lower surface of the stabilizing material **114**

6

(e.g., surface that would contact an upper surface of the upper foam layer **112**). The non-slip surface or reduced slip surface created by the elastomeric cushion member **116** may help the cushioning materials stay in place relative to one another.

The mattress assembly **100** may also include an optional top layer **118** over an upper surface of the elastomeric cushion member **116**. The optional top layer **118** may include, for example, a breathable material (e.g., a material comprising foam or batting fiber). A cover **120** may be located over an upper surface of the optional top layer **118** or, alternatively, over an upper surface of the elastomeric cushion member **116** and/or the upper foam layer **112**. In some embodiments, the cover **120** may include a single continuous sheet of material extending over upper surfaces, under bottom surfaces, and around side surfaces of the mattress assembly **100**. In other words, the cover **120** may fully encase each of the layers and/or materials within the mattress assembly **100**. In other embodiments, the cover **120** may include individual panels or portions that have been joined in order to provide an outer protective covering for at least a portion of the mattress assembly **100**.

FIG. 2 is an end view illustrating a portion of the mattress assembly **100** including the side panel assembly **104**. The end view of FIG. 2 may represent a portion of any one of side surfaces of the mattress assembly **100**. A side surface may include a surface disposed along lateral sides (e.g., around a periphery of the mattress) and ends of the mattress assembly **100** that are normally in a substantially vertical orientation during use. The side panel assembly **104** may include the spacer fabric **106** located between the base core layer **102** and the upper foam layer **112** in order to conceal and/or protect components of the inner core **111** (not shown) of the mattress assembly **100**. As shown in FIG. 2, the spacer fabric **106** may be located proximate (e.g., at or near) a perimeter of each of the base core layer **102** and the upper foam layer **112** in which each of the base core layer **102** and the upper foam layer **112** may be in direct physical contact with the spacer fabric **106**. In some embodiments, the spacer fabric **106** may be positioned between the inner core **111** and the cover **120** (FIG. 1) and may be in direct physical contact with (e.g., encased only by) the cover **120**. In other embodiments, an additional layer of material may be located between the spacer material **106** and the cover **120**.

In some embodiments, each of the base core layer **102**, the spacer fabric **106**, the upper foam layer **112**, and the elastomeric cushion member **116** may be sized and positioned such that outer vertical edges thereof define an outer wall of the side panel assembly **104**. In such a configuration, an outer portion of the spacer fabric **106** may be substantially aligned with an outer end surface of each of the base core layer **102** and the upper foam layer **112**, defining, in part, the outer wall of the side panel assembly **104**, and thus providing sidewall structure for the mattress assembly **100**. For example, a lower surface of the spacer fabric **106** may abut the upper surface of the base core layer **102** and an upper surface of the spacer fabric **106** may abut the lower surface of the upper foam layer **112**. In other embodiments, each of the base core layer **102**, the upper foam layer **112**, and the elastomeric cushion member **116** may be sized and positioned such that outer vertical edges thereof are internal to the outer wall of the side panel assembly **104** by a distance substantially equal to a thickness of the spacer fabric **106**. In such a configuration, the spacer fabric **106** may extend from a top to a bottom of the side panel assembly **104** in which the spacer fabric **106** alone defines an outer wall of the side panel assembly **104**.

The spacer fabric **106** may be coupled with other cushioning elements of the mattress assembly **100** in which the spacer fabric **106** may be attached or adhered to surrounding materials utilizing adhesives, thermal bonding, or mechanical fasteners. For example, the spacer fabric **106** may be attached to surrounding cushioning materials using hog rings, zippers, stitching and/or sewing, pockets, staples, buttons, heat fusing, etc. In addition, the spacer fabric **106** may be adhered to surrounding cushioning materials using glue (hot glue, water-based glue, etc.), hook-and-loop adhesives, or other such adhesive materials. In some embodiments, a lower surface of the spacer fabric **106** may be attached or adhered to an upper surface **121** of the base core layer **102** and/or an upper surface of the spacer fabric **106** may be adhered to a lower surface **122** of the upper foam layer **112**. In other embodiments, the spacer fabric **106** may not be attached or adhered to either of the base core layer **102** or the upper foam layer **112**, but may remain free to move relative thereto. For example, the spacer fabric **106** may be free floating and may rely on tension between the cover **120** and the inner core **111** (FIG. 1) to hold the spacer fabric **106** in place. In some embodiments, the spacer fabric **106** may be sewn into the side paneling of the cover **120** so as to form a part thereof. In yet other embodiments, the spacer fabric **106** may be attached to one or more elements of the inner core **111** of the mattress assembly **100** as described in greater detail below. Further, the spacer fabric **106** may be attached at multiple locations using a combination of attachment and/or adherence articles. When the mattress assembly **100** is subjected to a process involving compression, packing, and decompression, the spacer fabric **106** may bulge or decompress in an unsatisfactory manner. For example, if the spacer fabric **106** is only attached on the top and bottom, the spacer fabric **106** may bulge in the middle when unpacked and/or the spacer fabric **106** may bulge in the middle during use. Alternatively, if the spacer fabric **106** is only attached in the middle, the top and bottom may flare out. Therefore, the spacer fabric **106** may be attached or adhered at strategic locations to ensure satisfactory performance and aesthetics, such as in the middle, as well as at the top and bottom thereof. It may be appreciated that other configurations for attachment may be employed.

The spacer fabric **106** may be wrapped along any one or all four vertical sides of the mattress assembly **100** defining an outer lateral periphery of the mattress assembly **100**. In some embodiments, the spacer fabric **106** may be wrapped around the four vertical sides of the mattress assembly **100** in a single continuous piece of fabric. In such a configuration, the spacer fabric **106** may be aligned vertically along at least a portion of the side panel assembly **104** without being aligned horizontally among other cushioning elements of the mattress assembly **100**. In other embodiments, the spacer fabric **106** may be wrapped under a lower surface of the base core layer **102** and upward along each of the four vertical sides so as to form a "bucket." It may be appreciated that the spacer fabric **106** may be applied to or within the mattress assembly **100** in any configuration to facilitate coverage of selected portions and/or an entirety of the vertical sides thereof. In some embodiments, the spacer fabric **106** may be utilized in the side panel assembly **104** along an entire vertical side (i.e., top to bottom) of the mattress assembly **100** as described in greater detail above. In other embodiments, the spacer fabric **106** may not extend from the top to the bottom of the mattress assembly **100**, but may only extend along a portion of the side panel assembly **104**. In such an embodiment, the spacer fabric **106** may be located to cover at least a portion of a designated area, such

as to cover at least a portion of the inner core **111** containing the coil springs **108** within the casings **110**.

As shown in FIG. 2, one or more (e.g., two) elastomeric cushion members **116** may be located over the upper foam layer **112**. As described in greater detail above, the stabilizing material **114** may be located on a bottom surface of each of the elastomeric cushion members **116**. In this manner, the stabilizing material **114** may be utilized as a stable surface with which to attach or adhere the elastomeric cushion members **116** to one another and/or to an upper surface of the upper foam layer **112**. In some embodiments, the elastomeric cushion members **116** may include a single elastomeric cushion member **116** of a selected thickness in which the thickness thereof may be selected for specific cushioning support. For example, the thickness of the elastomeric cushion member **116** may be selected based at least in part by the size of the mattress assembly **100**. By way of non-limiting example, the elastomeric cushion members **116** may have a thickness (e.g., vertical height) of about 2 in (0.0508 m), 3 in (0.0762 m), or 4 in (0.1016 m), which thickness may be dependent in part on the size of the mattress assembly **100** along with desired cushioning properties thereof. The optional top layer **118** may be located over an upper surface of an uppermost elastomeric cushion member **116** and the cover **120** (FIG. 1) may be located over the optional top layer **118** and/or surrounding at least a portion of the mattress assembly **100**.

In order to accommodate differing size requirements (e.g., king, queen, full, single, etc.) of the mattress assembly **100** and/or for desired cushioning properties thereof, the size, thickness and stiffness of cushioning materials may be adjusted. In some embodiments, the base core layer **102** may include a foam layer (e.g., high resilience flexible polyurethane foam) having a thickness between about 0.5 in and 2 in. By way of non-limiting example, the base core layer **102** may have a thickness of about 1 in. In some embodiments, the base core layer **102** may have a bulk foam density of about 2.0 lbs/in² and may have an Indentation Force Deflection (IFD) between about 40 lbs/50 in² and 70 lbs/50 in². Indentation Force Deflection (IFD) is defined as a force required to compress 50 in² of a 20 in by 20 in by 4 in sample by 25%, as measured in accordance with ASTM Standard D3574 (Standard Test Methods for Flexible Cellular Materials—Slab, Bonded, and Molded Urethane Foams, ASTM Int'l, West Conshohocken, PA, 2011). By way of non-limiting example, the IFD of the base core layer **102** may be about 55 lbs/50 in². In addition, the spacer fabric **106** may have vertical height of between about 6 in and 9 in. By way of non-limiting example, the spacer fabric **106** may have a vertical height of about 7.5 in. In some embodiments, the upper foam layer **112** may include a foam layer (e.g., high resilience flexible polyurethane foam) having a thickness between about 0.25 in and 1 in. By way of non-limiting example, the upper foam layer **112** may have a thickness of about 0.5 in. In some embodiments, the upper foam layer **112** may have a bulk foam density of about 2.0 lbs/in² and may have an IFD between about 10 lbs/50 in² and about 40 lbs/50 in². By way of non-limiting example, the IFD of the upper foam layer **112** may be about 18 lbs/50 in².

The elastomeric cushion member **116** may include one or more layers of an elastomer gel material (e.g., a flexible, resilient, gel cushioning media having shape memory) having a thickness of about 2 in (0.0508 m), 3 in (0.0762 m), or 4 in (0.1016 m). Further, in order to accommodate size requirements and/or to achieve a particular look or feel of the mattress assembly **100**, the size of the spacer fabric **106**, including the stiffness of the micro-filaments, the yarn

crimp, the weave or knit, as well as the volume fraction in the spacer fabric **106** may be adjusted. As understood by those of ordinary skill in the art, the durometer (hardness) of such fabric may be controlled by thickness and density of the internal fibers, and the density of the outer layers being connected by such internal fibers. By way of non-limiting example, the spacer fabric **106** may have a material density of about 1200 grams per square meter (g/m^2).

EXAMPLES

Example 1

A queen mattress having a side panel height of about 10 in may include the base core layer **102** (e.g., conventional foam) having a thickness of about 1 in, a density of about 1.8 lb/ft.^3 , and an IFD of about 55 lbs/50 in^2 . The 10 in queen mattress may include the inner core **111** having a height of about 6.5 in, the upper foam layer **112** (e.g., conventional foam) having a thickness of about 0.5 in, a density of about 1.8 lb/ft.^3 , and an IFD of about 18 lbs/50 in^2 , and the elastomeric cushion member **116** having a height of about 2 in in either full coverage (i.e., edge to edge) or in two 25 in by 56 in pieces while leaving a perimeter free of the elastomeric cushion member **116**. In some embodiments, the perimeter may include a foam layer (e.g., conventional foam) having a thickness of about 1.95 in, a density of about 1.8 lb/ft.^3 , and an IFD of about 18 lbs/50 in^2 . The lateral distance of the foam perimeter may be between about 3 in to about 9 in.

Example 2

A queen mattress having a side panel height of about 12 in may include the base core layer **102** having a thickness of about 1 in, a density of about 1.8 lb/ft.^3 , and an IFD of about 55 lbs/50 in^2 . The 12 in queen mattress may include the inner core **111** having a height of about 7.5 in the upper foam layer **112** having a thickness of about 0.5 in, a density of about 1.8 lb/ft.^3 , and an IFD of about 18 lbs/50 in^2 , and the elastomeric cushion member **116** having a height of about 3 in in full coverage.

Example 3

A queen mattress having a side panel height of about 14 in may include the base core layer **102** having a thickness of about 1 in, a density of about 1.8 lb/ft.^3 , and an IFD of about 55 lbs/50 in^2 . The 14 in queen mattress may include the inner core **111** having a height of about 8.5 in, the upper foam layer **112** having a thickness of about 0.5 in, a density of about 1.8 lb/ft.^3 , and an IFD of about 18 lbs/50 in^2 , and the elastomeric cushion member **116** having a height of about 4 in in full coverage.

FIG. 3 is a cross-sectional side view illustrating a portion of the mattress assembly **100** including the spacer fabric **106**. The spacer fabric **106** may include a first knit layer **106a**, an inner fibrous material **106b**, and a second knit layer **106c**. The first knit layer **106a** and the second knit layer **106c** may be generally aligned (e.g., perpendicular) with one another to support the inner fibrous material **106b** located (e.g., sewn) therebetween. As shown in FIG. 3, the first knit layer **106a** may be located proximate the outermost edge of the mattress assembly **100**. In other words, the first knit layer **106a** may define at least a portion of the outer boundary of the side panel assembly **104** and, thus, be located proximate (e.g., at) an outer boundary of the mattress assembly **100**,

and may further lack cushioning materials (e.g., foam material) in a region between the spacer fabric **106** and the cover **120** (FIG. 1). The second knit layer **106c** may be located inward from the outer boundary of the mattress assembly **100** and may be located proximate (e.g., at a boundary of) the inner core **111** of the mattress assembly **100**. Further, the second knit layer **106c** may be proximate to (e.g., in direct physical contact with) an outer surface of the outermost casings **110** including the coil springs **108** and may lack cushioning materials (e.g., foam) between the spacer fabric **106** and the inner core **111** including the casings **110** and the coil springs **108**.

Portions of the spacer fabric **106** may be attached or adhered to surrounding cushioning materials of the mattress assembly **100**. In some embodiments, portions of the spacer fabric **106** (e.g., the second knit layer **106c**) may be attached or adhered to the outer surface of the casings **110** and/or the coil springs **108**. For example, at least a portion of the second knit layer **106c** and/or at least a portion of the inner fibrous material **106b** may be coupled to a rung of the outermost coil spring **108**. By way of non-limiting example, the spacer fabric **106** may be coupled to the rung of the outermost coil spring **108** using fasteners **130**. In some embodiments, fasteners **130** (e.g., hog rings) are only attached or attached primarily to the second knit layer **106c** of the spacer fabric **106** so as to prevent unnecessary divots and/or indentations along the side panel assembly **104** that would be caused by the fastener **130** pulling an outside edge of the spacer fabric **106** inward. In other embodiments, the fasteners **130** may be attached or adhered (e.g., sewn, glued, heat fused, etc.) to other surrounding materials, such as the base core layer **102**, the casings **110**, and/or the upper foam layer **112**, for example.

FIG. 4 is a cross-sectional top view illustrating a portion of the mattress assembly **100**. An upper end view of the casings **110** including the coil springs **108** is depicted from looking downward toward the base core layer **102**. The casings **110** including the coil springs **108** may be located within the inner core **111** of the mattress assembly **100** as described in greater detail with reference to FIG. 1. The spacer fabric **106** includes the first knit layer **106a** and the second knit layer **106c** having the inner fibrous material **106b** therebetween. In some embodiments, portions of the spacer fabric **106** (e.g., the second knit layer **106c**) may be attached or adhered to the outer surface of the casings **110** and/or the coil springs **108**. For example, the fasteners **130** may extend through at least a portion of the second knit layer **106c** and/or at least a portion of the inner fibrous material **106b**, through at least a portion of the casings **110**, and coupled to a rung of the outermost coil spring **108**. By way of non-limiting example, the spacer fabric **106** may be coupled to the rung of the outermost coil spring **108** using the fasteners **130** (e.g., hog rings). In other embodiments, at least a portion of the spacer fabric **106** may be adhered (e.g., sewn, glued, etc.) to surrounding materials, such as the casings **110**, for example.

In some embodiments, the spacer fabric **106** may be formulated such that the spacer fabric **106** is more readily compressible in a direction that is generally transverse (e.g., perpendicular) to threads of the inner fibrous material **106b**. For example, the spacer fabric **106** may be relatively more compressible along a first axis (e.g., vertical axis) than that of a second axis and a third axis (e.g., horizontal axes), which axes are located generally transverse (e.g., perpendicular) to the first axis. In other words, the spacer fabric **106** may be configured and positioned to exhibit a first elasticity along the first axis (e.g., vertical axis) having a relatively

11

greater elasticity (e.g., modulus of elasticity) than that of a second and third elasticity along each of the second axis and the third axis. In this manner, the mattress assembly **100** including the side panel assembly **104** may allow deformation (e.g., compression) in a designated direction (e.g., vertical direction) in order to facilitate packing of the mattress assembly **100** for shipping and/or storage. Such relative elasticity properties may be determined by an inherent knitted pattern in each of the first knit layer **106a** and the second knit layer **106c**. For example, each of the first knit layer **106a** and the second knit layer **106c** may include a knitted pattern having an increased elasticity (e.g., a lower relative stiffness, more susceptible to buckling) along the first axis (e.g., vertical axis) while having a reduced elasticity (e.g., a higher relative stiffness, less susceptible to buckling) along the second axis (e.g., lateral). In such an embodiment, the fibers of the inner fibrous material **106b** are disposed along the third axis (e.g., lateral axis) extending from the outermost edge of the side panel assembly **104** inward toward the inner core **111** thereof. In some embodiments, the compressibility (e.g., decrease of an initial thickness due to an increase of compressive force) of the spacer fabric **106** along the first axis may be greater than the compressibility of the spacer fabric **106** along the second axis, which in turn is greater than the compressibility of the spacer fabric **106** along the third axis (i.e., aligned with the fibers of the inner fibrous material **106b**) in order to facilitate compression of the mattress assembly **100**. Upon delivery and use thereof, the mattress assembly **100** may be decompressed and restored to a full extent (e.g., may recover from an elastic deformation). In such an embodiment, the spacer fabric **106** may be configured to be decompressed and restored to a full extent without deforming or harming the cushioning materials thereof. Thus, foam products may be reduced (e.g., minimized or eliminated) in the side panel assembly **104** to facilitate compressibility during shipping and/or storing while providing a positive aesthetic and/or tactile experience during use.

Additional non-limiting example embodiments of the disclosure are described below.

Embodiment 1: A mattress assembly, comprising: a base core layer; an inner core located over the base core layer, the inner core comprising coil springs; and a side panel assembly located around at least a portion of a perimeter of the inner core, the side panel assembly comprising a spacer fabric located over and extending transverse to the base core layer, wherein the spacer fabric comprises a first knit layer, a second knit layer, and an inner fibrous material located therebetween.

Embodiment 2: The mattress assembly of Embodiment 1, further comprising: at least one elastomeric cushion member located over the inner core; and a stabilizing material located on a lower surface of the at least one elastomeric cushion member.

Embodiment 3: The mattress assembly of Embodiment 2, wherein the stabilizing material comprises a thin material comprising cotton spandex adhered to the lower surface of the at least one elastomeric cushion member.

Embodiment 4: The mattress assembly of Embodiment 2, further comprising: an upper foam layer located between the inner core and the at least one elastomeric cushion member; a cover located over the upper foam layer, the cover disposed around at least a portion of the side panel assembly; and a top layer located between an upper surface of an uppermost elastomeric cushion member and the cover.

Embodiment 5: The mattress assembly of Embodiment 4, wherein a lower surface of the spacer fabric abuts an upper

12

surface of the base core layer and an upper surface of the spacer fabric abuts a lower surface of the upper foam layer.

Embodiment 6: The mattress assembly of Embodiment 5, wherein a region located between the upper surface of the base core layer and the lower surface of the upper foam layer is substantially free of foam material.

Embodiment 7: The mattress assembly of Embodiment 4, wherein an outer surface of each of the base core layer, the spacer fabric, the upper foam layer, and the at least one elastomeric cushion member defines an outer surface of the mattress assembly.

Embodiment 8: The mattress assembly of Embodiment 4, further comprising fasteners coupled between the spacer fabric and at least one of the base core layer, the coil springs, or the upper foam layer, wherein the fasteners comprise at least one of hog rings, zippers, stitching, sewing, pockets, staples, buttons, heat fusing, or adhesives.

Embodiment 9: The mattress assembly of Embodiment 4, wherein the spacer fabric is sewn into a side paneling of the cover.

Embodiment 10: A mattress assembly, comprising: a base core layer; an inner core located over the base core layer, the inner core comprising at least one coil spring; and a side panel assembly located around at least a portion of a lateral perimeter of the inner core, the side panel assembly comprising a spacer fabric including a first knit layer, a second knit layer, and an inner fibrous material between the first knit layer and the second knit layer.

Embodiment 11: The mattress assembly of Embodiment 10, further comprising at least one elastomeric cushion member located over the inner core.

Embodiment 12: The mattress assembly of Embodiment 11, wherein the spacer fabric extends from a location proximate a lower surface of the base core layer to a location proximate an upper surface of an uppermost elastomeric cushion member such that an outer surface of the spacer fabric defines an entire outer lateral surface of the side panel assembly.

Embodiment 13: The mattress assembly of Embodiment 10, wherein: each of the first knit layer and the second knit layer of the spacer fabric comprises at least one of a knit, a cloth, or a polymeric film; and the inner fibrous material comprises extruded woven fibers.

Embodiment 14: The mattress assembly of Embodiment 13, wherein each of the first knit layer and the second knit layer comprises a greater elasticity along a vertical axis of the side panel assembly relative to an elasticity along a lateral axis of the side panel assembly, transverse to the vertical axis.

Embodiment 15: The mattress assembly of Embodiment 11, wherein the at least one elastomeric cushion member comprises interconnected buckling walls.

Embodiment 16: A method of forming a mattress assembly, comprising: providing a base core layer as a substrate for a mattress; disposing a plurality of coil springs positioned within individual casings in an inner core located over the base core layer; and disposing a spacer fabric around at least a portion of a perimeter of the inner core, the spacer fabric defining at least a portion of a side panel assembly of the mattress, the spacer fabric positioned over the base core layer, wherein the spacer fabric comprises a first knit layer, a second knit layer, and an inner fibrous material located therebetween.

Embodiment 17: The method of Embodiment 16, further comprising: disposing at least one elastomeric cushion

13

member over the inner core; and disposing an upper foam layer between the inner core and the at least one elastomeric cushion member.

Embodiment 18: The method of Embodiment 17, further comprising: adhering a thin stabilizing material to a lower surface of the at least one elastomeric cushion member; and adhering a lower surface of the thin stabilizing material to an upper surface of the upper foam layer.

Embodiment 19: The method of Embodiment 17, wherein disposing the spacer fabric around the perimeter of the inner core comprises abutting a lower surface of the spacer fabric against an upper surface of the base core layer and abutting an upper surface of the spacer fabric against a lower surface of the upper foam layer, a thickness of the spacer fabric being substantially equal to a distance that each of the base core layer, the spacer fabric, the upper foam layer, and the at least one elastomeric cushion member extend beyond the inner core.

Embodiment 20: The method of Embodiment 19, wherein disposing the spacer fabric around the perimeter of the inner core further comprises positioning the spacer fabric such that materials thereof exhibit a first compressibility along a vertical axis of the mattress having a relatively greater compressibility than that of a second compressibility along a first horizontal axis of the mattress, transverse to the vertical axis, and a third compressibility along a second horizontal axis of the mattress, transverse to the vertical axis and the first horizontal axis.

While the present disclosure has been described herein with respect to certain illustrated embodiments, those of ordinary skill in the art will recognize and appreciate that it is not so limited. Rather, many additions, deletions, and modifications to the illustrated embodiments may be made without departing from the scope of the disclosure as hereinafter claimed, including legal equivalents thereof. In addition, features from one embodiment may be combined with features of another embodiment while still being encompassed within the scope of the disclosure as contemplated. Further, embodiments of the disclosure have utility with different and various mattress types and configurations.

What is claimed is:

1. A mattress, comprising:
 - a coil layer;
 - a spacer fabric partially extending around a lateral side of the coil layer; and
 - an elastomeric cushion over the coil layer, the elastomeric cushion including:
 - a body comprising an elastomeric gel, with a plasticizer, and oppositely facing major surfaces; and
 - a scrim fabric on at least one major surface of the oppositely facing major surfaces, the elastomeric gel securing the scrim fabric to the at least one major surface of the body by the elastomeric gel seeping into the scrim fabric.
2. The mattress of claim 1, wherein the coil layer comprises an array of pocketed coils.
3. The mattress of claim 1, wherein the spacer fabric comprises:
 - a first knit layer defining a first side;
 - a second knit layer defining a second side; and
 - a fibrous material between the first knit layer and the second knit layer.

14

4. The mattress of claim 1, wherein the elastomeric gel is exposed on an outer surface of the scrim fabric opposite from the body.

5. The mattress of claim 4, wherein the elastomeric gel exposed on the outer surface defines a reduced slip surface or a non-slip surface on the scrim fabric.

6. The mattress of claim 4, wherein the elastomeric gel exposed on the outer surface contacts the coil layer or a cover of the coil layer.

7. The mattress of claim 1, wherein the elastomeric gel of the body of the elastomeric cushion defines a plurality of interconnected walls that define an array of cells.

8. The mattress of claim 7, wherein the walls extend between the oppositely facing major surfaces of the body.

9. The mattress of claim 8, wherein the array of cells opens to at least one surface of the oppositely facing surfaces of the body.

10. The mattress of claim 1, further comprising: a foam layer between the coil layer and the elastomeric cushion.

11. The mattress of claim 10, wherein the scrim fabric of the elastomeric cushion is positioned against the foam layer.

12. The mattress of claim 11, wherein the elastomeric cushion is secured to the foam layer.

13. The mattress of claim 1, further comprising a cover over the at least one elastomeric cushion and around at least a portion of the spacer fabric,

wherein the spacer fabric comprises a first side and a second side opposite the first side, and

wherein the first side of the spacer fabric is adjacent the coil layer and the second side of the spacer fabric is adjacent the cover.

14. A mattress, comprising:

- a coil layer;
- a spacer fabric partially extending around a lateral side of the coil layer; and
- an elastomeric cushion over the coil layer, the elastomeric cushion including:

- a body comprising an elastomeric gel, with a plasticizer, and oppositely facing major surfaces; and
- a scrim fabric on at least one major surface of the oppositely facing major surfaces, the elastomeric gel securing the scrim fabric to the at least one major surface of the body by the elastomeric gel seeping through the scrim fabric; and

- a cover at least partly over the at least one elastomeric cushion and around at least a portion of the spacer fabric.

15. The mattress of claim 14, wherein the elastomeric gel on an outer surface of the scrim fabric contacts the coil layer or a cover of the coil layer.

16. The mattress of claim 14, wherein the scrim fabric is adhesively secured to the coil layer or a cover of the coil layer.

17. The mattress of claim 14, further comprising:

- a layer between the coil layer and the elastomeric cushion.

18. The mattress of claim 17, wherein the layer comprises foam.

19. The mattress of claim 18, wherein the scrim fabric faces the foam.

20. The mattress of claim 19, wherein the scrim fabric is secured to the foam.

* * * * *