

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384303
Kind Code	B1
Date of Patent	August 12, 2025
Inventor(s)	Huang; Guanghua

Navigation device

Abstract

A navigation device includes a navigation device main body and a mounting bracket. The mounting bracket is detachably connected to the navigation device main body. The mounting bracket is used for connecting with a car. Therefore, the navigation device main body is capable of being disassembled and separated from the mounting bracket. This not only facilitates production and marketing, but also makes it easy for a user to install the navigation device main body and the mounting bracket. Moreover, the navigation device has strong universality, and the navigation device main body or the mounting bracket can be replaced according to the needs of different users. The difficulty of modification is relatively small, especially for people who need to modify their car navigation devices. Non professionals can also complete the modification work easily, greatly improving the user's modification experience, and effectively reducing a return rate.

Inventors:	Huang; Guanghua (Shenzhen, CN)
Applicant:	Huang; Guanghua (Shenzhen, CN)
Family ID:	1000008140189
Appl. No.:	18/826812
Filed:	September 06, 2024

Foreign Application Priority Data

CN	202422107065.8	Aug. 29, 2024
----	----------------	---------------

Publication Classification

Int. Cl.: B60R11/02 (20060101); B60R11/00 (20060101)

U.S. Cl.:

CPC **B60R11/0258** (20130101); B60R2011/0066 (20130101); B60R2011/008 (20130101)

Field of Classification Search

CPC: B60R (2011/0059); B60R (2011/0071); B60R (2011/0078); B60R (11/0258); B60R (11/0205); B60R (11/02); B60R (2011/0066); B60R (2011/008); B60R (2011/0084)

USPC: 296/37.1; 224/929; 701/444

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4066307	12/1977	Barding	70/423	B60R 11/02
4738420	12/1987	Angle	455/345	B60R 11/0205
4829595	12/1988	Kobayashi	312/7.1	H04B 1/082
4867398	12/1988	Butcher	248/27.3	B60R 11/0205
4895326	12/1989	Nimpoeno	455/345	B60K 35/50
4911386	12/1989	Putman	455/345	B60K 35/50
5779197	12/1997	Kim	296/70	B60R 11/0211
5791606	12/1997	Blackburn	361/814	B60R 11/0205
5887829	12/1998	Wong	248/27.1	B60R 11/02
6504731	12/2002	Okamoto	174/72A	H05K 5/0017
7165798	12/2006	Chamberlain	296/37.1	B60R 11/0205
8264856	12/2011	Snider	381/86	H05K 1/0215
8416566	12/2012	Renkel, Jr.	361/752	H05K 7/1491
D704697	12/2013	Fiore, IV	D14/258	N/A
2001/0016432	12/2000	Yamauchi	439/34	B60K 35/10
2003/0160134	12/2002	Upson	296/70	B60K 35/50
2006/0250531	12/2005	Hsu	348/844	B60R 11/0235
2008/0043408	12/2007	Quilling	361/679.01	B60R 11/02
2008/0049949	12/2007	Snider	381/86	H05K 13/00
2009/0268411	12/2008	Baker	29/428	B60R 11/02
2010/0053882	12/2009	Hayashi	361/679.43	H04B 1/3822
2011/0292769	12/2010	Snider	368/47	H05K 9/0045
2012/0160974	12/2011	Washiyama	248/201	B60R 11/02
2014/0347831	12/2013	Snider	361/752	G04G 5/002
2018/0041236	12/2017	Riggs	N/A	B60R 11/0205
2021/0138901	12/2020	Shoji	N/A	B60K 35/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202004010667	12/2003	DE	G11B 25/043
19980033415	12/1997	KR	N/A
WO-2013008388	12/2012	WO	B60R 11/02

Primary Examiner: Gutman; Hilary L

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to the field of automobiles, particularly to a navigation device.

BACKGROUND ART

(2) In recent years, China's automobile industry has developed rapidly, with an extremely fast growth rate that is far ahead of the world. With the construction of roads, economic exchanges between cities have become more frequent, and car navigation devices have become very important. A navigation device that integrates accurate positioning, navigation, and entertainment functions can better meet the needs of car owners and become a basic equipment on the car.

(3) The current car audio-visual navigation devices on the current market adopt an integral-machine structure, with a host (including a housing), a mounting plate, and a display screen installed and sold as an integral whole. This has many drawbacks, for example: nowadays, car navigation devices are all integral machines, with extremely low modularization and universalization. With the increasing number of car models, it has caused difficulties in the entire business process of production, wholesale, and retail. Not only is it inconvenient for production, manufacturing, and marketing, but it is also extremely difficult to modify for people who need to modify car navigation devices, making it difficult for non professionals to complete the modification work and resulting in a very high return rate.

SUMMARY

(4) In order to overcome the shortcomings of the prior art, a navigation device is provided in the present disclosure. The navigation device includes a navigation device main body and a mounting bracket. The mounting bracket is detachably connected to the navigation device main body. The mounting bracket is used for connecting with a car.

(5) As an improvement of the present disclosure, the navigation device main body includes a screen. The screen is detachably connected to the mounting bracket. The navigation device further includes first connecting parts. The screen is detachably connected to the mounting bracket through the first connecting part.

(6) As an improvement of the present disclosure, the navigation device main body further includes a host. The host is electrically connected to the screen. The host is electrically connected to the screen through an electrical connection cable.

(7) As an improvement of the present disclosure, the navigation device main body further includes a host. The host is electrically connected to the screen. The host is detachably connected to the mounting bracket.

(8) As an improvement of the present disclosure, the first connecting part includes a first connecting member and a first connecting fitting member. The first connecting member is connected to the screen, the first connecting fitting member is connected to the mounting bracket, and the first connecting member is detachably connected to the first connecting fitting member.

(9) As an improvement of the present disclosure, the first connecting member is a first connecting buckle, and the first connecting fitting member is provided with a first connecting opening. The first connecting buckle is provided with an elastic wall. When the first connecting buckle is inserted into the first connecting opening, the elastic wall is pressed against and locked to an inner wall of the first connecting opening. Alternatively, the first connecting fitting member is a first connecting buckle, the first connecting member is provided with a first connecting opening, and the first connecting buckle is provided with an elastic wall. When the first connecting buckle is inserted into the first connecting opening, the elastic wall is pressed against and locked to an inner wall of the first connecting opening.

(10) As an improvement of the present disclosure, the elastic wall is provided with concave fixing slot portions and guiding inclined surfaces adjacent to the fixing slot portions. The guiding inclined surface is connected to the fixing slot portion, and the inner wall of the first connecting opening is equipped with protruding buckle portions. The guiding inclined surface and the fixing slot portion

pass through the first connecting opening in sequence, so that the fixing slot portion is engaged with the buckle portion.

(11) As an improvement of the present disclosure, the first connecting member is detachably connected to the screen, and the first connecting fitting member is detachably connected to the mounting bracket.

(12) As an improvement of the present disclosure, the first connecting member is a first connecting buckle, and the first connecting fitting member is equipped with a first connecting opening. The first connecting buckle is equipped with an elastic wall. When the first connecting buckle is inserted into the first connecting opening, the elastic wall is pressed against and locked to an inner wall of the first connecting opening. Alternatively, the first connecting fitting member is a first connecting buckle, the first connecting member is equipped with a first connecting opening, and the first connecting buckle is equipped with an elastic wall. When the first connecting buckle is inserted into the first connecting opening, the elastic wall is pressed against and locked to an inner wall of the first connecting opening.

(13) As an improvement of the present disclosure, the first connecting member is also equipped with first guiding protrusions, and the inner wall of the first connecting opening is also provided with first guiding grooves. The first guiding protrusion is connected to the first guiding groove. The first connecting member is also provided with a first connecting lug. The first connecting lug is provided with a second mounting hole.

(14) The second mounting hole is used for detachable connection between the first connecting member and the screen. The first connecting fitting member is also provided with a second connecting lug. The second connecting lug is provided with a third mounting hole. The third mounting hole is used for detachable connection between the first connecting fitting member and a mounting bracket. The first connecting member includes a main body part and an elastic part. The elastic part is detachably connected to the main body part, and the elastic wall is provided on the elastic part. An elastic gap is defined between the elastic wall and the main body part. The main body part is provided with a mounting block, and the elastic part is provided with a mounting slot. An upper side of the mounting slot is provided with a first elastic block, and a lower side of the mounting slot is provided with a second elastic block. A flexible slit is formed between the first elastic block and the second elastic block, and the mounting block is inserted into the mounting slot through the slit. The first elastic block and the second elastic block stop the mounting block in the mounting slot.

(15) Beneficial effects of the present disclosure are as follows. The navigation device is provided in the present disclosure. The navigation device includes the navigation device main body and the mounting bracket. The mounting bracket is detachably connected to the navigation device main body. The mounting bracket is used for connecting with the car. Therefore, the navigation device main body is capable of being disassembled and separated from the mounting bracket. This not only facilitates production, manufacturing, and marketing, but also makes it easy for a user to install the navigation device main body and the mounting bracket. Moreover, the navigation device has strong universality, and the navigation device main body or the mounting bracket can be replaced according to the needs of different users. The difficulty of modification is relatively small, especially for people who need to modify their car navigation devices. Non professionals can also complete the modification work easily, thereby greatly improving the user's modification experience, and effectively reducing the return rate.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Implementations of the present disclosure will now be described, by way of embodiment, with

reference to the attached figures. It should be understood, the drawings are shown for illustrative purpose only, for ordinary person skilled in the art, other drawings obtained from these drawings without paying creative labor by an ordinary person skilled in the art should be within scope of the present disclosure.

- (2) FIG. 1 is a schematic diagram of an overall structure of the present disclosure.
- (3) FIG. 2 is another schematic diagram of an overall structure of the present disclosure.
- (4) FIG. 3 is an exploded view of the present disclosure.
- (5) FIG. 4 is an enlarged view of area A in FIG. 3.
- (6) FIG. 5 is an enlarged view of area B in FIG. 3.
- (7) FIG. 6 is another exploded view of the present disclosure.
- (8) FIG. 7 is an enlarged view of area C in FIG. 6.
- (9) FIG. 8 is a sectional view cut along a screen, a host, and a mounting bracket.
- (10) FIG. 9 is an enlarged view of area D in FIG. 8.
- (11) FIG. 10 is a sectional view cut along a screen, a main bracket, and a side bracket.
- (12) FIG. 11 is an enlarged view of area E in FIG. 10.
- (13) FIG. 12 is a sectional view cut along a host, a main bracket, and a side bracket.
- (14) FIG. 13 is an enlarged view of area F in FIG. 12.
- (15) FIG. 14 is a sectional view cut along a first connecting part and a second connecting part.
- (16) FIG. 15 is an enlarged view of area G in FIG. 14.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (17) Referring to FIGS. 1-15, a navigation device includes a navigation device main body 1 and a mounting bracket 2. The mounting bracket 2 is detachably connected to the navigation device main body 1. The mounting bracket 2 is used for connecting with a car.
- (18) Through the above structure, the navigation device includes the navigation device main body 1 and the mounting bracket 2. The mounting bracket 2 is detachably connected to the navigation device main body 1. The mounting bracket 2 is used for connecting with the car. Therefore, the navigation device main body 1 is capable of being disassembled and separated from the mounting bracket 2. This not only facilitates production, manufacturing, and marketing, but also makes it easy for a user to install the navigation device main body 1 and the mounting bracket 2. Moreover, the navigation device has strong universality, and the navigation device main body 1 or the mounting bracket 2 can be replaced according to the needs of different users. The difficulty of modification is relatively small, especially for people who need to modify their car navigation devices. Non professionals can also complete the modification work easily, thereby greatly improving the user's modification experience, and effectively reducing the return rate.
- (19) In this embodiment, the navigation device main body 1 includes a screen 11. The screen 11 is detachably connected to the mounting bracket 2. The navigation device further includes first connecting parts 3. The screen 11 is detachably connected to the mounting bracket 2 through the first connecting part 3. The navigation device main body 1 further includes a host 4. The host 4 is electrically connected to the screen 11. Through the above structure, as the screen 11 is detachably connected to the mounting bracket 2 through the first connecting part 3, users can choose to replace the screen 11 with different sizes and models according to their preferences to meet the modification needs of different users.
- (20) In this embodiment, the navigation device main body 1 further includes a host 4. The host 4 is electrically connected to the screen 11. The host 4 is electrically connected to the screen 11 through an electrical connection cable 7. The host 4 is detachably connected to the mounting bracket 2. Through the above structure, the navigation device main body 1 further includes the host 4, the host 4 is electrically connected to the screen 11 through the electrical connection cable 7, and the host 4 is detachably connected to the mounting bracket 2, so that the user can selectively install the host 4 on the mounting bracket 2 or on other positions in the car, further reducing the difficulty of installing the navigation device.

(21) In this embodiment, the navigation device further includes second connecting parts 5. The screen 11 is detachably connected to the mounting bracket 2 through the first connecting part 3 and the second connecting part 5. The first connecting part 3 and the second connecting part 5 are arranged in sequence from left to right along the screen 11 and the mounting bracket 2.

(22) Through the above structure, the screen 11 is detachably connected to the mounting bracket 2 through the first connecting part 3 and the second connecting part 5, and the first connecting part 3 and the second connecting part 5 are arranged in sequence from left to right along the screen 11 and the mounting bracket 2, so that both a left side and a right side of the screen 11 are connected to the mounting bracket 2, greatly improving the stability of the installation of the screen 11 and making it less likely for the screen 11 to fall off. Furthermore, the user can selectively connect one of the first connecting part 3 and the second connecting part 5 to adjust up and down positions of the screen 11, making it easier for the user to install the screen 11.

(23) In this embodiment, a total number of the first connecting parts 3 is at least two, and at least two of the first connecting parts 3 are arranged in sequence from top to bottom along the screen 11 and the mounting bracket 2. A total number of the second connecting parts 5 is at least two, and at least two of the second connecting parts 5 are arranged in sequence from top to bottom along the screen 11 and the mounting bracket 2. Through the above structure, at least two of the first connecting parts 3 are arranged in sequence from top to bottom along the screen 11 and the mounting bracket 2, and at least two of the second connecting parts 5 are arranged in sequence from top to bottom along the screen 11 and the mounting bracket 2, so that both an upper side and a lower side of the screen 11 are connected to the mounting bracket 2, greatly improving the stability of the installation of the screen 11 and making it less likely for the screen 11 to fall off.

Furthermore, the user can selectively connect one of the two first connecting parts 3, and can selectively connect one of the two second connecting parts 5, so as to adjust the up and down positions of the screen 11, making it easier for the user to install the screen 11. In this embodiment, the first connecting part 3 includes a first connecting member 31 and a first connecting fitting member 32. The first connecting member 31 is connected to the screen 11, the first connecting fitting member 32 is connected to the mounting bracket 2, and the first connecting member 31 is detachably connected to the first connecting fitting member 32. The first connecting member 31 is a first connecting buckle, and the first connecting fitting member 32 is provided with a first connecting opening 321. The first connecting buckle is provided with an elastic wall 311. When the first connecting buckle is inserted into the first connecting opening 321, the elastic wall 311 is pressed against and locked to an inner wall of the first connecting opening 321. Alternatively, the first connecting fitting member 32 is a first connecting buckle, the first connecting member 31 is provided with a first connecting opening 321, and the first connecting buckle is provided with an elastic wall 311. When the first connecting buckle is inserted into the first connecting opening 321, the elastic wall 311 is pressed against and locked to an inner wall of the first connecting opening 321. Specifically, the elastic wall 311 is provided with concave fixing slot portions 3111 and guiding inclined surfaces 3112 adjacent to the fixing slot portions 3111. The guiding inclined surface 3112 is connected to the fixing slot portion 3111, and the inner wall of the first connecting opening 321 is equipped with protruding buckle portions 3211. The guiding inclined surface 3112 and the fixing slot portion 3111 pass through the first connecting opening 321 in sequence, so that the fixing slot portion 3111 is engaged with the buckle portion 3211. Through the above structure, the setting of the first connecting part 3 is effectively achieved, and when the user needs to connect the first connecting buckle to the first connecting opening 321, the first connecting buckle can be inserted into the first connecting opening 321. During the process of inserting the first connecting buckle into the first connecting opening 321, the guiding inclined surface 3112 and the fixing slot portion 3111 of the elastic wall 311 pass through the first connecting opening 321 in sequence, and the elastic wall 311 is squeezed. When the fixing slot portion 3111 is connected to the buckle portion 3211, an elastic restoring force generated when the elastic wall 311 is squeezed pushes the

elastic wall **311** to be restored, so that the buckle portion **3211** of the elastic wall **311** is pressed against the fixing slot portion **3111**, thereby completing the connection between the first connecting member **31** and the first connecting fitting member **32**, and completing the connection between the screen **11** and the mounting bracket **2**. Moreover, when the user needs to detach the screen **11** from the mounting bracket **2**, only an external force greater than the elastic restoring force of the elastic wall **311** needs to be applied to the screen **11**, and the elastic wall **311** will be squeezed, so that the buckle portion **3211** can detach from the fixing slot portion **3111** along the guiding inclined surface **3112**, and the first connecting member **31** and the first connecting fitting member **32** can be separated to detach the screen **11** from the mounting bracket **2**, making it easy for the user to disassemble and assemble the screen **11**. In particular, when the mounting bracket **2** is connected to the car, due to a limited space inside the car, the disassembly and assembly of the screen **11** and the mounting bracket **2** are extremely difficult. The disassembly and assembly structure of the first connecting member **31** and the first connecting fitting member **32** effectively solves this difficulty. Furthermore, the elastic wall **311** includes two fixing slot portions **3111**. The elastic wall **311** includes two guiding inclined surfaces **3112**. The two fixing slot portions **3111** are respectively positioned on a left side and a right side of the elastic wall **311**, and the two guiding inclined surfaces **3112** are respectively positioned on the left side and the right side of the elastic wall **311**. Furthermore, the first connecting member **31** is detachably connected to the screen **11** through screws, and the first connecting fitting member **32** is detachably connected to the mounting bracket **2** through screws.

(24) In this embodiment, the mounting bracket **2** includes a main bracket **21** and side brackets **22**. The main bracket **21** is detachably connected to the side bracket **22**, and the main bracket **21** is connected to the screen **11**. The side bracket **22** is used for connecting with the car. The side bracket **22** is provided with a first mounting hole **221**. The first mounting hole **221** is used for connecting with the car. Through the above structure, compared with an existing integral-machine navigation device, the integral-machine navigation device needs to be connected to a navigation device mounting hole of the car. The integral-machine navigation device needs to have a hole corresponding to the navigation device mounting hole of the car. The navigation device mounting holes of different car models are different and have tens of thousands of variations. The existing practice on the market is to drill a hole on the integral-machine navigation device, so that the integral-machine navigation device has the hole corresponding to the navigation device mounting hole of the car. However, some non professional modification users not only find it difficult to set the hole of the integral-machine navigation device to be consistent with the navigation device mounting hole of the car, but also often drill through the host **4** of the integral-machine navigation device during the drilling process, resulting in the entire navigation device being directly scrapped. Since the mounting bracket **2** in the present application includes the main bracket **21** and the side bracket **22**, the main bracket **21** is detachably connected to the side bracket **22**, the main bracket **21** is connected to the screen **11**, the side bracket **22** is used for connecting with the car, the side bracket **22** is provided with the first mounting hole **221**, and the first mounting hole **221** is used for connecting with the car, the user can directly purchase and replace the side bracket **22** with one that matches the model of the car. The modular design allows the user to select the side bracket **22** equipped with the first mounting hole **221** which is consistent with the navigation device mounting hole of the car according to different car models, so that the user can directly connect the side bracket **22** that matches the model and mounting hole of the car to the main bracket **21**, and then connect the first mounting hole **221** of the side bracket **22** to the navigation device mounting hole of the car to complete the installation of the navigation device. The installation is simple, thereby greatly improving the user experience, reducing the return rate of the navigation device, and solving the difficulty of installing the navigation device. Taking a step back, even if the user has not selected the side bracket **22** that matches the navigation device mounting hole of the car, the user can first drill the first mounting hole **221** that matches the navigation device mounting hole of the

car on the existing side bracket **22**, then connect the side bracket **22** to the main bracket **21**, and finally connect the first mounting hole **221** of the side bracket **22** to the navigation device mounting hole of the car to complete the installation of the navigation device. This can prevent the host **4** of the integral-machine navigation device from being pierced during the drilling process and prevent the navigation device from being damaged. A total number of the side brackets **22** is two, and the two side brackets **22** are respectively detachably connected to a left side and a right side of the main bracket **21**.

(25) In this embodiment, the side bracket **22** is slidably connected to the main bracket **21**, so that the side bracket **22** is capable of sliding and telescoping on the main bracket **21**. Through the above structure, the side bracket **22** is slidably connected to the main bracket **21**, allowing the side bracket **22** to slide and telescope on the main bracket **21**, and the screen **11** is connected to the main bracket **21**, so that when the side bracket **22** is fixed to the car, front and rear positions of the screen **11** can be adjusted by relative sliding and telescoping between the main bracket **21** and the side bracket **22**. For example, when a size of the screen **11** is larger than a navigation device embedding hole of the car, the screen **11** can be extended to suspend above the navigation device embedding hole of the car, so that the size of the screen **11** is not limited by the car's navigation device embedding hole, allowing the user to choose more models of the screen **11** to meet needs. Moreover, the screen **11** suspended above the navigation device embedding hole of the car is not only more beautiful and personalized, but also easy to install and disassemble, with stronger universality, which is a blessing for car modification users.

(26) In this embodiment, the navigation device further includes a first locking member **6**. The first locking member **6** is used for locking the side bracket **22** to the main bracket **21**, so that the side bracket **22** and the main bracket **21** cannot slide against each other. When the first locking member **6** unlocks the main bracket **21** and the side bracket **22**, the side bracket **22** can slide and telescope on the main bracket **21**. The side bracket **22** is provided with a plurality of first adjusting holes **227**, and the main bracket **21** is provided with second adjusting holes **211**. When the side bracket **22** slides and telescopes on the main bracket **21** until the first adjusting hole **227** aligns with the second adjusting hole **211**, the first locking member **6** passes through the first adjusting hole **227** and the second adjusting hole **211** to lock the side bracket **22** to the main bracket **21**, so that the side bracket **22** and the main bracket **21** cannot slide against each other. Alternatively, the main bracket **21** is provided with a plurality of first adjusting holes **227**, and the side bracket **22** is provided with second adjusting holes **211**. When the side bracket **22** slides and telescopes on the main bracket **21** until the first adjusting hole **227** aligns with the second adjusting hole **211**, the first locking member **6** passes through the first adjusting hole **227** and the second adjusting hole **211** to lock the side bracket **22** to the main bracket **21**, so that the side bracket **22** and the main bracket **21** cannot slide against each other. Specifically, the navigation device main body **1** further includes a host **4**, and the host **4** is electrically connected to the screen **11**. The host **4** is detachably connected to the mounting bracket **2**. The main bracket **21** includes a first middle side wall **212**, a first upper side wall **213**, and a first lower side wall **214**. The first upper side wall **213** extends from an upper side of the first middle side wall **212**, and the first lower side wall **214** extends from a lower side of the first middle side wall **212**. The first middle side wall **212** is provided with a first front surface **2121** and a first rear surface **2122**. The first front surface **2121** of the first middle side wall **212** is detachably connected to the screen **11**. A first accommodating cavity **215** is formed between the first upper side wall **213**, the first lower side wall **214**, and the first rear surface **2122** of the first middle side wall **212**. The host **4** is detachably arranged in the first accommodating cavity **215**. The host **4** is detachably connected to the main bracket **21**. Furthermore, the side bracket **22** is detachably connected to the first upper side wall **213** and the first lower side wall **214**. The side bracket **22** includes a second middle side wall **222**, a second upper side wall **223**, and a second lower side wall **224**. The second upper side wall **223** extends from an upper side of the second middle side wall **222**, and the second lower side wall **224** extends from a lower side of the second

middle side wall **222**. The second upper side wall **223** is detachably connected to the first upper side wall **213** through the first locking member **6**, and the second lower side wall **224** is detachably connected to the first lower side wall **214** through the first locking member **6**. A first sliding slot **225** is formed between the second upper side wall **223** and the second middle side wall **222**, and a second sliding slot **226** is formed between the second lower side wall **224** and the second middle side wall **222**. When the locking of the first locking member **6** is released, the first upper side wall **213** is slidable inside the first sliding slot **225**, and the first lower side wall **214** is slidable inside the second sliding slot **226**. The plurality of first adjusting holes **227** are in communication with each other. Through the above structure, the detachable connection between the host **4** and the main bracket **21** is effectively achieved, allowing the user to install the host **4** in the first accommodating cavity **215** or in other positions, thereby reducing the difficulty of installing the navigation device. Furthermore, when the user needs to adjust the front and rear positions of the screen **11**, the locking of the first locking member **6** can be released, and the front and rear positions of the screen **11** can be adjusted by sliding and telescoping relative to each other between the main bracket **21** and the side bracket **22**. After adjustment, the side bracket **22** can be locked to the main bracket **21** by the first locking member **6**, so that the side bracket **22** and the main bracket **21** cannot slide or telescope relative to each other, thereby fixing the position of the screen **11**. Furthermore, the plurality of first adjusting holes **227** provide a plurality of locking positions for adjusting and fixing the position of the screen **11**. Furthermore, the first locking member **6** is a locking screw.

(27) In this embodiment, the first upper side wall **213** is provided with a first avoidance notch **2131**, and the first lower side wall **214** is provided with a second avoidance notch **2141**. The first upper side wall **213** and the first middle side wall **212** are arranged at a right angle, obtuse angle, or acute angle. The first lower side wall **214** and the first middle side wall **212** are arranged at a right angle, obtuse angle, or acute angle. The second upper side wall **223** and the second middle side wall **222** are arranged at a right angle, obtuse angle, or acute angle. The second lower side wall **224** and the second middle side wall **222** are arranged at a right angle, obtuse angle, or acute angle. The screen **11** is provided with a first data interface **111**, and the host **4** is provided with a second data interface **41**. The first data interface **111** is electrically connected to the second data interface **41** through the electrical connection cable **7**. The main bracket **21** is equipped with a third avoidance notch **216**, and the first data interface **111** can be exposed from the main bracket **21** through the third avoidance notch **216**, so that the electrical connection cable **7** can be electrically connected to the first data interface **111** through the third avoidance notch **216**. Through the above structure, the electrical connection between the screen **11**, the electrical connection cable **7**, and the host **4** is effectively achieved, allowing the user to install the host **4** in the first accommodating cavity **215** or in other positions of the car. Moreover, the host **4** is internally equipped with a cooling fan. A plurality of cooling openings **4111** are defined in the host **4**. The design of the first avoidance notch **2131** and the second avoidance notch **2141** facilitates the installation of the host **4**. At the same time, the first avoidance notch **2131** and the second avoidance notch **2141** can avoid the cooling openings **4111** of the host **4**, making it easier for the cooling fan of the host **4** to dissipate heat through the cooling openings **4111**.

(28) In this embodiment, the first connecting member **31** is detachably connected to the screen **11**, and the first connecting fitting member **32** is detachably connected to the mounting bracket **2**. A plurality of fifth adjusting holes **112** are defined in the screen **11**. The plurality of fifth adjusting holes **112** are arranged in sequence from top to bottom along the screen **11**. The first connecting member **31** is detachably connected to one of the plurality of fifth adjusting holes **112**.

Alternatively, a plurality of fifth adjusting holes **112** are defined in the screen **11**, the plurality of fifth adjusting holes **112** are arranged in sequence from left to right along the screen **11**, and the first connecting member **31** is detachably connected to one of the plurality of fifth adjusting holes **112**. Through the above structure, the plurality of fifth adjusting holes **112** are arranged in sequence from top to bottom along the screen **11**, and the first connecting member **31** is detachably

connected to one of the plurality of fifth adjusting holes **112**, so that the up and down positions of the screen **11** can be adjusted, facilitating the user to accurately install the screen **11** of the navigation device main body **1** and adjust the screen **11** to the most suitable position. The plurality of fifth adjusting holes **112** are defined in the screen **11**, the plurality of fifth adjusting holes **112** are arranged in sequence from left to right along the screen **11**, and the first connecting member **31** is detachably connected to one of the plurality of fifth adjusting holes **112**, so that the left and right positions of the screen **11** can be adjusted, making it easy for the user to accurately install the screen **11** of the navigation device main body **1** and adjust the screen **11** to the most suitable position.

(29) In this embodiment, the first connecting member **31** is a first connecting buckle, and the first connecting fitting member **32** is equipped with a first connecting opening **321**. The first connecting buckle is equipped with an elastic wall **311**. When the first connecting buckle is inserted into the first connecting opening **321**, the elastic wall **311** is pressed against and locked to an inner wall of the first connecting opening **321**. Alternatively, the first connecting fitting member **32** is a first connecting buckle, the first connecting member **31** is equipped with a first connecting opening **321**, and the first connecting buckle is equipped with an elastic wall **311**. When the first connecting buckle is inserted into the first connecting opening **321**, the elastic wall **311** is pressed against and locked to an inner wall of the first connecting opening **321**. The first connecting member **31** is also equipped with first guiding protrusions **312**, and the inner wall of the first connecting opening **321** is also provided with first guiding grooves **3212**. The first guiding protrusion **312** is connected to the first guiding groove **3212**. The first connecting member **31** is also provided with a first connecting lug **313**. The first connecting lug **313** is provided with a second mounting hole **3131**. The second mounting hole **3131** is used for detachable connection between the first connecting member **31** and one of the plurality of fifth adjusting holes **112**. The first connecting fitting member **32** is also provided with a second connecting lug **322**. The second connecting lug **322** is provided with a third mounting hole **3221**. The third mounting hole **3221** is used for detachable connection between the first connecting fitting member **32** and the mounting bracket **2**. The first connecting member **31** includes a main body part **314** and an elastic part **315**. The elastic part **315** is detachably connected to the main body part **314**, and the elastic wall **311** is provided on the elastic part **315**. An elastic gap **316** is defined between the elastic wall **311** and the main body part **314**. The main body part **314** is provided with a mounting block **3141**, and the elastic part **315** is provided with a mounting slot **3151**. An upper side of the mounting slot **3151** is provided with a first elastic block **31511**, and a lower side of the mounting slot **3151** is provided with a second elastic block **31512**. A flexible slit **31513** is formed between the first elastic block **31511** and the second elastic block **31512**, and the mounting block **3141** is inserted into the mounting slot **3151** through the slit **31513**. The first elastic block **31511** and the second elastic block **31512** stop the mounting block **3141** in the mounting slot **3151**. Furthermore, the first connecting opening **321** is equipped with two buckle portions **3211**. The two buckle portions **3211** are respectively positioned on a left side and a right side of an inner wall of the first connecting opening **321**. The first connecting opening **321** is provided with two first guiding grooves **3212**. The two first guiding grooves **3212** are respectively positioned in an upper side and a lower side of the inner wall of the first connecting opening **321**. Through the above structure, the setting between the main body part **314** and the elastic part **315** is effectively achieved. When the mounting block **3141** is inserted into the mounting slot **3151** through the slit **31513**, the mounting block **3141** will press the first elastic block **31511** and the second elastic block **31512**, and the slit **31513** will be stretched open by the mounting block **3141** to undergo elastic deformation, so that the mounting block **3141** can be smoothly inserted into the mounting slot **3151**. After the mounting block **3141** is inserted into the mounting slot **3151**, the first elastic block **31511** and the second elastic block **31512** are restored to shrink the slit **31513**, thereby stopping the mounting block **3141** in the mounting slot **3151**, and completing the connection between the main body part **314** and the elastic part **315**.

(30) In this embodiment, the second upper side wall and the second lower side wall are both provided with the first adjusting holes, and the first upper side wall and the first lower side wall are both provided with the second adjusting holes. The first mounting hole is defined in the second middle side wall. The first mounting hole includes a first mounting hole unit **22111**, a second mounting hole unit **22112**, and a third mounting hole unit **22113**. The shapes of the first mounting hole unit, the second mounting hole unit, and the third mounting hole unit are different from each other. Through the above structure, due to the different shapes of the first mounting hole unit, the second mounting hole unit, and the third mounting hole unit, the difficulty of installing the side bracket onto the car can be further reduced, making it easier for the user to connect the side bracket with the navigation device mounting hole of the car. The second connecting part in the present application has an identical structure with the first connecting part.

(31) The above presents one or more embodiments provided in conjunction with specific content and does not limit the specific implementations of the utility model to these descriptions. Any methods, structures, or similar equivalents related to the utility model, or any technical deductions or substitutions made under the premise of the conceptual framework of this utility model, shall be considered within the scope of protection of this utility model.

Claims

1. A navigation device, comprising: a navigation device main body; and a mounting bracket, wherein the mounting bracket is detachably connected to the navigation device main body, and the mounting bracket is used for connecting with a car; wherein the navigation device main body comprises a screen, and the screen is detachably connected to the mounting bracket; the navigation device further comprises first connecting parts, and the screen is detachably connected to the mounting bracket through the first connecting part; wherein the mounting bracket comprises a main bracket and side brackets, the main bracket is detachably connected to the side bracket, the main bracket is connected to the screen, and the side bracket is used for connecting with the car.
2. The navigation device according to claim 1, wherein the navigation device main body further comprises a host, the host is electrically connected to the screen, and the host is electrically connected to the screen through an electrical connection cable.
3. The navigation device according to claim 1, wherein the navigation device main body further comprises a host, the host is electrically connected to the screen, and the host is detachably connected to the mounting bracket.
4. The navigation device according to claim 1, further comprising second connecting parts, wherein the screen is detachably connected to the mounting bracket through the first connecting part and the second connecting part, and the first connecting part and the second connecting part are arranged in sequence from left to right along the screen and the mounting bracket.
5. The navigation device according to claim 4, wherein a total number of the first connecting parts is at least two, and at least two of the first connecting parts are arranged in sequence from top to bottom along the screen and the mounting bracket; a total number of the second connecting parts is at least two, and at least two of the second connecting parts are arranged in sequence from top to bottom along the screen and the mounting bracket.
6. The navigation device according to claim 1, wherein the first connecting part comprises a first connecting member and a first connecting fitting member, the first connecting member is connected to the screen, the first connecting fitting member is connected to the mounting bracket, and the first connecting member is detachably connected to the first connecting fitting member.
7. The navigation device according to claim 6, wherein the first connecting member is a first connecting buckle, the first connecting fitting member is provided with a first connecting opening, the first connecting buckle is provided with an elastic wall, and when the first connecting buckle is inserted into the first connecting opening, the elastic wall is pressed against and locked to an inner

wall of the first connecting opening.

8. The navigation device according to claim 7, wherein the elastic wall is provided with concave fixing slot portions and guiding inclined surfaces adjacent to the fixing slot portions, the guiding inclined surface is connected to the fixing slot portion, the inner wall of the first connecting opening is equipped with protruding buckle portions, and the guiding inclined surface and the fixing slot portion pass through the first connecting opening in sequence, so that the fixing slot portion is engaged with the buckle portion.

9. The navigation device according to claim 1, wherein the side bracket is provided with a first mounting hole, and the first mounting hole is used for connecting with the car.

10. The navigation device according to claim 1, wherein the side bracket is slidably connected to the main bracket, so that the side bracket is capable of sliding and telescoping on the main bracket.

11. The navigation device according to claim 10, further comprising a first locking member, wherein the first locking member is used for locking the side bracket to the main bracket, so that the side bracket and the main bracket cannot slide against each other; when the first locking member unlocks the main bracket and the side bracket, the side bracket can slide and telescope on the main bracket.

12. The navigation device according to claim 11, wherein the side bracket is provided with a plurality of first adjusting holes, the main bracket is provided with second adjusting holes, and when the side bracket slides and telescopes on the main bracket until the first adjusting hole aligns with the second adjusting hole, the first locking member passes through the first adjusting hole and the second adjusting hole to lock the side bracket to the main bracket, so that the side bracket and the main bracket cannot slide against each other; alternatively, the main bracket is provided with a plurality of first adjusting holes, the side bracket is provided with second adjusting holes, and when the side bracket slides and telescopes on the main bracket until the first adjusting hole aligns with the second adjusting hole, the first locking member passes through the first adjusting hole and the second adjusting hole to lock the side bracket to the main bracket, so that the side bracket and the main bracket cannot slide against each other.

13. The navigation device according to claim 11, wherein the navigation device main body further comprises a host, and the host is electrically connected to the screen; the host is detachably connected to the mounting bracket; the main bracket comprises a first middle side wall, a first upper side wall, and a first lower side wall; the first upper side wall extends from an upper side of the first middle side wall, and the first lower side wall extends from a lower side of the first middle side wall; the first middle side wall is provided with a first front surface and a first rear surface, and the first front surface of the first middle side wall is detachably connected to the screen; a first accommodating cavity is formed between the first upper side wall, the first lower side wall, and the first rear surface of the first middle side wall; the host is detachably arranged in the first accommodating cavity; and the host is detachably connected to the main bracket.

14. The navigation device according to claim 13, wherein the side bracket is detachably connected to the first upper side wall and the first lower side wall; the side bracket comprises a second middle side wall, a second upper side wall, and a second lower side wall; the second upper side wall extends from an upper side of the second middle side wall, and the second lower side wall extends from a lower side of the second middle side wall; the second upper side wall is detachably connected to the first upper side wall through the first locking member, and the second lower side wall is detachably connected to the first lower side wall through the first locking member; a first sliding slot is formed between the second upper side wall and the second middle side wall, and a second sliding slot is formed between the second lower side wall and the second middle side wall; when the locking of the first locking member is released, the first upper side wall can slide inside the first sliding slot, and the first lower side wall can slide inside the second sliding slot.

15. The navigation device according to claim 14, wherein the first upper side wall is provided with a first avoidance notch, and the first lower side wall is provided with a second avoidance notch; the

first upper side wall and the first middle side wall are arranged at a right angle, obtuse angle, or acute angle; the first lower side wall and the first middle side wall are arranged at a right angle, obtuse angle, or acute angle; the second upper side wall and the second middle side wall are arranged at a right angle, obtuse angle, or acute angle; the second lower side wall and the second middle side wall are arranged at a right angle, obtuse angle, or acute angle; the screen is provided with a first data interface, the host is provided with a second data interface, and the first data interface is electrically connected to the second data interface through the electrical connection cable; the main bracket is equipped with a third avoidance notch, and the first data interface can be exposed from the main bracket through the third avoidance notch, so that the electrical connection cable can be electrically connected to the first data interface through the third avoidance notch.

16. The navigation device according to claim 6, wherein the first connecting member is detachably connected to the screen, and the first connecting fitting member is detachably connected to the mounting bracket.

17. The navigation device according to claim 16, wherein a plurality of fifth adjusting holes are defined in the screen, the plurality of fifth adjusting holes are arranged in sequence from top to bottom along the screen, and the first connecting member is detachably connected to one of the plurality of fifth adjusting holes.

18. The navigation device according to claim 17, wherein the first connecting member is a first connecting buckle, the first connecting fitting member is equipped with a first connecting opening, the first connecting buckle is equipped with an elastic wall, and when the first connecting buckle is inserted into the first connecting opening, the elastic wall is pressed against and locked to an inner wall of the first connecting opening; the first connecting member is also equipped with first guiding protrusions, the inner wall of the first connecting opening is also provided with first guiding grooves, and the first guiding protrusion is connected to the first guiding groove; the first connecting member is also provided with a first connecting lug, the first connecting lug is provided with a second mounting hole, and the second mounting hole is used for detachable connection between the first connecting member and one of the plurality of fifth adjusting holes; the first connecting fitting member is also provided with a second connecting lug, the second connecting lug is provided with a third mounting hole, and the third mounting hole is used for detachable connection between the first connecting fitting member and the mounting bracket; the first connecting member comprises a main body part and an elastic part, the elastic part is detachably connected to the main body part, the elastic wall is provided on the elastic part, and an elastic gap is defined between the elastic wall and the main body part; the main body part is provided with a mounting block, the elastic part is provided with a mounting slot, an upper side of the mounting slot is provided with a first elastic block, a lower side of the mounting slot is provided with a second elastic block, a flexible slit is formed between the first elastic block and the second elastic block, the mounting block is inserted into the mounting slot through the slit, and the first elastic block and the second elastic block stop the mounting block in the mounting slot.
