

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389732
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kikuchi; Norifumi et al.

Display device and surface mount device

Abstract

A display device is provided with a substrate, a plurality of surface mount devices two-dimensionally arranged on the substrate in a first direction and a second direction, and a plurality of signal lines and a plurality of scanning lines arranged on the substrate. The surface mount device is provided with four pixels. Each of the four pixels is provided with light sources of three colors, and each of the light sources of three colors includes a light emitting diode element. The plurality of scanning lines extends in the first direction, and the plurality of signal lines extends in the second direction. The number of signal lines is three for two pixels arranged in the first direction, and the number of scanning lines is four for two pixels arranged in the second direction.

Inventors:	Kikuchi; Norifumi (Kanagawa, JP), Sakurai; Hisao (Saitama, JP), Nishinaka; Ippei (Kanagawa, JP)
Applicant:	SONY SEMICONDUCTOR SOLUTIONS CORPORATION (Kanagawa, JP)
Family ID:	1000008751486
Assignee:	Sony Semiconductor Solutions Corporation (Kanagawa, JP)
Appl. No.:	17/997046
Filed (or PCT Filed):	April 27, 2021
PCT No.:	PCT/JP2021/016806
PCT Pub. No.:	WO2021/221056
PCT Pub. Date:	November 04, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230170454 A1	Jun. 01, 2023

Foreign Application Priority Data

JP2020-081365

May. 01, 2020

Publication Classification

Int. Cl.: H10H20/857 (20250101); H01L25/075 (20060101)

U.S. Cl.:

CPC H10H20/857 (20250101); H01L25/0753 (20130101);

Field of Classification Search

CPC: H10H (20/857); H10H (20/8513); H10H (20/8506); H10H (20/851); H10H (29/142); H01L (25/0753); G09G (3/32); G09G (2300/0426); G09G (2300/0452); G09G (3/14); G09F (9/302); G09F (9/33)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0175650	12/2011	Tomiyoshi	257/89	G02F 1/133603
2012/0256814	12/2011	Ootorii	345/82	G09G 3/3208
2014/0035798	12/2013	Kawada	345/77	G09G 3/3233
2014/0111557	12/2013	Omata	345/76	G09G 3/3233
2014/0168037	12/2013	Sakariya	N/A	N/A
2016/0365031	12/2015	Wu	N/A	G09G 3/3275
2017/0213502	12/2016	Henry et al.	N/A	N/A
2019/0393389	12/2018	Chen	N/A	H10H 20/8514
2020/0051964	12/2019	Jung et al.	N/A	N/A
2023/0124835	12/2022	Kikuchi	345/694	H10K 59/351
2023/0420441	12/2022	Kikuchi	N/A	H01L 23/5386

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202404841	12/2011	CN	N/A
103545304	12/2013	CN	N/A
103996676	12/2013	CN	N/A
107078132	12/2016	CN	N/A
110828510	12/2019	CN	N/A
3175482	12/2016	EP	N/A
3608964	12/2019	EP	N/A
2001-075508	12/2000	JP	N/A
2001-127344	12/2000	JP	N/A
2017-529557	12/2016	JP	N/A
2019140361	12/2018	JP	N/A
2017-0037975	12/2016	KR	N/A

20190143323	12/2018	KR	N/A
2020-0017336	12/2019	KR	N/A
WO 2016/016460	12/2015	WO	N/A
WO 2019/049360	12/2018	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion prepared by the Japan Patent Office on Jun. 17, 2021, for International Application No. PCT/JP2021/016806, 3 pgs. cited by applicant

Primary Examiner: Mandala; Victor A

Attorney, Agent or Firm: SHERIDAN ROSS P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a national stage application under 35 U.S.C. 371 and claims the benefit of PCT Application No. PCT/JP2021/016806, having an international filing date of 27 Apr. 2021, which designated the United States, which PCT application claimed the benefit of Japanese Patent Application No. 2020-081365, filed 1 May 2020, the entire disclosures of each of which are incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to a display device and a surface mount device.

BACKGROUND ART

(3) In recent years, a display device in which a plurality of surface mount devices (hereinafter appropriately referred to as “SMD”) is two-dimensionally arranged has been proposed (refer to, for example, Patent Document 1 and Patent Document 2). The SMD is provided with pixels including light emitting diode elements (hereinafter, appropriately referred to as “LED elements”) of three colors or two colors.

CITATION LIST

Patent Document

(4) Patent Document 1: Japanese Patent Application Laid-Open No. 2001-75508 Patent Document 2: Japanese Patent Application Laid-Open No. 2001-127344

SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

(5) However, in the LED display device described above, since the number of signal lines connected to the SMD is large, there is a problem that line-and-space (hereinafter, appropriately referred to as “L/S”) of the signal lines is narrow.

(6) An object of the present disclosure is to provide a display device and a surface mount device capable of suppressing L/S of signal lines from narrowing.

Solutions to Problems

(7) In order to solve the above-described problem, a first disclosure is a display device provided with: a substrate; a plurality of surface mount devices two-dimensionally arranged on the substrate in a first direction and a second direction; and a plurality of signal lines and a plurality of scanning lines arranged on the substrate, in which a surface mount device is provided with four pixels, each of the four pixels is provided with light sources of three colors, and each of the light sources of three colors includes a light emitting diode element, the plurality of scanning lines extends in the first direction, the plurality of signal lines extends in the second direction, the number of signal

lines is three for two pixels arranged in the first direction, and the number of scanning lines is four for two pixels arranged in the second direction.

(8) A second disclosure is a display device provided with: a substrate; a plurality of surface mount devices two-dimensionally arranged on the substrate in a first direction and a second direction; and a plurality of signal lines and a plurality of scanning lines arranged on the substrate, in which a surface mount device is provided with four pixels, each of the four pixels is provided with light sources of two colors, and each of the light sources of two colors includes a light emitting diode element, a plurality of scanning lines extends in the first direction, a plurality of signal lines extends in the second direction, the number of signal lines is three for two pixels arranged in the second direction, and the number of scanning lines is three or four for two pixels arranged in the first direction.

(9) A third disclosure is a surface mount device used in a display device, the surface mount device provided with: four pixels; a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal connected to different scanning lines, respectively, in which each of the four pixels is provided with light sources of three colors, and each of the light sources of three colors includes a light emitting diode element.

(10) A fourth disclosure is a surface mount device used in a display device, the surface mount device provided with: four pixels; a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal connected to different scanning lines, respectively, in which each of the four pixels is provided with light sources of two colors, and each of the light sources of two colors includes a light emitting diode element.

(11) A fifth disclosure is a surface mount device used in a display device, the surface mount device provided with: four pixels; a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, and a sixth terminal connected to different scanning lines, respectively, in which each of the four pixels is provided with light sources of two colors, and each of the light sources of two colors includes a light emitting diode element.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a plane view illustrating an example of a configuration of a display device according to a first embodiment of the present disclosure.

(2) FIG. 2A is a plane view illustrating an example of a configuration of an SMD provided on the display device according to the first embodiment of the present disclosure.

(3) FIG. 2B is a circuit diagram illustrating an example of a circuit of the SMD provided on the display device according to the first embodiment of the present disclosure.

(4) FIG. 2C is a schematic diagram illustrating an example of arrangement of signal lines and scanning lines of the display device according to the first embodiment of the present disclosure.

(5) FIG. 3A is a plane view illustrating a configuration of an SMD provided on a display device according to Comparative Example 1.

(6) FIG. 3B is a circuit diagram illustrating a circuit of the SMD provided on the display device according to Comparative Example 1.

(7) FIG. 3C is a schematic diagram illustrating arrangement of signal lines and scanning lines of the display device according to Comparative Example 1.

(8) FIG. 4A is a plane view illustrating an example of a configuration of an SMD provided on a display device according to a second embodiment of the present disclosure.

- (9) FIG. 4B is a circuit diagram illustrating an example of a circuit of the SMD provided on the display device according to the second embodiment of the present disclosure.
- (10) FIG. 5A is a plane view illustrating a configuration of an SMD provided on a display device according to Comparative Example 2.
- (11) FIG. 5B is a circuit diagram illustrating a circuit of the SMD provided on the display device according to Comparative Example 2.
- (12) FIG. 6A is a plane view illustrating a configuration of an SMD provided on a display device according to Variation 1.
- (13) FIG. 6B is a circuit diagram illustrating an example of a circuit of the SMD provided on the display device according to Variation 1.
- (14) FIG. 7 is a circuit diagram illustrating an example of a circuit of an SMD provided on a display device according to Variation 2.
- (15) FIG. 8A is a plane view illustrating a first configuration example of a red light source, a green light source, and a blue light source provided on a first pixel.
- (16) FIG. 8B is a cross-sectional view taken along line VIIIB-VIIIB of FIG. 8A.
- (17) FIG. 9 is a cross-sectional view illustrating a second configuration example of the red light source, the green light source, and the blue light source provided on the first pixel.
- (18) FIG. 10A is a plane view illustrating a first variation of a red light source and a green light source provided on the first pixel.
- (19) FIG. 10B is a cross-sectional view taken along line XB-XB of FIG. 10A.
- (20) FIG. 11A is a view illustrating a first variation of a blue light source and a green light source provided on a second pixel.
- (21) FIG. 11B is a cross-sectional view taken along line XIB-XIB of FIG. 11A.
- (22) FIG. 12 is a view illustrating a second variation of a red light source and a green light source provided on the first pixel.
- (23) FIG. 13 is a view illustrating a second configuration example of the blue light source and the green light source provided on the second pixel.

MODE FOR CARRYING OUT THE INVENTION

(24) Embodiments of the present disclosure are described in the following order. Note that, the same or corresponding portions are assigned with the same reference sign throughout all the drawings of the following embodiments. 1 First Embodiment (example of display device in which light sources of three colors form pixels) 2 Second Embodiment (example of display device in which light sources of two colors form pixels) 3 Variation

1 First Embodiment

(25) [Configuration of Display Device]

(26) FIG. 1 is a plane view illustrating an example of a configuration of a display device **10** according to a first embodiment of the present disclosure. The display device **10** is a so-called LED display device, and is provided with a substrate **11**, a plurality of SMDs **12** arranged on the substrate **11**, and a plurality of signal lines **22** and a plurality of scanning lines **23** arranged on the substrate **11**. The display device **10** may further be provided with a driver integrated circuit (IC) arranged on the substrate **11**. The display device **10** may be a fine-pitch display having a pixel pitch of 1 mm or shorter.

(27) (Substrate)

(28) The substrate **11** is, for example, a printed circuit board (PCB). A principal surface of the substrate **11** may have a planar shape or may have a curved shape. The substrate **11** may be a flexible substrate. In this specification, a first direction and a second direction orthogonal to each other in a plane of the substrate **11** are referred to as an X-axis direction and a Y-axis direction, respectively.

(29) (Signal Line, Scanning Line)

(30) The plurality of scanning lines **23** extends in the X-axis direction (first direction). The plurality

of signal lines **22** extends in the Y-axis direction (second direction).

(31) (Driver IC)

(32) The driver IC controls image display of the display device **10** by controlling the plurality of SMDs **12** via the plurality of scanning lines **23** and the plurality of signal lines **22**.

(33) (SMD)

(34) The plurality of SMDs **12** is two-dimensionally arranged on the substrate **11** in the X-axis direction (first direction) and the Y-axis direction (second direction). The two-dimensional arrangement is lattice-shaped arrangement.

(35) FIG. 2A is a plane view illustrating an example of a configuration of the SMD **12**. FIG. 2B is a circuit diagram illustrating an example of a circuit of the SMD **12**. The SMD **12** is an SMD (4in1 SMD) obtained by integrating four pixels into one chip, and is provided with a first pixel **21P1**, a second pixel **21P2**, a third pixel **21P3**, and a fourth pixel **21P4**. In the following description, the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are sometimes referred to as a pixel **21P** in a case where they are not especially distinguished.

(36) A plurality of pixels **21P** is two-dimensionally arranged on the substrate **11** in the X-axis direction and the Y-axis direction. The two-dimensional arrangement is lattice-shaped arrangement. Although FIGS. 1 and 2A illustrate an example in which a basic lattice L in the lattice-shaped arrangement is a square, the shape of the basic lattice L is not limited thereto, and may be a quadrangle such as a rectangle, a rhombus, or a parallelogram. The SMD **12** includes one basic lattice L.

(37) In one basic lattice L, the first pixel **21P1** and the fourth pixel **21P4** are diagonally arranged, and the second pixel **21P2** and the third pixel **21P3** are diagonally arranged. An nth (n is an odd number not smaller than 1) pixel column in the X-axis direction is formed by alternately arranging the first pixel **21P1** and the third pixel **21P3** in the Y-axis direction. An mth (m is an even number not smaller than 2) pixel column in the X-axis direction is formed by alternately arranging the second pixel **21P2** and the fourth pixel **21P4** in the Y-axis direction.

(38) Each pixel **21P** is provided with light sources of three colors. Specifically, each pixel **21P** is provided with a red LED element **20R**, a green LED element **20G**, and a blue LED element **20B**. The red LED element **20R** is an example of a red light source configured to be able to emit red light. The green LED element **20G** is an example of a green light source configured to be able to emit green light. The blue LED element **20B** is an example of a blue light source configured to be able to emit blue light. The red light source is an example of a first color light source configured to be able to emit first color light. The green light source is an example of a second color light source configured to be able to emit second color light. The blue light source is an example of a third color light source configured to be able to emit third color light.

(39) In the first embodiment, an anode provided on each of the red LED element **20R**, the green LED element **20G**, and the blue LED element **20B** is an example of a first electrode, and a cathode provided on each of the red LED element **20R**, the green LED element **20G**, and the blue LED element **20B** is an example of a second electrode.

(40) The SMD **12** is of a cathode common type in which the cathode is a common terminal. The SMD **12** is provided with an anode terminal **24R1**, an anode terminal **24G1**, an anode terminal **24B1**, a cathode terminal (gate terminal) **24GT1**, a cathode terminal (gate terminal) **24GT2**, a cathode terminal (gate terminal) **24GT3**, and a cathode terminal (gate terminal) **24GT4**. The cathode terminal **24GT1**, the cathode terminal **24GT2**, the cathode terminal **24GT3**, and the cathode terminal **24GT4** are the common terminals.

(41) In the first embodiment, the anode terminal **24R1**, the anode terminal **24G1**, and the anode terminal **24B1** are examples of a first terminal, a second terminal, and a third terminal, respectively. The cathode terminal **24GT1**, the cathode terminal **24GT2**, the cathode terminal **24GT3**, and the cathode terminal **24GT4** are examples of a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal, respectively.

(42) The anodes (first electrodes) of the red LED elements **20R** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the anode terminal **24R1**. The cathodes (second electrodes) of the red LED elements **20R** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the cathode terminal **24GT1**, the cathode terminal **24GT2**, the cathode terminal **24GT3**, and the cathode terminal **24GT4**, respectively.

(43) The anodes (first electrodes) of the green LED elements **20G** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the anode terminal **24G1**. The cathodes (second electrodes) of the green LED elements **20G** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the cathode terminal **24GT1**, the cathode terminal **24GT2**, the cathode terminal **24GT3**, and the cathode terminal **24GT4**, respectively.

(44) The anodes (first electrodes) of the blue LED elements **20B** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the anode terminal **24B1**. The cathodes (second electrodes) of the blue LED elements **20B** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the cathode terminal **24GT1**, the cathode terminal **24GT2**, the cathode terminal **24GT3**, and the cathode terminal **24GT4**, respectively.

(45) The anode terminal **24R1**, the anode terminal **24G1**, and the anode terminal **24B1** are connected to different signal lines **22**, respectively. One end of the signal line **22** is connected to a direct current source DC. The cathode terminal **24GT1**, the cathode terminal **24GT2**, the cathode terminal **24GT3**, and the cathode terminal **24GT4** are connected to different scanning lines **23**, respectively. One end of the scanning line **23** is connected to a gate (not illustrated) as a switch. In the cathode common type SMD **12**, a current is applied from a driver into each of the LED elements **20R**, **20G**, and **20B**.

(46) FIG. 2C is a schematic diagram illustrating an example of arrangement of the signal lines **22** and the scanning lines **23** of the display device **10**. The number of signal lines **22** is three for one SMD **12**. More specifically, the number is three for two pixels **21P** arranged in the X-axis direction in one SMD **12**. The three signal lines **22** are connected to the anode terminal **24R1**, the anode terminal **24G1**, and the anode terminal **24B1**, respectively.

(47) The number of scanning lines **23** is four for one SMD **12**. More specifically, the number is four for two pixels **21P** arranged in the Y-axis direction in one SMD **12**. The four scanning lines **23** are made the cathode terminal **24GT1**, the cathode terminal **24GT2**, the cathode terminal **24GT3**, and the cathode terminal **24GT4**, respectively.

(48) [Action and Effect]

(49) Hereinafter, action and effect are described while comparing a display device according to Comparative Example 1 with the display device **10** according to the first embodiment.

(50) FIG. 3A is a plane view illustrating a configuration of an SMD **112** provided on the display device according to Comparative Example 1. FIG. 3B is a circuit diagram illustrating a circuit of the SMD **112** provided on the display device according to Comparative Example 1. FIG. 3C is a schematic diagram illustrating arrangement of signal lines **22** and scanning lines **23** of the display device according to Comparative Example 1.

(51) The display device according to Comparative Example 1 is provided with a plurality of SMDs **112** having following configurations (A1), (B1), and (C1). (A1) Both anodes of red LED elements **20R** included in a first pixel **21P1** and a third pixel **21P3** are connected to an anode terminal **24R1**, and cathodes of the red LED elements **20R** included in the first pixel **21P1** and the third pixel **21P3** are connected to cathode terminals **24GT1** and **24GT2**, respectively. Both the anodes of the red LED elements **20R** included in a second pixel **21P2** and a fourth pixel **21P4** are connected to an anode terminal **24R2**, and the cathodes of the red LED elements **20R** included in the second pixel **21P2** and the fourth pixel **21P4** are connected to the cathode terminals **24GT1** and **24GT2**,

respectively. (B1) Both anodes of green LED elements **20G** included in the first pixel **21P1** and the third pixel **21P3** are connected to an anode terminal **24G1**, and cathodes of the green LED elements **20G** included in the first pixel **21P1** and the third pixel **21P3** are connected to the cathode terminals **24GT1** and **24GT2**, respectively. Both the anodes of the green LED elements **20G** included in the second pixel **21P2** and the fourth pixel **21P4** are connected to an anode terminal **24G2**, and the cathodes of the green LED elements **20G** included in the second pixel **21P2** and the fourth pixel **21P4** are connected to the cathode terminals **24GT1** and **24GT2**, respectively. (C1) Both anodes of blue LED elements **20B** included in the first pixel **21P1** and the third pixel **21P3** are connected to an anode terminal **24B1**, and cathodes of the blue LED elements **20B** included in the first pixel **21P1** and the third pixel **21P3** are connected to the cathode terminals **24GT1** and **24GT2**, respectively. Both the anodes of the blue LED elements **20B** included in the second pixel **21P2** and the fourth pixel **21P4** are connected to an anode terminal **24B2**, and the cathodes of the blue LED elements **20B** included in the second pixel **21P2** and the fourth pixel **21P4** are connected to the cathode terminals **24GT1** and **24GT2**, respectively.

(52) Since the display device according to Comparative Example 1 is provided with the plurality of SMDs **12A** having the above-described configurations (A1), (B1), and (C1), the number of scanning lines **23** is two for one SMD **12A**, but the number of signal lines **22** is six for one SMD **12A**. Therefore, the number of signal lines **22** is large, and it is difficult to provide a margin to L/S of the signal lines **22**.

(53) The display device **10** according to the first embodiment is provided with the plurality of SMDs **12** having the following configurations (A2), (B2), and (C2). (A2) All the anodes of the red LED elements **20R** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the anode terminal **24R1**. The cathodes of the red LED elements **20R** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the cathode terminals **24GT1**, **24GT2**, **24GT3**, and **24GT4**, respectively. (B2) All the anodes of the green LED elements **20G** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the anode terminal **24G1**. The cathodes of the green LED elements **20G** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the cathode terminals **24GT1**, **24GT2**, **24GT3**, and **24GT4**, respectively. (C2) All the anodes of the blue LED elements **20B** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the anode terminal **24B1**. The cathodes of the blue LED elements **20B** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the cathode terminals **24GT1**, **24GT2**, **24GT3**, and **24GT4**, respectively.

(54) Since the display device **10** according to the first embodiment is provided with the plurality of SMDs **12** having the above-described configurations (A2), (B2), and (C2), the number of signal lines **22** is three for one SMD **12**. Therefore, since the number of scanning lines **23** may be halved with respect to the display device according to Comparative Example 1, it is possible to suppress the L/S of the signal lines **22** from being narrowed, to provide a margin to the L/S of the signal lines **22**, and to reduce processes. Therefore, a cost of the substrate **11** such as the PCB may be reduced. Furthermore, by providing the margin to the L/S of the signal lines **22**, it is possible to suppress deterioration in image quality (especially, deterioration in image quality of low gradation luminance of short-time light emission).

(55) The configuration described above is especially effective in the fine-pitch display having the pixel pitch of 1 mm or shorter. This is because, in such fine-pitch display, the L/S of the signal lines has been especially narrow conventionally, and thus the effect obtained in a case where the configuration described above is applied is remarkable.

2 Second Embodiment

(56) [Configuration of Display Device]

(57) FIG. 4A is a plane view illustrating an example of a configuration of an SMD 12A provided on a display device according to a second embodiment. FIG. 4B is a circuit diagram illustrating an example of a circuit of the SMD 12A provided on the display device according to the second embodiment.

(58) Each of a first pixel 25P1, a second pixel 25P2, a third pixel 25P3, and a fourth pixel 25P4 is provided with light sources of two colors. Specifically, each of the first pixel 25P1 and the fourth pixel 25P4 is provided with a red LED element 20R and a green LED element 20G. Each of the second pixel 25P2 and the third pixel 25P3 is provided with a blue LED element 20B and the green LED element 20G.

(59) Since resolution recognition of blue is low (the number of M cone cells is small) in human eyes, even if the blue LED element 20B is thinned out from a first pixel 21P1 and a fourth pixel 21P4 (refer to FIG. 2A) provided with light sources of three colors of the red LED element 20R, the green LED element 20G, and the blue LED element 20B to form the first pixel 25P1 and the fourth pixel 25P4, an influence on a sense of resolution is small. Furthermore, since resolution recognition of red is lower in visibility than that of green, even if the red LED element 20R is thinned out from a second pixel 21P2 and a third pixel 21P3 (refer to FIG. 2A) provided with the light sources of three colors described above to form the second pixel 25P2 and the third pixel 25P3, an influence on the sense of resolution is small.

(60) Anodes (first electrodes) of the red LED elements 20R included in the first pixel 25P1 and the fourth pixel 25P4 are connected to an anode terminal 24R1. Cathodes (second electrodes) of the red LED elements 20R included in the first pixel 25P1 and the fourth pixel 25P4 are connected to a cathode terminal 24GT1 and a cathode terminal 24GT4, respectively.

(61) Anodes (first electrodes) of the blue LED elements 20B included in the second pixel 25P2 and the third pixel 25P3 are connected to an anode terminal 24B1. Cathodes (second electrodes) of the blue LED elements 20B included in the second pixel 25P2 and the third pixel 25P3 are connected to a cathode terminal 24GT2 and a cathode terminal 24GT3, respectively.

(62) The display device according to the second embodiment is similar to the display device 10 according to the first embodiment except for the description above.

(63) [Action and Effect]

(64) Hereinafter, action and effect are described while comparing a display device according to Comparative Example 2 with a display device 10 according to the second embodiment.

(65) FIG. 5A is a plane view illustrating a configuration of an SMD 112A provided on the display device according to Comparative Example 2. FIG. 5B is a circuit diagram illustrating a circuit of the SMD 112A provided on the display device according to Comparative Example 2.

(66) The display device according to Comparative Example 2 is provided with a plurality of SMDs 112A having the following configurations.

(67) Both anodes of green LED elements 20G included in a first pixel 25P1 and a third pixel 25P3 are connected to an anode terminal 24G1. Cathodes of the green LED elements 20G included in the first pixel 25P1 and the third pixel 25P3 are connected to a cathode terminal 24GT1 and a cathode terminal 24GT2, respectively.

(68) Both the anodes of the green LED elements 20G included in a second pixel 25P2 and a fourth pixel 25P4 are connected to an anode terminal 24G2. The cathodes of the green LED elements 20G included in the second pixel 25P2 and the fourth pixel 25P4 are connected to the cathode terminal 24GT1 and the cathode terminal 24GT2, respectively.

(69) Since the display device according to Comparative Example 2 is provided with a plurality of SMDs 12A having the above-described configurations, the number of scanning lines 23 is two for one SMD 12A, but the number of signal lines 22 is four for one SMD 12A. Therefore, the number of scanning lines 23 is large, and it is difficult to provide a margin to L/S of the signal lines 22.

(70) The display device according to the second embodiment is provided with the plurality of SMDs 12A having the following configurations.

(71) All anodes of green LED elements **20G** included in the first pixel **25P1**, the second pixel **25P2**, the third pixel **25P3**, and the fourth pixel **25P4** are connected to an anode terminal **24G1**. Cathodes of the green LED elements **20G** included in the first pixel **25P1**, the second pixel **25P2**, the third pixel **25P3**, and the fourth pixel **25P4** are connected to the cathode terminals **24GT1**, **24GT2**, **24GT3**, and **24GT4**, respectively.

(72) Since the display device according to the second embodiment is provided with the plurality of SMDs **12A** having the above-described configurations, the number of signal lines **22** is three for one SMD **12**. Therefore, since the number of scanning lines **23** may be reduced by one with respect to the display device according to Comparative Example 2, the action and effect similar to those of the display device **10** according to the first embodiment may be obtained.

(73) Furthermore, in the display device according to the second embodiment, the blue LED element **20B** is thinned out from the first pixel **21P1** and the fourth pixel **21P4** (refer to FIG. 2A) of the first embodiment to form the first pixel **25P1** and the fourth pixel **25P4**, respectively. Furthermore, the red LED element **20R** is thinned out from the second pixel **21P2** and the third pixel **21P3** (refer to FIG. 2A) of the first embodiment to form the second pixel **25P2** and the third pixel **25P3**, respectively. Therefore, since the number of LED elements may be reduced, the number of components of the display device may be reduced. Therefore, reliability of the display device may be improved, and a cost of the display device may be reduced. Furthermore, manufacturing processes may be further reduced.

(74) Since each of the first pixel **25P1**, the second pixel **25P2**, the third pixel **25P3**, and the fourth pixel **25P4** is provided with the green LED element **20G** having a high luminosity factor, even if the blue LED element **20B** or the red LED element **20R** is thinned out from the LED elements of three colors, deterioration in sense of resolution (image quality) may be suppressed.

3 Variation

(75) (Variation 1)

(76) In the second embodiment, the example in which the SMD **12A** is provided with the anode terminal **24R1**, the anode terminal **24G1**, and the anode terminal **24B1** (refer to FIG. 4A) has been described; however, as illustrated in FIG. 6A, this may be provided with an anode terminal **24BG** in place of the anode terminal **24B1**. Furthermore, in the second embodiment, the example in which the SMD **12A** is provided with the cathode terminal **24GT1**, the cathode terminal **24GT2**, the cathode terminal **24GT3**, and the cathode terminal **24GT4** (refer to FIG. 4A) has been described; however, as illustrated in FIG. 6A, the SMD **12A** is not necessarily provided with the cathode terminal **24GT4**.

(77) The SMD **12A** having a terminal configuration described above may have the following circuit configuration. An anode of a blue LED element **20B** included in a second pixel **25P2** is connected to the anode terminal **24BG** as illustrated in FIG. 6B instead of being connected to the anode terminal **24B1** (refer to FIG. 4A). A cathode of the blue LED element **20B** included in the second pixel **25P2** is connected to the cathode terminal **24GT1** as illustrated in FIG. 6B instead of being connected to the cathode terminal **24GT2** (refer to FIG. 4A).

(78) The anode of the blue LED element **20B** included in a third pixel **25P3** is connected to the anode terminal **24BG** as illustrated in FIG. 6B instead of being connected to the anode terminal **24B1** (refer to FIG. 4A).

(79) A cathode of a red LED element **20R** included in a fourth pixel **25P4** is connected to the cathode terminal **24GT3** as illustrated in FIG. 6B instead of being connected to the cathode terminal **24GT4** (refer to FIG. 4A). An anode of a green LED element **20G** included in the fourth pixel **25P4** is connected to the anode terminal **24BG** as illustrated in FIG. 6B instead of being connected to the anode terminal **24G1** (refer to FIG. 4A). A cathode of the green LED element **20G** included in the fourth pixel **25P4** is connected to the cathode terminal **24GT2** as illustrated in FIG. 6B instead of being connected to the cathode terminal **24GT4** (refer to FIG. 4A).

(80) In the SMD **12A** having the above-described configuration, since the cathode terminal (gate

terminal) **24GT4** may be reduced, the number of scanning lines **23** for one SMD **12A** may be reduced from four to three.

(81) (Variation 2)

(82) In the first and second embodiments, the example has been described in which the SMD **12** is of the cathode common type in which the cathode is the common terminal, but this may be of an anode common type in which an anode is a common terminal. In an anode common type SMD **12**, a gate (switch) is provided on a common anode side of each of LED elements **20R**, **20G**, and **20B**, it is switched on a power supply side (high potential side), and a current is drawn from each of the LED elements **20R**, **20G**, and **20B** by a current source on a cathode side.

(83) FIG. 7 is a circuit diagram illustrating an example of a circuit of the anode common type SMD **12**. The anode common type SMD **12** is provided with an anode terminal (gate terminal) **26GT1**, an anode terminal (gate terminal) **26GT2**, an anode terminal (gate terminal) **26GT3**, an anode terminal (gate terminal) **26GT4**, a cathode terminal **26R1**, a cathode terminal **26G1**, and a cathode terminal **26B1**. The anode terminal **26GT1**, the anode terminal **26GT2**, the anode terminal **26GT3**, and the anode terminal **26GT4** are the common terminals.

(84) In Variation 2, the cathode terminal **26G1**, the cathode terminal **26G2**, and the cathode terminal **26B2** are examples of a first terminal, a second terminal, and a third terminal, respectively. The anode terminal **26GT1**, the anode terminal **26GT2**, the anode terminal **26GT3**, and the anode terminal **26GT4** are examples of a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal, respectively.

(85) In Variation 2, a cathode provided on each of the red LED element **20R**, the green LED element **20G**, and the blue LED element **20B** is an example of a first electrode, and an anode provided on each of the red LED element **20R**, the green LED element **20G**, and the blue LED element **20B** is an example of a second electrode.

(86) The cathodes (first electrodes) of the red LED elements **20R** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the cathode terminal **26R1**. The anodes (second electrodes) of the red LED elements **20R** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the anode terminal **26GT1**, the anode terminal **26GT2**, the anode terminal **26GT3**, and the anode terminal **26GT4**, respectively.

(87) The cathodes (first electrodes) of the green LED elements **20G** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the cathode terminal **26G1**. The anodes (second electrodes) of the green LED elements **20G** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the anode terminal **26GT1**, the anode terminal **26GT2**, the anode terminal **26GT3**, and the anode terminal **26GT4**, respectively.

(88) The cathodes (first electrodes) of the blue LED elements **20B** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the cathode terminal **26B1**. The anodes (second electrodes) of the blue LED elements **20B** included in the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are connected to the anode terminal **26GT1**, the anode terminal **26GT2**, the anode terminal **26GT3**, and the anode terminal **26GT4**, respectively.

(89) The cathode terminal **26R1**, the cathode terminal **26G1**, and the cathode terminal **26B1** are connected to different signal lines **22**, respectively. The anode terminal **26GT1**, the anode terminal **26GT2**, the anode terminal **26GT3**, and the anode terminal **26GT4** are connected to different scanning lines **23**, respectively. In the anode common type SMD **12**, a current is drawn from each of the LED elements **20R**, **20G**, and **20B** by the driver.

(90) Note that, in the second embodiment also, the SMD **12** may be of the anode common type instead of the cathode common type.

(91) (Variation 3)

(92) In the first embodiment described above, the example has been described in which the red light source, the green light source, and the blue light source provided on the first pixel **21P1**, the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are the red LED element **20R**, the green LED element **20G**, and the blue LED element **20B**, respectively, but the light source is not limited to this example.

(93) FIGS. **8A** and **8B** are views illustrating a first configuration example of a red light source **20RL**, a green light source **20GL**, and a blue light source **20BL** provided on a first pixel **21P1**. Since configurations of the first pixel **21P1**, a second pixel **21P2**, a third pixel **21P3**, and a fourth pixel **21P4** may be made the same as the configuration of the first pixel **21P1**, the description of the configurations of the second pixel **21P2**, the third pixel **21P3**, and the fourth pixel **21P4** are omitted below.

(94) The red light source **20RL** provided on the first pixel **21P1** may include, instead of the red LED element **20R**, a white LED element **20W** and a red filter **20RF** provided on the white LED element **20W**. The white LED element **20W** is configured to be able to emit white light. The red filter **20RF** absorbs light having a specified wavelength among the white light emitted from the white LED element **20W** and transmits red light.

(95) The green light source **20GL** provided on the first pixel **21P1** may include, instead of the green LED element **20G**, the white LED element **20W** and a green filter **20GF** provided on the white LED element **20W**. The green filter **20GF** absorbs light having a specified wavelength among the white light emitted from the white LED element **20W** and transmits green light.

(96) The blue light source **20BL** provided on the first pixel **21P1** may include, instead of the blue LED element **20B**, the white LED element **20W** and a blue filter **20BF** provided on the white LED element **20W**. The blue filter **20BF** absorbs light having a specified wavelength among the white light emitted from the white LED element **20W** and transmits blue light.

(97) FIG. **9** is a view illustrating a second configuration example of the red light source **20RL**, the green light source **20GL**, and the blue light source **20BL** provided on the first pixel **21P1**. The red light source **20RL** provided on the first pixel **21P1** may include, instead of the red LED element **20R**, the blue LED element **20B** and a color conversion layer **20RQ** provided on the blue LED element **20B**. The color conversion layer **20RQ** converts the blue light emitted from the blue LED element **20B** into the red light. The color conversion layer **20RQ** is, for example, a quantum dot (QD).

(98) The green light source **20GL** provided on the first pixel **21P1** may include, instead of the green LED element **20G**, the blue LED element **20B** and a color conversion layer **20GQ** provided on the blue LED element **20B**. The color conversion layer **20GQ** converts the blue light emitted from the blue LED element **20B** into the green light. The color conversion layer **20GQ** is, for example, a quantum dot.

(99) The blue light source **20BL** is the blue LED element **20B** as in the first embodiment.

(100) (Variation 4)

(101) In the second embodiment described above, the example has been described in which the red light source and the green light source provided on the first pixel **25P1** and the fourth pixel **25P4** are the red LED element **20R** and the green LED element **20G**, respectively, and the blue light source and the green light source provided on the second pixel **25P2** and the third pixel **25P3** are the blue LED element **20B** and the green LED element **20G**, respectively, but the light source is not limited to this example.

(102) FIGS. **10A** and **10B** are views illustrating a first variation of a red light source **20RL** and a green light source **20GL** provided on a first pixel **25P1**. Since a configuration of a fourth pixel **25P4** may be made the same as that of the first pixel **25P1**, the description of the configuration of the fourth pixel **25P4** is omitted below.

(103) The red light source **20RL** provided on the first pixel **25P1** may include, instead of the red LED element **20R**, a white LED element **20W** and a red filter **20RF** provided on the white LED

element **20W**.

(104) The green light source **20GL** provided on the first pixel **25P1** may include, instead of the green LED element **20G**, the white LED element **20W** and a green filter **20GF** provided on the white LED element **20W**.

(105) FIGS. **11A** and **11B** are views illustrating a first variation of a blue light source **20BL** and the green light source **20GL** provided on a second pixel **25P2**. Since a configuration of a third pixel **25P3** may be made the same as that of the second pixel **25P2**, the description of the configuration of the third pixel **25P3** is omitted below.

(106) The blue light source **20BL** provided on the second pixel **25P2** may include, instead of the blue LED element **20B**, the white LED element **20W** and a blue filter **20BF** provided on the white LED element **20W**.

(107) The green light source **20GL** provided on the second pixel **25P2** may include, instead of the green LED element **20G**, the white LED element **20W** and the green filter **20GF** provided on the white LED element **20W**.

(108) FIG. **12** is a view illustrating a second variation of the red light source **20RL** and the green light source **20GL** provided on the first pixel **25P1**. The red light source **20RL** provided on the first pixel **25P1** may include, instead of the red LED element **20R**, the blue LED element **20B** and a color conversion layer **20RQ** provided on the blue LED element **20B**. The color conversion layer **20RQ** is as described in Variation 3.

(109) The green light source **20GL** provided on the first pixel **25P1** may include, instead of the green LED element **20G**, the blue LED element **20B** and a color conversion layer **20GQ** provided on the blue LED element **20B**. The color conversion layer **20GQ** is as described in Variation 3.

(110) FIG. **13** is a view illustrating a second configuration example of the blue light source **20BL** and the green light source **20GL** provided on the second pixel **25P2**. The blue light source **20BL** provided on the second pixel **25P2** is the blue LED element **20B** as in the first embodiment.

(111) The green light source **20GL** provided on the second pixel **25P2** may include, instead of the green LED element **20G**, the blue LED element **20B** and a color conversion layer **20GQ** provided on the blue LED element **20B**. The color conversion layer **20GQ** is as described in Variation 3.

(112) Although the first and second embodiments and the variations thereof of the present disclosure are specifically described above, the present disclosure is not limited to the above-described first and second embodiments and variations, and various modifications based on the technical idea of the present disclosure may be made.

(113) For example, the configuration, method, shape and the like described in the above-described first and second embodiments and variations are merely examples, and the configuration, method, shape and the like different from those may also be used as necessary.

(114) The configuration, method, shape and the like of the above-described first and second embodiments and variations thereof may be combined with one another without departing from the gist of the present disclosure.

(115) Furthermore, the present disclosure may also adopt the following configurations.

(116) (1)

(117) A display device provided with: a substrate; a plurality of surface mount devices two-dimensionally arranged on the substrate in a first direction and a second direction; and a plurality of signal lines and a plurality of scanning lines arranged on the substrate, in which a surface mount device is provided with four pixels, each of the four pixels is provided with light sources of three colors, and each of the light sources of three colors includes a light emitting diode element, a plurality of the scanning lines extends in the first direction, a plurality of the signal lines extends in the second direction, the number of the signal lines is three for two pixels arranged in the first direction, and the number of the scanning lines is four for two pixels arranged in the second direction.

(2)

(118) The display device according to (1), in which the light sources of three colors are a red light source, a green light source, and a blue light source.

(119) (3)

(120) The display device according to (2), in which the light emitting diode element included in the red light source is a red light emitting diode element, the light emitting diode element included in the green light source is a green light emitting diode element, and the light emitting diode element included in the blue light source is a blue light emitting diode element.

(4)

(121) The display device according to any one of (1) to (3), in which each of the light sources of three colors further includes a filter provided on the light emitting diode element.

(122) (5)

(123) The display device according to (1) or (2), in which each of light sources of two colors of the light sources of three colors further includes a color conversion layer provided on the light emitting diode element.

(124) (6)

(125) The display device according to (5), in which the light emitting diode element is a blue light emitting diode element, and the light sources of two colors are a red light source and a green light source.

(7)

(126) The display device according to (1), in which the surface mount device further is further provided with: a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal connected to different scanning lines, respectively.

(8)

(127) The display device according to (7), in which the light sources of three colors are a first color light source, a second color light source, and a third color light source, the four pixels is provided with a first pixel, a second pixel, a third pixel, and a fourth pixel, first electrodes of first color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel, respectively, are connected to the first terminal, second electrodes of the first color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel are connected to the fourth terminal, the fifth terminal, the sixth terminal, and the seventh terminal, respectively, first electrodes of second color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel respectively, are connected to the second terminal, second electrodes of the second color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel are connected to the fourth terminal, the fifth terminal, the sixth terminal, and the seventh terminal, respectively, first electrodes of third color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel, respectively, are connected to the third terminal, and second electrodes of the third color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel are connected to the fourth terminal, the fifth terminal, the sixth terminal, and the seventh terminal, respectively.

(9)

(128) The display device according to (8), in which the first color light source, the second color light source, and the third color light source are a red light source, a green light source, and a blue light source, respectively.

(129) (10)

(130) A display device provided with: a substrate; a plurality of surface mount devices two-dimensionally arranged on the substrate in a first direction and a second direction; and a plurality of signal lines and a plurality of scanning lines arranged on the substrate, in which a surface mount device is provided with four pixels, each of the four pixels is provided with light sources of two colors, and each of the light sources of two colors includes a light emitting diode element, a

plurality of the scanning lines extends in the first direction, a plurality of the signal lines extends in the second direction, the number of the signal lines is three for two pixels arranged in the first direction, and the number of the scanning lines is three or four for two pixels arranged in the second direction.

(11)

(131) The display device according to (10), in which the four pixels is provided with a first pixel, a second pixel, a third pixel, and a fourth pixel, the first pixel and the fourth pixel are diagonally arranged, and the second pixel and the third pixel are diagonally arranged.

(12)

(132) The display device according to (11), in which the light sources of two colors included in the first pixel and the fourth pixel are a first color light source and a second color light source, and the light sources of two colors included in the second pixel and the third pixel are the second color light source and a third color light source.

(13)

(133) The display device according to (12), in which the first color light source, the second color light source, and the third color light source are a red light source, a green light source, and a blue light source, respectively.

(134) (14)

(135) The display device according to (12) or (13), in which the number of the scanning lines is four for two pixels arranged in the second direction, and the surface mount device is further provided with: a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal connected to different scanning lines, respectively.

(15)

(136) The display device according to (14), in which first electrodes of first color light sources provided on the first pixel and the fourth pixel, respectively, are connected to the first terminal, second electrodes of the first color light sources provided on the first pixel and the fourth pixel are connected to the fourth terminal and the seventh terminal, respectively, first electrodes of second color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel, respectively, are connected to the second terminal, second electrodes of the second color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel are connected to the fourth terminal, the fifth terminal, the sixth terminal, and the seventh terminal, respectively, first electrodes of third color light sources provided on the second pixel and the third pixel, respectively, are connected to the third terminal, and second electrodes of the third color light sources provided on the second pixel and the third pixel are connected to the fifth terminal and the sixth terminal, respectively.

(16)

(137) The display device according to (12) or (13), in which the number of the scanning lines is three for two pixels arranged in the second direction, and the surface mount device is further provided with: a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, and a sixth terminal connected to different scanning lines, respectively.

(17)

(138) The display device according to (16), in which first electrodes of first color light sources provided on the first pixel and the fourth pixel, respectively, are connected to the first terminal, second electrodes of the first color light sources provided on the first pixel and the fourth pixel are connected to the fourth terminal and the sixth terminal, respectively, first electrodes of second color light sources provided on the first pixel, the second pixel, and the third pixel, respectively, are connected to the second terminal, second electrodes of the second color light sources provided on the first pixel, the second pixel, and the third pixel are connected to the fourth terminal, the fifth

terminal, and the sixth terminal, respectively, a first electrode of the second color light source included in the fourth pixel is connected to the third terminal, and a second electrode of the second color light source included in the fourth pixel is connected to the fifth terminal, first electrodes of third color light sources provided on the second pixel and the third pixel, respectively, are connected to the third terminal, and second electrodes of the third color light sources provided on the second pixel and the third pixel are connected to the fourth terminal and the sixth terminal, respectively.

(18)

(139) A surface mount device used in a display device, the surface mount device provided with: four pixels; a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal connected to different scanning lines, respectively, in which each of the four pixels is provided with light sources of three colors, and each of the light sources of three colors includes a light emitting diode element.

(19)

(140) A surface mount device used in a display device, the surface mount device provided with: four pixels; a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal connected to different scanning lines, respectively, in which each of the four pixels is provided with light sources of two colors, and each of the light sources of two colors includes a light emitting diode element.

(20)

(141) A surface mount device used in a display device, the surface mount device provided with: four pixels; a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, and a sixth terminal connected to different scanning lines, respectively, in which each of the four pixels is provided with light sources of two colors, and each of the light sources of two colors includes a light emitting diode element.

REFERENCE SIGNS LIST

(142) **10** Display device **11** Substrate **12, 12A, 112, 112A** SMD **20R** Red LED element **20G** Green LED element **20B** Blue LED element **20Y** Yellow LED element **20W** White LED element **20RL** Red light source **20GL** Green light source **20BL** Blue light source **20RF** Red filter **20GF** Green filter **20BF** Blue filter **20RQ, 20GQ** Color conversion layer **21P1, 25P1** First pixel **21P2, 25P2** Second pixel **21P3, 25P3** Third pixel **21P4, 25P4** Fourth pixel **22** Signal line **23** Scanning line **24R1, 24R2, 24G1, 24G2, 24B1, 24B2, 24BG** Anode terminal **24GT1, 24GT2, 24GT3, 24GT4** Cathode terminal **25R1, 25R2, 25R3** Cathode terminal **25GT1, 25GT2, 25GT3, 25GT4** Anode terminal **DC** Direct current source

Claims

1. A display device comprising: a substrate; a plurality of surface mount devices two-dimensionally arranged on the substrate in a first direction and a second direction; and a plurality of signal lines and a plurality of scanning lines arranged on the substrate, wherein a surface mount device is provided with four pixels, each of the four pixels is provided with light sources of three colors, and each of the light sources of three colors includes a light emitting diode element, a plurality of the scanning lines extends in the first direction, a plurality of the signal lines extends in the second direction, a number of the signal lines is three for two pixels arranged in the first direction, and a number of the scanning lines is four for two pixels arranged in the second direction.
2. The display device according to claim 1, wherein the light sources of three colors are a red light source, a green light source, and a blue light source.
3. The display device according to claim 2, wherein the light emitting diode element included in the

red light source is a red light emitting diode element, the light emitting diode element included in the green light source is a green light emitting diode element, and the light emitting diode element included in the blue light source is a blue light emitting diode element.

4. The display device according to claim 1, wherein each of the light sources of three colors further includes a filter provided on the light emitting diode element.

5. The display device according to claim 1, wherein each of light sources of two colors of the light sources of three colors further includes a color conversion layer provided on the light emitting diode element.

6. The display device according to claim 5, wherein the light emitting diode element is a blue light emitting diode element, and the light sources of two colors are a red light source and a green light source.

7. The display device according to claim 1, wherein the surface mount device further is further provided with: a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal connected to different scanning lines, respectively.

8. The display device according to claim 7, wherein the light sources of three colors are a first color light source, a second color light source, and a third color light source, the four pixels is provided with a first pixel, a second pixel, a third pixel, and a fourth pixel, first electrodes of first color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel, respectively, are connected to the first terminal, second electrodes of the first color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel are connected to the fourth terminal, the fifth terminal, the sixth terminal, and the seventh terminal, respectively, first electrodes of second color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel respectively, are connected to the second terminal, second electrodes of the second color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel are connected to the fourth terminal, the fifth terminal, the sixth terminal, and the seventh terminal, respectively, first electrodes of third color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel, respectively, are connected to the third terminal, and second electrodes of the third color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel are connected to the fourth terminal, the fifth terminal, the sixth terminal, and the seventh terminal, respectively.

9. The display device according to claim 8, wherein the first color light source, the second color light source, and the third color light source are a red light source, a green light source, and a blue light source, respectively.

10. A display device comprising: a substrate; a plurality of surface mount devices two-dimensionally arranged on the substrate in a first direction and a second direction; and a plurality of signal lines and a plurality of scanning lines arranged on the substrate, wherein a surface mount device is provided with four pixels, each of the four pixels is provided with light sources of two colors, and each of the light sources of two colors includes a light emitting diode element, a plurality of the scanning lines extends in the first direction, a plurality of the signal lines extends in the second direction, a number of the signal lines is three for two pixels arranged in the first direction, and a number of the scanning lines is three or four for two pixels arranged in the second direction.

11. The display device according to claim 10, wherein the four pixels is provided with a first pixel, a second pixel, a third pixel, and a fourth pixel, the first pixel and the fourth pixel are diagonally arranged, and the second pixel and the third pixel are diagonally arranged.

12. The display device according to claim 11, wherein the light sources of two colors included in the first pixel and the fourth pixel are a first color light source and a second color light source, and the light sources of two colors included in the second pixel and the third pixel are the second color light source and a third color light source.

13. The display device according to claim 12, wherein the first color light source, the second color light source, and the third color light source are a red light source, a green light source, and a blue light source, respectively.

14. The display device according to claim 12, wherein a number of the scanning lines is four for two pixels arranged in the second direction, and the surface mount device is further provided with: a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal connected to different scanning lines, respectively.

15. The display device according to claim 14, wherein first electrodes of first color light sources provided on the first pixel and the fourth pixel, respectively, are connected to the first terminal, second electrodes of the first color light sources provided on the first pixel and the fourth pixel are connected to the fourth terminal and the seventh terminal, respectively, first electrodes of second color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel, respectively, are connected to the second terminal, second electrodes of the second color light sources provided on the first pixel, the second pixel, the third pixel, and the fourth pixel are connected to the fourth terminal, the fifth terminal, the sixth terminal, and the seventh terminal, respectively, first electrodes of third color light sources provided on the second pixel and the third pixel, respectively, are connected to the third terminal, and second electrodes of the third color light sources provided on the second pixel and the third pixel are connected to the fifth terminal and the sixth terminal, respectively.

16. The display device according to claim 12, wherein a number of the scanning lines is three for two pixels arranged in the second direction, and the surface mount device is further provided with: a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, and a sixth terminal connected to different scanning lines, respectively.

17. The display device according to claim 16, wherein first electrodes of first color light sources provided on the first pixel and the fourth pixel, respectively, are connected to the first terminal, second electrodes of the first color light sources provided on the first pixel and the fourth pixel are connected to the fourth terminal and the sixth terminal, respectively, first electrodes of second color light sources provided on the first pixel, the second pixel, and the third pixel, respectively, are connected to the second terminal, second electrodes of the second color light sources provided on the first pixel, the second pixel, and the third pixel are connected to the fourth terminal, the fifth terminal, and the sixth terminal, respectively, a first electrode of the second color light source included in the fourth pixel is connected to the third terminal, and a second electrode of the second color light source included in the fourth pixel is connected to the fifth terminal, first electrodes of third color light sources provided on the second pixel and the third pixel, respectively, are connected to the third terminal, and second electrodes of the third color light sources provided on the second pixel and the third pixel are connected to the fourth terminal and the sixth terminal, respectively.

18. A surface mount device used in a display device, the surface mount device comprising: four pixels; a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal connected to different scanning lines, respectively, wherein each of the four pixels is provided with light sources of three colors, and each of the light sources of three colors includes a light emitting diode element.

19. A surface mount device used in a display device, the surface mount device comprising: four pixels; a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, a sixth terminal, and a seventh terminal connected to different scanning lines, respectively, wherein each of the four pixels is provided with light sources of two colors, and each of the light sources of two colors includes a light emitting

diode element.

20. A surface mount device used in a display device, the surface mount device comprising: four pixels; a first terminal, a second terminal, and a third terminal connected to different signal lines, respectively; and a fourth terminal, a fifth terminal, and a sixth terminal connected to different scanning lines, respectively, wherein each of the four pixels is provided with light sources of two colors, and each of the light sources of two colors includes a light emitting diode element.
