

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250248585

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

TAKAHASHI; Ikuma et al.

INFORMATION PROCESSING APPARATUS, CONTROL METHOD, AND PROGRAM

Abstract

An information processing apparatus (2000) detects an abnormal region (30) from a moving image frame (14). The abnormal region (30) is a region that is estimated to represent an abnormal part inside a body of a subject. The information processing apparatus (2000) generates and outputs output information based on the number of detected abnormal regions (30).

Inventors: TAKAHASHI; Ikuma (Tokyo, JP), SANO; Baki (Tokyo, JP), TAKOH; Kimiyasu (Tokyo, JP), OKUTSU; Motoyasu (Tokyo, JP), TANAKA; Chiemi (Tokyo, JP), SAIKOU; Masahiro (Tokyo, JP), IMAOKA; Hitoshi (Tokyo, JP), KAMIJO; Kenichi (Tokyo, JP), HAMAMOTO; Ryuji (Tokyo, JP), SAITO; Yutaka (Tokyo, JP), YAMADA; Masayoshi (Tokyo, JP)

Applicant: NEC CORPORATION (Tokyo, JP); NATIONAL CANCER CENTER (Tokyo, JP)

Family ID: 69778318

Assignee: NEC CORPORATION (Tokyo, JP); NATIONAL CANCER CENTER (Tokyo, JP)

Appl. No.: 19/184819

Filed: April 21, 2025

Foreign Application Priority Data

| | | |
|----|-------------|---------------|
| JP | 2018-169722 | Sep. 11, 2018 |
|----|-------------|---------------|

Related U.S. Application Data

parent US continuation 18601521 20240311 parent-grant-document US 12295545 child US 19184819

Publication Classification

Int. Cl.: **A61B1/00** (20060101); **G06T7/00** (20170101); **H04N5/272** (20060101)

U.S. Cl.:

CPC **A61B1/000094** (20220201); **A61B1/0005** (20130101); **G06T7/0012** (20130101);
H04N5/272 (20130101); G06T2207/10068 (20130101); G06T2207/30096 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a Continuation of U.S. application Ser. No. 18/601,521, filed on Mar. 11, 2024, which is Continuation of U.S. application Ser. No. 17/274,713, filed on Mar. 9, 2021, now U.S. Pat. No. 11,957,300 issued on Apr. 16, 2024, which is a National Stage of International Application No. PCT/JP2019/035158 filed Sep. 6, 2019, claiming priority based on Japanese Patent Application No. 2018-169722 filed Sep. 11, 2018, the contents of all of which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

[0002] The present invention relates to an examination of an inside of a body of a person or other animals using a captured image.

BACKGROUND ART

[0003] An examination is performed to find out whether or not there is an abnormality inside a body using an image in which an inside of a body of a person or an animal is imaged. As an example, an endoscope examination is known. In the endoscope examination, a physician inserts a scope provided with a camera at a tip from a nose, a mouth, an anus, or the like of a subject and moves the scope inside a body. In this manner, a state inside the body is imaged by the camera. The physician checks whether or not an abnormal part exists inside the body of the subject while viewing the state inside the body being imaged by the camera using moving image displayed on the display apparatus.

[0004] A technique that supports an examination using such an image has been developed. For example, Patent Document 1 discloses a technique that detects a lesion from an image and changes the detected lesion to a color tone different from other parts, thereby enabling easy discrimination of the lesion from other parts. Patent Document 2 discloses a technique that detects a lesion included in an image, computes a degree of seriousness of the lesion, and applies a mark indicating a position or the degree of seriousness of the lesion to the image. Patent Document 3 discloses a technique that, when a lesion is detected from an image, outputs an icon relating to the lesion in a display aspect according to the size of the lesion.

RELATED DOCUMENTS

Patent Documents

[0005] [Patent Document 1] Japanese Patent Application Publication No. 2017-060806 [0006]
[Patent Document 2] Japanese Patent Application Publication No. 2016-158681 [0007] [Patent
Document 3] Japanese Patent Application Publication No. 2015-112429

SUMMARY OF THE INVENTION

Technical Problem

[0008] In the method in which the examination is performed by moving the camera inside the body

of the subject, since the camera is moved inside the body, a part that can be observed by the physician changes over time. For this reason, the physician may miss an abnormal part, and there is actually a difference in lesion detection rate depending on physicians in charge of the examination. Accordingly, in order to improve the quality of the examination using an image in which the inside of the body of the subject is imaged, there is demand for various techniques that support the examination.

[0009] The present invention has been accomplished in view of the above-described problem. An object of the present invention is to provide a new technique that improves quality of an examination using an image in which an inside of a body of a subject is imaged.

Solution to Problem

[0010] An information processing apparatus of the present invention includes 1) a detection unit that detects an abnormal region inside a body from a captured image in which the inside of the body is imaged, and 2) an output unit that generates output information based on the number of the abnormal regions and outputs the generated output information.

[0011] A control method of the present invention is executed by a computer. The control method includes 1) a detection step of detecting an abnormal region inside a body from a captured image in which the inside of the body is imaged, and 2) an output step of generating output information based on the number of the abnormal regions and outputting the generated output information.

[0012] A program of the present invention causes a computer to execute each step of the control method of the present invention.

Advantageous Effects of Invention

[0013] According to the present invention, there is provided a new technique that improves the quality of the examination using an image in which the inside of the body of the subject is imaged.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] FIG. 1 is a diagram conceptually illustrating an information processing apparatus of Example Embodiment 1.

[0015] FIG. 2 is a block diagram illustrating the functional configuration of the information processing apparatus.

[0016] FIG. 3 is a diagram illustrating a computer for implementing the information processing apparatus.

[0017] FIG. 4 is a diagram showing a specific example of a usage environment of the information processing apparatus.

[0018] FIG. 5 is a flowchart illustrating a flow of processing that is executed by the information processing apparatus of Example Embodiment 1.

[0019] FIG. 6 is a diagram illustrating output information indicating the number of detections.

[0020] FIG. 7 is a diagram illustrating output information indicating the number of detections.

[0021] FIG. 8 is diagram illustrating output information indicating the number of detections.

[0022] FIG. 9 is a diagram illustrating variation of highlighting.

[0023] FIG. 10 is a diagram illustrating variation of highlighting.

[0024] FIG. 11A-11F are diagrams illustrating marks that are applied to abnormal regions.

DESCRIPTION OF EMBODIMENTS

[0025] Hereinafter, an example embodiment of the present invention will be described referring to the drawings. In all drawings, the same components are represented by the same reference numerals, and description thereof will not be repeated. In respective block diagrams, unless particular description is provided, each block is not a configuration of a hardware unit but a configuration of a function unit.

Example Embodiment 1

[0026] FIG. 1 is a diagram conceptually illustrating an information processing apparatus **2000** of Example Embodiment 1. It should be noted that FIG. 1 merely shows an example of the operation for ease of understanding of the information processing apparatus **2000**, and is not intended to limit the functions of the information processing apparatus **2000**.

[0027] A camera **10** is used for an examination of a person or other animals. Hereinafter, a person or the like to be examined is referred to as a subject. The camera **10** is any camera that can image an inside of a body of the subject, and generates a moving image frame **14** representing an imaging result. For example, the camera **10** is an endoscope camera. Moving image data **12** is composed of a plurality of moving image frames **14** generated at different times.

[0028] A user (for example, a physician) of the information processing apparatus **2000** recognizes a state inside the body of the subject by viewing moving image data **12**. More specifically, the user recognizes whether or not there is an abnormal part inside the body of the subject, a degree of abnormality, or the like. Here, “abnormal part inside the body” is, for example, a part having a lesion, a part having a wound, a part having a foreign substance, or the like. The lesion is a change in a living body caused by a disease, and is, for example, a tumor or the like.

[0029] Here, useful information obtained by analyzing moving image data **12** is provided, whereby improvement of the accuracy of an endoscope examination or the like can be expected. For example, in the endoscope examination, the physician or the like searches for an abnormal part inside the body while observing the inside of the body of the subject with the camera. In this case, even though an abnormal part is imaged by the camera, the physician may miss the abnormal part. For this reason, it is preferable to perform support such that the physician easily recognizes the abnormal part, and to prevent missing of the abnormal part.

[0030] Accordingly, the information processing apparatus **2000** of the example embodiment performs the following operation. First, the information processing apparatus **2000** acquires moving image data **12** and performs image analysis on the moving image frame **14** composing moving image data **12**. Specifically, the information processing apparatus **2000** detects an abnormal region **30** from the moving image frame **14**. The abnormal region **30** is a region that is presumed to represent an abnormal part inside the body of the subject. For example, the abnormal region **30** of FIG. 1 is a region including a tumor (a region representing a lesion). Then, the information processing apparatus **2000** outputs output information based on the number of detected abnormal regions **30**.

[0031] The information processing apparatus **2000** performs an output based on the number of abnormal regions **30**, thereby making the physician or the like recognize that the number of abnormal regions **30** is not one but is plural or the number of abnormal regions **30** is large. For example, in FIG. 1, the information processing apparatus **2000** processes the moving image frame **14** so as to superimpose a frame **80** on the abnormal region **30**, and then, displays the moving image frame **14** on a display apparatus **20**. In this case, the thickness of the frame **80** in a case where the number of abnormal regions **30** detected from the moving image frame **14** is plural is made thicker than the thickness of the frame **80** in a case where the number of abnormal regions **30** detected from the moving image frame **14** is one. With this, the physician or the like who views the moving image frame **14** can intuitively recognize that a plurality of abnormal regions **30** are detected.

[0032] In this way, with the information processing apparatus **2000**, since the output information according to the number of abnormal regions **30** is output, the physician or the like who views the moving image frame **14** can easily recognize information relating to the number of abnormal regions **30**. With this, an effect that the physician or the like can be prevented from missing the abnormal region **30** or an effect that the physician or the like can efficiently observe the abnormal region **30** is achieved. Then, an effect that the quality of the examination by the physician or the like is improved is obtained from such an effect.

[0033] Hereinafter, the example embodiment will be described in more detail.

<Functional Configuration>

[0034] FIG. 2 is a block diagram illustrating the functional configuration of the information processing apparatus **2000**. The information processing apparatus **2000** includes a detection unit **2020** and an output unit **2040**. The detection unit **2020** detects the abnormal region **30** from the moving image frame **14**. The output unit **2040** outputs the output information based on the number of detected abnormal regions **30**.

<Example of Hardware Configuration of Information Processing Apparatus **2000**>

[0035] Each functional component of the information processing apparatus **2000** may be implemented by hardware (for example, a hard-wired electronic circuit or the like) that implements each functional component or may be implemented by a combination of hardware and software (for example, a combination of an electronic circuit and a program that controls the electronic circuit, or the like). Hereinafter, a case where each functional component of the information processing apparatus **2000** is implemented by a combination of hardware and software will be further described.

[0036] FIG. 3 is a diagram illustrating a computer **1000** for implementing the information processing apparatus **2000**. The computer **1000** is any computer. For example, the computer **1000** is a stationary computer, such as a personal computer (PC) or a server machine. In addition, for example, the computer **1000** is a portable computer, such as a smartphone or a tablet terminal. The computer **1000** may be a dedicated computer designed in order to implement the information processing apparatus **2000** or may be a general-purpose computer.

[0037] The computer **1000** has a bus **1020**, a processor **1040**, a memory **1060**, a storage device **1080**, an input-output interface **1100**, and a network interface **1120**. The bus **1020** is a data transmission path through which the processor **1040**, the memory **1060**, the storage device **1080**, the input-output interface **1100**, and the network interface **1120** transmit and receive data from one another. However, a method of connecting the processor **1040** and the like to one another is not limited to bus connection.

[0038] A processor **1040** is various processors, such as a central processing unit (CPU), a graphics processing unit (GPU), and a field-programmable gate array (FPGA). A memory **1060** is a main storage that is implemented using a random access memory (RAM) or the like. A storage device **1080** is an auxiliary storage that is implemented using a hard disk, a solid state drive (SSD), a memory card, or a read only memory (ROM).

[0039] The input-output interface **1100** is an interface that connects the computer **1000** and an input-output device. For example, the camera **10** or the display apparatus **20** is connected to the input-output interface **1100**.

[0040] The network interface **1120** is an interface that connects the computer **1000** to a communication network. The communication network is, for example, a local area network (LAN) or a wide area network (WAN). A method in which the network interface **1120** is connected to the communication network may be wireless connection or may be wired connection.

[0041] The storage device **1080** stores a program module that implements each functional component of the information processing apparatus **2000**. The processor **1040** reads each program module to the memory **1060** and executes each program module, thereby implementing a function corresponding to each program module.

<Specific Example of Usage Environment of Information Processing Apparatus **2000**>

[0042] FIG. 4 is a diagram illustrating a specific example of a usage environment of the information processing apparatus **2000**. For example, the information processing apparatus **2000** is used along with the scope **40** and the endoscope system **50**. The scope **40** is connected to the endoscope system **50**. The scope **40** is provided with the camera **10**. In this case, moving image data **12** is composed of a plurality of moving image frames **14** generated by the camera **10** provided in the scope **40**. The endoscope system **50** outputs moving image data **12** to the information

processing apparatus **2000**. For example, moving image data **12** is output from an interface for video output (for example, a High-Definition Multimedia Interface (HDMI) (Registered Trademark) interface) provided in the endoscope system **50** to an interface for video input in the information processing apparatus **2000**. Then, the information processing apparatus **2000** processes moving image data **12** acquired from the endoscope system **50** to generate the output information. [0043] Here, as described below, the output information may be display that is performed using the display apparatus **20** or may be other kinds. In the former case, the information processing apparatus **2000** performs control on the display apparatus **20** such that moving image data **12** is displayed on the display apparatus **20** along with the output information. On the other hand, in the latter case, the processing of displaying moving image data **12** on the display apparatus **20** may be executed by the information processing apparatus **2000** or may be executed by another apparatus (for example, the endoscope system **50**). In a case where the processing of displaying moving image data **12** on the display apparatus **20** is executed by the endoscope system **50**, the display apparatus **20** does not need to be connected to the information processing apparatus **2000**.

[0044] The configuration shown in FIG. **4** is merely illustrative, and the usage environment of the information processing apparatus **2000** is not limited to the configuration shown in FIG. **4**. For example, the information processing apparatus **2000** may be provided inside the camera **10**, the endoscope system **50**, or the display apparatus **20**. In addition, for example, moving image data **12** may be output from the camera **10** to the information processing apparatus **2000**. In this case, the information processing apparatus **2000** may not be connected to the endoscope system **50**.

<Flow of Processing>

[0045] FIG. **5** is a flowchart illustrating a flow of processing that is executed by the information processing apparatus **2000** of Example Embodiment 1. The detection unit **2020** acquires the moving image frame **14** (S102). The detection unit **2020** detects the abnormal region **30** from the acquired moving image frame **14** (S104). The output unit **2040** outputs the output information based on the number of detected abnormal regions **30** (S106).

[0046] There are various timings at which a series of processing shown in FIG. **5** is executed. For example, the information processing apparatus **2000** executes the series of processing shown in FIG. **5** each time the moving image frame **14** is generated by the camera **10**. In addition, for example, the information processing apparatus **2000** may acquire moving image data **12** from a storage apparatus at a predetermined timing and may execute the series of processing shown in FIG. **5** on each of a plurality of moving image frames **14** composing moving image data **12** (may execute so-called batch processing).

<Acquisition of Moving Image Data **12**: S102>

[0047] Any method in which the detection unit **2020** acquires moving image data **12** may be used. For example, the detection unit **2020** accesses the storage apparatus in which moving image data **12** is stored, thereby acquiring moving image data **12**. The storage apparatus in which moving image data **12** is stored may be provided inside the camera **10** or may be provided outside the camera **10**. Alternatively, for example, the detection unit **2020** may receive moving image data **12** transmitted from the camera **10**, thereby acquiring moving image data **12**. In addition, the detection unit **2020** may acquire moving image data **12** from another apparatus (for example, the above-described endoscope system **50**) connected to the camera **10**.

<Detection of Abnormal Region **30**: S104>

[0048] The detection unit **2020** detects the abnormal region **30** from each moving image frame **14** composing moving image data **12**. Here, an existing technique can be used as a technique that analyzes the image, in which the inside of the body is imaged, to detect the abnormal part. For example, a method, such as feature value matching or template matching, can be used. For example, in a case of detecting a tumor by feature value matching, one or more values (feature values) representing a feature of an appearance (color, pattern, shape, or the like) of the tumor are defined in advance. The detection unit **2020** detects an image region having high similarity to the

feature value of the tumor defined in advance from among image regions of the moving image frame **14**. Then, the detection unit **2020** handles the detected image region as an image region representing the abnormal region **30**. The same method can be employed in a case of detecting a wound or a foreign substance.

[0049] In addition, for example, a detector that detects the abnormal region **30** from the moving image frame **14** may be generated by machine learning, and the abnormal region **30** may be detected using the detector. As a model of the detector, various models, such as a neural network or a support vector machine, can be employed. It should be noted that an existing technique can be used as a technique that generates a detector, which detects a region having a specific feature from an image, by machine learning.

[0050] It should be noted that, in a case where a foreign substance is desired to be detected, it is assumed that a foreign substance which entered the inside of the body is identified. In this case, it is preferable that a feature value of the foreign substance can be specified to the information processing apparatus **2000**. For example, a photograph of the foreign substance which entered the inside of the body is input to the information processing apparatus **2000**. The information processing apparatus **2000** performs image analysis on the photograph, thereby computing the feature value of the foreign substance to be detected. Then, the detection unit **2020** detects the foreign substance having the computed feature value from the moving image frame **14**.

<Output of Output Information: **S106**>

[0051] The output unit **2040** counts the number of abnormal regions **30** included in the moving image frame **14** and outputs the output information based on the number of abnormal regions **30** (**S106**). Hereinafter, the number of abnormal region **30** detected from a certain moving image frame **14** is also denoted as the number of detections for the moving image frame **14**.

[0052] Here, as the output information based on the number of abnormal regions **30**, various kinds of information can be generated. Hereinafter, variation of the output information is illustrated.

<<Output of Number of Abnormal Regions **30**>>

[0053] For example, the output unit **2040** generates the output information indicating the number of detections. FIGS. **6** to **8** are diagrams illustrating the output information indicating the number of detections. In FIG. **6**, display **90** representing the number of detections is displayed in the vicinity of the frame **80** representing the abnormal region **30**.

[0054] Here, it is preferable that, for each abnormal region **30** detected from the moving image frame **14**, the display **90** representing the number of detections is displayed at a position having a predetermined relationship with the abnormal region **30**.

[0055] The position having the predetermined relationship with the abnormal region **30** is, for example, the vicinity of the abnormal region **30** (a position at a distance equal to or less than a predetermined value from the abnormal region **30**, or the like).

[0056] For example, in FIG. **6**, three abnormal regions **30** are detected, and display **90-1**, display **90-2**, and display **90-3** are displayed in the vicinity of the abnormal regions **30**, respectively. With this, the physician or the like can easily recognize whether or not the abnormal region **30** other than the abnormal region **30** currently viewed by the physician or the like is detected or the number of abnormal regions **30** (that is, the number of abnormal regions **30** that should be observed by the physician or the like) detected from the moving image frame **14** only by viewing any one abnormal region **30**. For example, in FIG. **6**, when observing one abnormal region **30**, the physician or the like can naturally view the display **90** displayed in the vicinity of the abnormal region **30**, and as a result, can recognize that three (two other than the abnormal region **30** under observation) abnormal regions **30** in total are detected.

[0057] In FIG. **7**, output information is an image in which a moving image frame **14** is included. For example, the image is an image that is displayed on the display apparatus. In FIG. **7**, display **90** representing the number of detections is displayed outside the moving image frame **14**.

[0058] In FIG. **8**, output information is an image in which moving image frames **14** are included. In

FIG. 8, the moving image frames **14** are displayed in two display regions, respectively. In a display region **22**, a latest moving image frame **14** (a moving image frame **14** representing a place being currently imaged by the camera **10**) is displayed. On the other hand, in a display region **24**, each moving image frame **14** from which abnormal region **30** is detected in the past is displayed. In other words, the display region **24** is a region where a history of the abnormal regions **30** detected so far is displayed.

[0059] In FIG. 8, display **90** representing the number of detections is displayed for each moving image frame **14** of the display region **22** and the display region **24**. Here, as a method itself of displaying the number of detections for each moving image frame **14**, a method of displaying the number of detections in the vicinity of the frame **80** illustrated in FIG. 6, a method of displaying the number of detections outside the moving image frame **14** illustrated in FIG. 7, or the like can be employed. In FIG. 8, outside each moving image frame **14**, the number of abnormal regions **30** detected from the moving image frame **14** is displayed.

[0060] It should be noted that the moving image frames **14** displayed in the display region **24** may be some of the moving image frames **14** from which the abnormal regions **30** are detected, not all the moving image frames **14**. For example, for a plurality of moving image frames **14** in which the same abnormal regions **30** are included, any one moving image frame may be displayed in the display region **24**.

[0061] For example, the output unit **2040** outputs the image including the display **90** and the moving image frame **14** to the display apparatus connected to the information processing apparatus **2000**. In addition, for example, the output unit **2040** may store the image including the display **90** and the moving image frame **14** in the storage apparatus.

<<Highlighting>>

[0062] The output unit **2040** may perform highlighting in a case where the number of detections is equal to or greater than a threshold value. Here, in a case where the threshold value is 2, the processing corresponds to processing of “performing highlighting in a case where a plurality of abnormal regions **30** are detected from one moving image frame **14**”. It should be noted that the threshold value may be set in advance in the output unit **2040** or may be stored in a storage apparatus that is accessible from the output unit **2040**.

[0063] FIGS. 9 and 10 are diagrams illustrating variation of highlighting. There are various methods of highlighting. In FIG. 9, highlighting is performed for the frame surrounding the abnormal region **30**. Specifically, the output unit **2040** performs highlighting by making the thickness of the frame **80** in a case where the number of detections is equal to or greater than the threshold value (in FIG. 9, the threshold value=2) thicker than the thickness of the frame **80** in a case where the number of detections is less than the threshold value. It should be noted that, instead of changing the thickness of the frame, a shape or a color of the frame may be changed or a color with which the frame is colored may be changed.

[0064] In FIG. 10, highlighting is performed for the frame of the moving image frame **14**. Specifically, the output unit **2040** performs highlighting by thickening the frame of the moving image frame **14** in a case where the number of detections is equal to or greater than the threshold value more than the frame of the moving image frame **14** in a case where the number of detections is less than the threshold value. In this case, instead of changing the thickness of the frame, a color of the frame or a color with which the frame is colored may be changed. Alternatively, highlighting may be realized such that the frame is applied to the moving image frame **14** in a case where the number of detections is equal to or greater than the threshold value and the frame is not applied to the moving image frame **14** in a case where the number of detections is less than the threshold value.

[0065] It should be noted that, since the frame is applied to the moving image frame **14**, the output information in the case of FIG. 10 is an image, in which the moving image frame **14** is included, as in the case of FIG. 7 or 8.

[0066] Here, a plurality of threshold values of the number of detections may be provided. In this case, the output unit **2040** performs highlighting according to a maximum threshold value satisfying “the number of detections \geq the threshold value”. Here, it is preferable that, as the maximum threshold value satisfying “the number of detections \geq the threshold value” is greater, more highlighted display (that is, display that is likely to attract person's attention) is used. For example, as the maximum threshold value satisfying “the number of detections \geq the threshold value” is greater, the thickness of the frame **80** is made thicker or a color that is likely to attract person's attention is used for the frame **80**.

[0067] For example, it is assumed that two threshold values T1 and T2 are provided, and $T1 > T2$. In this case, three cases of 1) the number of detections $\geq T1$, 2) $T1 >$ the number of detections $\geq T2$, and 3) the number of detections $< T2$ are considered. In this case, the output unit **2040** performs highlighting in the cases 1) and 2). As the display of the case 1), display that is more likely to attract person's attention than the display of the case 2) is used.

[0068] For example, in general, there are red and yellow as a color that is used for alert. Then, a case of using red often draws person's attention more strongly than a case of using yellow. Now, for example, the output unit **2040** sets the color of the frame **80** to red in the case 1) and sets the color of the frame **80** to yellow in the case 2). In the case 3) where the number of detections is less than the threshold value, the color of the frame **80** may be set to a color representing a comparatively safe situation, such as green. For example, the threshold value T2 is set to 2, and the threshold value T1 is set to 3. In this case, the frame **80** is green in a case where the number of detections is 1, the frame **80** is yellow in a case where the number of detections is 2, and the frame **80** is red in a case where the number of detections is equal to or greater than 3.

[0069] In addition, for example, the output unit **2040** may increase the thickness of the frame **80** in an order of the case 1), the case 2), and the case 3).

[0070] It should be noted that, in the above-described description, although the rectangular frame **80** is applied to abnormal region **30**, the present invention is not limited to the rectangular frame being applied to the abnormal region **30**, and any mark can be applied. FIG. **11A-11F** are diagrams illustrating marks that are applied to the abnormal regions **30**.

[0071] For example, the output unit **2040** outputs the highlighted moving image frame **14** to the display apparatus. In addition, for example, the output unit **2040** may store the highlighted moving image frame **14** in the storage apparatus.

<<Output of Sound>>

[0072] For example, the output unit **2040** outputs alarm sound according to the number of detections. For example, the output unit **2040** outputs alarm sound to a speaker or the like connected to the information processing apparatus **2000**.

[0073] Here, alarm sound may be output only in a case where the number of detections is equal to or greater than the threshold value or alarm sound may be output even in a case where the number of detections is less than the threshold value. In the latter case, the output unit **2040** uses different kinds of alarm sound between a case where the number of detections is equal to or greater than the threshold value and a case where the number of detections is less than the threshold value.

[0074] It is preferable that alarm sound in a case where the number of detections is equal to or greater than the threshold value is more likely to attract person's attention than alarm sound in a case where the number of detections is less than the threshold value. For example, a length of alarm sound in a case where the number of detections is equal to or greater than the threshold value is set to be longer than a length of alarm sound in a case where the number of detections is less than the threshold value. In addition, for example, a volume of alarm sound in a case where the number of detections is equal to or greater than the threshold value is set to be greater than a volume of alarm sound in a case where the number of detections is less than the threshold value.

[0075] Here, as in the case of highlighting, a plurality of threshold values of the number of detections may be provided. In this case, the output unit **2040** outputs alarm sound according to the

maximum threshold value satisfying “the number of detections \geq the threshold value”. For example, as the maximum threshold value satisfying “the number of detections \geq the threshold value” is greater, the length of alarm sound may be set to be longer or the volume of alarm sound may be set to be greater.

[0076] In addition, for example, the output unit **2040** may output sound that allows the recognition of the number of detections. For example, the output unit **2040** outputs sound (“1”, “2”, or the like) representing the number of detections. In addition, for example, the output unit **2040** may output alarm sound the same number of times as the number of detections.

[0077] Although the example embodiment of the present invention has been described referring to the drawings, the example embodiment is merely an example of the present invention. The present invention can employ a combination of the example embodiment or various configurations other than the above.

[0078] A part or the whole of the above-described example embodiments can be described as, but is not limited to, the following supplementary notes.

[0079] 1. An information processing apparatus including: [0080] a detection unit that detects an abnormal region inside a body from a captured image in which the inside of the body is imaged; and [0081] an output unit that generates output information based on the number of the abnormal regions and outputs the generated output information.

[0082] 2. The information processing apparatus described in 1, [0083] in which the output unit generates the output information including information indicating the number of the abnormal regions.

[0084] 3. The information processing apparatus described in 2, [0085] in which the output unit includes an image, in which the information indicating the number of the abnormal regions is superimposed on the captured image, in the output information.

[0086] 4. The information processing apparatus described in 3, [0087] in which, in a case where a plurality of abnormal regions are detected from the captured image, for each of the plurality of abnormal regions, the output unit superimposes the information indicating the number of the abnormal regions at a position having a predetermined relationship with the abnormal region.

[0088] 5. The information processing apparatus described in 2, [0089] in which the output unit includes a second image, in which the captured image is included, in the output information, and [0090] the second image includes the information indicating the number of the abnormal regions outside the captured image.

[0091] 6. The information processing apparatus described in 2, [0092] in which the output unit includes a second image, in which a plurality of the captured images having the abnormal region detected are included, in the output information, and [0093] for each of the plurality of the captured images, the second image includes the information indicating the number of abnormal regions detected from the captured image.

[0094] 7. The information processing apparatus described in 1, [0095] in which the output unit generates the output information in which the captured image having the number of the abnormal regions equal to or greater than a threshold value is highlighted more than other captured images.

[0096] 8. The information processing apparatus described in 7, [0097] in which the highlighting of the captured image is highlighting of the abnormal region included in the captured image or highlighting of the entire captured image.

[0098] 9. The information processing apparatus described in 7 or 8, [0099] in which the output unit performs highlighting in different aspects between the output information in a case where the number of the abnormal regions is equal to or greater than a first threshold value and the output information in a case where the number of the abnormal regions is less than the first threshold value and is equal to or greater than a second threshold value.

[0100] 10. The information processing apparatus described in 1 or 2, [0101] in which the output unit outputs sound determined based on the number of the abnormal regions as the output

information.

[0102] 11. The information processing apparatus described in 10, [0103] in which the output unit outputs different kinds of sound between a case where the number of the abnormal regions is equal to or greater than a threshold value and a case where the number of the abnormal regions is less than a threshold value.

[0104] 12. A control method that is executed by a computer, the control method including: [0105] a detection step of detecting an abnormal region inside a body from a captured image in which the inside of the body is imaged; and [0106] an output step of generating output information based on the number of the abnormal regions and outputting the generated output information.

[0107] 13. The control method described in 12, [0108] in which, in the output step, the output information including information indicating the number of the abnormal regions is generated.

[0109] 14. The control method described in 13, [0110] in which, in the output step, an image in which the information indicating the number of the abnormal regions is superimposed on the captured image is included in the output information.

[0111] 15. The control method described in 14, [0112] in which, in a case where a plurality of abnormal regions are detected from the captured image, in the output step, for each of the plurality of abnormal regions, the information indicating the number of the abnormal regions is superimposed at a position having a predetermined relationship with the abnormal region.

[0113] 16. The control method described in 13, [0114] in which, in the output step, a second image, in which the captured image is included, is included in the output information, and [0115] the second image includes the information indicating the number of the abnormal regions outside the captured image.

[0116] 17. The control method described in 13, [0117] in which, in the output step, a second image, in which a plurality of the captured images having the abnormal region detected are included, is included in the output information, and [0118] for each of the plurality of the captured images, the second image includes the information indicating the number of abnormal regions detected from the captured image.

[0119] 18. The control method described in 12, [0120] in which, in the output step, the output information in which the captured image having the number of the abnormal regions equal to or greater than a threshold value is highlighted more than other captured images is generated.

[0121] 19. The control method described in 18, [0122] in which the highlighting of the captured image is highlighting of the abnormal region included in the captured image or highlighting of the entire captured image.

[0123] 20. The control method described in 18 or 19, [0124] in which, in the output step, the output information in a case where the number of the abnormal regions is equal to or greater than a first threshold value and the output information in a case where the number of the abnormal regions is less than the first threshold value and is equal to or greater than a second threshold value are highlighted in different aspects from each other.

[0125] 21. The control method described in 12 or 13, [0126] in which, in the output step, sound determined based on the number of the abnormal regions is output as the output information.

[0127] 22. The control method described in 21, [0128] in which, in the output step, different kinds of sound are output between a case where the number of the abnormal regions is equal to or greater than a threshold value and a case where the number of the abnormal regions is less than a threshold value.

[0129] 23. A program causing a computer to execute each step of the control method described in any one of 12 to 22.

[0130] This application is based upon and claims the benefit of priority from Japanese patent application No. 2018-169722, filed on Sep. 11, 2018, the disclosure of which is incorporated herein in its entirety by reference.

REFERENCE SIGNS LIST

[0131] **10**: camera [0132] **12**: moving image data [0133] **14**: moving image frame [0134] **20**: display apparatus [0135] **22**: display region [0136] **24**: display region [0137] **30**: abnormal region [0138] **40**: scope [0139] **50**: endoscope system [0140] **80**: frame [0141] **90**: display [0142] **1000**: computer [0143] **1020**: bus [0144] **1040**: processor [0145] **1060**: memory [0146] **1080**: storage device [0147] **1100**: input-output interface [0148] **1120**: network interface [0149] **2000**: information processing apparatus [0150] **2020**: detection unit [0151] **2040**: output unit

Claims

1. An information processing apparatus comprising: at least one memory storing instructions; and at least one processor configured to execute the instructions to: detect an abnormal region inside a body from a captured image in which the inside of the body is imaged; generate output information based on a number of detected abnormal regions which are detected and output the generated output information; generate the output information including a value indicating the number of the detected abnormal regions; include a second image, in which the value indicating the number of the detected abnormal regions is superimposed on the captured image, in the output information; and in a case where a plurality of abnormal regions are detected from the captured image, for each of the plurality of abnormal regions, output the value indicating the number of the detected abnormal regions at a position having a predetermined relationship with the abnormal region.
2. The information processing apparatus according to claim 1, wherein the at least one processor is configured to include the second image, in which the captured image is included, in the output information, and the second image further includes the information indicating the number of the detected abnormal regions outside the captured image.
3. The information processing apparatus according to claim 1, wherein the at least one processor is configured to include a plurality of the second images, in which a plurality of the captured images having the abnormal region detected are included, respectively, in the output information.
4. The information processing apparatus according to claim 1, wherein the at least one processor is configured to generate the output information in which the captured image having the number of the detected abnormal regions equal to or greater than a threshold value is highlighted more than other captured images.
5. The information processing apparatus according to claim 4, wherein the highlighting of the captured image is highlighting of the abnormal region included in the captured image or highlighting of the entire captured image.
6. The information processing apparatus according to claim 4, wherein the at least one processor is configured to perform highlighting in different aspects between the output information in a case where the number of the detected abnormal regions is equal to or greater than a first threshold value and the output information in a case where the number of the detected abnormal regions is less than the first threshold value and is equal to or greater than a second threshold value.
7. The information processing apparatus according to claim 1, wherein the at least one processor is configured to output sound determined based on the number of the detected abnormal regions as the output information.
8. The information processing apparatus according to claim 7, wherein the at least one processor is configured to output different kinds of sound between a case where the number of the detected abnormal regions is equal to or greater than a threshold value and a case where the number of the detected abnormal regions is less than the threshold value to support user's decision making.
9. A control method that is executed by a computer, the control method comprising: detecting an abnormal region inside a body from a captured image in which the inside of the body is imaged; generating output information based on a number of detected abnormal regions which are detected and output the generated output information; generating the output information including a value indicating the number of the detected abnormal regions; including a second image, in which the

value indicating the number of the detected abnormal regions is superimposed on the captured image, in the output information; and in a case where a plurality of abnormal regions are detected from the captured image, for each of the plurality of abnormal regions, output the value indicating the number of the detected abnormal regions at a position having a predetermined relationship with the abnormal region.

10. A non-transitory computer-readable storage medium storing a program causing a computer to execute a control method comprising: detecting an abnormal region inside a body from a captured image in which the inside of the body is imaged; generating output information based on a number of detected abnormal regions which are detected and output the generated output information; generating the output information including a value indicating the number of the detected abnormal regions; including a second image, in which the value indicating the number of the detected abnormal regions is superimposed on the captured image, in the output information; and in a case where a plurality of abnormal regions are detected from the captured image, for each of the plurality of abnormal regions, output the value indicating the number of the detected abnormal regions at a position having a predetermined relationship with the abnormal region.
