



US012386125B2

(12) **United States Patent**
Chang et al.

(10) **Patent No.:** **US 12,386,125 B2**
(45) **Date of Patent:** **Aug. 12, 2025**

(54) **OPTICAL FIBER CONNECTOR WITH
CHANGEABLE GENDER**

(71) Applicant: **Senko Advanced Components, Inc.**,
Hudson, MA (US)

(72) Inventors: **Jimmy Jun Fu Chang**, Sturbridge, MA
(US); **Kazuyoshi Takano**, Tokyo (JP)

(73) Assignee: **Senko Advanced Components, Inc.**,
Hudson, MA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/431,896**

(22) Filed: **Feb. 2, 2024**

(65) **Prior Publication Data**

US 2024/0176080 A1 May 30, 2024

Related U.S. Application Data

(63) Continuation of application No. 18/170,498, filed on
Feb. 16, 2023, now Pat. No. 11,892,688, which is a
continuation of application No. 17/195,137, filed on
Mar. 8, 2021, now Pat. No. 11,585,988, which is a
continuation of application No. 16/784,993, filed on
Feb. 7, 2020, now abandoned, which is a continuation
of application No. 16/453,115, filed on Jun. 26, 2019,
now Pat. No. 11,073,662, which is a continuation of
application No. 15/958,227, filed on Apr. 20, 2018,
now Pat. No. 10,409,009, which is a continuation of
application No. 15/626,430, filed on Jun. 19, 2017,
(Continued)

(51) **Int. Cl.**
G02B 6/38 (2006.01)

(52) **U.S. Cl.**
CPC **G02B 6/3882** (2013.01); **G02B 6/3825**
(2013.01); **G02B 6/3826** (2013.01); **G02B**
6/3885 (2013.01)

(58) **Field of Classification Search**
CPC .. **G02B 6/3882**; **G02B 6/3825**; **G02B 6/3826**;
G02B 6/3885
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,163,201 A 6/1939 Kalencik
2,538,296 A 1/1951 Crocker
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2495693 A1 4/2004
CN 2836038 Y 11/2006
(Continued)

OTHER PUBLICATIONS

Non-Final Office Action received for U.S. Appl. No. 16/453,115
dated Jul. 24, 2020, 27 pages.


(Continued)

Primary Examiner — John Bedtelyon

(57) **ABSTRACT**

A multi-fiber, fiber optic connector is interchangeable
between a male connector and a female connector by includ-
ing a pin retainer having a releasable retention device
configured to lock the pins in place within the retainer. The
retention device may be opened, for example, with a release
tool, to free the retention pins for removal of the pins. A
method for switching a connector between a male connector
configuration and a female connector configuration may be
possible as a result of the releasable retention configuration.

27 Claims, 12 Drawing Sheets



Related U.S. Application Data

now Pat. No. 9,977,199, which is a continuation of application No. 14/725,514, filed on May 29, 2015, now Pat. No. 9,684,139.

(56)

References Cited

U.S. PATENT DOCUMENTS

2,624,776 A	6/1953	Price	7,090,407 B2	8/2006	Melton et al.
3,025,486 A	3/1962	Falconer	7,111,990 B2	9/2006	Melton et al.
3,721,945 A	3/1973	Hults	7,113,679 B2	9/2006	Melton et al.
3,733,576 A	5/1973	Cooper	7,121,850 B2	10/2006	Yeh
4,296,999 A	10/1981	Mead	D533,504 S	12/2006	Lee
4,327,964 A	8/1982	Haesley et al.	D534,124 S	12/2006	Taguchi
4,356,360 A	10/1982	Volz	7,077,576 B2	12/2006	Luther et al.
4,478,473 A	10/1984	Frear	7,150,567 B1	12/2006	Luther et al.
4,626,052 A	12/1986	Rumble	7,153,041 B2	12/2006	Mine et al.
4,762,388 A	8/1988	Tanaka et al.	7,198,409 B2	4/2007	Smith et al.
4,764,129 A	8/1988	Jones et al.	7,207,724 B2	4/2007	Gurreri
4,840,451 A	6/1989	Sampson et al.	D543,146 S	5/2007	Chen et al.
4,872,736 A	10/1989	Myers et al.	7,258,493 B2	8/2007	Milette
4,979,792 A	12/1990	Weber et al.	7,264,402 B2	9/2007	Theuerkom
5,041,025 A	8/1991	Haitmanek	7,281,859 B2	10/2007	Mudd et al.
D323,143 S	1/1992	Ohkura et al.	D558,675 S	1/2008	Chien et al.
5,210,934 A	5/1993	Lenzi et al.	7,315,682 B1	1/2008	En Lin et al.
5,212,752 A	5/1993	Stephenson et al.	7,325,976 B2	2/2008	Gurreri et al.
5,265,181 A	11/1993	Chang	7,325,980 B2	2/2008	Pepe
5,289,554 A	2/1994	Cubukciyan et al.	7,329,137 B2	2/2008	Martin et al.
5,317,663 A	5/1994	Beard et al.	7,331,718 B2	2/2008	Yazaki et al.
5,335,301 A	5/1994	Newman et al.	7,354,291 B2	4/2008	Caveney et al.
5,348,487 A	9/1994	Marazzi et al.	7,371,082 B2	5/2008	Zimmel et al.
5,444,806 A	8/1995	DeMarchi et al.	7,387,447 B2	6/2008	Mudd et al.
5,481,634 A	1/1996	Anderson et al.	7,390,203 B2	6/2008	Murano et al.
5,506,922 A	4/1996	Grois et al.	D572,661 S	7/2008	En Lin et al.
5,521,997 A	5/1996	Rovenolt et al.	7,431,604 B2	10/2008	Waters et al.
5,570,445 A	10/1996	Chou et al.	7,463,803 B2	12/2008	Cody et al.
5,588,079 A	12/1996	Tanabe et al.	7,465,180 B2	12/2008	Kusuda et al.
5,684,903 A	11/1997	Kyomasu et al.	7,510,335 B1	3/2009	Bing et al.
5,687,268 A	11/1997	Stephenson et al.	7,513,695 B1	4/2009	Lin et al.
5,781,681 A	7/1998	Manning	7,540,666 B2	6/2009	Luther
5,791,921 A	8/1998	Lee	7,561,775 B2	7/2009	Lin et al.
5,937,130 A	8/1999	Amberg et al.	7,591,595 B2	9/2009	Lu et al.
5,956,444 A	9/1999	Duda et al.	7,594,766 B1	9/2009	Sasser et al.
5,971,626 A	10/1999	Knodell et al.	7,641,398 B2	1/2010	O'Riorden et al.
6,041,155 A	3/2000	Anderson et al.	7,670,177 B2	3/2010	Myer et al.
6,049,040 A	4/2000	Biles et al.	7,695,199 B2	4/2010	Teo et al.
6,085,003 A	7/2000	Knight	7,695,316 B2	4/2010	Sun
6,134,370 A	10/2000	Childers et al.	7,699,533 B2	4/2010	Milette
6,178,283 B1	1/2001	Weigel	7,785,019 B2	8/2010	Lewallen
RE37,080 E	3/2001	Stephenson et al.	7,824,113 B2	11/2010	Wong et al.
6,200,040 B1	3/2001	Edwards et al.	7,837,395 B2	11/2010	Lin et al.
6,206,577 B1	3/2001	Hall, III et al.	D641,708 S	7/2011	Yamauchi
6,206,581 B1	3/2001	Driscoll et al.	8,157,578 B2	4/2012	Lee
6,227,717 B1	5/2001	Ott et al.	8,186,890 B2	5/2012	Lu
6,238,104 B1	5/2001	Yamakawa et al.	8,192,091 B2	6/2012	Hsu et al.
6,247,849 B1	6/2001	Liu	8,202,009 B2	6/2012	Lin et al.
6,419,504 B1	7/2002	Nelson	8,251,733 B2	8/2012	Wu
6,461,054 B1	10/2002	Iwase	8,267,595 B2	9/2012	Lin et al.
6,464,408 B1	10/2002	Nolan	8,270,796 B2	9/2012	Nhep
6,471,412 B1	10/2002	Belenkiy et al.	8,277,237 B1	10/2012	Cherish
6,478,472 B1	11/2002	Anderson et al.	8,408,815 B2	4/2013	Lin et al.
6,530,696 B1	3/2003	Ueda	8,465,317 B2	6/2013	Gniadek et al.
6,551,117 B2	4/2003	Poplawski et al.	8,534,928 B2	9/2013	Cooke
6,579,014 B2	6/2003	Melton et al.	8,622,634 B2	1/2014	Arnold
6,634,801 B1	10/2003	Waldron et al.	8,651,749 B2	2/2014	Junior et al.
6,648,520 B2	11/2003	McDonald et al.	8,678,670 B2	3/2014	Takahashi
6,669,377 B2	12/2003	Barnes et al.	8,757,893 B1	6/2014	Isenhour et al.
6,682,228 B2	1/2004	Rathnam et al.	8,768,125 B2	7/2014	Beatty et al.
6,685,362 B2	2/2004	Burkholder et al.	9,046,660 B2	6/2015	Good et al.
6,695,486 B1	2/2004	Falkenberg	9,411,101 B2	8/2016	Takahashi et al.
6,854,894 B1	2/2005	Yunker et al.	9,684,139 B2	6/2017	Chang et al.
6,872,039 B2	3/2005	Baus et al.	9,778,425 B2	10/2017	Nguyen et al.
6,923,666 B1	8/2005	Liao	9,798,094 B2	10/2017	Kuffel
6,935,789 B2	8/2005	Gross, III et al.	9,829,645 B2	11/2017	Good
7,036,993 B2	5/2006	Luther	9,977,199 B2	5/2018	Jimmy et al.
7,091,421 B2	5/2006	Kukita et al.	10,725,249 B2	7/2020	Higley et al.
7,090,406 B2	8/2006	Melton et al.	2002/0110333 A1	8/2002	Yang
			2002/0191919 A1	12/2002	Nolan
			2003/0053787 A1	3/2003	Lee
			2004/0052473 A1	3/2004	Seo et al.
			2004/0136657 A1	7/2004	Ngo
			2004/0141693 A1	7/2004	Szilagy et al.
			2004/0152354 A1	8/2004	Luther et al.
			2004/0161958 A1	8/2004	Togami et al.
			2004/0234209 A1	11/2004	Cox et al.
			2005/0111796 A1	5/2005	Matasek et al.
			2005/0141817 A1	6/2005	Yazaki et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

2006/0067628	A1	3/2006	Suzuki et al.
2006/0089049	A1	4/2006	Sedor
2006/0127025	A1	6/2006	Haberman
2006/0269194	A1	11/2006	Luther et al.
2006/0274411	A1	12/2006	Yamauchi
2007/0025665	A1	2/2007	Dean et al.
2007/0028409	A1	2/2007	Yamada
2007/0079854	A1	4/2007	You
2007/0098329	A1	5/2007	Shimoji et al.
2007/0149062	A1	6/2007	Long et al.
2007/0230874	A1	10/2007	Lin
2007/0232115	A1	10/2007	Burke et al.
2007/0243749	A1	10/2007	Wu
2008/0008430	A1	1/2008	Kewitsch
2008/0044137	A1	2/2008	Luther et al.
2008/0069501	A1	3/2008	Mudd et al.
2008/0101757	A1	5/2008	Lin et al.
2008/0226237	A1	9/2008	O'Riorden et al.
2008/0267566	A1	10/2008	En Lin
2009/0022457	A1	1/2009	de Jong et al.
2009/0028507	A1	1/2009	Jones et al.
2009/0196555	A1	8/2009	Lin et al.
2009/0214162	A1	8/2009	O'Riorden et al.
2009/0220197	A1	9/2009	Gniadek et al.
2010/0034502	A1	2/2010	Lu et al.
2010/0092136	A1	4/2010	Nhep
2010/0247041	A1	9/2010	Szilagyi
2010/0322561	A1	12/2010	Lin et al.
2011/0044588	A1	2/2011	Larson et al.
2011/0131801	A1	6/2011	Nelson et al.
2011/0177710	A1	7/2011	Tobey
2012/0099822	A1	4/2012	Kuffel et al.
2012/0189260	A1	7/2012	Kowalczyk et al.
2012/0269485	A1	10/2012	Haley et al.
2012/0301080	A1	11/2012	Gniadek
2013/0071067	A1	3/2013	Lin
2013/0089995	A1	4/2013	Gniadek et al.
2013/0094816	A1	4/2013	Lin et al.
2013/0121653	A1	5/2013	Shitama et al.
2013/0170797	A1	7/2013	Ott
2013/0183012	A1	7/2013	Cabanne Lopez et al.
2013/0216185	A1*	8/2013	Klavuhn G02B 6/3882 385/60
2013/0259429	A1	10/2013	Czosnowski et al.
2013/0315539	A1	11/2013	Koreeda et al.
2013/0322825	A1	12/2013	Cooke et al.
2014/0016901	A1	1/2014	Lambourn et al.
2014/0023322	A1	1/2014	Gniadek
2014/0023326	A1	1/2014	Anderson et al.
2014/0050446	A1	2/2014	Chang
2014/0133808	A1	5/2014	Hill et al.
2014/0154913	A1	6/2014	Ho
2014/0226946	A1	8/2014	Cooke et al.
2014/0334780	A1	11/2014	Nguyen et al.
2014/0348477	A1	11/2014	Chang
2015/0003785	A1	1/2015	Raven et al.
2015/0378113	A1	12/2015	Good et al.
2018/0364421	A1	12/2018	Chang et al.
2019/0384017	A1	12/2019	Lu

FOREIGN PATENT DOCUMENTS

CN	201383588	Y	1/2010
CN	202600189	U	12/2012
DE	202006011910	U1	4/2007
DE	102006019335	A1	10/2007
EP	1074868	A1	7/2001
EP	1211537	A2	6/2002
EP	1245980	A2	10/2002
EP	1566674	A1	8/2005
GB	2111240	A	6/1983
JP	S63229416	A	9/1988
JP	3363479	A	2/1994
JP	2003014983	A	1/2003

JP	2009229545	A	10/2009
JP	2009276493	A	11/2009
KR	20110009902	A	1/2011
TW	200821653	A	5/2008
WO	2001/79904	A2	10/2001
WO	2004/027485	A1	4/2004
WO	2008/112986	A1	9/2008
WO	2009/135787	A1	11/2009
WO	2010/024851	A2	3/2010
WO	2012/136702	A1	10/2012
WO	2012/162385	A1	11/2012
WO	2013038204	A1	3/2013
WO	2014/028527	A1	2/2014
WO	2014/182351	A1	11/2014
WO	2015/191024	A1	12/2015
WO	2016053851	A1	4/2016
WO	2016/148741	A1	9/2016

OTHER PUBLICATIONS

Notice of Allowance received for U.S. Appl. No. 16/453,115 dated Oct. 3, 2019, 26 pages.

European Search Report and Written Opinion dated Mar. 3, 2015 for EP 14187661.

European Search Report and Written Opinion dated Feb. 19, 2015 for EP 14168005.

"Fiber Optic Connectors and Assemblies Catalog" 2009, Huber & Suhner Fiber Optics, Herisau, Switzerland, www.nubersuhner.com.
 "Fiber Optic Interconnect Solutions, Tactical Fiber Optical Connectors, Cables and Termini" 2006, Glenair, Inc., Glendale, California, www.mps-electronics.de.

Fiber Optic Products Catalog Nov. 2007, Tyco Electronics Corporation, Harrisburg, Pennsylvania, www.ampnetconnect.com.

International Search Report and Written Opinion dated Apr. 27, 2012 for PCT/US2011/058799.

International Search Report and Written Opinion dated Aug. 27, 2012 for PCT/US2012/039126.

International Search Report and Written Opinion dated Jan. 16, 2014 for PCT/US2013/54784.

International Search Report and Written Opinion dated Oct. 9, 2014 for PCT/US2014/041500.

International Search Report and Written Opinion dated May 14, 2014 for PCT/US2014/012137.

International Search Report and Written Opinion dated Aug. 21, 2008 for PCT/US2008/057023.

International Preliminary Report on Patentability dated Aug. 22, 2016 from related International Application No. PCT/US2015/059458, International Filing Date Nov. 6, 2015.

International Search Report {ISR} W02008112986 Sep. 15, 2009. ISR W020140285271SR Feb. 20, 2014.

ISR W02015US57610ISR Jan. 21, 2016.

Ex Parte ReExamination, Application No. 90/020, 125, dated Apr. 15, 2019, p. 31.

International Search Report and Written Opinion dated Mar. 30, 2016 from corresponding International Application No. PCT/US15/65479, International Filing Date Dec. 14, 2015.

International Preliminary Report on Patentability dated Dec. 14, 2017, from related International Application No. PCT/US15/65479, International Filing Date Dec. 14, 2015.

Non-Final Office Action from related U.S. Appl. No. 14/725,514, filed May 29, 2015, dated Jun. 30, 2016, 10 pages.

Non-Final Office Action from related U.S. Appl. No. 15/626,430 dated Jul. 28, 2017, 10 pages.

International Search Report, Application No. 15/894,501.4, pp. 8, dated Dec. 3, 2018.

Jones, et al., U.S. Appl. No. 62/058, 188, filed Oct. 1, 2014, entitled: Fiber Optic Connector and Pin Change Method for the Same.

Chang et al., Request for Ex Parte Reexamination of U.S. Pat. No. 9,977,199, dated Dec. 7, 2018, entitled: Optical Fiber Connector With Changeable Gender.

Non-Final Office Action received for U.S. Appl. No. 16/784,993 dated Oct. 6, 2020, 12 pages.




(56)

References Cited

OTHER PUBLICATIONS

Non-Final Office Action received for U.S. Appl. No. 15/958,227
dated Oct. 1, 2018, 14 pages.

* cited by examiner






FIG. 4




FIG. 5A





FIG. 5B






FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A





FIG. 8C



SECTION C-C

FIG. 8B





FIG. 8D



SECTION D-D





FIG. 12




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 17A




FIG. 17C




FIG. 17B




FIG. 17D




FIG. 18A





FIG. 18B



1

OPTICAL FIBER CONNECTOR WITH CHANGEABLE GENDER

CROSS-REFERENCE TO RELATED APPLICATION

This application a continuation of U.S. patent application Ser. No. 18/170,498 filed on Feb. 16, 2023, which is a continuation of U.S. patent application Ser. No. 17/195,137 filed on Mar. 8, 2021 and now U.S. Pat. No. 11,585,988 granted on 02/21/2023, which is a continuation of U.S. patent application Ser. No. 16/784,993 filed on Feb. 7, 2020, a continuation of U.S. patent application Ser. No. 16/453,115 filed on Jun. 26, 2019 and now U.S. Pat. No. 11,073,662 granted on 07/27/2021, a continuation of U.S. patent application Ser. No. 15/958,227, filed Apr. 20, 2018 and now U.S. Pat. No. 10,409,009 granted on Sep. 10, 2019, which is a continuation of U.S. patent application Ser. No. 15/626,430 filed on Jun. 19, 2017 and is now U.S. Pat. No. 9,977,199 issued on May 22, 2018, which is continuation of U.S. patent application Ser. No. 14/725,514, filed May 29, 2015, now U.S. Pat. No. 9,684,139 issued on Jun. 20, 2017, all of which are incorporated herein by reference in its entirety.

BACKGROUND

Demand for bandwidth by enterprises and individual consumers continues to experience exponential growth. To meet this demand efficiently and economically, data centers have to achieve ultra-high density cabling with low loss budgets. Fiber optics have become the standard cabling medium used by data centers to meet the growing needs for data volume and transmission speeds.

Individual optical fibers are extremely small. For example, even with protective coatings, optical fibers may be only about 250 microns in diameter (only about 4 times the diameter of a human hair). As such, hundreds of fibers can be installed in cables that will take up relatively little space. For connections between cables, however, the fibers are terminated with connectors. Multiple fibers may be arranged within a single connector. For example, multi-fiber connectors such as those using multi-fiber push-on/pull-off (MPO) technology may contain and connect 12 or 24 fibers. Connectors, such as MPO type connectors, generally include a housing portion that contains a ferrule that terminates the ends of the fibers. Ferrules are generally used to retain the ends of the optical fibers for connecting the optical fibers. One type of optical ferrule that may be used with MPO type connectors is an MT (Mechanically Transferable) ferrule.

Typically, MPO connectors are joined together to connect the optical transmission path of one fiber optic cable to another fiber optic cable or device, and the connection may be made by inserting the MPO connectors in an MPO adapter. An adapter generally includes a housing, or portion of a housing, having at least one port which is configured to receive and hold a connector to facilitate the optical connection of the connector ferrule with the ferrule of another connector or other device. Adapters may be used to facilitate connections contained within a chassis. The term “chassis” as used herein broadly refers to a containment structure for housing electrical components or switching components.

MT (Mechanically Transferable) ferrules are optical ferrules which are standardized according to JIS C 5981, IEC 61754-5 and the like. The MT ferrules get pushed together within the adapter to optically connect the ferrules by means of a so-called PC (Physical Contact) connection, wherein the optical fibers in one ferrule contact the optical fibers in the

2

other ferrule and get compressed together to provide an optical connection. Optical transmission performance between the optical fibers is strongly dependent on connecting conditions such as axis alignment and inclination of the optical fibers, and gaps between the opposing optical fibers.

MT ferrules generally use at least two guide pins for high-accuracy alignment of the optical fibers in the mating ferrules. An MT ferrule body may include at least two guide pin holes on the end surface of the ferrule for receiving the guide pins therein. For a pair of mating connectors, one of the ferrule bodies of a first connector may be provided with guide pins in the guide pin holes (generally called the ‘male’ connector), and the other ferrule body of a second connector may have only the guide pin holes (generally called the ‘female’ connector). As such, a highly accurate mating of the connectors may be achieved when the guide pins of the male connector are disposed within the guide pin holes of the female connector.

The gender, male or female, designation of a connector may often be typically predisposed during manufacturing of the connector, wherein connectors may be manufactured to be either male or female. Such connectors may be pre-installed on cable ends, and care must be taken so that the cables are all installed in the proper direction so that mating of male and female ends may possible. Alternatively, for on-site installation, a connector may be assembled onto a cable end, and during assembly the installer may install pins or a pin component into a ferrule body to provide a male connector, or alternatively, leave such pieces absent to provide a female connector.

For installations wherein the gender may accidentally end up being incorrect, or installations where the gender may need to be changed for one reason or another, such as a renovation or installation of a gender specific component, the gender of typical connectors is not changeable, or only changeable after disassembly and reassembly in the opposite designation. As such, for predetermined gender connectors, an entire connector may need to be removed and essentially scrapped, for replacement by an opposite gender connector, or for connectors requiring disassembly and reassembly, much time may be wasted in the re-gendering process.

Therefore, there remains a need for multi-fiber, fiber optic connectors that have the flexibility of easily changing the gender of the connector on site.

SUMMARY

A multi-fiber, fiber optic connector may include removable guide pins for changing the gender of the connector. The connector may be configured to releasably retain the guide pins therein. The guide pins may be insertable into the connector to convert the connector from a female connector to a male connector. Once inserted, the guide pins may be retained, or locked in place with a retention configuration. To convert from male to female, the retention configuration may be opened to release the guide pins, and the guide pins may be removed from the connector.

In an embodiment, a multi-fiber fiber optic connector interconvertible between a male connector and a female connector, includes a ferrule comprising a plurality of optical fibers supported therein and terminating at a first end of the ferrule for alignment with optical fibers of an additional device, at least two spaced apart passages disposed along at least a portion of the ferrule and configured for receiving alignment pins therein, a pin retainer configured for releasably retaining the alignment pins in the connector when the alignment pins are disposed in the passages, and a housing

3

disposed around the pin retainer and at least a portion of the ferrule. The pin retainer includes a portion for engaging each alignment pin to retain the alignment pins in the connector for a male configuration, wherein the portion for engaging is selectively releasable from the alignment pins for removal of the alignment pins for a female configuration.

In an embodiment a pin retainer for a fiber optic connector includes a body portion for being disposed with a ferrule in the connector, an at least one selectively displaceable locking member configured for locking an alignment pin with the body portion, wherein the selectively displaceable locking member has a first position for engaging an alignment pin to lock an alignment pin with the body portion, and a second position displaced from the first position for release of an alignment pin locked with the body portion.

In an embodiment a method for interconversion of a fiber optic connector between a male configuration with at least one alignment pin, and a female configuration with at least one passage for receiving an alignment pin is provided. The connector includes at least one selectively displaceable locking member for locking at least one alignment pin therein, and the method includes, for converting a female configuration to a male configuration, slidably inserting at least one alignment pin into engagement with the selectively displaceable locking member to lock the alignment pin into the connector, and for converting a male configuration to a female configuration, releasing the selectively displaceable locking member from the alignment pin, and slidably removing the alignment pin from the connector.

BRIEF DESCRIPTION OF THE FIGURES

FIGS. 1A and 1B depict male and female configurations of an MPO connector according to an embodiment.

FIG. 2 depicts an MPO adapter as generally used for mating MPO connectors of FIGS. 1A and 1B.

FIG. 3 is an exploded view of a male connector according to an embodiment.

FIG. 4 is a perspective view of a ferrule and a pin retainer according to an embodiment.

FIGS. 5A and 5B are front and rear exploded perspective views of the ferrule and the pin retainer of FIG. 4.

FIG. 6 is a perspective view of a pin retainer and guide pins according to an embodiment.

FIGS. 7A-7D are top, side, front and rear face views of a pin retainer according to an embodiment.

FIGS. 8A-8D provide top, side and sectional views of a pin retained with a pin retainer according to an embodiment.

FIG. 9 depicts a perspective view of a male connector with its outer housing pulled back to show the release slots according to an embodiment.

FIG. 10 provides a side view of the inner housing showing the release slots according to an embodiment.

FIG. 11 is a detailed view of the release slots shown in FIG. 10 according to an embodiment.

FIG. 12 shows a tool and placement thereof relative to the release slots according to an embodiment.

FIGS. 13A-13B are side and sectional views of the embodiment of FIG. 12 according to an embodiment.

FIGS. 14A and 14B are sectional views showing use of a tool to release the pins according to an embodiment.

FIGS. 15A and 15B show an alternative tool configuration according to an embodiment.

FIGS. 16A-16D show an alternative configuration of a pin retainer according to an embodiment.

FIGS. 17A-17D show an alternative configuration of a pin retainer according to an embodiment.

4

FIGS. 18A-18B show a one-piece housing and pin retainer according to an embodiment.

DETAILED DESCRIPTION

As used herein, the term “optical fiber” is intended to apply to all types of single mode and multi-mode light waveguides, including one or more bare optical fibers, coated optical fibers, loose-tube optical fibers, tight-buffered optical fibers, ribbonized optical fibers, bend performance optical fibers, bend insensitive optical fibers, nanostructured optical fibers or any other expedient for transmitting light signals. A multi-fiber optic cable includes a plurality of the optical fibers. Such cables have a variety of names depending on their particular usage, and may be considered as “trunk cables” or “trunks” when connected to fiber optic modules used to form connections to jumper cables using a select polarity.

For connection of cables together or with other fiber optic devices, the terminal ends of a cable may include a male connector 10 or female connector 12 as represented in FIGS. 1A and 1B, respectively, or in exploded view of FIG. 3. A connector 10, 12 may include an inner housing structure 14 configured to interact with and connect with an adapter 15 as represented in FIG. 2. An adapter 15, in a simple form, may include two aligned ports 18a, 18b for aligning fiber optic connectors 10, 12 therein to align and connect optical fibers 16 end-to-end. For proper alignment, the connectors to be aligned generally include one male connector 10 and one female connector 12. The male connector 10 generally includes at least two guide/alignment pins 20 that fit into the guide/alignment holes 22 of the female connector 12, thereby essentially ensuring proper alignment of the optical fibers 16 of the two connectors when mated end to end. As described herein, the connectors 10, 12 and adapters 15 may be considered multi-fiber connectors and multi-fiber adapters.

While the following description is directed towards MPO adapters and MPO connectors with MT optical ferrules, the embodiments described may be applicable to other adapters, connectors and ferrule types as well. An embodiment of an MPO connector 10, 12 may include a ferrule 24 that may be a multi-fiber ferrule as shown at a first end of the connector. In addition, the connector 10 may have attached thereto, a fiber optic cable 26 and cable boot 28 that may extend from a second end of the connector.

An adapter 15 may include a first end 30a having a first port 18a for receiving the ferrule end of an optical fiber connector 10, 12 therein, and may include a second end 30b having an additional port 18b (not visible) for receiving an additional optical fiber connector, or other type of fiber optic device therein.

For retention of an MPO connector 10 within each of the ports 18a, 18b, the ports may be provided internally with a connector clip that may be formed by the two resilient tabs 32a, 32b. The tabs 32a, 32b may be configured to be displaceable outwardly for insertion and removal of a connector 10, 12 into or out of the ports 18a, 18b, and may return to essentially their original position to engage and retain a connector in the ports. Adapters 15 may be configured to be mounted on a chassis panel, and may include mounting flanges 34a, 34b to mount the adapter via screws, for example.

A connector 10, 12 may include an inner housing 14 that may surround the ferrule 24. A connector 10, 12 may also include a displaceable outer housing member 36 that may be slidably disposed about the inner housing 14 adjacent the

5

second end of the connector 10, 12. To provide for a pre-determined alignment of the fiber optic cables within the adapter 15, the inner housing 14 may include an alignment key 38 that is configured to fit within keying slot 40 of the adapter. Inner housing 14 may slide into port 18a (for example) until tabs 32a, 32b engage into slots 42 of the inner housing 14. The outer housing 36 may be moved towards the second end to allow the tabs 32a, 32b to engage into slots 42, and to retain the tabs in the slots, the outer housing 36 may be slid back towards the first end and over the tabs within the port 18a. The outer housing 36 may be biased towards the first end via springs 44, as shown for example in FIG. 3, or alternative types of biasing devices.

A male connector 10 is depicted in exploded view in FIG. 3. In an embodiment as shown, the ferrule 24, as part of a terminal cable assembly 50, may fit within the inner housing 14. The assembly 50 may also include a guide pin retainer 52 (described in more detail below), a terminal housing 54 to which the cable 26 attaches via the terminal post 56. A biasing member, such as a spring 58 may be disposed between the terminal housing 54 and the pin retainer 52 to bias the ferrule 24 forwardly within the inner housing 14. Such biasing provides a biased mating of ferrule ends and optical fibers 16 when connectors 10, 12 are mated in an adapter 15 to thereby hold the mated ferrule ends and optical fibers in contact with one another.

A fiber optic cable 26 as shown in FIGS. 1A, 1B may be retained with the terminal post 56 by means of a crimp sleeve 60, or other type of detainment connector. A connector such as sleeve 60 may be crimped to the terminal post 56 as well as to a cable sheathing of the cable 26 to thereby prevent the cable from being pulled away from the terminal housing 54.

A more detailed view of the ferrule 24 and pin retainer 52 are represented in FIGS. 4, 5A and 5B. As represented, the ferrule 24 may include at least two pin receiving holes or passages 22 that extend through the body of the ferrule. Guide pins 20 may be attached with the pin retainer 52, and may be slidably inserted into the holes 22 from the rear end of the ferrule 24 to provide a male ferrule assembly as represented in FIG. 4, for a male connector 10 as represented in FIG. 1A. For a female connector 12, as represented in FIG. 1B, the pin retainer 52 may be used alone, without the attached guide pins 20, thereby leaving the holes 22 open for mating with guide pins of a male connector 10.

In an embodiment as represented in FIG. 6 and FIGS. 7A-7D, the pin retainer 52 may be configured so that the guide pins 20 may be insertable into, and removable from the pin retainer. For each guide pin 20, the pin retainer may include a pin retention configuration, which may include a clip formed from a pair of opposed arms 70a, 70b. The arms 70a, 70b may define a retention space 72 therebetween into which a guide pin 20 may be disposed. The retention space may be cylindrical and may have a diameter (d_1) that corresponds with a reduced diameter notch 20b formed in the guide pin 20. The notch 20b may have a diameter (d_2) that is less than the diameter (d_3) of the guide pin 20 at least adjacent each side of the notch.

The arms 70a, 70b may be configured to have a degree of resilience sufficient to allow the arms to move away from one another by an amount sufficient to allow a guide pin 20 to be inserted between the arms, and once the guide pin is inserted, have the arms return to their original position to retain the guide pin in place.

As represented by the dashed line in FIG. 6, a guide pin 20 may be laterally inserted into the retention space 72. The arms 70a, 70b may define a tapered groove 74 that has a first

6

width (w_1) at the exterior lateral side of the pin retainer 52, and tapers to a second width (w_2) adjacent the retention space 72. The first width (w_1) may be greater than the diameter (d_2) of the pin 20 in the notch 20b, and the second width (w_2) may be less than the diameter (d_2) of the pin in the notch, and the diameter (d_2) of the pin in the notch 20b may correspond essentially to the diameter (d_1) of the retention space 72. As the pin 20 is laterally inserted into the groove 74, the pin will move into the groove and first engage the arms 70a, 70b. The pin 20 may then be pressed further inward, displacing the arms 70a, 70b away from one another until the pin passes between the arms and moves into the retention space 72, at which point, the arms may return towards their original position and retain the pin therebetween, with the pin notch 20b, disposed in, and retained within the retention space.

Alternatively, a guide pin 20 may be inserted axially into the retention space 72 between the arms 70a, 70b. A tapered end 20a of the guide pin 20 may be tapered so that, as the guide pin is moved axially into the retention space 72, the tapered end 20a forces the arms 70a, 70b apart to the point wherein the guide pin may fit therebetween. The guide pin may then be further inserted until the notch 20b is disposed between the arms 70a, 70b, wherein the arms may return towards their original position and retain the pin therebetween.

Both axial ends of the notch 20b may be defined by a radial (orthogonal) edge 75a or 75b, extending from the reduced diameter (d_2) of the notch to the diameter (d_3) of the pin 20. As such, axial movement of the pin 20 out of the retention space may be prevented. For axial or lateral removal of the pin 20, the arms 70a, 70b need to be forced apart, as discussed further below, to create an opening of a size sufficient to allow the pin to pass therethrough. If, in an embodiment, the edge 75b were instead tapered from the reduced diameter (d_2) of the notch 20b to the diameter (d_3) of the pin 20, in a direction the tapered end 20a, application of an axial pulling force to the pin may allow for the pin to be axially withdrawn from the pin retainer 52 as the taper would slide between the arms 70a, 70b and open the arms as the pin was withdrawn. However, to prevent tampering, or unauthorized removal of the pins 20, a preferred embodiment requires the use of a tool, as discussed below with reference to FIGS. 12, 13A, 13B, 14A and 14B, for example, to force open the retaining arms 70a, 70b.

FIGS. 8A-8D provide top and side views, as well as sectional views of a pin 20 retained with a pin retainer 52. FIG. 8C depicts a longitudinal section through the pin 20 and pin retainer 52 of an embodiment as represented in FIG. 8A. As shown, the pin 20 may be axially retained within the pin retainer 52. FIG. 8D depicts a transverse section through the pin 20 and pin retainer 52 of an embodiment as represented in FIG. 8B. As shown, the pin 20 may be laterally retained within the pin retainer 52.

As represented in FIG. 9, to provide a fiber optic connector that may be changed from male (with pins 20) to female (without pins 20) access to release the pins may be provided via passages 80 that may be provided in the sides of the inner housing 14. In an embodiment as shown, the passages 80 may be provided within the slots 42. As represented in FIG. 9, in comparison to the view provided by FIG. 1A, the outer housing 36 may be moved rearwardly away from the front end of the connector to expose the slots 42 and passages 80. The passages 80 (refer to FIG. 10) may be configured to provide access to the arms 70a, 70b (refer to FIG. 11) through the walls of the inner housing 14.

The passages **80** may be configured to accommodate a release tool **82** as depicted in FIGS. 12-13B. In an embodiment, the release tool **82** may be configured to include at least two nibs **84a**, **84b** that fit through the passages **80**, one on each side of the inner housing **14**, so that, when forced inwardly through the passages, push the arms **70a**, **70b** apart by an amount sufficient to release the pins **20** from the pin retainer **52**. FIG. 13B depicts a general positioning of a release tool **82** and nibs **84a**, **84b** relative to a connector **10** with the outer housing **36** displaced rearwardly for removal of the pins **20**.

For clarity, FIGS. 14A and 14B reproduce only the pin retainer **52**, pins **20**, and a portion of the release tool **82** of FIG. 13B. As shown in FIGS. 14A and 14B, the tool nibs **84a**, **84b** may be aligned with the tapered groove **74** between the arms **70a**, **70b**. In an embodiment, the tool arms **82a**, **82b** may be squeezed towards one another to move the nibs **84a**, **84b** into the tapered groove **74** and between the arms **70a**, **70b** to displace the arms away from one another and away from the pins **20** as represented in FIG. 14B. After the arms **70a**, **70b** are sufficiently displaced, the pins **20** may be removed from the pin retainer **52** and from the connector **10** to change the connector from a male connector **10** (FIG. 1A) to a female connector **12** (FIG. 1B).

Referring to FIG. 6, 8B, 8C, 10 or 11, alternatively, a female connector **12** may be converted to a male connector **10** by inserting the tapered ends **20a** of the pins **20** into the guide/alignment holes **22**, and pushing the pins inwardly into the pin retainer **52**. Because of the tapered configuration of the ends **20a** of the pins **20**, the tapered ends **20a** may force the retainer arms **70a**, **70b** apart to make it possible for the pins to enter between the arms. When the pin notch **20b** passes into the retention space **72** between the arms, the arms may return to their original position to lock the pins in place. If desired, to facilitate insertion of the pins **20** into the pin retainer **52** the release tool **82** could be used to open the arms **70a**, **70b** thereby making it possible to insert the pins with less force on the pins.

An alternative embodiment of a release tool **90** is depicted in FIGS. 15A and 15B. As shown, the release tool **90** may be more compact while maintaining nibs **90a**, **90b** in a configuration appropriate for entering the passages **80**. While two variants of a release tool are shown, other configurations within the general skill of the artisan may also be provided. In an embodiment (not shown directly, but a variant of which is provided below) a separate tool may not be needed if the inner housing **14** was configured with release tabs that are integral with the housing and include nibs that project partially into the tapered groove **74**. A user may then simply squeeze the sides of the connector at the corresponding tabs to press the nibs further in the groove **74** to displace the arms **70a**, **70b**.

An alternative embodiment of a pin retainer **152** and associated release tool **182** are represented in FIGS. 16A-16D. Instead of having lateral tapered grooves **74** like the embodiment of pin retainer **52**, the retainer may be configured to include tapered grooves **174** that extend from a top or bottom surface of the retainer. Arms **170a** may be displaceable laterally away from a central core **175**. In essentially the same manner as previously discussed with reference to the earlier embodiments, the pins **20** may be retained within the retainer **152**, but between displaceable arms **170a** and the central core **175**. For converting a female connector to a male connector, the pins **20**, because of the tapered ends **20a**, may be pushed into the retainer **152** so that

as the tapered ends are pushed between the arms **170a** and the central core **175**, the arms may be forced away from the central core.

To convert from a male connector to a female connector, a release tool, such as tool **182** may be used to force the arms **170a** laterally away from the central core **175** to open the retainer and provide clearance for the pins **20** to be released from the retainer. In an embodiment (not shown), the tool **182** may be a separate tool carried by the user, and the inner housing **114** may include a corresponding opening, openings **115** for accommodating the tool so that the nibs **190a**, **190b** may be inserted through the housing to displace the arms **170a**.

In an alternative embodiment, as shown in FIGS. 16C and 16D, the tool **182** may be separate from the housings and retainer, but included as a component of the connector **111**. As represented in FIG. 16B, the tool **182** may include a body portion **183** from which the nibs **190a**, **190b** project. The tool **182** may include projecting hooks **191** that extend laterally away from the nibs **190a**, **190b** and body portion **183**, such that the body portion may define a first length (L_1) and the hooks define a second length (L_2) that is greater than the first length (L_1). The inner housing **114** may include an opening **115** that accommodates the body portion **183**. The opening **115** may have a width that is essentially the same as, or slightly greater than a width of the body portion **183**, and a length (L_3) that is essentially the same as or slightly greater than the length (L_1), but less than the length (L_2). With such a configuration of the tool **182**, the hooks **191** will not fit through the opening **115** so that the tool **182** is retained within the inner housing **114**. The tool body portion **183** may have flexibility and resiliency to allow the tool **182** to be bent for insertion through the opening. For example, a first side with nibs **190a** may be inserted through the opening **115**, the tool can be bent to reduce the length (L_3) to fit through the opening, and the second end with nibs **190b** may be inserted into place wherein the tool may then return to its original configuration as shown.

Application of an inward pressure on the body portion **183** may force the nibs **190a**, **190b** inwardly into the tapered grooves **174** to press arms **170a**, **170a** outwardly away from the central core **175**, thereby providing clearance between the pins **20** and the arms to allow the pins to be removed in a similar manner as to that shown and discussed with reference to FIG. 14B. While not shown in the drawings, the outer housing **36**, when in its forward position (shown displaced rearwardly in FIG. 16C), may completely cover, or alternatively cover a substantial portion of the tool body portion **183** and opening **115** to prevent an accidental force on the body portion from releasing the pins **20**.

An alternative configuration of a pin retainer **252** is represented in FIGS. 17A-17D. In an embodiment, a U-shaped retention clip **283** may include J-shaped hooks **271a**, **271b** at the ends of arms **270a**, **270b**. The J-shaped hooks **271a**, **271b** may be configured to curl into, or fit into the pin notches **20b** so that, when disposed in the notches, the pins **20** will be held within the pin retainer **252**. FIG. 17C represents a top view looking down at a J-hook **271b** and pin **20** from the top of the configuration of FIG. 17B. The pin retainer **252** may include resilient spring arms **253a**, **253b** configured to apply pressure to the J-hooks **271a**, **271b** to retain the J-hooks in the notches **20b**. With reference to FIG. 17B, resilient spring arms **253a**, **253b**, may apply a downward pressure on J-hooks **271a**, **271b** to hold the J-hooks in the notches **20b** (shown in cross-section).

Referring to FIG. 17A, to release pins **20**, an upward force against the spring arms **253a**, **253b** may be applied to the

clip **283** so that arms **270a**, **270b** move the J-hooks **271a**, **271b** upwardly and out of the notches **20b**. This will free the pins **20** so that the pins may be removed from the pin retainer **252**. Upon removal of the pins **20**, the spring arms **270a**, **270b** may return to their original position pushing the J-hooks **271a**, **271b** downwardly. As for previous embodiments, to insert pins **20** into the retainer **252**, the tapered ends **20a** may be inserted in and forced under the J-hooks **271a**, **271b** to move the J-hooks upwardly against the force of spring arms **253a**, **253b** until the notches **20b** are aligned with the J-hooks, at which time the J-hooks will be forced downwardly into the notches under the force of the spring arms.

As shown in cross-section in FIG. **17D**, the inner housing **214** may include an opening **215** for access (which could resemble the opening **115** as shown in FIG. **16C**) to press inwardly on the clip **283**. While not shown in the drawings, the outer housing **36**, when in its forward position may completely cover, or alternatively cover a substantial portion of, the clip **283** and opening **215** to prevent an accidental force on the body portion from releasing the pins **20**.

In an alternative embodiment, spring arms **253a**, **253b** could be configured to fit into the notches **20b** to engage with the pins **20** and retain the pins in the retainer **252** instead of the J-hooks. A U-shaped, or alternative configuration tool (not shown), for example a U-shaped tool essentially resembling the clip **283**, but without the J-hooks may be configured to release the pins **20**. The tool may be separate from the connector housing, or included as a part of the connector housing, and may be configured to be pushed into the housing to engage the spring arms **253a**, **253b** and move the spring arms away from and out of the notches **20b** to release the pins **20**.

As represented in FIGS. **18A** and **18B**, a pin retainer **352** may be configured integral with the inner housing **324** to form a one-piece housing unit (compared with the configuration of FIG. **4**). In an embodiment, the arms **370a**, **370b** may be configured similar to arms **70a**, **70b** as previously discussed, for example with reference to FIG. **6**. Arms **370a**, **370b** may define a tapered notch **374** therebetween, and a tool, such as tool **82** (FIG. **12**) may be used to open the arms for release of pins **20**.

Various parts, components or configurations described with respect to any one embodiment above may also be adapted to any others of the embodiments provided.

This disclosure is not limited to the particular systems, devices and methods described, as these may vary. The terminology used in the description is for the purpose of describing the particular versions or embodiments only, and is not intended to limit the scope.

In the above detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be used, and other changes may be made, without departing from the spirit or scope of the subject matter presented herein. It will be readily understood that the aspects of the present disclosure, as generally described herein, and illustrated in the figures, can be arranged, substituted, combined, separated, and designed in a wide variety of different configurations, all of which are explicitly contemplated herein.

The present disclosure is not to be limited in terms of the particular embodiments described in this application, which are intended as illustrations of various aspects. Many modi-

fications and variations can be made without departing from its spirit and scope, as will be apparent to those skilled in the art. Functionally equivalent methods and apparatuses within the scope of the disclosure, in addition to those enumerated herein, will be apparent to those skilled in the art from the foregoing descriptions. Such modifications and variations are intended to fall within the scope of the appended claims. The present disclosure is to be limited only by the terms of the appended claims, along with the full scope of equivalents to which such claims are entitled. It is to be understood that this disclosure is not limited to particular methods, reagents, compounds, compositions or biological systems, which can, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting.

As used in this document, the singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise. Unless defined otherwise, all technical and scientific terms used herein have the same meanings as commonly understood by one of ordinary skill in the art. Nothing in this disclosure is to be construed as an admission that the embodiments described in this disclosure are not entitled to antedate such disclosure by virtue of prior invention. As used in this document, the term “comprising” means “including, but not limited to.”

While various compositions, methods, and devices are described in terms of “comprising” various components or steps (interpreted as meaning “including, but not limited to”), the compositions, methods, and devices can also “consist essentially of” or “consist of” the various components and steps, and such terminology should be interpreted as defining essentially closed-member groups.

With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity.

It will be understood by those within the art that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to embodiments containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” with-

11

out other modifiers, means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that virtually any disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms. For example, the phrase “A or B” will be understood to include the possibilities of “A” or “B” or “A and B.”

In addition, where features or aspects of the disclosure are described in terms of Markush groups, those skilled in the art will recognize that the disclosure is also thereby described in terms of any individual member or subgroup of members of the Markush group.

As will be understood by one skilled in the art, for any and all purposes, such as in terms of providing a written description, all ranges disclosed herein also encompass any and all possible subranges and combinations of subranges thereof. Any listed range can be easily recognized as sufficiently describing and enabling the same range being broken down into at least equal halves, thirds, quarters, fifths, tenths, etc. As a non-limiting example, each range discussed herein can be readily broken down into a lower third, middle third and upper third, etc. As will also be understood by one skilled in the art all language such as “up to,” “at least,” and the like include the number recited and refer to ranges which can be subsequently broken down into subranges as discussed above. Finally, as will be understood by one skilled in the art, a range includes each individual member. Thus, for example, a group having 1-3 cells refers to groups having 1, 2, or 3 cells. Similarly, a group having 1-5 cells refers to groups having 1, 2, 3, 4, or 5 cells, and so forth.

Various of the above-disclosed and other features and functions, or alternatives thereof, may be combined into many other different systems or applications. Various presently unforeseen or unanticipated alternatives, modifications, variations or improvements therein may be subsequently made by those skilled in the art, each of which is also intended to be encompassed by the disclosed embodiments.

The invention claimed is:

1. A multi-fiber fiber optic connector configured to be converted between a female connector configuration and a male connector configuration by releasing or connecting notched guide pins, each notched guide pin including a retention notch, the multi-fiber fiber optic connector comprising:

- a housing having a front end portion and a rear end portion spaced apart along a longitudinal axis;
- a ferrule disposed in the housing for terminating a plurality of optical fibers, the ferrule having a front end portion and a rear end portion spaced apart along a

12

longitudinal axis, the ferrule comprising first and second guide pin passages extending longitudinally from the rear end portion through the front end portion, the first and second guide pin passages being spaced apart along a fiber alignment axis, the ferrule configured to hold a plurality of optical fibers in one or more rows parallel to the fiber alignment axis, the ferrule being configured to accept one of the notched guide pins in each of the first and second guide pin passages such that the retention notch is rearward of the rear end portion of the ferrule; and

- a pin keeper disposed in the housing rearward of the rear end portion of the ferrule, the pin keeper comprising a retention clip having an operating shape, the retention clip being movable in relation to the ferrule between a retaining position and a release position without deflection of the retaining clip from its operating shape during movement of the retention clip between the retaining position and the release position, wherein when the retention clip is in the retaining position, the retention clip is configured to move into the retention notches of the notched guide pins received in the first and second guide pin passages for retaining the notched guide pins in the first and second guide pin passages, wherein when the retention clip is in the release position, the retention clip disengages from the retention notches of notched guide pins received in the first and second guide pin passages for releasing the guide pins from the first and second guide pin passages; and
- wherein the multi-fiber fiber optic connector is configured so that the retention clip is resiliently biased toward the retaining position.

2. The multi-fiber fiber optic connector as set forth in claim 1, further comprising a spring configured to apply pressure to the retention clip to resiliently bias the retention clip toward the retaining position.

3. The multi-fiber fiber optic connector as set forth in claim 1, wherein the housing is an inner housing, the multi-fiber optic connector further comprising an outer housing disposed on the inner housing for movement relative to the inner housing between a forward position and a rear position.

4. The multi-fiber fiber optic connector as set forth in claim 3, wherein the inner housing comprises an access opening operatively aligned with the retention clip such that the retention clip can be moved from the retaining position to the release position.

5. The multi-fiber fiber optic connector as set forth in claim 4, wherein the outer housing is configured to cover the access opening in the forward position and expose the access opening in the rear position.

6. The multi-fiber fiber optic connector as set forth in claim 1, wherein the pin keeper further comprises a front body portion between the retention clip and the ferrule.

7. The multi-fiber fiber optic connector as set forth in claim 6, wherein the retention clip is a separate piece from the front body portion.

8. The multi-fiber fiber optic connector as set forth in claim 7, wherein the front body portion defines first and second guide pin openings through which notched guide pins extend rearward to the retention clip.

9. The multi-fiber fiber optic connector as set forth in claim 7, wherein the retention clip is displaceable in relation to the front body portion between the retaining position and the release position.

10. A multi-fiber fiber optic connector configured to be converted between a female connector configuration and a

13

male connector configuration by releasing or connecting notched guide pins, each notched guide pin including a retention notch, the multi-fiber fiber optic connector comprising:

- an housing having a front end portion and a rear end portion spaced apart along a longitudinal axis;
- a ferrule disposed in the housing for terminating a plurality of optical fibers, the ferrule having a front end portion and a rear end portion spaced apart along a longitudinal axis, the ferrule comprising first and second guide pin passages extending longitudinally from the rear end portion through the front end portion, the first and second guide pin passages being spaced apart along a fiber alignment axis, the ferrule configured to hold a plurality of optical fibers in one or more rows parallel to the fiber alignment axis, the ferrule being configured to accept one of the notched guide pins in each of the first and second guide pin passages such that the retention notch is rearward of the rear end portion of the ferrule;

- a pin keeper disposed in the housing rearward of the rear end portion of the ferrule, the pin keeper comprising a retention clip defining a first opening and a second opening larger than the first opening, the retention clip further defining a throat, the first and second openings communicating with each other through the throat, the pin keeper being adjustable for moving the retention clip between a retaining position and a release position by moving the entire retention clip relative to the ferrule such that the notched guide pin passes through the throat from the first opening to the second opening in a direction transverse to the alignment axis as the retention clip moves from the retaining position to the release position;

wherein when the retention clip is in the retaining position, the retention clip is configured to move into the retention notches of the notched guide pins received in the first and second guide pin passages for retaining the notched guide pins in the first and second guide pin passages; and

wherein when the retention clip is in the release position, the retention clip disengages from the retention notches of notched guide pins received in the first and second guide pin passages for releasing the guide pins from the first and second guide pin passages.

11. The multi-fiber fiber optic connector as set forth in claim 10, wherein the retention clip has a first arm having a curved end portion configured for selectively engaging the retention notch of a notched guide pin received in the first guide pin passage and a second arm having a curved end portion configured for selectively engaging the retention notch of a notched guide pin received in the second guide pin passage.

12. The multi-fiber optic connector as set forth in claim 11, wherein the clip is shaped and arranged such that the curved end portions of the first and second arms move conjointly in relation to the ferrule as the clip is moved.

13. The multi-fiber fiber optic connector of claim 12, wherein the curved end portions of the first and second arms define concave edges configured to face toward the notched guide pins, the concave edge of the first arm facing toward the fiber alignment axis.

14. The multi-fiber optic connector as set forth in claim 11, wherein the curved end portion of the first arm defines a curved hook.

15. The multi-fiber fiber optic connector as set forth in claim 10, wherein the multi-fiber fiber optic connector is

14

configured so that the retention clip is resiliently biased toward the retaining position.

16. A multi-fiber fiber optic connector configured to be converted between a female connector configuration and a male connector configuration by releasing or connecting notched guide pins, each notched guide pin including a retention notch, the multi-fiber fiber optic connector comprising:

- a housing having a front end portion and a rear end portion spaced apart along a longitudinal axis;

- a ferrule disposed in the housing for terminating a plurality of optical fibers, the ferrule having a front end portion and a rear end portion spaced apart along a longitudinal axis, the ferrule comprising first and second guide pin passages extending longitudinally from the rear end portion through the front end portion, the first and second guide pin passages being spaced apart along a fiber alignment axis, the ferrule configured to hold a plurality of optical fibers in one or more rows parallel to the fiber alignment axis, the ferrule being configured to accept one of the notched guide pins in each of the first and second guide pin passages such that the retention notch is rearward of the rear end portion of the ferrule;

- a pin keeper disposed in the housing rearward of the rear end portion of the ferrule, the pin keeper comprising a front body portion, a rear body portion, and a retention clip being disposed between front body portion and the rear body portion, the front body portion configured to pass the notched guide pins received in the first and second guide pin passages to the retention clip, the rear body portion defining a space for receiving rear end portions of notched guide pins retained by the retention clip, the retention clip being formed from a separate piece of material than the front body portion and the rear body portion, the retention clip being movable in relation to the ferrule between a retaining position and a release position;

wherein when the retention clip is in the retaining position, the retention clip is configured to move into the retention notches of the notched guide pins received in the first and second guide pin passages for retaining the notched guide pins in the first and second guide pin passages; and

wherein when the retention clip is in the release position, the retention clip disengages from the retention notches of notched guide pins received in the first and second guide pin passages for releasing the guide pins from the first and second guide pin passages.

17. The multi-fiber optic connector as set forth in claim 16, wherein the multi-fiber optic connector is configured to resiliently bias the retention clip toward the retaining position.

18. The multi-fiber fiber optic connector as set forth in claim 17, wherein the retention clip is configured to move between the retaining position and the release position substantially without deforming.

19. A multi-fiber fiber optic connector configured to be converted between a female connector configuration and a male connector configuration by releasing or connecting notched guide pins, each notched guide pin including a retention notch, the multi-fiber fiber optic connector comprising:

- an housing having a front end portion and a rear end portion spaced apart along a longitudinal axis;

- a ferrule disposed in the housing for terminating a plurality of optical fibers, the ferrule having a front end

15

portion and a rear end portion spaced apart along a longitudinal axis, the ferrule comprising first and second guide pin passages extending longitudinally from the rear end portion through the front end portion, the first and second guide pin passages being spaced apart along a fiber alignment axis, the ferrule configured to hold a plurality of optical fibers in one or more rows parallel to the fiber alignment axis, the ferrule being configured to accept one of the notched guide pins in each of the first and second guide pin passages;

a retention clip disposed in the housing, the retention clip defining a first opening and a second opening larger than the first opening, the retention clip further defining a throat, the first and second openings communicating with each other through the throat, the retention clip being movable with respect to the ferrule between a retaining position and a release position by moving the entire retention clip relative to the ferrule such that the notched guide pin passes in a direction transverse to the alignment axis through the throat from the first opening to the second opening as the retention clip moves from the retaining position to the release position;

wherein when the retention clip is in the retaining position, the retention clip is configured to move into the retention notches of the notched guide pins received in the first and second guide pin passages for retaining the notched guide pins in the first and second guide pin passages; and

wherein when the retention clip is in the release position, the retention clip disengages from the retention notches of notched guide pins received in the first and second guide pin passages for releasing the guide pins from the first and second guide pin passages.

20. The multi-fiber fiber optic connector as set forth in claim **19** wherein the retention clip has an external perimeter and axial projections of the first and second guide pin passages remain within the external perimeter of the in the retaining position and in the release position.

21. The multi-fiber fiber optic connector as set forth in claim **20**, wherein the retention clip is configured to move between the retaining position and the release position substantially without deforming.

22. The multi-fiber fiber optic connector as set forth in claim **20**, wherein the retention clip comprises a single piece of material configured to simultaneously engage into the retention notches of the two notched guide pins received in the first and second guide pin passages in the retaining position.

23. The multi-fiber fiber optic connector as set forth in claim **22**, the retention clip defining a pair of first openings spaced apart along the lateral axis, a pair of second openings larger than the first openings spaced apart along the lateral axis, and a pair of throats spaced apart along the lateral axis, wherein each first opening communicates with a respective second opening through a respective throat, wherein the retention clip is sized and arranged so that:

when the retention clip is in the retaining position, the first and second guide pin passages are aligned vertically and laterally with the pair of first openings such that the notched guide pins received in the first and second guide pin passages are seated in the pair of first openings;

when the retention clip is in the release position, the first and second guide pin passages are aligned vertically and laterally with the pair of second openings; and

16

as the retention clip moves from the retaining position to the release position, the notched guide pins received in the first and second guide pin passages pass from the pair of first openings to the pair of second openings through the pair of throats.

24. A multi-fiber fiber optic connector configured to be converted between a female connector configuration and a male connector configuration by releasing or connecting notched guide pins, each notched guide pin including a retention notch, the multi-fiber fiber optic connector comprising:

an inner housing having a front end portion and a rear end portion spaced apart along a longitudinal axis, the inner housing having opposite first and second side walls spaced apart along a lateral axis perpendicular to the longitudinal axis, and a top wall and a bottom wall spaced apart along a vertical axis perpendicular to the lateral axis, the inner housing having an access opening for facilitating gender change;

a ferrule disposed in the inner housing for terminating a plurality of optical fibers, the ferrule having a front end portion and a rear end portion spaced apart along a longitudinal axis, the ferrule comprising first and second guide pin passages extending longitudinally from the rear end portion through the front end portion, the first and second guide pin passages being spaced apart along a fiber alignment axis parallel to the lateral axis, the ferrule configured to hold a plurality of optical fibers in one or more rows parallel to the fiber alignment axis, the ferrule being configured to accept one of the notched guide pins in each of the first and second guide pin passages such that the retention notch is rearward of the rear end portion of the ferrule;

a retention clip disposed in the inner housing rearward of the rear end portion of the ferrule, the retention clip adjustable via the access opening for moving the retention clip between a retaining position and a release position by displacing the entire retention clip relative to the ferrule in a plane transverse to the longitudinal axis;

wherein when the retention clip is in the retaining position, the retention clip is configured to engage into the retention notches of the notched guide pins received in the first and second guide pin passages for retaining the notched guide pins in the first and second guide pin passages; and

wherein when the retention clip is in the release position, the retention clip disengages from the retention notches of notched guide pins received in the first and second guide pin passages for releasing the guide pins from the first and second guide pin passages.

25. The multi-fiber fiber optic connector as set forth in claim **24**, wherein the retention clip has a first curved surface configured for selectively engaging the retention notch of a notched guide pin received in the first guide pin passage and a second curved surface configured for selectively engaging the retention notch of a notched guide pin received in the second guide pin passage.

26. The multi-fiber optic connector as set forth in claim **25**, wherein the first and second curved surfaces move conjointly in relation to the ferrule as the retention clip is displaced in the plane transverse to the longitudinal axis.

27. The multi-fiber fiber optic connector of claim **25**, wherein the first curved surface and the second curved surface face in a vertical direction.

* * * * *