

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250254944

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

SHI; Yun et al.

TRANSISTOR DEVICES, CIRCUITS AND METHODS FOR RADIO-FREQUENCY APPLICATIONS

Abstract

A method for fabricating a transistor can include forming a plurality of source regions and a plurality of drain regions arranged in an alternating manner, such that each of the source regions and the drain regions is implemented as a first type active region; and implementing a plurality of gate structures relative to the source regions and the drain regions such that application of a voltage to each gate structure results in formation of a conductive channel between a respective pair of source and drain regions. The method can further include forming a body region to provide the respective conductive channel upon the application of the voltage to the corresponding gate structure, such that the body region is implemented as a second type active region; and forming a recessed region at an end of each drain region and one or both of the gate structures adjacent to the drain region.

Inventors: SHI; Yun (San Diego, CA), LEE; Tzung-Yin (Costa Mesa, CA)

Applicant: SKYWORKS SOLUTIONS, INC. (Irvine, CA)

Family ID: 73046526

Appl. No.: 19/012732

Filed: January 07, 2025

Related U.S. Application Data

parent US continuation 18353478 20230717 parent-grant-document US 12191353 child US 19012732

parent US continuation 16872575 20200512 parent-grant-document US 11705487 child US 18353478

us-provisional-application US 62846684 20190512

Publication Classification

Int. Cl.: **H10D62/10** (20250101); **H10D30/69** (20250101); **H10D62/17** (20250101); **H10D64/27** (20250101)

U.S. Cl.:

CPC **H10D62/127** (20250101); **H10D30/711** (20250101); **H10D62/393** (20250101); **H10D64/519** (20250101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) [0001] This application is a continuation of U.S. application Ser. No. 18/353,478 filed Jul. 17, 2023, entitled TRANSISTORS FOR RADIO-FREQUENCY CIRCUITS AND DEVICES, which is a continuation of U.S. application Ser. No. 16/872,575 filed May 12, 2020, entitled TRANSISTORS HAVING REDUCED PARASITICS AND ENHANCED PERFORMANCE, which claims priority to and the benefit of the filing date of U.S. Provisional Application No. 62/846,684 filed May 12, 2019, entitled TRANSISTORS HAVING REDUCED PARASITICS AND ENHANCED PERFORMANCE, the benefits of the filing dates of which are hereby claimed and the disclosures of which are hereby expressly incorporated by reference herein in their entirety.

BACKGROUND

Field

[0002] The present disclosure relates to transistors having reduced parasitics.

Description of the Related Art

[0003] Transistors such as field-effect transistors (FETs) can be utilized in a number of electronic applications. Such a transistor typically includes some parasitic effects resulting from, for example, structure and arrangement of various parts of the transistor. In many situations, such parasitic effects can degrade performance of the transistor.

SUMMARY

[0004] In some implementations, the present disclosure relates to a transistor that includes a source and a drain each implemented as a first type active region, and a gate implemented relative to the source and the drain such that application of a voltage to the gate results in formation of a conductive channel between the source and the drain. The transistor further includes a body configured to provide the conductive channel upon the application of the voltage to the gate. The body is implemented as a second type active region that butts with the first type active region on the source side at a respective area not covered by the gate, and does not butt with the first type active region on the drain side at a respective area not covered by the gate.

[0005] In some embodiments, the first type active region can include an N⁺ active region, and the second type active region can include a P⁺ active region.

[0006] In some embodiments, the transistor can further include an insulator layer implemented under the body, such that the body is a floating body.

[0007] In some embodiments, the transistor can further include a gate oxide layer between the gate and the body.

[0008] In some embodiments, the second type active region of the body butting with the first type active region of the source can result in electrical potentials of the source and the body to be approximately same.

[0009] In some embodiments, the gate can have a symmetric shape about a line along a width

direction of the gate. In some embodiments, the gate can have a rectangular shape dimensioned to allow the butting of the second type active region of the body and the first type active region of the source. The second type active region of the body can include a boundary substantially along the width direction line of the gate. In some embodiments, the gate can have a modified T shape with a shortened extension along a direction perpendicular to the width direction, with the shortened extension of the gate being dimensioned to allow the butting of the second type active region of the body and the first type active region of the source. The second type active region of the body can include a boundary substantially along the width direction line of the gate.

[0010] In some embodiments, the gate can have an asymmetric shape about a line along a width direction of the gate. The gate can have a modified L shape with a shortened extension along a direction perpendicular to the width direction, with the shortened extension of the gate being dimensioned to allow the butting of the second type active region of the body and the first type active region of the source. The second type active region of the body can include a boundary that is offset towards the source side from the width direction line of the gate.

[0011] In some embodiments, the gate can have first and second ends along a width direction of the gate. In some embodiments, the second type active region of the body that butts with the first type active region on the source side can be implemented on one of the first and second ends of the gate. In some embodiments, the second type active region of the body that butts with the first type active region on the source side can be implemented on each of the first and second ends of the gate.

[0012] According to some teachings, the present disclosure relates to a semiconductor die that includes a substrate and one or more transistors implemented on the substrate. Each transistor includes a source and a drain each implemented as a first type active region, and a gate implemented relative to the source and the drain such that application of a voltage to the gate results in formation of a conductive channel between the source and the drain. The transistor further includes a body configured to provide the conductive channel upon the application of the voltage to the gate. The body is implemented as a second type active region that butts with the first type active region on the source side at a respective area not covered by the gate, and does not butt with the first type active region on the drain side at a respective area not covered by the gate.

[0013] In some embodiments, the substrate can include a silicon-on-insulator substrate. In some embodiments, each transistor can be configured as a radio-frequency transistor. In some embodiments, each transistor can be configured as a digital cell transistor.

[0014] In accordance with a number of implementations, the present disclosure relates to a packaged module that includes a packaging substrate and a semiconductor die mounted on the packaging substrate. The semiconductor die includes one or more transistors, with each transistor including a source and a drain each implemented as a first type active region, and a gate implemented relative to the source and the drain such that application of a voltage to the gate results in formation of a conductive channel between the source and the drain. The transistor further includes a body configured to provide the conductive channel upon the application of the voltage to the gate, with the body being implemented as a second type active region that butts with the first type active region on the source side at a respective area not covered by the gate, and does not butt with the first type active region on the drain side at a respective area not covered by the gate.

[0015] In some teachings, the present disclosure relates to a transistor that includes a plurality of source regions and a plurality of drain regions arranged in an alternating manner, with each of the source regions and the drain regions being implemented as a first type active region. The transistor further includes a plurality of gate structures implemented relative to the source regions and the drain regions such that application of a voltage to each gate structure results in formation of a conductive channel between a respective pair of source and drain regions. The transistor further includes a body region configured to provide the respective conductive channel upon the application of the voltage to the corresponding gate structure, with the body region being

implemented as a second type active region. The transistor further includes a recessed region defined by an end of each drain region and one or both of the gate structures adjacent to the drain region.

[0016] In some embodiments, the transistor can further include an insulator layer implemented under the body regions, such that the body regions function as a floating body.

[0017] In some embodiments, the transistor can further include a gate oxide layer between each gate structure and the respective body region.

[0018] In some embodiments, each first type active region can include an N⁺ active region, and each second type active region can include a P⁺ active region. In some embodiments, the N⁺ active regions can be parts of an N⁺ implant region, and the P⁺ active regions can be parts of a P⁺ implant region. In some embodiments, each recessed region can include a portion of the P⁺ implant region bordered by two neighboring P⁺ body regions, and a portion of the N⁺ implant region bordered by two neighboring gate structures and the end of the respective drain region. The P⁺ implant region and the N⁺ implant region can be dimensioned such that the P⁺ body region under the respective gate structure has a reduced width to reduce parasitic capacitance associated with the gate structure.

[0019] In some embodiments, each recessed region can include a portion of an N⁺ implant region implemented between two neighboring P⁺ implant regions having the respective P⁺ body regions, and the end of the respective drain region. Each P⁺ body region can be dimensioned to include a portion that is not covered by the respective gate structure and having an edge forms a butted P⁺/N⁺ interface with a respective N⁺ source region. The portion of the P⁺ body region forming the butted P⁺/N⁺ interface with the N⁺ source region can result in electrical potentials of the source region and the body region to be approximately same.

[0020] In some embodiments, the transistor can further include another recessed region defined by the other end of each drain region and the one or both of the gate structures adjacent to the drain region.

[0021] In a number of implementations, the present disclosure relates to a semiconductor die that includes a substrate and one or more transistors implemented on the substrate. Each transistor includes a plurality of source regions and a plurality of drain regions arranged in an alternating manner, with each of the source regions and the drain regions being implemented as a first type active region. The transistor further includes a plurality of gate structures implemented relative to the source regions and the drain regions such that application of a voltage to each gate structure results in formation of a conductive channel between a respective pair of source and drain regions. The transistor further includes a body region configured to provide the respective conductive channel upon the application of the voltage to the corresponding gate structure, with the body region being implemented as a second type active region. The transistor further includes a recessed region defined by an end of each drain region and one or both of the gate structures adjacent to the drain region.

[0022] In some embodiments, the substrate can include a silicon-on-insulator substrate. In some embodiments, each transistor can be configured as a radio-frequency transistor. In some embodiments, each transistor can be configured as a digital cell transistor.

[0023] In some implementations, the present disclosure relates to a packaged module that includes a packaging substrate and a semiconductor die mounted on the packaging substrate and including one or more transistors. Each transistor includes a plurality of source regions and a plurality of drain regions arranged in an alternating manner, with each of the source regions and the drain regions being implemented as a first type active region. The transistor further includes a plurality of gate structures implemented relative to the source regions and the drain regions such that application of a voltage to each gate structure results in formation of a conductive channel between a respective pair of source and drain regions. The transistor further includes a body region configured to provide the respective conductive channel upon the application of the voltage to the

corresponding gate structure, with the body region being implemented as a second type active region. The transistor further includes a recessed region defined by an end of each drain region and one or both of the gate structures adjacent to the drain region.

[0024] In some teachings, the present disclosure relates to a transistor that includes a source and a drain each implemented as a first type active region, and a gate implemented relative to the source and the drain such that application of a voltage to the gate results in formation of a conductive channel between the source and the drain. The transistor further includes a body configured to provide the conductive channel upon the application of the voltage to the gate, with the body being implemented as a second type active region, and the gate defining an opening dimensioned to allow a contact with the body to reduce parasitic capacitance associated with the gate.

[0025] In some embodiments, the first type active region can include an N⁺ active region, and the second type active region can include a P⁺ active region. In some embodiments, the gate can have first and second ends along a width direction of the gate. In some embodiments, the second type active region of the body and the respective opening of the gate can be implemented on one of the first and second ends of the gate. In some embodiments, the second type active region of the body and the respective opening of the gate can be implemented on each of the first and second ends of the gate.

[0026] In accordance with some teachings, the present disclosure relates to a semiconductor die that includes a substrate and one or more transistors implemented on the substrate. Each transistor includes a source and a drain each implemented as a first type active region, and a gate implemented relative to the source and the drain such that application of a voltage to the gate results in formation of a conductive channel between the source and the drain. The transistor further includes a body configured to provide the conductive channel upon the application of the voltage to the gate, with the body being implemented as a second type active region, and the gate defining an opening dimensioned to allow a contact with the body to reduce parasitic capacitance associated with the gate.

[0027] In a number of implementations, the present disclosure relates to a packaged module that includes a packaging substrate and a semiconductor die mounted on the packaging substrate and including one or more transistors. Each transistor includes a source and a drain each implemented as a first type active region, and a gate implemented relative to the source and the drain such that application of a voltage to the gate results in formation of a conductive channel between the source and the drain. The transistor further includes a body configured to provide the conductive channel upon the application of the voltage to the gate, with the body being implemented as a second type active region, and the gate defining an opening dimensioned to allow a contact with the body to reduce parasitic capacitance associated with the gate.

[0028] For purposes of summarizing the disclosure, certain aspects, advantages and novel features of the inventions have been described herein. It is to be understood that not necessarily all such advantages may be achieved in accordance with any particular embodiment of the invention. Thus, the invention may be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0029] FIG. 1 depicts a transistor having one or more features as described herein.

[0030] FIG. 2 shows that in some embodiments, the transistor of FIG. 1 can be implemented in a circuit and/or a device.

[0031] FIG. 3 shows an example of a silicon-on-insulator (SOI) transistor having a floating body

configuration.

[0032] FIG. 4A shows a sectional view as indicated in FIG. 3.

[0033] FIG. 4B shows another sectional view as indicated in FIG. 3.

[0034] FIG. 5 shows another example of a silicon-on-insulator (SOI) transistor having a floating body configuration, and an L-shape gate.

[0035] FIG. 6 shows a silicon-on-insulator (SOI) transistor having an active region and an N+ implant region.

[0036] FIG. 7 shows that in some embodiments, a region opposing the P+ implant region of FIG. 6 can be implemented as an N+ implant region.

[0037] FIG. 8 shows that in some embodiments, a transistor can be similar to the example of FIG. 7, but with a P+ implant region on each of the two ends of the gate.

[0038] , FIG. 9 shows a transistor having a modified T-shape gate with a shortened extension to allow a butted P+/N+ interface on one side of the gate.

[0039] FIG. 10 shows that in some embodiments, a region opposing the P+ implant region of FIG. 9 can be implemented as an N+ implant region.

[0040] FIG. 11 shows that in some embodiments, a transistor can include a butted P+/N+ interface on one side of a gate for each of both ends of the gate.

[0041] FIG. 12 shows a transistor having a modified L-shape gate with a shortened extension to allow a butted P+/N+ interface on one side of the gate.

[0042] FIG. 13 shows that in some embodiments, a region opposing the P+ implant region of FIG. 12 can be implemented as an N+ implant region.

[0043] FIG. 14 shows that in some embodiments, a transistor can include a butted P+/N+ interface on one side of a gate for each of both ends of the gate.

[0044] FIGS. 15A and 15B show that in some embodiments, a silicon-on-insulator (SOI) transistor can include an active region and an N+ implant region.

[0045] FIG. 16 shows that in some embodiments, a silicon-on-insulator (SOI) transistor can include a plurality of gate structures, and such gate structures can separate alternating source and drain regions.

[0046] FIG. 17 shows a transistor having gate structures, source regions and drain regions similar to the example FIG. 16.

[0047] FIG. 18 shows that in some embodiments, a transistor can include recessed regions associated with the drain regions for each of both ends of the gate.

[0048] FIG. 19 shows a transistor having gate structures, source regions and drain regions similar to the example FIG. 16.

[0049] FIG. 20 shows that in some embodiments, a transistor can include recessed regions associated with the drain regions for each of both ends of the gate.

[0050] FIG. 21 shows that in some embodiments, a transistor can include a gate such as a T-shape gate.

[0051] FIG. 22 shows that in some embodiments, a transistor can include an opening similar to the example of FIG. 21, for each of both ends of the gate.

[0052] FIG. 23 shows that in some embodiments, one or more transistors as described herein can be implemented on a device such as a die.

[0053] FIG. 24 shows that in some embodiments, a die/device can include one or more transistors as described herein, configured as RF building blocks.

[0054] FIG. 25 shows that in some embodiments, a die/device can include one or more transistors as described herein, configured for digital applications.

[0055] FIG. 26 shows that in some embodiments, one or more transistors as described herein can be implemented in a packaged module.

[0056] FIG. 27 depicts an example wireless device having one or more advantageous features described herein.

DETAILED DESCRIPTION OF SOME EMBODIMENTS

[0057] The headings provided herein, if any, are for convenience only and do not necessarily affect the scope or meaning of the claimed invention.

[0058] FIG. 1 depicts a transistor **100** having one or more features as described herein. FIG. 2 shows that in some embodiments, the transistor **100** of FIG. 100 can be implemented in a circuit and/or a device **102**. Accordingly, the circuit/device **102** can benefit from the one or more features of the transistor **100**. Examples related to such a transistor and related circuit/device are described herein in greater detail.

[0059] In metal-oxide-semiconductor field-effect transistors (MOSFETs) such as silicon-on-insulator (SOI) transistors, a floating-body (FB) configuration can provide lower parasitics (e.g., parasitic capacitance) than a body-connected (BC) configuration. Thus, FB SOI transistors tend to provide better performance than BC SOI transistors. However, the floating-body effect can limit practical applications of FB SOI transistors.

[0060] FIG. 3 shows an example of a silicon-on-insulator (SOI) transistor **10** having a floating body configuration. FIGS. 4A and 4B show sectional views as indicated in FIG. 3.

[0061] In FIGS. 3 and 4, the example transistor **10** is shown to include an N⁺ implant region **14** and a P⁺ implant region **12** formed over an insulator layer **28** (e.g., a buried oxide (BOX) layer). The N⁺ implant region **14** can include an N⁺ active region **20** and an N⁺ active region **22**. Such active regions can function as source (S) and drain (D) of the transistor **10**. The P⁺ implant region **12** can include a P⁺ active region **18**, and a portion of such an active region can function as a body of the transistor **10**.

[0062] In the example of FIGS. 3 and 4, a gate structure **24** is shown to be implemented over the foregoing active regions **20**, **22**, **18**. In some embodiments, such a gate can include, for example, polysilicon material. As shown in FIGS. 4A and 4B, a body **26** can be at least partially between the two N⁺ active regions **20**, **22**, and can be at least partially under the gate **24**. Typically, an insulator layer such as a gate oxide layer can be present between the gate **24** and the body **26**.

[0063] FIG. 3 shows an example where the gate **24** has a T-shape. FIG. 5 shows another example of a silicon-on-insulator (SOI) transistor **10** having a floating body configuration, and an L-shape gate **24**. In the example of FIG. 5, the example transistor **10** is shown to include an N⁺ implant region **14** and a P⁺ implant region **12** formed over an insulator layer (e.g., **28** in FIG. 4A) (e.g., a buried oxide (BOX) layer). The N⁺ implant region **14** can include an N⁺ active region **20** and an N⁺ active region **22**. Such active regions can function as source (S) and drain (D) of the transistor **10**. The P⁺ implant region **12** can include a P⁺ active region **18**, and a portion of such an active region can function as a body of the transistor **10**.

[0064] In the example of FIG. 5, the L-shaped gate structure **24** is shown to be implemented over the foregoing active regions **20**, **22**, **18**. In some embodiments, such a gate can include, for example, polysilicon material. Similar to the example of FIG. 3, a body can be at least partially between the two N⁺ active regions **20**, **22**, and can be at least partially under the gate **24**. Typically, an insulator layer such as a gate oxide layer can be present between the gate **24** and the body.

[0065] In the example of FIG. 5, the P⁺ active area **18** and the N⁺ active area **22** can be butted with each other generally along an interface **23**. With such a configuration, and assuming that the N⁺ active area **22** is configured as a source (S), the source (S) and the body (B) can have a common potential so as to provide $V_{SB}=0$ across the butted P⁺/N⁺ interface **23**.

[0066] In the example of FIG. 5, it is noted that the P⁺ implant region **12** extends from the N⁺ active region **22** (butted) to the N⁺ active region **20** (not butted).

[0067] It is noted that in the examples of FIGS. 3-5, parasitic capacitances (e.g., gate capacitance C_{gg}) associated with the T-shape and L-shape gates can be about two or three times an intrinsic parasitic capacitance associated with the transistors. Accordingly, such parasitic capacitances C_{gg} can lead to undesirable effects such as, for example, reduced speed in digital cell applications, and increased loss in radio-frequency (RF) applications.

[0068] In some embodiments, the present disclosure relates to a transistor having a P+ implant region implemented on one side of a gate, and the corresponding region on the other side of the gate being a non-P+ implant region.

[0069] For example, FIG. 6 shows a silicon-on-insulator (SOI) transistor **100** having an active region **116** and an N+ implant region **114**. In some embodiments, a P+ implant region **111** can be formed on a first side of a gate **124**, but not on the other side. The N+ implant region **114** can include a first N+ active region **120** and a second N+ active region **122**. Such active regions can function as source (S) and drain (D) of the transistor **100**. The P+ implant region **111** can include a P+ active region **118**, and a portion of such an active region can function as a body of the transistor **100**. Thus, the P+ body **118** is implemented on the first side (e.g., the source side associated with the N+ active region **120**), but not on the other side (e.g., the drain side associated with the N+ active region **122**).

[0070] In the example of FIG. 6, the gate structure **124** is shown to be implemented as a rectangular shape. In some embodiments, such a gate can include, for example, polysilicon material. A body which is coupled to the P+ body **118** can be at least partially between the two N+ active regions **120**, **122**, and can be at least partially under the gate **124**. Typically, an insulator layer such as a gate oxide layer can be present between the gate **124** and the body.

[0071] In the example of FIG. 6, the P+ active area **118** and the first N+ active area **120** can be butted with each other generally along an interface **123**. With such a configuration, and assuming that the first N+ active region **120** is configured as a source (S), the source (S) and the body (B) can have a common potential so as to provide $V_{sub,SB}=0$ across the butted P+/N+ interface **123**. Such a configuration can remove or reduce parasitic capacitance C_{gg} associated with the gate **124**.

[0072] FIG. 7 shows that in some embodiments, a region opposing the P+ implant region **111** of FIG. 6 (and on the side of the second N+ active region **122**) can be implemented as an N+ implant region **113**. Such an N+ implant region (**113**) can be contiguous with the N+ implant region **114**, be formed separately, or some combination thereof. In the example of FIG. 7, other portions of the transistor **100** can be similar to the example of FIG. 6.

[0073] In the examples of FIGS. 6 and 7, the butted P+/N+ interface **123** on one side of the rectangular shaped gate **124** is implemented on one end of the gate. FIG. 8 shows that in some embodiments, a transistor **100** can include a butted P+/N+ interface **123** on one side of a gate **124** for each of both ends of the gate. For example, in FIG. 8, the transistor **100** can be similar to the example of FIG. 7, but with a P+ implant region on each of the two ends of the gate **124**. More particularly, a first P+ implant region **111a** can include a first P+ active region **118a**, and a portion of such an active region can function as a body of the transistor **100**. Thus, the first P+ body **118a** is implemented on the first side (e.g., the source side associated with the N+ active region **120**), but not on the other side (e.g., the drain side associated with the N+ active region **122**). Similarly, a second P+ implant region **111b** can include a second P+ active region **118b**, and a portion of such an active region can function as a body of the transistor **100**.

[0074] In the examples of FIGS. 6-8, the rectangular shaped gate allows for the respective butted P+/N+ interfaces (**123**). FIGS. 9-14 show examples of transistors with gate shapes that are different than the rectangular shaped gates of FIGS. 6-8.

[0075] For example, FIG. 9 shows a transistor **100** (e.g., an SOI transistor) having a modified T-shape gate **124** with a shortened extension (sideway when viewed as depicted in FIG. 9) to allow a butted P+/N+ interface **123** on one side of the gate **124**. The transistor **100** is shown to include an active region **116** and an N+ implant region **114**. In some embodiments, a P+ implant region **111** can be formed on a first side of a gate **124**, but not on the other side. The N+ implant region **114** can include a first N+ active region **120** and a second N+ active region **122**. Such active regions can function as source (S) and drain (D) of the transistor **100**. The P+ implant region **111** can include a P+ active region **118**, and a portion of such an active region can function as a body of the transistor **100**. Thus, the P+ body **118** is implemented on the first side (e.g., the source side

associated with the N+ active region **120**), but not on the other side (e.g., the drain side associated with the N+ active region **122**).

[0076] In the example of FIG. **9**, the gate structure **124** is shown to be implemented as a modified T-shape. In some embodiments, such a gate can include, for example, polysilicon material. A body which is coupled to the P+ body **118** can be at least partially between the two N+ active regions **120**, **122**, and can be at least partially under the gate **124**. Typically, an insulator layer such as a gate oxide layer can be present between the gate **124** and the body.

[0077] In the example of FIG. **9**, the P+ active area **118** and the first N+ active area **120** can be butted with each other generally along an interface **123**. In some embodiments, such a butted P+/N+ interface **123** is not covered by the gate **124**.

[0078] With the foregoing configuration, and assuming that the first N+ active region **120** is configured as a source (S), the source (S) and the body (B) can have a common potential so as to provide $V_{sub,SB}=0$ across the butted P+/N+ interface **123**. Such a configuration can remove or reduce parasitic capacitance C_{gg} associated with the gate **124**.

[0079] FIG. **10** shows that in some embodiments, a region opposing the P+ implant region **111** of FIG. **9** (and on the side of the second N+ active region **122**) can be implemented as an N+ implant region **113**. Such an N+ implant region (**113**) can be contiguous with the N+ implant region **114**, be formed separately, or some combination thereof. In the example of FIG. **10**, other portions of the transistor **100** can be similar to the example of FIG. **9**.

[0080] In the examples of FIGS. **9** and **10**, the butted P+/N+ interface **123** on one side of the modified T-shaped gate **124** is implemented on one end of the gate. FIG. **11** shows that in some embodiments, a transistor **100** can include a butted P+/N+ interface **123** on one side of a gate for each of both ends of the gate. For example, in FIG. **11**, the transistor **100** can be similar to the example of FIG. **10**, but with a P+ implant region on each of the two ends of the gate **124**. More particularly, a first P+ implant region **111a** can include a first P+ active region **118a**, and a portion of such an active region can function as a body of the transistor **100**. Thus, the first P+ body **118a** is implemented on the first side (e.g., the source side associated with the N+ active region **120**), but not on the other side (e.g., the drain side associated with the N+ active region **122**). Similarly, a second P+ implant region **111b** can include a second P+ active region **118b**, and a portion of such an active region can function as a body of the transistor **100**.

[0081] In another example, FIG. **12** shows a transistor **100** (e.g., an SOI transistor) having a modified L-shape gate **124** with a shortened extension (sideway to the left when viewed as depicted in FIG. **12**) to allow a butted P+/N+ interface **123** on one side of the gate **124**. The transistor **100** is shown to include an active region **116** and an N+ implant region **114**. In some embodiments, a P+ implant region **111** can be formed on a first side of a gate **124**, but not on the other side. The N+ implant region **114** can include a first N+ active region **120** and a second N+ active region **122**. Such active regions can function as source (S) and drain (D) of the transistor **100**. The P+ implant region **111** can include a P+ active region **118**, and a portion of such an active region can function as a body of the transistor **100**. Thus, the P+ body **118** is implemented on the first side (e.g., the source side associated with the N+ active region **120**), but not on the other side (e.g., the drain side associated with the N+ active region **122**).

[0082] In the example of FIG. **12**, the gate structure **124** is shown to be implemented as a modified L-shape. In some embodiments, such a gate can include, for example, polysilicon material. A body which is coupled to the P+ body **118** can be at least partially between the two N+ active regions **120**, **122**, and can be at least partially under the gate **124**. Typically, an insulator layer such as a gate oxide layer can be present between the gate **124** and the body.

[0083] In the example of FIG. **12**, the P+ active area **118** and the first N+ active area **120** can be butted with each other generally along an interface **123**. In some embodiments, such a butted P+/N+ interface **123** is not covered by the gate **124**.

[0084] With the foregoing configuration, and assuming that the first N+ active region **120** is

configured as a source (S), the source (S) and the body (B) can have a common potential so as to provide $V_{sub.SB}=0$ across the butted P+/N+ interface **123**. Such a configuration can remove or reduce parasitic capacitance C_{gg} associated with the gate **124**.

[0085] FIG. **13** shows that in some embodiments, a region opposing the P+ implant region **111** of FIG. **12** (and on the side of the second N+ active region **122**) can be implemented as an N+ implant region **113**. Such an N+ implant region (**113**) can be contiguous with the N+ implant region **114**, be formed separately, or some combination thereof. In the example of FIG. **13**, other portions of the transistor **100** can be similar to the example of FIG. **12**.

[0086] In the examples of FIGS. **12** and **13**, the butted P+/N+ interface **123** on one side of the modified L-shaped gate **124** is implemented on one end of the gate. FIG. **14** shows that in some embodiments, a transistor **100** can include a butted P+/N+ interface **123** on one side of a gate for each of both ends of the gate. For example, in FIG. **14**, the transistor **100** can be similar to the example of FIG. **13**, but with a P+ implant region on each of the two ends of the gate **124**. More particularly, a first P+ implant region **111a** can include a first P+ active region **118a**, and a portion of such an active region can function as a body of the transistor **100**. Thus, the first P+ body **118a** is implemented on the first side (e.g., the source side associated with the N+ active region **120**), but not on the other side (e.g., the drain side associated with the N+ active region **122**). Similarly, a second P+ implant region **111b** can include a second P+ active region **118b**, and a portion of such an active region can function as a body of the transistor **100**.

[0087] In at least some of the examples of FIGS. **12-14**, the P+ implant region (**111**) can be dimensioned and positioned to be on the source side of the respective gate (**124**). For example, suppose that a middle of the gate **124** is defined along a midline of the strip (vertical strip when viewed as shown in FIGS. **12-14**) that separates the source and drain regions **120**, **122**. With such an assumption, the P+ implant region (**111**) can be dimensioned and positioned so as to be entirely on the source side of the middle of the gate **124**.

[0088] FIGS. **15A** and **15B** show that in some embodiments, a silicon-on-insulator (SOI) transistor **100** can include an active region **116** and an N+ implant region **114**. In some embodiments, a P+ implant region **111** can be formed on a first side of a gate **124**, but not on the other side. The N+ implant region **114** can include a first N+ active region **120** and a second N+ active region **122**. Such active regions can function as source (S) and drain (D) of the transistor **100**. The P+ implant region **111** implemented on the source side can result in a P+ active region **118**. The P+ body **118** is implemented appropriately in the foregoing manner can result in a P-link **127** below the N+ active region **120**, and such a P-link can provide a coupling to the body under the gate **124**.

[0089] With the foregoing configuration, and assuming that the first N+ active region **120** is configured as a source (S), the source (S) and the body (B) can have a common potential so as to provide $V_{sub.SB}=0$ across the butted P+/N+ interface **123**. Such a configuration can remove or reduce parasitic capacitance C_{gg} associated with the gate **124**.

[0090] FIG. **16** shows that in some embodiments, a silicon-on-insulator (SOI) transistor **100** can include a plurality of gate structures **124**, and such gate structures can separate alternating source and drain regions. For example, the source regions can be N+ active regions **120**, and the drain regions can be N+ active regions **122**. Such N+ active regions (**120**, **122**) can be implemented within an N+ implant region.

[0091] In the example of FIG. **16**, a plurality of P+ body regions **118** can be provided, and such P+ body regions can be implemented as parts of one or more P+ implant regions. In some embodiments, the transistor **100** of FIG. **16** can include recessed regions **130** adjacent the N+ active regions **122** associated with the drains. In some embodiments, each of such recessed regions can be bordered by two neighboring P+ body regions **118**, portions of the corresponding pair of gate structures **124**, and the respective N+ active region **122**. In some embodiments, each recessed region **130** can overlap with either or both of a P+ implant region and an N+ implant region.

[0092] For example, FIG. **17** shows a transistor **100** (e.g., an SOI transistor) having gate structures

124, source regions **120** and drain regions **122** similar to the example FIG. **16**. In the example of FIG. **17**, the N+ active regions associated with the sources and drains can be included in an N+ implant region **114**, and a P+ implant region **111** can be implemented adjacent to the N+ implant region **114** so as to overlap with all of the P+ body regions **118**. Thus, each recessed region **130** can be within the P+ implant region **111**, and be bordered by two neighboring P+ body regions **118**, portions of the corresponding pair of gate structures **124**, and the respective N+ active region **122**. [0093] In the example of FIG. **17**, the depth of the recessed regions **130** can be selected (e.g., by appropriately dimensioning the P+ implant region **111** and the N+ implant region **114**), such that the resulting P+ body regions under the respective portions of the gate structures **124** have minimum or reduced width to reduce parasitic capacitance C_{gg} associated with the gate **124**. [0094] In the example of FIG. **17**, the recessed regions **130** associated with the drain regions are implemented on one end of the gate structures **124**. FIG. **18** shows that in some embodiments, a transistor **100** can include recessed regions **130** associated with the drain regions for each of both ends of the gate **124**.

[0095] In another example, FIG. **19** shows a transistor **100** (e.g., an SOI transistor) having gate structures **124**, source regions **120** and drain regions **122** similar to the example FIG. **16**. In the example of FIG. **19**, the N+ active regions associated with the sources and drains can be included in an N+ implant region **114**, and the region above the N+ implant region **114** can include alternating P+ implant region **111** and N+ implant region **113**. Thus, each recessed region **130** can be within the respective N+ implant region **113**.

[0096] In the example of FIG. **19**, the depth of the recessed regions **130** can be selected (e.g., by appropriately dimensioning the P+ implant region **111**, the N+ implant region **113**, and the N+ implant region **114**) to provide one or more desired functionalities. For example, each P+ implant region **111** can be implemented on the source side of a respective gate structure **124**, and be dimensioned to provide a provide a respective butted P+/N+ interface **123** and a corresponding $V_{sub,SB}=0$ across the interface as described herein.

[0097] In the example of FIG. **19**, the recessed regions **130** associated with the drain regions are implemented on one end of the gate structures **124**. FIG. **20** shows that in some embodiments, a transistor **100** can include recessed regions **130** associated with the drain regions for each of both ends of the gate **124**.

[0098] FIG. **21** shows that in some embodiments, a transistor **100** (e.g., an SOI transistor) can include a gate such as a T-shape gate **124**. The transistor **100** is shown to include an active region **116** and an N+ implant region **114**. In some embodiments, a P+ implant region **111** can be formed under the gate **124**. The N+ implant region **114** can include a first N+ active region **120** and a second N+ active region **122**. Such active regions can function as source (S) and drain (D) of the transistor **100**. The P+ implant region **111** can include a P+ active region, and a portion of such an active region can function as a body of the transistor **100**.

[0099] In the example of FIG. **21**, an opening **134** such as a hole or a via can be formed through the gate **124** so as to allow contact with the body under the gate **124**. Such an opening can be utilized to reduce parasitic capacitance C_{gg} associated with the gate **124**.

[0100] In the example of FIG. **21**, the opening **134** associated with the gate **124** and the body is implemented on one end of the gate structures **124**. FIG. **22** shows that in some embodiments, a transistor **100** can include an opening **134** similar to the example of FIG. **21**, for each of both ends of the gate **124**.

[0101] In some embodiments, a transistor having one or more features as described herein can benefit by having a suppressed floating body effect. Such a suppressed floating body effect can be achieved by providing a minimum or reduced body contact with a least or reduced amount of additional parasitics such as parasitic capacitance. With such a suppressed floating body effect, advantageous features can be achieved, such as improved RF performance for RF transistors such as SOI transistors, improved performance and size associated with digital standard cells, and

elimination or reduction of unwanted floating body effect associated with floating body SOI transistors.

[0102] FIG. **23** shows that in some embodiments, one or more transistors **100** having one or more features as described herein can be implemented on a device **102** such as a die **300**. Such a die can include a substrate **302** such as, for example, silicon-on-insulator (SOI) substrate.

[0103] FIGS. **24** and **25** show examples of the die/device **102/300** of FIG. **23**. FIG. **24** shows that in some embodiments, a die/device **102/300** can include one or more transistors **100** as described herein, configured as RF building blocks. Such RF building blocks can include, for example, switching transistors, amplifying transistors, and transistors associated with RF applications (e.g., voltage-controlled oscillator, mixer, etc.).

[0104] FIG. **25** shows that in some embodiments, a die/device **102/300** can include one or more transistors **100** as described herein, configured for digital applications. For example, one or more digital cells can be implemented with transistor(s) having one or more features as described herein.

[0105] FIG. **26** shows that in some embodiments, one or more transistors having one or more features described herein can be implemented in a packaged module **400**. Such a packaged module can include a packaging substrate **402** configured to receive a plurality of components. At least some of the components mounted on the packaging substrate **402** can include a die **300** such as one or more of the example die **300** of FIGS. **23-25**.

[0106] In some implementations, a device and/or a circuit having one or more features described herein can be included in an RF device such as a wireless device. Such a device and/or a circuit can be implemented directly in the wireless device, in a modular form as described herein, or in some combination thereof. In some embodiments, such a wireless device can include, for example, a cellular phone, a smart-phone, a hand-held wireless device with or without phone functionality, a wireless tablet, etc.

[0107] FIG. **27** depicts an example wireless device **900** having one or more advantageous features described herein. In the context of various transistors as described herein, a switch **920** based on such transistors can be implemented in a module **910**. It will be understood that a transistor having one or more features as described herein can also be utilized in other portions of the wireless device.

[0108] In the example wireless device **900**, a power amplifier (PA) assembly **916** having a plurality of PAs can provide one or more amplified RF signals to the switch **920** (via an assembly of one or more duplexers **918**), and the switch **920** can route the amplified RF signal(s) to one or more antennas. The PAs **916** can receive corresponding unamplified RF signal(s) from a transceiver **914** that can be configured and operated in known manners. The transceiver **914** can also be configured to process received signals. The transceiver **914** is shown to interact with a baseband sub-system **910** that is configured to provide conversion between data and/or voice signals suitable for a user and RF signals suitable for the transceiver **914**. The transceiver **914** is also shown to be connected to a power management component **906** that is configured to manage power for the operation of the wireless device **900**. Such a power management component can also control operations of the baseband sub-system **910** and the module **910**.

[0109] The baseband sub-system **910** is shown to be connected to a user interface **902** to facilitate various input and output of voice and/or data provided to and received from the user. The baseband sub-system **910** can also be connected to a memory **904** that is configured to store data and/or instructions to facilitate the operation of the wireless device, and/or to provide storage of information for the user.

[0110] In some embodiments, the duplexers **918** can allow transmit and receive operations to be performed simultaneously using a common antenna (e.g., **924**). In FIG. **27**, received signals are shown to be routed to “Rx” paths that can include, for example, one or more low-noise amplifiers (LNAs).

[0111] A number of other wireless device configurations can utilize one or more features described

herein. For example, a wireless device does not need to be a multi-band device. In another example, a wireless device can include additional antennas such as diversity antenna, and additional connectivity features such as Wi-Fi, Bluetooth, and GPS.

[0112] Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise,” “comprising,” and the like are to be construed in an inclusive sense, as opposed to an exclusive or exhaustive sense; that is to say, in the sense of “including, but not limited to.” The word “coupled”, as generally used herein, refers to two or more elements that may be either directly connected, or connected by way of one or more intermediate elements. Additionally, the words “herein,” “above,” “below,” and words of similar import, when used in this application, shall refer to this application as a whole and not to any particular portions of this application. Where the context permits, words in the above Description using the singular or plural number may also include the plural or singular number respectively. The word “or” in reference to a list of two or more items, that word covers all of the following interpretations of the word: any of the items in the list, all of the items in the list, and any combination of the items in the list

[0113] The above detailed description of embodiments of the invention is not intended to be exhaustive or to limit the invention to the precise form disclosed above. While specific embodiments of, and examples for, the invention are described above for illustrative purposes, various equivalent modifications are possible within the scope of the invention, as those skilled in the relevant art will recognize. For example, while processes or blocks are presented in a given order, alternative embodiments may perform routines having steps, or employ systems having blocks, in a different order, and some processes or blocks may be deleted, moved, added, subdivided, combined, and/or modified. Each of these processes or blocks may be implemented in a variety of different ways. Also, while processes or blocks are at times shown as being performed in series, these processes or blocks may instead be performed in parallel, or may be performed at different times.

[0114] The teachings of the invention provided herein can be applied to other systems, not necessarily the system described above. The elements and acts of the various embodiments described above can be combined to provide further embodiments.

[0115] While some embodiments of the inventions have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of the disclosure. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions and changes in the form of the methods and systems described herein may be made without departing from the spirit of the disclosure. The accompanying claims and their equivalents are intended to cover such forms or modifications as would fall within the scope and spirit of the disclosure.

Claims

1. A method for fabricating a transistor, the method comprising: forming a plurality of source regions and a plurality of drain regions arranged in an alternating manner, such that each of the source regions and the drain regions is implemented as a first type active region; implementing a plurality of gate structures relative to the source regions and the drain regions such that application of a voltage to each gate structure results in formation of a conductive channel between a respective pair of source and drain regions; forming a body region to provide the respective conductive channel upon the application of the voltage to the corresponding gate structure, such that the body region is implemented as a second type active region; and forming a recessed region at an end of each drain region and one or both of the gate structures adjacent to the drain region.
