

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250256181

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Mason; Kent et al.

---

### **MOLDED HOCKEY PUCK WITH ELECTRONIC SIGNAL TRANSMITTER CORE**

---

#### **Abstract**

A hockey puck is disclosed including an internal signal transmitter enabling instantaneous identification of its position as it moves around. The hockey puck includes two molded subcomponents, which encapsulate the signal transmitter. The signal transmitter includes driver electronics and a number of signal transmitters which together generate and emit an electromagnetic signal. The electromagnetic signal is emitted by a plurality of diodes mounted in cavities in the subcomponents, for example around an outer circumference of the hockey puck and through a top and bottom surfaces of the hockey puck. The hockey puck is alternatively formed of a material that allows electromagnetic radiation to be emitted through the subcomponents, and the diode cavities omitted.

---

**Inventors:** Mason; Kent (Sunnyvale, CA), Cavallaro; Richard H. (Mountain View, CA), Doeden; Jim (Pleasanton, CA)

**Applicant:** SportsMEDIA Technology Corporation (Durham, NC)

**Family ID:** 1000008563515

**Assignee:** SportsMEDIA Technology Corporation (Durham, NC)

**Appl. No.:** 19/194823

**Filed:** April 30, 2025

#### **Related U.S. Application Data**

parent US continuation 17752401 20220524 parent-grant-document US 12290728 child US 19194823

parent US continuation 16503061 20190703 parent-grant-document US 11344778 child US 17752401

parent US continuation 16027594 20180705 parent-grant-document US 10343042 child US 16503061

## Publication Classification

**Int. Cl.:** **A63B67/14** (20060101); **A63B24/00** (20060101); **A63B43/00** (20060101); **A63B71/06** (20060101); **A63B102/24** (20150101)

**U.S. Cl.:**

**CPC** **A63B67/14** (20130101); **A63B24/0021** (20130101); **A63B43/00** (20130101); **A63B71/06** (20130101); **A63B43/008** (20130101); **A63B2102/24** (20151001)

---

## Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is related to and claims priority from the following U.S. patents and patent applications. This application is a continuation of U.S. patent application Ser. No. 17/752,401, filed May 24, 2022, which is a continuation of U.S. patent application Ser. No. 16/503,061, filed Jul. 3, 2019, which is a continuation of U.S. patent application Ser. No. 16/027,594, filed Jul. 5, 2018, which is a continuation of U.S. patent application Ser. No. 15/260,122, now U.S. Pat. No. 10,016,669, filed Sep. 8, 2016, each of which is incorporated herein by reference in its entirety.

### BACKGROUND OF THE INVENTION

[0002] Despite the current popularity of hockey, television viewing is hampered by the poor visibility of the hockey puck as it moves around the ice at high speeds. In order to be able to view all areas of the ice rink, cameras must be located far from the ice rink. Thus, a standard hockey puck tends to appear as a small dot on the screen. As a result, it is difficult to follow the puck as it is passed from player to player, and it is especially difficult to follow the puck as it is shot toward the goal and either deflected, caught or missed by the goalie. Often, viewers recognize a score only when a signal light is lit or the announcer informs the viewer that a goal has been scored.

[0003] U.S. Pat. No. 5,564,698 discloses a hockey puck including electromagnetic transmitters. The transmitters transmit a signal, for example an IR signal, which is captured in one or more sensors around the ice rink. The sensors are able to locate the instantaneous position of the hockey puck, which permits enhancement of the image of the puck on a television monitor. It is important that the transmitters within the puck not affect the overall dimensions of the puck, or the performance of the puck, such as its feel when struck and its reaction when received on a stick or bouncing off a surface.

### SUMMARY OF THE INVENTION

[0004] Embodiments of the present technology relate to a hockey puck including an internal transmitter enabling instantaneous identification of its position as it moves around. In embodiments, the puck is comprised of two molded subcomponents, which encapsulate a signal transmitter and are sealed together to form the hockey puck. The signal transmitter may include driver electronics and a number of signal transmitters which together generate and emit an electromagnetic signal. In one embodiment, the electromagnetic signal may be infrared (IR) light emitted by a plurality of diodes mounted in openings in the subcomponents, for example around an outer circumference of the hockey puck and through a top and bottom surfaces of the hockey puck. In still further embodiments, the puck may be formed of a material that allows electromagnetic radiation to be emitted through the subcomponents, and the diode cavities may be omitted.

[0005] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 is a perspective view of a hockey puck according to embodiments of the present invention.

[0007] FIG. 2 is an exploded perspective view of a first embodiment of a hockey puck according to the present invention.

[0008] FIG. 3 is a perspective view of an embodiment of a signal transmitter according to the present invention.

[0009] FIG. 4 is a perspective view of an embodiment of a subcomponent of a hockey puck according to the present invention.

[0010] FIG. 5 is a cross-sectional view of a hockey puck according to the first embodiment.

[0011] FIG. 6 is an exploded perspective view of a second embodiment of a hockey puck according to the present invention.

[0012] FIG. 7 is a top perspective view of one embodiment of subcomponents according to the present invention.

[0013] FIG. 8 is a bottom perspective view of one embodiment of subcomponents according to the present invention.

[0014] FIG. 9 is a perspective of a section of a capsule for encapsulating the signal transmitter according to one embodiment of the present invention.

[0015] FIG. 10 is a top view of a section of a capsule for encapsulating the signal transmitter according to one embodiment of the present invention.

[0016] FIG. 11 is a cross-sectional view of a hockey puck according to the second embodiment.

[0017] FIG. 12 is an exploded perspective view of a third embodiment of a hockey puck according to the present invention.

[0018] FIG. 13 a top view of a hockey puck according to embodiments of the present invention.

[0019] FIG. 14 is a cross-sectional view through line 14-14 of FIG. 13.

[0020] FIG. 15 is a cross-sectional view through line 15-15 of FIG. 13.

[0021] FIG. 16 is a top view of a bottom subcomponent according to the third embodiment.

[0022] FIG. 17 is a cross-sectional view through line 17-17 of FIG. 16.

[0023] FIG. 18 is a cross-sectional view through line 18-18 of FIG. 16.

[0024] FIG. 19 is an exploded perspective view of a fourth embodiment of a hockey puck according to the present invention.

[0025] FIG. 20 a top view of a hockey puck according to the fourth embodiment of the present invention.

[0026] FIG. 21 a cross-sectional view of a hockey puck according to the fourth embodiment of the present invention.

[0027] FIG. 22 illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0028] FIG. 23 illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0029] FIG. 24 illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0030] FIG. 25 illustrates an alternative configuration of subcomponents of a hockey puck

according to a further embodiment of the present invention.

[0031] FIG. **26** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0032] FIG. **27** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0033] FIG. **28** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0034] FIG. **29** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0035] FIG. **30** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0036] FIG. **31** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0037] FIG. **32** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0038] FIG. **33** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0039] FIG. **34** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0040] FIG. **35** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0041] FIG. **36** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0042] FIG. **37** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0043] FIG. **38** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0044] FIG. **39** illustrates an alternative configuration of subcomponents of a hockey puck according to a further embodiment of the present invention.

[0045] FIG. **40** is an exploded perspective view of a mold including mold plates and fixtures for use in gluing together subcomponents of the hockey puck according to an embodiment of the present invention.

[0046] FIG. **41** is a cross-sectional view of the mold of FIG. **40** gluing together subcomponents of a hockey puck according to embodiments of the present invention.

[0047] FIG. **42** is an enlarged view of area C from FIG. **41**.

[0048] FIG. **43** is a perspective view of a puck according to a further embodiment of the present invention.

#### DETAILED DESCRIPTION

[0049] Embodiments of the present technology will now be described with reference to the figures, which in general relate to a hockey puck including an internal signal transmitter enabling instantaneous identification of the puck position as it moves around an ice rink. In embodiments, the puck is comprised of two molded subcomponents, which encapsulate a signal transmitter and fit together to form the hockey puck. The two molded subcomponents may be formed of vulcanized rubber, and may include various features for supporting the signal transmitter and for ensuring a tight and secure fit when the subcomponents are joined together. In embodiments, the subcomponents may be formed of top and bottom halves, or an outer ring surrounding an inner plug.

[0050] It is understood that the present invention may be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete and will fully

convey the invention to those skilled in the art. Indeed, the invention is intended to cover alternatives, modifications and equivalents of these embodiments, which are included within the scope and spirit of the invention as defined by the appended claims. Furthermore, in the following detailed description of the present invention, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be clear to those of ordinary skill in the art that the present invention may be practiced without such specific details. [0051] The terms “top” and “bottom,” “upper” and “lower” and “vertical” and “horizontal,” or variations thereof, as may be used herein are by way of example and illustrative purposes only, and are not meant to limit the description of the invention inasmuch as the referenced item can be exchanged in position and orientation. Also, as used herein, the terms “substantially” and/or “about” mean that the specified dimension or parameter may be varied within an acceptable manufacturing tolerance for a given application. In one embodiment, the acceptable manufacturing tolerance is  $\pm 0.25\%$ .

[0052] The signal transmitter may include a printed circuit board with driver electronics, power source and a number of signal transmitters which together generate and emit an electromagnetic signal. In one embodiment, the electromagnetic signal may be infrared (IR) light emitted by a plurality of diodes around an outer circumference of the hockey puck and through top and bottom surfaces of the hockey puck. Other wavelengths of electromagnetic energy may be used in further embodiments. In embodiments, the printed circuit board and diodes may be encased within a capsule, but the capsule may be omitted in further embodiments.

[0053] In embodiments using diodes, the subcomponents may be formed with openings around the outer circumference and top and bottom surfaces for receiving the diodes. The openings allow ends of the diodes to extend to the outer surface of the puck to enable signal emission from the puck. In embodiments where the diodes are encased within a capsule recessed within the puck, signals from the diodes may be communicated from the diodes to the outer surface of the puck by light pipes provided in the openings in the subcomponents. In still further embodiments, the puck may be formed of a material that allows electromagnetic radiation to be emitted through the subcomponents, and the diode openings may be omitted.

[0054] The physical characteristics of the puck of the present technology may be the same as a conventional puck without a signal transmitter. Thus, the composition of the subcomponents may be customized for each embodiment of the signal transmitter. The physical characteristics may for example include the look, feel, size and weight of the puck. The physical characteristics may further include the performance of the puck, such as its feel and reaction when caught, struck or passed, and its reaction when bouncing off a surface.

[0055] FIG. 1 illustrates a perspective view of an exterior of a hockey puck **100** according to embodiments of the present technology. With the exception of holes **102** for the emission of an electromagnetic signal, and an embossed seam **104** (both of which are explained below), the exterior appearance and physical characteristics of puck **100** may match that of a conventional hockey puck, such as for example those used in the U.S. National Hockey League. Puck **100** may have a cylindrical shape, with a 1 inch thickness and a 3 inch circular diameter. Although not shown in FIG. 1, the outer circumference of puck **100** may include a dimple pattern as in a conventional hockey puck to increase friction between the puck **100** and a hockey stick handling, passing and shooting the puck.

[0056] As explained below, puck **100** may house a signal transmitter. As such, subcomponents of the puck **100** may be molded, and then assembled together with the signal transmitter encased within an interior of the puck **100**. In the embodiment shown in FIG. 1, subcomponents **106** and **108** comprise upper and lower cylindrical halves which may be affixed together around the signal transmitter, for example in a glue process explained below. Each of the subcomponents **106**, **108** may be formed of vulcanized rubber and, in one embodiment, may be fabricated by Soucy Baron Inc., having an office in Saint-Jérôme, Canada. The subcomponents **106**, **108** may be formed of

other materials and fabricated by other companies in further embodiments. The subcomponents **106**, **108** may include the same materials as those used in the fabrication of a conventional hockey puck (natural rubber, oils, minerals and carbon black).

[0057] However, as explained below, the ratios of the various materials may be adjusted relative to those used in a conventional hockey puck to provide the same performance as a conventional hockey puck despite the hollow core and signal transmitter encased therein. In addition to or instead of varying the ratio of the puck materials, the cure time and/or temperature at which the subcomponents **106**, **108** are formed may vary relative to that of a conventional hockey puck to provide the same performance as a conventional hockey puck.

[0058] FIG. 2 shows an exploded perspective view of a first embodiment of a hockey puck **100**. The hockey puck **100** of this embodiment may include top and bottom subcomponents **106** and **108**, respectively, and a signal transmitter **110** housed therebetween. Each of the subcomponents **106**, **108** includes an exterior surface **103** visible when the subcomponents are sealed together to form the finished hockey puck, and an interior surface **105** that is not visible after the subcomponents are sealed together.

[0059] The signal transmitter **110** emits electromagnetic radiation from the different surfaces of the puck **100**, which radiation is detected by sensors around the ice rink regardless of the orientation of the puck **100**. The sensors are able to locate the instantaneous position of the hockey puck, which permits enhancement of the image of the puck on a television monitor. For example, the puck may be highlighted in different colors, or different-colored contrails may be shown behind the puck, as it is shot, passed, leaves the ice surface or enters the goal.

[0060] Details of the electronics and components of signal transmitter **110** are disclosed for example in U.S. Pat. No. 5,564,698, entitled "Electromagnetic Transmitting Hockey Puck." However, referring now to the perspective view of FIG. 3, signal transmitter **110** may generally include a printed circuit board (PCB) **114** having driver electronics formed on top and bottom surfaces of the PCB **114**. The signal transmitter **110** may further include a power source **112** such as a rechargeable battery.

[0061] In embodiments, the signal transmitter **110** may further include a number of diodes **120** (some of which are numbered in FIG. 3) which generate and emit electromagnetic radiation under the control of the driver electronics on PCB **114**. The diodes **120** may emit electromagnetic radiation outside of the visible light spectrum, such as for example IR light. It is conceivable that diodes **120** emit light in the visible spectrum in further embodiments.

[0062] In the embodiment shown, there are a total of eighteen diodes **120**: four axially extending diodes **120a** on a top surface of PCB **114** (to emit a signal from a top surface of the puck), four axially extending diodes **120b** on a bottom surface of PCB **114** (to emit a signal from a bottom surface of the puck), and ten radially extending diodes **120c** extending radially from the outer circumference of the PCB **114** (to emit the signal from an outer circumference of the puck). Thus, radiation from the puck may be detected regardless of an orientation of the puck. It is understood that the signal transmitter **110** may include more or less diodes **120** in further embodiments, and diodes in other places than shown. When the puck **100** is fully assembled, outer ends of the diodes **120** (i.e., most distal from the PCB **114**) may lie flush with the exterior surfaces **103** of the subcomponents **106**, **108**.

[0063] As opposed to embodiments described hereinafter, the signal transmitter **110** in the embodiment of FIGS. 2 and 3 is unencapsulated, and interior surfaces **105** of the subcomponents **106**, **108** are keyed with features to directly support a battery **112**, the printed circuit board **114** and the diodes **120** of the signal transmitter **110**. FIG. 4 illustrates interior surfaces **105** of the bottom subcomponent **108** for receiving and supporting the signal transmitter **110**. It is understood that the top subcomponent **106** may include similar features for receiving and supporting the signal transmitter **110**.

[0064] As seen in FIG. 4, the interior surface **105** of subcomponent **108** may include a cavity **122**

sized and shaped to receive the battery **112** on a bottom surface of the PCB **114**. The interior surface of subcomponent **108** further includes holes **102** (two of which are numbered) for receiving the axially extending diodes **120b** on a bottom surface of the PCB **114**. The interior surface of subcomponent **108** may further include semicircular channels **124** (some of which are numbered) for receiving the radially extending diodes **120c** around an outer circumference of the PCB **114**. The interior surface of subcomponent **106** may have a corresponding set of semicircular channels **124**, so that the semicircular channels in the subcomponents **106**, **108** together form radially extending holes enclosing the diodes **120c**.

[0065] As seen in FIG. **3**, the radially extending diodes **120c** may include ridges **128** (one of which is numbered). These ridges mate within the detents **129** (again, one of which is numbered) in the channels **124** of subcomponent **106**, **108**. The mating of the ridges **128** within detents **129** provides resistance to the shear forces which are generated when the subcomponents **106**, **108** are glued together as explained below. The ridges **128** and detents **129** may be omitted in further embodiments.

[0066] The cavities **122**, holes **102**, channels **124** and other indentations on the interior surfaces **105** of subcomponents **106**, **108** allow the subcomponents **106**, **108** to fit tightly together with the signal transmitter **110** enclosed snugly therebetween. With the exception of holes **102** and channels **124**, no other indentations formed on the interior surfaces of subcomponents **106**, **108** are open to an exterior of the puck **100**.

[0067] The interior surfaces **105** of subcomponents **106**, **108** further include keyed features **130** for ensuring a tight and secure fit of the subcomponents when they are glued to each other. The keyed features **130** may be in a variety of different configurations, some of which are shown in the drawings. In FIGS. **4** and **5**, the keyed features **130** include a plurality of wedges arranged in concentric circles. As shown in the cross-section view of FIG. **5**, the concentric wedges in the subcomponent **108** are offset from, and complementary to, the concentric wedges in the subcomponent **106**. In particular, the peaks of the wedges in subcomponent **108** align with the valleys of the wedges in subcomponent **106**, and vice-versa. Thus, when assembled together as shown in the cross-sectional view of FIG. **5**, the features **130** on the interior surface **105** of subcomponent **108** mate snugly with the features **130** on the interior surface **105** of subcomponent **106**.

[0068] The features **130** may have various characteristics. First, the features provide a relatively large surface area for receiving glue as explained below to securely affix the subcomponents **106** and **108** to each other. Second, in embodiments, the features **130** may be sandblasted, or formed within a mold that is sandblasted. The features/mold may alternatively be chemically etched. Sandblasting/chemical etching increases the surface area and provides nooks and crannies for the glue between adjacent surfaces of the features **130** of subcomponents **106**, **108**. Sandblasting may be omitted in further embodiments. Third, extending vertically, the features **130** are able to exert lateral forces against each other (for example parallel to the top and bottom surfaces of the puck **100**) to provide a resistance to shear forces when the subcomponents are affixed together and thereafter.

[0069] FIG. **6** shows an exploded perspective view of a puck **600** including an alternative design of the subcomponents **107**, **109** and an alternative design of the signal transmitter **110**. FIGS. **7** and **8** show perspective views of the interior surfaces **105** of the subcomponents **107**, **109** according to the embodiment of FIG. **6**. As shown, each subcomponent **107**, **109** includes an outer ring **140** having features **130** (some of which are numbered). In this embodiment, the features **130** in each ring **140** may comprise a number of positively extending truncated cones and a number of negatively recessed truncated cones. Full cones may be used instead of truncated cones in further embodiments. Additionally, complementary positively extending and negatively recessed shapes other than cones may be used in further embodiments.

[0070] The cones are arranged on the respective rings **140** such that, when the subcomponents **107**,

**109** are mated together, a positively extending cone mates within a negatively recessed cone in the opposite subcomponent. In the embodiments of FIGS. **7** and **8**, each subcomponent includes both positively extending and negatively recessed cones, which mate within their compliment in the opposite subcomponent. In further embodiments, the ring **140** on subcomponent **107** may be all positively extending cones or negatively recessed cones, and the ring **140** on subcomponent **109** may include all of the opposite shape. Thus, the positively extending cones mate within the negatively recessed cones when the subcomponents **107**, **109** are mated together. The features **130** on the rings **140** in the embodiment of FIGS. **7** and **8** may include the characteristics described above with respect to the features shown in FIG. **4**.

[0071] Referring again to the exploded perspective view of FIG. **6**, this embodiment may include a signal transmitter **110** that may be encased within a capsule **144** comprised of sub-capsule halves **146** and **148**. Sub-capsule halves **146**, **148** may for example be formed of molded silicone (or other encapsulant) and may completely enclose the signal transmitter **110** when the halves **146**, **148** are assembled together.

[0072] FIGS. **9** and **10** illustrate a perspective view of an exterior surface **152** and a top view of an interior surface **154** of sub-capsule halves **146**, **148**. The halves **146**, **148** may be identical to each other, with the exception that components in the half **146** may be rotated off axis with respect to the corresponding components in the half **148**, as explained below.

[0073] The capsule **144** includes light pipes **156** and **160** for receiving diodes **120** and for communicating the electromagnetic radiation from diodes **120** to the exterior surface **103** of the hockey puck **100**. Each sub-capsule half **146**, **148** includes axially extending light pipes **156** (FIGS. **9** and **11**) extending from exterior surface **152**. These axially extending light pipes in respective halves **146**, **148** receive the axially extending diodes **120a**, **120b** extending from the top and bottom surfaces, respectively, of the PCB **114**. The light pipes **156** in turn fit through holes **102** in the subcomponents **107**, **109** to be flush with the exterior surface **103** of the subcomponents **107**, **109**.

[0074] The capsule **144** may further include radially extending light pipes **160** extending from an outer circumference of capsule **144**. The radially extending light pipes **160** in capsule **144** receive the radially extending diodes **120c** extending from the outer circumference of the PCB **114**. Each of the radially extending light pipes **160** is formed of two mating pieces, with a first piece formed in sub-capsule half **146** and a second, complementary piece formed in sub-capsule half **148**. The two pieces fit together around diodes **120c** when the sub-capsule halves **146**, **148** are brought together. The light pipes **160** in turn fit within channels **124** in the subcomponents **107**, **109** to be flush with the exterior surface **103** of the subcomponents **107**, **109**.

[0075] The first and second pieces in respective halves may have the same configuration, each forming one-half of the light pipe **160**. However, in other embodiments, the pieces may be dissimilar. For example, in FIGS. **9** and **10**, one piece (**160a**) is larger than the complementary piece (**160b**) in the other sub-capsule half. In the embodiment shown in FIGS. **9** and **10**, the radially extending diodes **120c** may fit within the piece **160a** and the piece **160b** may act as a cover to encase the diodes **120c**. In embodiments where the pieces are dissimilar, a sub-capsule half **146**, **148** may have both larger pieces **160a** and smaller pieces **160b**, and the other sub-capsule half may have the complementary smaller pieces **160b** and larger pieces **160a**. Alternatively, one sub-capsule half may have all of one type of piece (for example **160a**) and the other sub-capsule half may have all of the other type of piece (for example **160b**).

[0076] The sub-capsule halves may each have a cavity **122** for receiving the battery **112** as described above. The subcomponents **107**, **109** may each include a recess **153** (FIGS. **7** and **8**). The recesses **153** define a central void within the interior of the puck **600** when the subcomponents **107**, **109** are brought together. The central void defined by recesses **153** is sized and shaped to snugly receive the capsule **144**.

[0077] The capsule **144** includes notches **164** as shown for example in FIGS. **9** and **10**. The notches **164** are positioned so that there is a single rotational orientation, and a single side facing upward,



where the notches **164** align with and fit over raised key-points **166** in the subcomponents **107**, **109** (FIGS. **7** and **8**). Proper alignment of the raised key-points **166** in the notches **164** ensures the capsule **144** is properly seated between the subcomponents in the proper orientation and with the proper side of the capsule facing upward. In particular, there are two key-points on one side of the subcomponents, and one on the opposite side, which together form a triangle that is not an equilateral triangle. Thus, the key-points define a unique orientation and one side facing upward where the notches **164** in the capsule **144** fit over the key-points.

[0078] Exterior surfaces of the sub-capsule halves **146**, **148** may include dimples **168** (FIG. **9**) which increase the surface area for receiving glue, and provide shear resistance against lateral movement of the capsule **144** in the subcomponents **107**, **109** during the gluing process. As seen in FIGS. **7** and **8**, the subcomponents **107**, **109** may further include weep holes **170** which provide channels for seepage of the glue out of the cavities **153** when the subcomponents are affixed together as explained below.

[0079] FIGS. **12-18** illustrate a further embodiment of the hockey puck according to the present technology. FIG. **12** illustrates an exploded perspective view which is similar to the embodiment shown in FIG. **6**, with one difference being that the capsule **144** is preassembled prior to placing the capsule **144** between the subcomponents **111**, **113**. The capsule **144** shown in FIG. **12** may be identical to the capsule **144** shown in FIG. **6**. However, instead of having two separate sub-capsule halves encasing the signal transmitter **145**, the signal transmitter **145** including the PCB **114** and diodes **120** may be put in a mold and encased in a single-piece capsule **144** of silicone (or other encapsulant). Thus, the capsule **144** and signal transmitter **145** may be a single integrated unit when assembled between the subcomponents **111**, **113**.

[0080] In order to communicate the electromagnetic radiation from the diodes **120** within the capsule **144**, the embodiment of FIG. **12** may further include light pipes **174** and **176**. In the embodiment of FIG. **6**, the light pipes **156**, **160** were integrally formed on the capsule **144**. In the embodiment of FIG. **12**, the light pipes **174**, **176** may be silicone (or other like material) that are molded separately from the capsule **144**.

[0081] Further details of the puck **1200** of the embodiment of FIG. **12** are shown in the top and cross-sectional views of FIGS. **13-15**. FIGS. **14** and **15** are cross-sectional views of the hockey puck **1200**, through lines **14-14** and **15-15**, respectively, in FIG. **13**. The axial light pipes **174** may be plugs that fit within holes **102** in the subcomponents **111**, **113**. As shown for example in FIGS. **12** and **15**, axial light pipes **174** may have a length so that a first end of a light pipe **174** lies against the capsule **144** (over an encased diode **120a**, **120b**) and a second, opposite end lies flush with the exterior surface **103** of the subcomponents **111**, **113**.

[0082] As seen for example in FIGS. **12** and **14**, the radial light pipes **176** may be molded together on a ring **178**. The ring **178** may fit snugly over an outer circumference of the capsule **144**, with first ends of the radial light pipes **176** aligned with and lying over the encased diodes **120c**. The radial light pipes **176** may lie in channels **126**, and may have a first end against the capsule **144** and a second, opposite end flush with the exterior surface **103** of the subcomponents **111**, **113**. In this way, the light pipes **174**, **176** transmit the electromagnetic radiation from the diodes **120** to the exterior of the puck **1200**. The capsule **144** may include notches **164** (not shown in FIGS. **12-18**) which receive raised key-points **166** to ensure the capsule is properly oriented, with the correct side facing upward, so that the light pipes **174**, **176** align with their respective diodes **120**.

[0083] Further details of the subcomponents **111**, **113** of the embodiment of FIG. **12** are shown in the top and cross-sectional views of FIGS. **16-18**. FIGS. **17** and **18** are cross-sectional views through lines **17-17** and **18-18**, respectively, in FIG. **16**. In general, the subcomponents **111**, **113** of the embodiment of FIG. **12** may have the same features as the subcomponents **111**, **113** described above the respect to FIG. **6**. These features include for example recess **153** with holes **102**, and a ring **140** including channels **124** and features **130** in the form of positively extending and negatively recessed truncated cones. The subcomponents **111**, **113** may further include weep holes

**170.** Each of these components may be structurally and operationally similar to the like components described above with respect to the embodiment in FIG. 6.

[0084] While the embodiment of FIG. 6 is described and shown with light pipes integrally formed on capsule **144**, it is understood that the embodiment of FIG. 6 may have separate light pipes as shown and described above with respect to FIG. 12. In a further example, instead of being formed on a separate ring **178**, the light pipes **174** and/or **176** may be integrally formed on the capsule **144** in the embodiment of FIG. 12. Light pipes integrally formed on the capsule may have an advantage that they are able to better withstand the hydrostatic forces generated during the gluing process explained below, so that they do not get pushed out of the holes **102** and channels **124**.

[0085] In embodiments described thus far, subcomponents described are top and bottom halves of the hockey puck. FIGS. 19-21 illustrate a further embodiment of the hockey puck **1900** including a subcomponent **180** comprising the bottom portion of the puck **1900**. Subcomponent **180** comprises a larger piece, e.g., a base, and includes the bottom surface of the puck **1900**, the rounded circumferential edge of the puck **1900**, and a portion of the top surface of the puck **1900**. Subcomponent **182** comprises a smaller piece, e.g., a cover, filling in the remainder of the top surface of puck **1900**. The edges of the cover and bottom portion of the puck abut with a toothed design. Thus, where the embodiments of FIGS. 1-18 have a lip (embossed seam **104**) in the puck **1900** around rounded circumferential edge of the puck **1900**, the embodiment of FIGS. 19-21 have a seam on the top planar surface of puck (or on the bottom planar surface where the subcomponents **180**, **182** are switched).

[0086] In the embodiment of FIGS. 19 and 20, the signal transmitter **110** includes axial diodes **120a** and **120b** on top and bottom surfaces, respectively, of PCB **114**. The subcomponent **180** includes an opening **184** for receiving signal transmitter **110**. Opening **184** may have circumferential edges defined by channels **186a** and **186b**. The channels **186b** receive and mate with the downwardly extending diodes **120b**. The bottom portion **190** of channels **186b** is open to the exterior surface of the puck **1900** so that electromagnetic radiation from diodes **120b** may be omitted from a bottom surface of the puck **1900**.

[0087] The channels **186a** receive and mate with the upwardly extending diodes **120a**. A bottom portion **192** of the channels **186a** may be sealed. The subcomponent **182**, referred to hereinafter as cover **182**, includes a number of axial recesses **196a** and axial protrusions **196b** around its outer circumference. The recesses **196a** align with channels **186a** and, together with the channels **186a**, enclose the upwardly extending diodes **120a** along their lengths when cover **182** is sealed within the opening **184**. The recesses **196a** and channels **186a** are open at an upper surface of the puck **1900** to allow emission of electromagnetic radiation from diodes **120a** at the upper surface, as shown in the top view of puck **1900** in FIG. 20.

[0088] The protrusions **196b** align with and fill channels **186b**. As shown in the cross-sectional view of FIG. 21, when the cover **182** is sealed within the opening **184**, the protrusions **196b** axially align over the diodes **120b** and seal the channels **186b** above the diodes **120b**.

[0089] FIGS. 22-39 are edge and perspective views of subcomponent configurations according to a variety of alternative embodiments. FIGS. 21-24 illustrate subcomponents **181**, **183** which form a seam extending to a top portion of the puck **2300** and around a circumferential edge of the hockey puck **2300**.

[0090] FIGS. 25-27 illustrate embodiments of subcomponents **185**, **187** forming puck **2600** is similar to those described above the respect to FIGS. 19-21, but the spacing of the different sections forming the vertical walls at an interface between subcomponents **185**, **187** is slightly different.

[0091] FIGS. 28-30 illustrate embodiments of subcomponents **191**, **198** forming a seam on upper surface of the hockey puck **2900**. In this embodiment, the upper subcomponent **198** includes an interior facing flange **193** that seats against a surface **194** in the lower subcomponent **191**. The embodiments of the puck **3200** of FIGS. 31-33 are similar to that of FIGS. 28-30, but the lower

subcomponent **199** includes elongated holes **102** which taper toward a bottom surface of the subcomponent **199** and away from upper subcomponent **197**.

[0092] FIGS. **34-36** illustrate an embodiment of a subcomponent **205** including a lip **195** which snaps into an annular space **196** in the subcomponent **203** upon mating of the subcomponents **203**, **205** in puck **3500**.

[0093] FIGS. **37-39** illustrate an embodiment of subcomponents **207**, **209** forming a seam around the circumferential edge of the hockey puck **3800**. In this embodiment, the upper subcomponent **209** is formed with downwardly-extending saw-tooth protrusions defined by vertical edges. These protrusions mate with upwardly-extending saw-tooth protrusions in the lower subcomponent **207** to form interleaved finger joints that make full surface contact between adjacent protrusions. The protrusions are tapered so that the edges that contact adjacent protrusions align along a radius of the puck, such that each protrusion is wider towards an exterior of the first and second subcomponents and narrower towards an interior of the first and second subcomponents, and wherein an interior end of each protrusion is curved.

[0094] FIGS. **40-42** illustrate a press **4000** for use in gluing together the subcomponents of the various embodiments shown in the figures. Press **4000** may include a top plate **4002** and a bottom plate **4004**. Press **4000** may further include top fixture **4006** and bottom fixture **4008**. The plates and fixtures of press **4000** may for example be formed of stainless steel.

[0095] In operation, a subcomponent, such as for example subcomponent **108**, may be placed on a platform **4010** on the bottom plate **4004**. The fixture **4008** may then be fit down over the bottom plate **4004** so that adjacent surfaces of the fixture **4008** and bottom plate **4004** lie contact with each other. The bottom plate **4004** may include a pair of upwardly extending guideposts **4012** received within guide holes **4014** in fixture **4008** to ensure precise alignment of the fixture **4008** on top of the bottom plate **4004**.

[0096] The fixture **4008** includes a central opening **4016** which fits down over platform **4010**. The central opening has a raised surface **4018** so that a height of the cylindrical walls of opening **4016** are equal to the height of the platform **4010** plus the height of the subcomponent **108** on top of platform **4010**. An uppermost circular portion of the cylindrical walls of opening **4016** (where the raised surface **4018** meets the cylindrical walls) defines a lip **4020**.

[0097] The top plate **4002** and top fixture **4006** have the same configurations and structures as lower plate **4004** and bottom fixture **4008**, as indicated for example by those components which are numbered on top plate **4002** and top fixture **4006**. The top plate and fixture **4002**, **4006** may be turned upside down, and the second subcomponent, for example subcomponent **106**, may then be placed on a platform **4010**. The top fixture **4006** may then be fit over top plate **4002** to secure the subcomponent **106** in place as described above with respect to the bottom plate and fixture.

[0098] An adhesive material may then be applied to the features **130** (described above) on the interior surface(s) of subcomponent **106** and/or **108**. The top plate **4002**, top fixture **4006** and subcomponent **106** may then be flipped and fit on top of bottom plate **4004**, bottom fixture **4008** and subcomponent **108**. The guideposts **4012** in top plate **4002** fit through the guide holes in bottom fixture **4008**. Similarly, the guideposts **4012** in bottom plate **4004** fit into guide holes **4014** in the top fixture **4006**. This ensures proper alignment of all components in the press **4000**, and proper alignment of the subcomponents **106** and **108** with respect to each other.

[0099] Thereafter, large compressive forces may be applied to the top and bottom plates **4002**, **4004** by a hydraulic device (not shown) to press the features **130** on the interior surfaces of subcomponents **106**, **108** against each other. The adhesive may then be cured under pressure for a period of time, and possibly at an elevated temperature. The adhesive may form a mechanical or chemical bond to seal the subcomponents **106**, **108** together. The pressure may squeeze out any excess adhesive from between the subcomponents **106** and **108**. The press **4000** may be heated during the gluing process to reduce the hydrostatic pressure generated by the glue as it is forced out from between the subcomponents **106**, **108**.

[0100] FIG. 41 is a cross-sectional view of the components of press 4000 sealing subcomponents 106 and 108 together. FIG. 42 is an enlarged sectional view of the area C of FIG. 41. As shown in FIGS. 41 and 42, when the bottom fixture 4008 is seated on top of bottom platform 4004, around subcomponent 108, the lip 4020 aligns snugly against the seam 104 in a top portion of the outer circumferential edge of subcomponent 108. Similarly, when the top fixture 4006 is seated on over of top plate 4002, around subcomponent 106, the lip 4020 aligns snugly against the seam 104 around a lower edge portion of the outer circumferential edge of subcomponent 106.

[0101] The tight engagement of the lip 4020 against the seam 104 in the subcomponents 106 and 108 ensures that, as glue is squeezed out from between subcomponents 106 and 108, the excess glue enters a space 4030 defined between the top and bottom fixtures 4006, 4008. Significantly, the tight engagement of the lip 4020 against the seam 104 prevents any excess glue from passing between the respective subcomponents and fixtures, onto the outer circumferential edge of the subcomponent 106 and/or 108. As discussed above, the outer circumferential edge of the hockey puck 100 may include a dimple pattern. The tight engagement of the lip 4020 against the seam 104 prevents adhesive from bleeding onto the dimple pattern.

[0102] Turning now to the fabrication of the subcomponents of hockey puck 100, the subcomponents may be formed of vulcanized rubber, for example containing natural rubber, oils for durability, minerals for curing and anti-aging agents, and coal dust (carbon black) for color. The various materials of the subcomponents may be thoroughly mixed together in predefined ratios, and then placed in a mold under pressure of a hydraulic press and cured, for example at 300° F. to 500° F. for 15 to 20 minutes. These temperatures and times are by way of example only, the curing temperatures and times may be lower or higher than the stated ranges in further embodiments.

[0103] The materials and ratios are controlled to provide the puck 100 with the same characteristics and properties as a conventional puck not having a signal transmitter core. For example, the signal transmitter in the hollow core tends to increase the amount by which the puck bounces off a surface as compared to a conventional puck. Thus, the materials and/or ratios may be controlled to be relatively energy absorbing so as to deaden the response of the subcomponents in comparison to the vulcanized rubber used in a conventional puck. In this way, the response of puck 100 including the signal transmitter core is the same as a conventional puck. It is understood that the materials and/or ratios may be varied, depending on whether the signal transmitter 110 is encased within a capsule 144 or sealed within the puck 100 without a capsule 144.

[0104] The subcomponents may be made in two pieces, and then glued around the signal transmitter 110 (as the signal transmitter may not withstand the curing conditions for the subcomponents if a single subcomponent were molded around the signal transmitter). However, in further embodiments, it is contemplated that the vulcanized rubber be molded in a single piece around the signal transmitter. In such embodiments, the signal transmitter maybe encased in a capsule as described above, or not encased in a capsule as described above. The press 4000 may form a single puck 100. Alternatively, the press may be elongated (or made into an x-y matrix) including multiple central openings 4016 and other components described above for receiving multiple pairs of subcomponents 106, 108, so that multiple pucks 100 may be formed in a single process.

[0105] In embodiments described above, the subcomponents include openings so that the electromagnetic radiation from the diodes may be transmitted through the subcomponents to an exterior of the puck 100. In embodiments, the vulcanized rubber of the subcomponents may include carbon black, which prevents the transmission of certain wavelengths of electromagnetic radiation, such as for example radiation in the IR wavelengths.

[0106] In further embodiments of the present technology, the puck may be formed of materials that are transparent to the wavelengths of the electromagnetic radiation emitted from the signal transmitter 157. In such embodiments, the axial openings and radial channels in the subcomponents may be omitted, and the electromagnetic radiation may be transmitted through the walls of the

subcomponents. Such an embodiment is shown in the perspective view of FIG. 43. [0107] FIG. 43 shows a signal transmitter 157 encased within the interior of a puck 4300. The signal transmitter 157 may be as described above, and may or may not be encased within capsule. The puck 4300 of FIG. 43 may have the same color and other properties of a conventional hockey puck, but may for example be colored black without the use of carbon black. Other black-pigmented materials, such as for example powdered ash or other powdered materials, may be used in the vulcanized rubber to give the puck 4300 its black color. Without carbon black, the electromagnetic radiation from signal transmitter 157 may radiate from the puck 4300 without having to provide openings in the puck.

[0108] It is further conceivable that the signal transmitter transmits at wavelengths that are not blocked or absorbed by carbon black. In such embodiments, the vulcanized rubber of puck 100 may include carbon black.

[0109] In summary, embodiments of the present technology relate to a hockey puck, comprising: first and second subcomponents including complementary features operable to mate with each other, the first and second subcomponents together defining a central void interior to the first and second subcomponents together; a capsule sized and shaped to fit within the central void of the first and second subcomponents, the capsule including a central space interior to the capsule; and a signal transmitter sized and shaped to fit within the central space of the capsule, the signal transmitter operable to emit electromagnetic radiation to enable detection of an instantaneous position of the hockey puck.

[0110] In further embodiments, the present technology relates to a hockey puck, comprising: first and second subcomponents including complementary features operable to mate with each other, the first and second subcomponents together defining a central void interior to the first and second subcomponents together; and a signal transmitter sized and shaped to fit within the central void of the first and second subcomponents, the signal transmitter operable to emit electromagnetic radiation to enable detection of an instantaneous position of the hockey puck; wherein the first and second subcomponents comprise a first set of materials, the first set of materials absorbing a greater amount of energy than a second set of materials used in a second hockey puck having a solid core without the signal transmitter.

[0111] In other embodiments, the present technology relates to a hockey puck, comprising: first and second subcomponents including complementary features operable to mate with each other, the first and second subcomponents together defining a central void interior to the first and second subcomponents together; and a signal transmitter sized and shaped to fit within the central void of the first and second subcomponents, the signal transmitter operable to emit electromagnetic radiation in a wavelength band to enable detection of an instantaneous position of the hockey puck; wherein the first and second subcomponents comprise materials that are transparent to the wavelength band at which the electromagnetic radiation is emitted.

[0112] Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims. It is intended that the scope of the invention be defined by the claims appended hereto.

## Claims

1. A hockey puck, comprising: a first subcomponent and a second subcomponent, wherein the first subcomponent and the second subcomponent are attached; wherein the first subcomponent defines an exterior top surface of the hockey puck and the second subcomponent defines an exterior bottom surface of the hockey puck; wherein the first subcomponent includes at least one opening and the second subcomponent includes at least one opening; wherein an interior compartment is defined

between the first subcomponent and the second subcomponent; a capsule constructed and configured with a profile mated to contours of the interior compartment such that the capsule maintains an orientation within the interior compartment and does not move within the interior compartment; a signal transmitter operable to generate and emit non-visible electromagnetic radiation operable to be received by a plurality of sensors around an ice rink; wherein the signal transmitter comprises at least one diode; wherein the signal transmitter is sized and shaped to fit within the capsule; at least one light pipe integrally formed with the capsule and extending outwardly from the capsule to at least one of the exterior top surface or the exterior bottom surface of the hockey puck in a direction substantially perpendicular to the exterior top or bottom surfaces of the hockey puck; wherein the at least one light pipe is open to at least one of the exterior top surface or the exterior bottom surface of the hockey puck; and wherein the at least one light pipe is operable to receive the at least one diode of the signal transmitter and communicate the non-visible electromagnetic radiation from the at least one diode to the at least one opening of the first subcomponent and/or the at least one opening of the second subcomponent.

2. The hockey puck of claim 1, wherein the first subcomponent and the second subcomponent are joined via a plurality of complementary features, including a plurality of concentrically arranged wedges and a plurality of concentrically arranged valleys.

3. The hockey puck of claim 1, wherein physical characteristics of the hockey puck match physical characteristics of a conventional hockey puck used in the United States National Hockey League (NHL).

4. The hockey puck of claim 1, wherein the hockey puck has a thickness of approximately one inch and a diameter of approximately three inches.

5. The hockey puck of claim 1, wherein an outer circumference of the hockey puck includes a dimple pattern.

6. The hockey puck of claim 1, wherein the plurality of sensors around the ice rink are configured to communicate an instantaneous position of the hockey puck on the ice rink and communicate the instantaneous position of the hockey puck on the ice rink for display on a television monitor.

7. A hockey puck, comprising: a first subcomponent and a second subcomponent, wherein the first subcomponent and the second subcomponent are attached; wherein the first subcomponent defines an exterior top surface and the second subcomponent defines an exterior bottom surface of the hockey puck; wherein the first subcomponent includes at least one opening and the second subcomponent includes at least one opening; wherein an interior compartment is defined between the first subcomponent and the second subcomponent, wherein the interior compartment includes a capsule, and wherein the capsule is constructed and configured with a profile mated to contours of the interior compartment; wherein the capsule fully fills the interior compartment; at least one light pipe integrally formed with the capsule and extending outwardly from the capsule in a direction substantially perpendicular to the exterior top or bottom surfaces; wherein the at least one light pipe extends into at least one corresponding channel formed between the first subcomponent and/or the second subcomponent; wherein the at least one light pipe is open to at least one of the exterior top or bottom surfaces of the hockey puck; a signal transmitter operable to generate and emit non-visible electromagnetic radiation; wherein the at least one light pipe is operable to receive a component of the signal transmitter and communicate the non-visible electromagnetic radiation from the component of the signal transmitter to the at least one opening of the first subcomponent and/or the at least one opening of the second subcomponent.

8. The hockey puck of claim 7, wherein the first subcomponent and the second subcomponent are joined via a plurality of complementary features, including a plurality of wedges and a plurality of valleys.

9. The hockey puck of claim 7, wherein physical characteristics of the hockey puck match physical characteristics of a conventional hockey puck used in the United States National Hockey League (NHL).

- 10.** The hockey puck of claim 7, wherein the hockey puck has a thickness of approximately one inch and a diameter of approximately three inches.
  - 11.** The hockey puck of claim 7, wherein an outer circumference of the hockey puck includes a dimple pattern.
  - 12.** The hockey puck of claim 7, wherein the non-visible electromagnetic radiation generated and emitted by the signal transmitter is operable to be received by a plurality of sensors around an ice rink regardless of an orientation of the hockey puck, wherein the plurality of sensors around the ice rink are configured to communicate an instantaneous position of the hockey puck on the ice rink and communicate the instantaneous position of the hockey puck on the ice rink for display on a television monitor, wherein the hockey puck is highlighted in a color on the television monitor.
  - 13.** A hockey puck, comprising: a first outer subcomponent and a second outer subcomponent, wherein the first outer subcomponent and the second outer subcomponent are joined; a capsule located between the first outer subcomponent and the second outer subcomponent; wherein the capsule is constructed and configured with a profile mated to contours of an interior compartment between the first outer subcomponent and the second outer subcomponent; and a signal transmitter operable to generate and emit electromagnetic radiation; wherein the first outer subcomponent defines an exterior top surface of the hockey puck and the second outer subcomponent defines an exterior bottom surface of the hockey puck; wherein the first outer subcomponent includes at least one opening and the second outer subcomponent includes at least one opening; wherein a first capsule subcomponent includes at least one first light pipe that extends from the first capsule subcomponent, and wherein a second capsule subcomponent includes at least one second light pipe that extends from the second capsule subcomponent; wherein the at least one first light pipe and the at least one second light pipe are operable to receive at least one diode and communicate the electromagnetic radiation from the at least one diode to the at least one opening of the first outer subcomponent and/or the at least one opening of the second outer subcomponent; wherein the at least one first light pipe and/or the at least one second light pipe are open to at least one of the exterior top or bottom surfaces of the hockey puck; and wherein the at least one first light pipe and/or the at least one second light pipe are integrally formed with the capsule.
  - 14.** The hockey puck of claim 13, wherein the first outer subcomponent and the second outer subcomponent are joined via a plurality of complementary features, including a plurality of wedges and a plurality of valleys.
  - 15.** The hockey puck of claim 13, wherein physical characteristics of the hockey puck match physical characteristics of a conventional hockey puck used in the United States National Hockey League (NHL).
  - 16.** The hockey puck of claim 13, wherein the hockey puck has a thickness of approximately one inch and a diameter of approximately three inches.
  - 17.** The hockey puck of claim 13, wherein an outer circumference of the hockey puck includes a dimple pattern.
  - 18.** The hockey puck of claim 13, wherein the signal transmitter is operable to generate and emit electromagnetic radiation operable to be received by a plurality of sensors around an ice rink regardless of an orientation of the hockey puck, wherein the plurality of sensors around the ice rink are configured to communicate an instantaneous position of the hockey puck on the ice rink and communicate the instantaneous position of the hockey puck on the ice rink for display on a television monitor, wherein the hockey puck is highlighted in a color on the television monitor.
  - 19.** The hockey puck of claim 13, wherein the electromagnetic radiation includes non-visible electromagnetic radiation.
  - 20.** The hockey puck of claim 13, wherein the first outer subcomponent and the second outer subcomponent are bonded.
-