

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250257736

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Wangler; Adam Joseph et al.

APPARATUS TO REDUCE BEARING FAILURE

Abstract

Methods, apparatus, systems, and articles of manufacture are disclosed to reduce failure to bearings in a pump system. Disclosed herein is a pump system comprising a shaft connected to an impeller of the pump system, and a bearing to provide a dampening to the shaft, the bearing including a journal lining, the journal lining supported in the pump system, a spring-loaded foil to separate the shaft from the journal lining, an inner lining between the shaft and the spring-loaded foil, and a deformation limiter located between the spring-loaded foil and the journal lining.

Inventors: Wangler; Adam Joseph (Evendale, OH), Ertas; Bugra H. (Niskayuna, NY), Manem; Veera Venkata Amarnath (Bengaluru, IN)

Applicant: General Electric Company (Evendale, OH)

Family ID: 1000008572113

Appl. No.: 19/177992

Filed: April 14, 2025

Foreign Application Priority Data

IN 202211073553

Dec. 19, 2022

Related U.S. Application Data

parent US continuation 18356690 20230721 parent-grant-document US 12281657 child US 19177992

Publication Classification

Int. Cl.: F04D29/057 (20060101); F04D17/10 (20060101); F04D29/66 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application arises as a continuation of U.S. patent application Ser. No. 18/356,690 (now U.S. Pat. _____), filed on Jul. 21, 2023, which claims priority to and the benefit of Indian patent application Ser. No. 202211073553, filed on Dec. 19, 2022. U.S. patent application Ser. No. 18/356,690 and Indian patent application Ser. No. 202211073553 are hereby incorporated herein by reference in their entireties. Priority to U.S. patent application Ser. No. 18/356,690 and Indian patent application Ser. No. 202211073553 is hereby claimed.

FIELD OF THE DISCLOSURE

[0002] This disclosure relates generally to fluid pumps and, more particularly, to an apparatus to reduce bearing failure.

BACKGROUND

[0003] Aircraft typically include various accessory systems supporting the operation of the aircraft and/or its gas turbine engine(s). For example, such accessory systems may include a lubrication system that lubricates components of the engine(s), an engine cooling system that provides cooling air to engine components, an environmental control system that provides cooled air to the cabin of the aircraft, and/or the like. Such accessory systems also include bearings of various types to enable proper operation of the accessory systems.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 is a side view of an example aircraft.

[0005] FIG. 2 is a schematic cross-sectional view of an example gas turbine engine of an aircraft.

[0006] FIG. 3 is a schematic diagram of an example thermal management system for transferring heat between fluids.

[0007] FIG. 4 illustrates example integrated bearing systems for dynamically supporting a rotating shaft in an example pump system in accordance with the teachings of this disclosure.

[0008] FIG. 5 illustrates an example integrated bearing system for dynamically supporting the rotating shaft in the example pump system in accordance with the teachings of this disclosure.

[0009] FIG. 6 illustrates a first example foil bearing used in the fluid pump system of FIGS. 4 and/or 5.

[0010] FIG. 7 illustrates a second example foil bearing used in the fluid pump system of FIGS. 4 and/or 5.

[0011] FIG. 8 illustrates an example thrust bearing used in the fluid pump system of FIGS. 4 and/or 5.

[0012] FIG. 9 illustrates an enlarged view of a thrust bearing assembly using the thrust bearing of FIG. 8.

[0013] In general, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts. The figures are not to scale. Instead, the thickness of the layers or regions may be enlarged in the drawings. Although the figures show layers and regions with clean lines and boundaries, some or all of these lines and/or boundaries may be idealized. In reality, the boundaries and/or lines may be unobservable, blended, and/or irregular.

DETAILED DESCRIPTION

[0014] “Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including, having, etc.) as a preamble or within a claim recitation of any kind, it is to be understood that additional elements, terms, etc., may be present without falling outside the scope of the corresponding claim or recitation. As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, (6) B with C, or (7) A with B and with C. As used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. As used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B.

[0015] As used herein, unless otherwise stated, the term “above” describes the relationship of two parts relative to Earth. A first part is above a second part, if the second part has at least one part between Earth and the first part. Likewise, as used herein, a first part is “below” a second part when the first part is closer to the Earth than the second part. As noted above, a first part can be above or below a second part with one or more of: other parts therebetween, without other parts therebetween, with the first and second parts touching, or without the first and second parts being in direct contact with one another.

[0016] As used herein, singular references (e.g., “a”, “an”, “first”, “second”, etc.) do not exclude a plurality. The term “a” or “an” object, as used herein, refers to one or more of that object. The terms “a” (or “an”), “one or more”, and “at least one” are used interchangeably herein.

Furthermore, although individually listed, a plurality of means, elements or method actions may be implemented by, e.g., the same entity or object. Additionally, although individual features may be included in different examples or claims, these may possibly be combined, and the inclusion in different examples or claims does not imply that a combination of features is not feasible and/or advantageous.

[0017] As used in this patent, stating that any part (e.g., a layer, film, area, region, or plate) is in any way on (e.g., positioned on, located on, disposed on, or formed on, etc.) another part, indicates that the referenced part is either in contact with the other part, or that the referenced part is above the other part with one or more intermediate part(s) located therebetween.

[0018] As used herein, connection references (e.g., attached, coupled, connected, and joined) may include intermediate members between the elements referenced by the connection reference and/or relative movement between those elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and/or in fixed relation to each other. As used herein, stating that any part is in “contact” with another part is defined to mean that there is no intermediate part between the two parts.

[0019] Unless specifically stated otherwise, descriptors such as “first,” “second,” “third,” etc., are used herein without imputing or otherwise indicating any meaning of priority, physical order,

arrangement in a list, and/or ordering in any way, but are merely used as labels and/or arbitrary names to distinguish elements for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In such instances, it should be understood that such descriptors are used merely for identifying those elements distinctly that might, for example, otherwise share a same name.

[0020] As used herein, “approximately” and “about” modify their subjects/values to recognize the potential presence of variations that occur in real world applications. For example, “approximately” and “about” may modify dimensions that may not be exact due to manufacturing tolerances and/or other real world imperfections as will be understood by persons of ordinary skill in the art. For example, “approximately” and “about” may indicate such dimensions may be within a tolerance range of $\pm 10\%$ unless otherwise specified in the below description.

[0021] The terms “forward” and “aft” refer to relative positions within a gas turbine engine, pump, or vehicle, and refer to the normal operational attitude of the gas turbine engine, pump, or vehicle. For example, with regard to a gas turbine engine, forward refers to a position closer to an engine inlet and aft refers to a position closer to an engine nozzle or exhaust. Further, with regard to a pump, forward refers to a position closer to a pump inlet and aft refers to a position closer to an end of the pump opposite the inlet.

[0022] The terms “upstream” and “downstream” refer to the relative direction with respect to a flow in a pathway. For example, with respect to a fluid flow, “upstream” refers to the direction from which the fluid flows, and “downstream” refers to the direction to which the fluid flows.

[0023] As used herein, “radially” is used to express a point or points along a radial vector originating at a central axis of a rotating body and pointing perpendicularly outward from the central axis. In some examples, two gears are said to be radially connected or coupled, meaning that the two gears are in physical contact with each other at point(s) along the circumferential outer edge surface of the gears via interlocking gear teeth. In some examples, two pulleys are said to be radially connected or coupled, meaning that the two pulleys are in physical contact with a drive belt at point(s) along the circumferential outer edge surface of the pulleys.

[0024] Centrifugal fluid pumps move fluid through systems by converting rotational kinetic energy of an impeller to hydrodynamic energy of a flowing fluid. In other words, the angular velocity of the impeller is directly proportional to the flow rate of the flowing fluid exiting the pump. The impeller provides a change in rotational kinetic energy from an electric motor applying mechanical work to an impeller shaft coupled to the impeller and to the rotor of the electric motor. The rotor is provided a change in mechanical work over a period of time (i.e., mechanical power) from a stator in the electric motor applying electromagnetic forces to the rotor in the form of torque. If the motor supplies a constant amount of electrical energy to the stator, then the rotor will supply a constant amount of mechanical energy to the impeller. In this case, the mechanical power supplied to the pump by the electric motor would be equal to the quotient of the rotational kinetic energy and the amount of time the power is being supplied. In rotational systems, such as a centrifugal fluid pump, the mechanical power of the impeller is equal to the product of the torque and the angular velocity. If the rotor of the electric motor and the impeller shaft of the centrifugal fluid pump are coupled axially (e.g., by a magnetic coupling), then the torque and angular velocity of the rotor would transfer to the impeller, via the coupled shafts, and would be of the same values.

[0025] In some examples of fluid pump systems, a motor shaft (e.g., a rotor) can be axially coupled to an impeller shaft via a magnetic coupling. Magnetic couplings transfer torque between two shafts without physical contact between the shafts. In some examples, the magnetic coupling can be in the form of an inner hub fastened to a first shaft (e.g., an impeller shaft) and an outer hub fastened to a second shaft (e.g., a rotor shaft). In the example outer hub, there are a series of magnets (e.g., bar magnets) positioned to surround the example inner hub with each magnet having an opposite charge of the preceding magnet in the series. In the inner hub, a similar series of

magnets are positioned around an axis of rotation of the first shaft. In some examples, the outer hub and inner hub have the same number of magnets. Because magnets of opposite charges are attracted to each other via magnetic fields, when the outer hub is positioned around the inner hub, a rotation of the outer hub causes the inner hub to rotate at the same rate. In other words, the example inner hub and the example outer hub are rotatably interlocked. This type of magnetic coupling can be referred to as a co-axial magnetic coupling. Because there is no physical contact between the inner hub and outer hub of the co-axial magnetic coupling, a containment barrier can be fastened to the housing surrounding the inner hub such that no fluid can pass from the inner hub side to the outer hub side.

[0026] Foil bearings are included in fluid pump systems to act as buffers preventing shafts (e.g., a rotor shaft, a radial shaft, etc.) from contacting with a lining surrounding the shaft and allowing relative motion between the shaft and the lining. In some examples, the foil bearing may become damaged when the shaft exerts too much force on the foil bearing, causing permanent deformation to the foil bearing and ultimately causing damage to the pump system. In such an example, the foil bearing is rated to support a load applied to the foil bearing by the shaft, and when the shaft exceeds that load, the foil bearing becomes damaged.

[0027] Certain examples provide an improved bearing design that resists damage caused by the forces applied by aircraft engines, the forces of flight of an aircraft, and the forces applied by pump systems. As discussed further below, certain examples provide an improved bearing design to improve the integrity, stability, and reliability of bearings used in apparatus such as the aircraft, engine, and pump described below.

[0028] FIG. 1 is a side view of an example aircraft 10. As shown, the aircraft 10 includes a fuselage 12 and a pair of wings 14 (one is shown) extending outward from the fuselage 12. In the illustrated example of FIG. 1, a gas turbine engine 100 is supported on each wing 14 to propel the aircraft through the air during flight. Additionally, as shown, the aircraft 10 includes a vertical stabilizer 16 and a pair of horizontal stabilizers 18 (one is shown). However, in alternative examples, the aircraft 10 may be configured differently, such as with a different number and/or type of engines.

[0029] Furthermore, the aircraft 10 may include a thermal management system 200 for transferring heat between fluids supporting the operation of the aircraft 10. More specifically, the aircraft 10 may include one or more accessory systems configured to support the operation of the aircraft 10. For example, such accessory systems include a lubrication system that lubricates components of the engines 100, a cooling system that provides cooling air to components of the engines 100, an environmental control system that provides cooled air to the cabin of the aircraft 10, and/or the like. In such examples, the thermal management system 200 is configured to transfer heat to and/or from one or more fluids supporting the operation of the aircraft 10 (e.g., the oil of the lubrication system, the air of the cooling system and/or the environmental control system, and/or the like) from and/or to one or more other fluids supporting the operation of the aircraft 10 (e.g., the fuel supplied to the engines 100). However, in alternative examples, the thermal management system 200 may be configured to transfer heat between other fluids supporting the operation of the aircraft 10.

[0030] In addition to the thermal management system 200, the aircraft 10 is subjected to various forces during operation which include aerodynamic forces (e.g., lift, thrust, drag, gravity), vibration forces, shear forces, etc. As such, components within the aircraft 10 (e.g., such as the example thermal management system 200, the engine 100, etc.) need to withstand such forces without failure to ensure the aircraft 10 functions properly. Failure to the thermal management system 200 due to excessive forces can lead to failure of the engine 100 or failure to other systems on the aircraft 10.

[0031] The configuration of the aircraft 10 described above and shown in FIG. 1 is provided only to place the present subject matter in an example field of use. Thus, the present subject matter may be readily adaptable to any manner of aircraft and/or any other suitable heat transfer application.

[0032] FIG. 2 is a schematic cross-sectional view of an example gas turbine engine 100. In the

illustrated example, the engine **100** is configured as a high-bypass turbofan engine. However, in alternative examples, the engine **100** may be configured as a propfan engine, a turbojet engine, a turboprop engine, a turboshaft gas turbine engine, or any other suitable type of gas turbine engine. [0033] In general, the engine **100** extends along an axial centerline **102** and includes a fan **104**, a low-pressure (LP) spool **106**, and a high pressure (HP) spool **108** at least partially encased by an annular nacelle **110**. More specifically, the fan **104** may include a fan rotor **112** and a plurality of fan blades **114** (one is shown) coupled to the fan rotor **112**. In this respect, the fan blades **114** are circumferentially spaced apart and extend radially outward from the fan rotor **112**. Moreover, the LP and HP spools **106**, **108** are positioned downstream from the fan **104** along the axial centerline **102**. As shown, the LP spool **106** is rotatably coupled to the fan rotor **112**, thereby permitting the LP spool **106** to rotate the fan blades **114**. Additionally, a plurality of outlet guide vanes or struts **116** circumferentially spaced apart from each other and extend radially between an outer casing **118** surrounding the LP and HP spools **106**, **108** and the nacelle **110**. As such, the struts **116** support the nacelle **110** relative to the outer casing **118** such that the outer casing **118** and the nacelle **110** define a bypass airflow passage **120** positioned therebetween.

[0034] The outer casing **118** generally surrounds or encases, in serial flow order, a compressor section **122**, a combustion section **124**, a turbine section **126**, and an exhaust section **128**. In some examples, the compressor section **122** may include a low-pressure (LP) compressor **130** of the LP spool **106** and a high-pressure (HP) compressor **132** of the HP spool **108** positioned downstream from the LP compressor **130** along the axial centerline **102**. Each compressor **130**, **132** may, in turn, include one or more rows of stator vanes **134** interdigitated with one or more rows of compressor rotor blades **136**. As such, the compressors **130**, **132** define a compressed air flow path **133** extending therethrough. Moreover, in some examples, the turbine section **126** includes a high-pressure (HP) turbine **138** of the HP spool **108** and a low-pressure (LP) turbine **140** of the LP spool **106** positioned downstream from the HP turbine **138** along the axial centerline **102**. Each turbine **138**, **140** may, in turn, include one or more rows of stator vanes **142** interdigitated with one or more rows of turbine rotor blades **144**.

[0035] Additionally, the LP spool **106** includes the low-pressure (LP) shaft **146** and the HP spool **108** includes a high pressure (HP) shaft **148** positioned concentrically around the LP shaft **146**. In such examples, the HP shaft **148** rotatably couples the turbine rotor blades **144** of the HP turbine **138** and the compressor rotor blades **136** of the HP compressor **132** such that rotation of the turbine rotor blades **144** of the HP turbine **138** rotatably drives the compressor rotor blades **136** of the HP compressor **132**. As shown, the LP shaft **146** is directly coupled to the turbine rotor blades **144** of the LP turbine **140** and the compressor rotor blades **136** of the LP compressor **130**. Furthermore, the LP shaft **146** is coupled to the fan **104** via a gearbox **150**. In this respect, the rotation of the turbine rotor blades **144** of the LP turbine **140** rotatably drives the compressor rotor blades **136** of the LP compressor **130** and the fan blades **114**.

[0036] In some examples, the engine **100** may generate thrust to propel an aircraft. More specifically, during operation, air (indicated by arrow **152**) enters an inlet portion **154** of the engine **100**. The fan **104** supplies a first portion (indicated by arrow **156**) of the air **152** to the bypass airflow passage **120** and a second portion (indicated by arrow **158**) of the air **152** to the compressor section **122**. The second portion **158** of the air **152** first flows through the LP compressor **130** in which the compressor rotor blades **136** therein progressively compress the second portion **158** of the air **152**. Next, the second portion **158** of the air **152** flows through the HP compressor **132** in which the compressor rotor blades **136** therein continue to progressively compress the second portion **158** of the air **152**. The compressed second portion **158** of the air **152** is subsequently delivered to the combustion section **124**. In the combustion section **124**, the second portion **158** of the air **152** mixes with fuel and burns to generate high-temperature and high-pressure combustion gases **160**. Thereafter, the combustion gases **160** flow through the HP turbine **138** which the turbine rotor blades **144** of the HP turbine **138** extract a first portion of kinetic and/or thermal energy

therefrom. This energy extraction rotates the HP shaft **148**, thereby driving the HP compressor **132**. The combustion gases **160** then flow through the LP turbine **140** in which the turbine rotor blades **144** of the LP turbine **140** extract a second portion of kinetic and/or thermal energy therefrom. This energy extraction rotates the LP shaft **146**, thereby driving the LP compressor **130** and the fan **104** via the gearbox **150**. The combustion gases **160** then exit the engine **100** through the exhaust section **128**.

[0037] As mentioned above, the aircraft **10** may include a thermal management system **200** for transferring heat between fluids supporting the operation of the aircraft **10**. In this respect, the thermal management system **200** may be positioned within the engine **100**. For example, as shown in FIG. 2, the thermal management system **200** is positioned within the outer casing **118** of the engine **100**. However, in alternative examples, the thermal management system **200** may be positioned at any other suitable location within the engine **100**.

[0038] Furthermore, in some examples, the engine **100** defines a third-stream flow path **170**. In general, the third-stream flow path **170** extends from the compressed air flow path **133** defined by the compressor section **122** to the bypass airflow passage **120**. In this respect, the third-stream flow path **170** allows a portion of the compressed air **158** from the compressor section **122** to bypass the combustion section **124**. More specifically, in some examples, the third-stream flow path **170** may define a concentric or non-concentric passage relative to the compressed air flow path **170** downstream of one or more of the compressors **130**, **132** or the fan **104**. The third-stream flow path **170** may be configured to selectively remove a portion of compressed air **158** from the compressed air flow path **170** via one or more variable guide vanes, nozzles, or other actuable flow control structures. In addition, as will be described below, in some examples, the thermal management system **200** may transfer heat to the air flowing through the third-stream flow path **170**. However, a pressure and/or a flow rate of a fluid (e.g., a heat exchange fluid such as a supercritical fluid (e.g., supercritical carbon dioxide (sCO₂), etc.)) within the thermal management system **200** limits a rate at which thermal energy is transferred between the air and the heat exchange fluid. Additionally, it is advantageous for the thermal management system **200** to produce the pressure and/or the flow rate with components (e.g., pump systems) that minimize and/or otherwise reduce a physical size of the thermal management system **200** and/or the components (e.g., pump systems) included therein. Moreover, the thermal management system **200** may ensure that the heat exchange fluid is free of contaminants when thermal energy is to be transferred.

[0039] The example thermal management system **200**, as described above, ensures proper operation of the aircraft **10**. As such, the thermal management system **200** must be operational to support the operation of the aircraft **10**. The thermal management system **200** can include a pump system to move fluid throughout the thermal management system **200** to support heat transfer functionality. Pump systems can include bearings which support the operation of the pump system. As disclosed above, failure of bearings in pump systems can occur where the bearings are subjected to excessive forces (e.g., vibration, shear, stress, etc.) beyond what the bearings are rated for, and thus, can cause failure to the pump system. Consequently, failure to the pump system can cause failure to the thermal management system **200** and, likewise, failure to the engine **100**.

[0040] The configuration of the gas turbine engine **100** described above and shown in FIG. 2 is provided only to place the present subject matter in an example field of use. Thus, the present subject matter may be readily adaptable to any manner of gas turbine engine configuration, including other types of aviation-based gas turbine engines, marine-based gas turbine engines, and/or land-based/industrial gas turbine engines.

[0041] FIG. 3 is a schematic view of an example implementation of the thermal management system **200** for transferring heat between fluids. In general, the thermal management system **200** will be discussed in the context of the aircraft **10** and the gas turbine engine **100** described above and shown in FIGS. 1 and 2. However, the disclosed thermal management system **200** may be implemented within other aircraft and/or any gas turbine engine configuration.

[0042] As shown, the thermal management system **200** includes a thermal transport bus **202**. Specifically, in several examples, the thermal transport bus **202** is configured as one or more fluid conduits through which a fluid (e.g., a heat exchange fluid) flows. As will be described below, the heat exchange fluid flows through various heat exchangers such that heat is added to and/or removed from the heat exchange fluid. In this respect, the heat exchange fluid may be any suitable fluid, such as supercritical carbon dioxide. Moreover, in such examples, the thermal management system **200** includes a pump **204** configured to pump the heat exchange fluid through the thermal transport bus **202**.

[0043] Additionally, the thermal management system **200** includes one or more heat source heat exchangers **206** arranged along the thermal transport bus **202**. More specifically, the heat source heat exchanger(s) **206** is fluidly coupled to the thermal transport bus **202** such that the heat exchange fluid flows through the heat source heat exchanger(s) **206**. In this respect, the heat source heat exchanger(s) **206** is configured to transfer heat from fluids supporting the operation of the aircraft **10** to the heat exchange fluid, thereby cooling the fluids supporting the operation of the aircraft **10**. Thus, the heat source heat exchanger(s) **206** adds heat to the heat exchange fluid. Although FIG. 3 illustrates two heat source heat exchangers **206**, the thermal management system **200** may include a single heat source heat exchanger **206** or three or more heat source heat exchangers **206**.

[0044] The heat source heat exchanger(s) **206** may correspond to any suitable heat exchanger(s) that cool a fluid supporting the operation of the aircraft **10**. In one example, at least one of the heat exchangers **206** is a heat exchanger(s) of the lubrication system(s) of the engine(s) **100**. In such an example, this heat exchanger(s) **206** transfers heat from the oil lubricating the engine(s) **100** to the heat transfer fluid. In another example, at least one of the heat exchangers **206** is a heat exchanger(s) of the cooling system of the engine(s) **100**. In such an example, this heat exchanger(s) **206** transfers heat from the cooling air bled from the compressor section(s) **122** (or a compressor discharge plenum) of the engine(s) **100** to the heat transfer fluid. However, in alternative examples, the heat source heat exchanger(s) **206** may correspond to any other suitable heat exchangers that cool a fluid supporting the operation of the aircraft **10**.

[0045] Furthermore, the thermal management system **200** includes a plurality of heat sink heat exchangers **208** arranged along the thermal transport bus **202**. More specifically, the heat sink heat exchangers **208** are fluidly coupled to the thermal transport bus **202** such that the heat exchange fluid flows through the heat sink heat exchangers **208**. In this respect, the heat sink heat exchangers **208** are configured to transfer heat from the heat exchange fluid to other fluids supporting the operation of the aircraft **10**, thereby heating the other fluids supporting the operation of the aircraft **10**. Thus, the heat sink heat exchangers **208** remove heat from the heat exchange fluid. Although FIG. 3 illustrates two heat sink heat exchangers **208**, the thermal management system **200** may include three or more heat sink heat exchangers **208**.

[0046] The heat sink heat exchangers **208** may correspond to any suitable heat exchangers that heat a fluid supporting the operation of the aircraft **10**. For example, at least one of the heat exchangers **208** is a heat exchanger(s) of the fuel system(s) of the engine(s) **100**. In such an example, the fuel system heat exchanger(s) **208** transfers heat from the heat transfer fluid to the fuel supplied to the engine(s) **100**. In another embodiment, at least one of the heat exchangers **208** is a heat exchanger(s) in contact with the air **156** flowing through the bypass airflow passage(s) **120** of the engine(s) **100**. In such an example, this heat exchanger(s) **208** transfers heat from the heat exchange fluid to the air **156** flowing through the bypass airflow passage(s) **120**.

[0047] In several examples, one or more of the heat exchangers **208** are configured to transfer heat to the air flowing through the third-stream flow path **170**. In such examples, the heat exchanger(s) **208** is in contact with the air flow through the third-stream flow path **170**. Thus, heat from the heat exchange fluid flowing through the thermal transport bus **202** may be transferred to the air flow through the third-stream flow path **170**. The use of the third-stream flow path **170** as a heat sink for

the thermal management system **200** provides one or more technical advantages. For example, the third-stream flow path **170** provides greater cooling than other sources of bleed air because a larger volume of air flows through the third-stream flow path **170** than other bleed air flow paths. Moreover, the air flowing through third-stream flow path **170** is cooler than the air flowing through other bleed air flow paths and the compressor bleed air. Additionally, the air in the third-stream flow path **170** is pressurized, thereby allowing the heat exchanger(s) **208** to be smaller than heat exchangers relying on other heat sinks within the engine. Furthermore, in examples in which the engine **100** is unducted, using the third-stream flow path **170** as a heat sink does not increase drag on the engine **100** unlike the use of ambient air (e.g., a heat exchanger in contact with air flowing around the engine **100**). However, in alternative examples, the heat sink heat exchangers **208** may correspond to any other suitable heat exchangers that heats a fluid supporting the operation of the aircraft **10**.

[0048] Moreover, in several examples, the thermal management system **200** includes one or more bypass conduits **210**. Specifically, as shown in the example of FIG. 3, each bypass conduit **210** is fluidly coupled to the thermal transport bus **202** such that the bypass conduit **210** allows at least a portion of the heat exchange fluid to bypass one of the heat exchangers **206**, **208**. In some examples, the heat exchange fluid bypasses one or more of the heat exchangers **206**, **208** to adjust the temperature of the heat exchange fluid within the thermal transport bus **202**. The flow of example heat exchange fluid through the bypass conduit(s) **210** is controlled to regulate the pressure of the heat exchange fluid within the thermal transport bus **202**. In the illustrated example of FIG. 3, each heat exchanger **206**, **208** has a corresponding bypass conduit **210**. However, in alternative examples, any number of heat exchangers **206**, **208** may have a corresponding bypass conduit **210** so long as there is at least one bypass conduit **210**.

[0049] Additionally, in several examples, the thermal management system **200** includes one or more heat source valves **212** and one or more heat sink valves **214**. In general, each heat source valve **212** is configured to control the flow of the heat exchange fluid through a bypass conduit **210** that bypasses a heat source heat exchanger **206**. Similarly, each heat sink valve **214** is configured to control the flow of the heat exchange fluid through a bypass conduit **210** that bypasses a heat sink heat exchanger **208**. In this respect, each valve **212**, **214** is fluidly coupled to the thermal transport bus **202** and a corresponding bypass conduit **210**. As such, each valve **212**, **214** may be moved between fully and/or partially opened and/or closed positions to selectively occlude the flow of heat exchange through its corresponding bypass conduit **210**.

[0050] The valves **212**, **214** are controlled based on the pressure of the heat exchange fluid within the thermal transport bus **202**. More specifically, as indicated above, in certain instances, the pressure of the heat exchange fluid flowing through the thermal transport bus **202** may fall outside of a desired pressure range. When the pressure of the heat exchange fluid is too high, the thermal management system **200** may incur accelerated wear. In this respect, when the pressure of the heat exchange fluid within the thermal transport bus **202** exceeds a maximum or otherwise increased pressure value, one or more heat source valves **212** open. In such instances, at least a portion of the heat exchange fluid flows through the bypass conduits **210** instead of the heat source heat exchanger(s) **206**. Thus, less heat is added to the heat exchange fluid by the heat source heat exchanger(s) **206**, thereby reducing the temperature and, thus, the pressure of the fluid. In several embodiments, the maximum pressure value is between 3800 and 4000 pounds per square inch or less. In some embodiments, the maximum pressure value is between 2700 and 2900 pounds per square inch, such as 2800 pounds per square inch. In other embodiments, the maximum pressure value is between 1300 and 1500 pounds per square inch, such as 1400 pounds per square inch. Such maximum pressure values generally prevent the thermal management system **200** from incurring accelerated wear.

[0051] In some examples, the maximum pressure value is set prior to and/or during operation based on parameters (e.g., materials utilized, pump **204** design, aircraft **10** design, gas turbine engine **100**

design, heat exchange fluid, etc.) associated with the thermal management system **200**. The example maximum pressure value can be adjusted relative to the pressure capacities of the thermal transport bus **202**, the pump **204**, the heat exchangers **206**, **208**, the bypass conduit(s) **210**, and/or the valves **212**, **214**. Some examples of pump **204** architecture that influence example maximum pressure capacities are described in greater detail below.

[0052] Conversely, when the pressure of the heat exchange fluid is too low, the pump **204** may experience operability problems and increased wear. As such, when the pressure of the heat exchange fluid within the thermal transport bus falls below a minimum or otherwise reduced pressure value, one or more thermal sink valves **214** open. In such instances, at least a portion of the heat exchange fluid flows through the bypass conduits **210** instead of the heat sink heat exchangers **208**. Thus, less heat is removed from the heat exchange fluid by the heat sink heat exchangers **208**, thereby increasing the temperature and, thus, the pressure of the fluid. In several examples, the minimum pressure value is 1070 pounds per square inch or more. In some examples, the minimum pressure value is between 1150 and 1350 pounds per square inch, such as 1250 pounds per square inch. In other examples, the minimum pressure value is between 2400 and 2600 pounds per square inch, such as 2500 pounds per square inch. Such minimum pressure values are generally utilized when the heat exchange fluid is in a supercritical state (e.g., when the heat exchange fluid is carbon dioxide).

[0053] As such, the thermal management system **200** may be configured to operate such that the pressure of the heat transport fluid is maintained with a range extending between the minimum and maximum pressure values. In some examples, the range extends from 1070 to 4000 pounds per square inch. Specifically, in one example, the range extends from 1250 to 1400 pounds per square inch. In another example, range extends from 2500 to 2800 pounds per square inch.

[0054] Accordingly, the operation of the pump **204** and the valves **212**, **214** allows the disclosed thermal management system **200** to maintain the pressure of the heat exchange fluid within the thermal transport bus **202** within a specified range of values as the thermal load placed on the thermal management system **200** varies.

[0055] Furthermore, the example pump **204** drives the flow of the heat exchange fluid through the thermal management system **200**. In some examples, the thermal management system **200** includes one pump **204** or multiple pumps **204** depending on the desired flow rate, delta pressure across the pump **204**, and/or the kinetic energy loss of the heat exchange fluid in the thermal transport bus **202**. For example, the pump **204** may increase the output pressure head to accelerate the flow of the heat exchange fluid to a first flowrate. As the heat exchange fluid passes through the thermal transport bus **202**, the example kinetic energy of the heat exchange fluid dissipates due to friction, temperature variations, etc. Due to the kinetic energy losses, the heat exchange fluid decelerates to a second flow rate at some point upstream of the pump **204**. If the example second flow rate is below a desired operating flow rate of the heat exchange fluid, then the pump **204** can either be of a different architecture that outputs a higher first flow rate, or one or more additional pumps **204** can be included in the thermal management system **200**.

[0056] As disclosed above, the example pump **204** is important for proper functionality of the engine **100** and subsequently the aircraft **10**. Failure to the pump **204** can result in increases in temperature of the fluid, insufficient pressure of the fluid, and/or insufficient fluid flow rate of the fluid moving throughout the thermal management system **200**. Such failures can occur due to bearings within the pump **204** failing when the forces acting on the bearings exceed their rated thresholds. As discussed further below, examples disclosed herein provide an improved bearing design to improve the integrity, stability, and reliability of bearings used in apparatus such as the aircraft **10**, engine **100**, and pump **204**.

[0057] The operations of some example fluid pump systems and centrifugal fluid pump systems have a rotor shaft connected directly to the impeller in a pump system without a magnetic coupling to connect the rotor/radial shaft and an impeller shaft. In some examples, a bearing is used to

support a radial and/or an axial load that a rotor/radial shaft generates, respectively, during operation of the pump system. In some examples, the bearing supporting the radial load can include a foil bearing and the bearing supporting the axial load can include a thrust bearing. A foil/thrust bearing is a form of air bearing that uses a spring-loaded foil between a shaft and a journal lining to support the shaft at low startup speeds. Once the shaft is rotating at a high enough rate (depending on the architecture of the foil/thrust bearing) a working fluid (e.g., air, nitrogen, argon, etc.) is pulled into the foil/thrust bearing due to the viscosity effects of the working fluid. Thus, the working fluid pressure increases in the foil/thrust bearing, pushes the foil outward from the shaft, and supports the radial/axial load that the shaft generates creating a frictionless bearing with no liquid lubricants. Since the foil/thrust bearing does not use liquid lubricants, a hermetic sealing (e.g., a magnetic coupling) may not be used to prevent lubricants from contaminating a fluid (e.g., heat exchange fluid such as a supercritical fluid (e.g., sCO₂, etc.)) that the pump system pressurizes.

[0058] In some examples, the foil/thrust bearing used to support the radial/axial load that the rotor/radial shaft produces experiences wear during the start-up, stopping, and non-operation of the pump system. More specifically, the spring-loaded foil that supports the weight of the rotor shaft at lower speeds (start-up and stopping rotational speeds) experiences damage over time due to frictional erosion. Additionally, non-operation of the pump purports the same damage possibilities where the aircraft **10** may cause vibration to the pump system while the aircraft **10** is in operation, causing the rotor/radial shafts to damage the foil/thrust bearings. In the examples disclosed herein, a deformation limiter is disposed in the foil/thrust bearing to limit deformation of the spring-loaded foil during start-up, stopping, and non-operation of the pump system. Thus, the examples disclosed herein limit a radial/axial deformation that the foil/thrust bearing may experience during start-up, stopping, and non-operation of the pump system and reduce damage to the foil/thrust bearings to increase the lifespan (e.g., usable life) of the foil/thrust bearings.

[0059] FIG. **4** illustrates a cross-sectional view of a pump system **400** for pressurizing fluid (e.g., a heat exchange fluid such as a supercritical fluid (e.g., sCO₂, etc.)) in a system (e.g., thermal management system **200** of FIG. **3**). In some examples, the pump system **400** is used to pump sCO₂ through a thermal management system on an aircraft (e.g., aircraft **10** of FIG. **1**) and/or a gas turbine engine (e.g., gas turbine engine **100** of FIG. **2**). As shown in FIG. **4**, the pump system **400** includes an impeller **402**, a rotor shaft **404**, a rotor **405**, a stator **406**, a thrust bearing **408**, radial shafts **409**, a first integrated bearing system **410**, a thrust bearing assembly **411**, a first sprag clutch **412**, a first bearing housing **413**, a first rolling-element bearing **414**, a first foil bearing **416**, a second integrated bearing system **418**, a second sprag clutch **420**, a second bearing housing **421**, a second rolling-element bearing **422**, and a second foil bearing **424**.

[0060] The example pump system **400** illustrated in FIG. **4** includes the impeller **402** to pressurize the fluid (e.g., sCO₂) in the system (e.g., the thermal management system **200** of FIG. **3**). The example impeller **402** is a component of the pump system **400** that is connected to the rotor shaft **404** and rotates at a same rotational speed as the rotor shaft **404**. In some examples, the impeller **402** is same as or similar to impellers used in centrifugal pumps and includes vanes and/or blades to deflect flow of the incoming fluid radially outward into outlet flowlines. The example impeller **402** converts mechanical power of a motor (e.g., the rotor shaft **404** and the stator **406**) into hydrodynamic power of the fluid flow.

[0061] The example pump system **400** illustrated in FIG. **4** includes the stator **406** to apply a torque on the rotor **405**, which is coupled to the rotor shaft **404**. Since the example rotor **405** is connected to the rotor shaft **404** (e.g., via bolts, adhesives, interference fit, etc.), the stator **406** causes the rotor shaft **404** to rotate while the stator **406** remains stationary. The example stator **406**, the example rotor **405**, and the example rotor shaft **404** are included as parts of an example electric motor and/or the engine **100**. In some examples, the stator **406** includes field magnets (e.g., electromagnets or permanent magnets) that generate magnetic field(s) based on an electric current (e.g., direct current

or alternating current) passing through various the electromagnets of the stator **406**. The example stator **406** generates a first set of magnetic fields that apply a force (e.g., Lorentz force) on a second set of magnetic fields that the rotor **405** generates. The example rotor **405** generates the second set of magnetic fields via permanent magnets and/or electromagnets. Since the example stator **406** is stationary (e.g., fixed in place), the force causes the example rotor **405** to rotate and to produce a torque. Since the example rotor shaft **404** is connected to the example rotor **405**, the rotor shaft **404** produces the same torque and rotates at a same angular velocity as the rotor **405**.

[0062] The example thrust bearing assembly **411** illustrated in FIG. **4** includes the thrust bearing **408** to support a thrust load (axial load) that the rotor shaft **404** generates during operation. The example thrust bearing **408** illustrated in FIG. **4** is further described below in reference to FIGS. **8** and **9**. The example rotor shaft **404** is connected to two or more radial shafts **409** that are positioned perpendicular to the axis of rotation of the rotor shaft **404**. In some examples, the radial shafts **409** are connected to the rotor shaft via bolts, adhesives, interference fits, etc. The example pump system **400** illustrated in FIG. **4** includes two radial shafts **409**. However, more radial shafts **409** may be connected to the rotor shaft **404**. In some examples, the thrust bearing **408** includes an inner lining that interfaces with the radial shafts **409** and the spring-loaded foil. In some examples, the radial shafts **409** is a disk that is connected to the rotor shaft **404** and interacts directly with the spring-loaded foil of the thrust bearing **408**.

[0063] The example pump system **400** of FIG. **4** includes the first integrated bearing system **410** to support the radial loads of the rotor shaft **404** during operation of the pump system **400**. The example first integrated bearing system **410** includes the first sprag clutch **412**, the bearing housing **413**, the first rolling-element bearing **414**, and the first foil bearing **416**. The example pump system **400** of FIG. **4** also includes the second integrated bearing system **418** to similarly support the radial loads of the rotor shaft **404**. The second integrated bearing system **418** includes the second sprag clutch **420**, the second rolling-element bearing **422**, and the second foil bearing **424**. In some examples, the pump system **400** includes one integrated bearing system. In some examples, the pump system **400** includes one or more integrated bearing systems. The example first integrated bearing system **410** and the example second integrated bearing system **418** of the example pump system **400** illustrated in FIG. **4** are substantially similar. Thus, references and descriptions regarding the first integrated bearing system **410** (“bearing system **410**”), the first sprag clutch **412** (“sprag clutch **412**”), the first bearing housing **413** (“bearing housing **413**”), the first rolling-element bearing **414** (“rolling-element bearing **414**”), and the first foil bearing **416** (“foil bearing **416**”) can also be applied to the second integrated bearing system **418**, the second sprag clutch **420**, the second bearing housing **421**, the second rolling-element bearing **422**, and the second foil bearing **424**, respectively.

[0064] The example pump system **400** illustrated in FIG. **4** includes the sprag clutch **412** to engage and disengage the rolling-element bearing **414** and the foil bearing **416** from one another during operation of the pump system **400**. The example sprag clutch **412** is a disengaging-type sprag clutch that resembles a rolling-element bearing but includes non-revolving asymmetric sprag elements instead of revolving symmetric cylinders, spheres, etc. The example sprag clutch **412** includes an inner race and an outer race between which the sprag elements fit in place. The example sprag clutch **412** also includes a spring ribbon to produce a pre-loaded spring force on the sprag elements to engage the sprag clutch with the inner race and the outer race during non-operation. Due to the asymmetric figure-eight shaped geometry of the sprag elements, when the sprag elements rotate and wedge between the outer race and the inner race, the friction force that occurs between the components of the sprag clutch **412** cause the inner race to rotate at the same angular velocity as the outer race. When the example sprag clutch **412**, inner race, and outer race rotate at a first operational speed range, the sprag elements of the sprag clutch **412** remain engaged with the outer race and the inner race due to the pre-loaded spring force and a resulting spring moment. When the example sprag clutch **412**, inner race, and outer race rotate at a second

operational speed range, the sprag elements of the sprag clutch **412** become disengaged with the outer race and the inner race due to a centrifugal force and resulting centrifugal moment counteracting and surpassing the spring moment. Further descriptions of the example sprag clutch **412** and the operations thereof are provided below.

[0065] The example pump system **400** illustrated in FIG. **4** includes the rolling-element bearing **414** to support the radial load of the rotor shaft **404** at the first operational speed range. Some examples of the first operational speed range include a first tangential speed range of the rotor shaft **404** and/or the foil bearing **416** from 0 m/s to 50 m/s, a first fluid flow speed range exiting the pump system **400** from 0 m/s to 10 m/s, etc. The example rolling-element bearing **414** includes an inner race, an outer race, and rolling elements (e.g., balls, spheres, cylinders, etc.). The inner race and outer race of the example rolling-element bearing **414** are able to rotate freely in either direction. In some examples, the rolling-element bearing **414** includes liquid lubricant (e.g., oil, grease, etc.) to reduce the friction forces within the rolling-element bearing **414** and increase the lifespan of the rolling-element bearing **414**. If the example pump system **400** uses liquid lubricants for the rolling-element bearing **414**, then an example oil separator may be included in the pump system **400** to help ensure the fluid does not get contaminated. Some examples of oil separators that can be utilized in the examples disclosed herein are described in further detail below. In some examples, the rolling-element bearing **414** includes an inorganic grease (e.g., silicone grease, bentonite clay, polyurea, etc.) as a lubricant. The example rolling-element bearing **414** illustrated in FIG. **4** uses a solid lubricant (e.g., silver coating, graphite, molybdenum disulfide, etc.) to reduce friction in the rolling-element bearing **414** and to increase the lifespan of the rolling-element bearing **414** while removing the risk of contaminating the fluid with liquid lubricants. The rolling-element bearing **414** can be one of many types of rolling-element bearings familiar to those with skill in the art, such as cylindrical rolling-element bearings, angular contact ball bearings, hybrid ceramic bearings, tapered rolling-element bearings, deep groove single ball bearings, duplex ball bearings, spherical ball bearings, or any combination thereof. In some examples, the rolling-element bearing **414** is hermetically sealed from the example fluid via one or more hermetic seals (e.g., piston seals, epoxy seal, ceramic-to-metal seal, etc.). The example rolling-element bearing **414** may have a lifespan of 1000 hours or more depending on the type of rolling-element bearing, the type of lubricant, and/or the effectiveness of the hermetic sealing. In some examples, the rolling-element bearing **414** is externally cooled via conductive heat exchange from the rolling-element bearing **414** to fuel, oil, air, and/or the thermal transport bus **202** of FIG. **2**. Additionally or alternatively, an evaporative cooling system may be used to cool the example rolling-element bearing **414**.

[0066] The example pump system **400** illustrated in FIG. **4** includes the foil bearing **416** to support the radial load of the rotor shaft **404** at the second operational speed range. Some examples of the second operational speed range include a second tangential speed range of the rotor shaft **404** and/or the foil bearing **416** from 50 m/s to 200 m/s, a second fluid flow speed range exiting the pump system **400** from 10 m/s to 100 m/s, etc. The example foil bearing **416** is further described in reference to FIGS. **6** and **7** below. The example foil bearing **416**, the example rolling-element bearing **414**, the example sprag clutch **412**, and, in general, the example integrated bearing system **410** are described in greater detail below.

[0067] The example pump system **400** illustrated in FIG. **4** includes the bearing housing **413** to support the rolling-element bearing **414** and the foil bearing **416**. In some examples, the bearing housing **413** is an additively manufactured part that is designed to fit dimensions of the rolling-element bearing **414** and the foil bearing **416**. In some examples, the bearing housing **413** is fabricated via subtractive manufacturing to fit dimensions of the rolling-element bearing **414** and the foil bearing **416**. In some examples, the bearing housing **413** securely supports the rolling-element bearing **414** and the foil bearing **416** via bolts, dowels, pins, adhesives, and/or interference fits.

[0068] FIG. 5 illustrates an enlarged view 500 of the example integrated bearing system 410 of the pump system 400 for supporting radial loads that the rotor shaft 404 generates during operation of the pump system 400. As shown in FIG. 5, the enlarged view 500 includes the rotor shaft 404, the integrated bearing system 410, the sprag clutch 412, the bearing housing 413, the rolling-element bearing 414, the foil bearing 416, sprag elements 502, a first inner race 504, a first outer race 506, a second inner race 508, and a second outer race 510. As mentioned earlier, the example components of the integrated bearing system 410 illustrated in FIG. 5 can be included in the example second integrated bearing system 418 illustrated in FIG. 4. The example enlarged view 500 of FIG. 5 illustrates the rotor shaft 404, the integrated bearing system 410, the sprag clutch 412, the bearing housing 413, the rolling-element bearing 414, and the foil bearing 416 as previously described in reference to FIG. 4.

[0069] The example integrated bearing system 410 as illustrated in FIG. 5 includes the sprag elements 502 to engage the first inner race 504 and the first outer race 506 such that the first inner race 504 and the first outer race 506 rotate simultaneously and with the same torque output. Although two sprag elements 502 are illustrated in FIG. 5, the example integrated bearing system 410 can include two or more sprag elements 502. As mentioned previously, the example sprag elements 502 are asymmetrically shaped such that when the sprag elements 502 rotate about an axis of rotation in a first direction, the sprag elements wedge between the first inner race 504 and the first outer race 506 and create friction forces between the components. The friction forces that the example sprag elements 502 create occur between the sprag elements 502 and the first inner race 504 as well as between the sprag elements 502 and the first outer race 506. The friction forces that the sprag elements 502 create cause the first inner race 504 and the first outer race 506 to rotate at a same angular velocity. As mentioned previously, the asymmetric shape of the sprag elements 502 also allow the first inner race 504 and the first outer race 506 to rotate freely in either direction when the sprag elements 502 rotate about the axis of rotation in a second direction opposite from the first direction. The sprag elements 502 and the operations thereof are described in greater detail below.

[0070] The example integrated bearing system 410 as illustrated in FIG. 5 includes the first inner race 504 to engage with the sprag elements 502 and the rolling-element bearing 414 at the first operational speed range (e.g., tangential speed range of the rotor shaft 404 and/or the foil bearing 416 from 0 m/s to 50 m/s, fluid flow speed range exiting the pump system 400 from 0 m/s to 10 m/s, etc.). The example first inner race 504 illustrated in FIG. 5 is a hollow shaft that envelops the rotor shaft 404 and is connected to the second inner race 508 of the rolling-element bearing 414 via bolts, adhesives, interference fits, etc. In some examples, the first inner race 504 is manufactured (e.g., subtractive machining or additive manufacturing) as the same part as the second inner race 508. The example first inner race 504 is longer than the second inner race 508 and the second outer race 510 such that the first inner race 504 interfaces with the second inner race 508 and the sprag elements 502.

[0071] The example integrated bearing system 410 as illustrated in FIG. 5 includes the first outer race 506 to engage with the sprag elements 502 and the foil bearing 416 at the second operational speed range (e.g., tangential speed range of the rotor shaft 404 and/or the foil bearing 416 from 50 m/s to 200 m/s, fluid flow speed range exiting the pump system 400 from 10 m/s to 100 m/s, etc.). The example first outer race 506 illustrated in FIG. 5 is a shaft that is connected to the rotor shaft 404 via bolts, adhesives, interference fits, etc. In some examples, the first outer race 506 is manufactured (e.g., subtractive machining or additive manufacturing) as the same part as the rotor shaft 404. The example first outer race 506 is designed such that the first outer race 506 interfaces with the sprag elements 502 and the inner lining of the example foil bearing 416.

[0072] FIG. 6 illustrates a first example foil bearing 600 which can be used in the pump system 400 of FIG. 4. The first example foil bearing 600 can be used in place of the foil bearing 416 in the pump system 400 of FIG. 4. The first example foil bearing 600 includes a fluid pocket 610, a

journal lining **620**, a spring-loaded foil **630**, an inner lining **640**, and a deformation limiter **650**. The spring-loaded foil **630** is coupled to the journal lining **620**, where the spring-loaded foil **630** is disposed between the inner lining **640** and the journal lining **620**.

[0073] The fluid pocket **610** is a pocket of pressurized fluid (e.g., compressed air) to create a non-contact barrier between the rotor shaft **404** and the inner lining **640**. In some examples, the fluid pocket **610** can be filled with pressurized fluid from the pump system **400** of FIG. **4**. When there is no fluid or not enough fluid to support the load of the rotor shaft **404**, the rotor shaft **404** can contact the inner lining **640** directly, increasing the risk of damage to the foil bearing **416**.

[0074] The journal lining **620** is a structural backing member that couples with the spring-loaded foil **630**. In the examples disclosed herein, the journal lining **620** is supported by the bearing housing **413**, **421** inside the pump system **400**. As illustrated by the first example foil bearing **600** of FIG. **6**, in some examples, the deformation limiter **650** is coupled to the journal lining **620**. In such an example, the deformation limiter **650** may be manufactured with the journal lining **620** and made of the same material as the journal lining **620** (e.g., such as steel or any other suitable material for the operating conditions of the foil bearing **416**).

[0075] The spring-loaded foil **630** is a structural member extending outward from the journal lining **620** to provide a dampening to a radial load. In some examples, the spring-loaded foil **630** provides the dampening to the radial load applied by the rotor shaft **404**. When the pump system **400** is in operation at high speeds, the fluid pocket **610** protects the spring-loaded foil **630** from deforming (e.g., plastically deforming). As noted above, when not in operation or at low speeds, the rotor shaft **404** can apply a radial load to the foil bearing **416**. The spring-loaded foil **630** provides a spring dampening to the load applied by the rotor shaft **404** to prevent damage to the journal lining **620**, and consequently, the pump system **400**. In some examples, the spring-loaded foil **630** implements means for dampening a load applied by the rotor shaft **404** to the first example foil bearing **600**.

[0076] The inner lining **640** is displaced between the spring-loaded foil **630** and the rotor shaft **404**. In some examples, the inner lining **640** includes a friction-less coating to reduce friction caused by the pressurized fluid in the fluid pocket **610**. Such an example coating may include Teflon™ or any other suitable friction-less/low-friction coating. The inner lining **640** provides a buffer surface between the spring-loaded foil **630** and the rotor shaft **404**. In some examples, the inner lining **640** provides an evenly distributed load to the spring-loaded foil **630** when the rotor shaft **404** is applying a radial load. In the examples disclosed herein, inner lining **640** and journal lining **620** of the foil bearing **416** are able to rotate freely in either direction. In some examples, the inner lining **640** implements means for separating a rotor shaft **404** from the spring-loaded foil **630**.

[0077] In the illustrated example of FIG. **6**, the deformation limiter **650** is coupled to/manufactured with the journal lining **620**. When a radial load is applied to the spring-loaded foil **630**, the deformation limiter **650** defines a maximum plastic deformation in which the spring-loaded foil **630** may be deformed (e.g., a structural maximum amount of deformation). The use of the deformation limiter **650** prevents damage to the journal lining **620**, and consequently the pump system **400**, by eliminating the possibility of the rotor shaft **404** directly contacting the journal lining **620**. In some examples, the deformation limiter **650** implements means for reducing a deformation to the spring-loaded foil **630**.

[0078] In the examples disclosed herein, the deformation limiter **650** may be sized per a parameterization function, such that a size of the deformation limiter **650** can be obtained by evaluating a maximum amount of radial deformation allowable, a minimum clearance that needs to be maintained between the spring-loaded foil **630** and the deformation limiter **650** (or, more generally, a minimum clearance between the rotor shaft **404** and the journal lining **620**), a maximum load applied by the rotor shaft **404**, or any other list of suitable parameters. For example, the parameterization function can characterize one or more rotating regions within the pump such that a maximum amount of allowable radial deformation prevents clearance closure and rubbing at the impeller and/or seals, etc. In some examples, the parameterization function may be an

exponential expansion of the desired size of the deformation limiter **650** based upon the changes to any one of or combination of parameters, such as the parameters listed above. In other examples, a polynomial function may be used to characterize each parameter and determine the size of the deformation limiter **650**. As such, the size, shape, and location of the deformation limiter **650** is not limited to the examples disclosed herein. The deformation limiter **650** can be used on various other types of bearings within a pump system and within other systems.

[0079] FIG. 7 illustrates a second example foil bearing **700** which can be used in the pump system **400** of FIG. 4. The second example foil bearing **700** can be used in place of the foil bearing **416** in the pump system **400** of FIG. 4. The second example foil bearing **700** includes the same components as the first example foil bearing **600** (e.g., the fluid pocket **610**, the journal lining **620**, the spring-loaded foil **630**, the inner lining **640**, and the deformation limiter **650**). In the second example foil bearing **700**, the deformation limiter **650** is disposed on the spring-loaded foil **630**. The deformation limiter **650** of the second example foil bearing **700** of FIG. 7 performs the same function as the deformation limiter **650** of the first example foil bearing **600** of FIG. 6.

[0080] As illustrated in FIG. 7, the disposition of the deformation limiter **650** on the spring-loaded foil **630** instead of the journal lining **620** may be desired. In such an example, the spring-loaded foil **630** may require additional structural integrity to function properly, which the deformation limiter **650** can provide. In other examples, it may be cheaper to manufacture the deformation limiter **650** with the spring-loaded foil **630** while still maintaining the same amount of protection to the pump system **400**. In yet another example, the deformation limiter **650** being disposed on the spring-loaded foil **630** may provide easier maintainability and/or replacement should the second example foil bearing **700** require replacement.

[0081] In operation, the first example foil bearing **600** and the second example foil bearing **700** operate similarly to react to forces applied by the aircraft **10** and/or the pump system **400**. As a force (e.g., the radial load) is applied to the first and second foil bearing **500**, **600**, the deformation limiter **650** limits the deformation (e.g., plastic deformation) of the spring-loaded foil **630**. The size, shape, material, etc. of the deformation limiter **650** produce a maximum deformation of the spring-loaded foil **630** by stopping the spring-loaded foil **630** from deforming once the deformation limiter **650** is in contact with both the spring-loaded foil **630** and the journal lining **620**.

[0082] FIG. 8 illustrates an example thrust bearing **800** which can be used in the pump system **400**. The example thrust bearing **800** can be used within the thrust bearing assembly **411** of the pump system **400** of FIG. 4. The example thrust bearing **800** supports the thrust load (axial load) that the rotor shaft **404** generates during operation, which is applied to the thrust bearing **408** via the radial shaft **409**. The example thrust bearing **800** includes a plurality of spring-loaded foils **630**.

[0083] As the aircraft **10**, engine **100**, pump system **200**, or any other system in which bearings are used, multiple loads may be applied to the system (e.g., aerodynamic forces, vibrations, shear, stress, etc.). As such, bearings need to be placed in the system to protect the components of the system from damage due to those varying forces. As discussed below in reference to FIG. 9, the example thrust bearing **800** provides a dampening to an axial force. In the examples disclosed herein, the example thrust bearing **800** provides a dampening to the axial force applied by the radial shaft **409**.

[0084] In operation, as a force (e.g., the axial load) is applied to the example thrust bearing **800**, the deformation limiter **650** limits the deformation (e.g., plastic deformation) of the spring-loaded foil **630**. The size, shape, material, etc. of the deformation limiter **650** produce a maximum deformation of the spring-loaded foil **630** by stopping the spring-loaded foil **630** from deforming once the deformation limiter **650** is in contact with both the spring-loaded foil **630** and the journal lining **620**.

[0085] FIG. 9 illustrates an enlarged view of the thrust bearing assembly **411** of FIG. 4. In the illustrated example of FIG. 9, the example thrust bearing **800** can be interchangeably used in place of the thrust bearing **408** within the thrust bearing assembly **411** of the pump system **400** of FIG. 4.

The enlarged view **900** includes the fluid pocket **610**, the journal lining **620**, the spring-loaded foil **630**, the inner lining **640**, and the deformation limiter **650**. The spring-loaded foil **630** is coupled to the journal lining **620** and the inner lining **640** is coupled to the journal lining **620** and extends over the spring-loaded foil **630**.

[0086] The fluid pocket **610** of FIG. **9**, similar to the fluid pocket **610** of FIG. **6**, is a pocket of pressurized fluid to create a non-contact barrier between the radial shaft **409** and the inner lining **640**. In some examples, the fluid pocket **610** can be filled with pressurized fluid from the pump system **400** of FIG. **4**. When there is no fluid or not enough fluid to support the load of the radial shaft **409**, the radial shaft **409** can contact the inner lining **640** directly, increasing the risk of damage to the thrust bearing **408**.

[0087] The journal lining **620** of FIG. **9**, similar to the journal lining **620** of FIG. **6**, is a structural backing member that couples with the spring-loaded foil **630**. As illustrated in FIG. **9**, the deformation limiter **650** is coupled to the journal lining **620**. In such an example, the deformation limiter **650** may be manufactured with the journal lining **620** and made of the same material as the journal lining **620** (e.g., such as steel or any other suitable material for the operating conditions of the thrust bearing **408**).

[0088] The spring-loaded foil **630** of FIG. **9**, similar to the spring-loaded foil **630** of FIG. **6**, is a structural member extending outward from the journal lining **620** to provide a dampening to an axial load. In some examples, the spring-loaded foil **630** provides the dampening to the axial load applied by the radial shaft **409**. When the pump system **400** is in operation at high speeds, the fluid pocket **610** protects the spring-loaded foil **630** from deforming (e.g., plastically deforming). As noted above, when not in operation or at low speeds, the rotor shaft **404** can apply a radial load to the foil bearing **416**. The spring-loaded foil **630** provides a spring dampening to the load applied by the rotor shaft **404** to prevent damage to the journal lining **620**, and consequently, the pump system **400**. In some examples, the spring-loaded foil **630** implements means for dampening a load applied by the radial shaft **409** to the example thrust bearing **800**.

[0089] The inner lining **640** of FIG. **9**, similar to the inner lining **640** of FIG. **6**, is displaced between the spring-loaded foil **630** and the radial shaft **409**. In some examples, the inner lining **640** includes a friction-less coating to reduce friction caused by the pressurized fluid in the fluid pocket **610**. Such an example coating may include Teflon™ or any other suitable friction-less/low-friction coating. The inner lining **640** provides a buffer surface between the spring-loaded foil **630** and the radial shaft **409**. In some examples, the inner lining **640** provides an evenly distributed load to the spring-loaded foil **630** when the radial shaft **409** is applying an axial load. In some examples, the inner lining **640** implements means for separating a radial shaft **409** from the spring-loaded foil **630**.

[0090] In the illustrated example of FIG. **9**, the deformation limiter **650** is coupled to/manufactured with the journal lining **620**. When an axial load is applied to the spring-loaded foil **630**, the deformation limiter **650** defines a maximum plastic deformation in which the spring-loaded foil **630** may be deformed (e.g., a structural maximum amount of deformation). The use of the deformation limiter **650** prevents damage to the journal lining **620**, and consequently the pump system **400**, by eliminating the possibility of the radial shaft **409** directly contacting the journal lining **620**. As disclosed above, in some examples, the deformation limiter **650** implements means for reducing a deformation to the spring-loaded foil **630**.

[0091] In the examples disclosed herein, the deformation limiter **650** may be sized per a parameterization function, such that a size of the deformation limiter **650** can be obtained by evaluating a maximum amount of axial deformation allowable, a minimum clearance that needs to be maintained between the spring-loaded foil **630** and the deformation limiter **650** (or, more generally, a minimum clearance between the radial shaft **409** and the journal lining **620**), a maximum load applied by the radial shaft **409**, or any other list of suitable parameters. For example, the parameterization function can characterize one or more rotating regions within the

pump such that a maximum amount of allowable radial deformation prevents clearance closure and rubbing at the impeller and/or seals, etc. In some examples, the parameterization function may be an exponential expansion of the required size of the deformation limiter 650 based upon the changes to any one of or combination of parameters, such as the parameters listed above. In other examples, a polynomial function may be used to characterize each parameter and determine the size of the deformation limiter 650. As such, the size, shape, and location of the deformation limiter 650 is not limited to the examples disclosed herein. The deformation limiter 650 can be used on various other types of bearing within a pump system and within other systems.

[0092] From the foregoing, it will be appreciated that example systems, methods, apparatus, and articles of manufacture have been disclosed that reduce failure to bearings in a pump system. The bearings disclosed herein can be foil bearings for supporting a radial load and/or a thrust bearing for supporting an axial load. The disclosed systems, methods, apparatus, and articles of manufacture reduce failure to bearings by adding a structural deformation limiter inside the spring-loaded foil of a bearing to define a maximum deformation of the spring-loaded foil when a load (e.g., a force) is applied to the spring-loaded foil that exceeds rated limits.

[0093] Further aspects of the presently disclosed subject matter are provided by the following clauses. Example methods, apparatus, systems, and articles of manufacture to reduce failure to bearings in a pump system are disclosed herein. Further examples and combinations thereof include the following:

[0094] Example 1 includes a pump system comprising a shaft connected to an impeller of the pump system, and a bearing to provide a dampening to the shaft, the bearing including a journal lining, the journal lining supported in the pump system, a spring-loaded foil to separate the shaft from the journal lining, an inner lining between the shaft and the spring-loaded foil, and a deformation limiter located between the spring-loaded foil and the journal lining.

[0095] Example 2 includes the pump system of any preceding clause, wherein the deformation limiter is coupled to the journal lining.

[0096] Example 3 includes the pump system of any preceding clause, wherein the deformation limiter is manufactured with the journal lining and made of the same material as the journal lining.

[0097] Example 4 includes the pump system of any preceding clause, wherein the deformation limiter is coupled to the spring-loaded foil.

[0098] Example 5 includes the pump system of any preceding clause, wherein the deformation limiter is manufactured with the spring-loaded foil and is made of the same material as the spring-loaded foil.

[0099] Example 6 includes the pump system of any preceding clause, wherein the deformation limiter is to establish a maximum deformation of the spring-loaded foil while the pump system is inoperable.

[0100] Example 7 includes the pump system of any preceding clause, wherein the deformation limiter is to establish a maximum deformation of the spring-loaded foil while the pump system is in operation.

[0101] Example 8 includes the pump system of any preceding clause, wherein the bearing is a radial foil bearing, wherein the deformation limiter is to establish a maximum radial deformation of the radial foil bearing due to a radial load applied by the shaft to the radial foil bearing.

[0102] Example 9 includes the pump system of any preceding clause, wherein the bearing is an axial thrust bearing, wherein the deformation limiter is to establish a maximum axial deformation of the axial thrust bearing due to an axial load applied by the shaft to the axial thrust bearing.

[0103] Example 10 includes the pump system of any preceding clause, wherein a size of the deformation limiter is parametrized based upon a maximum deformation of the spring-loaded foil due to a load from the shaft being applied to the spring-loaded foil.

[0104] Example 11 includes the pump system of any preceding clause, wherein the deformation limiter size is parametrized based upon at least one of a maximum deformation allowable, a

minimum clearance maintainable between the shaft and the journal lining, or a maximum load applied by the shaft.

[0105] Example 12 includes the pump system of any preceding clause, wherein the bearing is at least one of a foil bearing or a thrust bearing.

[0106] Example 13 includes a bearing comprising a housing, a journal lining, the journal lining supported in the housing, a spring-loaded foil to separate a shaft from the journal lining, an inner lining between the spring-loaded foil and the shaft, and a deformation limiter located between the spring-loaded foil and the journal lining.

[0107] Example 14 includes the bearing of any preceding clause, wherein the deformation limiter is coupled to the journal lining.

[0108] Example 15 includes the bearing of any preceding clause, wherein the deformation limiter is manufactured with the journal lining and made of the same material as the journal lining.

[0109] Example 16 includes the bearing of any preceding clause, wherein the deformation limiter is coupled to the spring-loaded foil.

[0110] Example 17 includes the bearing of any preceding clause, wherein the deformation limiter is manufactured with the spring-loaded foil and is made of the same material as the spring-loaded foil.

[0111] Example 18 includes the bearing of any preceding clause, wherein the bearing is used within a pump system.

[0112] Example 19 includes the bearing of any preceding clause, wherein the deformation limiter is to establish a maximum deformation of the spring-loaded foil while the pump system housing the bearing is inoperable.

[0113] Example 20 includes the bearing of any preceding clause, wherein the deformation limiter is to establish a maximum deformation of the spring-loaded foil while the pump system housing the bearing is in operation.

[0114] Example 21 includes the bearing of any preceding clause, wherein the bearing is a radial foil bearing, wherein the deformation limiter is to establish a maximum radial deformation of the radial foil bearing due to a radial load applied by the shaft to the radial foil bearing.

[0115] Example 22 includes the bearing of any preceding clause, wherein the bearing is an axial thrust bearing, wherein the deformation limiter is to establish a maximum axial deformation of the axial thrust bearing due to an axial load applied by the shaft to the axial thrust bearing.

[0116] Example 23 includes the bearing of any preceding clause, wherein a size of the deformation limiter is parametrized based upon a maximum deformation of the spring-loaded foil due to a load from the shaft being applied to the spring-loaded foil.

[0117] Example 24 includes the bearing of any preceding clause, wherein the deformation limiter size is parametrized based upon at least one of a maximum deformation allowable, a minimum clearance maintainable between the shaft and the journal lining, or a maximum load applied by the shaft.

[0118] Example 25 includes the bearing of any preceding clause, wherein the bearing is at least one of a foil bearing or a thrust bearing.

[0119] Example 26 includes a gas turbine engine for an aircraft, the turbine engine comprising a nacelle, a plurality of fan blades inside the nacelle to produce fluid flow, an outer casing aft of the plurality of fan blades, a thermal management system within the outer casing, the thermal management system including a pump system to move fluid through the thermal management system, the pump system including a shaft connected to an impeller of the pump system, and a bearing to provide a dampening to the shaft, the bearing including a journal lining, the journal lining supported in the pump system, a spring-loaded foil to separate the shaft from the journal lining, an inner lining between the shaft and the spring-loaded foil, and a deformation limiter located between the spring-loaded foil and the journal lining.

[0120] Example 27 includes the turbine engine of any preceding clause, wherein the deformation

limiter is coupled to the journal lining.

[0121] Example 28 includes the turbine engine of any preceding clause, wherein the deformation limiter is manufactured with the journal lining and made of the same material as the journal lining.

[0122] Example 29 includes the turbine engine of any preceding clause, wherein the deformation limiter is coupled to the spring-loaded foil.

[0123] Example 30 includes the turbine engine of any preceding clause, wherein the deformation limiter is manufactured with the spring-loaded foil and is made of the same material as the spring-loaded foil.

[0124] Example 31 includes the turbine engine of any preceding clause, wherein the deformation limiter is to establish a maximum deformation of the spring-loaded foil while the pump system is inoperable.

[0125] Example 32 includes the turbine engine of any preceding clause, wherein the deformation limiter is to establish a maximum deformation of the spring-loaded foil while the pump system is in operation.

[0126] Example 33 includes the turbine engine of any preceding clause, wherein the bearing is a radial foil bearing, wherein the deformation limiter is to establish a maximum radial deformation of the radial foil bearing due to a radial load applied by the shaft to the radial foil bearing.

[0127] Example 34 includes the turbine engine of any preceding clause, wherein the bearing is an axial thrust bearing, wherein the deformation limiter is to establish a maximum axial deformation of the axial thrust bearing due to an axial load applied by the shaft to the axial thrust bearing.

[0128] Example 35 includes the turbine engine of any preceding clause, wherein a size of the deformation limiter is parametrized based upon a maximum deformation of the spring-loaded foil due to a load from the shaft being applied to the spring-loaded foil.

[0129] Example 36 includes the turbine engine of any preceding clause, wherein the deformation limiter size is parametrized based upon at least one of a maximum deformation allowable, a minimum clearance maintainable between the shaft and the journal lining, or a maximum load applied by the shaft.

[0130] Example 37 includes the turbine engine of any preceding clause, wherein the bearing is at least one of a foil bearing or a thrust bearing.

[0131] Example 38 includes a bearing comprising means for separating a shaft from the bearing, means for dampening a load applied by the shaft to the bearing, and means for reducing a deformation to the dampening means.

[0132] The following claims are hereby incorporated into this Detailed Description by this reference. Although certain example systems, methods, apparatus, and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all systems, methods, apparatus, and articles of manufacture fairly falling within the scope of the claims of this patent.

Claims

1. A bearing comprising: an outer lining; a spring-loaded lining; an inner lining, the spring-loaded lining between the outer lining and the inner lining; and a fluid pocket, the fluid pocket between the inner lining and a rotor shaft and includes a pressurized fluid to create a barrier between the rotor shaft and the inner lining.

2. The bearing of claim 1, further including a deformation limiter located between the spring-loaded lining and the outer lining.

3. The bearing of claim 2, wherein a size of the deformation limiter is based on a parameterization function, the parameterization function including at least one of a maximum amount of allowable radial deformation, a minimum clearance between the spring-loaded lining and the deformation limiter, or a maximum load applied to the rotor shaft.

- 4.** The bearing of claim 1, wherein the pressurized fluid is compressed air from a pump system of a gas turbine engine.
 - 5.** The bearing of claim 1, wherein the bearing is a thrust bearing, and the fluid pocket is disposed within a thrust bearing assembly of a pump system.
 - 6.** The bearing of claim 5, wherein the fluid pocket is disposed in a longitudinal direction relative to the rotor shaft.
 - 7.** The bearing of claim 1, wherein the bearing is a foil bearing, and the fluid pocket is disposed circumferentially between the rotor shaft and the inner lining.
 - 8.** A pump system comprising: a shaft; and a bearing to dampen the shaft, the bearing including: an outer lining, the outer lining supported in the pump system; a spring-loaded lining to separate the shaft from the outer lining; an inner lining, the spring-loaded lining between the outer lining and the inner lining; and a fluid pocket, the fluid pocket between the inner lining and a rotor shaft and includes a pressurized fluid to create a barrier between the shaft and the inner lining.
 - 9.** The pump system of claim 8, further including a deformation limiter located between the spring-loaded lining and the outer lining.
 - 10.** The pump system of claim 9, wherein a size of the deformation limiter is based on a parameterization function, the parameterization function including at least one of a maximum amount of allowable radial deformation, a minimum clearance between the spring-loaded lining and the deformation limiter, or a maximum load applied to the rotor shaft.
 - 11.** The pump system of claim 8, wherein the pressurized fluid is compressed air from the pump system of a gas turbine engine.
 - 12.** The pump system of claim 8, wherein the bearing is a thrust bearing, and the fluid pocket is disposed within a thrust bearing assembly of the pump system.
 - 13.** The pump system of claim 12, wherein the fluid pocket is disposed in a longitudinal direction relative to the shaft.
 - 14.** The pump system of claim 8, wherein the bearing is a foil bearing, and the fluid pocket is disposed circumferentially between the shaft and the inner lining.
 - 15.** An apparatus for a turbine engine, comprising: means for supporting a shaft of a pump system; means for separating the shaft and the means for supporting the shaft; means for lining an inside of a bearing, the means for separating is between the means for supporting and the means for lining; and means for creating a barrier between the shaft of the pump system and the means for lining the inside of the bearing.
 - 16.** The apparatus of claim 15, further including means for limiting deformation of the means for separating, the means for limiting located between the means for separating and the means for supporting.
 - 17.** The apparatus of claim 16, wherein a size of the means for limiting is based on a parameterization function, the parameterization function including at least one of a maximum amount of allowable radial deformation, a minimum clearance between the means for supporting and the means for limiting, or a maximum load applied to the shaft.
 - 18.** The apparatus of claim 15, wherein the means for creating is compressed air from the pump system of a gas turbine engine.
 - 19.** The apparatus of claim 15, wherein the bearing is a thrust bearing, and the means for creating is disposed within a thrust bearing assembly of the pump system.
 - 20.** The apparatus of claim 19, wherein the means for creating is disposed in a longitudinal direction relative to the shaft.
-