

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250250113

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

LIU; Kai et al.

Transferring robot, warehousing logistics system and item transferring method

Abstract

A transferring robot is disclosed in the disclosure. The transferring robot includes a movable chassis configured to move along a path among adjacent warehouse storage containers; a temporary storage shelf provided on the movable chassis, the temporary storage shelf being configured to store a target case; a fetching assembly provided on the movable chassis, the fetching assembly being configured to extend or retract horizontally relative to the movable chassis, so as to realize fetching and placing of the target case between the storage containers and the temporary storage shelf, where a direction along which the fetching assembly extends or retracts horizontally is perpendicular to a moving direction. A warehousing and logistics system includes the foregoing transferring robot. The disclosure further discloses a warehousing system and an item transferring method.

Inventors: LIU; Kai (Beijing, CN), SUN; Langlang (Beijing, CN), TANG; Yan (Beijing, CN), WANG; Kun (Beijing, CN), XIAO; Yuhui (Beijing, CN), LIU; Xiang (Beijing, CN)

Applicant: BEIJING GEEKPLUS TECHNOLOGY CO., LTD. (Beijing, CN)

Family ID: 71128700

Appl. No.: 19/191619

Filed: April 28, 2025

Foreign Application Priority Data

| | | |
|----|----------------|---------------|
| CN | 201811594425.4 | Dec. 25, 2018 |
| CN | 201811614557.9 | Dec. 27, 2018 |
| CN | 201910087638.6 | Jan. 29, 2019 |

Related U.S. Application Data

Publication Classification

Int. Cl.: **B65G1/137** (20060101); **B65G1/04** (20060101); **B66F9/06** (20060101); **B66F9/075** (20060101); **B66F9/12** (20060101); **B66F9/18** (20060101)

U.S. Cl.:

CPC **B65G1/1373** (20130101); **B65G1/0421** (20130101); **B66F9/063** (20130101); **B66F9/0755** (20130101); **B66F9/122** (20130101); **B66F9/183** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application is a continuation of U.S. patent application Ser. No. 17/357,434, filed on Jun. 24, 2021, which is a continuation-in-part of International Patent Application No. PCT/CN2019/128111, filed on Dec. 25, 2019, which claims priority to Chinese Patent Application No. 201910087638.6, filed on Jan. 29, 2019, Chinese Patent Application No. 201811614557.9, filed on Dec. 27, 2018, and Chinese Patent Application No. 201811594425.4, filed on Dec. 25, 2018. The entire disclosures of the above-identified applications are hereby incorporated herein by reference.

FIELD OF THE TECHNOLOGY

[0002] The present disclosure relates to the technical field of warehousing and logistics, for example, to a transferring robot, a warehousing and logistics system, and an item transferring method.

BACKGROUND OF THE DISCLOSURE

[0003] The rapid development of E-commerce has not only brought unprecedented development opportunities to the warehousing and logistics industry, but also posed severe challenges to warehousing and logistics services. How to carry out package picking in an efficient, low-cost, flexible and accurate way has always been a problem faced by the warehousing and logistics industry. With the continuous development of robotics technology, robots are used to transfer target storage containers, in which goods to be picked up are stored, to worker stations, and then at the worker stations the goods are taken out from the storage containers and put into the order boxes. However, the traditional way of “storage container-to-worker” picking-up requires robots to move the entire storage container to the picking area, which increases the load of the robots and causes a huge waste of resources.

SUMMARY

[0004] The present application provides a transferring robot which can improve space utilization of the warehouse and efficiency in transferring a target case.

[0005] The present application provides a warehousing and logistics system which improves space utilization of the warehouse and logistics efficiency.

[0006] The present application provides another transferring robot, which realizes transferring of cases, simplifies complexity of the structure and operation of the transferring robot, and facilitates ordering and adjusting of the cases by the transferring robot.

[0007] The present application provides another warehousing system which improves the efficiency of goods issuance for the warehousing system and reduces the energy consumption of

the warehousing system.

[0008] The present application provides an item transferring method to resolve the problem in the related art that only cases storing a same type of goods can be transferred at a time and the transferring efficiency is low.

[0009] The present application provides a transferring robot, the transferring robot including:

[0010] a movable chassis configured to move along a path among adjacent warehouse storage containers; [0011] a temporary storage shelf provided on the movable chassis, the temporary storage shelf being configured to store a target case; and [0012] a fetching assembly provided on the movable chassis, the fetching assembly being configured to extend or retract horizontally relative to the movable chassis, so as to realize fetching and placing of the target case between the storage containers and the temporary storage shelf, where a direction along which the fetching assembly extends or retracts horizontally is perpendicular to a direction along which the movable chassis moves.

[0013] The present application provides another transferring robot, the transferring robot including:

[0014] a movable chassis; [0015] a temporary storage shelf vertically provided on the movable chassis, where the temporary storage shelf are provided with a plurality of case storage areas along a vertical direction, and a connecting portion for connecting a target case is provided within each case storage area; and [0016] a fetching assembly configured to grip the target case, where the fetching assembly includes two extending arms, the two extending arms are arranged on two sides of the temporary storage shelf along a width direction of the temporary storage shelf, and the fetching assembly can move up and down vertically relative to the temporary storage shelf and extend and retract horizontally relative to the temporary storage shelf so as to separate the target case from the case storage area or place the target case to the case storage area.

[0017] The present application provides another transferring robot, the transferring robot including:

a movable chassis provided with a robot controller, and a stacking mechanism provided on the movable chassis, where [0018] the stacking mechanism includes a temporary storage shelf and a transmission component, the transmission component is provided on the temporary storage shelf and moves along a vertical direction of the temporary storage shelf under control of the robot controller; [0019] the movable chassis provided with a robot controller is configured to move to a transferring position of at least one target case according to a received item transferring instruction; and [0020] the robot controller is configured to control the transmission component to move up and down along the vertical direction of the temporary storage shelf, fetch the at least one target case, and place the fetched target case onto the temporary storage shelf.

[0021] The present application provides a warehousing system including the transferring robot according to any one of foregoing embodiments, and a warehouse storage container for storing the target case.

[0022] The present application provides an item transferring method executed by a transferring robot, where the transferring robot includes a movable chassis provided with a robot controller, and a stacking mechanism provided on the movable chassis, the stacking mechanism includes a temporary storage shelf and a transmission component, the transmission component is provided on the temporary storage shelf; [0023] the method includes: [0024] receiving an item transferring instruction, wherein the item transferring instruction includes information about a transferring position and a height of at least one target item; and [0025] moving toward the transferring position of the at least one target item, controlling the transmission component to move up and down along a vertical direction of the temporary storage shelf according to the height of the at least one target item, and fetching and placing the at least one target item onto the temporary storage shelf.

[0026] The present application provides an item transferring method including transferring the target case by using the transferring robot according to any one of foregoing embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] FIG. 1 is a schematic structural diagram of a transferring robot provided in Embodiment 1 of the present disclosure;

[0028] FIG. 2 is a schematic structural diagram of a telescoping adjustment assembly in a first direction provided in Embodiment 1 of the present disclosure;

[0029] FIG. 3 is a schematic structural diagram of the telescoping adjustment assembly in a second direction provided in Embodiment 1 of the present disclosure;

[0030] FIG. 4 is a schematic structural diagram of a telescoping transmission assembly provided in Embodiment 1 of the present disclosure;

[0031] FIG. 5 is a schematic diagram of a method for positioning a center of a target case provided in Embodiment 1 of the present disclosure;

[0032] FIG. 6 is a schematic structural diagram of a transferring robot provided in Embodiment 2 of the present disclosure;

[0033] FIG. 7 is a case transferring robot provided by related art;

[0034] FIG. 8 is a schematic structural diagram of a case transferring robot in a state of gripping a target case provided in Embodiment 3 of the present disclosure;

[0035] FIG. 9 is a schematic structural diagram of the transferring robot provided in Embodiment 3 of the present disclosure;

[0036] FIG. 10 is a schematic structural diagram of a three-dimensional intelligent warehouse storage container in the related art;

[0037] FIG. 11 is a schematic structural diagram of a transferring robot provided in Embodiment 4 of the present disclosure;

[0038] FIG. 12 is a schematic structural diagram of another transferring robot provided in Embodiment 4 of the present disclosure;

[0039] FIG. 13 is a schematic flowchart of a method for item transferring provided in Embodiment 5 of the present disclosure; and

[0040] FIG. 14 is a schematic structural diagram of a warehousing system provided in an embodiment of the present disclosure.

[0041] Reference numbers in the drawings: [0042] **10**-transferring robot; **20**-target case; [0043] **1**-movable chassis; **11**-chassis body; **12**-drive wheel; [0044] **2**-temporary storage shelf; **21**-shelf body; **211**-support rod; **212**-support block; **22**-temporary storage plate; **221**-mainbody; **222**-connecting portion; **223**-opening; [0045] **3**-fetching assembly; **30**-warehouse storage container; **31**-extending arm; **32**-lever; **33**-lever transmission shaft; **34**-lever driving assembly;

[0046] **4**-lifting adjustment assembly; **41**-lifting bracket; **42**-lifting transmission assembly; **421**-lifting chain; **422**-lifting sprocket; **43**-lifting driving assembly; [0047] **5**-telescoping adjustment assembly; **51**-connecting plate; **52**-telescoping plate; **53**-first telescoping transmission assembly; **531**-telescoping sprocket; **532**-first telescoping chain; **533**-second telescoping chain; **534**-first transmission belt; **535**-first transmission wheel; **54**-second telescoping transmission assembly; **541**-second transmission belt; **542**-second transmission wheel; **55**-telescoping driving assembly; **56**-telescoping guiding assembly; **561**-first guide groove; **562**-second guide grooves; **563**-first guide rail; **564**-second guide rail; **57**-limit detection switch; [0048] **6**-clamping assembly; **61**-first left sensor; **62**-first right sensor; **63**-second left sensor; **64**-second right sensor; [0049] **8**-connecting portion; **80**-case storage area; **81**-supporting portion; **82**-case portion; **83**-extending portion; [0050] **100**-driving unit; **110**-driving mechanism; **200**-case storage unit; **220**-pallet; **300**-case transport unit; **301**-flange; **302**-supporting member; **303**-item; **304**-identification code; **310**-frame; **320**-lifting device; **330**-telescoping fork; **340**-rotating device; **400**-case; **410**-first adjustment portion; **420**-second adjustment portion; [0051] **2100**-stacking mechanism; **2200**-transmission assembly

DESCRIPTION OF EMBODIMENTS

[0052] The present application will be described below with reference to the drawings and embodiments. It can be understood that the specific embodiments described here are only used to explain the application, but not to limit the application. For description, the drawings only show parts of the structure related to the present disclosure, but not all of the structure.

[0053] In the description of the present application, unless expressly specified and defined, the terms “connected”, “connecting”, and “fixed” shall be understood in a broad sense, for example, there can be a fixed connection, a detachable connection, or an integration; there can be a mechanical connection or an electrical connection; there can be a direct connection or an indirect connection through an intermediate medium; and it can be the internal communication between two elements or the interaction between two elements. For those of ordinary skill in the art, the specific meaning of the above-mentioned terms in the present disclosure can be understood under specific circumstances.

[0054] In the present disclosure, unless expressly specified and defined, a first feature being “on” or “under” a second feature may include direct contact between the first feature and the second feature, or include the first feature and the second feature being not in direct contact but through another feature between them. Moreover, the first feature being “above”, “over” and “on top of” the second feature may include the case that the first feature being right above and obliquely above the second feature, or simply means that the level of the first feature is higher than that of the second feature. The first feature being “below”, “under” and “on bottom of” the second feature includes the case that the first feature being directly below and obliquely below the second feature, or simply means that the level of the first feature is lower than that of the second feature.

[0055] In the description of this embodiment, the terms “upper”, “lower”, “left”, “right” and other orientations or positional relationships are based on the orientations or positional relationships shown in the drawings, and are only for convenience of description and for simplification of operations. It does not indicate or imply that the referenced device or element must have a specific orientation, be constructed and operated in a specific orientation, and therefore cannot be understood as a limitation to the present disclosure. In addition, the terms “first” and “second” are used to distinguish in description.

[0056] Related technologies propose a picking method of “target case-to-person” to solve the waste of resources and energy consumption caused by the traditional picking method of “storage container-to-person”. The picking method of “target case-to-person” is to use a transferring robot to move the target case instead of the storage container to the picking area: after receiving an order instruction, the robot moves to a warehouse path in front of the target case; the robot turns around to face the target case directly, and the telescoping mechanism on the robot extends to take the target case out of the warehouse container and place the case onto a case storage shelf provided on the robot; after completing the gripping of the target case, the robot will turn around again to face the warehouse path directly, so that the robot can move the target case to a designated location along the warehouse path.

[0057] For the transferring robot provided by related technologies, the robot needs to turn around in the warehouse path to realize the fetching and placing of the target case or the travelling of the robot in the warehouse container. The motion of turning around requires a wide warehouse path, which is disadvantageous for the space utilization of the warehouse; and each time the robot has to turn around twice to pick up and place one target case, which is disadvantageous for the efficiency of the transferring robot.

Embodiment 1

[0058] FIG. 1 is a schematic structural diagram of a transferring robot **10** provided by an embodiment of the application. As shown in FIG. 1, this embodiment provides a transferring robot **10** configured to realize the transferring, fetching and placing of a target case **20**. The transferring robot **10** is applicable in warehousing and logistics industry, and performs the fetching, placing and

transporting of the target case **20** in which ordered goods or express parcels are stored, so as to realize the order-based pickup or loading operation. The transferring robot can also be applied to other environments where the target case **20** or goods needs to be transferred. The application of the transferring robot **10** in this embodiment is exemplary.

[0059] In an embodiment, the target case **20** can be replaced with goods or items, which means that the transferring robot **10** performs fetching, placing and transporting of the goods or items. The target case **20** is exemplary.

[0060] In an embodiment, in the warehousing and logistics industry, the transferring robot **10** fetches, loads and transfers the target case **20** in the warehouse container based on orders: when an order management center receives a pick-up order, the order management center analyzes the pick-up order to determine location information of the target case **20** corresponding to the required goods in the pick-up order, and sends the location information to the transferring robot **10**. After receiving the pickup information and the location information, the transferring robot **10** automatically navigates to the location of the corresponding target case **20** in the warehouse container, fetches and places the target case **20** onto the transferring robot **10**, and then the transferring robot **10** transfers the target case **20** to staff processing area for goods picking. When the order management center receives a loading order, the order management center analyzes the loading order and determines location information where the target case **20** corresponding to goods to be loaded according to the loading order should be placed in the warehouse container, and the order management center dispatches the transferring robot **10** to the staff processing area. The staff places the target case **20** to be loaded onto the transferring robot **10**, and at the same time the order management center sends the loading information and the location information to the transferring robot **10**. The transferring robot **10** automatically navigates to a location of the warehouse container for placing the target case **20** according to the location information, and takes the target case **20** to be loaded from the transferring robot **10** and places the target case **20** at the designated position of the warehouse container.

[0061] The transferring robot **10** provided in an embodiment includes: a movable chassis **1**, on which is provided a drive wheel mechanism for driving the movable chassis **1** to move, the movable chassis **1** being configured to realize translation movement and turning movement of the transferring robot **10** on ground; a temporary storage shelf **2** provided on the movable chassis **1**, configured to store the target case **20**; a fetching assembly **3** provided on the movable chassis **1**, configured to realize fetching and placing of the target case **20** between a storage container and the temporary storage shelf **2**; a lifting adjustment assembly **4** provided on the movable chassis **1**, configured to move the fetching assembly **3** vertically so as to realize the fetching and placing of the target case **20** located at different heights of the warehouse container; a telescoping adjustment assembly **5** provided on the lifting adjustment assembly **4** and moving vertically together with the lifting adjustment assembly **4**, the telescoping adjustment assembly **5** being connected with the fetching assembly **3**, and being configured to move the fetching assembly **3** horizontally so as to realize the fetching and placing of the target case **20** between the warehouse container and the temporary storage shelf **2**; a control assembly, configured to control and adjust an operating status of the transferring robot **10**; a detection assembly, configured to detect a working status of the transferring robot **10** and an environment status and assist the control assembly to regulate operation of the transferring robot **10**.

[0062] The movable chassis **1** includes a chassis body **11** and a drive wheel mechanism provided at bottom of the chassis body **11**. In an embodiment, the drive wheel mechanism adopts the form of differential driving, and includes a drive wheel motor, two drive wheels **12** provided at the bottom of the chassis body **11**, and a connecting assembly connecting the drive motor and the two drive wheels **12**, etc. Two drive wheels **12** are respectively provided on two sides of the chassis body **11** along a direction perpendicular to a horizontal retracting direction of the telescoping adjustment assembly **5**, that is, a line connecting centers of the two drive wheels **12** is parallel to the retracting

direction of the telescoping adjustment assembly 5, so that a direction of the translation motion of the transferring robot 10 is perpendicular to the horizontal retracting direction of the fetching assembly 3.

[0063] In this configuration, after the transferring robot 10 travels in the warehouse path to the front of the target case 20, the fetching assembly 3 may extend and retract toward the target case 20 to realize the fetching and placing of the target case 20 between the warehouse container and the temporary storage shelf 2 without the turning-around movement of the transferring robot 10, thereby reducing the movement space required by the transferring robot 10 in the warehouse path, so that the transferring robot 10 is applicable for transferring the target case 20 in a narrow warehouse path, the layout of the warehouse containers in the warehouse is optimized, and the utilization rate of the warehouse is improved; and the transferring robot 10 can move out of the warehouse path by a straight line movement after completing the transfer of the target case 20 between the warehouse container and the temporary storage shelf 2, and transfer the target case 20 to a designated location, simplifying the operation of the transferring robot 10, saving the transportation time of the target case 20, improving the efficiency of the transferring robot 10 to transfer the target case 20, and improving the efficiency of warehousing logistics.

[0064] In an embodiment, the drive wheel mechanism is provided on two sides of the middle of the chassis body 11 and is provided symmetrically with respect to the axis of the chassis body 11, which is beneficial to the movement stability of the movable chassis 1. Each of the two ends of the chassis body 11 along the translational movement is provided with a pair of universal driven wheels, and the two pairs of universal driven wheels are provided symmetrically with respect to the pair of drive wheels 12, which further improves the stable movement of the movable chassis 1, especially the stability in turning movement of the movable chassis 1, and prevents the movable chassis 1 from toppling during the movement.

[0065] In an embodiment, the drive wheel mechanism using differential drive is commonly used in the art and details are not described in this embodiment. In other embodiments, the drive wheel mechanism may also be other mechanisms that can drive the chassis body 11 to move, such as a single drive mechanism, a dual drive mechanism, or a multi-wheel drive mechanism. The embodiments do not limit the specific structure of the drive wheel mechanism. Any drive wheel mechanism, that can drive the movable chassis 1 to move forward, backward, turn, and rotate in place, with the translational movement direction of the movable chassis 1 being perpendicular to the retracting direction of the fetching assembly 3, is applicable.

[0066] In an embodiment, the two sides of the chassis body 11 perpendicular to the horizontal retracting direction of the fetching assembly 3 are flat, which is beneficial to reduce the width of the chassis body 11, thereby reducing the width of the warehouse path required for the travelling of the transferring robot 10 in the warehouse path. The two ends of the chassis body 11 along the direction of movement are in convex arc structures, each of which connects two side planes, which are beneficial to improve the aesthetics of the chassis body 11 and increase the area on the top of the movable chassis 1, and is convenient for the arrangement of the lifting adjustment assembly 4, the temporary storage shelf 2 and the like on the top of the movable chassis 1.

[0067] The lifting adjustment assembly 4 includes a lifting bracket 41, a lifting transmission assembly 42 and a lifting driving assembly 43. The lifting bracket 41 is vertically provided on the top of the chassis body 11, and is connected to the chassis body 11 by welding or detachable connection. The detachable connection is threaded connection or the like, which is beneficial to improve the stability and convenience of the connection. The lifting bracket 41 is a frame structure, and the lifting bracket 41 is provided with lifting transmission assemblies 42 and sliding rails on two sides perpendicular to the horizontal retracting direction of the fetching assembly 3, and on each side, there are two sliding rails provided in parallel and spaced from each other. It is beneficial to improve the steadiness of the lifting of the telescoping adjustment assembly 5.

[0068] The lifting driving assembly 43 is provided at the bottom of the lifting bracket 41, and the

lifting driving assembly **43** can be connected to the lifting bracket **41** or can be connected to the chassis body **11**. In an embodiment, the lifting driving assembly **43** is a motor, and the lifting transmission assembly **42** is a sprocket-chain transmission assembly. The sprocket-chain transmission assembly includes two lifting sprockets **422** provided at the top end of the lifting bracket **41** and two lifting chains **421** sleeved on the two lifting sprockets **422**. The telescoping adjustment assembly **5** is connected to part of the lifting chains **421**, and the telescoping adjustment assembly **5** is provided with sliding blocks cooperating with the two sliding rails. The vertical lifting of the telescoping adjustment assembly **5** is realized through the coordinated transmission of the lifting sprockets **422** and the lifting chains **421** together with the guidance of the sliding rails and sliding blocks.

[0069] In an embodiment, the two lifting transmission assemblies **42** are driven by a same lifting driving assembly **43**, and the two lifting transmission assemblies **42** are connected by a lifting transmission shaft between the two lifting sprockets **422** provided at the top end of the lifting bracket **41**, such that the synchronous movement of the two lifting transmission assemblies **42** is realized. In other embodiments, the two lifting transmission assemblies **42** can be driven by two lifting driving assemblies **43** respectively; or the arrangement of the sprocket-chain transmission assemblies can be in other forms. For example, only the lifting sprocket **422** is provided at the top end of the lifting bracket **41**, the lifting chain **421** sleeves on the lifting sprocket **422**, one end of the lifting chain **421** is connected to the telescoping adjustment assembly **5**, and the other end of the lifting chain **421** is connected to a counterweight element, to realize the lifting of the telescoping adjustment assembly **5** through the transmission of the lifting chain **421**; or the lifting transmission assembly **42** can also be of a gear-rack type, a pulley drive type, a screw-nut type and other transmission modes. The embodiments do not limit the specific structure and form of the lifting transmission assembly **42**, and all the lifting transmission methods capable of realizing lifting movement in the related art can be applied to the lifting transmission assembly **42** in the present disclosure. Since the lifting driving is conventional in the mechanical field, details are not discussed herein.

[0070] The temporary storage shelf **2** includes a shelf body **21** and temporary storage plates **22**. The shelf body **21** is vertically provided on the top of the movable chassis **1** and configured to support and connect the temporary storage plates **22**. A plurality of temporary storage plates **22** are arranged in parallel at intervals along the height direction of the shelf body **21**, and each temporary storage plate **22** can be configured to store the target case **20**.

[0071] In an embodiment, the shelf body **21** includes four vertical support rods **211**. The four support rods **211** are provided in a rectangular distribution, and the four support rods **211** are connected at the bottom by a support block **212**. The support block **212** and the movable chassis **1** are connected by detachable connection such as threaded connection or by integrated connection such as welding. By providing the support block **212**, it is beneficial to improve the stability and reliability of the connection between the shelf body **21** and the movable chassis **1**. In addition, the size of the movable chassis **1** can be reduced while ensuring that the dimension of the shelf body **21** meets the requirement for storing the target case **20**, thereby further reducing the width of the warehouse path required for the transferring robot **10**, and further improving the utilization rate of the warehouse.

[0072] The temporary storage plate **22** is horizontally provided between the four support rods **211**, and four corners of the temporary storage plate **22** are respectively connected with the four support rods **211**. The connection can be welding connection, or can be detachable connection such as screw connection, plug connection, clamping connection and the like. In an embodiment, the temporary storage plate **22** includes a rectangular main body **221**, which is located on an inner side of the lifting bracket **41** in the horizontal retracting direction perpendicular to the fetching assembly **3**, which is beneficial to make the horizontal projection of the temporary storage shelf **2** lie within the projection range of the movable chassis **1** at least in a direction perpendicular to the horizontal

retracting direction, so that in the direction perpendicular to the horizontal retracting direction a maximum width of the transferring robot **10** equals to a maximum width of the movable chassis **1**, and during the movement of the transferring robot **10** in the warehouse path, the temporary storage shelf **2** will not cause collision or interference to the warehouse containers on the two sides of the warehouse path.

[0073] The main body **221** extends outwardly with connecting portions **222** at both ends of the two sides perpendicular to the horizontal retracting direction, and each connecting portion **222** is connected to a corresponding support rod **211**, so that the temporary storage plate **22** has an opening **223** for avoiding the telescoping adjustment assembly **5** on each of the two sides perpendicular to the horizontal retracting direction. When the telescoping adjustment assembly **5** is in a fully retracted state, the vertical lifting of the telescoping adjustment assembly **5** on the lifting bracket **41** may be realized through each opening **223**.

[0074] In an embodiment, five temporary storage plates **22** are provided on the temporary storage shelf **2**, therefore the transferring robot can perform simultaneous transfer of five cases. However, in the present disclosure, the number of temporary storage plates **22** on the temporary storage shelf **2** is not limited, and the number of temporary storage plates **22** on the temporary storage shelf can be set according to requirements.

[0075] In an embodiment, the fetching assembly **3** includes extending arms **31**, levers **32**, and lever driving assemblies **34** (see FIG. 3). Two parallel extending arms **31** are oppositely provided on two sides of the temporary storage shelf **2**, and each extending arm **31** is connected to a telescoping adjustment assembly **5**. The extension direction of the extending arm **31** is the retracting direction of the telescoping adjustment assembly **5**. An inner side of each extending arm **31** is provided with levers **32** and lever driving assemblies **34**, and both ends of each extending arm **31** are each provided with one lever **32**. The lever driving assemblies **34** are connected to the levers **32** and drive the levers **32** to rotate. The rotation direction of the lever **32** is parallel to the length direction of the extending arm **31**.

[0076] In an embodiment, the two levers **32** located on the same extending arm **31** may be driven by the same lever driving assembly **34**, or alternatively each lever is provided with a corresponding driving assembly **34**. The driving assembly **34** is provided on the extending arm **31** and is configured to drive the rotation of the lever **32** connected thereto in a rotatable manner.

[0077] The lever driving assembly **34** includes a drive motor and a lever transmission shaft **33**. An output shaft of the lever drive motor is connected with the lever transmission shaft **33**, both ends of the lever transmission shaft **33** are respectively connected and fixed with the levers **32**, and the two levers **32** located at both ends of the same lever transmission shaft **33** are perpendicular to each other.

[0078] In another embodiment of the disclosure, for the two levers **32** on the same extending arm **31**, the lever **32** connected to an outer side is connected to the extending arm **31** in a rotatable manner, and is driven by the driving assembly **34**; and the lever **32** connected to an inner side is fixedly connected with the extending arm **31** and is maintained in a horizontal state.

[0079] A rotation axis of the lever **32** connected with the extending arm in a rotatable manner is parallel to the length direction of the extending arm (**31**). The width of the lever **32** fixedly connected to the extending arm is not limited, and may be a rail or a baffle, which is not limited in this application.

[0080] In actual application, the extending arm **31** extends outwardly, the lever **32** at the outer side rotates to a horizontal state, and the case is pulled from a storage rack to the temporary storage shelf of the robot; the fixedly connected lever can push the case on the temporary storage shelf of the robot to the storage rack.

[0081] In an embodiment, the drive motor is a steering gear, which can realize precise control of the rotation angle of the lever **32** through the feedback mechanism and angle setting of the steering gear. The steering gear has a small volume, which facilitates the installation and setting of the lever

driving assembly **34**. In other embodiments, the drive motor can also be a servo motor or in other drive forms capable of controlling the rotation angle.

[0082] When the fetching assembly **3** fetches the target case **20** from the warehouse container and places the target case **20** onto the temporary storage plate **22**, the telescoping adjustment assembly **5** drives the two extending arms **31** to extend to the two sides of the target case **20** respectively. After the arms **31** are extended by a preset length, the lever driving assembly **34** drives the levers **32** to rotate, so that the lever **32** at a front end of the extending arm **31** is horizontally arranged and is perpendicular to the extending arm **31**, and the lever **32** at a rear end of the extending arm **31** is vertically arranged. By controlling the telescoping adjustment assembly **5** to drive the extending arms **31** to retract, the levers **32** at the front end of the two extending arms **31** contact a front end of the target case **20** and take the target case **20** to move toward the temporary storage shelf **2**. Since the levers **32** at the rear end of the extending arms **31** are in a vertical state, the passage between the warehouse container and the temporary storage plate **22** is opened, and the target case **20** is placed onto the temporary storage shelf **2** under the action of the levers **32**. When the fetching assembly **3** takes the target case **20** from the temporary storage plate **22** and places the target case **20** into the warehouse container, the lever driving assembly **34** drives the levers **32** to rotate, so that the lever **32** on the rear end of the extending arm **31** is horizontally arranged and is perpendicular to the extending arm **31**, and the lever **32** on the front end of the extending arm **31** is vertically arranged; by controlling the telescoping adjustment assembly **5** to extend, the extending arms **31** are driven to move toward the warehouse container, and the rear ends of the extending arms **31** contact the target case **20** and take the target case **20** to move toward the warehouse container. Since the levers **32** at the front end of the extending arms **31** are in a vertical state, the passage between the temporary storage plate **22** and the warehouse container is opened, and the target case **20** is moved into the warehouse container under the action of the telescoping adjustment assembly **5** and the levers **32**.

[0083] In an embodiment, the movement of the target case **20** is achieved in the way of moving the target case **20** by the levers **32**, which can simplify the structure of the fetching assembly **3**, facilitate the operation of the fetching assembly **3**, lower the requirement on the fetching assembly **3** for locating the target case **20**, and is applicable in fetching and placing target cases **20** of various sizes and shapes. In another embodiment, it is also possible that the fetching assembly **3** only includes extending arms **31**, and the target case **20** is gripped and placed by the extending arms **31** clamping the target case **20**. In another embodiment, other forms and structures of the fetching assembly **3** can be used to achieve the fetching and placing of the target case **20**.

[0084] In an embodiment, the telescoping adjustment assembly **5** is a two-stage telescoping structure, which is beneficial to increase the maximum extending length of the telescoping adjustment assembly **5** while reducing the size of the telescoping adjustment assembly **5** when retracted, thereby reducing the overall size of the transferring robot **10**. FIG. **2** is a schematic structural diagram of the telescoping adjustment assembly provided in an embodiment of the application in a first direction, FIG. **3** is a schematic structural diagram of the telescoping adjustment assembly provided in an embodiment of the application in a second direction, and FIG. **4** is a schematic structural diagram of a telescoping transmission assembly provided in an embodiment of the application. As shown in FIGS. **2-4**, the telescoping adjustment assembly **5** includes a connecting plate **51**, a telescoping plate **52**, a telescoping transmission assembly and a telescoping driving assembly **55**.

[0085] The connecting plate **51**, the telescoping plate **52** and the extending arm **31** are parallel to each other. The connecting plate **51** is provided to realize the connection between the telescoping adjustment assembly **5** and the lifting adjustment assembly **4**. An outer side of the connecting plate **51** is provided with a chain connector and two sliding blocks, the chain connector is connected with the lifting chain **421**, and the two sliding blocks are in sliding connection with the two sliding rails to realize the steady lifting of the connecting plate **51**. The telescoping plate **52** is located on an inner side of the connecting plate **51**, and the telescoping plate **52** is located between the

connecting plate **51** and the extending arm **31** and is connected to both of the connecting plate **51** and the extending arm **31**. The telescoping plate **52** may extend and retract relative to the connecting plate **51**, and the extending arm **31** may extend and retract relative to the telescoping plate **52**.

[0086] In an embodiment, the telescoping transmission assembly adopts two-stage synchronous extension and retraction, that is, when the telescoping plate **52** extends or retracts relative to the connecting plate **51**, the extending arm **31** synchronously extends or retracts relative to the telescoping plate **52**, so that the efficiency of the telescoping adjustment assembly **5** can be improved and the efficiency of the transferring robot **10** to fetch the cases can be improved.

[0087] The telescoping transmission assembly includes a first telescoping transmission assembly **53** provided between the connecting plate **51** and the telescoping plate **52** and a second telescoping transmission assembly **54** provided between the telescoping plate **52** and the extending arm **31**.

[0088] In an embodiment, the first telescoping transmission assembly **53** includes a primary transmission assembly, where the primary transmission assembly includes two telescoping sprockets **531** provided at both ends of the connecting plate **51**, and a first telescoping chain **532** matched with the telescoping sprockets **531** sleeves the two telescoping sprockets **531**. One of the telescoping sprockets **531** is connected with the output shaft of the drive motor in the telescoping driving assembly **55**, and the output shaft of the drive motor drives the telescoping sprocket **531** to rotate, thereby driving the first telescoping chain **532** to rotate. The telescoping plate **52** is located above the first telescoping chain **532**, and the lower lateral side of the telescoping plate **52** is provided with a second telescoping chain **533** that matches with the first telescoping chain **532**. The rotation of the second telescoping chain **532** drives the second telescoping chain **533** to perform translation motion, thereby driving the telescoping plate **52** to extend and retract with respect to the connecting plate **51**.

[0089] In an embodiment, by adopting a chain-sprocket transmission mode, the extending and retraction of the telescoping plate **52** with respect to the front and rear ends of the connecting plate **51** can be realized on the premise of keeping the position of the first telescoping chain **532** unchanged, so that the telescoping adjustment assembly **5** can drive the extending arm **31** to extend to and retract from either side of the temporary storage shelf **2**, and the transferring robot **10** can take the case on either side of the warehouse container without turning and reversing, so as to improve the convenience and flexibility in transferring the target case **20**. In other embodiments, other transmission forms, such as screw-nut transmission, a gear-rack transmission and the like, may be used to drive the telescoping plate **52** to extend and retract with respect to the connecting plate **51**.

[0090] In an embodiment, the first telescoping transmission assembly **53** further includes an auxiliary transmission assembly provided on an upper side of the telescoping adjustment assembly **5**, and the auxiliary transmission assembly includes a first transmission belt **534** and a first transmission wheel **535**. With reference to the left and right directions of the structure shown in FIG. **4**, the auxiliary transmission assembly is described. The left end (right end) of the telescoping plate **52** is provided with a first installation port, and the first installation port travels through two pairs of side surfaces of the telescoping plate **52**. The first transmission wheel **535** is installed in the first installation port and can be connected with the telescoping plate **52** in a rotatable manner, and the axis of the first transmission wheel **535** is vertically arranged. One end of the first transmission belt **534** is fixed to a right end (left end) of the connecting plate **51**, and the other end of the first transmission belt **534** goes around the first transmission wheel **535** and is fixed on a side of the telescoping plate **52** away from the connecting plate **51**. When the movement of the primary transmission assembly drives the telescoping plate **52** to extend and retract relative to the connecting plate **51**, the two ends of the first transmission belt **534** approach or move away from each other due to the rotation of the first transmission wheel **535**, which helps the telescoping plate **52** to extend or retract relative to the connecting plate **51**. By providing the auxiliary transmission

assembly, on one hand, the steady extending and retraction of the telescoping plate **52** relative to the connecting plate **51** can be improved, and it is ensured that the telescoping adjustment assembly bears stable force and travels reliably during the extending and retracting movement. On the other hand, since the two ends of the telescoping plate are respectively fixed to the connecting plate **51** and the telescoping plate **52**, the maximum extension length of the telescoping plate **52** relative to the connecting plate **51** is limited, playing a role of limiting the extension of the telescoping plate **52**.

[0091] The second telescoping transmission assembly **54** includes a second transmission belt **541** and a second transmission wheel **542**. With reference to the left and right directions of the structure shown in FIG. **4**, the second telescoping transmission assembly **54** is described. The right end (left end) of the telescoping plate **52** is provided with a second installation port, and the second installation port travels through two opposite side surfaces of the telescoping plate **52**. The second transmission wheel **542** is installed in the second installation port in a rotatable manner, and the axis of the second transmission wheel **542** is vertically arranged. One end of the second transmission belt **541** is fixed to an end of the extending arm **31** away from the connecting plate **51**, and the other end of the second transmission belt **541** goes around the second transmission wheel **542** and is fixed to the left end (right end) of the connection plate **51**.

[0092] When the telescoping plate **52** retracts relative to the connecting plate **51**, since the second transmission belt **541** goes around the second transmission wheel **542** provided on the telescoping plate **52** and the length of the second transmission belt **541** is constant, while the second transmission wheel **542** moves in translation with the telescoping plate **52**, the second transmission wheel **542** rotates relative to the second transmission belt **541**, which makes the length of the second transmission belt **541** on the side of the telescoping plate **52** facing the connecting plate **51** to increase, and the length of the side of the telescoping plate **52** facing the extending arm **31** to decrease, thereby the extending arm **31** is pulled to retract relative to the telescoping plate **52**. In the same way, when the telescoping plate **52** extends relative to the connecting plate **51**, the second transmission belt **541** and the second transmission wheel **542** drive the extending arm **31** to extend relative to the telescoping plate **52**. Thus, when the telescoping driving assembly **55** drives the first telescoping transmission assembly **53** to extend and retract, the extending arm **31** is synchronously driven to extend and retract with respect to the telescoping plate **52**, that is, the two-stage synchronous telescoping adjustment of the telescoping adjustment assembly **5** is realized.

[0093] In an embodiment, the first transmission belt **534** and the second transmission belt **541** can be belts, synchronous belts, flat belts, or chains. The first transmission wheel **535** and the second transmission wheel **542** are structures that cooperate with the first transmission belt **534** or the second transmission belt **541**.

[0094] In an embodiment, the lengths of the connecting plate **51**, the telescoping plate **52** and the extending arm **31** are basically the same, and the lengths of the first transmission belt **534** and the second transmission belt **541** are basically twice the length of the connecting plate **51**, which is beneficial to increase the extension of the extension arm **31** relative to the telescoping plate **52** and the extension of the telescoping plate **52** relative to the connecting plate **51** as much as possible. In other words, the size of the telescoping adjustment assembly **5** in retracted status is reduced, while the maximum extension length of the telescoping adjustment assembly **5** is increased as much as possible, thereby further reducing the overall size of the transferring robot **10**.

[0095] In an embodiment, in order to improve the steadiness of the extending and retracting movement of the telescoping adjustment assembly **5**, the telescoping adjustment assembly **5** further includes a telescoping guiding assembly **56**. The telescoping guiding assembly **56** includes a first guide groove **561** and a second guide groove **562** respectively provided on an inner side of the connecting plate **51** and an inner side of the telescoping plate **52**, and a first guide rail **563** and a second guide rail **564** respectively provided on an outer side of the telescoping plate **52** and an outer side of the extension arm **31**. The first guide rail **563** is in sliding connection with the first

guide groove **561**, and the second guide rail **564** is in sliding connection with the second guide groove **562**.

[0096] In an embodiment, the telescoping adjustment assembly further includes limit detection switches **57** provided at both ends of the extending arm **31**, which are configured to detect the limit position for the extension or retraction of the extending arm **31**, so as to regulate the operation of the telescoping adjustment assembly **5** and ensure the operational reliability of the telescoping adjustment assembly **5**.

[0097] In an embodiment, the telescoping transmission assembly can also adopt other transmission forms to realize two-stage synchronous extension, such as a gear-rack form. In another embodiment, a telescoping transmission assembly is provided between the telescoping plate **52** and the connecting plate **51** and between the telescoping plate **52** and the extending arm **31** to realize the independent extension and retraction of the telescoping plate **52** and the extending arm **31**.

[0098] In an embodiment, each telescoping adjustment assembly **5** is provided with a telescoping driving assembly **55**, so that the setting of each telescoping driving assembly **55** does not affect the storage of the target case **20** on the temporary storage plate **22**. In other embodiments, it is also possible that two telescoping adjustment assemblies **5** share the same telescoping driving assembly **55** to cooperate with the transmission shaft to realize the synchronous movement of the two telescoping transmission assemblies.

[0099] In an embodiment, the transferring robot **10** is further provided with a control assembly configured to control the operation of multiple actions of the transferring robot **10**. The control assembly includes a controller, an order management module, a navigation module, an information transmission module, an information-processing module, an identification module, a display module, an alarm module, and a power supply module. Each of the drive wheel mechanism, the lifting driving assembly **43**, the telescoping driving assembly, the lever driving assembly **34**, the detection module and the modules in the control assembly is connected to the controller.

[0100] The navigation module is configured to realize the autonomous navigation function of the movable chassis **1**, so that the transferring robot **10** can plan the optimal route according to the position of the target case **20** and automatically navigate to the target case **20** according to the planned optimal route. The movable chassis **1** can be navigated in the mode of two-dimensional code, barcode, and radar simultaneous localization and mapping (SLAM) navigation, or can be guided to the target position by a traditional electric or magnetic guidance.

[0101] The information transmission module includes a wireless communication module for realizing the communication between the transferring robot **10** and the outside, and a wired communication module for realizing the internal communication in the transferring robot **10**. The wireless communication module is configured to perform wireless communication with the order management center in the warehousing and logistics system to receive order information, so as to realize the scheduling of the transferring robot **10** by the order management center. The wired communication module is configured for the internal communication between the controller and the movable chassis **1**, the lifting adjustment assembly **4**, the telescoping adjustment assembly **5** and the fetching assembly **3**, to control the movement of the movable chassis **1** to a specific position, the raising or lowering of the fetching assembly **3** to a specific position, the extending or retracting of the fetching assembly **3**, or a rotation of the lever **32** to a specific angle, so as to achieve the accurate fetching and placement of the target case **20** by the fetching assembly **3**.

[0102] The order management module is configured to receive information sent by the order processing center to the transferring robot **10**, and update completed orders and uncompleted orders in a timely manner according to the transferring actions of the transferring robot **10**, so that the system can monitor the status of the orders in real time. The identification module is configured to identify external information and convert the external information into information that can be processed by the controller, such as identifying the barcode information pasted on the bottom surface to realize the path navigation of the movable chassis **1**, and identifying the tag code pasted

on the target case **20** to obtain information about the goods in the target case **20**, where the tag code may be a two-dimensional code, a barcode, or a radio frequency identification (RFID) code, etc. The power supply module is configured to perform power control for the movable chassis **1**. The power supply module includes a rechargeable battery, a charging port, and a power on/off circuit provided on the movable chassis **1**. The power supply module can be a wired charging module or a wireless charging module. The display module is configured to display an operating status of the transferring robot **10**, for example, to display power status of the transferring robot **10** by setting a status indicator and display order processing status by setting a displayer. The alarm module is configured to alarm abnormal operation status of the transferring robot **10**, to facilitate the staff to find the fault in time. The alarm module can be one of a buzzer, a voice announcer, a light emitting diode (LED) display, etc., or a combination thereof.

[0103] The detection assembly includes an environment monitoring module configured to capture external environment information and an obstacle avoidance sensor configured to detect obstacles. Both the environment monitoring module and obstacle avoidance sensor are connected to the controller and are configured to assist the movable chassis **1** for navigation and obstacle avoidance, so as to achieve the steady traveling of the transferring robot **10**.

[0104] The detection assembly further includes a detection sensor provided on the transferring robot **10** for locating the position of the target case **20**. In an embodiment, the detection sensor is provided on the extending arm **31** of the fetching assembly **3**, and both ends of each extending arm **31** are each provided with a detection sensor.

[0105] When being used to transfer the target case **20**, the transferring robot **10** travels along the warehouse path to the front of the target case **20** according to the order information and the navigation information. However, because of tilted placement of the target case **20** in the warehouse container, the accuracy of the navigation information and the tilt of the warehouse floor, a center of the target case **20** may not be aligned with the center of the fetching assembly **3**. If the fetching assembly **3** fetches the case at this time, the extending arms **31** may touch the front surface of the target case **20** instead of extending to the two sides of the target case **20**. Therefore, after preliminary positioning by navigation, the detection sensor is used to accurately positioning the fetching assembly **3** relative to the center position of the target case **20**.

[0106] FIG. 5 is a schematic diagram of a method for positioning the center of the target case **20** according to an embodiment of the application. For convenient description of the method for positioning the center of the target case **20**, the two detection sensors located on two sides of the front end of the movement direction are respectively named as a first left sensor **61** and a first right sensor **62**, and the two sensors located on two sides of the rear end of the movement direction are respectively named as a second left sensor **63** and a second right sensor **64**. The first left sensor **61** and the second left sensor **63** are located on a same side of the movable chassis **1**, and the first right sensor **62** and the second right sensor **64** are located on a same side of the movable chassis **1**.

[0107] The method for positioning the center of the target case **20** will be described in the example that the target case **20** is on the left side of the transferring robot **10**: [0108] before the transferring robot **10** travels to the front of the target case **20**, the fetching assembly **3** rises to a height of the target case **20** according to the position of the target case **20** in the warehouse container; [0109] when the transferring robot **10** travels in the warehouse path into the range where the target case **20** is located, the first left sensor **61** scans a first edge of the target case **20** and a signal from the first left sensor **61** changes from null to non-null, and a coordinate position X1 of the transferring robot **10** at a moment of signal change is recorded; [0110] the transferring robot **10** continues to move forward, the first left sensor **61** scans across a second edge of the target case **20** and the signal of the first left sensor **61** changes from non-null to null, and a coordinate position X2 of the transferring robot **10** at the moment of signal change is recorded; [0111] a coordinate position of the transferring robot **10** corresponding to the center position of the target case **20** is calculated as $(X2-X1)/2$; and [0112] by calculating the coordinate of the transferring robot **10** corresponding to

the center position of the target case **20**, the transferring robot **10** is moved to the coordinate position $(X2-X1)/2$, so that the center of the fetching assembly **3** can be aligned with the center of the target case **20**. At this time, by extending the extending arms **31**, the two extending arms **31** can be respectively located on two sides of the target case **20**, avoiding collision or interference between the extending arms **31** and the target case **20**, and improving the accuracy of picking up the target case **20** by the fetching assembly **3**.

[0113] In an embodiment of the disclosure, the transferring robot **10** may include a calculation unit and a control unit; the calculation unit records a position $X1$ of the transferring robot **10** once the detection sensor scans an edge of the target case (**20**) for the first time, and records a position $X2$ of the transferring robot **10** once the detection sensor scans an edge of the target case **20** for the second time; and calculates a center position of the target case (**20**) as $(X2-X1)/2$; and the control unit controls the transferring robot **10** to move to the center position $(X2-X1)/2$.

[0114] In an embodiment, the detection sensor is an infrared sensor, and different detection signals are output dependent on whether the light emitted by the target case **20** to the infrared sensor is blocked by the target case **20**.

[0115] In an embodiment, the center position of the target case **20** may be in front of a navigated position. At this time, the transferring robot **10** is driven to continue to move forward to the center position of the target case **20**. The center position of the target case **20** may also be behind the navigated position. At this time, after reaches the navigated position, the transferring robot **10** moves backward to the center position of the target case **20**.

[0116] When the target case **20** is located on the right side of the transferring robot **10**, the method for determining the center of the target case **20** is the same, except for using the first right sensor **62** in detection. When the moving direction of the transferring robot **10** is opposite to the direction shown in the drawing, the second right sensor **64** or the second left sensor **63** is used for position detection. In other words, by providing detection sensors at both ends of each extending arm **31**, it is possible to accurately position the target case **20** regardless of different movement directions and on different sides of the transferring robot **10**, thereby improving the accuracy of the transferring robot **10** or the fetching and placement of the target case **20**.

[0117] In an embodiment, the detection assembly may further include a camera module for identifying position tag code. The warehouse container is provided with position tag codes corresponding to center positions of areas for storing the target cases **20**, and the position tag codes together with the camera module are used by the transferring robot **10** to obtain position coordinates of the target cases **20** in the accurate loading.

[0118] An embodiment further provides a case transferring method used in picking up goods, which includes the following steps: [0119] Step 1: the transferring robot **10** receives order information from an order management center and analyzes location of ordered goods; [0120] Step 2: the transferring robot **10** plans an optimal travel path according to the location of the ordered goods, and automatically navigates along a warehouse path; [0121] Step 3: during the automatic navigation of the transferring robot **10**, a center of a target case **20** is located by using the above-mentioned method for locating the center of the target case **20**; [0122] Step 4: the transferring robot **10** moves to a position $(X2-X1)/2$ corresponding to the center of the target case **20**; [0123] Step 5: the telescoping adjustment assembly **5** controls the extending arms **31** to extend by a preset length; [0124] Step 6: the lever driving assembly **34** drives the lever **32** facing the target case **20** to be placed horizontally; [0125] Step 7: the telescoping adjustment assembly **5** controls the extending arms **31** to retract to an initial state; and [0126] Step 8: the transferring robot **10** moves out of the warehouse path in translation and moves to a target picking position.

[0127] An embodiment further provides a case transferring method used in loading goods, which includes the following steps: [0128] Step 1: after receiving a loading instruction, the transferring robot **10** moves to a loading area, and the target case **20** is placed on the temporary storage shelf **2** of the transferring robot **10** by labors or by mechanical arms; [0129] Step 2: the transferring robot

10 plans an optimal travel path according to a position of the target case **20** in the warehouse container, and automatically navigates along a warehouse path; [0130] Step 3: during the automatic navigation of the transferring robot **10**, a center position of an area for storing the target case **20** in the warehouse container is determined by the camera module and the position tag code on the warehouse container; [0131] Step 4: the transferring robot **10** moves to a position corresponding to the center position of the area for storing the target case **20**; [0132] Step 5: the lever driving assembly **34** drives the lever **32** at an end farther from the warehouse container to be placed horizontally; [0133] Step 6: the telescoping adjustment assembly **5** controls the extending arms **31** to extend by a preset length; and [0134] Step 7: the telescoping adjustment assembly **5** controls the extending arms **31** to retract to an initial state.

[0135] As shown in FIG. **14**, an embodiment further provides a warehousing logistics system, which includes the aforementioned transferring robot **10** and further includes a warehouse storage container for storing the target case **20**.

[0136] In the warehousing system provided according to the present disclosure, by using the above-mentioned transferring robot, the width of the warehouse path required by the transferring robot is reduced, the warehouse layout is optimized, the utilization rate of the warehouse space is improved, and logistics efficiency is enhanced.

Embodiment 2

[0137] FIG. **6** is a schematic structural diagram of a transferring robot **10** provided by an embodiment of this application. As shown in FIG. **6**, an embodiment provides a transferring robot **10** configured to transfer a target case **20**. Compared with the embodiment 1, the transferring robot **10** provided in this embodiment, having the same basic structure as the transferring robot **10** provided in the embodiment 1, includes a movable chassis **1**, a lifting adjustment assembly **4**, a temporary storage shelf **2**, a telescoping adjustment assembly **5**, a fetching assembly **3**, a control assembly and a detection assembly. The movable chassis **1**, the lifting adjustment assembly **4**, the telescoping adjustment assembly **5**, the fetching assembly **3**, the control assembly and the detection assembly have same structure as those in the embodiment 1, except that the temporary storage shelf **2** has a different configuration, and the structure or contents same as the embodiment 1 will not be described in this embodiment.

[0138] As shown in FIG. **6**, the temporary storage shelf **2** of the transferring robot **10** provided in an embodiment only includes one temporary storage plate **22**, which means that the transferring robot **10** provided in this embodiment can only transfer one target case **20** at a time. The temporary storage plate **22** is located at an inner side of the lifting bracket **41**, and the two sides of the temporary storage plate **22** are respectively connected to two connecting plates **51** of the telescoping adjustment assembly **5**, so that the lifting and lowering of the telescoping adjustment assembly **5** drives the temporary storage plate **22** to move.

[0139] The transferring robot **10** provided in an embodiment can only transfer one target case **20** at a time; however, since the temporary storage plate **22** can move up and down synchronously with the telescoping adjustment assembly **5**, pickup or load operation may be performed on target cases **20** located at different heights, which improves the convenience and flexibility of pick-up or loading.

[0140] An embodiment further provides a method for locating a center of the target case **20**, which is the same as the method in the embodiment 1, and will not be repeated in this embodiment.

[0141] An embodiment further provides a case transferring method used in picking up goods, which is the same as the method in the embodiment 1, and will not be repeated in this embodiment.

[0142] An embodiment further provides a case transferring method used in loading goods, which includes the following steps: [0143] S1: after receiving a loading instruction, the transferring robot **10** moves to a loading area, and the target case **20** is placed on the temporary storage shelf **2** of the transferring robot **10** by labors or by mechanical arms; [0144] S2: the lifting adjustment assembly **4** and the telescoping adjustment assembly **5** rise to a height of a warehouse container where the

target case **20** is located; [0145] S3: the transferring robot **10** plans an optimal travel path according to a position of the target case **20** in the warehouse container, and automatically navigates along a warehouse path; [0146] S4: during the automatic navigation of the transferring robot **10**, a center position of an area for storing the target case **20** in the warehouse container is determined by the camera module and the position tag code on the warehouse container; [0147] S5: the transferring robot **10** moves to a position corresponding to the center position of the area for storing the target case **20**; [0148] S6: the lever driving assembly **34** drives the lever **32** at an end farther from the warehouse container to be placed horizontally; [0149] S7: the telescoping adjustment assembly **5** controls the extending arms **31** to extend by a preset length; and [0150] S8: the telescoping adjustment assembly **5** controls the extending arms **31** to retract to an initial state. [0151] An embodiment further provides a warehousing and logistics system, as shown in FIG. **14**, including the above-mentioned transferring robot **10** and a warehouse storage container **30** for storing the target case **20**.

Embodiment 3

[0152] FIG. **7** is a case transferring robot provided by related art. As shown in FIG. **7**, the robot includes a driving unit **100**, a case storage unit **200**, and a case transport unit **300**. The driving unit **100** carries the case storage unit **200** and the case transport unit **300** to move together. The case storage unit **200** includes one or more case storage spaces. The case transport unit **300** is configured to transport the case **400** between the case storage space and the storage container. The case transport unit **300** includes a frame **310** for placing case(s), a lifting device **320** for driving the case(s) **400** to go up and down, a telescoping fork **330** for driving the case(s) **400** to extend and retract, and a rotating device for driving the case(s) **400** to rotate.

[0153] The case transferring robot proposed in the related art can realize transferring of the case(s) **400** other than the storage container, and the robot can transfer multiple kinds of goods at the same time, which improves the transferring efficiency of the transferring robot. However, the case transport unit as in the related art needs the cooperation of the lifting device **320**, the telescoping fork **330** and the rotating device **340** to transport the case from the storage container to the case storage unit **200**. The structure of the case transport unit **300** is complicated; and in the process of fetching and placing the case, the case needs to be placed in the center of the frame **310**, otherwise, after being rotated by the rotating device, the case may be hindered by the guide rail or pallet on the case storage unit and cannot be placed onto the pallet successfully; the operation is complicated and is prone to fail.

[0154] FIG. **8** is a schematic structural diagram of a transferring robot **10** provided in an embodiment of the present disclosure in a state of gripping a target case, and FIG. **9** is a schematic structural diagram of the transferring robot provided in an embodiment of the present disclosure. As shown in FIGS. **8** and **9**, embodiments provide a transferring robot **10** configured to realize the transferring of a target case **20**. The transferring robot **10** is applicable in warehousing and logistics industry, and performs the picking and transporting of the target case **20** in which ordered goods or express parcels are stored. The transferring robot **10** can also be applied to other environments where the case or goods needs to be transferred. The application of the transferring robot **10** in the embodiments is exemplary.

[0155] The transferring robot **10** provided in an embodiment includes: a movable chassis **1** configured to realize movement of the transferring robot **10** on ground and realize transportation of the target case **20** by the transferring robot **10**; a temporary storage shelf (or called a stand) **2** provided on the movable chassis **1**, configured to fix, support and store the target case **20** to be transferred, where a connecting portion **5** for connecting and fixing the target case **20** is provided on the temporary storage shelf **2**; a fetching assembly **3** (configured to clamp the target case **20** and also called clamping assembly) provided on the temporary storage shelf **2**, configured to grip the target case **20**, fetch the target case **20** from the warehouse storage container (i.e., a storage container external to the transferring robot **10**) **30** and place the target case **20** on the temporary

storage shelf **2**, or fetch the target case **20** from the temporary storage shelf **2**, so that the target case **20** is separated from the temporary storage shelf **2**, or adjust position of the target case **20** on the temporary storage shelf **2**; an adjustment mechanism, provided on the temporary storage shelf **2** and connected with the fetching assembly **3**, configured to adjust the position of the fetching assembly **3** relative to the temporary storage shelf **2** and assist the fetching assembly **3** to fetch and place the target case **20** on the temporary storage shelf **2**; a control assembly configured to control an operating status of the transferring robot **10**; a detection assembly configured to detect a working status of the transferring robot **10** and an environment status, and assist the control assembly to perform intelligent control on the transferring robot **10**.

[0156] The movable chassis **1** includes a chassis body **11** and a drive wheel mechanism provided at bottom of the chassis body **11**, and the drive wheel mechanism is configured to realize the movement of the movable chassis **1**. The drive wheel mechanism may adopt a form of differential driving, and includes a drive wheel motor, two drive wheels **12** provided at the bottom of the chassis body **11**, and a connecting assembly connecting the drive wheel motor and the two drive wheels. The two drive wheels **12** are respectively provided on two sides of the chassis body **11**; the drive wheel motor is provided inside the chassis body **11**, and a rotation output shaft of the drive wheel motor is connected with the drive wheels and drives the drive wheels to move, so as to realize the linear or turning movement of the movable chassis **1**.

[0157] In an embodiment, the drive wheel mechanism is provided on two sides of the middle of the movable chassis **1**, which is beneficial to improve the movement steadiness of the movable chassis **1**. The chassis body **11** can be further provided with multiple universal driven wheels. For example, the front and rear of the chassis body **11** can each be provided with a pair of universal driven wheels, and the two pairs of universal driven wheels are provided symmetrically with respect to the pair of drive wheels, which is beneficial to further improve the movement steadiness of the movable chassis **1**, especially the stability in turning movement of the movable chassis **1**, and prevent the movable chassis **1** from toppling during the movement.

[0158] The drive wheel mechanism can also adopt other mechanisms that can drive the chassis body **11** to move. This embodiment does not limit the specific form of the drive wheel mechanism, and does not limit the specific structure of the movable chassis **1**. Any structure capable of driving the temporary storage shelf **2** to move is applicable, such as the robot structure in the related art.

[0159] The temporary storage shelf **2** is provided on a top of the movable chassis **1** and is fixedly connected with the movable chassis **1** so that the movement of the movable chassis **1** drives the temporary storage shelf **2** to move. The temporary storage shelf **2** includes a supporting portion **81** arranged horizontally and a case portion **82** arranged vertically. The supporting portion **81** is connected to an upper end surface of the movable chassis **1**. In an embodiment, the upper end surface of the movable chassis **1** is a flat surface, and the supporting portion **81** has a flat structure, which is beneficial to simplify the connection between the temporary storage shelf **2** and the movable chassis **1**.

[0160] The supporting portion **81** and the movable chassis **1** can be connected in a non-detachable manner. For example, welding is applicable to connect the temporary storage shelf **2** and the chassis body **11** as a whole, which is beneficial to improve the stability of the supporting portion **81** and the chassis body **11**. In an embodiment, the movable chassis **1** and the supporting portion **81** are connected in a detachable connection, such as a screw connection, a magnetic connection, etc., which is beneficial to change different types of the temporary storage shelf **2** according to the number of the target cases **20** to be transferred, so as to improve the design universality and usage flexibility of the transferring robot **10**.

[0161] The case portion **82** is provided with a plurality of case storage areas **80** along the vertical direction, and two adjacent case storage areas **80** are virtually separated, that is, there is no blocking between two adjacent case storage areas **80**. In an embodiment, the case portion **82** includes vertically arranged plate-like structure(s). One side of the plate-like structure is provided

with a connecting portion **8** for connecting the target case **20**. A plurality of connecting portions **8** are arranged at intervals along the vertical direction of the case portion **82**, so that the case portion **82** is virtually divided into a plurality of case storage areas **80**. By providing the virtually separated case storage areas **80**, the movement of the target case **20** among the multiple case storage areas is not obstructed, and the movement of the target case **20** among different case storage areas **80** is facilitated.

[0162] In an embodiment, the case portion **82** may be in a fence-like structure, and the connecting portions **8** are provided on the slats of the fence-like structure. In another embodiment, the case portion **82** may have other forms of structure.

[0163] The fetching assembly **3** is provided on the case portion **82** and is configured to grip the target case **20**. In an embodiment, the fetching assembly **3** includes two extending arms (or called clamping arms) **31**. The two extending arms **31** are provided in parallel on two sides of the case portion **82** along a width direction of the case portion **82**, and the two extending arm **31** are provided along a thickness direction of the case portion **82**.

[0164] In an embodiment, a periphery of an open end of the target case **20** extends outwardly with vertical flanges **301**. When gripping the target case **20**, the two extending arms **31** are respectively located on two sides of the target case **20**, and the extending arms **31** grip the target case **20** through a contact between an upper surface of the arms and a lower surface of the flanges **301**. And when the extending arms **31** are in an initial state, a distance between the two extending arms **31** is greater than a width of the target case **20** and smaller than a maximum width between the flanges **301** on the two opposite sides of the target case **20** to be gripped, so that when the extending arms **31** grip the target case **20**, the distance between the two extending arms **31** does not need to be adjusted, and the two extending arms **31** can directly extend into the two sides of the target case **20**; through the lifting adjustment assembly **4**, the extending arms **31** is raised to contact the flanges **301** of the target case **20** and drive the target case **20** to rise, so that the target case **20** can be gripped. The operation is simple and convenient, the requirement for positioning at the clamping location on the target case **20** by the extending arms **31** is lowered, and the difficulty of adjustment in gripping the target case **20** is reduced.

[0165] By arranging the flanges **301** at the open end of the target case **20**, the interference between the structure of the target case **20** and the warehouse storage container **30** or between the target case **20** and the temporary storage shelf **2** can be reduced, and the strength of the target case **20** can be enhanced. In other embodiments, the flanges **301** may be provided in the middle of the side walls of the target case **20**, or the flanges **301** may be provided only on opposite sides of the target case **20** to be clamped.

[0166] In an embodiment, the extending arm **31** is a rod-shaped structure, which is beneficial to simplify the structure of the extending arm **31**. In other embodiments, the extending arm **31** may be a plate-shaped structure, or may be a structure such as a pneumatic gripper.

[0167] The fetching assembly **3** is connected to the case portion **82** through an adjustment mechanism. The adjustment mechanism includes a lifting adjustment assembly **4**, a telescoping adjustment assembly **5** and a lateral adjustment assembly. The lifting adjustment assembly **4** is provided on the temporary storage shelf **2**, and is configured to go up and down vertically along the temporary storage shelf **2** and to adjust a position of the fetching assembly **3** in the vertical direction; the telescoping adjustment assembly **5** is provided on the lifting adjustment assembly **4**, and is configured to adjust a horizontal distance from the fetching assembly **3** to the case portion **82** by extending or retracting the fetching assembly **3** relative to the case portion **82**; the lateral adjustment assembly is configured to adjust a width between the two extending arms **31** to achieve the opening or closing of the two extending arms **31**.

[0168] In an embodiment, the lifting adjustment assembly **4** is U-shaped, and includes a second adjustment portion **420** constituting a bottom of the U-shape and two first adjustment portions **410** constituting arms of the U-shape. The second adjustment portion **420** is horizontally arranged,

along a width direction of the case portion **82**, on a side of the case portion **82** away from the connecting portion **8**, and the two first adjustment portions **410** are provided on two sides of the case portion **82** in parallel along a thickness direction of the case portion **82**.

[0169] The lifting adjustment assembly **4** further includes a lifting driving assembly. The second adjustment portion **420** is connected to the case portion **82** through the lifting driving assembly, and can move in a vertical direction relative to the case portion **82**. The two first adjustment portions **410** are provided in parallel, and one ends of which are respectively connected, through the lateral adjustment assembly, to the two ends of the second adjustment portion **420** in a width direction of the second adjustment portion **420**. The first adjustment portions **410** can move relative to the second adjustment portion **420** along the width direction of the second adjustment portion **420**, to adjust a distance between the two first adjustment portions **410**. The two extending arms **31** are respectively connected with the first adjustment portions **410** through the telescoping adjustment assembly **5**, so that the extending arms **31** can move along a length direction of the first adjustment portions **410**, thereby realizing the extension or retraction of the extending arms **31**.

[0170] In an embodiment, the lifting driving assembly may include a drive motor and a screw-nut assembly. The screw is rotatable provided in the vertical direction on a side of the case portion **82** away from the target case **20**. The second adjustment portion **420** is provided with a nut seat matched with the screw on one side facing the case portion **82**. The drive motor is fixed on the case portion **82**, and an output shaft is connected with the screw. In this arrangement, the drive motor is provided on the case portion **82**, which is beneficial to reduce the size of the second adjustment portion **420**. The lifting driving assembly may alternatively include a drive motor and a gear-rack assembly, where the rack is vertically provided on the case portion **82**, the gear and the drive motor are provided on the second adjustment portion **420**. The lifting driving assembly may be in other structure for realizing the vertical movement of the second adjustment portion **420** relative to the case portion **82**, such as hydraulic linear drive, motor cooperating with sprocket chain for driving, motor cooperating with belt for driving, or motor drive cooperating with pulley movement. This embodiment does not limit the specific structure of the lifting driving assembly.

[0171] In order to realize the steady lifting of the second adjustment portion **420**, a guiding rail is vertically provided on the case portion **82**, and a sliding block is provided on the second adjustment portion **420**. The sliding block is in sliding connection with the guiding rail, to reduce resistance in the lifting movement of the second adjustment portion **420**, and increase the steadiness of the lifting movement of the second adjustment portion **420**.

[0172] In an embodiment, the extending arms **31** are provided on the inner side of the first adjustment portions **410**, which avoids that the first adjustment portions **410** interferes with the target case **20** when the extending arms **31** transfer the target case **20**.

[0173] In an embodiment, the telescoping adjustment assembly **5** can be in a structure in which a drive motor cooperates with screw-nut, in a structure in which a drive motor cooperates with gear-rack, in a structure in which a drive motor cooperates with chain-sprocket, or in other structures that drives the extending arms **31** to move in translation relative to the first adjustment portion **410**. Moreover, in this embodiment, the structure of the drive motor cooperating with the gear-rack is adopted to realize the extending and retracting of the extending arm **31**, which is beneficial to reduce the size of the telescoping adjustment assembly **5** and simplify the structure of the telescoping adjustment assembly **5**.

[0174] In an embodiment, the rack is provided on an outer side of the extending arm **31** along a length direction of the extending arm **31**, the gear is provided on the first adjustment portion **410** and meshes with the rack for transmission, and the drive motor is provided on an outer side of the first adjustment portion **410** with an output shaft of the drive motor being connected to the gear. In this arrangement, the gear and the drive motor stay still during the extension and retraction of the extending arm **31**, which facilitates the setting of the drive motor, simplifies the structure of the extending arm **31**, and prevents the telescoping adjustment assembly **5** from interfering the

gripping of the target case **20**.

[0175] In an embodiment, the extending arm **31** is in a rod-shaped structure with a rectangular cross section, and its length direction is the same as the length direction of the first adjustment portion **410** and perpendicular to the width direction of the case portion **82**. This arrangement is beneficial to simplify the structure of the extending arm **31**, facilitates the gripping of the target case **20** by the extending arms **31**, and facilitates the arrangement of the rack on the outer side of the extending arm **31**. However, in this embodiment, the structure of the extending arm **31** is not limited.

[0176] In an embodiment, the first adjustment portion **410** is in a rod-shaped structure with an L-shaped cross section. An outer side surface of the extending arm **31** faces an inner side surface of the first adjustment portion **410**. The gear is provided on the inner side surface of the first adjustment portion **410** and meshes with the rack for transmission. The drive motor is provided on the outer side surface of the first adjustment portion **410**, and an output shaft of the drive motor passes through a vertical edge of the L-shaped section to be connected to the gear. A lower side surface of the extending arm **31** is in sliding connection with an upper surface of the horizontal side of the L-shaped rod structure, which improves the support of the first adjustment portion **410** to the extending arm **31** and ensures the stability of the translation movement of the extending arm **31**. The upper surface of the horizontal side can also be provided with a sliding groove, and the lower side surface of the extending arm **31** can be provided with a pulley, so that the pulley is sliding connected in the sliding groove, providing guidance for the movement of the extending arm **31** and improving the steadiness of the movement of the extending arm **31**. In other embodiments, the first adjustment portion **410** may alternatively have a plate-like structure or other structures, and the specific structure of the first adjustment portion **410** is not limited in the embodiments.

[0177] In an embodiment, the extending arm **31** realizes the relative opening or closing of the two extending arms **31** through the lateral adjustment assembly, which is beneficial to simplify the structural complexity of the extending arm **31**, and at the same time simplify the structural complexity of the transferring robot **10** on the side facing the target case **20**, reduces the interference of the structures in the transferring robot **10** on the gripping of the target case **20** as much as possible. In an embodiment, the first adjustment portion **410** has an extending portion **83** extending inwardly in a perpendicular manner from one end of the first adjustment portion **410** close to the case portion **82**. The extending portion **83** is in sliding connection with the second adjustment portion **420**, and the relative linear motion thereof is realized under the driving of the lateral adjustment assembly.

[0178] In an embodiment, the lateral adjustment assembly can be any structure that realizes linear movement between two elements. The lateral adjustment assembly can have the same structure as the lifting adjustment assembly **4** or the telescoping adjustment assembly **5**, or be of a different structure. Since there are many structures capable of realizing the relative linear movement of two structures, which are common in the art, the specific structure of the lateral adjustment assembly is not described in detail in this embodiment.

[0179] In an embodiment, the extending portion **83** is a U-shaped structure with an opening facing the second adjustment portion **420**. One end of the second adjustment portion **420** extends into the U-shaped opening of a corresponding extending portion **83**, and abuts against inner sides of two vertical sides of the U-shaped structure. Sliding blocks are provided on the inner sides of the two vertical sides of the U-shaped structure, and sliding grooves are respectively provided on two corresponding sides of the second adjustment portion **420**. The two sliding blocks of the extending portion **83** are respectively sliding connected in corresponding sliding grooves, which is beneficial to improve the motion stability of the extension portion **83** and the second adjustment portion **420**. In other embodiments, the extending portion **83** may alternatively be a plate-shaped or a bar-shaped structure, and is in sliding connection with the second adjustment portion **420** on only one side.

[0180] In an embodiment, the two vertical sides of the extending portion **83** are respectively

provided on two sides of the second adjustment portion **420** along the thickness direction of the case portion **82**. In other embodiments, the two vertical sides of the extending portion **83** may be respectively provided on upper and lower sides of the second adjustment portion **420**.

[0181] In an embodiment, the second adjustment portion **420** is a long strip structure with an I-shaped cross section, which has a length direction the same as the width direction of the target case **20**. The notches on two sides of the I-shaped structure are the foregoing sliding grooves. This arrangement simplifies the structure of the second adjustment portion **420**, and facilitates the connection between the second adjustment portion **420** and the first adjustment portion **410**. In other embodiments, the second adjustment portion **420** may have other structures, such as structures with U-shaped or L-shaped cross-section.

[0182] Each case storage area **80** is provided with a connecting portion **8** for connecting the target case **20**, and the target case **20** is provided with a matching portion for matching with the connecting portion **8**. In an embodiment, the target case **20** is hooked to the temporary storage shelf **2**, the connecting portion **8** is a hook, and one side of the target case **20** is correspondingly provided with a hook groove for matching with the hook; or the connecting portion **8** is the hook groove provided on the case portion **82**, and a hook matching with the hook groove is correspondingly provided on one side of the target case **20**. This connection has a simple structure and is convenient to set up. During the gripping of the target case **20**, the extending arms **31** are raised or lowered by the lifting mechanism to clamp the target case **20**, so as to disconnect the target case **20** from the hook or connect the target case **20** to the hook; which does not require high positioning accuracy, reduces the requirements for control accuracy during the gripping of the target case **20**, and simplifies the operation and control of the transferring robot **10** for gripping the target case **20**.

[0183] In an embodiment, the target case **20** and the temporary storage shelf **2** can be connected by magnetic attraction. For example, the connecting portion **8** is set as an electromagnet, the matching portion is set with a metal block, and the target cargo is controlled to be connected to or detached from the temporary storage shelf **2** by controlling the on or off of the electromagnet. Alternatively, the connecting portion **8** can be set as a magnetic element such as a magnetic sticker, and a metal block or a magnetic sticker with opposite polarity may be correspondingly provided on one side of the target case **20**.

[0184] In another embodiment, the target case **20** and the temporary storage shelf **2** can be connected in a plug-in form, for example, the connecting portion **8** is set as a connecting pin perpendicular to a surface of the case portion **82**, and a hole for plug-in of the connecting pin is correspondingly provided on one side of the target case **20**; or the connecting portion **8** is set as a hole, and a connecting pin is correspondingly provided on one side of the target case **20**. In order to ensure the connection strength, a plurality of holes or connecting pins may be correspondingly provided along the width direction of the case portion **82**.

[0185] In an embodiment, the hook has an L-shaped structure, one side of which is perpendicular to the surface of the case portion **82**, and the other side is parallel to the surface of the case portion **82**. The hook can have a certain width along the width direction of the case portion **82** to strengthen the hooking strength of the hook to the target case **20**. In other embodiments, a plurality of hooks may be provided at intervals along the width direction of the case portion **82**.

[0186] In an embodiment, the connecting portion **8** can be integrally formed with the case portion **82**, which is beneficial to enhance the structural strength of the connecting portion **8** and improve the supporting of the connecting portion **8** to the target case **20**. In other embodiments, the connecting portion **8** can be connected to the case portion **82** in a detachable manner, which is beneficial for the maintenance or replacement of the connecting portion **8**.

[0187] In an embodiment, the transferring robot **10** is further provided with a control assembly configured to control the operations of the transferring robot **10**. The control assembly includes a controller, an information transmission module, and an information processing module. The movable chassis **1**, the lifting adjustment assembly **4**, the lateral adjustment assembly, the

telescoping adjustment assembly 5, the detection assembly, the information transmission module and the information processing module are all connected to the controller.

[0188] The information transmission module includes a wireless communication module for realizing the communication between the transferring robot **10** and the outside, and a wired communication module for realizing the internal communication in the transferring robot **10**. The wireless communication module is configured to perform wireless communication with the order management center to receive order information: when the order management center receives a pick-up order, the order management center analyzes the pick-up order, determines location of ordered goods, and sends the location information of the ordered goods to the transferring robot **10** through the wireless communication module. After receiving the pick-up information and the location information of the ordered goods, the transferring robot **10** controls the movable chassis **1** to move to a warehouse storage container **30** at the corresponding location, to fetch a target case **20** corresponding to the goods and place the target case **20** onto a case storage area **80** of the temporary storage shelf **2**. After picking up the goods, the transferring robot **10** transfers the target case **20** to staff processing area. When the order management center receives a loading order, the order management center analyzes the loading order and determines location information where the goods to be loaded according to the loading order should be placed. The order management center dispatches the transferring robot **10** to the staff processing area. The staff places the target case **20** to be loaded onto the case storage area **80** of the transferring robot **10**, and the order management center sends the loading information and the location information to the transferring robot **10** via the wireless communication module. The transferring robot **10** controls the movable chassis **1** to move to a warehouse storage container **30** at a location corresponding to the location information, and grips the target case **20** to be loaded from the case storage area **80** and places the target case **20** at a designated position of the warehouse storage container **30**.

[0189] The wired communication module is configured to realize communication between the controller and the movable chassis **1**, the lifting adjustment assembly **4**, the telescoping adjustment assembly **5**, and the lateral adjustment assembly, to control the movement of the movable chassis **1** to a specific position, the raising or lowering of the extending arms **3** to a specific position, the opening or closing of the extending arms, and/or extending or retracting of the extending arms **3**, so as to achieve the accurate gripping and placing of the target case **20** by the extending arms. The controller controls the gripping action toward the target case **20** in the following aspects: [0190] (1) Controlling the extending arms **31** to grip the target case **20** from the warehouse storage container **30** to the case storage area **80** of the transferring robot **10**, including the following steps.

[0191] **S101**: The controller controls the lifting adjustment assembly **4** to move, so as to raise the extending arms **31** to a specific position. The specific position corresponds to a position of the target case **20** on the warehouse storage container **30**. The specific position can be preset by the controller according to a corresponding layer number on which the target case **20** is located on the warehouse storage container **30**, namely, each layer corresponds to a height value.

[0192] **S102**: The controller controls the telescoping adjustment assembly **5** to move, so as to extend the extending arms **31** by a preset length, so that the two extending arms **31** are respectively located on two sides of the target case **20** to be gripped. Since the warehouse storage container **30** and the target case **20** are arranged relatively neatly, the movement and posture of the transferring robot **10** can be preset to ensure that the transferring robot **10** is set with respect to the target case **20** in such a way that the extending arms **31** are located at the two sides of the target case **20** after the extending arms **31** being extended. It is also possible to set up an image acquisition module, such as a Charge Coupled Device (CCD) camera or the like, to collect image location information of the target case **20** and the warehouse storage container **30**. The image acquisition module is connected through the controller, so that the controller can adjust the posture of the transferring robot **10** according to the image information collected by the image acquisition module to ensure that the extended arms **31** are located on two sides of the target case **20** after the extended arms **31**

being extended.

[0193] **S103:** The controller controls the lifting adjustment assembly **4** to move, so that the extending arms **31** contact the flanges **301** of the target case **20** and raise the corresponding target case **20**, so that the target case **20** is out of contact with the warehouse storage container **30**.

[0194] **S104:** The controller controls the movable chassis **1** to move, so that the movable chassis **1** moves in a direction away from the warehouse storage container **30** and the target case **20** is out of the range of the warehouse storage container **30**.

[0195] **S105:** The controller controls the lifting adjustment assembly **4** to move, so that the target case **20** moves to a preset height. The preset height is specifically set according to a layer number where the target case **20** is located on the warehouse storage container **30** and a layer number where the target case **20** needs to be placed in the case storage area **80**.

[0196] **S106:** The controller controls the telescoping adjustment assembly **5** to move, so as to retract the extending arms **31** to an initial position.

[0197] **S107:** The controller controls the lifting adjustment assembly **4** to move so that the extending arms **31** drive the target case **20** to go down until the hook groove of the target case **20** is hooked with the hook.

[0198] **S108:** The controller controls the lifting adjustment assembly **4** to continue moving, so that the extending arms **31** go down and separate from the target case **20**. [0199] (2) Controlling the extending arms **31** to grip the target case **20** from the case storage area of the transferring robot **10** to the warehouse storage container **30** of the warehouse, including the following steps.

[0200] **S201:** The controller controls the lifting adjustment assembly **4** move, so as to raise the extending arms **31** to contact with the flanges **301** on the target case **20**, and raise the target case **20** so that the target case **20** is out of contact with the hook.

[0201] **S202:** The controller controls the telescoping adjustment assembly **5** to move so that the extending arms **31** extend by a preset length.

[0202] **S203:** The controller controls the lifting adjustment assembly **4** to move, so that the extending arms **31** move to a corresponding height of the warehouse storage container **30** where the target case **20** needs to be placed.

[0203] **S204:** The controller controls the movable chassis **1** to move in such a way that the movable chassis **1** moves toward the warehouse storage container **30**, so that the target case **20** extends into a range of the warehouse storage container **30** for placing the target case **20**.

[0204] **S205:** The controller controls the lifting adjustment assembly **4** to move so that the extending arms **31** drive the target case **20** to go down, and after the target case **20** contacts the warehouse storage container **30**, the extending arms **31** continue to move until the extending arms **31** separate from the target case **20**.

[0205] **S206:** The controller controls the telescoping adjustment assembly **5** to move, so as to retract the extending arms **31** to the initial position. [0206] (3) Controlling the extending arms **31** to adjust the position of the target case **20** of the transferring robot **10** among the case storage areas **80** without crossing over the target case **20**, including the following steps.

[0207] **S301:** The controller controls the lateral adjustment assembly to move so that the two extending arms **31** are opened with respect to each other until a distance between the two extending arms **31** is greater than a maximum width of the target case **20**.

[0208] **S302:** The controller controls the lifting adjustment assembly **4** to move, so that the extending arms **31** move to a height where the target case **20** to be adjusted is located.

[0209] **S303:** The controller controls the lateral adjustment assembly to move, as that the two extending arms **31** are closed to an initial position.

[0210] **S304:** The controller controls the lifting adjustment assembly **4** to move, so that the extending arms **31** go up and contact the flanges **301** on the target case **20** and drive the target case **20** to rise out of contact with the hook.

[0211] **S305:** The controller controls the telescoping adjustment assembly **5** to move so that the

extending arms **31** extend to a distance out from interference with the hook.

[0212] **S306**: The controller controls the lifting adjustment assembly **4** to move so that the extending arms **31** drive the target case **20** to move to a height of a target position.

[0213] **S307**: The controller controls the telescoping adjustment assembly **5** to move, so as to retract the extending arms **31** to the initial position.

[0214] **S308**: The controller controls the lifting adjustment assembly **4** to move, so that the extending arms **31** drive the target case **20** to go down and is hooked up, and thereafter the extending arms **31** continue to go down until the extending arms **31** separate from the target case **20**. [0215] (4) Controlling the extending arm **31** to adjust the position of the target case **20** of the transferring robot **10** among the case storage areas **80** on basis of crossing over the target case **20**, including the following steps.

[0216] **S401**: The controller controls the lateral adjustment assembly to move so that the two extending arms **31** are relatively opened until a distance between the two extending arms **31** is greater than a maximum width of the target case **20**.

[0217] **S402**: The controller controls the lifting adjustment assembly **4** to move, so that the extending arms **31** move to a height where the target case **20** to be adjusted is located.

[0218] **S403**: The controller controls the lateral adjustment assembly to move, so as to close the two extending arms **31** to an initial position.

[0219] **S404**: The controller controls the lifting adjustment assembly **4** to move, so that the extending arms **31** go up and contact with the flanges **301** on the target case **20**, and drive the target case **20** to rise out of contact with the hook.

[0220] **S405**: The controller controls the telescoping adjustment assembly **5** to move, so that the extending arms **31** extend to a distance out from interference with other target cases **20**.

[0221] **S406**: The controller controls the lifting adjustment assembly **4** to move, so that the extending arms **31** drive the target case **20** to move to a height of a target position.

[0222] **S407**: The controller controls the telescoping adjustment assembly **5** to move, so as to retract the extending arms **31** to the initial position.

[0223] **S408**: The controller controls the lifting adjustment assembly **4** to move so that the extending arms **31** drive the target case **20** to go down and is hooked up, and thereafter the extending arms **31** continue to go down until the extending arms **31** separate from the target case **20**.

[0224] Based on the above analysis, the transferring robot **10** can realize the gripping and placing of the target case **20** between the warehouse storage container **30** and the case storage area **80** of the transferring robot **10**, thereby realizing the pickup and loading functions of the transferring robot **10**. The transferring robot **10** can also realize the adjustment of the target case **20** among the case storage areas **80** on different layers of the transferring robot **10**, so as to organize the ordered goods better and facilitate the pick-up or load operation of the staff.

[0225] In the pickup or load operation, the order may involve many kinds of goods which are placed in different warehouse storage containers **30**. In order to improve the pickup efficiency of the transferring robot **10**, the transferring robot **10** obtain all the target cases **20** involved in the order or at least have all the case storage areas being filled with target cases **20** before move to the staff processing area for subsequent processing.

[0226] In an embodiment, the transferring robot **10** further includes an intelligent navigation system, which is connected to the controller. After the controller receives order information and location information corresponding to all ordered goods, the controller transmits the location information of the goods to the intelligent navigation system. The intelligent navigation system autonomously plans an optimal route to each of the location information. Alternatively, the order management center can generate the optimal route for the transferring robot **10** according to the order information, and transmit the optimal route to the intelligent navigation system of the transferring robot **10** through the wireless communication module, so that the transferring robot **10**

will arrive at the locations corresponding to the goods in turn according to the optimal route.

[0227] For better operation of the transferring robot **10**, the transferring robot **10** is further provided with a detection assembly. The detection assembly includes an obstacle avoidance sensor for detecting road obstacles, so that the transferring robot **10** can avoid road obstacles and travel well during operation.

[0228] The detection sensor further includes a case detection device for detecting whether there are goods stored in the case storage areas **80** on each layer. The case detection device is proximity switch, pressure sensor or the like designed to detect whether the target case **20** is connected to the case storage area, so as to determine whether the transferring robot **10** is in a fully loaded state, which facilitates the transferring robot **10** in a fully loaded state move to the staff processing area in time to process orders in batches when the number of orders is greater than the number of layers of the case storage areas **80**. The case detection device can alternatively be a code scanner installed in the case storage area. By scanning the two-dimensional code or barcode on the target case **20**, it is determined whether there is a target case **20** in the case storage area **80**, and the information of the goods in the target case **20** on the corresponding layer is obtained, which is helpful for the controller or the order management center to timely know which ordered goods have been transferred by the transferring robot **10**.

[0229] In an embodiment, a displayer may be provided on the transferring robot **10** to display order information received by the transferring robot **10** and the information of the target case **20** that has been transferred on the transferring robot **10**; and at the same time, the displayer may display information of the target case **20** corresponding to each layer of the case storage area **80**. This is beneficial for the quick picking of the goods by the staff in the staff processing area, as well as the checking and ordering of the ordered goods.

[0230] The transferring robot **10** provided in an embodiment can not only deploy intelligent warehousing robots to pick-up and load goods according to orders, but also have functions such as inbound business, outbound business, warehouse allocation, inventory allocation, and virtual warehouse management, so as to realize comprehensive application of batch management, material correspondence, inventory counting, quality inspection management, virtual warehouse management, real-time inventory management and other functions.

[0231] An embodiment further provides a warehousing system, as shown in FIG. **14**, which includes the aforementioned transferring robot **10** and a warehouse storage container **30** storing the target case **20**.

[0232] The transferring robot provided by the present disclosure can grip the target case by setting the extending arms, so that the extending arms can easily extend to the warehouse storage container for clamping the target case, and the extending arms can also retract to the case storage area, so that the case can be separated from or placed in the case storage area, the operation is simple and convenient, and the structure of the clamping assembly is simplified, thereby simplifying the structure of the transferring robot; and in the process of clamping or fetching-placing, the case is confined between the two extending arms, therefore it is easy to realize the positioning of the target case relative to the case storage area, which improves the efficiency of the transferring robot to fetch and place the case.

[0233] The warehousing system provided in the present disclosure has improved efficiency by adopting the above-mentioned transferring robot.

Embodiment 4

[0234] Three-dimensional intelligent warehouse is a warehousing structure with multiple columns, multiple layers, multiple cells, and multiple storage units, which is established to improve the storage capacity of the warehouse. In order to save space, products with outer packaging are usually stacked in three-dimensional intelligent warehouse. In the stacking process, stacking equipment is usually used to perform transferring and stacking operations between the storage containers in the warehouse. However, the stacking equipment in the related art can usually transfer

only one type of case of goods at a time, and the stacking equipment waits for too long when transferring the cases with low efficiency. FIG. 10 shows a schematic structural diagram of a three-dimensional intelligent warehouse storage container. As shown in FIG. 10, the warehouse storage container 30 stores items 303. Of course, the items 303 can be stored in case(s), which is (are) placed on the warehouse storage container 30. In an embodiment, the warehouse storage container 30 includes a plurality of compartments stacked along a vertical direction, and each compartment can accommodate a plurality of items 303. The bottom of the warehouse storage container 30 may include one or more supporting members 302 and an identification code 304 such as a two-dimensional code. During the stacking process, the robot 10 carries out goods transferring and stacking among multiple warehouse storage containers 30 for warehousing. How to efficiently transfer and stack items is one of the key issues to improve the efficiency of warehousing in E-commerce and other fields. Therefore, the present disclosure provides a transferring robot to improve the efficiency of item transferring and stacking in a three-dimensional warehouse.

[0235] FIG. 11 is a schematic structural diagram of a transferring robot 10 provided in an embodiment. The transferring robot 10 includes a movable chassis (also referred to as a robot body) 1 provided with a robot controller, and a stacking mechanism 2100 provided on the movable chassis 1. The movable chassis 1 includes a driving mechanism 110 through which the movable chassis 1 can move within a three-dimensional warehouse. The stacking mechanism 2100 includes a temporary storage shelf 2 and a transmission component 2200. The transmission component 2200 is provided on the temporary storage shelf 2 and moves along a vertical direction of the temporary storage shelf 2 under the control of the robot controller.

[0236] In an embodiment, the robot controller 1 is configured to move to a transferring position of at least one target item (for example, the target case 20) according to a received item transferring instruction, where the item transferring instruction includes a travel route of the transferring robot 10, type information of the target item to be transferred, position information of the target item, and a preset transferring position. The at least one target item could be of a same type or of different types. At the same time, the robot controller is configured to control the transmission component 2200 to move up and down in the vertical direction of the temporary storage shelf 2, so as to fetch at least one target item at the transferring position and place the at least one target item onto the temporary storage shelf 2, whereby many different types of items may be fetched in one transferring task, then the fetched items are transported to a designated place for stacking, and the whole process does not require human intervention.

[0237] Based on the foregoing description, in an embodiment, as shown in FIG. 12, a structure of a transferring robot is shown, including: a movable chassis 1 and a stacking mechanism 2100 (the structure represented by the large circle 2100 in FIG. 12), where the temporary storage shelf 2 in the stacking mechanism 2100 includes a case storage areas 80, and the transmission component includes a lifting adjustment assembly 4, a telescoping adjustment assembly 5, and a fetching assembly 3. The fetching assembly 3 includes extending arms 31 and clamping assemblies 6.

[0238] The robot controller is further configured to: before fetching at least one target item, adjust a height of the transmission component to be matched with a height of the target item, thereby ensuring that the target item can be fetched directly when the movable chassis 1 moves to the transferring position, improving the item fetching efficiency and the item transferring efficiency in turn.

[0239] In an embodiment, at least two layers of temporary storage plates 22 are provided on the case storage area (also referred to as a storage container of a robot) 80, and the temporary storage plates 22 are configured to carry items (for example, the target case 20). The number of the temporary storage plates 22 can be determined according to actual requirements, and the temporary storage plates 22 can be provided on the temporary storage shelf 2 at an equal interval. Based on the size of the temporary storage plate 22, each temporary storage plate 22 can accommodate multiple items. In an embodiment, since the temporary storage shelf 2 has a plurality of temporary

storage plates **22**, it is possible to place one type of item on one temporary storage plate **22**, which can further ensure that the robot can transfer multiple different types of items at the same time for one transferring task.

[0240] In an embodiment, the lifting adjustment assembly **4** is provided on the temporary storage shelf **2**, and the lifting adjustment assembly **4** moves along the vertical direction of the temporary storage shelf **2** under the control of the robot controller **1**; the telescoping adjustment assembly **5** is fixed on the lifting adjustment assembly **4**. The lifting adjustment assembly **4** is configured to drive the telescoping adjustment assembly **5** to go up and down according to the height of the target item. In other words, the lifting adjustment assembly **4** lifts or lowers the telescoping adjustment assembly **5** to the same height as the target item.

[0241] In an embodiment, the telescoping adjustment assembly **5** is connected to the fetching assembly **3**. The fetching assembly **3** includes extending arms **31** and clamping assemblies **6**, and the clamping assembly **6** is provided on an inner side of the extending arm **31**; the extending arms **31** are configured to extend the clamping assemblies **6** to two sides of the target item under the control of the robot controller after the telescoping adjustment assembly **5** moves to the same height as the target item; the clamping assemblies **6** are configured to grip the target item at the corresponding height after the extending arms **31** extend to the two sides of the target item. During operation, a telescoping cylinder or other similar mechanism in the telescoping adjustment assembly **5** drives the extending arms **31** to extend, and then the clamping assemblies **6** extend to fetch the target item.

[0242] After the clamping assemblies **6** grip the target item, under the control of the robot controller, the telescoping adjustment assembly **5** further retracts the extending arms **31** to a preset position through the telescoping cylinder or other similar mechanism, so as to place the gripped target item on the temporary storage plate **22**. Before fetching the target item, the item transferring instruction received by the robot controller includes indication for placing the target item on a designated layer of temporary storage plate **22**. Exemplarily, as shown in FIG. **12**, when the target item needs to be placed on the third-layer of temporary storage plate **22** according to the item transferring instruction, after fetching the target item, if the telescoping adjustment assembly **5** is just at a height of the third layer of temporary storage plate **22**, the target item is directly placed on the third-layer of temporary storage plate **22** through the telescoping adjustment assembly **5** and the fetching assembly **3**; if the height of the telescoping adjustment assembly **5** is lower or higher than the third-layer of temporary storage plate, the height of the telescoping adjustment assembly **5** is adjusted by the lifting adjustment assembly **4** and then the target item is placed on the third-layer of temporary storage plate **22** through the fetching assembly **3**.

[0243] This application provides a transferring robot, including a robot body (i.e., a movable chassis provided with a robot controller), and a stacking mechanism provided on the robot body. The stacking mechanism includes a temporary storage shelf and a transmission component, and the transmission component is provided on the temporary storage shelf in a height-adjustable manner. When carrying out the task of item transferring, before moving to the transferring position of the target item, the transmission component is adjusted to the height of the target item, which can ensure that the target item is directly fetched when the robot body moves to the transferring position, so as to improve efficiency of item fetching. In addition, the storage container includes multiple pates, which ensures that multiple different types of items can be fetched for one item transferring task. When performing the item fetching task, the robot body controls the transmission component to move up and down in the vertical direction of the temporary storage shelf, fetches at least two target items at different heights after reaching the transferring position, and places the at least two target items onto the temporary storage shelf, whereby multiple types of items can be fetched in one item fetching task and the efficiency of item fetching is improved.

[0244] In an embodiment, as shown in FIG. **14**, an embodiment of the present disclosure further provides a warehousing system, including the aforementioned transferring robot **10** and a

warehouse storage container **30** for storing the target case **20**.

Embodiment 5

[0245] FIG. **13** is a schematic flow chart of an item transferring method provided in Embodiment 5 of the present disclosure, which is applicable for transferring and stacking items in a warehouse. The method is executed by a transferring robot. The transferring robot includes a movable chassis provided with a robot controller, and a stacking mechanism provided on the movable chassis; the stacking mechanism includes a temporary storage shelf and a transmission component, and the transmission component is provided on the temporary storage shelf. As shown in FIG. **4**, the item transferring method includes the following steps.

[0246] **S210**. An item transferring instruction is received, where the item transferring instruction includes indication of a transferring position and a height of at least one target item.

[0247] When transferring and stacking items, the transferring robot receives and executes the item transferring instructions sent by the control center to complete the task of transferring and stacking items. The item transferring instruction includes information about a travel route of the transferring robot, and a transferring position and height of at least one target item. The at least one target item may be of the same type or be of different types. The transferring position refers to a position that is directly in front of the target item and is within a preset distance from the target item.

[0248] **S220**: The transferring robot moves to the transferring position of at least one target item, controls the transmission component to move up and down in the vertical direction of the temporary storage shelf according to the height of the at least one target item, and fetches at least one target item to place onto the temporary storage shelf.

[0249] In an embodiment, when the transferring robot receives and executes the item transferring instructions sent by the control center, before arriving the transferring position of the at least one target item, namely, during the movement of the robot, the transmission component is controlled to move up and down along the vertical direction of the temporary storage shelf according to the height of the at least one target item, i.e., to adjust a height of the transmission component to be equal to the height of the target item, so that when the robot moves to the item transferring position, the transmission component directly fetches the target item at the corresponding height and places the target item on the temporary storage shelf.

[0250] In an embodiment, after fetching all the target items in the transferring task, the transferring robot transfers the target items to a designated position for stacking. Exemplary, the items can be stacked in sequence according to the types of the items. In an embodiment, after reaching the designated position, the lifting adjustment assembly drives the telescoping adjustment assembly to move up or down, so that the telescoping adjustment assembly drives the fetching assembly to unload the items from different temporary storage plates for stacking, thereby realizing stacking of items of the same type to improve stacking efficiency.

[0251] In the embodiments of the present disclosure, the transferring robot receives and executes the item transferring instructions, moves toward the transferring position of at least one target item, and controls the transmission component to go up and down in the vertical direction of the temporary storage shelf according to the height of the at least one target item during the movement. Once arriving at the transferring position, the target item is directly fetched and placed on the temporary storage shelf, so that multiple different types of target items can be transferred at a time in one transferring task. In addition, the transmission component is controlled to act during the movement, and the item is directly fetched at the transferring position, which reduces the time that the robot waits for the transmission component to act, and improves the efficiency of item fetching.

Claims

1. A transferring robot comprising: a movable chassis configured to move along a path among adjacent warehouse storage containers; a lifting adjustment assembly provided on the movable

chassis; a case transport unit connected to the lifting adjustment assembly, the case transport unit comprising a telescoping adjustment assembly and a fetching assembly, the telescoping adjustment assembly being connected to the fetching assembly, the telescoping adjustment assembly being configured to drive the fetching assembly to extend or retract horizontally, and the lifting adjustment assembly being configured to drive the case transport unit move up or down vertically; and the fetching assembly configured to extend or retract horizontally relative to the movable chassis, so as to realize fetching and placing of a target case in a warehouse storage container.

2. The transferring robot according to claim 1, wherein the fetching assembly comprises: two extending arms, each extending arm being connected with one telescoping adjustment assembly, limit detection switches being provided at both ends of each extending arm and configured to detect a limit position for extension or retraction of each extending arm.
3. The transferring robot according to claim 2, wherein the fetching assembly further comprises: levers, wherein two ends of each extending arm are connected to the levers, and a rotation axis of a lever at a front end of each extending arm is parallel to a length direction of each extending arm; and lever driving assemblies provided on the two extending arms for driving the lever at the front end of each extending arm to rotate.
4. The transferring robot according to claim 3, wherein each lever driving assembly is connected to a lever transmission shaft, and the lever transmission shaft is connected to the lever.
5. The transferring robot according to claim 4, wherein a direction along which the fetching assembly extends or retracts horizontally is perpendicular to a direction along which the movable chassis moves, wherein when the fetching assembly fetches the target case from the warehouse storage container, the two extending arms extend to two sides of the target case respectively, and after the two extending arms are extended by a preset length, the lever at the front end of each extending arm is rotated to be horizontally arranged and to be perpendicular to each extending arm, when the fetching assembly places the target case into the warehouse storage container, the lever at the front end of each extending arm is rotated to be vertically arranged.
6. The transferring robot according to claim 2, wherein at least one of two ends of each extending arm are provided with detection sensors for detecting the target case.
7. The transferring robot according to claim 6, wherein the detection sensors are further configured for scanning the target case in turn during movement of the transferring robot along the path; the transferring robot further comprises a calculation unit and a control unit; the calculation unit is configured to calculate a center position of the target case; and the control unit is configured to control the transferring robot to move to the center position.
8. The transferring robot according to claim 2, wherein the telescoping adjustment assembly comprises: connecting plates connected with the case transport unit; and telescoping plates configured to extend or retract along the connecting plates, wherein the two extending arms are configured to extend or retract along the telescoping plates.
9. The transferring robot according to claim 8, wherein extending or retracting of the telescoping plates relative to the connecting plates is synchronized with extending or retracting of the two extending arms relative to the connecting plates.
10. The transferring robot according to claim 1, wherein the lifting adjustment assembly comprises: a lifting transmission assembly and a lifting driving assembly, the lifting transmission assembly is provided with two lifting sprockets and a lifting chain sleeved on each lifting sprocket, and an end of the lifting chain is connected to a counterweight element; and the lifting driving assembly is configured to drive the lifting transmission assembly to rotate in cooperation with the counterweight element, so as to control the lifting transmission assembly to move up and down.
11. A transferring robot comprising: a movable chassis provided with a robot controller and a drive wheel mechanism for driving the movable chassis to move; a lifting adjustment assembly provided on the movable chassis, the lifting adjustment assembly comprising a lifting bracket; one or more temporary storage plates connected to the lifting bracket, the one or more temporary storage plates

being configured to carry at least one target case; and a case transport unit connected to the lifting adjustment assembly, the case transport unit comprising a telescoping adjustment assembly and a fetching assembly, the telescoping adjustment assembly being connected to the fetching assembly, the telescoping adjustment assembly being configured to drive the fetching assembly to extend or retract horizontally; wherein the movable chassis provided with the robot controller is configured to move to a transferring position of the at least one target case by driving of the drive wheel mechanism according to a received item transferring instruction; and the robot controller is configured to control the case transport unit to fetch the at least one target case by controlling the lifting adjustment assembly to move up or down vertically, and place a fetched target case onto a temporary storage plate or a warehouse storage container.

12. The transferring robot according to claim 11, wherein in a case that the transferring robot comprises a plurality of temporary storage plates, the plurality of temporary storage plates are arranged at intervals along a vertical direction.

13. The transferring robot according to claim 11, the fetching assembly comprises extending arms; and the extending arms are configured to extend, under control of the robot controller, to two sides of the target case to fetch the target case after the case transport unit moves to a height adapted for the target case.

14. A warehousing system comprising the transferring robot according to claim 1, and the warehouse storage container for storing the target case.

15. The warehousing system according to claim 14, wherein the transferring robot is provided with a detection sensor configured for detecting the target case; the transferring robot is configured for moving along the path, and scanning the target case in turn through the detection sensor during movement of the transferring robot; calculating a center position of the target case; the transferring robot is configured for moving to the center position; and extending the fetching assembly of the transferring robot and fetching the target case when the fetching assembly rises to a height where the target case is located.
