



US012385501B2

(12) **United States Patent**  
**Cooper**

(10) **Patent No.:** **US 12,385,501 B2**

(45) **Date of Patent:** **\*Aug. 12, 2025**

(54) **TENSIONED SUPPORT POST AND OTHER  
MOLTEN METAL DEVICES**

(58) **Field of Classification Search**

CPC ..... F04D 29/605; F04D 29/042; F04D 7/065;  
F05B 2240/90

(71) Applicant: **Molten Metal Equipment Innovations,  
LLC**, Middlefield, OH (US)

(Continued)

(72) Inventor: **Paul V. Cooper**, Middlefield, OH (US)

(56)

**References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **Molten Metal Equipment Innovations,  
LLC**, Middlefield, OH (US)

35,604 A 6/1862 Guild  
116,797 A 7/1871 Barnhart

(Continued)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

This patent is subject to a terminal dis-  
claimer.

CA 683469 3/1964  
CA 2115929 8/1992

(Continued)

(21) Appl. No.: **18/753,675**

OTHER PUBLICATIONS

(22) Filed: **Jun. 25, 2024**

(65) **Prior Publication Data**

US 2024/0344528 A1 Oct. 17, 2024

“Response to Final Office Action and Request for Continued Exami-  
nation for U.S. Appl. No. 09/275,627,” including Declarations of  
Haynes and Johnson, Apr. 16, 2001.

(Continued)

*Primary Examiner* — Todd M Epps

(74) *Attorney, Agent, or Firm* — SNELL & WILMER  
L.L.P.

**Related U.S. Application Data**

(63) Continuation of application No. 18/139,936, filed on  
Apr. 26, 2023, now Pat. No. 12,031,550, which is a  
(Continued)

(51) **Int. Cl.**

**F04D 29/60** (2006.01)

**F04D 29/043** (2006.01)

**F04D 7/00** (2006.01)

(52) **U.S. Cl.**


CPC ..... **F04D 29/605** (2013.01); **F04D 29/043**  
(2013.01); **F04D 7/00** (2013.01); **F05B**  
**2240/60** (2013.01); **F05B 2240/90** (2013.01)

(57)

**ABSTRACT**

A vertically-elongated member, which is preferably a sup-  
port post used in a molten metal pump, includes a ceramic  
tube and tensioning structures to add a compressive load to  
the tube along its longitudinal axis. This makes the tube less  
prone to breakage. Another vertically-elongated member,  
such as a support post, includes one or more reinforcement  
members to help alleviate breakage. A device, such as a  
pump, used in a molten metal bath includes one or more of  
such vertical members.

**20 Claims, 11 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 17/496,229, filed on Oct. 7, 2021, now Pat. No. 11,976,672, which is a continuation of application No. 16/195,678, filed on Nov. 19, 2018, now Pat. No. 11,149,747.

- (60) Provisional application No. 62/588,090, filed on Nov. 17, 2017.

(58) **Field of Classification Search**

USPC ..... 248/677; 415/216.1  
See application file for complete search history.

(56) **References Cited**

## U.S. PATENT DOCUMENTS

209,219 A	10/1878	Bookwalter	2,543,633 A	2/1951	Lamphere
251,104 A	12/1881	Finch	2,566,892 A	9/1951	Jacobs
307,845 A	11/1884	Curtis	2,625,720 A	1/1953	Ross
364,804 A	6/1887	Cole	2,626,086 A	1/1953	Forrest
390,319 A	10/1888	Thomson	2,676,279 A	4/1954	Wilson
495,760 A	4/1893	Seitz	2,677,609 A	5/1954	Moore et al.
506,572 A	10/1893	Wagener	2,698,583 A	1/1955	House et al.
585,188 A	6/1897	Davis	2,714,354 A	8/1955	Farrand
757,932 A	4/1904	Jones	2,762,095 A	9/1956	Pemetzrieder
882,477 A	3/1908	Neumann	2,768,587 A	10/1956	Corneil
882,478 A	3/1908	Neumann	2,775,348 A	12/1956	Williams
890,319 A	6/1908	Wells	2,779,574 A	1/1957	Schneider
898,499 A	9/1908	O'Donnell	2,787,873 A	4/1957	Hadley
909,774 A	1/1909	Flora	2,808,782 A	10/1957	Thompson et al.
919,194 A	4/1909	Livingston	2,809,107 A	10/1957	Russell
1,037,659 A	9/1912	Rembert	2,821,472 A	1/1958	Peterson et al.
1,100,475 A	6/1914	Franckaerts	2,824,520 A	2/1958	Bartels
1,170,512 A	2/1916	Chapman	2,832,292 A	4/1958	Edwards
1,185,314 A	5/1916	Hedgcock	2,839,006 A	6/1958	Mayo
1,196,758 A	9/1916	Blair	2,853,019 A	9/1958	Thornton
1,304,068 A	5/1919	Krogh	2,865,295 A	12/1958	Nikolaus
1,331,997 A	2/1920	Neal	2,865,618 A	12/1958	Abell
1,377,101 A	5/1921	Sparling	2,868,132 A	1/1959	Rittershofer
1,380,798 A	6/1921	Hansen et al.	2,901,006 A	8/1959	Andrews
1,439,365 A	12/1922	Hazell	2,901,677 A	8/1959	Chessman et al.
1,454,967 A	5/1923	Gill	2,906,632 A	9/1959	Nickerson
1,470,607 A	10/1923	Hazell	2,918,876 A	12/1959	Howe
1,513,875 A	11/1924	Wilke	2,948,524 A	8/1960	Sweeney et al.
1,518,501 A	12/1924	Gill	2,958,293 A	11/1960	Pray, Jr.
1,522,765 A	1/1925	Wilke	2,966,345 A	12/1960	Burgoon et al.
1,526,851 A	2/1925	Hall	2,966,381 A	12/1960	Menzel
1,669,668 A	5/1928	Marshall	2,978,885 A	4/1961	Davison
1,673,594 A	6/1928	Schmidt	2,984,524 A	5/1961	Franzen
1,697,202 A	1/1929	Nagle	2,987,885 A	6/1961	Hodge
1,717,969 A	6/1929	Goodner	3,010,402 A	11/1961	King
1,718,396 A	6/1929	Wheeler	3,015,190 A	1/1962	Arbeit
1,896,201 A	2/1933	Sterner-Rainer	3,039,864 A	6/1962	Hess
1,988,875 A	1/1935	Saborio	3,044,408 A	7/1962	Mellott
2,013,455 A	9/1935	Baxter	3,048,384 A	8/1962	Sweeney et al.
2,035,282 A	3/1936	Schmeller, Sr.	3,070,393 A	12/1962	Silverberg et al.
2,038,221 A	4/1936	Kagi	3,092,030 A	6/1963	Wunder
2,075,633 A	3/1937	Anderegg	3,099,870 A	8/1963	Seeler
2,090,162 A	8/1937	Tighe	3,128,327 A	4/1964	Upton
2,091,677 A	8/1937	Fredericks	3,130,678 A	4/1964	Chenault
2,138,814 A	12/1938	Bressler	3,130,679 A	4/1964	Sence
2,173,377 A	9/1939	Schultz, Jr. et al.	3,151,565 A	10/1964	Albertson et al.
2,264,740 A	12/1941	Brown	3,171,357 A	3/1965	Egger
2,280,979 A	4/1942	Rocke	3,172,850 A	3/1965	Englesberg et al.
2,290,961 A	7/1942	Heuer	3,203,182 A	8/1965	Pohl
2,300,688 A	11/1942	Nagle	3,227,547 A	1/1966	Szekely
2,304,849 A	12/1942	Ruthman	3,244,109 A	4/1966	Barske
2,368,962 A	2/1945	Blom	3,251,676 A	5/1966	Johnson
2,383,424 A	8/1945	Stepanoff	3,255,702 A	6/1966	Gehrm
2,423,655 A	7/1947	Mars et al.	3,258,283 A	6/1966	Winberg et al.
2,488,447 A	11/1949	Tangen et al.	3,272,619 A	9/1966	Sweeney et al.
2,493,467 A	1/1950	Sunnen	3,289,473 A	12/1966	Louda
2,515,097 A	7/1950	Schryber	3,291,473 A	12/1966	Sweeney et al.
2,515,478 A	7/1950	Tooley et al.	3,368,805 A	2/1968	Davey et al.
2,528,208 A	10/1950	Bonsack et al.	3,374,943 A	3/1968	Cervinka
2,528,210 A	10/1950	Stewart	3,400,923 A	9/1968	Howie et al.
			3,417,929 A	12/1968	Secrest et al.
			3,432,336 A	3/1969	Langrod et al.
			3,459,133 A	8/1969	Scheffler
			3,459,346 A	8/1969	Tinnes
			3,477,383 A	11/1969	Rawson et al.
			3,487,805 A	1/1970	Satterthwaite
			3,512,762 A	5/1970	Umbricht
			3,512,788 A	5/1970	Kilbane
			3,532,445 A	10/1970	Scheffler et al.
			3,561,885 A	2/1971	Lake
			3,575,525 A	4/1971	Fox et al.
			3,581,767 A	6/1971	Jackson
			3,612,715 A	10/1971	Yedidiah
			3,618,917 A	11/1971	Fredrikson et al.
			3,620,716 A	11/1971	Hess
			3,650,730 A	3/1972	Derham et al.
			3,689,048 A	9/1972	Foulard et al.
			3,715,112 A	2/1973	Carbonnel
			3,732,032 A	5/1973	Daneel

(56)

## References Cited

## U.S. PATENT DOCUMENTS

3,737,304 A	6/1973	Blayden et al.	4,392,888 A	7/1983	Eckert et al.
3,737,305 A	6/1973	Blayden et al.	4,410,299 A	10/1983	Shimoyama
3,743,263 A	7/1973	Szekely	4,419,049 A	12/1983	Gerboth et al.
3,743,500 A	7/1973	Foulard et al.	4,456,424 A	6/1984	Araoka
3,753,690 A	8/1973	Emley et al.	4,470,846 A	9/1984	Dube
3,759,628 A	9/1973	Kempf	4,474,315 A	10/1984	Gilbert et al.
3,759,635 A	9/1973	Carter et al.	4,496,393 A	1/1985	Lustenberger
3,767,382 A	10/1973	Bruno et al.	4,504,392 A	3/1985	Groteke
3,776,660 A	12/1973	Anderson et al.	4,509,979 A	4/1985	Bauer
3,785,632 A	1/1974	Kraemer et al.	4,530,641 A	7/1985	Gschwender
3,787,143 A	1/1974	Carbonnel et al.	4,537,624 A	8/1985	Tenhover et al.
3,799,522 A	3/1974	Brant et al.	4,537,625 A	8/1985	Tenhover et al.
3,799,523 A	3/1974	Seki	4,545,887 A	10/1985	Amesen
3,807,708 A	4/1974	Jones	4,556,419 A	12/1985	Otsuka et al.
3,814,400 A	6/1974	Seki	4,557,766 A	12/1985	Tenhover et al.
3,824,028 A	7/1974	Zenkner et al.	4,586,845 A	5/1986	Morris
3,824,042 A	7/1974	Barnes et al.	4,592,700 A	6/1986	Toguchi et al.
3,836,280 A	9/1974	Koch	4,594,052 A	6/1986	Niskanen
3,839,019 A	10/1974	Bruno et al.	4,596,510 A	6/1986	Armeth et al.
3,844,972 A	10/1974	Tully, Jr. et al.	4,598,899 A	7/1986	Cooper
3,871,872 A	3/1975	Downing et al.	4,600,222 A	7/1986	Appling
3,873,073 A	3/1975	Baum et al.	4,607,825 A	8/1986	Briolle et al.
3,873,305 A	3/1975	Claxton et al.	4,609,442 A	9/1986	Tenhover et al.
3,881,039 A	4/1975	Baldieri et al.	4,611,790 A	9/1986	Otsuka et al.
3,886,992 A	6/1975	Maas et al.	4,617,232 A	10/1986	Chandler et al.
3,915,594 A	10/1975	Nesseth	4,634,105 A	1/1987	Withers et al.
3,915,694 A	10/1975	Ando	4,640,666 A	2/1987	Sodergard
3,935,003 A	1/1976	Steinke et al.	4,655,610 A	4/1987	Al-Jaroudi
3,941,588 A	3/1976	Dremann	4,668,166 A	5/1987	Lutz
3,941,589 A	3/1976	Norman et al.	4,669,953 A	6/1987	Gechwender
3,942,473 A	3/1976	Chodash	4,673,434 A	6/1987	Withers et al.
3,954,134 A	5/1976	Maas et al.	4,682,585 A	7/1987	Hiltebrandt
3,958,979 A	5/1976	Valdo	4,684,281 A	8/1987	Patterson
3,958,981 A	5/1976	Forberg et al.	4,685,822 A	8/1987	Pelton
3,961,778 A	6/1976	Carbonnel et al.	4,696,703 A	9/1987	Henderson et al.
3,966,456 A	6/1976	Ellenbaum et al.	4,701,226 A	10/1987	Henderson et al.
3,967,286 A	6/1976	Andersson et al.	4,702,768 A	10/1987	Areauz et al.
3,972,709 A	8/1976	Chin et al.	4,714,371 A	12/1987	Cuse
3,973,871 A	8/1976	Hance	4,717,540 A	1/1988	McRae et al.
3,984,234 A	10/1976	Claxton et al.	4,739,974 A	4/1988	Mordue
3,985,000 A	10/1976	Hartz	4,741,664 A	5/1988	Olmstead
3,997,336 A	12/1976	van Linden et al.	4,743,428 A	5/1988	McRae et al.
4,003,560 A	1/1977	Carbonnel	4,747,583 A	5/1988	Gordon et al.
4,008,884 A	2/1977	Fitzpatrick et al.	4,767,230 A	8/1988	Leas, Jr.
4,018,598 A	4/1977	Markus	4,770,701 A	9/1988	Henderson et al.
4,043,146 A	8/1977	Stegherr et al.	4,786,230 A	11/1988	Thut
4,052,199 A	10/1977	Mangalick	4,802,656 A	2/1989	Hudault et al.
4,055,390 A	10/1977	Young	4,804,168 A	2/1989	Otsuka et al.
4,063,849 A	12/1977	Modianos	4,810,314 A	3/1989	Henderson et al.
4,068,965 A	1/1978	Lichti	4,822,473 A	4/1989	Arnesen
4,073,606 A	2/1978	Eller	4,834,573 A	5/1989	Asano et al.
4,091,970 A	5/1978	Komiyama et al.	4,842,227 A	6/1989	Harrington et al.
4,119,141 A	10/1978	Thut et al.	4,844,425 A	7/1989	Piras et al.
4,125,146 A	11/1978	Muller	4,851,296 A	7/1989	Tenhover et al.
4,126,360 A	11/1978	Miller et al.	4,854,834 A	8/1989	Gschwender et al.
4,128,415 A	12/1978	van Linden et al.	4,859,413 A	8/1989	Harris et al.
4,147,474 A	4/1979	Heimdal et al.	4,860,819 A	8/1989	Moscoe et al.
4,169,584 A	10/1979	Mangalick	4,867,638 A	9/1989	Handtmann et al.
4,191,486 A	3/1980	Pelton	4,884,786 A	12/1989	Gillespie
4,213,742 A	7/1980	Henshaw	4,898,367 A	2/1990	Cooper
4,242,039 A	12/1980	Villard et al.	4,908,060 A	3/1990	Duenkelmann
4,244,423 A	1/1981	Thut et al.	4,909,704 A	3/1990	Lutz
4,286,985 A	9/1981	van Linden et al.	4,911,726 A	3/1990	Warkentin
4,305,214 A	12/1981	Hurst	4,923,770 A	5/1990	Grasselli et al.
4,322,245 A	3/1982	Claxton	4,930,986 A	6/1990	Cooper
4,338,062 A	7/1982	Neal	4,931,091 A	6/1990	Waite et al.
4,347,041 A	8/1982	Cooper	4,940,214 A	7/1990	Gillespie
4,351,514 A	9/1982	Koch	4,940,384 A	7/1990	Amra et al.
4,355,789 A	10/1982	Dolzhenkov et al.	4,954,167 A	9/1990	Cooper
4,356,940 A	11/1982	Ansorge	4,967,827 A	11/1990	Campbell
4,360,314 A	11/1982	Pennell	4,973,433 A	11/1990	Gilbert et al.
4,370,096 A	1/1983	Church	4,986,736 A	1/1991	Kajiwarra et al.
4,372,541 A	2/1983	Bocourt et al.	4,989,736 A	2/1991	Andersson et al.
4,375,937 A	3/1983	Cooper	5,000,025 A	3/1991	Beekel
4,389,159 A	6/1983	Sarvanne	5,015,518 A	5/1991	Sasaki et al.
			5,025,198 A	6/1991	Mordue et al.
			5,028,211 A	7/1991	Mordue et al.
			5,029,821 A	7/1991	Bar-on et al.
			5,058,654 A	10/1991	Simmons

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,078,572 A	1/1992	Amra et al.	5,613,245 A	3/1997	Robert
5,080,715 A	1/1992	Provencher et al.	5,616,167 A	4/1997	Eckert
5,083,753 A	1/1992	Soofi	5,622,481 A	4/1997	Thut
5,088,893 A	2/1992	Gilbert et al.	5,629,464 A	5/1997	Bach et al.
5,092,821 A	3/1992	Gilbert et al.	5,634,770 A	6/1997	Gilbert et al.
5,098,134 A	3/1992	Monckton	5,640,706 A	6/1997	Nagel et al.
5,099,554 A	3/1992	Cooper	5,640,707 A	6/1997	Nagel et al.
5,114,312 A	5/1992	Stanislao	5,640,709 A	6/1997	Nagel et al.
5,126,047 A	6/1992	Martin et al.	5,655,849 A	8/1997	McEwen et al.
5,131,632 A	7/1992	Olson	5,660,614 A	8/1997	Waite et al.
5,135,202 A	8/1992	Yamashita et al.	5,662,725 A	9/1997	Cooper
5,143,357 A	9/1992	Gilbert et al.	5,676,520 A	10/1997	Thut
5,145,322 A	9/1992	Senior, Jr. et al.	5,678,244 A	10/1997	Shaw et al.
5,152,631 A	10/1992	Bauer	5,678,807 A	10/1997	Cooper
5,154,652 A	10/1992	Ecklesdafer	5,679,132 A	10/1997	Rauenzahn et al.
5,158,440 A	10/1992	Cooper et al.	5,685,701 A	11/1997	Chandler et al.
5,162,858 A	11/1992	Shoji et al.	5,690,888 A	11/1997	Robert
5,165,858 A	11/1992	Gilbert et al.	5,695,732 A	12/1997	Sparks et al.
5,177,304 A	1/1993	Nagel	5,716,195 A	2/1998	Thut
5,191,154 A	3/1993	Nagel	5,717,149 A	2/1998	Nagel et al.
5,192,193 A	3/1993	Cooper et al.	5,718,416 A	2/1998	Flisakowski et al.
5,202,100 A	4/1993	Nagel et al.	5,735,668 A	4/1998	Klein
5,203,681 A	4/1993	Cooper	5,735,935 A	4/1998	Areaux
5,209,641 A	5/1993	Hoglund et al.	5,741,422 A	4/1998	Eichenmiller et al.
5,215,448 A	6/1993	Cooper	5,744,093 A	4/1998	Davis
5,268,020 A	12/1993	Claxton	5,744,117 A	4/1998	Wilkinson et al.
5,286,163 A	2/1994	Amra et al.	5,745,861 A	4/1998	Bell et al.
5,298,233 A	3/1994	Nagel	5,755,847 A	5/1998	Quayle
5,301,620 A	4/1994	Nagel et al.	5,758,712 A	6/1998	Pederson
5,303,903 A	4/1994	Butler et al.	5,772,324 A	6/1998	Falk
5,308,045 A	5/1994	Cooper	5,776,420 A	7/1998	Nagel
5,310,412 A	5/1994	Gilbert et al.	5,785,494 A	7/1998	Vild et al.
5,318,360 A	6/1994	Langer et al.	5,842,832 A	12/1998	Thut
5,322,547 A	6/1994	Nagel et al.	5,846,481 A	12/1998	Tilak
5,324,341 A	6/1994	Nagel et al.	5,858,059 A	1/1999	Abramovich et al.
5,330,328 A	7/1994	Cooper	5,863,314 A	1/1999	Morando
5,354,940 A	10/1994	Nagel	5,866,095 A	2/1999	McGeever et al.
5,358,549 A	10/1994	Nagel et al.	5,875,385 A	2/1999	Stephenson et al.
5,358,697 A	10/1994	Nagel	5,935,528 A	8/1999	Stephenson et al.
5,364,078 A	11/1994	Pelton	5,944,496 A	8/1999	Cooper
5,369,063 A	11/1994	Gee et al.	5,947,705 A	9/1999	Mordue et al.
5,383,651 A	1/1995	Blasen et al.	5,948,352 A	9/1999	Jagt et al.
5,388,633 A	2/1995	Mercer, II et al.	5,951,243 A	9/1999	Cooper
5,395,405 A	3/1995	Nagel et al.	5,961,285 A	10/1999	Meneice et al.
5,399,074 A	3/1995	Nose et al.	5,963,580 A	10/1999	Eckert
5,407,294 A	4/1995	Giannini	5,992,230 A	11/1999	Scarpa et al.
5,411,240 A	5/1995	Rapp et al.	5,993,726 A	11/1999	Huang
5,425,410 A	6/1995	Reynolds	5,993,728 A	11/1999	Vild
5,431,551 A	7/1995	Aquino et al.	6,007,313 A *	12/1999	Sigel ..... F04D 29/0413 417/424.1
5,435,982 A	7/1995	Wilkinson	6,019,576 A	2/2000	Thut
5,436,210 A	7/1995	Wilkinson et al.	6,027,685 A	2/2000	Cooper
5,443,572 A	8/1995	Wilkinson et al.	6,036,745 A	3/2000	Gilbert et al.
5,454,423 A	10/1995	Tsuchida et al.	6,074,455 A	6/2000	van Linden et al.
5,468,280 A	11/1995	Areaux	6,082,965 A	7/2000	Morando
5,470,201 A	11/1995	Gilbert et al.	6,093,000 A	7/2000	Cooper
5,484,265 A	1/1996	Horvath et al.	6,096,109 A	8/2000	Nagel et al.
5,489,734 A	2/1996	Nagel et al.	6,113,154 A	9/2000	Thut
5,491,279 A	2/1996	Robert et al.	6,123,523 A	9/2000	Cooper
5,494,382 A	2/1996	Kloppers	6,152,691 A	11/2000	Thut
5,495,746 A	3/1996	Sigworth	6,168,753 B1	1/2001	Morando
5,505,143 A	4/1996	Nagel	6,187,096 B1	2/2001	Thut
5,505,435 A	4/1996	Laszlo	6,199,836 B1	3/2001	Rexford et al.
5,509,791 A	4/1996	Turner	6,217,823 B1	4/2001	Vild et al.
5,511,766 A	4/1996	Vassilicos	6,231,639 B1	5/2001	Eichenmiller
5,520,422 A	5/1996	Friedrich	6,250,881 B1	6/2001	Mordue et al.
5,537,940 A	7/1996	Nagel et al.	6,254,340 B1	7/2001	Vild et al.
5,543,558 A	8/1996	Nagel et al.	6,270,717 B1	8/2001	Tremblay et al.
5,555,822 A	9/1996	Loewen et al.	6,280,157 B1	8/2001	Cooper
5,558,501 A	9/1996	Wang et al.	6,293,759 B1	9/2001	Thut
5,558,505 A	9/1996	Mordue et al.	6,303,074 B1	10/2001	Cooper
5,571,486 A	11/1996	Robert et al.	6,345,964 B1	2/2002	Cooper
5,585,532 A	12/1996	Nagel	6,354,796 B1	3/2002	Morando
5,586,863 A	12/1996	Gilbert et al.	6,358,467 B1	3/2002	Mordue
5,591,243 A	1/1997	Colussi et al.	6,364,930 B1	4/2002	Kos
5,597,289 A	1/1997	Thut	6,371,723 B1	4/2002	Grant et al.
			6,398,525 B1	6/2002	Cooper
			6,439,860 B1	8/2002	Greer
			6,451,247 B1	9/2002	Mordue et al.

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

6,457,940 B1	10/2002	Lehman	8,840,359 B2	9/2014	Vick et al.
6,457,950 B1	10/2002	Cooper et al.	8,899,932 B2	12/2014	Tetkoskie et al.
6,464,458 B2	10/2002	Vild et al.	8,915,830 B2	12/2014	March et al.
6,474,962 B1	11/2002	Allen et al.	8,920,680 B2	12/2014	Mao
6,495,948 B1	12/2002	Garrett, III	9,011,761 B2	4/2015	Cooper
6,497,559 B1	12/2002	Grant	9,017,597 B2	4/2015	Cooper
6,500,228 B1	12/2002	Klingensmith et al.	9,034,244 B2	5/2015	Cooper
6,503,292 B2	1/2003	Klingensmith et al.	9,057,376 B2	6/2015	Thut
6,524,066 B2	2/2003	Thut	9,057,377 B1	6/2015	Thut
6,533,535 B2	3/2003	Thut	9,074,601 B1	7/2015	Thut
6,551,060 B2	4/2003	Mordue et al.	9,080,577 B2	7/2015	Cooper
6,562,286 B1	5/2003	Lehman	9,108,224 B2	8/2015	Schererz et al.
6,656,415 B2	12/2003	Kos	9,108,244 B2	8/2015	Cooper
6,679,936 B2	1/2004	Quackenbush	9,156,087 B2	10/2015	Cooper
6,689,310 B1	2/2004	Cooper	9,193,532 B2	11/2015	March et al.
6,709,234 B2	3/2004	Gilbert et al.	9,205,490 B2	12/2015	Cooper
6,716,147 B1	4/2004	Hinkle et al.	9,234,520 B2	1/2016	Morando
6,723,276 B1	4/2004	Cooper	9,273,376 B2	3/2016	Lutes et al.
6,805,834 B2	10/2004	Thut	9,328,615 B2	5/2016	Cooper
6,843,640 B2	1/2005	Mordue et al.	9,377,028 B2	6/2016	Cooper
6,848,497 B2	2/2005	Sale et al.	9,382,599 B2	7/2016	Cooper
6,869,271 B2	3/2005	Gilbert et al.	9,383,140 B2	7/2016	Cooper
6,869,564 B2	3/2005	Gilbert et al.	9,388,925 B2	7/2016	Juarez
6,881,030 B2	4/2005	Thut	9,409,232 B2	8/2016	Cooper
6,887,424 B2	5/2005	Ohno et al.	9,410,744 B2	8/2016	Cooper
6,887,425 B2	5/2005	Mordue et al.	9,422,942 B2 *	8/2016	Cooper ..... F04D 29/043
6,902,696 B2	6/2005	Klingensmith et al.	9,435,343 B2	9/2016	Cooper
7,037,462 B2	5/2006	Klingensmith et al.	9,464,636 B2	10/2016	Cooper
7,074,361 B2	7/2006	Carolla et al.	9,470,239 B2	10/2016	Cooper
7,083,758 B2	8/2006	Tremblay	9,476,644 B2	10/2016	Howitt et al.
7,131,482 B2	11/2006	Vincent et al.	9,481,035 B2	11/2016	Cooper
7,157,043 B2	1/2007	Neff	9,481,918 B2	11/2016	Vild et al.
7,204,954 B2	4/2007	Mizuno	9,482,469 B2	11/2016	Cooper
7,273,582 B2	9/2007	Mordue	9,494,366 B1	11/2016	Thut
7,279,128 B2	10/2007	Kennedy et al.	9,506,129 B2	11/2016	Cooper
7,326,028 B2	2/2008	Morando	9,506,346 B2	11/2016	Bright et al.
7,402,276 B2	7/2008	Cooper	9,532,670 B2	1/2017	Vanessen
7,470,392 B2	12/2008	Cooper	9,566,645 B2	2/2017	Cooper
7,476,357 B2	1/2009	Thut	9,581,388 B2	2/2017	Cooper
7,481,966 B2	1/2009	Mizuno	9,587,883 B2	3/2017	Cooper
7,497,988 B2	3/2009	Thut	9,632,670 B2	4/2017	Wu
7,507,365 B2	3/2009	Thut	9,643,247 B2	5/2017	Cooper
7,507,367 B2	3/2009	Cooper	9,657,578 B2	5/2017	Cooper
7,543,605 B1	6/2009	Morando	9,855,600 B2	1/2018	Cooper
7,731,891 B2	6/2010	Cooper	9,862,026 B2	1/2018	Cooper
7,771,171 B2	8/2010	Mohr	9,903,383 B2	2/2018	Cooper
7,784,999 B1	8/2010	Lott	9,909,808 B2	3/2018	Cooper
7,841,379 B1	11/2010	Evans	9,920,767 B2	3/2018	Klain et al.
7,896,617 B1	3/2011	Morando	9,920,787 B2 *	3/2018	Paul ..... F16C 33/1045
7,906,068 B2	3/2011	Cooper	9,925,587 B2	3/2018	Cooper
8,075,837 B2	12/2011	Cooper	9,951,777 B2	4/2018	Morando et al.
8,110,141 B2	2/2012	Cooper	9,970,442 B2	5/2018	Tipton
8,137,023 B2	3/2012	Greer	9,982,945 B2	5/2018	Cooper
8,142,145 B2	3/2012	Thut	10,052,688 B2	8/2018	Cooper
8,178,037 B2	5/2012	Cooper	10,072,897 B2	9/2018	Cooper
8,328,540 B2	12/2012	Wang	10,126,058 B2	11/2018	Cooper
8,333,921 B2	12/2012	Thut	10,126,059 B2	11/2018	Cooper
8,337,746 B2	12/2012	Cooper	10,138,892 B2	11/2018	Cooper
8,361,379 B2	1/2013	Cooper	10,195,664 B2	2/2019	Cooper et al.
8,366,993 B2	2/2013	Cooper	10,267,314 B2 *	4/2019	Cooper ..... F04D 7/065
8,409,495 B2	4/2013	Cooper	10,274,256 B2	4/2019	Cooper
8,440,135 B2	5/2013	Cooper	10,302,361 B2	5/2019	Cooper
8,444,911 B2	5/2013	Cooper	10,307,821 B2	6/2019	Cooper
8,449,814 B2	5/2013	Cooper	10,309,725 B2	6/2019	Cooper
8,475,594 B2	7/2013	Bright et al.	10,322,451 B2	6/2019	Cooper
8,475,708 B2	7/2013	Cooper	10,345,045 B2	7/2019	Cooper
8,480,950 B2	7/2013	Jetten et al.	10,352,620 B2	7/2019	Cooper
8,501,084 B2	8/2013	Cooper	10,428,821 B2	10/2019	Cooper
8,524,146 B2	9/2013	Cooper	10,458,708 B2	10/2019	Cooper
8,529,828 B2	9/2013	Cooper	10,465,688 B2	11/2019	Cooper
8,535,603 B2	9/2013	Cooper	10,562,097 B2	2/2020	Cooper
8,580,218 B2	11/2013	Turenne et al.	10,570,745 B2	2/2020	Cooper
8,613,884 B2	12/2013	Cooper	10,641,270 B2 *	5/2020	Cooper ..... F04D 29/628
8,714,914 B2	5/2014	Cooper	10,641,279 B2	5/2020	Cooper
8,753,563 B2	6/2014	Cooper	10,675,679 B2	6/2020	Cooper
			11,020,798 B2	6/2021	Cooper
			11,098,719 B2	8/2021	Cooper
			11,098,720 B2 *	8/2021	Cooper ..... F04D 29/628
			11,103,920 B2	8/2021	Cooper

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

11,130,173	B2	9/2021	Cooper	2013/0306687	A1	11/2013	Cooper
11,149,747	B2 *	10/2021	Cooper ..... F04D 29/605	2013/0334744	A1	12/2013	Tremblay
11,167,345	B2	11/2021	Cooper	2013/0343904	A1	12/2013	Cooper
11,185,916	B2	11/2021	Cooper	2014/0008849	A1	1/2014	Cooper
11,286,939	B2	3/2022	Cooper	2014/0041252	A1	2/2014	Vild et al.
11,358,216	B2	6/2022	Cooper	2014/0044520	A1	2/2014	Tipton
11,358,217	B2	6/2022	Cooper	2014/0083253	A1	3/2014	Lutes et al.
11,391,293	B2	7/2022	Cooper	2014/0210144	A1	7/2014	Torres et al.
11,471,938	B2	10/2022	Fontana	2014/0232048	A1	8/2014	Howitt et al.
11,519,414	B2	12/2022	Cooper	2014/0252697	A1	9/2014	Rauch
12,031,550	B2 *	7/2024	Cooper ..... F04D 29/043	2014/0252701	A1	9/2014	Cooper
2001/0000465	A1	4/2001	Thut	2014/0261800	A1	9/2014	Cooper
2002/0089099	A1	7/2002	Denning	2014/0263482	A1	9/2014	Cooper
2002/0102159	A1	8/2002	Thut	2014/0265068	A1	9/2014	Cooper
2002/0146313	A1	10/2002	Thut	2014/0271219	A1	9/2014	Cooper
2002/0185789	A1	12/2002	Klingensmith et al.	2014/0363309	A1	12/2014	Henderson et al.
2002/0185790	A1	12/2002	Kilgenschmidt	2015/0069679	A1	3/2015	Henderson et al.
2002/0185794	A1	12/2002	Vincent	2015/0184311	A1	7/2015	Turenne
2003/0047850	A1	3/2003	Areaux	2015/0192364	A1	7/2015	Cooper
2003/0075844	A1	4/2003	Mordue et al.	2015/0217369	A1	8/2015	Cooper
2003/0082052	A1	5/2003	Gilbert et al.	2015/0219111	A1	8/2015	Cooper
2003/0151176	A1	8/2003	Ohno	2015/0219112	A1	8/2015	Cooper
2003/0201583	A1	10/2003	Klingensmith	2015/0219113	A1	8/2015	Cooper
2004/0050525	A1	3/2004	Kennedy et al.	2015/0219114	A1	8/2015	Cooper
2004/0076533	A1	4/2004	Cooper	2015/0224574	A1	8/2015	Cooper
2004/0096330	A1	5/2004	Gilbert	2015/0252807	A1	9/2015	Cooper
2004/0115079	A1	6/2004	Cooper	2015/0285557	A1	10/2015	Cooper
2004/0245684	A1	12/2004	Kojo	2015/0285558	A1	10/2015	Cooper
2004/0262825	A1	12/2004	Cooper	2015/0323256	A1	11/2015	Cooper
2005/0013713	A1	1/2005	Cooper	2015/0328682	A1	11/2015	Cooper
2005/0013714	A1	1/2005	Cooper	2015/0328683	A1	11/2015	Cooper
2005/0013715	A1	1/2005	Cooper	2016/0031007	A1	2/2016	Cooper
2005/0053499	A1	3/2005	Cooper	2016/0040265	A1	2/2016	Cooper
2005/0077730	A1	4/2005	Thut	2016/0047602	A1	2/2016	Cooper
2005/0081607	A1	4/2005	Patel et al.	2016/0053762	A1	2/2016	Cooper
2005/0116398	A1	6/2005	Tremblay	2016/0053814	A1	2/2016	Cooper
2006/0180963	A1	8/2006	Thut	2016/0082507	A1	3/2016	Cooper
2006/0198725	A1	9/2006	Thut	2016/0089718	A1	3/2016	Cooper
2007/0253807	A1	11/2007	Cooper	2016/0091251	A1	3/2016	Cooper
2008/0163999	A1	7/2008	Hymas et al.	2016/0116216	A1	4/2016	Schlicht et al.
2008/0202644	A1	8/2008	Grassi	2016/0221855	A1	8/2016	Retorick et al.
2008/0211147	A1	9/2008	Cooper	2016/0250686	A1	9/2016	Cooper
2008/0213111	A1	9/2008	Cooper	2016/0265535	A1	9/2016	Cooper
2008/0230966	A1	9/2008	Cooper	2016/0305711	A1	10/2016	Cooper
2008/0253905	A1	10/2008	Morando et al.	2016/0320129	A1	11/2016	Cooper
2008/0304970	A1	12/2008	Cooper	2016/0320130	A1	11/2016	Cooper
2008/0314548	A1	12/2008	Cooper	2016/0320131	A1	11/2016	Cooper
2009/0054167	A1	2/2009	Cooper	2016/0346836	A1	12/2016	Henderson et al.
2009/0140013	A1	6/2009	Cooper	2016/0348973	A1	12/2016	Cooper
2009/0269191	A1	10/2009	Cooper	2016/0348974	A1	12/2016	Cooper
2010/0104415	A1	4/2010	Morando	2016/0348975	A1	12/2016	Cooper
2010/0200354	A1	8/2010	Yagi et al.	2017/0037852	A1	2/2017	Bright et al.
2011/0133374	A1	6/2011	Cooper	2017/0038146	A1	2/2017	Cooper
2011/0135457	A1	6/2011	Cooper	2017/0045298	A1	2/2017	Cooper
2011/0140318	A1	6/2011	Reeves et al.	2017/0056973	A1	3/2017	Tremblay et al.
2011/0140319	A1	6/2011	Cooper	2017/0082368	A1	3/2017	Cooper
2011/0140619	A1	6/2011	Lin	2017/0106435	A1	4/2017	Vincent
2011/0142603	A1	6/2011	Cooper	2017/0106441	A1	4/2017	Vincent
2011/0142606	A1	6/2011	Cooper	2017/0130298	A1	5/2017	Teranishi et al.
2011/0148012	A1	6/2011	Cooper	2017/0167793	A1	6/2017	Cooper et al.
2011/0163486	A1	7/2011	Cooper	2017/0198721	A1	7/2017	Cooper
2011/0210232	A1	9/2011	Cooper	2017/0219289	A1	8/2017	Williams et al.
2011/0220771	A1	9/2011	Cooper	2017/0241713	A1	8/2017	Henderson et al.
2011/0227338	A1	9/2011	Pollack	2017/0246681	A1	8/2017	Tipton et al.
2011/0303706	A1	12/2011	Cooper	2017/0274446	A1	9/2017	Wagstaff
2012/0003099	A1	1/2012	Tetkoskie	2017/0276430	A1	9/2017	Cooper
2012/0163959	A1	6/2012	Morando	2018/0058465	A1	3/2018	Cooper
2013/0105102	A1	5/2013	Cooper	2018/0111189	A1	4/2018	Cooper
2013/0142625	A1	6/2013	Cooper	2018/0178281	A1	6/2018	Cooper
2013/0214014	A1	8/2013	Cooper	2018/0195513	A1	7/2018	Cooper
2013/0224038	A1	8/2013	Tetkoskie et al.	2018/0311726	A1	11/2018	Cooper
2013/0292426	A1	11/2013	Cooper	2019/0032675	A1	1/2019	Cooper
2013/0292427	A1	11/2013	Cooper	2019/0160642	A1	5/2019	Joo et al.
2013/0299524	A1	11/2013	Cooper	2019/0270134	A1	9/2019	Cooper
2013/0299525	A1	11/2013	Cooper	2019/0293089	A1	9/2019	Cooper
				2019/0351481	A1	11/2019	Tetkoskie
				2019/0360491	A1	11/2019	Cooper
				2019/0360492	A1	11/2019	Cooper
				2019/0368494	A1	12/2019	Cooper

(56)

**References Cited****U.S. PATENT DOCUMENTS**

2020/0130050	A1	4/2020	Cooper
2020/0130051	A1	4/2020	Cooper
2020/0130052	A1	4/2020	Cooper
2020/0130053	A1	4/2020	Cooper
2020/0130054	A1	4/2020	Cooper
2020/0182247	A1	6/2020	Cooper
2020/0182248	A1	6/2020	Cooper
2020/0256350	A1	8/2020	Cooper
2020/0360987	A1	11/2020	Cooper
2020/0360988	A1	11/2020	Fontana
2020/0360989	A1	11/2020	Cooper
2020/0360990	A1	11/2020	Cooper
2020/0362865	A1	11/2020	Cooper
2020/0363128	A1	11/2020	Cooper
2021/0199115	A1	7/2021	Cooper
2021/0254622	A1	8/2021	Cooper
2022/0025905	A1	1/2022	Cooper
2022/0080498	A1	3/2022	Cooper
2022/0193764	A1	6/2022	Cooper
2022/0213895	A1	7/2022	Cooper
2022/0234099	A1	7/2022	Cooper
2022/0381246	A1	12/2022	Cooper
2023/0001474	A1	1/2023	Cooper
2023/0219132	A1	7/2023	Cooper

**FOREIGN PATENT DOCUMENTS**

CA	2244251	6/1998
CA	2305865	2/2000
CA	2176475	7/2005
CA	2924572	4/2015
CH	392268	9/1965
CN	102943761	2/2013
CN	103511331	1/2014
DE	1800446	12/1969
DE	19541093	5/1997
DE	19614350	10/1997
DE	102006051814	7/2008
EP	168250	1/1986
EP	665378	8/1995
EP	1019635	6/2006
GB	161707 A	4/1921
GB	543607	3/1942
GB	942648	11/1963
GB	1185314	3/1970

GB	1565911	4/1980
GB	1575991	10/1980
GB	212260	1/1984
GB	2193257	2/1988
GB	2217784	3/1989
GB	2289919	12/1995
JP	58048796	3/1983
JP	63104773	5/1988
JP	11-270799	10/1999
JP	5112837	1/2013
MX	227385	4/2005
NO	90756	1/1959
SU	416401	2/1974
SU	773312	10/1980
WO	199808990	3/1998
WO	199825031	6/1998
WO	200009889	2/2000
WO	2002012147	2/2002
WO	2004029307	4/2004
WO	2010147932	12/2010
WO	2014031484	2/2014
WO	2014055082	4/2014
WO	2014150503	9/2014
WO	2014185971	11/2014

**OTHER PUBLICATIONS**

Document No. 504217: Excerpts from “Pyrotek Inc.’s Motion for Summary Judgment of Invalidity and Unenforceability of U.S. Pat. No. 7,402,276,” Oct. 2, 2009.

Document No. 505026: Excerpts from “MMEI’s Response to Pyrotek’s Motion for Summary Judgment of Invalidity or Enforceability of U.S. Pat. No. 7,402,276,” Oct. 9, 2009.

Document No. 507689: Excerpts from “MMEI’s Pre-Hearing Brief and Supplemental Motion for Summary Judgment of Infringement of Claims 3, 4, 15, 17-20, 26, 28 and 29 of the ’074 Patent and Motion for Reconsideration of the Validity of Claims 7-9 of the ’276 Patent,” Nov. 4, 2009.

Document No. 517158: Excerpts from “Reasoned Award,” Feb. 19, 2010.

Document No. 525055: Excerpts from “Molten Metal Equipment Innovations, Inc.’s Reply Brief in Support of Application to Confirm Arbitration Award and Opposition to Motion to Vacate,” May 12, 2010.

USPTO; Notice of Reissue Examination Certificate dated Aug. 27, 2001 in U.S. Appl. No. 90/005,910.

\* cited by examiner

FIG. 2






FIG. 2B




FIG. 2E




FIG. 2C







FIG. 2D








30



40













FIG. 13




FIG. 14



FIG. 15




FIG. 16




FIG.17




FIG.18




FIG.19




FIG.22




FIG.20






FIG.21








FIG. 27




FIG. 26




FIG. 28




FIG. 29




FIG. 30

# TENSIONED SUPPORT POST AND OTHER MOLTEN METAL DEVICES

## CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of, and claims priority to U.S. patent application Ser. No. 18/139,936, filed Apr. 26, 2023 and entitled “Tensioned Support Post and Other Molten Metal Devices,” which is a continuation of, and claims priority to U.S. patent application Ser. No. 17/496,229, filed Oct. 7, 2021 and entitled “Tensioned Support Post and Other Molten Metal Devices,” which is a continuation of, and claims priority to U.S. patent application Ser. No. 16/195,678 (Now U.S. Pat. No. 11,149,747), filed Nov. 19, 2018, and entitled “Tensioned Support Posts and Other Molten Metal Devices” which claims priority to U.S. Provisional Application 62/588,090, filed Nov. 17, 2017, and entitled “Tensioned Support Post and Other Molten Metal Devices,” each of the disclosures of which are incorporated herein by reference. This Application incorporates by reference U.S. application Ser. No. 15/406,515 (now U.S. Pat. No. 10,267,314), filed Jan. 13, 2017, and entitled “Tensioned Support Shaft and Other Molten Metal Devices,” to the extent such application does not conflict with the present disclosure.

## FIELD

The invention relates to tensioned support posts and other components, such as a reinforced support post that may be used in pumps for pumping molten metal.

## BACKGROUND

As used herein, the term “molten metal” means any metal or combination of metals in liquid form, such as aluminum, copper, iron, zinc, and alloys thereof. The term “gas” means any gas or combination of gases, including argon, nitrogen, chlorine, fluorine, Freon, and helium, which are released into molten metal.

Known molten-metal pumps include (a) a pump base (also called a housing or casing), (b) one or more inlets (an inlet being an opening in the housing to allow molten metal to enter a pump chamber), (c) a pump chamber of any suitable configuration, which is an open area formed within the housing, (d) a discharge, which is a channel or conduit of any structure or type communicating with the pump chamber (in an axial pump the chamber and discharge may be the same structure or different areas of the same structure) and that leads from the pump chamber to (e) an outlet, which is an opening formed in the exterior of the housing through which molten metal exits the casing. An impeller, also called a rotor, is mounted at least partially in the pump chamber and is connected to a drive system. The drive shaft is typically (a) an impeller shaft having one end connected to the impeller and the other end connected to a coupling, and (b) a motor shaft having one end connected to a motor (such as an electric, hydraulic, or pneumatic motor) and the other end connected to the coupling. Often, the impeller (or rotor) shaft is comprised of graphite and/or ceramic (such as silicon carbide), the motor shaft is comprised of steel, and the coupling is comprised of steel.

As the motor turns the drive shaft, the drive shaft turns the impeller and the impeller pushes molten metal out of the pump chamber, through the discharge, out of the outlet and into the molten metal bath. Most molten metal pumps are gravity fed, wherein gravity forces molten metal through the

inlet and into the pump chamber as the impeller pushes molten metal out of the pump chamber.

Some molten metal pumps do not include a base or support posts and are sized to fit into a structure by which molten metal is pumped. Most pumps have a metal platform, or superstructure, that is either supported by a plurality of support posts attached to the pump base, or supported by another structure if there is no pump base. The motor is positioned on the superstructure, if a superstructure is used.

This application incorporates by reference the portions of the following documents that are not inconsistent with this disclosure: U.S. Pat. No. 4,598,899, issued Jul. 8, 1986, to Paul V. Cooper, U.S. Pat. No. 5,203,681, issued Apr. 20, 1993, to Paul V. Cooper, U.S. Pat. No. 5,308,045, issued May 3, 1994, to Paul V. Cooper, U.S. Pat. No. 5,662,725, issued Sep. 2, 1997, to Paul V. Cooper, U.S. Pat. No. 5,678,807, issued Oct. 21, 1997, to Paul V. Cooper, U.S. Pat. No. 6,027,685, issued Feb. 22, 2000, to Paul V. Cooper, U.S. Pat. No. 6,124,523, issued Sep. 26, 2000, to Paul V. Cooper, U.S. Pat. No. 6,303,074, issued Oct. 16, 2001, to Paul V. Cooper, U.S. Pat. No. 6,689,310, issued Feb. 10, 2004, to Paul V. Cooper, U.S. Pat. No. 6,723,276, issued Apr. 20, 2004, to Paul V. Cooper, U.S. Pat. No. 7,402,276, issued Jul. 22, 2008, to Paul V. Cooper, U.S. Pat. No. 7,470,392, issued Dec. 30, 2008, to Paul V. Cooper, U.S. Pat. No. 7,507,367, issued Mar. 24, 2009, to Paul V. Cooper, U.S. Pat. No. 7,906,068, issued Mar. 15, 2011, to Paul V. Cooper, U.S. Pat. No. 8,075,837, issued Dec. 13, 2011, to Paul V. Cooper, U.S. Pat. No. 8,110,141, issued Feb. 7, 2012, to Paul V. Cooper, U.S. Pat. No. 8,178,037, issued May 15, 2012, to Paul V. Cooper, U.S. Pat. No. 8,337,746, issued Dec. 25, 2012, to Paul V. Cooper, U.S. Pat. No. 8,361,379, issued Jan. 29, 2013, to Paul V. Cooper, U.S. Pat. No. 8,366,993, issued Feb. 5, 2013, to Paul V. Cooper, U.S. Pat. No. 8,409,495, issued Apr. 2, 2013, to Paul V. Cooper, U.S. Pat. No. 8,440,135, issued May 15, 2013, to Paul V. Cooper, U.S. Pat. No. 8,444,911, issued May 21, 2013, to Paul V. Cooper, U.S. Pat. No. 8,449,814, issued May 28, 2013, to Paul V. Cooper, U.S. Pat. No. 8,475,708, issued Jul. 2, 2013, to Paul V. Cooper, U.S. Pat. No. 8,501,084, issued Aug. 6, 2013, to Paul V. Cooper, U.S. patent application Ser. No. 12/895,796, filed Sep. 30, 2010, to Paul V. Cooper, U.S. patent application Ser. No. 13/791,952, filed Mar. 9, 2013, to Paul V. Cooper, U.S. Pat. No. 8,529,828, issued Sep. 10, 2013, to Paul V. Cooper, U.S. Pat. No. 8,535,603 issued Sep. 17, 2013, to Paul V. Cooper, U.S. Pat. No. 8,613,884, issued Dec. 24, 2013 to Paul V. Cooper, U.S. Pat. No. 8,714,914, issued May 6, 2014 to Paul V. Cooper, U.S. Pat. No. 8,753,563, issued Jun. 17, 2014, to Paul V. Cooper, U.S. Pat. No. 9,011,761, issued Apr. 21, 2015, to Paul V. Cooper, U.S. Pat. No. 9,017,597, issued Apr. 28, 2015, to Paul V. Cooper, U.S. Pat. No. 9,034,244, issued May 19, 2015, to Paul V. Cooper, U.S. Pat. No. 9,080,577, issued Jul. 14, 2015, to Paul V. Cooper, U.S. Pat. No. 9,108,244, issued Aug. 18, 2015, to Paul V. Cooper, U.S. Pat. No. 9,156,087, issued Oct. 13, 2015, to Paul V. Cooper, U.S. Pat. No. 9,205,490, issued Dec. 8, 2015, to Paul V. Cooper, U.S. Pat. No. 9,328,615, issued May 3, 2016 to Paul V. Cooper, U.S. Pat. No. 9,377,028, issued Jun. 28, 2016, to Paul V. Cooper, U.S. Pat. No. 9,382,599, issued Jul. 5, 2016, to Paul V. Cooper, U.S. Pat. No. 9,383,140, issued Jul. 5, 2016, to Paul V. Cooper, U.S. Pat. No. 9,409,232, issued Aug. 9, 2016, to Paul V. Cooper, U.S. Pat. No. 9,410,744, issued Aug. 9, 2016, to Paul V. Cooper, U.S. Pat. No. 9,422,942, issued Aug. 23, 2016, to Paul V. Cooper, U.S. Pat. No. 9,435,343, issued Sep. 6, 2016, to Paul V. Cooper, U.S. Pat. No. 9,464,636, issued Oct. 11, 2016, to Paul V. Cooper, U.S. Pat. No.

9,470,239, issued Oct. 18, 2016, to Paul V. Cooper, 9,481, 035, issued Nov. 1, 2016, to Paul V. Cooper, U.S. Pat. No. 9,482,469, issued Nov. 1, 2016, to Paul V. Cooper, U.S. Pat. No. 9,506,129, issued Nov. 29, 2016, to Paul V. Cooper, U.S. Pat. No. 9,566,645, issued Feb. 14, 2017, to Paul V. Cooper, 9,581,388, issued Feb. 28, 2017, to Paul V. Cooper, U.S. Pat. No. 9,587,883, issued Mar. 7, 2017, to Paul V. Cooper, U.S. Pat. No. 9,643,247, issued May 9, 2017, to Paul V. Cooper, U.S. Pat. No. 9,657,578, issued May 23, 2017, to Paul V. Cooper, U.S. Pat. No. 9,855,600, issued Jan. 2, 2018, to Paul V. Cooper, U.S. Pat. No. 9,862,026, issued Jan. 9, 2018, to Paul V. Cooper, U.S. Pat. No. 9,903,383, issued Feb. 27, 2018, to Paul V. Cooper, U.S. Pat. No. 9,909,808, issued Mar. 6, 2018, to Paul V. Cooper, U.S. Pat. No. 9,925,587, issued Mar. 27, 2018, to Paul V. Cooper, entitled U.S. Pat. No. 9,982,945, issued May 29, 2018, to Paul V. Cooper, U.S. Pat. No. 10,052,688, issued Aug. 21, 2018, to Paul V. Cooper, U.S. Pat. No. 10,072,891, issued Sep. 11, 2018, to Paul V. Cooper, U.S. Pat. No. 10,126,058, issued Nov. 13, 2018, to Paul V. Cooper, U.S. Pat. No. 10,126,059, issued Nov. 13, 2018, to Paul V. Cooper, U.S. Pat. No. 10,138,892, issued Nov. 27, 2018, to Paul V. Cooper, U.S. Pat. No. 10,195,664, issued Feb. 5, 2019, to Paul V. Cooper, U.S. Pat. No. 10,267,314, issued Apr. 23, 2019, to Paul V. Cooper, U.S. Pat. No. 10,274,256, issued Apr. 30, 2019, to Paul V. Cooper, U.S. Pat. No. 10,302,361, issued May 28, 2019, to Paul V. Cooper, U.S. Pat. No. 10,309,725, issued Jun. 4, 2019, to Paul V. Cooper, U.S. Pat. No. 10,307,821, issued Jun. 4, 2019, to Paul V. Cooper, U.S. Pat. No. 10,322,451, issued Jun. 18, 2019, to Paul V. Cooper, U.S. Pat. No. 10,345,045, issued Jul. 9, 2019, to Paul V. Cooper, U.S. Pat. No. 10,352,620, issued Jul. 16, 2019, to Paul V. Cooper, U.S. Pat. No. 10,428,821, issued Oct. 1, 2019, to Paul V. Cooper, U.S. Pat. No. 10,458,708, issued Oct. 29, 2019, to Paul V. Cooper, U.S. Pat. No. 10,465,688, issued Nov. 5, 2019, to Paul V. Cooper, U.S. Pat. No. 10,562,097, issued Feb. 18, 2020, to Paul V. Cooper, U.S. Pat. No. 10,570,745, issued Feb. 25, 2020, to Paul V. Cooper, U.S. Pat. No. 10,641,279, issued May 5, 2020, to Paul V. Cooper, U.S. Pat. No. 10,641,270, issued May 5, 2020, to Paul V. Cooper, U.S. Pat. No. 10,675,679, issued Jun. 9, 2020, to Paul V. Cooper, U.S. Pat. No. 10,947,980, issued May 16, 2021, to Paul V. Cooper, U.S. Pat. No. 11,020,798, issued Jun. 1, 2021, to Paul V. Cooper, U.S. Pat. No. 11,098,719, issued Aug. 24, 2021, to Paul V. Cooper, U.S. Pat. No. 11,098,720, issued Aug. 24, 2021, to Paul V. Cooper, U.S. Pat. No. 11,103,920, issued Aug. 31, 2021, to Paul V. Cooper, U.S. Pat. No. 11,130,173, issued Sep. 28, 2021, to Paul V. Cooper, U.S. Pat. No. 11,149,747, issued Oct. 19, 2021, to Paul V. Cooper, U.S. Pat. No. 11,167,345, issued Nov. 9, 2021, to Paul V. Cooper, U.S. Pat. No. 11,185,916, issued Nov. 30, 2021, to Paul V. Cooper, U.S. Pat. No. 11,286,939, issued Mar. 29, 2022, to Paul V. Cooper, U.S. Pat. No. 11,391,293, issued Jul. 19, 2022, to Paul V. Cooper, U.S. Pat. No. 11,471,938, issued Oct. 18, 2022, to Paul V. Cooper, U.S. Pat. No. 11,358,216, issued Jun. 14, 2022, to Paul V. Cooper, U.S. Pat. No. 11,358,217, issued Jun. 14, 2022, to Paul V. Cooper, U.S. Pat. No. 11,519,414, issued Dec. 6, 2022, to Paul V. Cooper, U.S. Pat. No. 11,759,854, issued Sep. 19, 2023, to Paul V. Cooper, U.S. Pat. No. 11,759,853, issued Sep. 19, 2023, to Paul V. Cooper, U.S. patent application Ser. No. 16/413,142, filed May 15, 2019, by Paul V. Cooper, U.S. patent application Ser. No. 16/533,383, filed Aug. 6, 2019, by Paul V. Cooper, U.S. patent application Ser. No. 16/533,404, filed Aug. 6, 2019, by Paul V. Cooper, U.S. patent application Ser. No. 16/877,267, filed May 18, 2020, by Paul V. Cooper, U.S. patent application Ser. No. 16/877,364, filed

May 18, 2020, by Paul V. Cooper, U.S. patent application Ser. No. 17/200,785, filed Mar. 13, 2021, by Paul V. Cooper, U.S. patent application Ser. No. 17/334,259, filed May 28, 2021, by Paul V. Cooper, U.S. patent application Ser. No. 17/496,229, filed Oct. 7, 2021, by Paul V. Cooper, U.S. patent application Ser. No. 17/703,912, filed Mar. 24, 2022, by Paul V. Cooper, U.S. patent application Ser. No. 17/719,274, filed Apr. 12, 2022, by Paul V. Cooper, U.S. patent application Ser. No. 17/826,111, filed May 26, 2022, by Paul V. Cooper, U.S. patent application Ser. No. 17/939,898 filed Sep. 7, 2022, by Vince Fontana, U.S. patent application Ser. No. 18/114,665, filed Feb. 27, 2023, by Paul V. Cooper, U.S. patent application Ser. No. 18/139,936, filed Apr. 26, 2023, by Paul V. Cooper, U.S. patent application Ser. No. 18/480,755, filed Oct. 4, 2023, by Vince Fontana, U.S. patent application Ser. No. 18/502,457, filed Nov. 6, 2023, by Paul V. Cooper.

Three basic types of pumps for pumping molten metal, such as molten aluminum, are utilized: circulation pumps, transfer pumps and gas-release pumps. Circulation pumps are used to circulate the molten metal within a bath, thereby generally equalizing the temperature of the molten metal. Circulation pumps may be used in any vessel, such as in a reverberatory furnace having an external well. The well is usually an extension of the charging well, in which scrap metal is charged (i.e., added).

Standard transfer pumps are generally used to transfer molten metal from one structure to another structure such as a ladle or another furnace. A standard transfer pump has a riser tube connected to a pump discharge and supported by the superstructure. As molten metal is pumped it is pushed up the riser tube (sometimes called a metal-transfer conduit) and out of the riser tube, which generally has an elbow at its upper end, so molten metal is released into a different vessel from which the pump is positioned. Alternate transfer pumping systems can pump molten metal upwards to a launder, which can greatly eliminate turbulence and resulting dross.

Gas-release pumps, such as gas-injection pumps, circulate molten metal while introducing a gas into the molten metal. In the purification of molten metals, particularly aluminum, it is frequently desired to remove dissolved gases such as hydrogen, or dissolved metals, such as magnesium. As is known by those skilled in the art, the removing of dissolved gas is known as "degassing" while the removal of magnesium is known as "demagging." Gas-release pumps may be used for either of both of these purposes or for any other application for which it is desirable to introduce gas into molten metal.

Gas-release pumps generally include a gas-transfer conduit having a first end that is connected to a gas source and a second end submerged in the molten metal bath. Gas is introduced into the first end and is released from the second end into the molten metal. The gas may be released downstream of the pump chamber into either the pump discharge or a metal-transfer conduit extending from the discharge, or into a stream of molten metal exiting either the discharge or the metal-transfer conduit. Alternatively, gas may be released into the pump chamber or upstream of the pump chamber at a position where molten metal enters the pump chamber. The gas may also be released into any suitable location in a molten metal bath.

Molten metal pump casings and rotors often employ a bearing system comprising ceramic rings wherein there are one or more rings on the rotor that align with rings in the pump chamber (such as rings at the inlet and outlet) when the rotor is placed in the pump chamber. The purpose of the

bearing system is to reduce damage to the soft, graphite components, particularly the rotor and pump base, during pump operation.

Generally, a degasser (also called a rotary degasser) includes (1) an impeller shaft having a first end, a second end and a passage for transferring gas, (2) an impeller, and (3) a drive source for rotating the impeller shaft and the impeller. The first end of the impeller shaft is connected to the drive source and to a gas source and the second end is connected to the impeller.

Generally a scrap melter includes an impeller affixed to an end of a drive shaft, and a drive source attached to the other end of the drive shaft for rotating the shaft and the impeller. The movement of the impeller draws molten metal and scrap metal downward into the molten metal bath in order to melt the scrap. A circulation pump is preferably used in conjunction with the scrap melter to circulate the molten metal in order to maintain a relatively constant temperature within the molten metal.

The materials forming the components that contact the molten metal bath should remain relatively stable in the bath. Structural refractory materials, such as graphite or ceramics, that are resistant to disintegration by corrosive attack from the molten metal may be used. As used herein "ceramics" or "ceramic" refers to any oxidized metal (including silicon) or carbon-based material, excluding graphite, or other ceramic material capable of being used in the environment of a molten metal bath. "Graphite" means any type of graphite, whether or not chemically treated. Graphite is particularly suitable for being formed into pump components because it is (a) soft and relatively easy to machine, (b) not as brittle as ceramics and less prone to breakage, and (c) less expensive than ceramics.

Ceramic, however, is more resistant to corrosion by molten aluminum than graphite. It would therefore be advantageous to develop vertical members used in a molten metal device that are comprised of ceramic, but less costly than solid ceramic members, and less prone to breakage than normal ceramic.

## SUMMARY

Devices are disclosed that have increased resistance to breakage. One device comprises at least one tension rod positioned inside an outer core. The tension rod and optionally other structures apply tension (or compressive force) to the outer core in order to make it more resistant to breakage. In this disclosure, the tension rod is preferably tightened by in part using a molten metal pump superstructure (also called a platform) that supports the motor. All or most of the outer core is on the side of the superstructure opposite the surface on which the pump is positioned.

The tension rod may be affixed to the outer core by being affixed to a first block of material at the top of the outer core, and affixed to a second block of material at the bottom of the outer core. When the tension rod is tightened, it draws the first block and the second block together which applies axial compressive force to the outer core.

The outer core can be compressed in any suitable manner. If the first block and second block are utilized, the tension rod may be affixed to each by a bolt or other device attached to, and preferably having an area at least about 30% to 150% greater than the cross-sectional area of the tension rod. The bolt or other device could be inside or outside of the first block and/or second block.

A device according to this disclosure, such as a support post or impeller shaft, includes an outer core made of

structural refractory material, such as graphite, graphitized carbon, clay-bonded graphite, carbon-bonded graphite, silicon carbide, ceramics, or the like. The outer core has a first end and a second end and the tension rod includes a first end and a second end. At least one end of the tension rod can extend beyond and terminate outside of the one end of the outer core. Either the first end or the second end of the tension rod, or both, can be tightened against a superstructure. This puts the outer core under compression, and makes the outer core more resistant to breakage. By using the system of the invention, it is also possible to use a thinner cross-sectional outer core wall, thereby reducing material costs.

Also disclosed is a device, such as a support post, for use in molten metal that includes a reinforcement section to strengthen the device and help alleviate breakage.

Also disclosed are molten metal pumps that include one or more devices disclosed herein.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side, partial cross-sectional view of a support post according to this disclosure.

FIG. 2 is a side, partial cross-sectional view of the support post of FIG. 1 being mounted to a pump superstructure.

FIG. 2B is an optional bottom portion of the support post of FIGS. 1 and 2.

FIG. 2C is a top view of the bottom portion of the support post of FIG. 2B.

FIG. 2D is a cross-sectional view taken along lines D-D of FIG. 2C.

FIG. 2E is a cross-sectional view taken along lines E-E of FIG. 2C.

FIG. 3 is a side view of an alternate support post according to this disclosure.

FIG. 4 is a side, cross-sectional view of the support post of FIG. 3.

FIG. 5 is a top view of the support post of FIG. 3.

FIG. 6 is a partial, side view of the support post of FIG. 3 without the outer casing.

FIG. 7 is a partial, side view of the support post of FIG. 3 without the outer casing.

FIG. 8 is a top view of the support post of FIG. 6.

FIG. 9 is a close up view of detail B of FIG. 7.

FIG. 10 is a side view taken along lines A-A of FIG. 7.

FIG. 11 is a bottom view of the support post of FIGS. 6 and 7.

FIG. 11A is an end view of the support post of FIG. 11.

FIG. 12 is a cross-sectional side view of the support post of FIG. 11 taken along lines E-E.

FIG. 13 is a side view of an alternate support post according to this disclosure.

FIG. 14 is an exploded view of the support post of FIG. 13.

FIG. 15 is a top view of the support post of FIG. 13.

FIG. 16 is a cross-sectional, partial side view of the support post of FIG. 15 taken along lines A-A.

FIG. 17 is a close-up view of detail B shown in FIG. 16.

FIG. 18 is a close-up view of detail C shown in FIG. 16.

FIG. 19 is a side view of the base of the support post of FIGS. 3 and 6.

FIG. 20 is a top view of the base of FIG. 19.

FIG. 21 is a cross-sectional side view taken along line D-D of FIG. 20.

FIG. 22 is a cross-sectional side view taken along line E-E of FIG. 20.

7

FIG. 23 is a perspective, side view of an outer core according to this disclosure.

FIG. 24 is a top view of the outer core of FIG. 23.

FIG. 25 is a side, cross-sectional view of the outer core taken along line F-F of FIG. 24.

FIG. 26 is a perspective side view of a tension rod according to this disclosure.

FIG. 27 is a partial, side view of the tension rod of FIG. 26.

FIG. 28 is a perspective, top view of a support post top according to this disclosure.

FIG. 29 is a top view of the support post top of FIG. 28.

FIG. 30 is a side, cross-sectional view taken along line G-G of FIG. 29.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

For any device described herein, any of the components that contact the molten metal are preferably formed by a material that can withstand the molten metal environment. Preferred materials are oxidation-resistant graphite and ceramic, such as silicon carbide.

FIG. 1 shows a support post 10 in accordance with aspects of the disclosure. Shaft has an outer core 50 that has axial tension applied to it to make outer core 50 more resistant to breakage. Similar techniques, however, may be used to tension rotor shafts or other elongate molten metal pump components. Shaft 10 has a tension rod 20, a top support block 30, a bottom support block 60, an outer core 50, and a bottom 70.

Tension rod 20 is preferably comprised of steel and has a body 24, a first end 24 and a second end 26. As shown, tension rod 20 is threaded along about 5% to 25% of its length starting at first end 24 and moving upward, and along about 10% to 25% of its length starting at second end 26 and moving downward. The threaded portion 24A juxtaposed end 24 is preferably configured to be threaded into a channel 64 in second end 60 and into channel 76A in section 76. Portion 24A need only have sufficient threads to anchor it in second end 60 and/or section 76. Alternatively, shaft 20 need not be threaded into second end 60 and/or section 76, but could instead pass through them and be retained by nut 85 (or other suitable fastener) in section 76 or section 74.

Threaded portion 26A can optionally be threaded partially into bore 39 of top block 30. Nut 40 and nut 120 are threaded onto portion 26A as further described.

Tension rod 20 includes a top, threaded portion 26A that (as shown) threaded partially into top block 30. Top block 30 has an upper portion 34, a top surface 35, an opening 32, a sleeve 38, an internal wall surface 36, and a passage 39. Upper portion 34 is on top of and outside of outer core 50, and surface 36 rests on the top 52 to apply axial tension to outer core 50. Passage 39 is configured so rod 20 can pass therethrough. Opening 32 is formed in top surface 35, is preferably about 1.5 to 2.5 times the diameter of rod 20, and extends into top block 30 from upper surface 35 by about 1" to 3", although opening 32 can be of any suitable dimension. Sleeve 38 fits inside of outer coating 50 and extends downward about 10-30% of the length (although any suitable distance would work, or top block 30 could be stabilized in another manner) of outer coating 50 in order to stabilize top block 30 to outer coating 50.

Channels 80 and 82 are for injecting cement into the bottom of support post 20 to help connect it to a molten metal pump base in a manner known in the art. Any suitable molten metal pump base could be utilized.

8

FIG. 2 shows the support post 10 of FIG. 1 being connected to a superstructure 100 of a molten metal pump, wherein the superstructure 100 supports the pump motor. The superstructure 100 is preferably a steel plate or platform, and is known in the art. Here, it has an opening 102 formed therethrough, a bottom surface 104, and a top surface 106. To add additional tension to outer core 50, a compression spring 110 and nut 120 are positioned on tension rod 20 above surface 106. Nut 120 is then tightened, which ultimately tightens surface 35 of top block 30 against bottom surface 104. Spring 110 need not be used but it or a similar flexible structure is preferred.

Outer core 50 could instead be comprised of graphite and/or blocks 30 and 60 could be comprised of ceramic. Further, any of sections 72, 74, 76 could be comprised of graphite or ceramic.

FIGS. 3-5 show an alternate support post 200 with graphite core 210 and an outer ceramic (preferably silicon carbide) core 250. Alternatively, core 210 could be comprised of ceramic and/or outer core 250 could be comprised of graphite. A reinforcement member 300 is positioned in graphite core 210. In this embodiment outer core 250 is optional. Further, there may be more than one reinforcement member at either one end, or both ends of core 210. Or core 210 could have a single reinforcement member at each end or that extends therethrough or substantially therethrough.

As shown, the reinforcement member 300 is positioned in a manner, and is comprised of a material, such that it helps prevent the core 210 from breaking. Reinforcement member 300 is preferably comprised of steel, has a length of about 10% to 35%, or 15%-25% of the length of core 210, or a length of about 8" to 12", 10" to 16", or 12" to 16", and the cylindrical with a diameter about  $\frac{1}{10}$ ",  $\frac{1}{8}$ ",  $\frac{1}{6}$ ",  $\frac{1}{4}$ " or  $\frac{1}{2}$ ", or about 10%-30% the diameter of portion 214 of core 210.

Core 210 has a top end 212, a bottom end 214, a top section 212A, a bottom section 214A, and a central portion 216. A bore 220 is formed in core 210 and extends from end 214, preferably through bottom section 214A and partially into section 216. As shown, bore 220 is formed in the center of core 210, although it could be off center.

Reinforcement member 300 is positioned in bore 220 and may be secured by cement. Member 300 has a first end 302 that is preferably tapered and a second end 304. As shown, second end 304 is wider than the body portion 306. A cap 230 is positioned over second end 304 and preferably cemented in place to prevent molten metal from contacting reinforcement member 300. All or part of body portion 306 may be threaded so that member 300 is threaded into bore 220. As shown in FIG. 12, reinforcement member has a smaller-diameter portion 306A that is threaded. Portion 306A is threaded into smaller diameter portion 220A of bore 220. Larger diameter bore portion 220B receives second end 204.

Bores 250 and 252 are for connecting first end 212 of support post 200 to a support post clamp preferably positioned above the superstructure of a molten metal pump.

Some non-limiting examples of the disclosure are as follows:

Example 1: A component for use in a molten metal pump, the component comprising:

- an outer core constructed of graphite or ceramic;
- a tension rod positioned partially inside the outer core, wherein the tension rod has a first end and a second end, and is configured to apply an axial compressive force to the outer core in order to make the outer core less susceptible to breakage;

wherein the first end of the tension rod extends beyond the outer core and has an axially-compressive component positioned thereon, the axially-compressive component positioned against the outer core to place an axial-compressive force on the outer core.

Example 2: The component of example 1, wherein the tension rod has a first end and a second end, the outer core has a first end and a second end, and at least one of the first end or second end of the tension rod extends beyond either the first end or second end of the outer core.

Example 3: The component of example 2, wherein either the first end or the second end of the outer core has a cap, and the end of the tension rod that extends beyond the end of the outer core is tightened against the cap.

Example 4: The component of example 1, wherein the tension rod comprises at least one elongate, metal rod.

Example 5: The component of example 4, wherein the tension rod is comprised of steel.

Example 6: The component of example 1 that is a molten metal pump support post.

Example 7: The component of example 1, wherein the tension rod is secured in the outer core by cement.

Example 8: The component of example 7, wherein the tension rod is bonded to the outer core by the cement.

Example 9: The component of example 1, wherein the outer core comprises graphite.

Example 10: The component of example 1, wherein the outer core comprises silicon carbide.

Example 11: The component of example 1, wherein the outer core comprises material harder than graphite.

Example 12: The component of example 1, wherein the second end of the tension rod is inside of the outer core.

Example 13: The component of example 1, wherein the first end of the tension rod is threaded and the first axially-compressive component is a nut threaded onto the tension rod and tightened against the outer core.

Example 14: The component of example 1 that further includes a second axially-compressive component on the second end of the tension rod.

Example 15: The component of example 1, wherein the second end of the tension rod is threaded and that further comprises a second axially-compressive component at the second end of the tension rod.

Example 16: The component of example 15, wherein the second end of the tension rod is threaded and the second axially-compressive component is a nut threaded into the second end.

Example 17: The component of example 13, wherein the nut is hexagonal.

Example 18: The component of example 16, wherein the nut is hexagonal.

Example 19: The component of example 1 that further comprises a first support block at the first end of the outer core.

Example 20: The component of example 19, wherein the second axially-compressive component is positioned inside of the second support block.

Example 21: The component of example 19, wherein the first support block has a narrow portion positioned inside of the outer core and an enlarged portion that presses against at least part of the wall of the outer core.

Example 22: The component of example 20, wherein the second support block has an extension positioned inside of the outer core and an enlarged portion that presses against at least part of the wall of the outer core to provide axially-compressive force to the outer core.

Example 23: The component of example 1, wherein the second end of the extension rod extends beyond a stationary plate and a third axially-compressive component is positioned on the second end of the extension rod on a side of the stationary plate opposite the outer core, and the third axially-compressive component is compressed to the stationary plate.

Example 24: The component of example 23, wherein the stationary plate is a molten metal pump superstructure.

Example 25: The component of example 23 that includes a compression device between the third axially-compressive component and the stationary plate.

Example 26: The component of example 25, wherein the compression device is a spring.

Example 27: The component of example 19, wherein the first support block is comprised of graphite.

Example 28: The component of example 22, wherein the second support block is comprised of graphite.

Example 29: The component of example 20 that further includes a cap at the second end distal to the second axially-compressive component.

Some other non-limiting examples of the disclosure follow:

Example 1: A support post comprising an elongated body having a longitudinal axis and a height, a first end configured to connect to a superstructure and a second end configured to connect to a pump base, wherein the second end comprises at least one reinforcement section configured to make the second end resistant to breakage.

Example 2: The support post of example 1, wherein the at least one reinforcement section is elongated and has a longitudinal axis.

Example 3: The support post of example 2, wherein the longitudinal axis of the at least one reinforcement section is aligned with the longitudinal axis of the support post.

Example 4: The support post of example 1, wherein the support post is comprised of graphite and the at least one reinforcement section is comprised of one or more of the group consisting of: silicon carbide and steel.

Example 5: The support post of example 1, wherein the at least one reinforcement section is completely surrounded by the material of the support post so the reinforcement section is configured not to contact molten metal.

Example 6: The support post of example 1, wherein the at least one reinforcement section is less than 50% of the height of the support post.

Example 7: The support post of example 1, wherein the at least one reinforcement section is between 15%-35% of the height of the support post.

Example 8: The support post of example 1, wherein the at least one reinforcement section is between 15%-25% of the height of the support post.

Example 9: The support post of example 1, wherein the at least one reinforcement section has a cross-sectional area that is between  $\frac{1}{4}$  and  $\frac{1}{10}$  the cross-sectional area of the second end of the support post.

Example 10: The support post of example 1, wherein the at least one reinforcement section has a cross-sectional area that is between  $\frac{1}{5}$  and  $\frac{1}{8}$  the cross-sectional area of the second end of the support post.

Example 11: The support post of example 1, wherein the support post has a bore in its second end and the at least reinforcement section is positioned in the bore.

Example 12: The support post of example 11 that further includes cement in the bore to anchor the at least one reinforcement section.

## 11

Example 13: The support post of example 1 that further includes a ceramic outer cover.

Example 14: The support post of example 1 that is cylindrical.

Example 15: The support post of example 1, wherein the reinforcement section is cylindrical.

Example 16: The support post of example 1, wherein the second end includes a first portion having a first diameter, and a second portion having a second diameter, wherein the second diameter is less than the first diameter.

Example 17: The support post of example 1, wherein the second end includes a first portion having a first cross-sectional area, and a second portion having a second cross-sectional area is less than the first cross-sectional area.

Example 18: The support post of example 16, wherein the at least one reinforcement section is positioned partially in the first portion and partially in the second portion.

Example 19: The support post of example 17, wherein the reinforcement section is positioned partially in the first portion and partially in the second portion.

Example 20: The support post of example 1 that is cylindrical with a center and the reinforcement section is positioned in the center.

Example 21: The support post of example 1 that further includes one or more channels in the second end, wherein the channels are configured to receive cement.

Example 22: The support post of example 1, wherein the first end is configured to fit into a coupling.

Example 23: The support post of example 11 that further includes a plug at a second tip of the support post, wherein the plug is configured to cover the bore.

Example 24: The support post of example 1 that includes a single reinforcement section.

Example 25: The support post of example 1, wherein the at least one reinforcement section is concrete, positioned in a bore inside of the second end of the support post.

Example 26: The support post of example 1, wherein the at least one reinforcement section extends the length of the support post.

Example 27: The support post of example 1, wherein the at least one reinforcement section has an outer surface including threads, wherein the at least one reinforcement section is threadingly received in the support post.

Example 28: The support post of example 27, wherein the threads are received in the support post at its first diameter and first cross-sectional area.

Example 29: The support post of example 27, wherein the at least one reinforcement section has a length and the threads extend along the entire length.

Example 30: The support post of example 27, wherein the at least one reinforcement section has a length and the threads extend at least 50% of the length.

Example 31: The support post of example 27, wherein the at least one reinforcement section has a length and the threads extend at least 25% of the length.

Example 32: The support post of example 1 that has one or more air-relief grooves.

Example 33: The support post of example 32 that has two air-relief grooves.

Example 34: The support post of example 16, wherein the second diameter is between 3.5" and 4.5".

Example 35: The support post of example 16, wherein the second portion has a height of between 6.0" and 7.0".

Example 36: The support post of example 1, wherein the reinforcement section has a diameter of between 0.75" and 1.25".

## 12

Having thus described different embodiments, other variations and embodiments that do not depart from the spirit of this disclosure will become apparent to those skilled in the art. The scope of the claims is thus not limited to any particular embodiment, but is instead set forth in the claims and the legal equivalents thereof. Unless expressly stated in the written description or claims, the steps of any method recited in the claims may be performed in any order capable of yielding the desired product. No language in the specification should be construed as indicating that any non-claimed limitation is included in a claim. The terms "a" and "an" in the context of the following claims are to be construed to cover both the singular and the plural, unless otherwise indicated herein.

What is claimed is:

1. A component for use in a molten metal pump, the component comprising:

an inner core and an outer core; and

a tension rod positioned inside the inner core, wherein the tension rod has a first end that is threaded and has a length of 25% or less than a length of the inner core and has a second end that is threaded and has a length that is 25% or less than the length of the inner core, and the tension rod is configured to apply an axial compressive force to the inner core.

2. The component of claim 1, wherein the first end of the tension rod extends beyond the outer core and has an axially-compressive component positioned thereon, the axially-compressive component positioned against the outer core to place an axial-compressive force on the outer core.

3. The component of claim 1, wherein the second end of the tension rod is threaded and that further comprises a third axially-compressive component at the second end of the tension rod.

4. The component of claim 3, wherein the third axially-compressive component is positioned inside of a support block.

5. The component of claim 4, wherein the support block has an extension positioned inside of the outer core and an enlarged portion that presses against at least part of the wall of the outer core to provide axially-compressive force to the outer core.

6. The component of claim 1, wherein the outer core has a first end and a second end, and at least one of the first end or second end of the tension rod extends beyond either the first end or second end of the outer core.

7. The component of claim 6, wherein either the first end or the second end of the outer core has a cap, and each end of the tension rod that extends beyond the end of the outer core is tightened against the cap.

8. The component of claim 1, wherein the tension rod comprises at least one elongate, metal rod.

9. The component of claim 1, wherein the tension rod is comprised of steel.

10. The component of claim 1 that is a molten metal pump support post.

11. The component of claim 1, wherein the outer core comprises graphite.

12. The component of claim 1, wherein the outer core comprises silicon carbide.

13. The component of claim 1, wherein the outer core comprises material harder than graphite.

14. The component of claim 1, wherein the first end of the tension rod is threaded and the first axially-compressive component is a nut threaded onto the tension rod and tightened against the outer core.



**15.** The component of claim **1**, wherein the inner core has one or more bores that are configured to receive the tension rod.

**16.** The component of claim **1**, wherein the second end of the extension rod extends beyond a stationary plate and a second axially-compressive component is positioned on the second end of the extension rod on a side of the stationary plate opposite the outer core, and the second axially-compressive component is compressed to the stationary plate.

**17.** The component of claim **16**, wherein the stationary plate is a molten metal pump superstructure.

**18.** The component of claim **16** that includes a compression device between the second axially-compressive component and the stationary plate.

**19.** The component of claim **18**, wherein the compression device is a spring.

**20.** The component of claim **19** that further includes a cap at the second end distal to the second axially-compressive component.

\* \* \* \* \*