

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250255434

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Masek; Douglas W. et al.

ADJUSTABLE WARMING RACKS FOR COOKBOXES OF GRILLS

Abstract

Example adjustable warming racks for cookboxes of grills are disclosed. An example warming rack is configured to be coupled to a cookbox of a grill. The example warming rack includes a first rack and a second rack. The first rack is couplable to the cookbox. The second rack is pivotally coupled to the first rack. The second rack is movable relative to the first rack to transition the warming rack between an expanded configuration and a collapsed configuration.

Inventors: Masek; Douglas W. (Palatine, IL), Keclik; James (McHenry, IL), Graef; Michael A. (Aurora, IL), Mathews; Brian (Sycamore, IL), Mellas; Nathan (Lenoir City, TN), Nanos, JR.; Nicholas M. (Crystal Lake, IL)

Applicant: Weber-Stephen Products LLC (Palatine, IL)

Family ID: 1000008575242

Appl. No.: 19/196012

Filed: May 01, 2025

Related U.S. Application Data

parent US continuation 18672700 20240523 parent-grant-document US 12318039 child US 19196012

parent US continuation 17472271 20210910 parent-grant-document US 12029349 child US 18672700

us-provisional-application US 63120535 20201202

us-provisional-application US 63203923 20210804

Publication Classification

Int. Cl.: A47J37/07 (20060101)

Background/Summary

RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/672,700, filed May 23, 2024, which is a continuation of U.S. patent application Ser. No. 17/472,271, filed Sep. 10, 2021, which claims priority to U.S. Provisional Patent Application No. 63/203,923, filed Aug. 4, 2021, and to U.S. Provisional Patent Application No. 63/120,535, filed Dec. 2, 2020. The entireties of U.S. patent application Ser. No. 18/672,700, U.S. patent application Ser. No. 17/472,271, U.S. Provisional Patent Application No. 63/203,923, and U.S. Provisional Patent Application No. 63/120,535 are hereby incorporated by reference herein.

FIELD OF THE DISCLOSURE

[0002] This disclosure relates generally to warming racks and, more specifically, to adjustable warming racks for cookboxes of grills.

BACKGROUND

[0003] Cookboxes of grills (e.g., gas grills, charcoal grills, pellet grills, electric grills, etc.) are conventionally equipped with one or more cooking grate(s) that define a cooking surface. The cooking surface defined by the cooking grate(s) typically fills, covers, and/or occupies the substantial entirety of an upper opening of the cookbox. In some instances, such grills are additionally equipped with a warming rack coupled to a rear wall and/or to right and left sidewalls of the cookbox, with the warming rack being positioned at a vertical elevation and/or height above the vertical elevation and/or height of the cooking grate(s). The warming rack typically has a form factor and/or footprint (e.g., as defined by the width and the depth of the warming rack) that is substantially smaller than (e.g., less than half of) the form factor and/or footprint of the cooking grate(s) (e.g., as defined by the width(s) and the depth(s) of the cooking grate(s)).

[0004] Known warming racks for cookboxes of grills are typically configured such that the warming rack is stationary relative to the cookbox, with the warming rack having a fixed, non-adjustable form factor and/or footprint. Such stationary, non-adjustable warming rack implementations can negatively impact the user experience associated with the grill itself, and/or with various cooking operations to be performed using the grill. For example, a user may find the form factor and/or footprint of the warming rack to be too small to adequately support one or more food item(s) that the user would like to place on the warming rack. The stationary, non-adjustable form factor and/or footprint of the warming rack typically leaves the user with no recourse by which to expand the form factor and/or footprint of the warming rack to adequately support the desired food item(s). As another example, a user may find the form factor and/or footprint of the warming rack to be obstructive and/or too large with regard to one or more food item(s) that the user would like to place on the cooking grate(s) of the grill located below the warming rack. Aside from the less-than-ideal option of physically removing the warming rack from the cookbox of the grill, the stationary, non-adjustable form factor and/or footprint of the warming rack typically leaves the user with no other recourse by which to reduce the form factor and/or footprint of the warming rack relative to the cooking grate(s) to provide adequate clearance for the desired food item(s).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] FIG. **1** is a perspective view of an example warming rack constructed in accordance with teachings of this disclosure, with the warming rack shown positioned in an example expanded configuration.

[0006] FIG. **2** is a top view of the warming rack of FIG. **1**, with the warming rack shown positioned in the expanded configuration of FIG. **1**.

[0007] FIG. **3** is a bottom view of the warming rack of FIGS. **1** and **2**, with the warming rack shown positioned in the expanded configuration of FIGS. **1** and **2**.

[0008] FIG. **4** is a right side view of the warming rack of FIGS. **1-3**, with the warming rack shown positioned in the expanded configuration of FIGS. **1-3**.

[0009] FIG. **5** is a perspective view of the warming rack of FIGS. **1-4**, with the warming rack shown positioned in an example collapsed configuration.

[0010] FIG. **6** is a top view of the warming rack of FIGS. **1-5**, with the warming rack shown positioned in the collapsed configuration of FIG. **5**.

[0011] FIG. **7** is a bottom view of the warming rack of FIGS. **1-6**, with the warming rack shown positioned in the collapsed configuration of FIGS. **5** and **6**.

[0012] FIG. **8** is a right side view of the warming rack of FIGS. **1-7**, with the warming rack shown positioned in the collapsed configuration of FIGS. **5-7**.

[0013] FIG. **9** is a perspective view of an example grill having an example cookbox configured to support the warming rack of FIGS. **1-8**.

[0014] FIG. **10** is a first perspective view of the cookbox of FIG. **9**, with the warming rack shown positioned in the expanded configuration of FIGS. **1-4** and further positioned in an example horizontal orientation.

[0015] FIG. **11** is a second perspective view of the cookbox of FIGS. **9** and **10**, with the warming rack shown positioned in the expanded configuration of FIGS. **1-4** and **10** and the horizontal orientation of FIG. **10**.

[0016] FIG. **12** is a top view of the cookbox of FIGS. **9-11**, with the warming rack shown positioned in the expanded configuration of FIGS. **1-4**, **10**, and **11** and the horizontal orientation of FIGS. **10-11**.

[0017] FIG. **13** is a cross-sectional view of the cookbox of FIGS. **9-12** taken along section A-A of FIG. **12**, with the warming rack shown positioned in the expanded configuration of FIGS. **1-4** and **10-12** and the horizontal orientation of FIGS. **10-12**.

[0018] FIG. **14** is a first perspective view of the cookbox of FIG. **9**, with the warming rack shown positioned in the collapsed configuration of FIGS. **5-8** and further positioned in an example horizontal orientation.

[0019] FIG. **15** is a second perspective view of the cookbox of FIGS. **9** and **14**, with the warming rack shown positioned in the collapsed configuration of FIGS. **5-8** and **14** and the horizontal orientation of FIG. **14**.

[0020] FIG. **16** is a top view of the cookbox of FIGS. **9**, **14**, and **15**, with the warming rack shown positioned in the collapsed configuration of FIGS. **5-8**, **14**, and **15** and the horizontal orientation of FIGS. **14** and **15**.

[0021] FIG. **17** is a cross-sectional view of the cookbox of FIGS. **9** and **14-16** taken along section B-B of FIG. **16**, with the warming rack shown positioned in the collapsed configuration of FIGS. **5-8** and **14-16** and the horizontal orientation of FIGS. **14-16**.

[0022] FIG. **18** is a first perspective view of the cookbox of FIG. **9**, with the warming rack shown positioned in the collapsed configuration of FIGS. **5-8** and further positioned in an example non-horizontal orientation.

[0023] FIG. **19** is a second perspective view of the cookbox of FIGS. **9** and **18**, with the warming rack shown positioned in the collapsed configuration of FIGS. **5-8** and **18** and the non-horizontal

orientation of FIG. 18.

[0024] FIG. 20 is a top view of the cookbox of FIGS. 9, 18, and 19, with the warming rack shown positioned in the collapsed configuration of FIGS. 5-8, 18, and 19 and the non-horizontal orientation of FIGS. 18 and 19.

[0025] FIG. 21 is a cross-sectional view of the cookbox of FIGS. 9 and 18-20 taken along section C-C of FIG. 20, with the warming rack shown positioned in the collapsed configuration of FIGS. 5-8 and 18-20 and the non-horizontal orientation of FIGS. 18-20.

[0026] FIG. 22 is a perspective view of another example warming rack constructed in accordance with teachings of this disclosure, with the warming rack shown positioned in an example expanded configuration.

[0027] FIG. 23 is a top view of the warming rack of FIG. 22, with the warming rack shown positioned in the expanded configuration of FIG. 22.

[0028] FIG. 24 is a bottom view of the warming rack of FIGS. 22 and 23, with the warming rack shown positioned in the expanded configuration of FIGS. 22 and 23.

[0029] FIG. 25 is a right side view of the warming rack of FIGS. 22-24, with the warming rack shown positioned in the expanded configuration of FIGS. 22-24.

[0030] FIG. 26 is a perspective view of the warming rack of FIGS. 22-25, with the warming rack shown positioned in an example collapsed configuration.

[0031] FIG. 27 is a top view of the warming rack of FIGS. 22-26, with the warming rack shown positioned in the collapsed configuration of FIG. 26.

[0032] FIG. 28 is a bottom view of the warming rack of FIGS. 22-27, with the warming rack shown positioned in the collapsed configuration of FIGS. 26 and 27.

[0033] FIG. 29 is a right side view of the warming rack of FIGS. 22-28, with the warming rack shown positioned in the collapsed configuration of FIGS. 26-28.

[0034] Certain examples are shown in the above-identified figures and described in detail below. In describing these examples, like or identical reference numbers are used to identify the same or similar elements. The figures are not necessarily to scale and certain features and certain views of the figures may be shown exaggerated in scale or in schematic for clarity and/or conciseness.

[0035] Descriptors “first,” “second,” “third,” etc. are used herein when identifying multiple elements or components which may be referred to separately. Unless otherwise specified or understood based on their context of use, such descriptors are not intended to impute any meaning of priority or ordering in time but merely as labels for referring to multiple elements or components separately for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In such instances, it should be understood that such descriptors are used merely for case of referencing multiple elements or components.

DETAILED DESCRIPTION

[0036] Example adjustable warming racks disclosed herein are advantageously configured to be positionable and/or arrangeable in numerous configurations within a cookbox of a grill, with the adjustable warming racks being transitionable from one configuration to another. In some examples, adjustable warming racks disclosed herein are positionable and/or arrangeable in an expanded configuration having an associated horizontal orientation within the cookbox of the grill. Positioning and/or arranging the warming rack in the expanded configuration and its associated horizontal orientation maximizes the usable warming surface of the warming rack, which may be particularly advantageous in instances where a user wants to place a relatively larger sized food item and/or a greater number of food items on the warming rack, and/or in instances where the amount of available vertical clearance space residing above and/or over one or more primary cooking grate(s) of the grill at a location forward of the warming rack is of little or no concern to the user.

[0037] In some examples, adjustable warming racks disclosed herein are additionally or alternatively positionable and/or arrangeable in a collapsed configuration having an associated horizontal orientation within the cookbox of the grill. Positioning and/or arranging the warming rack in the collapsed configuration and its associated horizontal orientation reduces the usable warming surface of the warming rack (e.g., relative to the usable warming surface provided via the expanded configuration and its associated horizontal orientation), which may be particularly advantageous in instances where a user wants to place a relatively smaller sized food item and/or a lesser number of food items on the warming rack, and/or in instances where the amount of available vertical clearance space residing above and/or over the primary cooking grate(s) of the grill at a location forward of the warming rack is of moderate concern to the user.

[0038] In some examples, adjustable warming racks disclosed herein are additionally or alternatively positionable and/or arrangeable in a collapsed configuration having an associated non-horizontal orientation within the cookbox of the grill. Positioning and/or arranging the warming rack in the collapsed configuration and its associated non-horizontal orientation further reduces and/or eliminates the usable warming surface of the warming rack, which may be particularly advantageous in instances where a user does not want to place any food items on the warming rack, and/or in instances where the amount of available vertical clearance space residing above and/or over the primary cooking grate(s) of the grill at a location forward of the warming rack is of great concern to the user.

[0039] Adjustable warming racks disclosed herein accordingly provide enhanced flexibility with regard to the range of cooking operations that can be accommodated and/or performed within a cookbox of a grill. The above-identified features as well as other advantageous features of example adjustable warming racks disclosed herein are further described below in connection with the figures of the application. As used herein, the term “configured” means sized, shaped, arranged, structured, oriented, positioned and/or located. For example, in the context of a first object configured to fit within a second object, the first object is sized, shaped, arranged, structured, oriented, positioned and/or located to fit within the second object. As used herein in the context of a first object circumscribing a second object, the term “circumscribe” means that the first object is constructed around and/or defines an area around the second object. In interpreting the term “circumscribe” as used herein, it is to be understood that the first object circumscribing the second object can include gaps and/or can consist of multiple spaced-apart objects, such that a boundary formed by the first object around the second object is not necessarily a continuous boundary. For example, a plurality of trees can circumscribe a field.

[0040] FIG. 1 is a perspective view of an example warming rack **100** constructed in accordance with teachings of this disclosure, with the warming rack **100** shown positioned in an example expanded configuration **102**. FIG. 2 is a top view of the warming rack **100** of FIG. 1, with the warming rack **100** shown positioned in the expanded configuration **102** of FIG. 1. FIG. 3 is a bottom view of the warming rack **100** of FIGS. 1 and 2, with the warming rack **100** shown positioned in the expanded configuration **102** of FIGS. 1 and 2. FIG. 4 is a right side view of the warming rack **100** of FIGS. 1-3, with the warming rack **100** shown positioned in the expanded configuration **102** of FIGS. 1-3.

[0041] In the illustrated example of FIGS. 1-4, the warming rack **100** includes an example first rack **104** and an example second rack **106** pivotally coupled to the first rack **104**. The first rack **104** of FIGS. 1-4 includes an example first support rod **108**, an example second support rod **110** located proximate the first support rod **108** of the first rack **104**, an example third support rod **112** spaced apart from the first support rod **108** and the second support rod **110** of the first rack **104**, an example fourth support rod **114** extending between the first support rod **108** (and/or the second support rod **110**) and the third support rod **112** of the first rack **104**, and an example fifth support rod **116** spaced apart from the fourth support rod **114** of the first rack **104** and extending between the first support rod **108** (and/or the second support rod **110**) and the third support rod **112** of the

first rack **104**. The first support rod **108** and the second support rod **110** of the first rack **104** collectively define and/or extend along an example front end **118** of the first rack **104**. The third support rod **112** of the first rack **104** defines and/or extends along an example rear end **120** of the first rack **104**. The fourth support rod **114** of the first rack **104** defines and/or extends along an example right side **122** of the first rack **104**. The fifth support rod **116** of the first rack **104** defines and/or extends along an example left side **124** of the first rack **104**.

[0042] The first rack **104** of FIGS. **1-4** further includes example crosswise rods **126** that respectively extend between (e.g., span) the first support rod **108** (and/or the second support rod **110**) and the third support rod **112** of the first rack **104**. As shown in FIGS. **1-4**, the crosswise rods **126** of the first rack **104** provide and/or define an example top surface **128** of the first rack **104**, and further provide and/or define an example bottom surface **302** of the first rack **104** located opposite the top surface **128** of the first rack **104**. The crosswise rods **126** of the first rack **104** can be of any shape and/or size, and can form any pattern, layout, framework, and/or configuration. In the illustrated example of FIGS. **1-4**, the crosswise rods **126** of the first rack **104** provide and/or define a substantially flat, planar support surface of the first rack **104**, with the support surface being configured to support one or more food item(s) thereon.

[0043] The first rack **104** of FIGS. **1-4** further includes an example rail **130** extending upwardly from the top surface **128** of the first rack **104** along the rear end **120** of the first rack **104**. In the illustrated example of FIGS. **1-4**, the rail **130** of the first rack **104** provides and/or defines a rear boundary and/or mechanical stop configured to restrict, block, and/or prevent one or more food item(s) located and/or positioned on the top surface **128** of the first rack **104** from sliding off of the rear end **120** of the first rack **104**.

[0044] The first rack **104** of FIGS. **1-4** further includes an example first hook **132** and an example second hook **134**. In the illustrated example of FIGS. **1-4**, the first hook **132** is defined by and/or integrally formed with the fourth support rod **114** of the first rack **104**, with the first hook **132** being located and/or positioned rearwardly of the rear end **120** of the first rack **104**. Similarly, the second hook **134** is defined by and/or integrally formed with the fifth support rod **116** of the first rack **104**, with the second hook **134** also being located and/or positioned rearwardly of the rear end **120** of the first rack **104**. In other examples, the first hook **132** can instead be coupled to the fourth support rod **114** of the first rack **104**, and the second hook **134** can instead be coupled to the fifth support rod **116** of the first rack **104**. In still other examples, the first hook **132** and/or the second hook **134** can instead be integrally formed with and/or coupled to the third support rod **112**, the crosswise rods **126**, and/or the rail **130** of the first rack **104**.

[0045] In the illustrated examples of FIGS. **1-4**, the first hook **132** is canted relative to the fourth support rod **114** of the first rack **104**, with an upper portion of the first hook **132** being located laterally outward relative to the fourth support rod **114**, and with a lower portion of the first hook **132** being located laterally inward relative to the fourth support rod **114**. Similarly, the second hook **134** is canted relative to the fifth support rod **116** of the first rack **104**, with an upper portion of the second hook **134** being located laterally outward relative to the fifth support rod **116**, and with a lower portion of the second hook **134** being located laterally inward relative to the fifth support rod **116**. Thus, the lower portion of the first hook **132** is separated from the lower portion of the second hook **134** by a distance that is less than a corresponding distance by which the upper portion of the first hook **132** is separated from the upper portion of the second hook **134**. In other example, the first hook **132** and the second hook **134** can instead be canted in the opposite direction relative to the fourth support rod **114** and the fifth support rod **116** of the first rack **104**, such that the lower portion of the first hook **132** is separated from the lower portion of the second hook **134** by a distance that is greater than a corresponding distance by which the upper portion of the first hook **132** is separated from the upper portion of the second hook **134**. In still other examples, the first hook **132** and the second hook **134** can instead be oriented parallel to the fourth support rod **114** and the fifth support rod **116** of the first rack **104**, such that the lower portion of the first hook **132**

is separated from the lower portion of the second hook **134** by a distance that is substantially equal to a corresponding distance by which the upper portion of the first hook **132** is separated from the upper portion of the second hook **134**.

[0046] The first hook **132** and the second hook **134** of the first rack **104** of FIGS. **1-4** are respectively configured to couple and/or to mount the first rack **104** and/or, more generally, the warming rack **100** to and/or on a rear wall of a cookbox of a grill. For example, as shown in FIG. **4**, the first hook **132** of the first rack **104** includes an example first segment **402** extending upwardly from the top surface **128** of the first rack **104**, an example second segment **404** extending rearwardly from the first segment **402**, an example third segment **406** extending downwardly from the second segment **404**, an example fourth segment **408** extending forwardly from the third segment **406**, and an example fifth segment **410** extending upwardly from the fourth segment **408**. The first hook **132** of FIGS. **1-4** is configured such that the second segment **404** of the first hook **132** is positioned on and/or over an upper edge of a rear wall of a cookbox when the first rack **104** and/or, more generally, the warming rack **100** of FIGS. **1-4** is coupled and/or mounted to the rear wall of the cookbox with the first rack positioned in a horizontal orientation. The first hook **132** of FIGS. **1-4** is further configured such that the third segment **406** of the first hook **132** is positioned on and/or over an upper edge of a rear wall of a cookbox when the first rack **104** and/or, more generally, the warming rack **100** of FIGS. **1-4** is coupled and/or mounted to the rear wall of the cookbox with the first rack **104** positioned in a non-horizontal orientation (e.g., a substantially vertical orientation). The second hook **134** of the first rack **104** is structured and/or configured in a manner that is substantially identical to the above-described structure and/or configuration of the first hook **132** of the first rack **104**.

[0047] The first rack **104** of FIGS. **1-4** further includes an example first retention loop **136** and an example second retention loop **138**. In the illustrated example of FIGS. **1-4**, the first retention loop **136** is defined by and/or integrally formed with the fourth support rod **114** of the first rack **104**, with the first retention loop **136** being located and/or positioned forwardly of the front end **118** of the first rack **104**. Similarly, the second retention loop **138** is defined by and/or integrally formed with the fifth support rod **116** of the first rack **104**, with the second retention loop **138** also being located and/or positioned forwardly of the front end **118** of the first rack **104**. In other examples, the first retention loop **136** can instead be coupled to the fourth support rod **114** of the first rack **104**, and the second retention loop **138** can instead be coupled to the fifth support rod **116** of the first rack **104**. In still other examples, the first retention loop **136** and/or the second retention loop **138** can instead be integrally formed with and/or coupled to the first support rod **108**, the second support rod **110**, and/or the crosswise rods **126** of the first rack **104**.

[0048] As further described below, the first retention loop **136** and the second retention loop **138** of the first rack **104** of FIGS. **1-4** are respectively configured to circumferentially bound and/or contain corresponding first and second end portions of a rearwardly-located support rod of the second rack **106**, thereby forming a pivotal coupling between the first rack **104** and the second rack **106** of the warming rack **100**, with said pivotal coupling enabling the second rack **106** of the warming rack **100** to pivot and/or rotate relative to the first rack **104** of the warming rack **100**.

[0049] In the illustrated example of FIGS. **1-4**, the first support rod **108**, the second support rod **110**, the third support rod **112**, the fourth support rod **114**, the fifth support rod **116**, the crosswise rods **126**, the rail **130**, the first hook **132**, and the second hook **134** of the first rack **104** respectively have a circular cross-sectional profile. In other examples, the first support rod **108**, the second support rod **110**, the third support rod **112**, the fourth support rod **114**, the fifth support rod **116**, one or more of the crosswise rod(s) **126**, the rail **130**, the first hook **132**, and/or the second hook **134** of the first rack **104** can instead have a non-circular cross-sectional profile. For example, the first support rod **108**, the second support rod **110**, the third support rod **112**, the fourth support rod **114**, the fifth support rod **116**, one or more of the crosswise rod(s) **126**, the rail **130**, the first hook **132**, and/or the second hook **134** of the first rack **104** can instead have an elliptical cross-sectional

profile, a triangular cross-sectional profile, a rectangular cross-sectional profile, a hexagonal cross-sectional profile, etc.

[0050] The second rack **106** of FIGS. **1-4** includes an example first support rod **140**, an example second support rod **142** spaced apart from the first support rod **140** of the second rack **106**, an example third support rod **144** extending between the first support rod **140** and the second support rod **142** of the second rack **106**, and an example fourth support rod **146** spaced apart from the third support rod **144** of the second rack **106** and extending between the first support rod **140** and the second support rod **142** of the second rack **106**. The first support rod **140** of the second rack **106** defines and/or extends along an example front end **148** of the second rack **106**. The second support rod **142** of the second rack **106** defines and/or extends along an example rear end **150** of the second rack **106**. The third support rod **144** of the second rack **106** defines and/or extends along an example right side **152** of the second rack **106**. The fourth support rod **146** of the second rack **106** defines and/or extends along an example left side **154** of the second rack **106**.

[0051] The second rack **106** of FIGS. **1-4** further includes example crosswise rods **156** that respectively extend between (e.g., span) the first support rod **140** and the second support rod **142** of the second rack **106**. As shown in FIGS. **1-4**, the crosswise rods **156** of the second rack **106** provide and/or define an example top surface **158** of the second rack **106**, and further provide and/or define an example bottom surface **304** of the second rack **106** located opposite the top surface **158** of the second rack **106**. The crosswise rods **156** of the second rack **106** can be of any shape and/or size, and can form any pattern, layout, framework, and/or configuration. In the illustrated example of FIGS. **1-4**, the crosswise rods **156** of the second rack **106** provide and/or define a substantially flat, planar support surface of the second rack **106**, with the support surface being configured to support one or more food item(s) thereon.

[0052] The second rack **106** of FIGS. **1-4** further includes an example rail **160** extending downwardly from the bottom surface **304** of the second rack **106** along the front end **148** of the second rack **106**. In the illustrated example of FIGS. **1-4**, the rail **160** of the second rack **106** provides and/or defines a handle configured to assist a user in transitioning the warming rack **100** between the expanded configuration **102** shown in FIGS. **1-4** and a collapsed configuration shown in FIGS. **5-8** and further described below.

[0053] In the illustrated example of FIGS. **1-4**, the second support rod **142** of the second rack **106** includes an example first end portion **202** extending outwardly from the right side **152** of the second rack **106**, and an example second end portion **204** located opposite the first end portion **202** and extending outwardly from the left side **154** of the of the second rack **106**. The first end portion **202** of the second support rod **142** of the second rack **106** extends through the first retention loop **136** of the fourth support rod **114** of the first rack **104** such that the first end portion **202** of the second support rod **142** of the second rack **106** is pivotally coupled to, and circumferentially bound by and/or contained within, the first retention loop **136** of the fourth support rod **114** of the first rack **104**. Similarly, the second end portion **204** of the second support rod **142** of the second rack **106** extends through the second retention loop **138** of the fifth support rod **116** of the first rack **104** such that the second end portion **204** of the second support rod **142** of the second rack **106** is pivotally coupled to, and circumferentially bound by and/or contained within, the second retention loop **138** of the fifth support rod **116** of the first rack **104**. The joints formed by the above-described pivotal coupling of (1) the first end portion **202** of the second rack **106** to the first retention loop **136** of the first rack **104** and (2) the second end portion **204** of the second rack **106** to the second retention loop **138** of the first rack **104** collectively enable the second rack **106** of the warming rack **100** to pivot and/or rotate relative to the first rack **104** of the warming rack **100**.

[0054] The second rack **106** of FIGS. **1-4** further includes an example first stop arm **206** and an example second stop arm **208**. In the illustrated example of FIGS. **1-4**, the first stop arm **206** is defined by and/or integrally formed with the third support rod **144** of the second rack **106**, with the first stop arm **206** being located and/or positioned downwardly of the bottom surface **304** and/or

the rear end **150** of the second rack **106**. Similarly, the second stop arm **208** is defined by and/or integrally formed with the fourth support rod **146** of the second rack **106**, with the second stop arm **208** also being located and/or positioned downwardly of the bottom surface **304** and/or the rear end **150** of the second rack **106**. In other examples, the first stop arm **206** can instead be coupled to the third support rod **144** of the second rack **106**, and the second stop arm **208** can instead be coupled to the fourth support rod **146** of the second rack **106**. In still other examples, the first stop arm **206** and/or the second stop arm **208** can instead be integrally formed with and/or coupled to the second support rod **142** and/or the crosswise rods **156** of the second rack **106**.

[0055] In the illustrated example of FIGS. **1-4**, the first stop arm **206** and the second stop arm **208** of the second rack **106** respectively provide and/or define pivotal boundaries and/or mechanical stops configured to restrict, block and/or prevent the second rack **106** of the warming rack **100** from pivoting and/or rotating beyond a plane defined by the top surface **128** and/or the bottom surface **302** of the first rack **104** of the warming rack **100**. In this regard, the first stop arm **206** and the second stop arm **208** of the second rack **106** are respectively configured to contact the second support rod **110** of the first rack **104** when the warming rack **100** is positioned in the expanded configuration **102** shown in FIGS. **1-4**, thereby restricting, blocking, and/or preventing the second rack **106** from further downward rotation relative to the first rack **104**.

[0056] In the illustrated example of FIGS. **1-4**, the first support rod **140**, the second support rod **142**, the third support rod **144**, the fourth support rod **146**, the crosswise rods **156**, the rail **160**, the first end portion **202**, the second end portion **204**, the first stop arm **206**, and the second stop arm **208** of the second rack **106** respectively have a circular cross-sectional profile. In other examples, the first support rod **140**, the second support rod **142**, the third support rod **144**, the fourth support rod **146**, one or more of the crosswise rod(s) **156**, the rail **160**, the first end portion **202**, the second end portion **204**, the first stop arm **206**, and the second stop arm **208** of the second rack **106** can instead have a non-circular cross-sectional profile. For example, the first support rod **140**, the second support rod **142**, the third support rod **144**, the fourth support rod **146**, one or more of the crosswise rod(s) **156**, the rail **160**, the first end portion **202**, the second end portion **204**, the first stop arm **206**, and the second stop arm **208** of the second rack **106** can instead have an elliptical cross-sectional profile, a triangular cross-sectional profile, a rectangular cross-sectional profile, a hexagonal cross-sectional profile, etc.

[0057] As shown in FIGS. **1-4**, the second rack **106** is located and/or positioned in a side-by-side arrangement relative to the first rack **104** when the warming rack **100** is in the expanded configuration **102**. This spatial arrangement advantageously enables the first rack **104** and the second rack **106** to collectively provide a relatively large, planar, and substantially continuous warming surface onto which one or more food item(s) can be placed. In some examples, the warming rack **100** is configured such that the warming surface provided by the first rack **104** and the second rack **106** when the warming rack **100** is in the expanded configuration **102** fills, covers, and/or occupies substantially all of the width, and approximately half of the depth, of a cookbox to which the warming rack **100** is coupled. In this regard, positioning and/or arranging the warming rack **100** in the expanded configuration **102** maximizes the form factor and/or footprint of the useable warming surface provided by the first rack **104** and the second rack **106** of the warming rack **100**.

[0058] FIG. **5** is a perspective view of the warming rack **100** of FIGS. **1-4**, with the warming rack **100** shown positioned in an example collapsed configuration **502**. FIG. **6** is a top view of the warming rack **100** of FIGS. **1-5**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIG. **5**. FIG. **7** is a bottom view of the warming rack **100** of FIGS. **1-6**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIGS. **5** and **6**. FIG. **8** is a right side view of the warming rack **100** of FIGS. **1-7**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIGS. **5-7**.

[0059] The warming rack **100** of FIGS. **1-8** can be transitioned (e.g., by a user's hand and/or

fingers, or by means of a cooking utensil held by the user) from the expanded configuration **102** shown in FIGS. **1-4** into the collapsed configuration **502** shown in FIGS. **5-8** by pivoting and/or rotating the second rack **106** of the warming rack **100** relative to the first rack **104** of the warming rack **100** such that the top surface **158** of the second rack **106** is placed into a face-to-face arrangement with the top surface **128** of the first rack **104**. This spatial arrangement results in the first rack **104** and the second rack **106** collectively providing a planar warming surface onto which one or more food item(s) can be placed, with the provided warming surface associated with the collapsed configuration **502** of the warming rack **100** (e.g., as shown in FIGS. **5-8**) being relatively smaller than the corresponding warming surface associated with the expanded configuration **102** of the warming rack **100** (e.g., as shown in FIGS. **1-4**). In some examples, the warming rack **100** is configured such that the warming surface provided by the first rack **104** and the second rack **106** when the warming rack **100** is in the collapsed configuration **502** of FIGS. **5-8** fills, covers, and/or occupies substantially all of the width, and less than half (e.g., approximately one-third) of the depth, of a cookbox to which the warming rack **100** is coupled. In this regard, positioning and/or arranging the warming rack **100** in the collapsed configuration **502** shown in FIGS. **5-8** reduces the form factor and/or footprint of the useable warming surface provided by the first rack **104** and the second rack **106** of the warming rack **100** in comparison to the useable warming surface provided by the first rack **104** and the second rack **106** of the warming rack **100** when positioned and/or arranged in the expanded configuration **102** shown in FIGS. **1-4**.

[0060] The ability of the warming rack **100** of FIGS. **1-8** to be transitioned back and forth between the expanded configuration **102** shown in FIGS. **1-4** and the collapsed configuration **502** shown in FIGS. **5-8** provides advantageous tradeoff possibilities with regard to use of the warming rack **100** in conjunction with a cookbox of a grill to which the warming rack **100** may be coupled. For example, a user may find the form factor and/or footprint of the warming rack **100** when positioned and/or arranged (e.g., within the cookbox of the grill) in the collapsed configuration **502** of FIGS. **5-8** to be too small to adequately support one or more food item(s) that the user would like to place on the warming rack **100**. In such instances, the user can transition the warming rack **100** from the collapsed configuration **502** shown in FIGS. **5-8** into the expanded configuration **102** shown in FIGS. **1-4**, thereby increasing (e.g., maximizing) the form factor and/or footprint of the usable warming surface of the warming rack **100**. As another example, a user may find the form factor and/or footprint of the warming rack **100** when positioned and/or arranged (e.g., within the cookbox of the grill) in the expanded configuration **102** of FIGS. **1-4** to be obstructive and/or too large with regard to one or more food item(s) that the user would like to place on a cooking gate (e.g., positioned within the cookbox of the grill) that may be located below the warming rack **100**. In such instances, the user can transition the warming rack **100** from the expanded configuration **102** shown in FIGS. **1-4** into the collapsed configuration **502** shown in FIGS. **5-8**, thereby reducing the form factor and/or footprint of the usable warming surface of the warming rack **100** while at the same time increasing the available clearance space residing above and/or over the cooking grate.

[0061] FIG. **9** is a perspective view of an example grill **900** having an example cookbox **902** configured to support the warming rack **100** of FIGS. **1-8**. In the illustrated example of FIG. **9**, the warming rack **100** is shown coupled to the cookbox **902**, with the warming rack **100** being positioned and/or arranged in the expanded configuration **102** of FIGS. **1-4** described above. The grill **900** of FIG. **9** includes the warming rack **100**, the cookbox **902**, an example base **904**, and an example lid **906**. The cookbox **902** of the grill **900** is coupled to, positioned on, and/or supported by the base **904** of the grill **900**. The base **904** can be structured as a cart, a storage compartment, a frame, and/or any number of legs that may be suitable to support the cookbox **902**. The lid **906** of the grill **900** is movably coupled (e.g., via one or more hinge(s) or pin(s)) to the cookbox **902** of the grill **900** in a manner that enables the lid **906** to be moved (e.g., pivoted and/or rotated) relative to the cookbox **902** between a closed position and an open position (e.g., as shown in FIG. **9**). The cookbox **902** and the lid **906** collectively define a cooking chamber of the grill **900** when the lid

906 is in the closed position. Placement of the lid **906** in the open position (e.g., as shown in FIG. 9) enables a user to access the warming rack **100**, the cookbox **902**, and/or the cooking chamber, as may be required to load, unload, and/or otherwise access a food item located therein or thereon. Movement of the lid **906** between the closed position and the open position can be performed by a user of the grill **900** via an example handle **908** coupled to the lid **906**.

[0062] The cookbox **902** of the grill **900** can house, carry, and/or otherwise include a heat-generating and/or heat-emitting structure positioned within the cookbox **902**. For example, in instances where the grill **900** is a gas grill, the cookbox **902** of the grill **900** can house, carry, and/or otherwise include one or more burner tube(s) configured to generate and/or emit a heat-producing gas flame. As another example, in instances where the grill **900** is a solid-fuel grill (e.g., a charcoal grill, a pellet grill, etc.), the cookbox **902** of the grill **900** can house, carry, and/or otherwise include a burn pot and/or a burn pit configured to generate and/or emit heat from charcoal and/or wood pellets being combusted thereon or therein.

[0063] In the illustrated example of FIG. 9, the cookbox **902** includes an example front wall **910**, an example rear wall **912** spaced apart from the front wall **910**, an example right sidewall **914** extending between the front wall **910** and the rear wall **912**, and an example left sidewall **916** spaced apart from the right sidewall **914** and extending between the front wall **910** and the rear wall **912**. The warming rack **100** is coupled to the rear wall **912** of the cookbox **902** via the first hook **132** and the second hook **134** of the first rack **104** of the warming rack **100**. One or more example cooking grate(s) **918** of the grill **900** is/are located and/or positioned within the cookbox **902** at an elevation and/or height that is below the elevation and/or height at which the warming rack **100** is located and/or positioned within the cookbox **902**. The cooking grate(s) **918** is/are configured to form and/or define a substantially flat, planar cooking surface for cooking one or more food item(s) placed thereon. In the illustrated example of FIG. 9, the cooking grate(s) **918** is/are configured to fill, cover, and/or occupy the substantial entirety of the horizontal form factor and/or footprint of the cookbox **902** (e.g., as defined by the width and the depth of the cookbox **902**). In other examples, the cooking grate(s) **918** can instead be configured to fill, cover, and/or occupy a relatively smaller portion and/or percentage (e.g., less than the substantial entirety) of the horizontal form factor and/or footprint of the cookbox **902**.

[0064] FIG. 10 is a first perspective view of the cookbox **902** of FIG. 9, with the warming rack **100** shown positioned in the expanded configuration **102** of FIGS. 1-4 and further positioned in an example horizontal orientation **1002**. FIG. 11 is a second perspective view of the cookbox **902** of FIGS. 9 and 10, with the warming rack **100** shown positioned in the expanded configuration **102** of FIGS. 1-4 and 10 and the horizontal orientation **1002** of FIG. 10. FIG. 12 is a top view of the cookbox **902** of FIGS. 9-11, with the warming rack **100** shown positioned in the expanded configuration **102** of FIGS. 1-4, 10, and 11 and the horizontal orientation **1002** of FIGS. 10-11. FIG. 13 is a cross-sectional view of the cookbox **902** of FIGS. 9-12 taken along section A-A of FIG. 12, with the warming rack **100** shown positioned in the expanded configuration **102** of FIGS. 1-4 and 10-12 and the horizontal orientation **1002** of FIGS. 10-12.

[0065] In the illustrated example of FIGS. 10-13, the first rack **104** and/or, more generally, the warming rack **100** is coupled to the rear wall **912** of the cookbox **902** via the first hook **132** and the second hook **134** of the first rack **104**. As shown in FIG. 13, the first segment **402** of the first hook **132** is located within the cookbox **902**, with the first segment **402** contacting an interior surface of the rear wall **912** of the cookbox **902**. The second segment **404** of the first hook **132** is located above the cookbox **902**, with the second segment **404** contacting and extending across an upper edge of the rear wall **912** of the cookbox **902**. The third segment **406**, the fourth segment **408**, and the fifth segment **410** of the first hook **132** are respectively located outside of the cookbox **902**, with the fifth segment **410** contacting an exterior surface of the rear wall **912** of the cookbox **902**. The second hook **134** of the first rack **104** is arranged relative to the rear wall **912** of the cookbox **902** in a manner that is substantially identical to the above-described arrangement of the first hook

132 of the first rack **104** relative to the rear wall **912** of the cookbox **902**.

[0066] In the illustrated example of FIGS. **10-13**, the second rack **106** is located and/or positioned in a side-by-side arrangement relative to the first rack **104**, with the second rack **106** being located forward of the first rack **104**. This spatial arrangement between the first rack **104** and the second rack **106** advantageously provides a relatively large, planar, and substantially continuous warming surface onto which one or more food item(s) can be placed. The first rack **104** and the second rack **106** are respectively located and/or positioned above the cooking grate(s) **918** that are commonly located within the cookbox **902**. The horizontal orientation **1002** of the warming rack **100** as shown in FIGS. **10-13** is defined by the planar top surface **128** of the first rack **104** and/or the planar top surface **158** of the second rack **106**. As shown in FIGS. **10-13**, the planar top surface **128** of the first rack **104** and/or the planar top surface **158** of the second rack **106** is/are substantially parallel to a horizontal plane defined by the upper surface(s) of the cooking grate(s) **918**.

[0067] The warming rack **100** of FIGS. **1-13** is configured such that the warming surface provided by the first rack **104** and the second rack **106** when the warming rack **100** is positioned and/or arranged in the expanded configuration **102** and coupled to the cookbox **902** in the horizontal orientation **1002** fills, covers, and/or occupies substantially all of the width, and approximately half of the depth, of the cookbox **902**. For example, as shown in FIGS. **10-13**, the cooking grate(s) **918** has/have an example depth **1302** within the cookbox **902**. The warming rack **100** has an example depth **1304** within the cookbox **902**, with the depth **1304** of the warming rack **100** being approximately half of the depth **1302** of the cooking grate(s) **918**. Positioning and/or arranging the warming rack **100** in the expanded configuration **102** and the horizontal orientation **1002** shown in FIGS. **10-13** maximizes the form factor and/or footprint of the useable warming surface provided by the first rack **104** and the second rack **106** of the warming rack **100**. The spatial arrangement and/or configuration of the warming rack **100** as shown in FIGS. **10-13** can be particularly advantageous in instances where a user wants to place a relatively larger sized food item and/or a greater number of food items on the warming rack **100**, and/or in instances where the amount of available vertical clearance space residing above and/or over the cooking grate(s) **918** at a location forward of the warming rack **100** is of little or no concern to the user.

[0068] FIG. **14** is a first perspective view of the cookbox **902** of FIG. **9**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIGS. **5-8** and further positioned in an example horizontal orientation **1402**. FIG. **15** is a second perspective view of the cookbox **902** of FIGS. **9** and **14**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIGS. **5-8** and **14** and the horizontal orientation **1402** of FIG. **14**. FIG. **16** is a top view of the cookbox **902** of FIGS. **9**, **14**, and **15**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIGS. **5-8**, **14**, and **15** and the horizontal orientation **1002** of FIGS. **14** and **15**. FIG. **17** is a cross-sectional view of the cookbox **902** of FIGS. **9** and **14-16** taken along section B-B of FIG. **16**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIGS. **5-8** and **14-16** and the horizontal orientation **1402** of FIGS. **14-16**.

[0069] In the illustrated example of FIGS. **14-17**, the first rack **104** and/or, more generally, the warming rack **100** is coupled to the rear wall **912** of the cookbox **902** via the first hook **132** and the second hook **134** of the first rack **104**. As shown in FIG. **17**, the first segment **402** of the first hook **132** is located within the cookbox **902**, with the first segment **402** contacting an interior surface of the rear wall **912** of the cookbox **902**. The second segment **404** of the first hook **132** is located above the cookbox **902**, with the second segment **404** contacting and extending across an upper edge of the rear wall **912** of the cookbox **902**. The third segment **406**, the fourth segment **408**, and the fifth segment **410** of the first hook **132** are respectively located outside of the cookbox **902**, with the fifth segment **410** contacting an exterior surface of the rear wall **912** of the cookbox **902**. The second hook **134** of the first rack **104** is arranged relative to the rear wall **912** of the cookbox **902** in a manner that is substantially identical to the above-described arrangement of the first hook **132** of the first rack **104** relative to the rear wall **912** of the cookbox **902**.

[0070] In the illustrated example of FIGS. **14-17**, the second rack **106** is located and/or positioned in a face-to-face arrangement relative to the first rack **104**, with the second rack **106** being located above and/or on top of the first rack **104**. This spatial arrangement between the first rack **104** and the second rack **106** provides a relatively smaller, planar, and substantially continuous warming surface onto which one or more food item(s) can be placed. The first rack **104** and the second rack **106** are respectively located and/or positioned above the cooking grate(s) **918** that are commonly located within the cookbox **902**. The horizontal orientation **1402** of the warming rack **100** as shown in FIGS. **14-17** is defined by the planar top surface **128** of the first rack **104** and/or the planar bottom surface **304** of the second rack **106**. As shown in FIGS. **14-17**, the planar top surface **128** of the first rack **104** and/or the planar bottom surface **304** of the second rack **106** is/are substantially parallel to a horizontal plane defined by the upper surface(s) of the cooking grate(s) **918**.

[0071] The warming rack **100** of FIGS. **1-17** is configured such that the warming surface provided by the first rack **104** and the second rack **106** when the warming rack **100** is positioned and/or arranged in the collapsed configuration **502** and coupled to the cookbox **902** in the horizontal orientation **1402** fills, covers, and/or occupies substantially all of the width, and less than half (e.g., approximately one-third) of the depth, of the cookbox **902**. For example, as shown in FIGS. **14-17**, the cooking grate(s) **918** has/have an example depth **1302** within the cookbox **902**. The warming rack **100** has an example depth **1702** within the cookbox **902**, with the depth **1702** of the warming rack **100** being approximately one-third of the depth **1302** of the cooking grate(s) **918**. Positioning and/or arranging the warming rack **100** in the collapsed configuration **502** and the horizontal orientation **1402** shown in FIGS. **14-17** reduces the form factor and/or footprint of the useable warming surface provided by the first rack **104** and the second rack **106** of the warming rack **100** relative to the form factor and/or footprint of the useable warming surface provided by the first rack **104** and the second rack **106** of the warming rack **100** when the warming rack is positioned and/or arranged in the expanded configuration **102** and the horizontal orientation **1002** of FIGS. **10-13** described above. The spatial arrangement and/or configuration of the warming rack **100** as shown in FIGS. **14-17** can be particularly advantageous in instances where a user wants to place a relatively smaller sized food item and/or a lesser number of food items on the warming rack **100**, and/or in instances where the amount of available vertical clearance space residing above and/or over the cooking grate(s) **918** at a location forward of the warming rack **100** is of moderate concern to the user.

[0072] FIG. **18** is a first perspective view of the cookbox **902** of FIG. **9**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIGS. **5-8** and further positioned in an example non-horizontal orientation **1802**. FIG. **19** is a second perspective view of the cookbox **902** of FIGS. **9** and **18**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIGS. **5-8** and **18** and the non-horizontal orientation **1802** of FIG. **18**. FIG. **20** is a top view of the cookbox **902** of FIGS. **9**, **18**, and **19**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIGS. **5-8**, **18**, and **19** and the non-horizontal orientation **1802** of FIGS. **18** and **19**. FIG. **21** is a cross-sectional view of the cookbox **902** of FIGS. **9** and **18-20** taken along section C-C of FIG. **20**, with the warming rack **100** shown positioned in the collapsed configuration **502** of FIGS. **5-8** and **18-20** and the non-horizontal orientation **1802** of FIGS. **18-20**.

[0073] In the illustrated example of FIGS. **18-21**, the first rack **104** and/or, more generally, the warming rack **100** is coupled to the rear wall **912** of the cookbox **902** via the first hook **132** and the second hook **134** of the first rack **104**. As shown in FIG. **21**, the first segment **402** and the second segment **404** of the first hook **132** are respectively located within the cookbox **902**, with the bottom surface **302** of the first rack **104** contacting an interior surface of the rear wall **912** of the cookbox **902**. The third segment **406** of the first hook **132** is located above the cookbox **902**, with the third segment **406** contacting and extending across an upper edge of the rear wall **912** of the cookbox **902**. The fourth segment **408** and the fifth segment **410** of the first hook **132** are respectively located outside of the cookbox **902**, with a free end of the fifth segment **410** facing toward and/or

contacting an exterior surface of the rear wall **912** of the cookbox **902**. The second hook **134** of the first rack **104** is arranged relative to the rear wall **912** of the cookbox **902** in a manner that is substantially identical to the above-described arrangement of the first hook **132** of the first rack **104** relative to the rear wall **912** of the cookbox **902**.

[0074] In the illustrated example of FIGS. **18-21**, the second rack **106** is located and/or positioned in a face-to-face arrangement relative to the first rack **104**. The first rack **104** and the second rack **106** are respectively located and/or positioned above the cooking grate(s) **918** that are commonly located within the cookbox **902**. The non-horizontal orientation **1802** of the warming rack **100** as shown in FIGS. **18-21** is defined by the planar top surface **128** of the first rack **104** and/or the planar bottom surface **304** of the second rack **106**. As shown in FIGS. **18-21**, the planar top surface **128** of the first rack **104** and/or the planar bottom surface **304** of the second rack **106** is/are positioned at an example angle **2102** relative to a horizontal plane defined by the upper surface(s) of the cooking grate(s) **918**. In the illustrated example of FIGS. **18-21**, the angle **2102** is approximately eighty-five degrees) (85°). In other examples, the angle **2102** can instead be as little as forty-five degrees) (45°), or as great as ninety degrees) (90°).

[0075] The warming rack **100** of FIGS. **1-21** is configured such that the no usable warming surface is provided by the first rack **104** and the second rack **106** when the warming rack **100** is positioned and/or arranged in the collapsed configuration **502** and coupled to the cookbox **902** in the non-horizontal orientation **1802**. In this regard, when the warming rack is positioned, arranged, and or oriented as shown in FIGS. **18-21**, the warming rack fills, covers, and/or occupies substantially all of the width, and less than one-quarter (e.g., approximately one-tenth) of the depth of the cookbox **902**. For example, as shown in FIGS. **18-21**, the cooking grate(s) **918** has/have an example depth **1302** within the cookbox **902**. The warming rack **100** has an example depth **2104** within the cookbox **902**, with the depth **2104** of the warming rack **100** being approximately one-tenth of the depth **1302** of the cooking grate(s) **918**. Positioning and/or arranging the warming rack **100** in the collapsed configuration **502** and the non-horizontal orientation **1802** shown in FIGS. **18-21** further reduces and/or effectively eliminates the form factor and/or footprint of the useable warming surface provided by the first rack **104** and the second rack **106** of the warming rack **100** relative to the form factor and/or footprint of the useable warming surface provided by the first rack **104** and the second rack **106** of the warming rack **100** when the warming rack is positioned and/or arranged in the collapsed configuration **502** and the horizontal orientation **1402** of FIGS. **14-17** described above. The spatial arrangement and/or configuration of the warming rack **100** as shown in FIGS. **18-21** can be particularly advantageous in instances where a user does not want to place any food items on the warming rack **100**, and/or in instances where the amount of available vertical clearance space residing above and/or over the cooking grate(s) **918** at a location forward of the warming rack **100** is of great concern to the user.

[0076] FIG. **22** is a perspective view of another example warming rack **2200** constructed in accordance with teachings of this disclosure, with the warming rack **2200** shown positioned in an example expanded configuration **2202**. FIG. **23** is a top view of the warming rack **2200** of FIG. **22**, with the warming rack **2200** shown positioned in the expanded configuration **2202** of FIG. **22**. FIG. **24** is a bottom view of the warming rack **2200** of FIGS. **22** and **23**, with the warming rack **2200** shown positioned in the expanded configuration **2202** of FIGS. **22** and **23**. FIG. **25** is a right side view of the warming rack **2200** of FIGS. **22-24**, with the warming rack **2200** shown positioned in the expanded configuration **2202** of FIGS. **22-24**. FIG. **26** is a perspective view of the warming rack **2200** of FIGS. **22-25**, with the warming rack **2200** shown positioned in an example collapsed configuration **2602**. FIG. **27** is a top view of the warming rack **2200** of FIGS. **22-26**, with the warming rack **2200** shown positioned in the collapsed configuration **2602** of FIG. **26**. FIG. **28** is a bottom view of the warming rack **2200** of FIGS. **22-27**, with the warming rack **2200** shown positioned in the collapsed configuration **2602** of FIGS. **26** and **27**. FIG. **29** is a right side view of the warming rack **2200** of FIGS. **22-28**, with the warming rack **2200** shown positioned in the

collapsed configuration **2602** of FIGS. **26-28**.

[0077] The warming rack **2200** of FIGS. **22-29** is structured and/or configured in a manner that is substantially the same as the above-described warming rack **100** of FIG. **1-8**, with the warming rack **2200** of FIGS. **22-29** being movable between the expanded configuration **2202** of FIGS. **22-25** and the collapsed configuration **2602** of FIG. **26-29** in the same manner that the warming rack **100** of FIGS. **1-8** is movable between the expanded configuration **102** of FIGS. **1-4** and the collapsed configuration **502** of FIGS. **5-8**. With regard to correspondence among parts, the warming rack **2200** of FIGS. **22-29** includes an example first rack **2204** and an example second rack **2206** that are respectively structured and/or configured in a manner that is substantially the same as corresponding ones of the first rack **104** and the second rack **106** of the warming rack **100** of FIGS. **1-8**.

[0078] More specifically, the first rack **2204** of the warming rack **2200** of FIGS. **22-29** includes an example first support rod **2208**, an example second support rod **2210**, an example third support rod **2212**, an example fourth support rod **2214**, an example fifth support rod **2216**, an example front end **2218**, an example rear end **2220**, an example right side **2222**, an example left side **2224**, example crosswise rods **2226**, an example top surface **2228**, an example bottom surface **2402**, an example rail **2230**, an example first hook **2232** (having an example first segment **2502**, an example second segment **2504**, an example third segment **2506**, an example fourth segment **2508**, and an example fifth segment **2510**), an example second hook **2234**, an example first retention loop **2236**, and an example second retention loop **2238** that are respectively configured and/or structured in a manner that is substantially the same as corresponding ones of the first support rod **108**, the second support rod **110**, the third support rod **112**, the fourth support rod **114**, the fifth support rod **116**, the front end **118**, the rear end **120**, the right side **122**, the left side **124**, the crosswise rods **126**, the top surface **128**, the bottom surface **302**, the rail **130**, the first hook **132** (having the first segment **402**, the second segment **404**, the third segment **406**, the fourth segment **408**, and the fifth segment **410**), the second hook **134**, the first retention loop **136**, and the second retention loop **138** of the above-described first rack **104** of the warming rack **100** of FIGS. **1-8**.

[0079] Similarly, the second rack **2206** of the warming rack **2200** of FIGS. **22-29** includes an example first support rod **2240**, an example second support rod **2242** (having an example first end portion **2302** and an example second end portion **2304**), an example third support rod **2244** (having an example first stop arm **2306**), an example fourth support rod **2246** (having an example second stop arm **2308**), an example front end **2248**, an example rear end **2250**, an example right side **2252**, an example left side **2254**, example crosswise rods **2256**, an example top surface **2258**, an example bottom surface **2404**, and an example rail **2260** that are respectively structured and/or configured in a manner that is substantially the same as corresponding ones of the first support rod **140**, the second support rod **142** (having the first end portion **202** and the second end portion **204**), the third support rod **144** (having the first stop arm **206**), the fourth support rod **146** (having the second stop arm **208**), the front end **148**, the rear end **150**, the right side **152**, the left side **154**, the crosswise rods **156**, the top surface **158**, the bottom surface **304**, and the rail **160** of the above-described second rack **106** of the warming rack **100** of FIGS. **1-8**.

[0080] The structural differences between the warming rack **2200** of FIGS. **22-29** and the warming rack **100** of FIGS. **1-8** are relatively minimal. As one example, the first hook **132** is canted relative to the fourth support rod **114** of the first rack **104** of FIGS. **1-8**, and the second hook **134** is canted relative to the fifth support rod **116** of the first rack **104** of FIGS. **1-8**. By comparison, the first hook **2232** has a parallel orientation relative to the fourth support rod **2214** of the first rack **2204** of FIGS. **22-29**, and the second hook **2234** has a parallel orientation relative to the fifth support rod **2216** of the first rack **2204** of FIGS. **22-29**.

[0081] As another example, the second support rod **110** of the first rack **104** of FIGS. **1-8** has a linear shape extending from the right side **122** to the left side **124** of the first rack **104**. By comparison, the second support rod **2210** of the first rack **2204** of FIGS. **22-29** includes an example

first projection **2406** (e.g., a first forwardly-extending projection) located proximate the right side **2222** of the first rack **2204** and an example second projection **2408** (e.g., a second forwardly-extending projection) located proximate the left side **2224** of the first rack **2204**. As shown in FIGS. 22-25, the first projection **2406** of the second support rod **2210** of the first rack **2204** provides an engagement surface for the first stop arm **2306** of the second rack **2206**, and the second projection **2408** of the second support rod **2210** of the first rack **2204** provides an engagement surface for the second stop arm **2308** of the second rack **2206**. In this regard, the first stop arm **2306** and the second stop arm **2308** of the second rack **2206** are respectively configured to contact corresponding ones of the first projection **2406** and the second projection **2408** of the second support rod **2210** of the first rack **2204** when the warming rack **2200** is positioned in the expanded configuration **2202** shown in FIGS. 22-25, thereby restricting, blocking, and/or preventing the second rack **2206** from further downward rotation relative to the first rack **2204**.

[0082] As another example, the first end portion **202** and the second end portion **204** of the second support rod **142** of the second rack **106** of FIGS. 1-8 respectively terminate subsequent to extending outwardly through corresponding ones of the first retention loop **136** and the second retention loop **138** of the first rack **104** of FIGS. 1-8. By comparison, the first end portion **2302** and the second end portion **2304** of the second support rod **2242** of the second rack **2206** of FIGS. 22-29 respectively extend downward subsequent to extending outwardly through corresponding ones of the first retention loop **2236** and the second retention loop **2238** of the first rack **2204** of FIGS. 22-29. In some examples, the downward extension of the first end portion **2302** and the second end portion **2304** of the second support rod **2242** of the second rack **2206** of FIGS. 22-29 improves the mechanism by which the second rack **2206** is pivotally coupled to the first rack **2204**, and/or improves the mechanism by which the second support rod **2242** of the second rack **2206** is retained by the first retention loop **2236** and the second retention loop **2238** of the first rack **2204**.

[0083] As another example, the rail **160** of the second rack **106** of FIGS. 1-8 has a linear shape extending from the right side **152** to the left side **154** of the second rack **106**. By comparison, the rail **2260** of the second rack **2206** of FIGS. 22-29 has a contoured shape extending from the right side **2252** to the left side **2254** of the second rack **2206**, with the contoured shape including a relatively taller, centrally-located (e.g., middle) segment bounded by two relatively shorter segments. In some examples, the contoured shape of the rail **2260** of the second rack **2206** shown in FIGS. 22-29 improves the case by which a user may grip and/or grasp (e.g., by the user's hand and/or fingers, or by means of a cooking utensil held by the user) the rail **2260** of the second rack **2206** in connection with transitioning the warming rack **2200** between the expanded configuration **2202** of FIGS. 22-25 and the collapsed configuration **2602** of FIGS. 26-29.

[0084] Aside from the above-identified differences, the warming rack **2200** of FIGS. 22-29 is structured and/or configured in a manner that is substantially the same as the above-described warming rack **100** of FIG. 1-8, with the warming rack **2200** of FIGS. 22-29 being movable between the expanded configuration **2202** of FIGS. 22-25 and the collapsed configuration **2602** of FIG. 26-29 in the same manner that the warming rack **100** of FIGS. 1-8 is movable between the expanded configuration **102** of FIGS. 1-4 and the collapsed configuration **502** of FIGS. 5-8. As shown in FIGS. 22-25, the second rack **2206** is located and/or positioned in a side-by-side arrangement relative to the first rack **2204** when the warming rack **2200** is in the expanded configuration **2202**. This spatial arrangement advantageously enables the first rack **2204** and the second rack **2206** to collectively provide a relatively large, planar, and substantially continuous warming surface onto which one or more food item(s) can be placed. In some examples, the warming rack **2200** is configured such that the warming surface provided by the first rack **2204** and the second rack **2206** when the warming rack **2200** is in the expanded configuration **2202** fills, covers, and/or occupies substantially all of the width, and approximately half of the depth, of a cookbox to which the warming rack **2200** is coupled. In this regard, positioning and/or arranging the warming rack **2200** in the expanded configuration **2202** maximizes the form factor and/or footprint of the useable

warming surface provided by the first rack **2204** and the second rack **2206** of the warming rack **2200**.

[0085] The warming rack **2200** of FIGS. **22-29** can be transitioned (e.g., by a user's hand and/or fingers, or by means of a cooking utensil held by the user) from the expanded configuration **2202** shown in FIGS. **22-25** into the collapsed configuration **2602** shown in FIGS. **26-29** by pivoting and/or rotating the second rack **2206** of the warming rack **2200** relative to the first rack **2204** of the warming rack **2200** such that the top surface **2258** of the second rack **2206** is placed into a face-to-face arrangement with the top surface **2228** of the first rack **2204**. This spatial arrangement results in the first rack **2204** and the second rack **2206** collectively providing a planar warming surface onto which one or more food item(s) can be placed, with the provided warming surface associated with the collapsed configuration **2602** of the warming rack **2200** (e.g., as shown in FIGS. **26-29**) being relatively smaller than the corresponding warming surface associated with the expanded configuration **2202** of the warming rack **2200** (e.g., as shown in FIGS. **22-25**). In some examples, the warming rack **2200** is configured such that the warming surface provided by the first rack **2204** and the second rack **2206** when the warming rack **2200** is in the collapsed configuration **2602** of FIGS. **26-29** fills, covers, and/or occupies substantially all of the width, and less than half (e.g., approximately one-third) of the depth, of a cookbox to which the warming rack **2200** is coupled. In this regard, positioning and/or arranging the warming rack **2200** in the collapsed configuration **2602** shown in FIGS. **26-29** reduces the form factor and/or footprint of the useable warming surface provided by the first rack **2204** and the second rack **2206** of the warming rack **2200** in comparison to the useable warming surface provided by the first rack **2204** and the second rack **2206** of the warming rack **2200** when positioned and/or arranged in the expanded configuration **2202** shown in FIGS. **22-25**.

[0086] The ability of the warming rack **2200** of FIGS. **22-29** to be transitioned back and forth between the expanded configuration **2202** shown in FIGS. **22-25** and the collapsed configuration **2602** shown in FIGS. **26-29** provides advantageous tradeoff possibilities with regard to use of the warming rack **2200** in conjunction with a cookbox of a grill to which the warming rack **2200** may be coupled. For example, a user may find the form factor and/or footprint of the warming rack **2200** when positioned and/or arranged (e.g., within the cookbox of the grill) in the collapsed configuration **2602** of FIGS. **26-29** to be too small to adequately support one or more food item(s) that the user would like to place on the warming rack **2200**. In such instances, the user can transition the warming rack **2200** from the collapsed configuration **2602** shown in FIGS. **26-29** into the expanded configuration **2202** shown in FIGS. **22-25**, thereby increasing (e.g., maximizing) the form factor and/or footprint of the usable warming surface of the warming rack **2200**. As another example, a user may find the form factor and/or footprint of the warming rack **2200** when positioned and/or arranged (e.g., within the cookbox of the grill) in the expanded configuration **2202** of FIGS. **22-25** to be obstructive and/or too large with regard to one or more food item(s) that the user would like to place on a cooking gate (e.g., positioned within the cookbox of the grill) that may be located below the warming rack **2200**. In such instances, the user can transition the warming rack **2200** from the expanded configuration **2202** shown in FIGS. **22-25** into the collapsed configuration **2602** shown in FIGS. **26-29**, thereby reducing the form factor and/or footprint of the usable warming surface of the warming rack **2200** while at the same time increasing the available clearance space residing above and/or over the cooking grate

[0087] The warming rack **2200** of FIGS. **22-29** is structured and/or configured to be supported by and/or coupled to the cookbox **902** of the grill **900** of FIGS. **9-21** in the same manner that the warming rack **100** of FIGS. **1-8** is supported by and/or coupled to the cookbox **902** of the grill **900**, as shown in FIGS. **9-21** and described above. Thus, the warming rack **2200** of FIGS. **22-29** is structured and/or configured to: (1) have the above-described horizontal orientation **1002** shown in FIGS. **10-13** when the warming rack **2200** is coupled to the cookbox **902** of the grill **900** and positioned in the expanded configuration **2202** of FIGS. **22-25**; and (2) to selectively have either

the above-described horizontal orientation **1402** shown in FIGS. **14-17** or the above-described non-horizontal orientation **1802** of FIGS. **18-21** when the warming rack **2200** is coupled to the cookbox **902** of the grill **900** in the collapsed configuration **2602** of FIGS. **26-29**.

[0088] From the foregoing, it will be appreciated that example adjustable warming racks disclosed herein are advantageously configured to be positionable and/or arrangeable in numerous configurations within a cookbox of a grill, with the adjustable warming racks being transitionable from one configuration to another. Example adjustable warming racks disclosed herein accordingly provide enhanced flexibility with regard to the range of cooking operations that can be accommodated and/or performed within a cookbox of a grill.

[0089] In some examples, a warming rack is disclosed. In some disclosed examples, the warming rack is configured to be coupled to a cookbox of a grill. In some disclosed examples, the warming rack comprises a first rack and a second rack. In some disclosed examples, the first rack has a hook configured to couple the warming rack to the cookbox. In some disclosed examples, the second rack is pivotally coupled to the first rack. In some disclosed examples, the second rack is movable relative to the first rack to transition the warming rack between an expanded configuration and a collapsed configuration.

[0090] In some disclosed examples, the hook is configured to couple the warming rack to a rear wall of the cookbox.

[0091] In some disclosed examples, the second rack is positioned forward of the first rack within the cookbox when the warming rack is in the expanded configuration and positioned in a horizontal orientation.

[0092] In some disclosed examples, the second rack is positioned over the first rack within the cookbox when the warming rack is in the collapsed configuration and positioned in a horizontal orientation.

[0093] In some disclosed examples, the warming rack is movable from the horizontal orientation into a non-horizontal orientation when the warming rack is in the collapsed configuration.

[0094] In some disclosed examples, the non-horizontal orientation lies at an angle between forty-five and ninety degrees downward relative to the horizontal orientation.

[0095] In some disclosed examples, the hook is configured to enable movement of the warming rack from the horizontal orientation into the non-horizontal orientation when the warming rack is in the collapsed configuration.

[0096] In some disclosed examples, a bottom surface of the first rack contacts an interior surface of a rear wall of the cookbox when the warming rack is in the collapsed configuration and positioned in the non-horizontal orientation.

[0097] In some disclosed examples, the first rack includes a first retention loop located along a right side of the first rack and a second retention loop located along a left side of the first rack.

[0098] In some disclosed examples, the second rack includes a support rod having a first end portion extending through the first retention loop and a second end portion extending through the second retention loop.

[0099] In some disclosed examples, the first rack includes a rail located along a rear end of the first rack. In some disclosed examples, the rail is configured to prevent a food item from sliding off of the rear end of the first rack when the warming rack is in the expanded configuration and positioned in a horizontal orientation.

[0100] In some disclosed examples, the second rack includes a rail located along a front end of the second rack. In some disclosed examples, the rail is configured to provide a handle for transitioning the warming rack between the expanded configuration and the collapsed configuration when the warming rack is positioned.

[0101] In some disclosed examples, the first rack includes a support rod extending between a right side and a left side of the first rack. In some disclosed examples, the second rack includes a stop arm configured to engage the support rod when the warming rack is in the expanded configuration.

[0102] In some disclosed examples, engagement of the support rod with the stop arm prevents the second rack from moving downwardly relative to the first rack beyond a plane defined by the first rack.

[0103] In some examples, a warming rack is disclosed. In some disclosed examples, the warming rack is configured to be coupled to a cookbox of a grill. In some disclosed examples, the warming rack comprises a first rack and a second rack. In some disclosed examples, the first rack has a hook configured to couple the warming rack to a rear wall of the cookbox. In some disclosed examples, the second rack is pivotally coupled to the first rack. In some disclosed examples, the second rack is movable relative to the first rack to transition the warming rack between an expanded configuration and a collapsed configuration. In some disclosed examples, the second rack is to be positioned forward of the first rack within the cookbox when the warming rack is in the expanded configuration and positioned in a first horizontal orientation.

[0104] In some disclosed examples, the second rack is positioned over the first rack within the cookbox when the warming rack is in the collapsed configuration and positioned in a second horizontal orientation.

[0105] In some disclosed examples, the warming rack is movable from the second horizontal orientation into a non-horizontal orientation when the warming rack is in the collapsed configuration.

[0106] In some disclosed examples, the non-horizontal orientation lies at an angle between forty-five and ninety degrees downward relative to the second horizontal orientation.

[0107] In some disclosed examples, the hook is configured to enable movement of the warming rack from the second horizontal orientation into the non-horizontal orientation when the warming rack is in the collapsed configuration.

[0108] In some disclosed examples, a bottom surface of the first rack contacts an interior surface of a rear wall of the cookbox when the warming rack is in the collapsed configuration and positioned in the non-horizontal orientation.

[0109] Although certain example methods, apparatus and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all methods, apparatus and articles of manufacture fairly falling within the scope of the claims of this patent.

Claims

1. A grill, comprising: a cookbox; a cooking grate positioned within the cookbox; and a warming rack located above the cooking grate and positioned in a horizontal orientation, the warming rack including: a first rack coupled to the cookbox, the first rack including a front support rod, a rear support rod, a right support rod, a left support rod, and a plurality of crosswise rods, the rear support rod spaced apart from the front support rod, the right support rod extending between the front support rod and the rear support rod, the right support rod forming a first retention loop, the left support rod spaced apart from the right support rod and extending between the front support rod and the rear support rod, the left support rod forming a second retention loop, respective ones of the crosswise rods of the first rack extending between the front support rod and the rear support rod; and a second rack coupled to the first rack, the second rack including a first support rod, a second support rod, and a plurality of crosswise rods, the second support rod spaced apart from the first support rod, the second support rod including a first end portion extending through and retained by the first retention loop and a second end portion extending through and retained by the second retention loop, respective ones of the crosswise rods of the second rack extending between the first support rod and the second support rod, the second rack movable relative to the first rack to transition the warming rack between an expanded configuration and a collapsed configuration, the second rack positioned forward of the first rack when the warming rack is in the expanded

configuration, the second rack positioned over the first rack when the warming rack is in the collapsed configuration.

2. The grill of claim 1, wherein the front support rod of the first rack extends between the right support rod and the left support rod of the first rack, wherein the second rack includes a stop arm configured to engage the front support rod when the warming rack is in the expanded configuration, wherein the stop arm is located below the crosswise rods of the second rack when the warming rack is in the expanded configuration, wherein engagement of the stop arm with the front support rod prevents the second rack from moving downward relative to the first rack when the warming rack is in the expanded configuration.

3. The grill of claim 1, wherein the first rack includes a hook located rearward of the rear support rod, wherein the hook couples the warming rack to a rear wall of the cookbox.

4. The grill of claim 1, wherein the crosswise rods of the second rack are interleaved relative to the crosswise rods of the first rack when the warming rack is in the collapsed configuration.

5. The grill of claim 1, wherein the crosswise rods of the first rack and the crosswise rods of the second rack collectively provide a first planar warming surface when the warming rack is in the expanded configuration, wherein the crosswise rods of the second rack provide a second planar warming surface when the warming rack is in the collapsed configuration, wherein a depth of the second planar warming surface is less than a depth of the first planar warming surface.

6. A grill, comprising: a cookbox; a cooking grate positioned within the cookbox; and a warming rack located above the cooking grate and positioned in a horizontal orientation, the warming rack including: a first rack coupled to the cookbox, the first rack including a front support rod, a rear support rod, a right support rod, a left support rod, and a plurality of crosswise rods, the rear support rod spaced apart from the front support rod, the right support rod extending between the front support rod and the rear support rod, the left support rod spaced apart from the right support rod and extending between the front support rod and the rear support rod, respective ones of the crosswise rods of the first rack extending between the front support rod and the rear support rod; and a second rack coupled to the first rack, the second rack including a first support rod, a second support rod, and a plurality of crosswise rods, the second support rod spaced apart from the first support rod, respective ones of the crosswise rods of the second rack extending between the first support rod and the second support rod, the second rack movable relative to the first rack to transition the warming rack between an expanded configuration and a collapsed configuration, the second rack positioned forward of the first rack when the warming rack is in the expanded configuration, the second rack positioned over the first rack when the warming rack is in the collapsed configuration, the second rack further including a stop arm configured to engage the front support rod of the first rack when the warming rack is in the expanded configuration.

7. The grill of claim 6, wherein the stop arm is located below the crosswise rods of the second rack when the warming rack is in the expanded configuration, wherein engagement of the stop arm with the front support rod prevents the second rack from moving downward relative to the first rack when the warming rack is in the expanded configuration.

8. The grill of claim 6, wherein the first rack includes a hook located rearward of the rear support rod, wherein the hook couples the warming rack to a rear wall of the cookbox.

9. The grill of claim 6, wherein the crosswise rods of the second rack are interleaved relative to the crosswise rods of the first rack when the warming rack is in the collapsed configuration and positioned.

10. The grill of claim 6, wherein the crosswise rods of the first rack and the crosswise rods of the second rack collectively provide a first planar warming surface when the warming rack is in the expanded configuration, wherein the crosswise rods of the second rack provide a second planar warming surface when the warming rack is in the collapsed configuration, wherein a depth of the second planar warming surface is less than a depth of the first planar warming surface.

11. A grill, comprising: a cookbox; a cooking grate positioned within the cookbox; and a warming

rack located above the cooking grate and positioned in a horizontal orientation, the warming rack including: a first rack coupled to the cookbox, the first rack including a first front support rod, a second front support rod, a rear support rod, a right support rod, a left support rod, and a plurality of crosswise rods, the rear support rod spaced apart from the first front support rod, the right support rod extending between the first front support rod and the rear support rod, the left support rod spaced apart from the right support rod and extending between the first front support rod and the rear support rod, respective ones of the crosswise rods of the first rack extending between the first front support rod and the rear support rod; and a second rack coupled to the first rack, the second rack including a first support rod, a second support rod, and a plurality of crosswise rods, the second support rod spaced apart from the first support rod, respective ones of the crosswise rods of the second rack extending between the first support rod and the second support rod, the second rack movable relative to the first rack to transition the warming rack between an expanded configuration and a collapsed configuration, the second rack positioned forward of the first rack when the warming rack is in the expanded configuration, the second rack positioned over the first rack when the warming rack is in the collapsed configuration, the second rack further including a stop arm configured to engage the second front support rod of the first rack when the warming rack is in the expanded configuration.

12. The grill of claim 11, wherein the stop arm is located below the crosswise rods of the second rack when the warming rack is in the expanded configuration, wherein engagement of the stop arm with the second front support rod prevents the second rack from moving downward relative to the first rack when the warming rack is in the expanded configuration.

13. The grill of claim 11, wherein the second front support rod is located below the first front support rod.

14. The grill of claim 11, wherein the crosswise rods of the second rack are interleaved relative to the crosswise rods of the first rack when the warming rack is in the collapsed configuration.

15. The grill of claim 11, wherein the crosswise rods of the first rack and the crosswise rods of the second rack collectively provide a first planar warming surface when the warming rack is in the expanded configuration, wherein the crosswise rods of the second rack provide a second planar warming surface when the warming rack is in the collapsed configuration, wherein a depth of the second planar warming surface is less than a depth of the first planar warming surface.

16. A grill, comprising: a cookbox; a cooking grate positioned within the cookbox; and a warming rack located above the cooking grate and positioned in a horizontal orientation, the warming rack including: a first rack coupled to the cookbox, the first rack including a front support rod, a rear support rod, a right support rod, a left support rod, and a plurality of crosswise rods, the rear support rod spaced apart from the front support rod, the right support rod extending between the front support rod and the rear support rod, the right support rod forming a first retention loop, the left support rod spaced apart from the right support rod and extending between the front support rod and the rear support rod, the left support rod forming a second retention loop, respective ones of the crosswise rods of the first rack extending between the front support rod and the rear support rod; and a second rack coupled to the first rack, the second rack including a first support rod, a second support rod, a right support rod end portion, a left support rod end portion, and a plurality of crosswise rods, the second support rod spaced apart from the first support rod, the right support rod end portion extending outwardly from a right side of the second rack, the right support rod end portion extending through and retained by the first retention loop, the left support rod end portion extending outwardly from a left side of the second rack, the left support rod end portion extending through and retained by the second retention loop, respective ones of the crosswise rods of the second rack extending between the first support rod and the second support rod, the second rack movable relative to the first rack to transition the warming rack between an expanded configuration and a collapsed configuration, the second rack positioned forward of the first rack when the warming rack is in the expanded configuration, the second rack positioned over the first rack when

the warming rack is in the collapsed configuration.

17. The grill of claim 16, wherein the front support rod of the first rack is a first front support rod of the first rack, the first rack further including a second front support rod located below the first front support rod, wherein the second rack includes a stop arm configured to engage the second front support rod when the warming rack is in the expanded configuration.

18. The grill of claim 17, wherein the stop arm is located below the crosswise rods of the second rack when the warming rack is in the expanded configuration, wherein engagement of the stop arm with the second front support rod prevents the second rack from moving downward relative to the first rack when the warming rack is in the expanded configuration.

19. The grill of claim 16, wherein the crosswise rods of the second rack are interleaved relative to the crosswise rods of the first rack when the warming rack is in the collapsed configuration.

20. The grill of claim 16, wherein the crosswise rods of the first rack and the crosswise rods of the second rack collectively provide a first planar warming surface when the warming rack is in the expanded configuration, wherein the crosswise rods of the second rack provide a second planar warming surface when the warming rack is in the collapsed configuration, wherein a depth of the second planar warming surface is less than a depth of the first planar warming surface.
