

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385600
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Buscema; John et al.

Support apparatus for securing a portable electronic device

Abstract

A support apparatus for securing a portable electronic device includes a backer plate, a plurality of coupling devices, a power supply tray, a pivotable bracket assembly, a pair of stiffening plates, a pivot axis rod, a locking feature, and a securement strap. The plurality of coupling devices couple to the backer plate and can be coupled to one or more existing structural support elements. The power supply tray secures a stationary power supply electrically coupled to the portable electronic device. The pivotable bracket assembly secures and enables rotation of the portable electronic device. The pivot axis rod pivotally connects to the pivotable bracket assembly, and rigidly connects to the opposing stiffening plates. The locking feature selectively retains the pivotable bracket assembly in an upright vertical position. The securement strap couples the front of the pivotable bracket assembly to the backer plate while securing the top of the portable electronic device.

Inventors: Buscema; John (New Port Richey, FL), Ziegler; Jonathan (Wofford Heights, CA)

Applicant: SAFE Structure Designs, LLC (Las Vegas, NV)

Family ID: 1000008752393

Assignee: SAFE Structure Designs, LLC (Las Vegas, NV)

Appl. No.: 18/385902

Filed: October 31, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240142051 A1	May. 02, 2024

Related U.S. Application Data

us-provisional-application US 63421006 20221031

Publication Classification

Int. Cl.: F16M13/02 (20060101); F16M11/10 (20060101)

U.S. Cl.:

CPC F16M13/022 (20130101); F16M11/10 (20130101); F16M2200/021 (20130101)

Field of Classification Search

CPC: F16M (13/022); F16M (11/10); F16M (2200/021)

USPC: 248/176.1; 248/178.1

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4154381	12/1978	Zufich	D3/216	A45F 3/08
5472164	12/1994	Contee	N/A	N/A
5732867	12/1997	Perkins	224/628	A45F 3/08
5774338	12/1997	Wessling, III	361/733	G06F 1/163
6507486	12/2002	Peterson, III	361/730	G06F 1/163
6522531	12/2002	Quintana	361/679.09	G06F 1/163
6529372	12/2002	Ng	361/728	G06F 1/163
6932256	12/2004	Hale	224/648	A45F 3/042
6962277	12/2004	Quintana	709/201	G06F 1/163
7265970	12/2006	Jordan	361/679.27	G09F 21/02
8079503	12/2010	Yeates	224/268	A45C 7/0086
8104653	12/2011	Leung	224/636	A45F 3/04
8413938	12/2012	Whelan et al.	N/A	N/A
8505790	12/2012	Yu	224/625	F16M 11/041
8584917	12/2012	Hexels	2/2.5	A45F 3/14
9777997	12/2016	Swan	N/A	A41D 13/0518
9820556	12/2016	Adams	N/A	A45F 3/08
10007303	12/2017	Wang	N/A	A63F 13/98
10413044	12/2018	Husband	N/A	A45F 3/04
10617209	12/2019	Frost	N/A	N/A
10754380	12/2019	Pennington, Jr.	N/A	G06F 1/163
11089859	12/2020	Nordmann	N/A	A45F 3/08
2010/0032464	12/2009	Gleason, Jr.	224/628	A45F 3/047
2020/0055527	12/2019	Evans et al.	N/A	N/A

Primary Examiner: Millner; Monica E

Attorney, Agent or Firm: Lippes Mathias LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims the benefit of U.S. Provisional Application No. 63/421,006, filed Oct. 31, 2022, and is hereby incorporated by reference in its entirety for all purposes.

FIELD OF THE INVENTION

(1) The present disclosure relates generally to a support apparatus designed to secure a portable electronic device and pertains specifically to a support apparatus having a pivotable bracket assembly configured for securing a portable electronic device and further including a plurality of coupling devices for coupling the support apparatus to existing structural support elements.

BACKGROUND

(2) Traditionally, large portable electronic devices are stored in known wearable container assemblies which allow such devices to be transportable. However, having the user support the heavy load imparted by the weight of the portable electronic device in the wearable container assembly while they're walking can cause the user to become fatigued over time. Accordingly, a support apparatus is needed to transfer the load off the user and onto existing stationary structural support elements during times when transporting the electronic device is not necessary.

(3) There are known separate mounting kits available which include fixtures that function as hooks or adjustable clamps, and which are configured to be coupled to structural support elements such as railings, for example. These known separate mounting kits need to be stored and transported by the user as well, removed from their storage unit, and fastened to the railing. Then the user can remove their container assemblies and couple them to the installed mounting fixtures. There is a need for a support apparatus having a plurality of coupling devices pre-mounted to the rear of the support apparatus, and configured for coupling to existing structural elements such as, but not limited to, railing, posts, walls, beams or columns.

(4) Additionally, some large portable electronic devices require the securing of adjacent stationary external power supplies, as well as other compartments for securement of various adjacent auxiliary devices. There is a need for a support apparatus with separate compartments or trays configured for securing adjacent auxiliary devices used in conjunction with the portable electronic devices.

(5) Further, there is a need for a user to have convenient access to insert as well as pick up the portable electronic device from the support apparatus without having to detach it from its wearable container assembly. As such, there is a need for a support apparatus with a pivotable bracket tray configured for securing the electronic device and for providing convenient access to the device.

SUMMARY OF THE INVENTION

(6) A non-limiting exemplary embodiment (the “exemplary embodiment”) of a support apparatus for securing a portable electronic device is disclosed herein. The exemplary embodiment of the support apparatus includes a backer plate, a plurality of coupling devices, a power supply tray, a pivotable bracket assembly, a pair of stiffening plates, a pivot axis rod, a locking feature, and a securement strap. The backer plate includes a front surface and a rear surface. The plurality of coupling devices are coupled to the rear surface of the backer plate and are configured for coupling the support apparatus to one or more existing structural support elements. The power supply tray is coupled to the backer plate and is configured to secure a stationary power supply which may be electrically coupled to the portable electronic device. The pivotable bracket assembly is configured for securing the portable electronic device, and for enabling rotation of the portable electronic device from an upright vertical position down to an inclined position. The stiffening plates are configured to couple to the backer plate and are disposed each on opposing sides of the pivotable bracket assembly. The pivot axis rod is configured for pivotal connection to the pivotable bracket

assembly, and for rigid connection to the opposing stiffening plates. The locking feature is configured to selectively retain the pivotable bracket assembly in the upright vertical position by selectively preventing the pivotable bracket assembly from rotating about the pivotal axis rod forward and down to the inclined position. The securement strap is configured to couple the front of the pivotable bracket assembly to the backer plate while securing the top of the portable electronic device.

(7) Another embodiment of the support apparatus includes a backer plate, a plurality of coupling devices, a power supply tray, a pivotable bracket assembly, a pair of stiffening plates, a pivot axis rod, a locking feature, and a securement strap. The backer plate includes a front surface and a rear surface. The plurality of coupling devices are coupled to the rear surface of the backer plate and are configured for coupling the support apparatus to one or more existing structural support elements. The plurality of coupling devices are also interchangeable depending on the geometry of the one or more existing structural support elements. The power supply tray is coupled to the backer plate and is configured to secure a stationary power supply which may be electrically coupled to the portable electronic device. The pivotable bracket assembly is configured for securing the portable electronic device, and for enabling rotation of the portable electronic device from an upright vertical position down to an inclined position. The stiffening plates are configured to couple to the backer plate and are disposed each on opposing sides of the pivotable bracket assembly. The pivot axis rod is configured for pivotal connection to the pivotable bracket assembly, and for rigid connection to the opposing stiffening plates. The locking feature is configured to selectively retain the pivotable bracket assembly in the upright vertical position by selectively preventing the pivotable bracket assembly from rotating about the pivotal axis rod forward and down to the inclined position. The securement strap is adjustable and configured to couple the front of the pivotable bracket assembly to the backer plate while securing the top of the portable electronic device.

(8) A further embodiment of the support apparatus includes a backer plate, a plurality of coupling devices, a power supply tray, a pivotable bracket assembly, a pair of stiffening plates, a pivot axis rod, a locking feature, a securement strap, and a stabilizer. The backer plate includes a front surface and a rear surface. The plurality of coupling devices are coupled to the rear surface of the backer plate and are configured for coupling the support apparatus to one or more existing structural support elements. The power supply tray is coupled to the backer plate and is configured to secure a stationary power supply which may be electrically coupled to the portable electronic device. The pivotable bracket assembly is configured for securing the portable electronic device, and for enabling rotation of the portable electronic device from an upright vertical position down to an inclined position. The stiffening plates are configured to couple to the backer plate and are disposed each on opposing sides of the pivotable bracket assembly. The pivot axis rod is configured for pivotal connection to the pivotable bracket assembly, and for rigid connection to the opposing stiffening plates. The locking feature is configured to selectively retain the pivotable bracket assembly in the upright vertical position by selectively preventing the pivotable bracket assembly from rotating about the pivotal axis rod forward and down to the inclined position. The securement strap is configured to couple the front of the pivotable bracket assembly to the backer plate while securing the top of the portable electronic device. The stabilizer is configured to mechanically link between the pivotable bracket assembly and the backer plate, and to restrict the rate at which the pivotable bracket assembly is capable of rotating.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The appended figures merely illustrate an exemplary embodiment of the present disclosure and cannot be considered as limiting its scope.

- (2) FIG. 1 is a right front perspective view of an exemplary, non-limiting embodiment of a support apparatus.
- (3) FIG. 2 is a right-side elevation view of the of the support apparatus of FIG. 1 without the stabilizer showing, further depicting an exemplary embodiment of a power supply unit secured in a rear storage compartment and a display device in an auxiliary screen support.
- (4) FIG. 3 is a partial right-side view of a pivotable bracket assembly shown rotated into an inclined position.
- (5) FIG. 4 is a right front perspective view of the support apparatus of FIG. 1 further depicting an in-use exemplary embodiment of a portable electronic device secured in a pivotable bracket assembly, and additionally depicting an associated wearable container assembly.
- (6) FIG. 5 is a right bottom perspective view of the support apparatus of FIG. 1.
- (7) FIG. 6 is a top rear perspective view of the support apparatus of FIG. 1.
- (8) FIG. 7 is a left front perspective view of the support apparatus of FIG. 1.
- (9) FIG. 8A is a front top left perspective view of the support apparatus of FIG. 1.
- (10) FIG. 8B is a left top front perspective view of the support apparatus of FIG. 1.
- (11) FIG. 9 is a front elevation view of the support apparatus of FIG. 1.
- (12) FIG. 10 is a rear elevation view of the support apparatus of FIG. 1.
- (13) FIG. 11 is a top view of the support apparatus of FIG. 10.
- (14) FIG. 12 is a bottom view of the support apparatus of FIG. 10.
- (15) FIG. 13 is a right-side elevation view of the of the support apparatus of FIG. 1.
- (16) FIG. 14 is a left-side elevation view of the of the support apparatus of FIG. 1.
- (17) FIG. 15 is a vertical cross-sectional view of the support apparatus of FIG. 11 taken along the line A-A.
- (18) FIG. 16 is a second bottom perspective view of the support apparatus of FIG. 5, rotated slightly counter-clockwise.
- (19) FIG. 17 is an enlarged partial perspective view of the bottom of the support apparatus of FIG. 16 taken inside the circle A.
- (20) FIG. 18 is a rear right bottom perspective view of the support apparatus of FIG. 1.
- (21) FIG. 19 is a bottom rear perspective view of the support apparatus of FIG. 1.
- (22) FIG. 20 is a bottom right front perspective view of the support apparatus of FIG. 1.

NUMBER REFERENCES

(23) 1—Support apparatus 2—Portable electronic device 4—Stationary power supply 10—Backer plate 12—Top coupling devices 13—Bottom coupling devices 14—Power supply tray 15—Rear member 16—Tabs 17—Side walls 18—Top brace 19—Bottom brace 20—Stiffening plates 22—Bottom wall 24—Mounting protrusions 26—Mounting brackets 30—Pivotable bracket assembly 32—Front plate 34—Rear plate 36—Base plate 37—Aperture 38—Intermediate brace 40—Mounting block 41—Rear compartment 42—Securement strap 43—Clip 44—Spacer brace 45—Compressible pad 46—Bearing Pad 47—Cutout 48—Protrusions 50—Stabilizer 60—Pivot axis rod 62—Locking feature 70—Auxiliary compartment 72—Strap 74—Supplemental power supply units 76—Auxiliary screen support 78—Display device

DETAILED DESCRIPTION

(24) In the following description, reference is made to the accompanying drawings which form a part hereof and which illustrate an embodiment of the present disclosure. It is understood that other embodiments may be utilized, and structural and operational changes may be made without departing from the scope of the present disclosure.

(25) As shown in FIGS. 1-10, the present disclosure provides an exemplary, non-limiting embodiment of a support apparatus 1 for securing a portable electronic device 2 (electronic device is shown in FIG. 4). The support apparatus 1 generally includes a backer plate 10, a plurality of coupling devices (such as, for example, top and bottom coupling devices 12, 13), a power supply tray 14, a pair of stiffening plates 20, a pivotable bracket assembly 30, a securement strap 42, a

pivot axis rod **60**, and a locking feature **62**.

(26) The pivotable bracket assembly **30** is configured for securing a portable electronic device **2**, and for enabling rotation of the portable electronic device from an upright vertical position, as shown in FIG. **1**, forward and down to an inclined position, as shown in FIG. **3**. The portable electronic device **2** may be any suitable portable electronic device, such as, for example, an electronic frequency jamming device. The portable electronic device **2** may be electrically coupled to a stationary power supply **4** (power supply is shown in FIG. **2**) when the portable electronic device is stored within the pivotable bracket assembly **30**. The stationary power supply **4** may be any suitable stationary power supply, such as, for example, an AC/DC converter or a DC power supply. The stationary power supply **4** is secured within the power supply tray **14** (the tray is shown in FIGS. **1**, **2**, **5**, **8B**, **13** (top of tray) and **16**, **17** and **20** (bottom of tray)).

(27) The backer plate **10** is preferably constructed of a rigid material and includes a front and rear surface. A plurality of coupling devices, such as top coupling devices **12** and bottom coupling devices **13** attach to the rear surface of the backer plate **10**, as shown in FIGS. **2**, **6**, **10-15**, **18** and **19**. The top and bottom coupling devices **12**, **13**, are configured for coupling to one or more existing structural elements such as, but not limited to, railing, posts, walls, beams or columns. The top and bottom coupling devices **12**, **13**, are any type of suitable coupling device, such as hooks or clamps. At least one of the plurality of top and bottom coupling devices **12**, **13**, is configured to be translationally adjustable. In one aspect, the top coupling devices **12** are configured to couple to a first cylindrical railing member and the bottom coupling devices **13** are configured to couple to a second cylindrical railing member, wherein the first cylindrical railing member has a larger diameter than the second cylindrical railing member. It is anticipated that the number, layout, type, and size of the plurality of coupling devices can vary to accommodate a variety of structural elements which the support apparatus **1** may be configured to attach to. Further, the plurality of coupling devices are interchangeable depending on the geometry of the one or more existing structural support elements.

(28) In one aspect, as shown in FIGS. **1**, **2**, **5**, **8B**, **13** (top of tray) and **16**, **17** and **20** (bottom of tray), the power supply tray **14** includes a rear member **15** adjacent to the backer plate **10**. The rear member **15** is configured to couple to the backer plate **10**. In one aspect, the rear member **15** includes two tabs **16** spaced apart and extending from the top end of the rear member. The tabs **16** are configured to couple to the top end of the backer plate **10**. The rear member **15** further includes right and left opposing side walls **17** (one each extending from the rear member on the right side and on the left side), a bottom wall **22** extending from the rear member, and at least one brace spanning between and coupled to the right side wall **17** and to the left side wall **17**. In one aspect, the at least one brace includes a top brace **18** and a bottom brace **19**. Each of the right and left ends of the top and bottom braces **18**, **19** are coupled on the corresponding right and left side walls **17**. In one aspect, as shown in FIGS. **16**, **17** and **20**, the bottom wall **22** includes at least one mounting protrusion **24** coupled to an exterior surface of the bottom wall, and configured to couple to at least one mounting bracket **26** connected to the front surface of the backer plate **10**. In another aspect, two mounting protrusions **24** may be included, spaced apart, and each coupled to corresponding two mounting brackets **26**, as shown in the figures.

(29) The pair of stiffening plates **20** are configured to couple to the backer plate **10** and are disposed each on opposing sides of the pivotable bracket assembly **30**. The pair of stiffening plates **20** are each one attached to the front surface of the backer plate **10** near the bottom, at the opposing right and left outer edges, and are substantially aligned parallel with one another, spaced apart, as shown in FIGS. **5**, **9**, **16** and **20**.

(30) The pivotable bracket assembly **30** includes, but is not limited to, a front plate **32**, a rear plate **34**, a base plate **36**, an intermediate brace **38**, and a mounting block **40**. As shown in FIG. **15**, the vertical space between the rear plate **34** and the backer plate **10** forms a rear compartment **41**, and the rear compartment is configured to house the power supply tray **14** and the stationary power

supply 4.

(31) The mounting block **40** is preferably formed of a rigid material, and, as shown in FIGS. **19** and **20**, the mounting block **40** is configured as a generally rectangular band. The mounting block **40** is disposed below the base plate **36**. The right and left ends of the pivot axis rod **60** are pivotally connected to the mounting block **40** of the pivotable bracket assembly **30**, and the pivot axis rod spans between and is rigidly connected to each of the two stiffening plates **20** at their front top corners. The pivot axis rod **60** is constructed of a rigid material, such as a metal alloy, and is preferably a solid cylinder. However, it is anticipated that the pivot axis rod **60** may alternatively be tubular.

(32) Referring to FIGS. **1-3**, the front plate **32**, rear plate **34**, base plate **36**, and intermediate brace **38** provide a device storage space for storing and securing the portable electronic device **2**. The pivotable bracket assembly **30** is pivotally configurable about the pivotal axis rod **60** and may be disposed in the upright vertical position, as shown in FIG. **1**, or rotated forward and down to the inclined position by the user, as shown in FIG. **3**.

(33) The inclined position shown in FIG. **3** provides the user convenient access to insert as well as pick up the portable electronic device **2** from the pivotable bracket assembly **30** without having to detach the support apparatus **1** from its wearable container assembly that is exemplified in FIG. **4**. The inclined position comprises a pivotal rotation of the pivotable bracket assembly **30** of approximately 60 degrees forward relative to its upright position. However, it is anticipated that the inclined position may be greater than or less than 60 degrees.

(34) The front plate **32** is configured in a substantially rectangular profile and has a top end and a bottom end. The front plate **32** is rigidly connected to the mounting block **40** near its bottom end, as shown in FIGS. **1** and **5**. The front plate **32** is detachably coupled to the securement strap **42** near the top end of the front plate, and it is attached to the intermediate brace **38** in-between its top and bottom ends.

(35) The securement strap **42** is configured to couple the front of the pivotable bracket assembly **30** to the backer plate **10** while securing the top of the portable electronic device **2**. The securement strap **42** couples to and links the front plate **32** to the top of the backer plate **10** and includes a clip **43** configured for releasably fastening together the top and bottom portions of the securement strap. The top portion of the securement strap **42** includes a spacer brace **44** coupled underneath. The spacer brace **44** is configured to secure the top edges of the portable electronic device **2** (see FIG. **4**) while providing a clearance access space above the central top of the portable electronic device. The securement strap **42** is configured to be adjustable, such that it can be pulled taut when installed onto the portable electronic device **2** to further restrict movement of the pivotable bracket assembly **30** when it is oriented in its upright position.

(36) The intermediate brace **38** spans from the rear plate **34** to the front plate **32**, as shown in FIGS. **8A** and **9**, and provides lateral restraint of the portable electronic device **2** (see FIG. **4**). The intermediate brace **38** is preferably constructed of one or more pliable straps which are removably coupled to the front and rear plates **32**, **34**. However, it is also anticipated the intermediate brace **38** could, alternatively, be constructed of rigid or semi-rigid materials. In one aspect, the intermediate brace **38** is configured to be adjustable.

(37) As shown in FIG. **15**, the rear plate **34** has a top and bottom end and is rigidly connected to the rear of the mounting block **40** near its bottom end (see also FIGS. **19** and **20**). The rear plate **34** is preferably oriented in a substantially parallel plane relative to the front plate **32** and is preferably rigid. Additionally, the rear plate **34** has two protrusions **48**, each extending outward from opposing left and right sides, as shown in FIGS. **8A** and **9**. Each protrusion **48** of the two protrusions includes a notched recess which aids in positioning the intermediate brace **38** at a predetermined height.

(38) The base plate **36** preferably includes a bent plate with a u-shaped profile, as shown in FIGS. **1** and **7-8B**. The two upturned ends of the base plate **36** provide lateral support for securing the portable electronic device **2** within the pivotable bracket assembly **30**. The base plate **36** includes at

least one aperture 37 (see FIGS. 8A, 11, 12, 16 and 20) to provide enhanced cooling airflow passage up to the portable electronic device 2. The base plate 36 may optionally further include a bearing pad 46 coupled to the top surface of the base plate which assists in securement of the portable electronic device 2 as well as reducing the transmissibility of vibrations from the support apparatus 1 to the portable electronic device. The bearing pad 46 includes a cutout 47 (see FIGS. 8A and 11) aligned with the aperture 37 to allow unobstructed cooling airflow passage up to the portable electronic device 2. It is anticipated that a compressible pad 45 may be coupled to the rear surface of the front plate 32 as shown in FIGS. 2, 3, 6, and 13-15 to compress against the front of the portable electronic device 2 to further assist in securing the portable electronic device.

(39) In one aspect, the mounting block 40 may additionally be mechanically linked to at least one stabilizer 50, as shown in FIGS. 5, 9, 16, 17 and 19. The stabilizer 50 may be any suitable device, such as, for example, a mechanical spring or a gas spring and is configured to stabilize the pivotable bracket assembly 30 as it rotates about the pivotal axis rod 60 by restricting/slowing the rate at which the pivotable bracket assembly is capable of rotating. In one aspect, the top end of the stabilizer 50 is pivotally connected to the interior surface of the left sidewall of the mounting block 40, and the bottom end is pivotally connected near to the bottom left of the front surface of the backer plate 10. The stabilizer 50 is configured to be axially extensible to a predetermined maximum distance under a predetermined axial load.

(40) The locking feature 62 is configured to selectively retain the pivotable bracket assembly 30 in the upright vertical position, as shown in FIG. 1, by selectively preventing the pivotable bracket assembly from rotating about the pivotal axis rod 60 forward and down to the inclined position (as shown in FIG. 3). The locking feature 62 may be any suitable locking feature, such as, for example, pins, clamps or latches. In one aspect, the locking feature 62 includes a pair of locking pins configured to detachably couple one of the two stiffening plates 20 to a distinct side wall of the mounting block 40, as shown in FIGS. 5, 17, 19 and 20. The locking feature 62, when inserted, creates a shear plane relative to the respective stiffening plates 20 and mounting block 40 which decouples the moment resulting from the eccentricity between the center of gravity of the pivotable bracket assembly 30 and the longitudinal axis of the pivotal axis rod 60. Each locking feature 62 is preferably tethered to its respective stiffening plate 20 by a cord that is attached to the exterior surface of the respective stiffening plate 20. The user would remove each of the locking features 62 prior to rotating the pivotable bracket assembly 30 forward to the inclined position, and then re-insert each of the locking features back into the stiffening plates 20 after returning the pivotable bracket assembly back to its upright position.

(41) As shown in FIGS. 8A, 9 and 18, the support apparatus 1 further includes a pair of auxiliary compartments 70, one of each of the auxiliary compartments being disposed on the right side and the left side of the backer plate 10. The auxiliary compartment 70 is configured with a generally basket shaped profile and includes at least one strap 72 configured for securing a supplemental power supply unit 74 (see FIG. 4). The least one strap 72 is configured to be adjustable. The supplemental power supply unit 74 may be any suitable supplemental power supply unit configured to be electrically coupled to the portable electronic device 2, such as, for example, batteries. The support apparatus 1 may optionally also include an auxiliary screen support 76 configured for securing an electronic display device 78, such as a tablet, for example (see FIG. 4). The electronic display device 78 may be configured to be electronically coupled to the portable electronic device 2. The two auxiliary compartments 70 and auxiliary screen support 76 are each rigidly coupled to the backer plate 10.

(42) While the foregoing exemplary non-limiting embodiments of the support apparatus have been disclosed herein, certain modifications may be made by those skilled in the art to modify the embodiments without departing from the scope of the claims.

Claims

1. A support apparatus for securing a portable electronic device comprising: backer plate comprising a front surface and a rear surface; a plurality of coupling devices coupled to the rear surface of the backer plate; wherein the plurality of coupling devices are configured for coupling the support apparatus to one or more existing structural support elements; a power supply tray coupled to the backer plate; wherein the power supply tray is configured to secure a stationary power supply which is electrically coupled to the portable electronic device; a pivotable bracket assembly; wherein the pivotable bracket assembly is configured for securing the portable electronic device, and for enabling rotation of the portable electronic device from an upright vertical position down to an inclined position; a pair of stiffening plates; wherein the stiffening plates are configured to couple to the backer plate and are disposed each on opposing sides of the pivotable bracket assembly; a pivot axis rod; wherein the pivot axis rod is configured for pivotal connection to the pivotable bracket assembly, and for rigid connection to the opposing stiffening plates; a locking feature; wherein the locking feature is configured to selectively retain the pivotable bracket assembly in the upright vertical position by selectively preventing the pivotable bracket assembly from rotating about the pivotal axis rod forward and down to the inclined position; and a securement strap; wherein the securement strap is configured to couple a front of the pivotable bracket assembly to the backer plate while securing a top of the portable electronic device.
2. The support apparatus of claim 1, wherein the plurality of coupling devices includes at least one coupling device configured to be translationally adjustable.
3. The support apparatus of claim 1, wherein the power supply tray further includes a right side wall, a left side wall, and at least one brace spanning between and coupled to the right side wall and to the left side wall.
4. The support apparatus of claim 3, wherein the power supply tray further includes a bottom wall having at least one mounting protrusion coupled to an exterior surface of the bottom wall and configured to couple to at least one mounting bracket connected to the front surface of the backer plate.
5. The support apparatus of claim 1, wherein the pivotable bracket assembly further includes a front plate, a rear plate, a base plate, an intermediate brace, and a mounting block; wherein the mounting block is disposed below the base plate and configured to pivotally connect to the pivot axis rod.
6. The support apparatus of claim 5, wherein the base plate includes at least one aperture to provide enhanced cooling airflow passage up to the portable electronic device.
7. The support apparatus of claim 5, further comprising a stabilizer configured to mechanically link between the mounting block and the backer plate, and to restrict the rate at which the pivotable bracket assembly is rotating.
8. A support apparatus for securing a portable electronic device comprising: backer plate comprising a front surface and a rear surface; a plurality of coupling devices coupled to the rear surface of the backer plate; wherein the plurality of coupling devices are configured for coupling the support apparatus to one or more existing structural support elements; wherein the plurality of coupling devices are interchangeable depending on the geometry of the one or more existing structural support elements; a power supply tray coupled to the backer plate; wherein the power supply tray is configured to secure a stationary power supply which is electrically coupled to the portable electronic device; a pivotable bracket assembly; wherein the pivotable bracket assembly is configured for securing the portable electronic device, and for enabling rotation of the portable electronic device from an upright vertical position down to an inclined position; a pair of stiffening plates; wherein the stiffening plates are configured to couple to the backer plate and are disposed each on opposing sides of the pivotable bracket assembly; a pivot axis rod; wherein the pivot axis

rod is configured for pivotal connection to the pivotable bracket assembly, and for rigid connection to the opposing stiffening plates; a locking feature; wherein the locking feature is configured to selectively retain the pivotable bracket assembly in the upright vertical position by selectively preventing the pivotable bracket assembly from rotating about the pivotal axis rod forward and down to the inclined position; and a securement strap; wherein the securement strap is adjustable and configured to couple a front of the pivotable bracket assembly to the backer plate while securing a top of the portable electronic device.

9. The support apparatus of claim 8, wherein the plurality of coupling devices includes at least one coupling device configured to be translationally adjustable.

10. The support apparatus of claim 8, further comprising a pair of auxiliary compartments; wherein each of the auxiliary compartments includes at least one strap configured for securing a supplemental power supply unit configured to be electrically coupled to the portable electronic device; and wherein each of the auxiliary compartments is rigidly coupled to a right side and to a left side of the backer plate.

11. The support apparatus of claim 8, further comprising an auxiliary screen support configured for securing an electronic display device; wherein the electronic display device is configured to be electronically coupled to the portable electronic device; and wherein the auxiliary screen support is rigidly coupled to the backer plate.

12. The support apparatus of claim 8, wherein the pivotable bracket assembly further includes a front plate, a rear plate, a base plate, an intermediate brace, and a mounting block; wherein the mounting block is disposed below the base plate and configured to pivotally connect to the pivot axis rod.

13. The support apparatus of claim 12, wherein the intermediate brace is configured to be adjustable.

14. The support apparatus of claim 12, further comprising a gas spring configured to mechanically link between the mounting block and the backer plate, and to restrict the rate at which the pivotable bracket assembly is rotating.

15. A support apparatus for securing a portable electronic device comprising: backer plate comprising a front surface and a rear surface; a plurality of coupling devices coupled to the rear surface of the backer plate; wherein the plurality of coupling devices are configured for coupling the support apparatus to one or more existing structural support elements; a power supply tray coupled to the backer plate; wherein the power supply tray is configured to secure a stationary power supply which is electrically coupled to the portable electronic device; a pivotable bracket assembly; wherein the pivotable bracket assembly is configured for securing the portable electronic device, and for enabling rotation of the portable electronic device from an upright vertical position down to an inclined position; a pair of stiffening plates; wherein the stiffening plates are configured to couple to the backer plate and are disposed each on opposing sides of the pivotable bracket assembly; a pivot axis rod; wherein the pivot axis rod is configured for pivotal connection to the pivotable bracket assembly, and for rigid connection to the opposing stiffening plates; a locking feature; wherein the locking feature is configured to selectively retain the pivotable bracket assembly in the upright vertical position by selectively preventing the pivotable bracket assembly from rotating about the pivotal axis rod forward and down to the inclined position; a securement strap; wherein the securement strap is configured to couple a front of the pivotable bracket assembly to the backer plate while securing a top of the portable electronic device; and a stabilizer; wherein the stabilizer is configured to mechanically link between the pivotable bracket assembly and the backer plate, and to restrict the rate at which the pivotable bracket assembly is rotating.

16. The support apparatus of claim 15, wherein the stabilizer is a gas spring.

17. The support apparatus of claim 15, wherein the plurality of coupling devices includes at least one coupling device configured to be translationally adjustable.

18. The support apparatus of claim 15, wherein the pivotable bracket assembly further includes a

front plate, a rear plate, a base plate, an intermediate brace, and a mounting block; wherein the mounting block is disposed below the base plate and configured to pivotally connect to the pivot axis rod.

19. The support apparatus of claim 18, wherein the vertical space between the rear plate and the backer plate forms a rear compartment; wherein the rear compartment is configured to house the power supply tray and the stationary power supply.

20. The support apparatus of claim 18, wherein the power supply tray further includes a rear member, a right side wall, a left side wall, a bottom wall, and at least one brace spanning between and coupled to the right side wall and to the left side wall; and wherein the right side wall, the left side wall, and the bottom wall each extend from the rear member.
