

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250257643

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Curry; Zachary et al.

---

### SYSTEM AND METHOD FOR AN AUTOMATED AND INTELLIGENT FRAC PAD

---

#### Abstract

A system may include a built hydraulic fracturing system with a plurality of devices connected together and a simulation of the built hydraulic fracturing system on a software application. Additionally, a fracturing plan may be provided on the software application to include pre-made instructions to perform multiple processes in a hydraulic fracturing operation such as a sequence of valve operations to direct fluid flow through a selected path. Further, the fracturing plan may be modified to create a customized fracturing plan including the pre-made instructions and at least one modified instruction. Furthermore, the customized fracturing plan may be executed to perform at least one of the processes in the built hydraulic fracturing system.

---

**Inventors:** Curry; Zachary (Houston, TX), Cappello; Andrew (Houston, TX), Machado; Thiago (Houston, TX), Cook; James (Houston, TX), Gunatilleke; Sobitha (Houston, TX), Pillai; Rajeev (Houston, TX), Anzola; Hernan (Houston, TX), Ramsey; Nathaniel (Houston, TX), Dixon; Clay (Houston, TX), Tivioli-Melchert; Gabriel (Houston, TX)

**Applicant:** FMC Technologies, Inc. (Houston, TX)

**Family ID:** 1000008563613

**Appl. No.:** 19/193571

**Filed:** April 29, 2025

#### Related U.S. Application Data

parent US continuation 18619603 20240328 parent-grant-document US 12312929 child US 19193571

parent US continuation 17608093 20211101 parent-grant-document US 11976541 US continuation PCT/US2020/033383 20200518 child US 18619603

us-provisional-application US 62849375 20190517

---

## Publication Classification

Int. Cl.: E21B43/26 (20060101)

U.S. Cl.:

CPC E21B43/2607 (20200501); E21B2200/20 (20200501)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This patent application is a continuation application claiming priority benefit, with regard to all common subject matter, of U.S. patent application Ser. No. 18/619,603, filed Mar. 28, 2024, entitled “SYSTEM AND METHOD FOR AN AUTOMATED AND INTELLIGENT FRAC PAD” (“the '603 application”). The '603 application is a continuation application claiming priority benefit, with regard to all common subject matter, of U.S. patent application Ser. No. 17/608,093, filed Nov. 1, 2021, entitled “SYSTEM AND METHOD FOR AN AUTOMATED AND INTELLIGENT FRAC PAD,” now U.S. Pat. No. 11,976,541 (“the '541 patent”). The '541 patent is a National Stage Entry of PCT/US2020/033383, filed May 18, 2020, entitled “SYSTEM AND METHOD FOR AN AUTOMATED AND INTELLIGENT FRAC PAD,” which claims priority benefit, with regard to all common subject matter, of U.S. Provisional Patent Application No. 62/849,375, filed May 17, 2019, entitled “SYSTEM AND METHOD FOR AN AUTOMATED AND INTELLIGENT FRAC PAD.” The above-referenced applications and patent are hereby incorporated by reference in their entirety into the present application.

## BACKGROUND

[0002] Hydraulic fracturing is a stimulation treatment routinely performed on oil and gas wells in low-permeability reservoirs. Specially engineered fluids are pumped at high pressure and rate into the reservoir interval to be treated, causing a vertical fracture to open. The wings of the fracture extend away from the wellbore in opposing directions according to the natural stresses within the formation. Proppant, such as grains of sand of a particular size, is mixed with the treatment fluid to keep the fracture open when the treatment is complete. Hydraulic fracturing creates high-conductivity communication with a large area of formation and bypasses any damage that may exist in the near-wellbore area. Furthermore, hydraulic fracturing is used to increase the rate at which fluids, such as petroleum, water, or natural gas can be recovered from subterranean natural reservoirs. Reservoirs are typically porous sandstones, limestones or dolomite rocks, but also include “unconventional reservoirs” such as shale rock or coal beds. Hydraulic fracturing enables the extraction of natural gas and oil from rock formations deep below the earth's surface (e.g., generally 2,000-6,000 m (5,000-20,000 ft)), which is greatly below typical groundwater reservoir levels. At such depth, there may be insufficient permeability or reservoir pressure to allow natural gas and oil to flow from the rock into the wellbore at high economic return. Thus, creating conductive fractures in the rock is instrumental in extraction from naturally impermeable reservoirs.

[0003] A wide variety of hydraulic fracturing equipment is used in oil and natural gas fields such as a slurry blender, one or more high-pressure, high-volume fracturing pumps and a monitoring unit. Additionally, associated equipment includes fracturing tanks, one or more units for storage and handling of proppant, high-pressure treating iron, a chemical additive unit (used to accurately monitor chemical addition), low-pressure flexible hoses, and many gauges and meters for flow rate, fluid density, and treating pressure. Fracturing equipment operates over a range of pressures and

injection rates, and can reach up to 100 megapascals (15,000 psi) and 265 litres per second (9.4 cu ft/s) (100 barrels per minute).

[0004] With the wide variety of hydraulic fracturing equipment at a well site, the hydraulic fracturing operation may be conducted. A hydraulic fracturing operation requires planning, coordination, and cooperation of all parties. Safety is always the primary concern in the field, and it begins with a thorough understanding by all parties of their duties. Additionally, before a hydraulic fracturing operation, a worker, rig personal, or an engineer may conduct a detailed inventory of all the equipment and materials on location. The inventory should be compared with the design and the prognosis. After the hydraulic fracturing operation has concluded, another inventory of all the materials left on location should be conducted. In most cases, the difference in the two inventories can be used to verify what was mixed and pumped into the wellbore and the hydrocarbon-bearing formation. Conventional hydraulic fracturing operations are dependent on workers being present to oversee and conduct said operation over the full life-time to complete said operation.

#### SUMMARY OF DISCLOSURE

[0005] This summary is provided to introduce a selection of concepts that are further described below in the detailed description. This summary is not intended to identify key or essential features of the claimed subject matter, nor is it intended to be used as an aid in limiting the scope of the claimed subject matter.

[0006] In one aspect, this disclosure relates to a method that may include providing a template fracturing plan on a software application. Additionally, the template fracturing plan may include pre-made instructions to perform multiple processes carried out by a generic hydraulic fracturing system. Further, the method may include modifying the template fracturing plan to create a customized fracturing plan including the pre-made instructions and at least one modified instruction, and executing the customized fracturing plan to perform at least one of the processes in a built hydraulic fracturing system comprising a plurality of devices.

[0007] In another aspect, this disclosure relates to a method that may include mapping a plurality of devices in a hydraulic fracturing system into a simulated hydraulic fracturing system using a software application. Additionally, the method may include adding a new device, which may be firmware, to the hydraulic fracturing system and mapping the new device into the simulated hydraulic fracturing system. Further, the mapping of the new device may include casting a search for signals within a radius encompassing the hydraulic fracturing system, detecting at least one signal from the new device firmware, and communicating the new device firmware with the software application.

[0008] In yet another aspect, this disclosure relates to a system that may include a built hydraulic fracturing system with a plurality of devices connected together and a simulation of the built hydraulic fracturing system on a software application. Additionally, the system may further include a fracturing plan provided on the software application, wherein the fracturing plan may include instructions to perform multiple processes in a hydraulic fracturing operation such as a sequence of valve operations to direct fluid flow through a selected path.

[0009] Other aspects and advantages will be apparent from the following description and the appended claims.

---

## Description

#### BRIEF DESCRIPTION OF DRAWINGS

[0010] FIGS. 1A-1C illustrate a view of a hydraulic fracturing system at a well site according to one or more embodiments of the present disclosure.

[0011] FIG. 2 illustrates a view of a human machine interface (“HMI”) of the hydraulic fracturing system of FIGS. 1A-1C according to one or more embodiments of the present disclosure.

[0012] FIG. 3 illustrates a flowchart of automating a hydraulic fracturing system at a well site according to one or more embodiments of the present disclosure.

[0013] FIG. 4 illustrates a flowchart of a simulated hydraulic fracturing system according to one or more embodiments of the present disclosure.

#### DETAILED DESCRIPTION

[0014] Embodiments of the present disclosure are described below in detail with reference to the accompanying figures. Wherever possible, like or identical reference numerals are used in the figures to identify common or the same elements. The figures are not necessarily to scale and certain features and certain views of the figures may be shown exaggerated in scale for purposes of clarification. Further, in the following detailed description, numerous specific details are set forth in order to provide a more thorough understanding of the claimed subject matter. However, it will be apparent to one having ordinary skill in the art that the embodiments described may be practiced without these specific details. In other instances, well-known features have not been described in detail to avoid unnecessarily complicating the description. As used herein, the term “coupled” or “coupled to” or “connected” or “connected to” may indicate establishing either a direct or indirect connection, and is not limited to either unless expressly referenced as such.

[0015] Further, embodiments disclosed herein are described with terms designating a rig site in reference to a land rig, but any terms designating rig type should not be deemed to limit the scope of the disclosure. For example, embodiments of the disclosure may be used on an offshore rig and various rig sites, such as land/drilling rig and drilling vessel. It is to be further understood that the various embodiments described herein may be used in various stages of a well, such as rig site preparation, drilling, completion, abandonment etc., and in other environments, such as work-over rigs, fracking installation, well-testing installation, and oil and gas production installation, without departing from the scope of the present disclosure. The embodiments are described merely as examples of useful applications, which are not limited to any specific details of the embodiments herein.

[0016] In a fracturing operation, a plurality of equipment (i.e., fracturing equipment) is disposed around a rig site to perform a wide variety of fracturing operations during a life of the fracturing operation (i.e., rig site preparation to fracturing to removal of fracturing equipment) and form a built hydraulic fracturing system. At the site, there is a wide variety of fracturing equipment for operating the fracturing, such as, a slurry blender, one or more high-pressure, high-volume fracturing pumps a monitoring unit, fracturing tanks, one or more units for storage and handling of proppant, high-pressure treating iron, a chemical additive unit (used to accurately monitor chemical addition), low-pressure flexible hoses, and many gauges and meters for flow rate, fluid density, treating pressure, etc. The fracturing equipment encompasses a number of components that are durable, sensitive, complex, simple components, or any combination thereof. Furthermore, it is also understood that one or more of the fracturing equipment may be interdependent upon other components. Once the fracturing equipment is set up, typically, the fracturing operation may be capable of operating 24 hours a day.

[0017] Conventional hydraulic fracturing systems in the oil and gas industry typically require an entire team of workers to ensure proper sequencing. For example, a valve team may meet, plan, and agree on a valve sequence to then actuate the valves. As a result, conventional hydraulic fracturing systems are prone to human errors resulting in improper actuation of valves and expensive damage and non-productive time (NPT). In addition, there is no automated log of valve phases and operational information as conventional hydraulic fracturing systems are monitored by workers. As such, conventional hydraulic fracturing systems may fail to have real-time information on how long an activity lasted/duration and data supporting operational improvement or how many times valves have been actuated to determine maintenance requirements or service requirements.

[0018] One or more embodiments in the present disclosure may be used to overcome such challenges as well as provide additional advantages over conventional hydraulic fracturing systems.

For example, in some embodiments, an automated hydraulic fracturing system including a computing system described herein and a plurality of sensors working in conjunction with built hydraulic fracturing system may streamline and improve efficiency as compared with conventional hydraulic fracturing systems due, in part, to reducing or eliminating human interaction with the hydraulic fracturing systems by automating fracturing operations, monitoring, logging and alerts. [0019] In one aspect, embodiments disclosed herein relate to automating a hydraulic fracturing system that may perform multiple processes in a hydraulic fracturing operation. In another aspect, embodiments disclosed herein relate to simulating hydraulic fracturing systems. Simulations may be used, for example, to plan and/or execute hydraulic fracturing operations. Further, simulating hydraulic fracturing systems may be used in forming and executing automated hydraulic fracturing systems.

[0020] Simulated and automated hydraulic fracturing systems may utilize a fracturing plan provided on a software application, which may include pre-made instructions to perform multiple processes carried out by the hydraulic fracturing system. Such fracturing plans may include automating valves within the hydraulic fracturing system to have a valve sequencing (e.g., opening and closing) to direct fluids (e.g., frac fluid) in a selected path and/or control pressure within the system. As used herein, a valve may be interchangeably referred to as a gate valve in the present disclosure. Further, fluids may refer to slurries, liquids, gases, and/or mixtures thereof. In some embodiments, solids may be present in the fluids. Automating a hydraulic fracturing system according to one or more embodiments described herein may provide a cost-effective alternative to conventional hydraulic fracturing systems. The embodiments are described merely as examples of useful applications, which are not limited to any specific details of the embodiments herein.

[0021] FIG. 1A shows an automated hydraulic fracturing system according to embodiments of the present disclosure. The automated hydraulic fracturing system includes a built physical hydraulic fracturing system **100** having a plurality of connected together fracturing equipment at a rig site **1**. The built hydraulic fracturing system **100** may include at least one wellhead assembly **101** (e.g., a Christmas tree) coupled to at least one time and efficiency (TE) or zipper manifold **102** through one or more flow lines (not shown). The hydraulic fracturing system **100** may further include at least one pump manifold **103** in fluid communication with the zipper manifold **102**. In use, the at least one pump manifold **103** may be fluidly connected to and receive pressurized fracking fluid from one or more high pressure pumps (not shown), and direct that pressurized fracking fluid to the zipper manifold **102**, which may include one or more valves that may be closed to isolate the wellhead assembly **101** from the flow of pressurized fluid within the zipper manifold **102** and pump manifold **103**. Additionally, the at least one wellhead assembly **101** may comprise one or more valves fluidly connected to a wellhead that are adapted to control the flow of fluid into and out of wellhead. Typical valves associated with a wellhead assembly include, but are not limited to, upper and lower master valves, wing valves, and swab valves, each named according to a respective functionality on the wellhead assembly **101**.

[0022] Additionally, the valves of the at least one wellhead assembly **101** and zipper manifold **102** may be gate valves that may be actuated, but not limited to, electrically, hydraulically, pneumatically, or mechanically. In some embodiments, the built hydraulic fracturing system **100** may include a system **150** that may provide power to actuate the valves of the built hydraulic fracturing system **100**. In a non-limited example, when the valves are hydraulically actuated, the system **150** may include a hydraulic skid with accumulators to provide the hydraulic pressure required to open and close the valves, when needed. The system **150** may also be interchangeably referred to as a valve control system in the present disclosure.

[0023] Further, the built hydraulic fracturing system **100** includes a plurality of additional rig equipment for fracturing operations. In a non-limiting example, the built hydraulic fracturing system **100** may include at least one auxiliary manifold **104**, at least one pop-off/bleed-off tank manifold **105**, at least one isolation manifold **106**, and/or a spacer manifold **107**. The at least one

pump manifold **103** may be used to inject a slurry into the wellbore in order to fracture the hydrocarbon bearing formation, and thereby produce channels through which the oil or gas may flow, by providing a fluid connection between pump discharge and the hydraulic fracturing system **100**. The auxiliary manifold **104** may provide a universal power and control unit, including a power unit and a primary controller of the hydraulic fracturing system **100**. The at least one pop-off/bleed-off tank manifold **105** may allow discharge pressure from bleed off/pop off operations to be immediately relieved and controlled. The at least one isolation manifold **106** may be used to allow pump-side equipment and well-side equipment to be isolated from each other. The spacer manifold **107** may provide spacing between adjacent equipment, which may include equipment to connect between the equipment in the adjacent manifolds.

[0024] In one or more embodiments, the manifolds **102**, **103**, **104**, **105**, **106**, **107** may each include a primary manifold connection **110** with a single primary inlet and a single primary outlet and one or more primary flow paths extending therebetween mounted on same-sized A-frames **108**.

Additionally, the built hydraulic fracturing system **100** may be modular to allow for easy transportation and installation on the rig site. In a non-limiting example, the built hydraulic fracturing system **100** in accordance with the present disclosure may utilize the modular fracturing pad structure systems and methods, according to the systems and methods as described in U.S. patent application Ser. No. 15/943,306, which the entire teachings of are incorporated herein by reference. While not shown by FIG. **1**, one of ordinary skill in the art would understand the built hydraulic fracturing system **100** may include further equipment, such as, a blowout preventer (BOP), completions equipment, topdrive, automated pipe handling equipment, etc. Further, the built hydraulic fracturing system **100** may include a wide variety of equipment for different uses; and thus, for the purposes of simplicity, the terms “plurality of devices” or “rig equipment” are used hereinafter to encompass the wide variety equipment used to form a built hydraulic fracturing system comprising a plurality of devices connected together.

[0025] Still referring to FIG. **1A**, the automated hydraulic fracturing system may further include a plurality of sensors **111** provided at the rig site **1**. The plurality of sensors **111** may be associated with some or all of the plurality of devices of the built hydraulic fracturing system **100**, including components and subcomponents of the devices. In a non-limiting example, some of the plurality of sensors **111** may be associated with each of the valves of the wellhead assembly **101** and zipper manifold **102**. The plurality of sensors **111** may be a microphone, ultrasonic, ultrasound, sound navigation and ranging (SONAR), radio detection and ranging (RADAR), acoustic, piezoelectric, accelerometers, temperature, pressure, weight, position, or any sensor in the art to detect and monitor the plurality of devices. The plurality of sensors **111** may be disposed on the plurality of devices at the rig site **1** and/or during the manufacturing of said devices. It is further envisioned that the plurality of sensors **111** may be provided inside a component of the plurality of devices. Additionally, the plurality of sensors **111** may be any sensor or device capable of wireline monitoring, valve monitoring, pump monitoring, flow line monitoring, accumulators and energy harvesting, and equipment performance and damage.

[0026] The plurality of sensors **111** may be used to collect data on status, process conditions, performance, and overall quality of the device that said sensors are monitoring, for example, on/off status of equipment, open/closed status of valves, pressure readings, temperature readings, and others. One skilled in the art will appreciate the plurality of sensors **111** may aid in detecting possible failure mechanisms in individual components, approaching maintenance or service, and/or compliance issues. In some embodiments, the plurality of sensors **111** may transmit and receive information/instructions wirelessly and/or through wires attached to the plurality of sensors **111**. In a non-limiting example, each sensor of the plurality of sensors **111** may have an antenna (not shown) to be in communication with a master antenna **112** on any housing **113** at the rig site **1**. The housing **113** may be understood to one of ordinary skill to be any housing typically required at the rig site **1** such as a control room where an operator **114** may be within operator and view the rig

site **1** from a window **115** of the housing **113**. It is further envisioned that the plurality of sensors **111** may transmit and receive information/instructions to a remote location away from rig site **1**. In a non-limiting example, that the plurality of sensors **111** may collect signature data on the plurality of devices and deliver a real-time health analysis of plurality of devices.

[0027] In one aspect, a plurality of sensors **111** may be used to record and monitor the hydraulic fracturing equipment to aid in carrying out the fracturing plan. Additionally, data collected from the plurality of sensors **111** may be logged to create real-time logging of operational metric, such as duration between various stages and determining field efficiency. In a non-limiting example, the plurality of sensors **111** may aid in monitoring a valve position to determine current job state and provides choices for possible stages. In some examples, the plurality of sensors may provide information such that a current state of the hydraulic fracturing operation, possible failures of hydraulic fracturing equipment, maintenance or service requirements, and compliance issues that may arise is obtained. By obtaining such information, the automated hydraulic fracturing systems may form a closed loop valve control system, valve control and monitoring without visual inspection, and reduce or eliminate human interaction with the hydraulic fracturing equipment.

[0028] An automated hydraulic fracturing system may include a computing system for implementing methods disclosed herein. The computing system may include an human machine interface (“HMI”) using a software application and may be provided to aid in the automation of a built hydraulic fracturing system. In some embodiments, an HMI **116**, such as a computer, control panel, and/or other hardware components may allow the operator **114** to interact through the HMI **116** with the built hydraulic fracturing system **100** in an automated hydraulic fracturing system. The HMI **116** may include a screen, such as a touch screen, used as an input (e.g., for a person to input commands) and output (e.g., for display) of the computing system. In some embodiments, the HMI **116** may also include switches, knobs, joysticks and/or other hardware components which may allow an operator to interact through the HMI **116** with the automated hydraulic fracturing systems.

[0029] An automated hydraulic fracturing system, according to embodiments herein, may include the plurality of sensors **111**, valve control system **150**, and data acquisition hardware disposed on or around the hydraulic fracturing equipment, such as on valves, pumps and pipelines. In some embodiments, the data acquisition hardware is incorporated into the plurality of sensors **111**. In a non-limiting example, hardware in the automated hydraulic fracturing systems such as sensors, wireline monitoring devices, valve monitoring devices, pump monitoring devices, flow line monitoring devices, hydraulic skids including accumulators and energy harvesting devices, may be aggregated into single software architecture.

[0030] In one or more embodiments, single software architecture according to embodiments of the present disclosure may be implemented in one or more computing systems having the HMI **116** built therein or connected thereto. The single software architecture may be any combination of mobile, desktop, server, router, switch, embedded device, or other types of hardware may be used. For example, a computing system may include one or more computer processors, non-persistent storage (e.g., volatile memory, such as random access memory (RAM), cache memory), persistent storage (e.g., a hard disk, an optical drive such as a compact disk (CD) drive or digital versatile disk (DVD) drive, a flash memory, etc.), a communication interface (e.g., Bluetooth interface, infrared interface, network interface, optical interface, etc.), and numerous other elements and functionalities.

[0031] A computer processor(s) may be an integrated circuit for processing instructions. For example, the computer processor(s) may be one or more cores or micro-cores of a processor. Fracturing plans according to embodiments of the present disclosure may be executed on a computer processor. The computing system may also include one or more input devices, such as a touchscreen, keyboard, mouse, microphone, touchpad, electronic pen, or any other type of input device. Additionally, it is also understood that the computing system may receive data from the

sensors described herein as an input.

[0032] A communication interface may include an integrated circuit for connecting the computing system to a network (not shown) (e.g., a local area network (LAN), a wide area network (WAN) such as the Internet, mobile network, or any other type of network) and/or to another device, such as another computing device. Further, the computing system may include one or more output devices, such as a screen (e.g., a liquid crystal display (LCD), a plasma display, touchscreen, cathode ray tube (CRT) monitor, projector, or other display device), a printer, external storage, or any other output device. One or more of the output devices may be the same or different from the input device(s). The input and output device(s) may be locally or remotely connected to the computer processor(s), non-persistent storage, and persistent storage. Many different types of computing systems exist, and the aforementioned input and output device(s) may take other forms.

[0033] Software instructions in the form of computer readable program code to perform embodiments of the disclosure may be stored, in whole or in part, temporarily or permanently, on a non-transitory computer readable medium such as a CD, DVD, storage device, a diskette, a tape, flash memory, physical memory, or any other computer readable storage medium. Specifically, the software instructions may correspond to computer readable program code that, when executed by a processor(s), is configured to perform one or more embodiments of the disclosure. More specifically, the software instructions may correspond to computer readable program code, that when executed by a processor(s) may perform one or any of the automated hydraulic fracturing systems features described herein, including that associated with data interpretation and automated hydraulic fracturing systems.

[0034] Additionally, the software instructions may create a log of activities and users. In a non-limiting example, the log may maintain and monitor the operator **114** or others signing-in and signing-out, time usage of the fracturing plan, amount of times the fracturing plan was modified, amount times the operator **114** manually overrides the fracturing plan, maintenance of the plurality of devices, online and offline sensors, each modification added to the fracturing plan, and other operations performed at the rig site **1**.

[0035] The computing system may implement and/or be connected to a data repository, such as a database, which may be used to store data collected from an automated hydraulic fracturing system according to embodiments of the present disclosure. Such data may include, for example, valve data, such as identification of which valves in the system are open or closed, time recordings of when valves in the system open or close, time periods for how long valves in the system are open or closed, and valve pressure data. A database is a collection of information configured for ease of data retrieval, modification, re-organization, and deletion. The computing system of may include functionality to present raw and/or processed data, such as results of comparisons and other processing performed by an automation planner. For example, data may be presented through the HMI **116**. The HMI **116** may include a graphical user interface (GUI) that displays information on a display device of the HMI **116**. The GUI may include various GUI widgets that organize what data is shown as well as how data is presented to a user (e.g., data presented as actual data values through text, or rendered by the computing device into a visual representation of the data, such as through visualizing a data model).

[0036] The above description of functions presents only a few examples of functions performed by the computing system of automated hydraulic fracturing systems. Other functions may be performed using one or more embodiments of the disclosure.

[0037] The plurality of sensors **111** work in conjunction with the computer system to display information on the HMI **116**. Having the automated hydraulic fracturing system may significantly improve overall performance of the rig, rig safety, reduced risk of NPT and many other advantages. Embodiments of the present disclosure describe control systems, measurements, and strategies to automating rig operation (e.g., fracturing operations). It is further envisioned that the automated hydraulic fracturing system may locally collect, analyze, and transmit data to a cloud in real-time to



provide information, such as equipment health, performance metrics, alerts, and general monitoring, to third parties remotely or through the HMI **116**.

[0038] In some embodiments, a fracturing plan may be provided on the software application such that the fracturing plan may be displayed on the HMI **116**. The fracturing plan may be a set of instructions to perform multiple processes in a hydraulic fracturing operation. In a non-limiting example, the instructions may include a sequence of valve operations to direct fluid flow through a selected path in one or more of the wellhead assemblies and manifolds on the frac pad, with the sequence of valve operations being automatically controlled by the software through a valve control system associated with the valves. Further, the HMI **116** may have an emulate mode that can visually show the path through which fluid can flow by monitoring the valve positions to determine current job state and provides choices for possible stages. The emulate mode may allow the operator **114** to simulate a next stage of the fracturing operation prior to making changes to the fracturing plan. It is further envisioned that the software application may include a simulation system such that the fracturing plan may be simulated and said results may be displayed on the HMI **116**. Based on the simulated results, the fracturing plan may be modified to create a customized fracturing plan to be executed on the plurality of devices of the automated hydraulic fracturing system **10**. One skilled in the art will appreciate how the HMI **116** may allow the operator **114** to monitor, change, or shut down fracturing operation. In a non-limiting example, the HMI **116** may send permission requests to the operator **114** to perform various instructions from the fracturing plan and/or the customized fracturing plan. Additionally, the HMI **116** may include visual cues to allow for the monitoring and detection of a wireline stage, send alerts of a valve leak, and/or any erosion/corrosion caused by the flow of fluids in the plurality of devices.

[0039] In one or more embodiments, the plurality of sensors **111** may communicate with the software application on the computer system of the HMI **116** to automate the plurality of devices, such as a valve. In a non-limiting example, the fracturing plan may include an automated valve sequencing (e.g., when to open and close) during completion stage based on pre-approved sequence.

[0040] With reference to FIG. 2, FIG. 2 shows a non-limiting example of a simulated hydraulic fracturing system displayed on the HMI **116**. The simulation may include a plurality of equipment/devices **201** of a hydraulic fracturing system **200** arranged and connected together as they would be in the built hydraulic fracturing system (see **100** of FIGS. 1A-1C). The simulation may further show positions of devices being monitored and/or controlled through the system. In a non-limiting example, the simulation may display the open and closed positions of valves (e.g., see **202a** for open and **202b** for closed) in the hydraulic fracturing system **200**, thereby indicating the available path of fluid flow (see arrows **203**) through the system. The simulation may be used to simulate the outcome of a phase of hydraulic fracturing if selected devices were to be operated under certain parameters (e.g., if selected valves were opened or closed, if selected pumps were on or off, etc.). In some embodiments, the simulation may be used to evaluate performance and/or outcomes of hydraulic fracturing operations that have not yet been built or have not yet been operated. In some embodiments, the simulation may be used to simulate actual performance of an already built and in-use hydraulic fracturing system in order to monitor and evaluate the actual performance, which may be used, for example, to help make decisions on next steps in the operation. It is further envisioned that the HMI **116** may be a touch screen such that the operator (**114**) may open and close valves directly through the HMI **116**. Additionally, the HMI **116** may have buttons or portions of the touch screen **204** corresponding to commands in the simulated hydraulic fracturing system.

[0041] Additionally, the HMI **116** may store and display a logging of the operator **114** requesting valve operations and real-time logging of operational metric such as duration between various stages and determining field efficiency. Further, the HMI **116** may have a notification of current stage and alarming when valve moves out of place, such that an automated notification of possible

hazards in actuating certain valves may be displayed on the HMI **116**.

[0042] Referring back to FIG. **1A**, it is further envisioned that the plurality of sensors **111** may be used to determine a real-time conditioning of the plurality of devices, such as a valve (e.g., gate valve). In a non-limiting example, the software application, in one method, may instruct the plurality of sensors **111** to monitor a hydraulic pressure and stroke signature of the valve. The software application may then correlate said readings with a known pattern determined by experimentally and theoretically calculated data on the valve operating under good lubrication. Further, the pressure stroke signature may be known to follow a fixed pattern for specific valves. In an additional approach, the software application may instruct the plurality of sensors **111** to monitor hydraulic pressure spikes and volume of hydraulic fluid to determine a health status of the valve. In particular, algorithms based on a valve type may be used to determine when the valve is failing due to, for example, poor greasing conditions. It is further envisioned that the plurality of sensors **111** may utilize a combination of vibration and strain sensors to determine load on the valve stem and may correlate said load to an overall health of the valve.

[0043] Furthermore, a safety measure may be programmed in the software application such that the plurality of sensors **111** may automatically count a number of times a valve is opened and closed. Based on said safety measure, an automatic trigger may actuate such that the valve is greased once a pre-determined number of valve actuations (e.g., open/closed) has been reached. One skilled in the art will appreciate how once greasing requirements are determined, a specific volume of grease based on the condition of the valve may be automatically pumped into the gate valve to keep it running smoothly. In a non-limiting example, the software application, through the plurality of sensors **111**, may regulate an air manifold to prevent over-pressure of devices. The software application may use data based on the real-time valve position to prevent overpressure or other costly mistakes during the fracturing operations. It is further envisioned that safety and efficiency at the rig site may be increased by providing automated actuation of valves, remotely and outside of a red-zone (e.g., an area approximate the plurality of devices).

[0044] As shown in FIG. **1A**, in one or more embodiments, an automatic greasing unit **120** may be provided at the rig site **1** and may determine a greasing period and grease quantity by utilizing data collected by the plurality of sensors **111** placed on the plurality of devices and the automatic greasing unit **120**. Additionally, the automatic greasing unit **120** may receive and transmit data from and to the HMI **116**. Additionally, valve utilization may be used to further determine greasing requirements. The valve utilization may take into consideration, for example, duration a valve was exposed to a fracturing stage and the software application may determine the greasing requirements based on the amount of sand the valve may have been in contact with and the bore pressures. It is further envisioned that a valve signature may be analyzed and intelligence protocols may be applied to ensure the valves may only be greased when necessary based on time or number of actuations. Further, the plurality of sensors **111** may measure a pressure feedback during greasing to ensure efficient application of grease.

[0045] FIG. **1B** shows a close-up perspective view of an automatic greasing unit **120** at a rig site **1** approximate the at least one wellhead assembly **101** and the zipper manifold **102** according to one or more embodiments of the present disclosure. The automatic greasing unit **120** may include various equipment coupled to various equipment at the rig site **1**. For example, the automatic greasing unit **120** may have a grease tank **122** and a compressor **123** that may be operationally coupled to a grease pump **124** disposed on a trailer **121**. In a non-limiting example, the compressor **123** may provide compressed air to the grease pump **124** such that grease is pumped from the grease tank **122**. Additionally, generators **124** may be provided on the trailer **121** to power the automatic greasing unit **120**. Furthermore, a control panel **125** may be provided on the trailer **121** to operate the automatic greasing unit **120**. From the trailer **121**, grease and air lines **126** may connect to at least one wellhead assembly **101** and the zipper manifold **102** via one or more grease manifolds **127**. The grease manifolds **127** may be positioned within a red zone at the rig site **1**. The

red zone may be a danger area around equipment unsafe for workers to approach. The grease manifolds **127** may include pneumatically operated valves that open to direct grease to the corresponding valve in the at least one wellhead assembly **101** or the zipper manifold **102**.

[0046] The pneumatically operated valves may be electronically controlled using electric control valves to direct air where needed to open/close the pneumatically operated grease valves. In some embodiments, the control panel **125** may electronically control the opening and closing of the electronically controlled valves to direct air to open and close the pneumatically operated grease valves.

[0047] In addition, an intermediate automation control box **128** may be provided at the rig site **1**. Cables **129** may couple the control panel **125** to the intermediate automation control box **128**. With the cables **129**, the intermediate automation control box **128** may receive electric power and control signals from the control panel **125** located outside of the red zone. Further, the intermediate automation control box **128** may reduce the power received from the control panel **125**, and then send lower level power and control signals to the valves in the grease manifolds **127** necessary to grease the corresponding valve(s) indicated by the control panel **125**. By providing the step-down in power from the intermediate automation control box **128**, the grease manifolds **127** may be positioned closer to the wellhead assembly **101** (e.g., trees), which may decrease the needed length of costly grease lines. Further, by providing the step-down in power from the intermediate automation control box **128**, expensive electronically controlled valves that are rated to be used in areas with potentially explosive gases do not need to be used.

[0048] In conjunction with the plurality of sensors **111**, the control panel **125** or the intermediate automation control box **128** may automatically determine when to grease a valve based on the valve signature. It is further envisioned that the control panel **125** and the intermediate automation control box **128** may communicate with the HMI (**116**) as described in FIG. 2.

[0049] Referring now to FIG. 1C, another embodiment of the automatic greasing unit **120** at the rig site **1** according to embodiments herein is illustrated, where like numerals represent like parts. The embodiment of FIG. 1C is similar to that of the embodiment of FIG. 1B. However, instead of the control panel **125** provided on the trailer **121** of the automatic greasing unit **120** (see FIG. 1B), the control panel **125** is provided on the rig site **1** a distance from the trailer **121**. The trailer **121** may be spaced a distance D from the grease manifolds **127** such that the automatic greasing unit **120** is outside the red zone. Additionally, secondary spare valves **130** may be disposed at the rig site **1**. The secondary spare valves **130** may be coupled to the grease manifolds **127** via grease and air lines **126** such that the secondary spare valves **130** remained greased and ready for use.

[0050] According to embodiments of the present disclosure, a general plan suitable for use in planning a majority of hydraulic fracturing operations may be generated into a template fracturing plan. Thus, a template fracturing plan may include an outline or overview of high level phases for hydraulic fracturing operations and an initial set of instructions for how activities within the high level phases may be performed. A template fracturing plan may later be modified (e.g., by an end user or third party) to accommodate a particular standard operating procedure or to fit a particular hydraulic fracturing operation. For example, a user may modify a template fracturing plan to include one or more discrete plans, for example, to fit a particular hydraulic fracturing operation or standard operating procedure. One or more modifications to a template fracturing plan may include, for example, alternating the timing of valve openings, alternating a particular valve leak test to perform for each kind of valve, and alternating pressure testing methods.

[0051] In some embodiments, a template fracturing plan may be modified to include instructions for which steps in a hydraulic fracturing operation can proceed with and without human permission. Permission settings may be predefined in a modified fracturing plan to have certain steps require a user permission prior to proceeding and/or to have certain steps automatically proceed upon meeting certain system parameters. In some embodiments, permission settings may

include one or more approval settings (e.g., who has credentials or who needs to approve certain steps in a hydraulic fracturing operation), a log of users and/or a log of decisions to approve or disallow actions and who made the decisions. As a simplified example of modifying a template fracturing plan, a template fracturing plan may include instructions that if steps a, b and c go according to plan in a built hydraulic fracturing system, the operation may automatically proceed with step d, where the template fracturing plan may be modified to request permission before proceeding with one or more of steps a, b, c and d.

[0052] Referring to FIG. 3, in one or more embodiments, a system flow chart is shown of implementing an automated hydraulic fracturing system on the built hydraulic fracturing system **100** at the rig site **1** of FIG. 1A. The automated hydraulic fracturing system may include a fracturing plan **301**. In a non-limiting example, the fracturing plan **301** may include a list of activities for each phase of a hydraulic fracturing operation, such as: during a toe prep phase of an operation, activities may include standby, logging, pressure testing, and injection testing; during a zipper frac phase of an operation, activities may include standby, wireline, and fracturing; and during a drill out phase of an operation, activities may include standby and coiling. For each activity in each phase, the fracturing plan **301** may include settings for one or more device types in the hydraulic fracturing system, such as on/off positions of each valve in the system, pressure minimums and maximums, and others described herein. Furthermore, one of ordinary skill in the art would understand the fracturing plan **301** may include further operations, such as, a water and additive injection, initiating the hydraulic fracturing of the formation, the actuation of downhole equipment, or any operation during the life of a well.

[0053] In some embodiments, the fracturing plan **301** may be developed from one or more sets of pre-made instructions organized into a template fracturing plan **302**, which may include instructions to perform multiple processes carried out by the built hydraulic fracturing system **100**. In a non-limiting example, the template fracturing plan **302** may be designed prior to building the built hydraulic fracturing system **100** at a rig site such that the fracturing plan **301** may apply to any configuration of the plurality of devices. It is further envisioned that the fracturing plan **301** may be modified to form a customized fracturing plan **303**. The customized fracturing plan **303** may include pre-made instructions **304** from the template fracturing plan **302** and at least one modified instruction **305**. In a non-limiting example, the at least one modified instruction **305** may be inputted into the software application by a third party such as an operator with access to the software application through the HMI.

[0054] In one or more embodiments, the fracturing plan **301** (a template fracturing plan **302** and/or a customized fracturing plan **303**) may be run in a simulation **306** prior to performing an operation at the rig site. In a non-limiting example, the software application may include a simulation package such that the simulation **306** may be run to show fluid flow through the plurality of devices of the built hydraulic fracturing system **100** to a well bore or show the performance of individual components. It is further envisioned that the fracturing plan **301** may use limit switches to determine the valve positions on a fracturing operation. In addition, said limit switches may be incorporated within an isolation valve, tree valve, and/or manifold valve to monitor and transit positions of said valves. One skilled in the art will appreciate how the positions of said valves may determine a current stage of well as well as possible next stages during the fracturing operation. Further, the positions of said valves may be fed into a controller to enable a hydraulic valve to be automated in a safe manner.

[0055] Furthermore, a plurality of sensors (e.g., sensors **111** in FIG. 1A) may be disposed in and/or on the plurality of devices to measure data. It is also understood that depending on the piece of equipment (and its usage and/or importance), different numbers and/or types of sensors may be used. In a non-limiting example, the plurality of sensors **307** may collect data and display the data on the HMI to allow for real-time monitoring and updates. The plurality of sensors **307** are located on relevant equipment on locations where they can gather data and be able detect any changes to

the plurality of devices such as performance and possible damage. For example, a pump may have a sensor disposed at the inlet thereof, as well as, a sensor at the outlet thereof. Further examples may be a valve manifold that has a sensor disposed on the outer surface thereof, as well as, a sensor on an inner flow bore, or a sensor may be disposed on a valve within the flow bore to measure a position of the valve. It is further envisioned that pressure lines may be measured in a central location, such that, the sensor(s) connected to the pressure lines measures multiple pieces of equipment. Additionally, one of ordinary skill in the art will appreciate how the present disclosure is not limited to just the data listed above and may include any effects on the plurality of devices.

[0056] With data collected from the plurality of sensors, in one or embodiments, an execution **308** of the fracturing plan **301** (a template fracturing plan **302** or a customized fracturing plan **303**) may be performed on the plurality of devices of the built hydraulic fracturing system **100**. In a non-limiting example, the software application may automatically execute **309** the fracturing plan **301**. In some embodiments, to perform the execution **308**, the pre-made instructions and the at least one modified instruction may be sent to remotely operable hardware on the plurality of devices to perform a function (e.g., to achieve fracture). It is further envisioned that, an alert may occur on the HMI, such as a sound and/or visual cue. The alert may indicate that an operation requires human permission **310** to execute the customized fracturing plan prior to sending instructions to the plurality of devices. Additional alerts may also occur, such as from computer vision sensors that may detect personnel within an area of the built hydraulic fracturing system **300** at the rig site (e.g., if an entity has come within a restricted or hazardous area of the rig site). Furthermore, the plurality of sensors may, for example, monitor pressure data at a high sample rate to capture high pressure events for compliance and safety requirements. Additionally, the fracturing plan **301** may include a time to complete processes for each stage and the plurality of sensors may further provide information to modify said plans (**301**, **303**) to improve operational efficiency.

[0057] According to embodiments of the present disclosure, data collected from simulation **306** of a fracturing plan **301** and/or execution **308** of a fracturing plan **301** may indicate that one or more additional instructions **307** may be added to a customized fracturing plan **303** in order to optimize fracturing operations (e.g., make the operations safer, utilize less energy, utilize less material, etc.).

[0058] In one or more embodiments, the software application of the automated hydraulic fracturing system may automatically generate optimal responses by using artificial intelligence (“AI”) and/or machine learning (“ML”). In a non-limiting example, the optimal responses may be due to unforeseen events such as downhole conditions changing, equipment failures, weather conditions, and/or hydraulic fracturing performance changing, where the fracturing plan **301** may automatically change corresponding to the optimal responses. The optimal responses may optimally and automatically reroute the fracturing plan **301** in view of the unforeseen events and potentially unidentified risks. It is further envisioned that the plurality of sensors may continuously feed the software application data, such that additional optimal responses may be suggested on the HMI for the operator to accept or reject. In some embodiments, the operator may manually input, through the HMI, modification to the fracturing plan **301**. One skilled in the art will appreciate how the software application, using AI and/or ML, may learn the manual input from the operator such that predications of potential interruptions in the fracturing plan **301** may be displayed on the HMI and corresponding optimal responses.

[0059] Now referring to FIG. 4, FIG. 4 shows a system flow chart for developing a simulation of a hydraulic fracturing system **400** according to one or embodiments of the present disclosure. In step **401**, a plurality of devices in a hydraulic fracturing operation may be mapped into a simulated hydraulic fracturing system **400** using a software application. After a hydraulic fracturing operation has been mapped into a simulated system, one or more devices may be subsequently added or removed from the simulated hydraulic fracturing system. For example, a new device may be added to the hydraulic fracturing system **400** in step **402**. In a non-limiting example, the new device may include firmware and/or programmable logic controllers (PLCs) capable of communicating with

the software application. One skilled in the art will appreciate how the firmware may be in a format compatible with the software application. Additionally, in step **403**, the new device is mapped into the simulated hydraulic fracturing system **400**, where the new device may be identified, for example, by device type, device specifications, or others, and/or the new device location may be identified with reference to previously mapped devices in the hydraulic fracturing system. In a non-limiting example, the new device may be a valve in a flow path.

[0060] Equipment and/or devices of a hydraulic fracturing operation may be initially simulated in a simulated hydraulic fracturing system or equipment/devices in an already built hydraulic fracturing system may be simulated in a simulated hydraulic fracturing system. For example, according to some embodiments, commonly used devices in general hydraulic fracturing systems may be initially simulated into a simulated hydraulic fracturing system in order to design a template fracturing plan, as described above. In some embodiments, equipment in a built hydraulic fracturing system may be mapped into a simulated hydraulic fracturing system, where new devices may subsequently be added and mapped into the simulated hydraulic fracturing system.

[0061] In some embodiments, mapping a new device into a simulated hydraulic fracturing system may include first casting a search for signals within a radius encompassing a built hydraulic fracturing system in step **404**. It is further envisioned that the step **404** may be initiated by the new device firmware **404a** or by the software application **404b**. Next, in step **405**, at least one signal from the new device firmware is detected. Further to step **405**, the firmware may produce a pairing message, such as a beacon, in step **405a** to aid in detection. With the at least one signal detected, the new device firmware may communicate with the software application in step **406**. Furthermore, to ensure that the firmware is connected to the software application, the firmware may have an application programming interface (API) to produce a return message in step **407** to confirm that communication is allowable. With the new device connected to the software application, the new device may be mapped into a simulated hydraulic fracturing system, monitored, and/or controlled through the software application.

[0062] For example, a valve (e.g., a valve used in a built hydraulic fracturing system **100**) may be added into a simulated hydraulic fracturing system using a method such as shown in FIG. **4**, where the valve may be provided with firmware capable of sending and/or receiving signals from the software application simulating the simulated hydraulic fracturing system. Once added in the simulated hydraulic fracturing system, the simulated hydraulic fracturing system **400** may monitor a level of grease in the valve, determine when to grease the valve, and/or send an alert or command to lubricate the valve (e.g., where the valve may be automatically lubricated from an automatic greasing unit **120** or personnel may add lubricate upon being noticed of the alert). Additionally, depending on the type of the valve, the simulated hydraulic fracturing system **400** may determine a number of strokes of the valve and be able transmit said data to ensure maintenance requirements of the valve are met.

[0063] In addition to the benefits described above, the automated hydraulic fracturing system may improve an overall efficiency and performance at the rig site while reducing cost. Further, the automated hydraulic fracturing system may provide further advantages such as a complete closed loop valve control system, valve transitions may be recorded without visual inspection, partial valve transitions may be avoided, valve transition times may be optimized given the closed loop feedback, an automated valve rig up/checkout procedure may ensure that the flow lines have been attached to the intended actuators, and may reduce or eliminate human interaction with the rig equipment to reduce communication/confusion as a source of incorrect valve state changes. It is noted that the automated hydraulic fracturing system may be used for onshore and offshore oil and gas operations.

[0064] While the invention has been described with respect to a limited number of embodiments, those skilled in the art, having benefit of this disclosure, will appreciate that other embodiments can

be devised which do not depart from the scope of the invention as disclosed herein. Accordingly, the scope of the invention should be limited only by the attached claims.

## Claims

1. One or more non-transitory computer-readable media storing computer-executable instructions that, when executed by at least one processor, perform a method of operating a fracturing system, the method comprising: automatically controlling at least one valve of the fracturing system according to a valve sequencing plan to thereby direct fluids in a selected path within the fracturing system, the at least one valve in communication with a manifold; receiving at least one signal from one or more sensors, the at least one signal comprising information indicative of a state of the at least one valve; receiving electrical power from a control panel at a first power level; and outputting the electrical power to the manifold at a second power level lower than the first power level.
2. The one or more non-transitory computer-readable media of claim 1, wherein the method further comprises: mapping a plurality of devices in the fracturing system into a simulated hydraulic fracturing system; adding a new device to the fracturing system, the new device comprising new device firmware; mapping the new device into the simulated hydraulic fracturing system, comprising: casting a search for signals within a radius encompassing the fracturing system; detecting at least one signal from the new device firmware; and communicating the new device firmware.
3. The one or more non-transitory computer-readable media of claim 1, wherein the method further comprises: identifying a template fracturing plan for the fracturing system, the template fracturing plan comprising one or more instructions for operating the fracturing system; and modifying the template fracturing plan to produce a modified fracturing plan, the modified fracturing plan comprising one or more modified instructions for operating the fracturing system.
4. The one or more non-transitory computer-readable media of claim 3, wherein the method further comprises: simulating a next stage of the template fracturing plan prior to modifying the template fracturing plan.
5. The one or more non-transitory computer-readable media of claim 3, wherein the template fracturing plan comprises: one or more permission-based instructions that are performed responsive to operator approval; and one or more automatic instructions that are performed automatically, independent of operator approval.
6. The one or more non-transitory computer-readable media of claim 5, the method further comprising: generating a log of information associated with the fracturing system.
7. The one or more non-transitory computer-readable media of claim 6, wherein the log comprises: user sign-in information; time usage of the template fracturing plan and the modified fracturing plan; amount of times the template fracturing plan is modified; and amount of times the template fracturing plan is overridden.
8. A method of operating a fracturing system, the method comprising: identifying a red zone around the fracturing system that includes at least one valve, the at least one valve in fluid communication with a manifold positioned in the red zone; automatically controlling the at least one valve according to a valve sequencing plan to thereby direct fluids in a selected path within the fracturing system; and receiving at least one signal from one or more sensors, the at least one signal comprising information indicative of a state of the at least one valve.
9. The method of claim 8, further comprising: determining a valve utilization parameter based at least in part on the state of the at least one valve; and automatically determining when to grease the at least one valve based on the valve utilization parameter.
10. The method of claim 9, further comprising: providing an instruction to grease the at least one valve to one or more grease valves of a grease manifold disposed in the red zone.

- 11.** The method of claim 10, further comprising: receiving electrical power from a control panel at a first power level; and outputting the electrical power to the grease manifold at a second power level lower than the first power level.
- 12.** The method of claim 8, further comprising: identifying a fracturing plan for the fracturing system, the fracturing plan comprising a plurality of instructions for operating the fracturing system.
- 13.** The method of claim 12, further comprising: transmitting one or more permission requests to an operator, the one or more permission requests requesting permission to perform one or more respective instructions from the plurality of instructions of the fracturing plan.
- 14.** The method of claim 13, further comprising: responsive to receiving approval from the operator, allowing the one or more respective instructions from the plurality of instructions of the fracturing plan to proceed, wherein one or more other instructions of the plurality of instructions proceed automatically without approval from the operator.
- 15.** A method operating a fracturing system, the method comprising: identifying a red zone around a fracturing system that includes at least one valve, the at least one valve in fluid communication with a manifold positioned in the red zone; automatically controlling the at least one valve according to a valve sequencing plan to thereby direct fluids in a selected path within the fracturing system; and receiving at least one signal from one or more sensors, the at least one signal comprising information indicative of a state of the at least one valve; receiving electrical power from a control panel at a first power level; and outputting the electrical power to the manifold at a second power level lower than the first power level.
- 16.** The method of claim 15, further comprising: identifying a template fracturing plan for the fracturing system, the template fracturing plan comprising one or more instructions for operating the fracturing system; and modifying the template fracturing plan to produce a modified fracturing plan, the modified fracturing plan comprising one or more modified instructions for operating the fracturing system.
- 17.** The method of claim 16, further comprising: receiving an operator input through a human machine interface.
- 18.** The method of claim 17, further comprising: generating a log of activities and users associated with the fracturing system.
- 19.** The method of claim 18, wherein the log comprises: user sign-in information; a time usage of the template fracturing plan and the modified fracturing plan; an amount of times the template fracturing plan is modified; and an amount of times the template fracturing plan is overridden.
- 20.** The method of claim 19, wherein the log further comprises: device maintenance information; information indicative of online and offline sensors; information indicative of each modification added to the template fracturing plan; and information indicative of one or more operations performed on site of the fracturing system.
-