

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12387872
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Liscinsky; Steve et al.

---

### **Voltage booster isolation transformer system and method of operating the same**

---

#### **Abstract**

An isolation transformer boost system configured to be electrically connected to a shore power supply. The system including an isolation transformer having a primary winding and a secondary winding; and an electronic processor configured to operate in a static mode, wherein in the static mode the electronic processor is configured to activate an electrical characteristic boost when the system is initially powered by the shore power supply.

---

**Inventors:** Liscinsky; Steve (Stratford, CT), Schneider; Jean-Yves (Fox Point, WI), DiMaria; Joseph (Waterbury, CT), Brunier; Jack (Fort Lauderdale, FL)

**Applicant:** Hubbell Incorporated (Shelton, CT)

**Family ID:** 1000008752149

**Assignee:** Hubbell Incorporated (Shelton, CT)

**Appl. No.:** 18/543963

**Filed:** December 18, 2023

#### **Prior Publication Data**

Document Identifier	Publication Date
US 20240145164 A1	May. 02, 2024

#### **Related U.S. Application Data**

continuation parent-doc US 17188071 20210301 US 11848148 child-doc US 18543963  
continuation parent-doc US 16129247 20180912 US 10935577 20210302 child-doc US 17188071  
us-provisional-application US 62557482 20170912

---

## Publication Classification

**Int. Cl.:** H01F27/34 (20060101); G01R19/165 (20060101); G05F1/24 (20060101); H04W4/12 (20090101)

**U.S. Cl.:**

**CPC** H01F27/34 (20130101); G01R19/16547 (20130101); G05F1/24 (20130101); H04W4/12 (20130101);

## Field of Classification Search

**CPC:** H02M (3/335-33592); H02P (13/06); G05F (1/24); H04W (4/12); G01R (19/16547); H02J (3/14)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4916329	12/1989	Dang et al.	N/A	N/A
5119981	12/1991	Gnuechtel	226/18	B65H 23/038
5602462	12/1996	Stich et al.	N/A	N/A
5825164	12/1997	Williams	323/239	H02P 13/06
6751108	12/2003	Elferich	N/A	N/A
9362838	12/2015	Balogh	N/A	H02M 7/04
9568937	12/2016	Brooks	N/A	N/A
11169553	12/2020	Liscinsky et al.	N/A	N/A
2011/0162029	12/2010	Huang et al.	N/A	N/A
2012/0176819	12/2011	Gao et al.	N/A	N/A
2012/0188796	12/2011	Randall	N/A	N/A
2012/0310463	12/2011	Jeong	701/22	H02J 7/00036
2013/0050880	12/2012	Rozman et al.	N/A	N/A
2014/0153290	12/2013	Li	N/A	N/A
2014/0246926	12/2013	Cruz et al.	N/A	N/A
2016/0077534	12/2015	Carlen	N/A	N/A
2016/0195891	12/2015	Divan	323/301	H02M 5/12
2016/0269019	12/2015	Petersen et al.	N/A	N/A
2017/0086281	12/2016	Avrahamy	N/A	H05B 39/086

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2672669	12/2012	EP	N/A

### OTHER PUBLICATIONS

PCT/US2018/050659 International Search Report and written Opinion dated Nov. 7, 2018. cited by applicant

## Background/Summary

RELATED APPLICATIONS (1) This application claims priority to U.S. patent application Ser. No. 17/188,071, filed Mar. 1, 2021, which claims priority to U.S. patent application Ser. No. 16/129,247, filed Sep. 12, 2018, which claims priority to U.S. Provisional Patent Application No. 62/557,482, filed on Sep. 12, 2017, the entire contents of all of which are incorporated herein by reference.

### FIELD

(1) Embodiments relate to isolation transformer systems with booster systems.

### SUMMARY

(2) Watercrafts may demand shore supply or shoreside electrical power at berth while its main and auxiliary engines are shut down to save fuel while docked. Shore supply, whether from the grid of an electrical utility company or an external remote generator, is run from the shore to the watercraft's allotted place at the wharf or dock. The shore supply is fed to a transformer system within the watercraft, which supplies power to the watercraft's electrical system.

(3) Occasionally, the length at which the shore supply is run from its main source to a docked watercraft may be significant enough to cause an undesirable drop in power over the length of the cable. Similarly, the number of watercrafts also pulling power from the shore supply may also cause an undesirable power drop.

(4) Thus, one embodiment provides an isolation transformer boost system. The system includes an isolation transformer, a sensor, and an electronic processor coupled to the sensor. The electronic processor configured to receive an electrical characteristic measurement from the sensor, compare the electrical characteristic measurement to a predetermined threshold, and activate an electrical characteristic boost when the electrical characteristic measurement is below the predetermined threshold.

(5) Another embodiment provides a method of boosting an electrical characteristic of an isolation transformer of an isolation transformer system. The method includes receiving, from a sensor, an electrical characteristic measurement, comparing the electrical characteristic measurement to a predetermined threshold, and activating an electrical characteristic boost when the electrical characteristic measurement is below the predetermined threshold.

(6) Other aspects of the various embodiments will become apparent by consideration of the detailed description and accompanying drawings.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying figures, where like reference numerals refer to identical or functionally similar elements throughout the separate views, together with the detailed description below, are incorporated in and form part of the specification, and serve to further illustrate embodiments of concepts that include the claimed subject matter, and explain various principles and advantages of those embodiments.

(2) FIG. 1 illustrates a schematic diagram of an isolation transformer booster system of a transformer according to some embodiments.

(3) FIG. 2 illustrates a block diagram of a remote control module of the system of FIG. 1 according

to some embodiments.

(4) FIG. 3 illustrates a block diagram of a main module of the system of FIG. 1 according to some embodiments.

(5) FIG. 4 illustrates a flowchart illustrating a method of operating the system of FIG. 1 according to some embodiments.

(6) FIG. 5 illustrates an example of a graphical user interface screen of the remote control module of FIG. 2 within a browser of a portable communications device according to some embodiments.

(7) FIG. 6 illustrates a screen of a set-up page for configuring settings of the wireless access point and for joining wireless network of the remote control module of FIG. 2 according to some embodiments.

(8) FIG. 7 illustrates a status update transmitted by the remote control module of FIG. 2 according to some embodiments.

(9) FIG. 8 illustrates an isolation transformer of the system of FIG. 1 according another embodiment.

(10) The system and method components have been represented where appropriate by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the embodiments so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein.

#### DETAILED DESCRIPTION

(11) Before any embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The invention is capable of other embodiments and of being practiced or of being carried out in various ways.

(12) For ease of description, each of the exemplary systems or devices presented herein is illustrated with a single exemplar of each of its component parts. Some examples may not describe or illustrate all components of the systems. Other exemplary embodiments may include more or fewer of each of the illustrated components, may combine some components, or may include additional or alternative components. For example, the systems and the methods are described in terms of only a single isolation transformer. It should be understood that, in some embodiments, the systems and methods may include additional isolation transformers.

(13) FIG. 1 illustrates an isolation transformer system **100**. The system **100** includes a remote control module **110**, a main module **120**, a contactor **130**, and an isolation transformer **140**. The isolation transformer **140** is configured to receive power, for example, from a shore power supply **150**, and provides power to a main electrical system **160**. The main electrical system **160** may be, for example, an electrical system of a watercraft. In some embodiments, the shore power supply **150** is approximately 210 VAC to approximately 250 VAC (for example, approximately 240 VAC). In other embodiments, the shore power supply is approximately 110 VAC to approximately 130 VAC (for example, approximately 120 VAC).

(14) As illustrated in FIG. 2, the remote control module **110** may include an electronic processor **112**, a memory **113**, a transceiver **114**, and a user interface **115**. The memory **113** includes, for example, a program storage area and a data storage area. The program storage area and the data storage area can include combinations of different types of memory, such as read-only memory (ROM), random access memory (RAM). Various non-transitory computer readable media, for example, magnetic, optical, physical, or electronic memory may be used. The electronic processor **112** is communicatively coupled to the memory **113** and executes software instructions that are stored in the memory **113**, or stored on another non-transitory computer readable medium such as another memory or a disc. The software may include one or more applications, program data, filters, rules, one or more program modules, and other executable instructions.

(15) The transceiver **114** is configured to enable wireless communication between the remote

control module **110** and the main module **120**, via, for example, a wireless communication link. In other embodiments, rather than a transceiver **114**, the remote control module **110** may include separate transmitting and receiving components, for example, a transmitter and a receiver. In operation, the electronic processor **112** is configured to control the transceiver **114** to transmit and receive data to and from the remote control module **110**. The electronic processor **112** encodes and decodes digital data sent and received by the transceiver **114**. The transceiver **114** transmits and receives radio signals to and from various wireless communication networks. The electronic processor **112** and the transceiver **114** may include various digital and analog components, which for brevity are not described herein and which may be implemented in hardware, software, or a combination of both. Some embodiments include separate transmitting and receiving components, for example, a transmitter and a receiver, instead of a combined transceiver **114**.

(16) The electronic processor **112** is configured to enable the user interface **115**, implemented by the electronic processor **112**, from instructions and data stored in the memory **113**. The user interface **115** may include various digital and analog components, which for brevity are not described herein and which may be implemented in hardware, software, or a combination of both. For example, as illustrated in FIG. 2, the user interface **115** may include a display **116**, one or more user-actuated devices **117**, and one or more light emitting diodes (LEDs) **118**. The user interface **115** is configured to receive commands from (for example, via the user-actuated devices **117** and/or the display **116**) and display information to (for example, via the one or more LEDs **118** and/or the display **116**) a user of the system **100**. For example, the electronic processor **112** is configured to display information related to the system **100** on the display **116**. In some embodiments, the display **116** is a suitable touch-sensitive interface display such as, for example, a liquid crystal display (LCD) touch screen, or an organic light-emitting diode (OLED) touch screen. In such an embodiment, the display **116** displays output and receives user input using detected physical contact (for example, via detected capacitance or resistance). The electronic processor **112** may be configured to implement a graphical user interface on the display **116**, which is described in detail below with respect to FIGS. 5 and 6. In some embodiments, the display **116** may be configured to visually indicate a state of operation of the system **100**. For example, when an electrical characteristic boost is active (described in more detail below), the display **116** may illuminate a particular color and when the system **100** is receiving a low input from the shore power supply **150**, the display **116** may illuminate a different color.

(17) FIG. 3 is a schematic diagram illustrating the main module **120**. The main module **120** includes an electronic processor **121** coupled to an electrical characteristic input sensor **122** (also illustrated in FIG. 1). The input sensor **122** is configured to sense one or more types of electrical characteristics between the shore power supply **150** and the isolation transformer **140**. For example, the sensor **122** may be configured to sense the voltage, current, and/or power. In some embodiments, the main module **120** further includes a temperature sensor **124** (also illustrated in FIG. 1). The temperature sensor **124** is coupled to the electronic processor **121** and is configured to measure one or more temperatures within the system **100**. In some embodiments the system **100** also includes an electrical characteristic output sensor **126** (also illustrated in FIG. 1). The output sensor **126** is configured to sense one or more types of electrical characteristics between the isolation transformer **140** and the main electrical system **160**. For example, the output sensor **126** may be configured to sense the voltage, current, and/or power. In some embodiments, the system **100** includes additional sensors coupled to the electronic processor **121** and configured to measure electrical characteristics within the system **100**. The main module **120** may further include various digital and analog components, which for brevity are not described herein and which may be implemented in hardware, software, or a combination of both (for example, a memory).

(18) In some embodiments, the main module **120** includes a transceiver **127** and is configured to communicate with the remote control module **110**. For example, the main module **120** is configured to transmit measurements from the sensors (for example, the sensors **122**, **124**, and **126**)

to the remote control module **110** (for example, to the transceiver **114**). In some embodiments, the remote control module **110** may be mounted a distance away from the main module **120**.

Alternatively or in addition to the transceiver **127**, the remote control module **110** may be communicatively coupled to the main module **120** via a wired connection (as illustrated in FIG. **1**).

(19) Returning to FIG. **1**, the main module **120** is coupled to the contactor **130**. The contactor **130** includes one or more switches **132** each coupled to one or more voltage taps of a primary winding **142** of the isolation transformer **140**. As explained in more detail below, the contactor **130** is configured to receive a command from the main module **120** to activate and/or deactivate an electrical characteristic boost by actuating one or more contactor switches **132**. In some embodiments, the contactor **130** is an **80A** or a **100A** contactor.

(20) The isolation transformer **140** includes a primary winding **142** and a secondary winding **144**. The isolation transformer **140** is configured to receive power from the shore power supply **150** through the contactor **130** to the primary winding **142**. The power through the primary winding **142** induces power within the secondary winding **144**. The power from the secondary winding **144** is then provided to the main electrical system **160**.

(21) In some embodiments, the isolation transformer **140** includes an electrostatic shield. In such an embodiment, the electrostatic shield may prevent, or reduce, any electrical noise produced by the isolation transformer **140**. In some embodiments, the electrostatic shield is located between the primary winding **142** and the secondary winding **144**. In some embodiments, the electrostatic shield is electrically grounded. In some embodiments, the electrostatic shield is grounded separately from an isolation transformer ground **165**. In such an embodiment, the electrostatic shield may be grounded via a six-gauge insulated wire.

(22) FIG. **4** illustrates a method **400** of operating the system **100**. It should be understood that although the method **400** is described herein in terms of the main module **120**, in some embodiments one or more steps of the method **400** may also be performed by the remote control module **110**. At block **402**, the main module **120** receives, from the input electrical characteristic sensor **122**, an electrical characteristic measurement. At block **404**, the main module **120** compares the electrical characteristic measurement to a predetermined threshold. The predetermined threshold may be at least one selected from the group consisting of approximately 190V to approximately 220V (for example, 190V, 195V, 200V, 205V, 210V, 215V, and 220V). In some embodiments, the electrical characteristic measurement is compared to more than one predetermined threshold. At block **406**, the main module **120** determines if the electrical characteristic measurement is below the predetermined threshold. When the electrical characteristic measurement exceeds the predetermined threshold, the method **400** may return to block **402**. When the electrical characteristic is below the predetermined threshold, at block **408** the main module **120** activates an electrical characteristic boost. The electrical characteristic boost is activated by actuating the contactor **130** (specifically, one or more of its switches **132** connected to one or more voltage taps of the primary winding **142**). The electrical characteristic boost may be, for example, a voltage boost. In some embodiments, the electrical characteristic boost is a percent amount of the electrical characteristic measurement (for example, an approximately 10% boost). In other embodiments, the electrical characteristic boost is a fixed amount (for example, approximately 10 VAC). The method **400** may then return to block **402**.

(23) In some embodiments, the main module **120** is configured to activate the electrical characteristic boost when the electrical characteristic measurement is below the predetermined threshold for a predetermined time period. The predetermined time period may be, for example, approximately thirty seconds. This may be to avoid activating the boost in response to a momentary power fluctuation.

(24) In some embodiments, the method **400** further includes comparing the electrical characteristic measurement to a predetermined upper limit threshold, and decreasing or deactivating the electrical characteristic boost when the electrical characteristic measurement exceeds the predetermined

upper limit threshold. In some embodiments, the main module **120** is configured to decrease or deactivate the electrical characteristic boost when the electrical characteristic measurement exceeds the predetermined upper limit threshold for a predetermined time period. For example, the predetermined time period may be five seconds. This may be to avoid activating the boost in response to a momentary power fluctuation.

(25) In some embodiments, the system **100** is configured to run in one of a plurality of modes of operation. The modes of operation may include an automatic mode, a manual mode, and a programming mode.

(26) In the automatic mode, the main module **120** is configured to automatically affect (activate, deactivate, increase, or decrease) the electrical characteristic boost based on the electrical characteristic measurement. In some embodiments, the automatic mode further includes a static mode and a dynamic mode. In such an embodiment, when the system **100** is running in the static mode, the main module **120** is configured to activate the electrical characteristic boost when the system **100** is initially powered on by the shore power supply **150**. Likewise, when the system **100** is running in the dynamic mode, the main module **120** is configured to automatically affect the electrical characteristic boost while the system **100** is operating.

(27) When the system **100** is in the manual mode, the main module **120** is configured to affect the electrical characteristic boost based on a user input, rather than automatically. The user input may be received, for example, via the user interface **115** of the remote control module **110**. In response to the user input, the main module **120** may, for example, activate, deactivate, increase, or decrease the electrical characteristic boost.

(28) When the system **100** is in the programming mode, the main module **120** is configured to receive, via the user interface **115** of the remote control module **110**, one or more commands to adjust a setting of the operation of the system **100**. For example, the main module **120** may receive a command to adjust the predetermined threshold or the predetermined upper threshold. While in the programming mode, the remote control module **110** may be configured to receive a user command to activate a mode of operation (for example, automatic, static, dynamic, or manual).

(29) In some embodiments, while the system **100** is in the programming mode, the remote control module **110** may be configured to connect the system **100** to a wireless network and/or create a wireless access point. In such an embodiment, the system **100** may be configured to be coupled, via the network or access point to a portable communication device (for example, a smartphone, laptop, tablet, and the like). The system **100** may then receive commands from the portable communication device in lieu of or in addition to the remote control module **110**.

(30) In some embodiments, the system **100** while in the programming mode is further configured to calibrate the input sensor **122**, the temperature sensor **124**, the output sensor **126**, and/or any other sensors within the system **100**. In such an embodiment, the system **100** may be further configured to be manually calibrated via the remote control module **110** (for example, via the user interface **115**).

(31) In some embodiments, the main module **120** is further configured to compare the electrical characteristic measurement to a maximum limit threshold. In such an embodiment, when the electrical characteristic measurement exceeds the maximum limit threshold, the main module **120** may be configured to not activate the electrical characteristic boost (regardless of whether the system **100** is in the automatic mode or the manual mode). This may be to prevent an overpower condition from occurring. In some embodiments, the maximum limit threshold is approximately 225 V.

(32) As mentioned above in regard to FIG. 2, in some embodiments, the remote control module **110** includes a graphical user interface. As also mentioned above in regard to FIG. 2, in some embodiments, the remote control module **110** is configured to create a wireless access point and/or connect to a wireless network. The graphical user interface may include a graphical interface for a user to use when attempting to connect to the wireless access point of the system **100**. FIG. 5

illustrates an example of a graphical user interface screen **500** of the remote control module **110** within a browser of a portable communications device attempting to connect to the wireless access point of the system **100**. The interface screen **500** may include the current mode of operation, present measurements, thresholds, and alerts regarding the system **100**.

(33) FIG. **6** illustrates a screen of a set-up page **600** for configuring settings of the wireless access point and for joining wireless network of the remote control module **110**. The settings may include, for example, a network service set identifier (SSID), creating/modifying a password to access the network, and creating/modifying an internet protocol (IP) address. The page **600** may also include a scan button to find and present local wireless networks the system **100** may connect to. The set-up page **600** may be accessible through a web browser on a portable communications device.

(34) In some embodiments, the remote control module **110** is further configured to transmit a status update regarding the system **100** to a remote server through the wireless network. In such an embodiment, the remote control module **110** is configured to automatically transmit a status update periodically. FIG. **7** illustrates an example status update **700**. The status update **700** may include electrical characteristic measurements and temperature measurements from the sensors within the system **100** (for example, sensors **122**, **124**, and **126**). The status update **700** may also include an electrical characteristic boost status. In some embodiments, pages **500**, **600**, and **700** may be accessed via a remote device (for example, a smartphone, an external computer, a tablet, etc.). Additionally, in some embodiments, the system **100** may be monitored and/or controlled via the remote device.

(35) FIG. **8** illustrates an isolation transformer **800** and contactor **805** according to some embodiments. Isolation transformer **800** and contactor **805** may be used in conjunction with system **100** (for example, in lieu of isolation transformer **140** and contactor **130**).

(36) In the illustrated embodiment, isolation transformer **800** includes a primary winding **810** and a second winding **815**. The isolation transformer **800** is configured to receive power from the shore power supply **150**. The power through the primary winding **810** induces power within the secondary winding **815**. The power (for example, nominal voltage via L1, L2, and N) from the secondary winding **815** is then provided to the main electrical system **160** through contactor **805**.

(37) In the illustrated embodiment, contactor **805** includes one or more sets of switches **820**, each having one or more switches **825**. The switches **825** may be coupled to one or more voltage taps (for example, voltage taps X2, X3, X4, and X5). The contactor **805** is configured to receive a command from the main module **120** to activate and/or deactivate the electrical boost by actuating the one or more switches **825**. In some embodiments, isolation transformer **800** and contactor **805** is operated in a similar manner as described with respect to method **400**. Furthermore, in some embodiments, the isolation transformer **800** and contactor **805** provide similar electrical characteristic boosts as described above with respect to isolation transformer **140** and contactor **130**.

(38) It should be noted that a plurality of hardware and software based devices, as well as a plurality of different structural components may be utilized to implement the invention. In some embodiments, the invention provides a software application that is executable on a personal computing device, such as a smart phone, tablet computer, smart watch, and the like. In some embodiments, the software application may be stored and executed by a remote computing device, such as a server. In particular, the software application may be executed by a server, and a user can access and interact with the software application using a recognition device. Also, in some embodiments, functionality provided by the software application as described above may be distributed between a software application executed by a user's portable communication device and a software application executed by another electronic process or device (for example, a server) external to the recognition device. For example, a user can execute a software application (for example, a mobile application) installed on his or her smart device, which is configured to communicate with another software application installed on a server.



(39) In the foregoing specification, specific embodiments have been described. However, one of ordinary skill in the art appreciates that various modifications and changes may be made without departing from the scope of the invention as set forth in the claims below. Accordingly, the specification and figures are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of present teachings.

(40) The benefits, advantages, solutions to problems, and any element(s) that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as a critical, required, or essential features or elements of any or all the claims. The invention is defined solely by the appended claims including any amendments made during the pendency of this application and all equivalents of those claims as issued.

(41) Moreover in this document, relational terms such as first and second, top and bottom, and the like may be used solely to distinguish one entity or action from another entity or action without necessarily requiring or implying any actual such relationship or order between such entities or actions. The terms “comprises,” “comprising,” “has,” “having,” “includes,” “including,” “contains,” “containing” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises, has, includes, contains a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by “comprises . . . a,” “has . . . a,” “includes . . . a,” or “contains . . . a” does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises, has, includes, contains the element. The terms “a” and “an” are defined as one or more unless explicitly stated otherwise herein. The terms “substantially,” “essentially,” “approximately,” “about” or any other version thereof, are defined as being close to as understood by one of ordinary skill in the art, and in one non-limiting embodiment the term is defined to be within 10%, in another embodiment within 5%, in another embodiment within 1% and in another embodiment within 0.5%. The term “coupled” as used herein is defined as connected, although not necessarily directly and not necessarily mechanically. A device or structure that is “configured” in a certain way is configured in at least that way, but may also be configured in ways that are not listed.

(42) It will be appreciated that some embodiments may be comprised of one or more generic or specialized electronic processors (or “processing devices”) such as microprocessors, digital signal processors, customized processors and field programmable gate arrays (FPGAs) and unique stored program instructions (including both software and firmware) that control the one or more electronic processors to implement, in conjunction with certain non-processor circuits, some, most, or all of the functions of the method and/or apparatus described herein. Alternatively, some or all functions could be implemented by a state machine that has no stored program instructions, or in one or more application specific integrated circuits (ASICs), in which each function or some combinations of certain of the functions are implemented as custom logic. Of course, a combination of the two approaches could be used.

(43) Moreover, an embodiment may be implemented as a computer-readable storage medium having computer readable code stored thereon for programming a computer (for example, comprising an electronic processor) to perform a method as described and claimed herein. Examples of such computer-readable storage mediums include, but are not limited to, a hard disk, a CD-ROM, an optical storage device, a magnetic storage device, a ROM (Read Only Memory), a PROM (Programmable Read Only Memory), an EPROM (Erasable Programmable Read Only Memory), an EEPROM (Electrically Erasable Programmable Read Only Memory) and a Flash memory. Further, it is expected that one of ordinary skill, notwithstanding possibly significant effort and many design choices motivated by, for example, available time, current technology, and economic considerations, when guided by the concepts and principles disclosed herein will be readily capable of generating such software instructions and programs and ICs with minimal

experimentation.

(44) The Abstract of the Disclosure is provided to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in various embodiments for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separately claimed subject matter.

## Claims

1. An isolation transformer boost system configured to be electrically connected to a shore power supply, the system comprising: an isolation transformer having a primary winding and a secondary winding; and an electronic processor configured to operate in a static mode, wherein in the static mode the electronic processor is configured to activate an electrical characteristic boost when the system is initially powered by the shore power supply; wherein a display is illuminated with a first color when the electrical characteristic boost is activated and the display is illuminated with a second color when the isolation transformer is receiving a low input from the shore power supply.
2. The system of claim 1, wherein while the system is operating, the electronic processor is further configured to activate the electrical characteristic boost when an electrical characteristic measurement is below a predetermined threshold for a predetermined time period.
3. The system of claim 1, wherein the electronic processor is further configured to compare an electrical characteristic measurement to a predetermined upper limit threshold, and deactivate the electrical characteristic boost.
4. The system of claim 3, wherein while the system is operating, the electronic processor is configured to deactivate the electrical characteristic boost when the electrical characteristic measurement is above the predetermined upper limit threshold for a predetermined time period.
5. The system of claim 1, wherein the system is configured to run in one of a plurality of modes of operation, wherein the one of the plurality of modes of operation is selected from a group consisting of an automatic mode; a manual mode; and a programming mode.
6. The system of claim 5, wherein the automatic mode further includes a dynamic mode, wherein while the system is running in the dynamic mode, the electronic processor is configured to automatically affect the electrical characteristic boost while the system is operating; and wherein while the system is running in the programming mode, the system is configured to receive one or more commands to adjust a setting of the operation of the system.
7. The system of claim 1, wherein the electronic processor is further configured to provide a wireless access point.
8. The system of claim 1, wherein the electronic processor is further configured to connect to a wireless network.
9. The system of claim 8, wherein the electronic processor is further configured to automatically transmit a status update regarding the system to a remote server.
10. The system of claim 1, the system further comprising a contactor and wherein activating the electrical characteristic boost includes actuating the contactor.
11. The system of claim 10, wherein the contactor is coupled to a voltage tap of the primary winding of the isolation transformer.
12. A method of boosting an electrical characteristic of an isolation transformer of an isolation transformer system, the method comprising: providing the isolation transformer having a primary

winding and a secondary winding; and operating in a static mode, wherein when in the static mode the system is configured to activate an electrical characteristic boost when the system is initially powered by a shore power supply; and illuminating a display with a first color when the electrical characteristic boost is activated and illuminating the display with a second color when the isolation transformer is receiving a low input from the shore power supply.

13. The method of claim 12, the method further comprising, while the isolation transformer system is operating, activating the electrical characteristic boost when an electrical characteristic measurement is below a predetermined threshold for a predetermined time period.

14. The method of claim 13, the method further comprising: comparing the electrical characteristic measurement to a predetermined upper limit threshold, and deactivating the electrical characteristic boost.

15. The method of claim 14, the method further comprising, while the isolation transformer system is operating, deactivating the electrical characteristic boost when the electrical characteristic measurement is above the predetermined upper limit threshold for a predetermined time period.

16. The method of claim 12, wherein activating the electrical characteristic boost includes actuating a contactor.

17. The method of claim 16, wherein the contactor is connected to a voltage tap of the primary winding of the isolation transformer.

18. The method of claim 12, further comprising automatically transmitting a status update regarding the system to a remote server.

19. The method of claim 12, wherein the system includes a contactor and wherein activating the electrical characteristic boost includes actuating the contactor.

20. The method of claim 19, wherein the contactor is coupled to a voltage tap of the primary winding of the isolation transformer.

---