

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12384484
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Zawistowski; Peter et al.

---

### Integrated motor mount and suspension pivot

---

#### Abstract

Disclosed herein are examples of motive power sources suitable to power a two-wheeled vehicle. The vehicle may include a suspension linkage and a suspended body. In some examples, the motive power source may include a housing with a boss extending therefrom. The boss may include a first securement structure. The securement structure may include an instantaneous velocity center of the suspension linkage when coupled to the two wheeled vehicle. In some examples, a second securement structure is formed in the suspended body, a bottom link forms a portion of the suspension linkage, the bottom link includes a third securement structure, and an axle is coupled to the first, second, and third apertures. In some examples, the first, second, and third apertures are concentric with the axle.

---

**Inventors:** Zawistowski; Peter (Lakewood, CO), Hoogendoorn; Steven W. (Evergreen, CO)

**Applicant:** YETI CYCLING, LLC (Golden, CO)

**Family ID:** 1000008747720

**Assignee:** YETI CYCLING, LLC (Golden, CO)

**Appl. No.:** 17/528923

**Filed:** November 17, 2021

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20220153381 A1	May. 19, 2022

#### Related U.S. Application Data

us-provisional-application US 63115432 20201118

---

## Publication Classification

**Int. Cl.:** B62K25/26 (20060101); B62K25/28 (20060101); B62M6/55 (20100101)

**U.S. Cl.:**

**CPC** B62K25/26 (20130101); B62K25/286 (20130101); B62M6/55 (20130101);

## Field of Classification Search

**CPC:** B62M (6/55); B62K (25/26); B62K (25/286)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
421748	12/1889	McErlain	N/A	N/A
519855	12/1893	Whitaker	N/A	N/A
591306	12/1896	Tolson	N/A	N/A
630232	12/1898	Hughes et al.	N/A	N/A
712784	12/1901	Ellis	N/A	N/A
724871	12/1902	Hunter	N/A	N/A
944795	12/1908	Leet et al.	N/A	N/A
1043269	12/1911	Stephenson	N/A	N/A
1068583	12/1912	Harley	N/A	N/A
1168702	12/1915	Babis, Jr.	N/A	N/A
1220606	12/1916	Chelstrom	N/A	N/A
1261440	12/1917	Rigby	N/A	N/A
1283030	12/1917	Ashton	N/A	N/A
1369356	12/1920	Rigby	N/A	N/A
2173520	12/1938	Klatt	N/A	N/A
3803933	12/1973	Huret et al.	N/A	N/A
3813955	12/1973	Huret et al.	N/A	N/A
3847028	12/1973	Bergles	N/A	N/A
3917313	12/1974	Smith et al.	N/A	N/A
3977697	12/1975	MacPike et al.	N/A	N/A
4058181	12/1976	Buell	N/A	N/A
4076271	12/1977	Doncque	N/A	N/A
4114918	12/1977	Lutz	N/A	N/A
4241617	12/1979	Fujimoto et al.	N/A	N/A
4265329	12/1980	de Cortanze	N/A	N/A
4279172	12/1980	Nagano et al.	N/A	N/A
4322088	12/1981	Miyakoshi et al.	N/A	N/A
4360214	12/1981	Isono	N/A	N/A
4408674	12/1982	Boyesen	N/A	N/A
4410196	12/1982	Ribi	N/A	N/A
4415057	12/1982	Yamaguchi	N/A	N/A
4429760	12/1983	Koizumi et al.	N/A	N/A
4433747	12/1983	Offenstadt	N/A	N/A

4463824	12/1983	Boyesen	N/A	N/A
4463964	12/1983	Takayanagi et al.	N/A	N/A
4485885	12/1983	Fukuchi	N/A	N/A
4500302	12/1984	Crepin	N/A	N/A
4506755	12/1984	Tsuchida et al.	N/A	N/A
4540193	12/1984	Noda et al.	N/A	N/A
4544044	12/1984	Boyesen	N/A	N/A
RE32059	12/1984	Nagano	N/A	N/A
4558761	12/1984	Boyesen	N/A	N/A
4561519	12/1984	Omori	N/A	N/A
4574909	12/1985	Ribi	N/A	N/A
4582343	12/1985	Waugh	N/A	N/A
4586913	12/1985	Nagano	N/A	N/A
4596302	12/1985	Suzuki et al.	N/A	N/A
4619633	12/1985	Nagano	N/A	N/A
4621706	12/1985	Boyesen	N/A	N/A
4671525	12/1986	Ribi	N/A	N/A
4673053	12/1986	Tanaka et al.	N/A	N/A
4679811	12/1986	Shuler	N/A	N/A
4702338	12/1986	Trema	N/A	N/A
4735277	12/1987	Prince	N/A	N/A
4744434	12/1987	Miyakoshi et al.	N/A	N/A
4789042	12/1987	Pitts	N/A	N/A
4789174	12/1987	Lawwill	N/A	N/A
RE32924	12/1988	Nagano	N/A	N/A
4830391	12/1988	Silk	N/A	N/A
4878884	12/1988	Romano	N/A	N/A
4951791	12/1989	Creixell	N/A	N/A
5011459	12/1990	Van De Vel	N/A	N/A
5121937	12/1991	Lawwill	N/A	N/A
5205572	12/1992	Buell et al.	N/A	N/A
5226674	12/1992	Buell et al.	N/A	N/A
5244224	12/1992	Busby	N/A	N/A
5259637	12/1992	Busby	N/A	N/A
5282517	12/1993	Prince	N/A	N/A
5295702	12/1993	Buell	N/A	N/A
5299820	12/1993	Lawwill	N/A	N/A
5306036	12/1993	Busby	N/A	N/A
5332246	12/1993	Buell	N/A	N/A
5335929	12/1993	Takagaki et al.	N/A	N/A
5354085	12/1993	Gally	N/A	N/A
5356165	12/1993	Kulhawik et al.	N/A	N/A
5360078	12/1993	Rifenburg et al.	N/A	N/A
5370411	12/1993	Takamiya et al.	N/A	N/A
5409248	12/1994	Williams	N/A	N/A
5409249	12/1994	Busby	N/A	N/A
5417445	12/1994	Smart	N/A	N/A
5429380	12/1994	Lawwill	N/A	N/A
5435584	12/1994	Buell	N/A	N/A
5441292	12/1994	Busby	N/A	N/A

5452910	12/1994	Harris	N/A	N/A
5474318	12/1994	Castellano	N/A	N/A
5498013	12/1995	Hwang	N/A	N/A
5509679	12/1995	Leitner	N/A	N/A
5553881	12/1995	Klassen et al.	N/A	N/A
5570896	12/1995	Collins	N/A	N/A
5597366	12/1996	Ozaki	N/A	N/A
5607367	12/1996	Patterson	N/A	N/A
5611557	12/1996	Farris et al.	N/A	N/A
5628524	12/1996	Klassen et al.	N/A	N/A
5658001	12/1996	Blanchard	N/A	N/A
5678837	12/1996	Leitner	N/A	N/A
5688200	12/1996	White	N/A	N/A
5772228	12/1997	Owyang	N/A	N/A
5791674	12/1997	D'Aluisio et al.	N/A	N/A
5816966	12/1997	Yang et al.	N/A	N/A
5826899	12/1997	Klein et al.	N/A	N/A
5899480	12/1998	Leitner	N/A	N/A
5957473	12/1998	Lawwill	N/A	N/A
6012999	12/1999	Patterson	N/A	N/A
6076845	12/1999	Lawwill et al.	N/A	N/A
6086080	12/1999	Scheffer	N/A	N/A
6102421	12/1999	Lawwill et al.	N/A	N/A
6131934	12/1999	Sinclair	N/A	N/A
6203042	12/2000	Wilcox	N/A	N/A
6206397	12/2000	Klassen et al.	N/A	N/A
6244610	12/2000	Kramer-Massow	N/A	N/A
6406048	12/2001	Castellano	N/A	N/A
6439593	12/2001	Tseng	N/A	N/A
6450520	12/2001	Girard	N/A	N/A
6488301	12/2001	Klassen et al.	N/A	N/A
6543799	12/2002	Miyoshi	N/A	N/A
6629903	12/2002	Kondo	N/A	N/A
6712374	12/2003	Assier	N/A	N/A
6793230	12/2003	Cheng	N/A	N/A
6843494	12/2004	Lam	N/A	N/A
6845998	12/2004	Probst	N/A	N/A
6871867	12/2004	Parigian	N/A	N/A
6877591	12/2004	Hso	N/A	N/A
6886846	12/2004	Carroll	N/A	N/A
6902504	12/2004	Fukuda	N/A	N/A
6926298	12/2004	Ellsworth et al.	N/A	N/A
6955373	12/2004	Chang	N/A	N/A
6969081	12/2004	Whyte	N/A	N/A
7025698	12/2005	Wickliffe	N/A	N/A
7048292	12/2005	Weagle	N/A	N/A
7066481	12/2005	Soucek	N/A	N/A
RE39159	12/2005	Klassen et al.	N/A	N/A
7097190	12/2005	Matsumoto et al.	N/A	N/A
7100930	12/2005	Saiki	N/A	N/A

7104908	12/2005	Nagano	N/A	N/A
7128329	12/2005	Weagle	N/A	N/A
7131511	12/2005	Arnold	N/A	N/A
7210695	12/2006	Griffiths	N/A	N/A
7216883	12/2006	Oconnor	N/A	N/A
7296815	12/2006	Ellsworth et al.	N/A	N/A
7350797	12/2007	Carroll	N/A	N/A
7377535	12/2007	Chamberlain	N/A	N/A
7392999	12/2007	Oconnor	N/A	N/A
7395892	12/2007	Alonzo	N/A	N/A
7413208	12/2007	Weng	N/A	N/A
7427077	12/2007	Lesage et al.	N/A	N/A
7467803	12/2007	Buckley	N/A	N/A
7494146	12/2008	Tseng	N/A	N/A
7556276	12/2008	Dunlap	N/A	N/A
7581743	12/2008	Graney	N/A	N/A
7635141	12/2008	Oconnor	N/A	N/A
7658394	12/2009	Huang	N/A	N/A
7677347	12/2009	Brawn	N/A	N/A
7703785	12/2009	Colegrove et al.	N/A	N/A
7703788	12/2009	Tanouye et al.	N/A	N/A
7712757	12/2009	Berthold	N/A	N/A
7717212	12/2009	Weagle	N/A	N/A
7722072	12/2009	Hoogendoorn	N/A	N/A
7722488	12/2009	Kunisawa et al.	N/A	N/A
7766135	12/2009	Fox	N/A	N/A
7784810	12/2009	Graney	N/A	N/A
7806422	12/2009	I	N/A	N/A
7815207	12/2009	Currie	N/A	N/A
7828314	12/2009	Weagle	N/A	N/A
7837213	12/2009	Colegrove et al.	N/A	N/A
7837214	12/2009	Tribotte	N/A	N/A
7891688	12/2010	Chamberlain	N/A	N/A
7909347	12/2010	Earle	N/A	N/A
7914407	12/2010	Fukushima et al.	N/A	N/A
7934739	12/2010	Domahidy	N/A	N/A
7938424	12/2010	Arraiz	N/A	N/A
7938425	12/2010	Chamberlain	N/A	N/A
7954837	12/2010	Talavasek	N/A	N/A
7963541	12/2010	Chamberlain	N/A	N/A
7971892	12/2010	Sasnowski et al.	N/A	N/A
7980579	12/2010	Buckley	N/A	N/A
8002301	12/2010	Weagle	N/A	N/A
8006993	12/2010	Chamberlain	N/A	N/A
8007383	12/2010	Watarai et al.	N/A	N/A
8012052	12/2010	Shahana	N/A	N/A
8033558	12/2010	Earle	N/A	N/A
8066297	12/2010	Beale et al.	N/A	N/A
8075009	12/2010	Cocalis et al.	N/A	N/A
8136829	12/2011	Kang et al.	N/A	N/A

8152191	12/2011	Huang et al.	N/A	N/A
8201841	12/2011	Beale et al.	N/A	N/A
8272657	12/2011	Graney et al.	N/A	N/A
8272658	12/2011	Hoogendoorn	N/A	N/A
8286982	12/2011	Plantet et al.	N/A	N/A
8303443	12/2011	Wickliffe et al.	N/A	N/A
8348295	12/2012	Beaulieu et al.	N/A	N/A
8376382	12/2012	Twers	N/A	N/A
8382136	12/2012	Beale et al.	N/A	N/A
8419573	12/2012	Yamaguchi	N/A	N/A
8430415	12/2012	Earle et al.	N/A	N/A
8434776	12/2012	Wuthrich	N/A	N/A
8439383	12/2012	Talavasek	N/A	N/A
8459680	12/2012	Chamberlain	N/A	N/A
8585070	12/2012	Beale	N/A	N/A
8590914	12/2012	Domahidy	N/A	N/A
8622411	12/2013	Chamberlain	N/A	N/A
8641072	12/2013	Graney et al.	N/A	N/A
8646797	12/2013	Buckley	N/A	N/A
8678962	12/2013	Jordan	N/A	N/A
8696008	12/2013	Hoogendoorn	N/A	N/A
8727057	12/2013	Park et al.	N/A	N/A
8733774	12/2013	Graney et al.	N/A	N/A
8770360	12/2013	Fox	N/A	N/A
8833785	12/2013	Wagner	N/A	N/A
8851498	12/2013	Alsop	N/A	N/A
8882127	12/2013	Colegrove et al.	N/A	N/A
8919799	12/2013	Wimmer	N/A	N/A
8931793	12/2014	Klieber	N/A	N/A
8931794	12/2014	O'Connor	280/284	B62K 25/286
8932162	12/2014	Emura et al.	N/A	N/A
8998235	12/2014	Beale	N/A	N/A
9039026	12/2014	Hudec	N/A	N/A
9056644	12/2014	Hudák	N/A	N/A
9056647	12/2014	Hu	N/A	N/A
9061729	12/2014	Canfield et al.	N/A	N/A
9102378	12/2014	Zawistowski	N/A	N/A
9102379	12/2014	Capogna	N/A	N/A
9127766	12/2014	Kuwayama et al.	N/A	N/A
9145185	12/2014	Claro	N/A	N/A
9156521	12/2014	Lumpkin	N/A	N/A
9168977	12/2014	Mcleay	N/A	N/A
9216791	12/2014	Hudec	N/A	N/A
9221513	12/2014	Hoogendoorn	N/A	N/A
9242693	12/2015	Voss	N/A	N/A
9302732	12/2015	Beale	N/A	N/A
9327792	12/2015	Johnson et al.	N/A	N/A
9334011	12/2015	Chamberlain	N/A	N/A
9359039	12/2015	Lumpkin	N/A	N/A

9376156	12/2015	Chamberlain	N/A	N/A
9376162	12/2015	Colegrove et al.	N/A	N/A
9457871	12/2015	Kuwayama et al.	N/A	N/A
9469369	12/2015	Thoma	N/A	N/A
9505462	12/2015	Pasqua et al.	N/A	N/A
9561834	12/2016	Zawistowski	N/A	N/A
9598131	12/2016	Zusy et al.	N/A	N/A
9598140	12/2016	Berthold	N/A	N/A
9637199	12/2016	Pasqua et al.	N/A	N/A
9676446	12/2016	Pasqua et al.	N/A	N/A
9758217	12/2016	Bortoli et al.	N/A	N/A
9821879	12/2016	Hoogendoorn et al.	N/A	N/A
9908583	12/2017	Matheson et al.	N/A	N/A
9919765	12/2017	Wickliffe et al.	N/A	N/A
9988122	12/2017	Pedretti	N/A	N/A
10011318	12/2017	Beale	N/A	N/A
10099739	12/2017	Nishikawa	N/A	N/A
10160512	12/2017	Beale	N/A	N/A
10336398	12/2018	Hudec	N/A	N/A
10343742	12/2018	Zawistowski	N/A	N/A
10363988	12/2018	Buckley	N/A	N/A
10640169	12/2019	Pedretti	N/A	N/A
10703433	12/2019	Lauer	N/A	N/A
10926830	12/2020	Zawistowski	N/A	N/A
11052964	12/2020	Wallace	N/A	N/A
12145684	12/2023	Zawistowski	N/A	N/A
2001/0024024	12/2000	Klassen et al.	N/A	N/A
2003/0038450	12/2002	Lam	N/A	N/A
2003/0090082	12/2002	Ellsworth et al.	N/A	N/A
2003/0160421	12/2002	Assier	N/A	N/A
2003/0193163	12/2002	Chamberlain et al.	N/A	N/A
2003/0193164	12/2002	Parigian	N/A	N/A
2004/0046355	12/2003	Carroll	N/A	N/A
2004/0061305	12/2003	Christini	N/A	N/A
2004/0239071	12/2003	Chamberlain et al.	N/A	N/A
2005/0057018	12/2004	Saiki	N/A	N/A
2005/0067809	12/2004	Chamberlain	N/A	N/A
2005/0067810	12/2004	Weagle	N/A	N/A
2005/0184483	12/2004	Buckley	N/A	N/A
2005/0253357	12/2004	Chang et al.	N/A	N/A
2005/0285367	12/2004	Chang et al.	N/A	N/A
2006/0022428	12/2005	Whyte	N/A	N/A
2006/0061059	12/2005	Lesage et al.	N/A	N/A
2006/0071442	12/2005	Hoogendoorn	N/A	N/A
2006/0119070	12/2005	Weagle	N/A	N/A
2006/0181053	12/2005	Huang et al.	N/A	N/A
2006/0197306	12/2005	Oconnor	N/A	N/A
2006/0225942	12/2005	Weagle	N/A	N/A
2006/0231360	12/2005	Chen	N/A	N/A

2007/0024022	12/2006	Weagle	N/A	N/A
2007/0108725	12/2006	Graney	N/A	N/A
2007/0194550	12/2006	Wadelton	N/A	N/A
2007/0210555	12/2006	Oconnor	N/A	N/A
2008/0054595	12/2007	Lu	N/A	N/A
2008/0067772	12/2007	Weagle	N/A	N/A
2008/0217882	12/2007	Beaulieu et al.	N/A	N/A
2008/0238030	12/2007	Tseng	N/A	N/A
2008/0238031	12/2007	Tseng	N/A	N/A
2008/0252040	12/2007	Colegrove et al.	N/A	N/A
2008/0258427	12/2007	Buckley	N/A	N/A
2008/0303242	12/2007	Oconnor	N/A	N/A
2009/0001685	12/2008	Talavasek et al.	N/A	N/A
2009/0026728	12/2008	Domahidy	N/A	N/A
2009/0072512	12/2008	Earle	N/A	N/A
2009/0250897	12/2008	Tanouye et al.	N/A	N/A
2009/0261556	12/2008	Beale et al.	N/A	N/A
2009/0261557	12/2008	Beale et al.	N/A	N/A
2009/0278331	12/2008	Graney	N/A	N/A
2009/0283986	12/2008	Falke	N/A	N/A
2009/0322055	12/2008	Arraiz	N/A	N/A
2010/0059965	12/2009	Earle	N/A	N/A
2010/0102531	12/2009	Graney et al.	N/A	N/A
2010/0109282	12/2009	Weagle	N/A	N/A
2010/0127473	12/2009	Cocalis et al.	N/A	N/A
2010/0156066	12/2009	Oconnor	N/A	N/A
2010/0327553	12/2009	Talavasek	N/A	N/A
2010/0327554	12/2009	Talavasek	N/A	N/A
2010/0327556	12/2009	Chamberlain	N/A	N/A
2011/0025015	12/2010	Colegrove et al.	N/A	N/A
2011/0115181	12/2010	Weagle	N/A	N/A
2011/0175310	12/2010	Lewis	N/A	N/A
2011/0187078	12/2010	Higgon	N/A	N/A
2011/0233892	12/2010	Domahidy	N/A	N/A
2011/0233893	12/2010	Buckley	N/A	N/A
2011/0275256	12/2010	Gibbs et al.	N/A	N/A
2011/0285106	12/2010	Talavasek	N/A	N/A
2012/0223504	12/2011	Antonot	N/A	N/A
2012/0228850	12/2011	Tseng	N/A	N/A
2012/0280470	12/2011	Colegrove et al.	N/A	N/A
2012/0299268	12/2011	Chamberlain et al.	N/A	N/A
2013/0001918	12/2012	Graney et al.	N/A	N/A
2013/0001919	12/2012	Graney et al.	N/A	N/A
2013/0093160	12/2012	Alsop	N/A	N/A
2013/0096781	12/2012	Reichenbach et al.	N/A	N/A
2013/0214503	12/2012	Chiuppani	N/A	N/A
2013/0249181	12/2012	Becker et al.	N/A	N/A
2013/0249188	12/2012	Beale	N/A	N/A
2013/0285346	12/2012	Wimmer	N/A	N/A
2014/0001729	12/2013	Hudec	N/A	N/A



2014/0015220	12/2013	Talavasek	N/A	N/A
2014/0042726	12/2013	Canfield et al.	N/A	N/A
2014/0060950	12/2013	Beutner	N/A	N/A
2014/0109728	12/2013	Mcorrie	N/A	N/A
2014/0167385	12/2013	Gogo et al.	N/A	N/A
2014/0217697	12/2013	Buckley	N/A	N/A
2014/0318306	12/2013	Tetsuka	N/A	N/A
2015/0001829	12/2014	Berthold	N/A	N/A
2015/0054250	12/2014	Hu	N/A	N/A
2015/0115569	12/2014	Matheson et al.	N/A	N/A
2015/0175238	12/2014	Lumpkin	N/A	N/A
2015/0183487	12/2014	Tsai	N/A	N/A
2015/0191213	12/2014	Beale	N/A	N/A
2015/0251724	12/2014	Hudec	N/A	N/A
2015/0360743	12/2014	Oconnor	N/A	N/A
2016/0083042	12/2015	Voss	N/A	N/A
2016/0257371	12/2015	Droux	N/A	N/A
2016/0272273	12/2015	Colegrove et al.	N/A	N/A
2016/0280317	12/2015	Hoogendoorn	N/A	N/A
2016/0311493	12/2015	Scheffer	N/A	N/A
2016/0375956	12/2015	Talavasek et al.	N/A	N/A
2017/0101152	12/2016	Pedretti	N/A	N/A
2017/0151996	12/2016	Southall	N/A	N/A
2017/0313381	12/2016	Mano	N/A	B62K 25/286
2018/0037295	12/2017	Beale	N/A	N/A
2018/0072378	12/2017	Talavasek et al.	N/A	N/A
2018/0072379	12/2017	Talavasek et al.	N/A	N/A
2018/0072380	12/2017	Talavasek et al.	N/A	N/A
2018/0148123	12/2017	Neilson	N/A	N/A
2018/0229798	12/2017	Hoogendoorn et al.	N/A	N/A
2018/0265165	12/2017	Zawistowski	N/A	B62K 25/286
2018/0297661	12/2017	Beale	N/A	N/A
2019/0039682	12/2018	Zawistowski	N/A	N/A
2019/0039687	12/2018	Lay	N/A	B62M 6/55
2019/0144069	12/2018	Beale	N/A	N/A
2019/0300096	12/2018	Chamberlain et al.	N/A	N/A
2019/0300097	12/2018	Chamberlain et al.	N/A	N/A
2020/0070930	12/2019	Buckley	N/A	N/A
2020/0247500	12/2019	Zawistowski	N/A	N/A
2021/0046996	12/2020	Beale	N/A	N/A
2021/0269117	12/2020	Zawistowski	N/A	N/A
2022/0306240	12/2021	Talavasek et al.	N/A	N/A

#### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2293366	12/1997	CA	N/A

2980086	12/2004	CA	N/A
101445020	12/2008	CN	B62K 25/02
692011	12/1939	DE	N/A
9405076	12/1993	DE	N/A
9416803	12/1993	DE	N/A
4435482	12/1995	DE	N/A
1020190024 56	12/2018	DE	N/A
1020211047 53	12/2020	DE	N/A
0422324	12/1990	EP	N/A
0723907	12/1997	EP	N/A
0941917	12/1998	EP	N/A
1026073	12/1999	EP	N/A
1060979	12/1999	EP	N/A
1238900	12/2001	EP	N/A
2540609	12/2012	EP	N/A
2706002	12/2013	EP	N/A
1799534	12/2013	EP	N/A
2812234	12/2013	EP	N/A
541520	12/1921	FR	N/A
933079	12/1947	FR	N/A
2774966	12/1998	FR	N/A
17336	12/1912	GB	N/A
2086319	12/1981	GB	N/A
2338216	12/1998	GB	N/A
2525870	12/2016	GB	N/A
2590808	12/2021	GB	N/A
H0725378	12/1994	JP	N/A
2027223	12/2021	NL	N/A
9422710	12/1993	WO	N/A
9803390	12/1997	WO	N/A
9818671	12/1997	WO	N/A
9856645	12/1997	WO	N/A
199944880	12/1998	WO	N/A
9965760	12/1998	WO	N/A
9944880	12/1999	WO	N/A
03010042	12/2002	WO	N/A
03018392	12/2002	WO	N/A
03021129	12/2002	WO	N/A
2004045940	12/2003	WO	N/A
2005030564	12/2004	WO	N/A
2005030565	12/2004	WO	N/A
2005090149	12/2004	WO	N/A
2006005687	12/2005	WO	N/A
2006032052	12/2005	WO	N/A
2006061052	12/2005	WO	N/A
2008025950	12/2007	WO	N/A
2008130336	12/2007	WO	N/A
2009121936	12/2008	WO	N/A
2010033174	12/2009	WO	N/A
2010103057	12/2009	WO	N/A

2010121267	12/2009	WO	N/A
2012024697	12/2011	WO	N/A
2012027900	12/2011	WO	N/A
2012063098	12/2011	WO	N/A
2012122634	12/2011	WO	N/A
2013028138	12/2012	WO	N/A
2013078436	12/2012	WO	N/A
2013119616	12/2012	WO	N/A
2013142855	12/2012	WO	N/A
2013192622	12/2012	WO	N/A
2014009019	12/2013	WO	N/A
2014029759	12/2013	WO	N/A
2014202890	12/2013	WO	N/A
2015004490	12/2014	WO	N/A
2015196242	12/2014	WO	N/A
2016036237	12/2015	WO	N/A
2016097433	12/2015	WO	N/A
2016134471	12/2015	WO	N/A
2018027192	12/2017	WO	N/A
2018170505	12/2017	WO	N/A
2019010394	12/2018	WO	N/A
2021133996	12/2020	WO	N/A
2021174088	12/2020	WO	N/A

## OTHER PUBLICATIONS

CN-101445020-A translation (Year: 2009). cited by examiner

Nicolai Maschinenbau, “History of Nicolai, Gesellschaft für Zweirad und Maschinenbau mbh,” at least as early as 1995, 3 pages. cited by applicant

Nicolai, “Nicolai Trombone Frame,” at least as early as 1995, 6 pages. cited by applicant

Netherlands Patent Office, “Written Opinion and Search Report,” mailed Feb. 22, 2023, for Dutch Application No. 2029897, Dutch with partial English translation, 12 pages. cited by applicant

Aston, Paul, “Robot Bike Co R160 Custom—Review”, Outside Magazine, Oct. 17, 2016, 46 pages. cited by applicant

U.S. Patent and Trademark Office, Final Office Action mailed on Jul. 22, 2021, for U.S. Appl. No. 15/925,165, 15 pages. cited by applicant

“Combined Search and Examination Report under Sections 17 and 18(3)”, mailed by U.K.

Intellectual Property Office on Aug. 25, 2021, for U.K. Application No. GB2102854.3, 8 pages. cited by applicant

“European Patent Office, EP Extended Search Report”, mailed Sep. 21, 2022, for European Application No. 20747607.8, 2 pages. cited by applicant

“Extended European Search Report for EP 18768549.0”, mailed Feb. 8, 2021. cited by applicant

“International Search Report & Written Opinion”, mailed on Jul. 16, 2021, for PCT Application No. PCT/US2021/020034, 16 pages. cited by applicant

“International Search Report & Written Opinion mailed Apr. 13, 2021, in PCT Application No. PCT/US2020/066980, 16 pages”. cited by applicant

“International Search Report mailed Jun. 19, 2020, in PCT Application No. PCT/US2020/016265, 18 pages”. cited by applicant

“Netherlands Patent Office, Written Opinion and Search Report mailed Sep. 24, 2021”, in Dutch and English, for Netherlands Application No. 2027223, 17 pages. cited by applicant

“U.K. Intellectual Property Office, “Combined Search and Examination Report under Sections 17

an 18(3),””, mailed Apr. 21, 2021, for U.K. Application No. GB2020235.4, 6 pages. cited by applicant

Aston, “Canyon Sender—Review”, <https://www.pinkbike.com/news/canyon-sender-review-2017.html>, Mar. 13, 2017, 33 pages. cited by applicant

Aston, “Robot Bike Co R160—First Look”, <https://www.pinkbike.com/news/robot-bike-co-r160-first-look-2016.html> (Accessed Jun. 30, 2020), May 27, 2016, 39 pages. cited by applicant

Author Unknown, “Sarrus Linkage”, Wikipedia, [http://en.wikipedia.org/wiki/Sarrus\\_linkage](http://en.wikipedia.org/wiki/Sarrus_linkage), 1 page, at least as early as Aug. 20, 2010. cited by applicant

Chen, “Design of Structural Mechanisms”, A dissertation submitted for the degree of Doctor of Philosophy in the Department of Engineering Science at the University of Oxford, St Hugh's College, 2003, 160 Pages. cited by applicant

Cunningham, “First Look: Felt 2014”, <https://www.pinkbike.com/news/First-Look-Felt-2014.html> (Accessed Jun. 30, 2020), Aug. 7, 2013, 20 pages. cited by applicant

Db Bikes, “Felt Compulsion 50 Mountain Bike 2017”, <https://downhillbikesforsale.com/products/Felt-Compulsion-50-Mountain-Bike-2017.html>, (Accessed Jun. 30, 20), 9 pages. cited by applicant

EP, “European Extended Search Report”, Application No. 12851566.5, May 28, 2015, 7 pages. cited by applicant

EP, “Extended European Search Report”, Application No. 11818903.4, Sep. 15, 2015, 8 pages. cited by applicant

EP, “Supplementary Search Report”, Application No. 05798319.9, Dec. 11, 2009, 1 page. cited by applicant

European Patent Office, “Communication Pursuant to Article 94(3) EPC”, mailed Jul. 8, 2022, for European Application No. 18768549.0, 6 pages. cited by applicant

European Patent Office, “Extended European Search Report”, mailed Oct. 4, 2022, for European Application No. 20747607.8, 6 pages. cited by applicant

Foale, “Motorcycle Handling and Chassis Design: The Art and Science”, <https://epdf.pub/motorcycle-handling-and-chassis-design-the-art-and-science.html>, Mar. 2002, 498 pages. cited by applicant

GB IPO, “Combined Search and Exam Report”, App. No. 2020235.4, Apr. 21, 2021, 6 pages. cited by applicant

German Patent Office, “Examination Notice and Search Report”, mailed Apr. 13, 2022, for German Application No. 10 2020 134 843.6, 7 pages. cited by applicant

Giant Bicycles, “Anthem Advanced Pro 29 1”, <https://www.giant-bicycles.com/US/anthem-advanced-pro-29-1-2021>, (Accessed Sep. 14, 2020), 8 pages. cited by applicant

Kavik Bicycles, “Kavik Regen Suspension”, (Accessed Jun. 30, 20), 2 pages. cited by applicant

Li, “Movable Spatial 6R Linkages”, XP055249075, Retrieved from the Internet on Oct. 13, 2016: URL:<http://people.ricam.oeaw.ac.at/z.li/publications/talks/6.pdf>, Oct. 2, 2013, 48 Pages. cited by applicant

Mountain Bike Action, “Bike Test: Felt Compulsion 1 27.5”, <https://mbaction.com/oct-felt-compulsion-1-27-5/>, (Accessed Jun. 30, 2020), 10 pages. cited by applicant

MTBR: Mountain Bike Review Forum, “Jayem Discussion Starter #1—Knolly Suing Intense for Building Bikes with Seat-tubes in Front of the BB”, <https://www.mtbr.com/threads/knolly-suing-intense-for-building-bikes-with-seat-tubes-in-front-of-the-bb.1173867/>, Jan. 2021, 16 pages. cited by applicant

Overholt, Zach, Bikerumor , “IB17: Tantrum Cycles makes it to production, gets noticed by Adventure Capitalists”, <https://bikerumor.com/2017/09/26/ib17-tantrum-cycles-makes-it-to-production-gets-noticed-by-adventure-capitalists/> (Accessed Jun. 30, 2020), Sep. 26, 2017, 8 pages. cited by applicant

“International Search Report and Written Opinion”, Application No. PCT/US2011/048696, Dec.

14, 2011, 10 pages. cited by applicant  
“International Search Report and Written Opinion”, Application No. PCT/US2015/065090, Feb. 12, 2016, 11 pages. cited by applicant  
“International Search Report and Written Opinion”, Application No. PCT/US2012/066427, Jan. 18, 2013, 12 pages. cited by applicant  
“International Search Report and Written Opinion”, Application No. PCT/US2018/041054, Sep. 28, 2018, 12 pages. cited by applicant  
“International Search Report and Written Opinion”, Application No. PCT/US2018/023124, Aug. 2, 2018, 14 pages. cited by applicant  
“International Search Report and Written Opinion”, Application No. PCT/US2005/33410, Nov. 29, 2006, 5 pages. cited by applicant  
Ridemonkey, “how many links could a dw link if a dw could link links?”, <https://ridemonkey.bikemag.com/threads/how-many-links-could-a-dw-link-if-a-dw-could-link-links.276645/> (Accessed Jun. 30, 2020), May 27, 2016, 8 pages. cited by applicant  
Roberts, “First Ride: 2021 Canyon Sender CFR”, <https://www.pinkbike.com/news/first-ride-2021-canyon-sender-cfr.html>, Aug. 11, 2020, 23 pages. cited by applicant  
Sarrut, “Note Sur La Transformation Des Mouvements Rectilignes Alternatifs”, Académie des Sciences, 36, 1036-1038, 1853, 5 Pages. cited by applicant  
U.S. Patent and Trademark Office, “Non-Final Office Action”, mailed Sep. 16, 2022, for U.S. Appl. No. 16/705,049, 10 pages. cited by applicant  
U.S. Patent and Trademark Office, “U.S. Appl. No. 62/815,675”, Filed on Mar. 8, 2019, Mar. 8, 2019. cited by applicant  
U.S. Patent and Trademark Office, , “U.S. Appl. No. 62/833,496”, Filed on Apr. 12, 2019, Apr. 12, 2019. cited by applicant  
U.S. Patent and Trademark Office, , “U.S. Appl. No. 62/867,169”, filed Jun. 26, 2019, Jun. 26, 2019. cited by applicant  
Worsey, “Forbidden Druid Review—Are high pivots just for downhill?” Enduro, [online], Mar. 4, 2019 [retrieved on Jun. 16, 2021], From Internet: <url: <https://enduro-mtb.com/en/fobidden-druid-review/>>; 15 pages,. cited by applicant  
Zawistowski, Think Turquoise, <http://www.yeticycles.com/blog/?p=237> [Retrieved from the Internet on Jul. 27, 2011], Jul. 18, 2010. cited by applicant  
Zawistowski, “Quantifying Wheel Path”, Think Turquoise, <http://www.yeticycles.com/blog/?p=237> [Retrieved from the Internet on Jul. 27, 2011], Jul. 18, 2010, 4 Pages. cited by applicant  
Brown, “Preview: Nicolai Bikes Available in the U.S.: The belt-drive, big-hit bikes will be distributed by Nicolai USA,” Bike Mag, Jun. 3, 2014, 9 pages. cited by applicant  
Overholt, “SOC 14: Effigear Calls in the Cavalerie for new Gear Box Bikes in the US,” Bike Rumor, Apr. 23, 2014, 16 pages. cited by applicant  
Spot Bikes, Mayhem 140, “Inversion,” Jun. 17, 2024, 1 page. cited by applicant

---

*Primary Examiner:* Wehrly; Christopher B

*Attorney, Agent or Firm:* Dorsey & Whitney LLP

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to U.S. Provisional Patent Application No. 63/115,432, filed Nov. 18, 2020, entitled “Integrated Motor Mount and Suspension Pivot,” the contents of which are incorporated herein in their entirety

for all purposes. (2) The following applications are also incorporated herein by reference in their entireties, for all purposes: U.S. Provisional Patent Application 62/473,259, filed Mar. 17, 2017 entitled "Vehicle Suspension Linkage"; U.S. patent application Ser. No. 15/925,165, filed Mar. 19, 2018 entitled "Vehicle Suspension Linkage"; U.S. Provisional Patent Application 62/953,384, filed Dec. 24, 2019 entitled "Constrained Instantaneous Velocity Center Linkage Assembly for Vehicle Suspension"; U.S. Provisional Patent Application 62/800,181, filed Feb. 1, 2019 entitled "Multi-Body Vehicle Suspension Linkage"; U.S. Provisional Patent Application 62/815,675, filed Mar. 8, 2019 entitled "Multi-Body Vehicle Suspension Linkage"; U.S. Provisional Patent Application 62/833,496, filed Apr. 12, 2019 entitled "Multi-Body Vehicle Suspension Linkage"; U.S. Provisional Patent Application 62/867,169, filed Jun. 26, 2019 entitled "Multi-Body Vehicle Suspension Linkage"; U.S. Provisional Patent Application 62/894,469, filed Aug. 30, 2019 entitled "Multi-Body Vehicle Suspension Linkage"; and U.S. patent application Ser. No. 16/779,406, filed Jan. 31, 2020 entitled "Multi-Body Vehicle Suspension Linkage".

## TECHNICAL FIELD

(1) The technology described herein relates to vehicle suspension systems, specifically, to linkages within a vehicle suspension system.

## BACKGROUND

(2) Electronic bikes (also referred to as pedelecs or e-bikes) are a popular form of transportation. E-bikes may provide an extended riding range and speed for users, for example by supplementing the power provided by a user through a traditional crank and pedal assembly with power provided by a motive power source like an electric motor. However, traditional e-bikes may be heavy and bulky due to the need to package the motive power source and its source of electrical power (e.g., batteries).

(3) Some e-bikes may include a suspension, such as a rear suspension. Vehicle suspension terminology depends upon the reference frame considered. Consider a static vehicle that has two wheels, each of which are supported by the ground and a suspended body which is operatively coupled to each wheel. In a two-wheel vehicle, such as an e-bike, there is typically one rear wheel known as the driven wheel which includes a driven cog. There is also one front wheel. A driving cog is operatively coupled to the suspended body. A driving chain or belt connects the driven cog and the driving cog. The driving cog, which is connected to the driven cog via the driving chain/belt, is rotated by a crank under human power, or by a motor, or by combined motor and human power. The reaction between the driven wheel and the ground causes the vehicle to accelerate forward, or in the general direction from the rear wheel to the front wheel. Rearward is then defined as the general direction from the front wheel to the rear wheel.

(4) A linkage operatively couples the suspended body and the driven wheel. A linkage may be composed of multiple bodies (often referred to as links or members) that are operatively coupled to each other in a manner that allows the bodies to flex, cam, rotate or translate relative to one another. The linkage constrains the movement in which the driven wheel and brake may travel relative to the suspended body. A combination of damper(s) and/or spring(s) (e.g., a shock) is/are typically arranged to react to relative motion between the suspended body and the driven wheel. The linkage is highly responsible for the vehicle's dynamic response to acceleration and deceleration as well as the mechanical advantage over the shock.

(5) The information included in this Background section of the specification, including any references cited herein and any description or discussion thereof, is included for technical reference purposes only and is not to be regarded as subject matter by which the scope of the invention as defined in the claims is to be bound.

## BRIEF SUMMARY

(6) In one aspect, a motive power source for a two-wheeled vehicle includes a housing that contains the internal components of the motive power source, where the housing includes a boss

with a first securement structure where the securement structure is configured to attach the motive power source to a suspended body of the two-wheeled vehicle and to a suspension linkage of the two-wheeled vehicle.

(7) The motive power source may also include where the boss is integrally formed with the housing.

(8) In one aspect, a two-wheeled vehicle includes a suspended body, a suspension linkage including a bottom link body pivotally coupled to the suspended body at a joint, and a motive power source coupled to both the suspended body and the bottom link body at the joint.

(9) The two-wheeled vehicle may also include an instantaneous velocity center (IVC) of the suspension linkage located within the first, second, and third securement structure.

(10) The two-wheeled vehicle may also include the axle, the first securement structure, the second securement structure, and the third securement structure concentric with one another.

(11) The two-wheeled vehicle may also include a first securement structure formed in the suspended body; a second securement structure formed in the bottom link body; a housing forming an exterior portion of the motive power source, wherein a first boss extends from the housing, the first boss having a third securement structure; and an axle coupled to the first, second, and third securement structures.

(12) The two-wheeled vehicle may also include an axle assembly including the axle, where the axle includes an expandable portion at a first end of an elongate body and an internally threaded portion located proximate to the expandable portion, a tapered collet including an aperture therethrough, a fastener element is adapted to be received in the aperture and including an externally threaded portion adapted to mate with the internally threaded portion of the axle, where when the fastener is mated with the axle, the fastener causes the tapered collet to expand the expandable portion to secure the axle assembly to the suspended body.

(13) The two-wheeled vehicle may also include where the suspension linkage includes a plurality of linkage bodies including the suspended body, a second body, the bottom link body, a fourth body, a fifth body, and a sixth body operatively connected defining at least seven primary instantaneous velocity centers (IVCs) where, the suspended body is a binary link, a shock assembly is configured to resist movement between two or more of the suspended body, the second body, the bottom link body, the fourth body, the fifth body, or the sixth body, and at least one primary IVC migration path reverses as the suspension moves from an at least partially extended state to an at least partially compressed state.

(14) The two-wheeled vehicle may also include where the boss is selectively removable from the housing.

(15) The two-wheeled vehicle may also include a second boss selectively removable from the housing, where the first boss defines the IVC in a first location when coupled to the housing while the second boss is not coupled to the housing, and the second boss defines the IVC in a second location when coupled to the housing while the first boss is not coupled to the housing.

(16) The two-wheeled vehicle may also include where the housing is a load bearing member of the suspension linkage.

(17) The two-wheeled vehicle may also include where the plurality of linkage bodies define a driven wheel-path.

(18) The two-wheeled vehicle may also include wherein the suspended body (102) includes a jointed connection with the bottom link body (106) defining a primary IVC[102][106] (128), and a jointed connection with the fifth body (110) defining a primary IVC[102][110] (124), the bottom link body (106) includes a jointed connection with the fourth body (108) defining a primary IVC[106][108] (130), and a jointed connection with the sixth body (112) defining primary a IVC[106][112] (134), the fifth body (110) includes a jointed connection with the second body (104) defining a primary IVC[104][110] (132), and a jointed connection with the sixth body (112) defining a primary IVC[110][112] (122), and the second body (104) includes a jointed connection

with the fourth body (108) defining a primary IVC[104][108] (126), where a migration path defined by the IVC[106][112] (134) reverses as the suspension moves from the at least partially extended state to the at least partially compressed state.

(19) The two-wheeled vehicle may also include where a migration path defined by the IVC[106] [108] (130) reverses as the suspension moves from the at least partially extended state to the at least partially compressed state.

(20) The two-wheeled vehicle may also include where the second body (104) is a driven wheel carrier body or a brake carrier body.

(21) The two-wheeled vehicle may also include where the second body (104) is a driven wheel carrier body and a brake carrier body.

(22) The two-wheeled vehicle may also include where the fourth body (108) is a driven wheel carrier body or a brake carrier body.

(23) The two-wheeled vehicle may also include where the fourth body (108) is a driven wheel carrier body and a brake carrier body.

(24) The two-wheeled vehicle may also include where a lower base line is defined by the primary IVC[102][106] (128) and the primary IVC[106][108] (130), an upper base line is defined by the primary IVC[102][110] (124) and the primary IVC[104][110] (132), and the primary IVC[110] [112] (122) is located outside the upper and lower base lines.

(25) The two-wheeled vehicle may also include where a line defined by the primary IVC[106][112] (134) and the primary IVC[110][112] (122) is located outside the primary IVC[102][106] (128) and the primary IVC[106][108] (130).

(26) The two-wheeled vehicle may also include where the primary IVC[106][112] (134) and the primary IVC[106][108] (130) are on the same side of the primary IVC[102][106] (128). Other technical features may be readily apparent to one skilled in the art from the following figures, descriptions, and claims.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an isometric view of a frame of a two-wheeled vehicle including a suspension linkage with a motive power source coupled to the frame and the suspension linkage.
- (2) FIG. 2 is a side elevation view of the frame of FIG. 1.
- (3) FIG. 3 is a close-up view of a motive power source suitable for use with the frame of FIG. 1.
- (4) FIG. 4A is an isometric view of a link body of the suspension linkage of FIG. 1.
- (5) FIG. 4B is a side elevation view of the link body of FIG. 4A.
- (6) FIG. 4C is a rear elevation view of a link body of FIG. 4A.
- (7) FIG. 4D is a plan view of the link body of FIG. 4A.
- (8) FIG. 5 is a partial side elevation view of the frame of FIG. 1.
- (9) FIG. 6 is a partial detail isometric view of the frame of FIG. 1.
- (10) FIG. 7A is a partial exploded view of the frame of FIG. 1 with an embodiment of an axle assembly.
- (11) FIG. 7B is an exploded view of an axle assembly of the frame of FIG. 1.
- (12) FIG. 7C is a partial section view of the frame of FIG. 1 taken along section line 7-7 of FIG. 5.
- (13) FIG. 8A is a partial exploded view of the frame of FIG. 1 with an embodiment of an axle assembly.
- (14) FIG. 8B is a partial section view of the frame of FIG. 8A taken along a similar section line to section line 7-7 of FIG. 5.
- (15) FIG. 9 is a partial side elevation view of the frame of FIG. 1 with an embodiment of a motive power source.



- (16) FIG. 10 is an isometric view of the motive power source of FIG. 9.
- (17) FIG. 11 is a partially exploded view of the motive power source of FIG. 9.
- (18) FIG. 12 is a side elevation view of the motive power source of FIG. 9.
- (19) FIG. 13 is a side elevation view of the motive power source of FIG. 9 in alternate configurations.
- (20) FIG. 14 is a partial detail isometric view of the frame of FIG. 9 with the motive power source of FIG. 9.
- (21) FIG. 15A is a partial isometric view of the frame of FIG. 1 with the motive power source of FIG. 9 and an embodiment of an axle assembly.
- (22) FIG. 15B is a partial exploded view of FIG. 15A.
- (23) FIG. 15C is a partial section view of the frame of FIG. 9 taken along section line 15-15 of FIG. 9.
- (24) FIG. 16A is a partial isometric view of the frame of FIG. 1 with the motive power source of FIG. 9 and an embodiment of an axle assembly.
- (25) FIG. 16B is a partial exploded view of FIG. 16A.
- (26) FIG. 16C is a partial section view of the motive power source of FIG. 9 taken along section line 15-15 of FIG. 9 with the axle assembly of FIG. 16A.
- (27) FIG. 17A is an isometric view of an embodiment of a link body of the suspension linkage of FIG. 1.
- (28) FIG. 17B is a side elevation view of the link body of FIG. 17A.
- (29) FIG. 17C is a rear elevation view of a link body of FIG. 17A.
- (30) FIG. 17D is a plan view of the link body of FIG. 17A.
- (31) FIG. 18A is a partial isometric view of the frame of FIG. 1 with an embodiment of a motive power source and the axle assembly of FIG. 16B.
- (32) FIG. 18B is a partial exploded view of FIG. 18A.
- (33) FIG. 18C is a partial section view of the motive power source of FIG. 18A taken along section line 15-15 of FIG. 9 with the axle assembly of FIG. 16B.
- (34) FIG. 19A is a partial isometric view of the frame of FIG. 1 with an embodiment of a motive power source and the axle assembly of FIG. 16B.
- (35) FIG. 19B is a partial exploded view of FIG. 19A.
- (36) FIG. 19C is a partial section view of the motive power source of FIG. 19A taken along section line 15-15 of FIG. 9 with the axle assembly of FIG. 16B.

#### DETAILED DESCRIPTION

- (37) Disclosed herein are systems and methods of incorporating a motive power source into a frame and suspension of a two-wheeled vehicle such as a two wheeled vehicle like a bicycle, motorcycle or e-bike. As used herein an e-bike means any two-wheeled vehicle powered at least in part by a motive power source. A motive power source may be such as an electric motor powered by an on-board power source such as a battery. In other examples, a motive power source may be an engine such as an internal combustion engine, or a combination of an engine and a motor, or a combination of one or more of these with a transmission. An e-bike may also include a crank and pedals to enable the e-bike to be powered at least in part by a rider's legs.
- (38) Methods and devices are described herein to couple a motive power source to a frame, and/or suspension linkage of the two-wheeled vehicle. In some implementations a mount point for a motive power source is used to both mount the motive power source to the frame and also to serve as a joint in the suspension linkage. The various embodiments of combined motor mounts and suspension pivots may enable the design of lighter, more compact, simpler, and configurable suspension linkages and frames for two-wheeled vehicles such as e-bikes and/or motorcycles.
- (39) For clarity, directions are defined with respect to the frame 100 of the two wheeled vehicle. The longitudinal direction 156a is a direction generally aligned with the motion of the vehicle when the driven wheel rotates relative to the ground, (e.g., either forward or backward). The lateral

direction **156b** is a direction generally normal to the surface over which the vehicle travels (e.g., up or down). The transverse direction **156c** is a direction generally to the left or right of the longitudinal direction **156a**.

(40) Disclosed herein is a system or linkage that operatively couples a suspended body to a driven wheel. In accordance with the various embodiments provided herein, the suspension system linkage improves suspension performance based on the interrelationships of its linkage bodies and the related instantaneous velocity centers (IVCs). In one example, the linkage has 15 IVCs. In particular, the linkage may be a 6-bar linkage.

(41) Various theories, methods, algorithms or analysis systems are provided herein. These systems are provided for better understanding of the structures and configurations described. Unless specifically claimed, the systems are not limiting regardless of current accuracy or subsequent clarifications or understandings of the structures and configurations that may be determined by persons of ordinary skill in the art.

(42) Accordingly, provided herein are various methods or algorithms suitable for analyzing suspension systems. For example, various methods are provided for calculating unknown IVCs of a linkage for a suspension system. Such analytical methods are provided for fuller understanding of the various mechanisms discussed herein. For example, a triangular method may be used to determine an unknown IVC of interest. Additionally or alternatively, plotting the positional relationships of IVCs in a linkage of a suspension can be utilized. Accordingly, the positions of IVCs may change depending on the configuration of the system. A particular IVC may be in a different position depending on whether the system is in a compressed or extended state. IVC migration paths can be determined and vectors running tangential to such migration paths can be analyzed. Thus, the interrelationships between IVCs can be analyzed, allowing for a mathematical analysis of the movement of the linkage subsystem. Finally, methods to calculate anti-squat, anti-rise, and leverage rate is detailed.

(43) As it is understood that throughout this disclosure the relationship of various linkages are described with respect to characteristics of those linkages. One analysis system useful for assessing these relationships is the Mobility Analysis of Mechanisms. The Mobility Analysis of Mechanisms (Kutzbach (or Grubler) mobility criterion) may be used to describe the mobility, or output degree of freedom of a linkage. This system may be used to describe the mobility  $m$  of a planar linkage composed of  $n$  links that are coupled with  $p$  flexible joints/pivots. In the various embodiments, discussed herein, the links can be connected via these flexible joints/pivots allowing some degree of freedom between one another. Additionally, the relationship of the links via the joints define various characteristics such as instantaneous velocity centers (IVCs). In various examples as applied to the various embodiments discussed herein, the flexible joints/pivots can include revolute, slider, cam joints, or other suitable flexible joints or pivots that allow one degree of freedom movement between the two links they connect. Notably, flexible joints may include intermediary devices connecting the linkages. Depending on the types of joints, quality of joints, or the tolerances in the joints, characteristics (e.g. the IVCs or other characteristics discussed herein) may have small variances between joints due to real world engineering constraints and calculations. Terminology such as generally, substantially, or other similar terms may be used to account for the expected, calculated, or otherwise real world accuracy of the characteristics discussed herein while allowing for real world variance in the characteristics. Note that if bodies are coupled as one and not considered completely rigid, a specific joint (e.g. a revolute joint) may be assumed theoretically for analysis near the point of flexure in the flexible joint. Also, note that although the linkage is considered planar kinematically, the assembly of the mechanism may be 3-dimensional.

(44) The following equation is used for analysis of the various systems herein:

$$\text{mobility} = m(3n - 1 - p) + p$$
$$n = \text{number of bodies (or links or members)} \quad p = \text{number of joints} \quad \Sigma f = \text{sum of the kinetic variables in the mechanism}$$

(45) As an example, this equation may be applied to a 4-bar linkage. The following solves the

equation for a 4-bar linkage:

$$p=n=4$$

$$m=3(n-1-p)+p$$

$$m=3(4-1-4)+4$$

$$m=3(-1)+4$$

$$m=-3+4$$

$$m=1$$

(46) As another example, this equation may be applied to a 6-bar linkage. The following solves the equation for a 6-bar linkage:

$$n=6$$

$$p=7$$

$$m=3(n-1-p)+p$$

$$m=3(6-1-7)+7$$

$$m=3(-2)+7$$

$$m=-6+7$$

$$m=1$$

(47) In both noted 4-bar and 6-bar linkages,  $m=1$ , or there is one degree of freedom of motion. Therefore, the path of the axis of the driven wheel, known as the driven wheel axis path (DWAP) may be constrained to planar motion along a defined path or curve relative to the suspended body. This path or curve includes one end-point defined as the extended state, and another end-point as the compressed state. Any point on this curve or path between the extended and compressed points is known as an intermediate state. An intermediate state on an IVC migration curve or path correlates to an intermediate state of the linkage positions.

(48) Additionally, methods of analyzing vehicle suspension linkages design for its dynamic response is also disclosed. In one example, this method of analysis includes a collection of the system instantaneous velocity centers (IVCs), which can be determined graphically. An IVC is a point common to two linkage bodies where there is zero relative velocity. These IVCs change location instantaneously as the suspension is cycled from its extended to compressed state. The path of each IVC migration may then be plotted graphically as a path, curve, or spline from the extended to the compressed state. These IVC curves depend upon the reference frame considered. In various embodiments, the suspended body is considered fixed as the driven wheel moves from the extended to the compressed state. Total suspension travel (VWT[T]) is then defined as the perpendicular distance relative to the ground line at the extended state as measured between the extended suspension state point and the compressed suspension state point on the driven wheel axis path.

(49) It is possible for an IVC, known as a stationary IVC (SIVC), to have little to no migration from the extended to the compressed state. One example would be an IVC where a link body is operatively connected to the suspended body.

(50) For reference herein, specific instantaneous velocity centers of a linkage are denoted as IVC[Body-A][Body-B]. Body-A and Body-B being the relevant bodies in the relationship. For example, IVC[1][2] is the instantaneous velocity center relative to a body-1 and a body-2. Additionally, IVC[1][2] is equivalent to IVC[2][1].

(51) The structure surrounding the suspension system may include several bodies. In various examples, the structure may include a suspended body. In various embodiments, the suspended body can be suitable to be supported by suspension and support a user over the suspension. In various examples, the structure may include a “wheel carrier” body, which is operatively coupled to the driven wheel, a “brake carrier” body, which is operatively coupled to the driven wheel brake, or a “dynamic body” (DB), which is any combination of a wheel carrier and a brake carrier body (e.g., DB=wheel carrier body, or DB=brake carrier body, or DB=wheel and brake carrier body).

(52) Specific IVC migrations called dynamic IVCs (DIVCs) may be utilized to determine the

vehicle's dynamic response. The DIVCs depend upon the specific linkage layout but always depend upon suspended body-1 since this is the body in which a passenger or rider will be included.

(53) As used herein DIVC[AD] can define both the acceleration and deceleration response of the vehicle.

(54) As used herein DIVC[A] can define the acceleration response of the vehicle.

(55) As used herein DIVC[D] can define the deceleration response of the vehicle.

(56) As used herein DIVC[C] is defined as a DIVC that includes the acceleration component. DIVC[C] can be equal to DIVC[A] or DIVC[AD].

(57) As used herein DIVC[E] is defined as a DIVC that includes the deceleration component. DIVC[E] can be equal to DIVC[D] or DIVC[AD].

(58) As used herein DIVC is a general term and therefore a DIVC may be a DIVC[AD] or a DIVC[A] or a DIVC[D] or a DIVC[C] or a DIVC[E]. As used herein DIVC[L] is the length of the DIVC migration path, spline or curve.

(59) In accordance with various embodiments, the body-X can be both a wheel carrier and a brake carrier body. In such an embodiment, there is a single DIVC[AD] migration, DIVC[AD][1][X].

(60) In accordance with various embodiments, wheel carrier body-Y can be separate from the brake carrier body-Z. In such an embodiment, there are two DIVCs, DIVC[A][1][Y] and DIVC[D][1][Z].

(61) Finally, in accordance with various embodiments, the wheel carrier body-Y is pivotally concentric to a brake carrier body-Z. In this case, again there are two DIVCs, DIVC[A][1][Y] and DIVC[D][1][Z].

(62) Each of these various embodiments can be variously applied to the embodiments and examples of the various systems discussed in more detail below.

(63) For purposes of understanding, but not to be limiting, it can be noted that the point in which the force of gravity acts on the sum of the suspended vehicle mass (also known as the sprung mass) and any additional mass such as a passenger or cargo that is supported by the suspension is known as the center of gravity (COG). In the static case, with both wheels on the ground, the force due to the suspended mass through the COG is supported by the vehicle's 2 wheels. Depending on the COG location and the wheelbase of the vehicle, the distribution of force between the two wheels may vary. When the vehicle accelerates, load transfer occurs and the force distribution between the two wheels changes. The rear wheel load is increased while the front wheel load is decreased. Thus, the rear suspension tends to compress or squat. Driving forces of the vehicle such as a chain or belt may be utilized to counteract the tendency to squat during acceleration. This is known in vehicle dynamics as anti-squat.

(64) Anti-squat is typically described as a percentage value. One hundred percent anti-squat is when the anti-squat force is equal and opposite to the load transfer force due to acceleration. As a result, the system is in equilibrium and no suspension squat occurs. Over 100% anti-squat is when the anti-squat force is both opposite and greater than the load transfer force and therefore the suspension extends during acceleration. Anti-squat of 0% is when there is zero anti-squat force to counteract the load transfer and therefore suspension squats during acceleration. Anti-squat between 0-100% is when the anti-squat force is both opposite and less than the load transfer force and therefore the suspension squats during acceleration but to a lesser degree than with 0% anti-squat. A negative anti-squat percentage is when the anti-squat force acts in the same direction on the rear wheel as the load transfer force and therefore the squat due to load transfer is magnified. Anti-squat is directly related to the DIVC[C] migration of the suspension linkage. Anti-squat around or slightly above 100% is ideal where pedaling occurs typically around the first half of travel to improve pedaling efficiency. After this point an anti-squat below 100% is ideal so that the driving force is minimized, and the suspension can be utilized later in the travel where pedaling typically does not occur. This also minimizes feedback from the driving force to the rider. It is important to note that too high of an anti-squat is not ideal because it results in high feedback from the driving force to the rider and is detrimental to pedaling efficiency because the load transfer and

anti-squat force are as far from equilibrium.

(65) When the vehicle decelerates the force distribution changes and the front wheel load is increased while the rear wheel load is decreased. As a result, the rear suspension tends to extend or rise. This is known in vehicle dynamics as anti-rise. The magnitude of anti-rise is directly related to the DIVC[E] migration.

(66) One hundred percent anti-rise is when the anti-rise force is equal and opposite to the load transfer force due to deceleration. As a result, the system is in equilibrium and no suspension rise occurs. Over 100% anti-rise is when the anti-rise force is both opposite and greater than the load transfer force and therefore the suspension squats during deceleration. Anti-rise of 0% is when there is zero anti-rise force to counteract the load transfer and therefore suspension rises during deceleration. Anti-rise between 0-100% is when the anti-rise force is both opposite and less than the load transfer force and therefore the suspension rises during deceleration but to a lesser degree than with 0% anti-rise. A negative anti-rise percentage is when the anti-rise force acts in the same direction on the rear wheel as the load transfer force and therefore the rise due to load transfer is magnified. Anti-rise less than 100% may help improve traction while anti-rise greater than 0% may help stabilize geometry during deceleration. Therefore, an anti-rise in the 50-100% can be a suitable range for an improved ride.

(67) Based upon the number of bodies present in the structure, the total number of instantaneous velocity centers (IVCs) can be determined. The following equation can be used:

(68) Number of Instance Centers =  $N = \frac{n(n-1)}{2}$  n=number of bodies moving relative to one another N=total number of instantaneous velocity centers of the linkage

(69) As an example, this equation may be applied to a 4-bar linkage. In this example, n=4. The following solves the equation for a 4-bar linkage.

$$(70) N_4 = \frac{4(4-1)}{2} = \frac{12}{2} = 6$$

(71) This example shows that there are 6 total instantaneous velocity centers for a 4-bar linkage.

(72) As another example, this equation may be applied to a 6-bar linkage. In this example, n=6. The following solves the equation for a 6-bar linkage:

$$(73) N_6 = \frac{6(6-1)}{2} = \frac{30}{2} = 15$$

(74) This example shows that there are 15 total instantaneous velocity centers for a 6-bar linkage.

(75) Turning to the figures, FIG. 1 is an isometric view of a frame 100 for a two-wheeled vehicle. In accordance with various embodiments as shown in FIG. 1, the suspension system can include a 6-bar linkage. FIG. 1 specifically illustrates a 6-bar suspension system in the extended state. In this embodiment, the suspended body 102 is suspended by the suspension system at least at the rear of the bike and preferably by a suspension fork at the front, which is not shown herein for simplicity of the figures. As shown in FIG. 1, a seat stay 104 is a dynamic body (DB), comprising a wheel carrier and a brake carrier. Note that in other embodiments the seat stay 104 may be a wheel carrier only, a brake carrier only, or it can be a non-dynamic body. The seat stay 104 can include a driven wheel axis 118. In accordance with the embodiment, the seat stay 104 is operatively coupled to a driven wheel. The driven wheel engages with the ground. A brake rotor is operatively connected to the driven wheel, and the driven wheel is operatively connected to seat stay 104. A front wheel is operatively connected to a fork which is operatively connected to suspended body 102. A chain stay 108 is operatively coupled to the seat stay 104. An axle 170 is operatively coupled to suspended body 102, the chain stay 108 and a center link 112. A top link 110 is operatively coupled to the suspended body 102, the seat stay 104 and the center link 112. A shock assembly 116 is operatively coupled to the suspended body 102 and the top link 110. As illustrated in the formula above, there are 15 IVCs in a 6-bar linkage.

(76) Seven of the 15 IVCs are shown in FIG. 2: the IVC[110][112] 122, the IVC[102][110] 124, IVC[104][108] 126, the IVC[102][106] 128, the IVC[106][108] 130, the IVC[104][110] 132, and the IVC[106][112] 134. The IVCs of the suspension linkage 114 are described in more detail in U.S. patent application Ser. No. 15/925,165, filed Mar. 19, 2018 entitled "Vehicle Suspension

Linkage” which is incorporated herein by reference in its entirety for all purposes.

(77) FIGS. 1-2 show views of a frame **100** of a two wheeled vehicle such as an e-bike. The frame **100** includes a suspension linkage **114** coupled to the suspended body **102**. The suspended body **102** forms a receptacle **144** operative to receive a motive power source **300**. In some examples, the suspended body **102** includes a seat tube **120** operative to receive a seat post **120** of a seat assembly (not shown). In some examples, the suspended body **102** includes a downtube **198**. The seat tube **120**, downtube **198**, and a top tube may form a suspended body **102** in the form of a front triangle. The motive power source **300** may be coupled to the suspended body **102** and to the suspension linkage **114**. In some examples the motive power source **300** includes a mount that couples the motive power source **300** to the frame **100** and also to the suspension linkage **114**. The motive power source **300** may be at least partially received in the downtube **198** or seat tube **120**. For example, the receptacle **144** may be formed in the seat tube **120** or the downtube **198**. In some examples, a portion of the receptacle **144** may be formed in the seat tube **120** and another portion in communication with the first portion may be formed in the downtube **198**. For example, the seat tube **120** and the downtube **198** may converge near a lower portion of the suspended body **102** to form a combined structure that receives at least a portion of the motive power source. Such structures may enable the compact integration of the motive power source with the frame **100**.

(78) The suspended body and/or any of the links of the suspension linkage **114** may be made from a variety of suitable strong and lightweight material such as steel, aluminum, titanium, magnesium, or alloys related to the above, and/or composites such as carbon fiber, glass, or aramid reinforced fiber composites, or the like.

(79) FIG. 3 shows an example of a motive power source **300** for use with the frame **100**. One example of a suitable motive power source is the STEPS motor from Shimano (see, e.g., <https://www.shimano-steps.com/e-bikes/north-America/en/product-information/mtb/e8000>). The motive power source **300** may be an electric motor, an internal combustion engine, transmission, and/or a combination thereof. The motive power source **300** includes a power interface **302** that may provide motive power to the driving belt, chain, and/or shaft to propel the vehicle. Alternately or additionally, the power interface **302** may receive power from the driving belt, chain, or shaft, such as to recharge batteries that power the motive power source **300**. The motive power source **300** includes a housing **316** that contains the internal components of the motive power source **300**. The housing **316** may be made from a variety of suitable material that is lightweight and strong enough to withstand the forces imparted to the housing **316** in use. Some example materials include steel, aluminum, magnesium, titanium, plastics, composite materials, and/or alloys thereof. In some implementations, the housing **316** may be a load-bearing member that supports loads imparted to the frame **100** and/or suspension linkage **114** such as when the e-bike is ridden, pedaled, or propelled by the motive power source **300**. The housing **316** may include an aft portion **310** and a forward portion **308** located relative to one another along the longitudinal direction **156a**.

(80) In some examples, the housing **316** includes one or more bosses that define part of the housing. For example, the motive power source **300** may include a housing **316** that includes bosses **304**, **312**, and **306**. Any of the bosses disclosed herein (e.g., the bosses **304**, **306**, and/or **312**) may be integrally formed with a housing. For example, a boss may be integrally formed with the housing such as by casting or forging the boss with the housing. In some examples, the boss may be formed in a housing by removing material from the housing, such as by a machining or other selective removal process. For example, a housing may be formed with excess material that is removed by a process such as machining to form the boss. In other examples, a boss may be selectively attachable to the housing of the motive power source, such as with the motive power sources **1000** and **1900** described herein. Attachment to the frame **100** or suspension linkage **314** can be by attachment to the main body of the housing or attachment to a boss portion of the housing to the frame and/or suspension linkage **314**.

(81) One or more of the bosses may define a securement structure for mounting the motive power

source **300** to the frame **100**, the suspension linkage **114**, or both. In one example, at least one boss may include one or more apertures as securement structures defined therethrough to facilitate mounting the motive power source **300** to the frame **100**, to the suspension linkage **114**, or to both. In another example, a boss may have a securement structure of one or more pins extending outwardly from the boss in any of the lateral direction, transverse direction, longitudinal direction, or combinations thereof. The frame **100** may include suitable mating securement structures, such as apertures, adapted to receive the pins. In another example, the housing **316** may be coupled to the frame by welding, brazing, adhesives, or other suitable fastener elements.

(82) In some examples, securement structures such as apertures may extend through a boss in a generally transverse direction **156c**. In some embodiments one or more apertures may be through-apertures that extend from one transverse side of the boss to another, opposite transverse side of the boss. In some embodiments, one or more apertures may be blind apertures that extend into a boss, but not through to the other side. For example, the rearward boss **304** may include a mounting aperture **320** defined therethrough, the upper boss **312** may include a mounting aperture **318** defined therethrough, and/or the forward boss **306** may include a mounting aperture **314** defined therethrough. The mounting aperture **320** may be provided at alternate or additional locations within the rearward boss **304**, such as shown by the mounting aperture **320'**. For example, the mounting aperture **320'** may be located in an upper portion **338**, forward portion **344**, lower portion **342**, and/or a rearward portion **340** of the boss **304**. For example, the aperture **320'** may be located within one diameter of the aperture **320'** of an external upper face **346** of the boss, within one diameter of the aperture **320'** of a rear face **348** of the boss **304**, and/or within one diameter of the aperture of a forward face **350** of the boss **304**. In some examples, the aperture **320'** may be within one diameter of the aperture **320'** of the upper surface **330** of the housing **316**. The mounting aperture **320'** may be located independently of the aperture **320**.

(83) Providing alternate or additional locations of the mounting aperture **320/320'** may enable the use of the motive power source **300** with different frames **100** and/or suspension linkages **114**. Providing alternate or additional locations of the mounting aperture **320/320'** may enable tuning of performance characteristics of the suspension linkage **114**. Any of the mounting aperture **320**, mounting aperture **318**, and/or mounting aperture **314** may be adapted to receive an axle such as a fastener element like a bolt, pin, rivet, or the like to couple the respective boss to the suspended body **102** and/or the suspension linkage **114**. The axle **170** and the respective mounting aperture may form a pivoted connection between the suspended body **102** and/or the suspension linkage **114** and the housing **316**. For example, the mounting aperture **320** may form a pivoted joint that allows a portion of the suspension linkage **114** to pivot relative to the housing **316**. In other examples, a mounting aperture may form a non-pivoting connection with the suspension linkage **114** and/or the suspended body **102**. For example, the mounting aperture **314** and the upper boss **312** may form connections with the suspended body **102** that do not allow the motive power source **300** to pivot relative to the suspended body **102**. The attachments of the motive power source **300** to the suspended body may be at discrete locations that are load bearing. For example, the securement structure **314**, securement structure **320** and/or securement structure **318**, may bear loads transmitted to the frame **100** and/or suspension linkage, such as loads imparted by the movement of the two-wheeled vehicle over the ground, and/or loads imparted by a rider. A benefit of such load bearing may be that the housing **316** may strengthen or stiffen the assembled frame **100** while not needing to add additional stiffeners, or the like.

(84) The housing **316** may include one or more mounting points to mount the motive power source **300** to the frame **100** and/or the suspension linkage **114**. For example, the housing **316** may include a rearward boss **304** extending away from the aft portion **310** of the housing **316**. The housing **316** may include an upper portion **322** and a lower portion **324**. The upper portion **322** and the lower portion **324** encompass part of front portion **308** and aft portion **310**. The housing **316** includes opposing lateral sides **334** and **336**. The housing **316** includes a front portion **326**, rear portion **328**,

a top **330** side, and a bottom side **332**. The rearward boss **304** may extend upwardly from the rear portion **328** or upwardly in the lateral direction **156b** from the top side **330**. The rearward boss **304** may extend rearwardly in the longitudinal direction **156a** from the point at which the boss **304** attached to the top side **330**. The rearward boss **304** may be located above the power interface **302**. All, or a portion, of the rearward boss **304** may be located rearward of the power interface **302** in the longitudinal direction **156a**. In some examples all, or a portion, of the rearward boss **304** may be located forward of the power interface **302** in the longitudinal direction **156a**. In some examples, all or a portion, of the rearward boss **304** may be aligned in the longitudinal direction **156a** (i.e., vertically aligned) with the power interface **302**. The mounting aperture **320** may be located above the power interface **302**. All, or a portion, of the mounting aperture **320** may be located rearward of the power interface **302** in the longitudinal direction **156a**. In some examples all, or a portion, of the mounting aperture **320** may be located forward of the power interface **302** in the longitudinal direction **156a**. In some examples all, or a portion, of the mounting aperture **320** may be aligned in the longitudinal direction **156a** with the power interface **302**. The power interface **302** may extend transversely from either or both of the opposing lateral sides **334**, **336**.

(85) The motive power source **300** may include an upper boss **312** near the rearward boss **304**. The upper boss **312** may extend forwardly in the longitudinal direction **156a** from the point at which the boss **312** is attached to the top side **330**. The upper boss **312** may be located above the power interface **302**. All, or a portion, of the upper boss **312** may be located forward of the power interface **302** in the longitudinal direction **156a**. All, or a portion, of the upper boss **312** may be located rearward of the power interface **302** in the longitudinal direction **156a**. All, or a portion, of the upper boss **312** may be aligned in the longitudinal direction **156a** with the power interface **302** (i.e., vertically aligned). The mounting aperture **318** may be located above the power interface **302**. All, or a portion of, the mounting aperture **318** may be located forward of the power interface **302** in the longitudinal direction **156a**. All, or a portion of, the mounting aperture **318** may be located rearward of the power interface **302** in the longitudinal direction **156a**. All, or a portion, of the mounting aperture **314** may be aligned in the lateral direction **156b** with the power interface **302** (i.e., horizontally aligned).

(86) Likewise, the housing **316** may include a forward boss **306** extending away from the forward portion **308** of the housing **316**. The forward boss **306** may extend forwardly in the longitudinal direction **156a** from the point at which the boss **306** is attached to the front side **326** of the housing **316**. The forward boss **306** may be located above the power interface **302** in the lateral direction **156b**. All, or a portion, of the forward boss **306** may be located forward of the power interface **302** in the longitudinal direction **156a**. All, or a portion, of the forward boss **306** may be aligned in the longitudinal direction **156a** with the power interface **302** (i.e., vertically aligned). All, or a portion, of the forward boss **306** may be aligned in the lateral direction **156b** with the power interface **302** (i.e., horizontally aligned). The mounting aperture **314** may be located above the power interface **302**. All, or a portion, of the mounting aperture **314** may be located forward of the power interface **302** in the longitudinal direction **156a** (i.e., vertically aligned). All, or a portion, of the mounting aperture **314** may be aligned in the lateral direction **156b** with the power interface **302** (i.e., horizontally aligned).

(87) FIG. 4A—FIG. 4D show views of an example of a bottom link **106a**. The bottom link **106a** has a body **142a**. The bottom link **106a** has transversely opposing plates **161a/b**. Each plate **161a/b** being generally L or V shaped and each defining a first portion **140a/b** and a second portion **140c/d** and a third portion **141a/b** disposed between the respective first portions **140a/b** and the respective second portions **140c/d**. In some examples, the third portions **141a/b** are vertices between the respective first portions **140a/b** and the respective second portions **140c/d**. The transverse plates **161a/b** are attached to one another by a connecting portion **166** extending between the third portions **141a/b** and spacing the transverse plates **161a/b** apart. A securement structure such as an aperture **164** is formed in the first lobe **140a/b** of each plate **161a/b**. The apertures **164** are aligned



with each other. A securement structure such as an aperture **162** is formed in the second lobe **140c/d** of each plate **161a/b**. The apertures **162** are aligned with each other. A securement structure such as an aperture **160** is formed in the third portion **141a/b** of each plate **161a/b**. The apertures **160** are aligned with each other and run through the connection portion **166**.

(88) The body **142a** includes a connection portion **166** extending in a transverse direction **156c** between lobe **140a** and lobe **140b** disposed at opposite transverse ends of the connecting portion **166**. The lobes **140a** and **140b** extend in lateral direction **156b** from the connecting portion **166**. The bottom link **106a** includes lobes **140c** and lobes **140d** that extend in the longitudinal direction **156a** from the connecting portion **166** at opposite transverse sides of the connecting portion **166**. The bottom link **106a** includes a first aperture **160** defined within, and extending through, the connecting portion **166**. The bottom link **106a** includes a second aperture **162** extending through both the lobe **140c** and the lobe **140d**. The bottom link **106a** includes a third aperture **164** that extends through both the lobe **140a** and the lobe **140b**. Any of the first aperture **160**, the second aperture **162**, and/or the third aperture **164** may form a joint with any portion of the suspended body **102** and/or the suspension linkage **114**. The ordinal descriptions (e.g., first, second, third) of the apertures **160**, **162**, and **164** are for clarity of description only and are not meant to be limiting in any way. For example, a bottom link may include a third aperture, but not a first or second, and so on. For example, the first aperture **160** may form a pivoted joint between the bottom link **106a** and another part of the suspension linkage **114**, such as the chain stay **108**. The second aperture **162** may form a pivoted joint between the bottom link **106a** and the suspended body **102**. The third aperture **164** may form a pivoted joint between the bottom link **106a** and the center link **112**. When assembled to the frame **100** with the balance of the suspension linkage **114**, the IVC[**106**][**108**] **130** may be located within the first aperture **160**; the IVC[**102**][**106**] **128** may be located within the second aperture **162**; and the IVC[**106**][**112**] **134** may be located within the third aperture **164**. In some examples, the IVC[**106**][**108**] **130** is concentric with an axis of the first aperture **160**. In some examples, the IVC[**102**][**106**] **128** is concentric with an axis of the second aperture **162**. In some examples, the IVC[**106**][**112**] **134** is concentric with an axis of the third aperture **164**.

(89) FIG. 5 is a partial side elevation view of the frame **100**. FIG. 6 is a partial rear isometric view of the frame **100**. FIG. 7A is a partial exploded rear isometric of the frame **100**. FIG. 7B is an exploded view of the axle assembly **168a** shown in FIG. 7A. FIG. 7C is a section through the motive power source **300** taken along section line 7-7 of FIG. 5. In FIG. 5-FIG. 8B, portions of the suspension linkage **114** are removed, for clarity. As shown for example in FIG. 5-FIG. 8B, the motive power source **300** may be coupled to the suspended body **102** via the second aperture **162** and the axle assembly **168a** or **168b**. Additionally or alternately, the motive power source **300** may be coupled to the suspension linkage **114** via the aperture **162**. In some embodiments the motive power source **300** may be coupled to both the suspended body **102** and the suspension linkage **114**.

(90) As best shown in FIGS. 7A-7C, the motive power source **300** may be coupled to the suspended body **102** and the suspension linkage **114** by an axle assembly **168a**. The axle assembly **168a** may include a fastener element **148**, a tapered collet **150**, one or more outer race extenders **172**, a retainer **152**, one or more bearings **146a/b**, an axle **170**, and a cap **182**.

(91) The fastener element **148** may be a variety of types of fastener. In some examples, the fastener **148** is a socket head cap screw. The fastener **148** includes external helical fastener threads **184**. The tapered collet **150** has an aperture **186** formed therein and adapted to receive the fastener **148**. The aperture **186** is sufficiently large to allow a clearance with the fastener **148** such that the fastener threads **184** do not engage the tapered collet **150** at the aperture **186**. The tapered collet **150** may be assembled with the fastener **148** and held to the fastener **148** with a retainer **152** such as a snap ring, spring, circlip, or the like. The retainer **152** may help withdraw the tapered collet **150** when disassembling the axle assembly **168a**.

(92) The axle **170** may have an elongate body **188** with an expandable portion **176** at one end of the elongate body **188** and external axle threads **178** at an opposite end of the elongate body **188**. The

axle **170** may include internal axle threads **180** in an end of the elongate body **188** near the expandable portion **176**. The internal axle threads **180** (see, FIG. 7C) may be adapted to receive and mate with the fastener threads **184**. The inside diameter of the expandable portion **176** may be the same size or less than an outer diameter of the tapered collet **150**. The cap **182** may include internal cap threads **190** suitable to receive and mate with the external axle threads **178**.

(93) The bearings **146a/b** may allow for rotational motion of the bottom link **106a** with respect to the axle assembly **168a**. For example, the bearings **146a/b** may be roller bearings, tapered bearings, bushings, or the like. The bearings **146a/b** may be adapted to receive the outer race extender **172** and inner race extender **174** on an inner race of the bearings **146a/b**. The outer race extender **172** and inner race extender **174** may stabilize and/or locate the bearings in the axle assembly **168a**. The outer race extenders **172** and inner race extenders **174** may fit inside the inner race of the bearing **146a/b**, thereby effectively reducing the inner diameter of the bearings **146a/b**. Such an axle assembly **168a** may allow for installation of the race extenders to such that they do not fall out of the bottom link **106a** during assembly.

(94) As best shown in FIG. 7C, when assembled, the cap **182** may be secured to the suspended body **102** such as by the pulling force of the engagement of the external axle threads **178** with the internal cap threads **190**, a press fit, or by other suitable structures. The bearing **146a/b** and respective outer race extenders **172** and inner race extenders **174** may be assembled with the bottom link **106a**, such as within the second aperture **162** of the bottom link **106a**. Either of the bearings **146a/b** may be floating or fixed along the axle **170**. For example, the bottom link **106a** may include a locating feature **192**, such as a step, on a lobe **140c/d** that limits movement of the bearing **146b** in a transverse direction **156c** along the axle **170**. The bearing **146a** may be allowed to move in the transverse direction **156c** along the axle **170**, such as when the respective lobe **140c/d** does not include a locating feature **192**.

(95) FIG. 8A and FIG. 8B show an alternate embodiment of an axle assembly **168b** for use with the frame **100**. As shown in FIG. 8A and FIG. 8B, an axle assembly **168b** may be used that includes outer race extenders **172** that do not reduce the effective inner diameter of the bearings **146a/b**. In such an assembly, inner race extender **174** may be omitted and locator bosses **196** included in a portion of the rearward boss of the motive power source **300**. A notch in the bottom link **106a** may be included to allow the bottom link **106a** to be installed onto the rearward boss **304**. Other aspects of the axle assembly **168b** may be similar to those of axle assembly **168a** and are not repeated, for brevity.

(96) In either of the axle assemblies **168a/b** in FIG. 7A—FIG. 8B, the axle **170** may be inserted into the suspended body aperture **158**. The axle **170** may be extended through the bearings **146a/b** and through the outer race extenders **172**, inner race extenders **174** (if used), and/or locator bosses **196** (if used), which may be located within or adjacent to the second apertures **162**. The axle **170** may be extended through the mounting aperture **320** in the rearward boss **304** of the motive power source **300**. The axle **170** may be rotated such that the external axle threads **178** engage and mate with the internal cap threads **190**. The axle **170** may be screwed into the internal cap threads **190** such that the axle **170** is located at a datum **194**. The fastener **148** may be inserted through the aperture **186** in the tapered collet **150** and secured with the retainer **152**. The fastener **148** and tapered collet **150** may be inserted into the expandable portion **176** of the axle **170**. The fastener **148** may be rotated to engage the fastener threads **184** with the external axle threads **178**. As the fastener **148** is drawn into the external axle threads **178**, the tapered collet **150** presses against the expandable portion **176**, expanding the expandable portion **176** such that the expandable portion **176** engages the inner wall of the suspended body aperture **158**. The axle assembly **168a/b** allows for a large tolerance discrepancy between the inner diameter of the suspended body aperture **158**, and the outer diameter of the axle assembly **168a/b**. The floating bearing **146a** may force pre-load from the shock assembly **116** to the inner races of the bearings, as opposed to the bearings **146a/b** themselves.

(97) When assembled, the axle **170** may extend through the suspended body aperture **158** in the suspended body **102**, through the second aperture **162** of the bottom link **106a**, and through the mounting aperture **320** of the motive power source **300**. In some embodiments the axle **170** may provide a concentric joint between the suspended body aperture **158**, the second aperture **162** of the bottom link **106a**, and/or the mounting aperture **320** of the motive power source **300**. In some embodiments, the axle **170** may pass through the IVC[**102**][**106**] **128**. In some embodiments, the axle **170** may be concentric with the IVC[**102**][**106**] **128**.

(98) FIG. 9-FIG. 15C show another embodiment of a motive power source **1000** used with the axle assembly **168a**. FIG. 10 is an isometric view of an embodiment of a motive power source **1000**. The motive power source **1000** may include many similar features as the motive power source **300**, which are not repeated for the sake of brevity. The motive power source **1000** may be an electric motor, an internal combustion engine, a transmission, and/or a combination thereof. The motive power source **1000** includes a housing **1002** that contains the internal components of the motive power source **1000**. In some implementations, the housing **1002** may be a load-bearing member that supports loads imparted to the frame **100** and/or suspension linkage **114** such as when the e-bike is ridden, pedaled, or propelled by the motive power source **1000**. The housing **1002** may include an aft portion **1010** and a forward portion **1008** located relative to one another along the longitudinal direction **156a**. The housing **1002** may include one or more mounting points to mount the motive power source **1000** to the frame **100** and/or the suspension linkage **114**. The housing **1002** may include a forward boss **1006** extending away from the forward portion **1008** of the housing **1002**. The motive power source **1000** may include an upper boss **1012**.

(99) The attachments of the motive power source **1000** to the suspended body may be at discrete locations that are load bearing. For example, securement structures **1018**, securement structure **1020** and/or securement structure **1028**, may bear loads transmitted to the frame **100** and/or suspension linkage **314**, such as loads imparted by the movement of the two-wheeled vehicle over the ground, and/or loads imparted by a rider. A benefit of such load bearing may be that the housing **1002** may strengthen or stiffen the assembled frame **100** while not needing to add additional stiffeners, or the like.

(100) The housing **1002** may include, and/or be selectively couplable to, one or more mounting points to mount the motive power source **1000** to the frame **100** and/or the suspension linkage **114**. For example, the housing **1002** may include a removable rearward boss **1014** extending away from the aft portion **1010** of the housing **1002**. The housing **1002** may include an upper portion **1048** and a lower portion **1060**. The upper portion **1048** and the lower portion **1060** encompass part of front portion **1008** and aft portion **1010**. The housing **1002** includes opposing lateral sides **1044** and **1046**. The housing **1002** includes a front portion **1008**, rear portion **1502**, a top **1048** side, and a bottom side **1060**. The rearward boss **1014** may extend upwardly from the rear portion **1010** or upwardly in the lateral direction **156b** from the top side **1048**. The rearward boss **1014** may extend rearwardly in the longitudinal direction **156a** from the point at which the boss **1014** attached to the top side **1048**. The rearward boss **1014** may be located above the power interface **1004**. All, or a portion, of the rearward boss **1014** may be located rearward of the power interface **1004** in the longitudinal direction **156a**. In some examples all, or a portion, of the rearward boss **1014** may be located forward of the power interface **1004** in the longitudinal direction **156a**. In some examples, all or a portion, of the rearward boss **1014** may be aligned in the longitudinal direction **156a** (i.e., vertically aligned) with the power interface **1004**. The mounting aperture **1018** may be located above the power interface **1004**. All, or a portion, of the mounting aperture **1018** may be located rearward of the power interface **1004** in the longitudinal direction **156a**. In some examples all, or a portion, of the mounting aperture **1018** may be located forward of the power interface **302** in the longitudinal direction **156a**. In some examples all, or a portion, of the mounting aperture **1018** may be aligned in the longitudinal direction **156a** with the power interface **1004**. The power interface **1004** may extend transversely from either or both of the opposing lateral sides **1044**, **1046**.

(101) The motive power source **1000** may include an upper boss **1012** near the rearward boss **304**. The upper boss **1012** may extend forwardly in the longitudinal direction **156a** from the point at which the boss **1012** is attached to the top side **1048**. The upper boss **1012** may be located above the power interface **1004**. All, or a portion, of the upper boss **1012** may be located forward of the power interface **1004** in the longitudinal direction **156a**. All, or a portion, of the upper boss **1012** may be located rearward of the power interface **1004** in the longitudinal direction **156a**. All, or a portion, of the upper boss **1012** may be aligned in the longitudinal direction **156a** with the power interface **1004** (i.e., vertically aligned). The mounting aperture **1028** may be located above the power interface **1004**. All, or a portion of, the mounting aperture **1028** may be located forward of the power interface **1004** in the longitudinal direction **156a**. All, or a portion of, the mounting aperture **1028** may be located rearward of the power interface **1004** in the longitudinal direction **156a**. All, or a portion, of the mounting aperture **1028** may be aligned in the lateral direction **156b** with the power interface **1004** (i.e., horizontally aligned).

(102) Likewise, the housing **1002** may include a forward boss **1006** extending away from the forward portion **1008** of the housing **1002**. The forward boss **1006** may extend forwardly in the longitudinal direction **156a** from the point at which the boss **1006** is attached to the front side **1008** of the housing **1002**. The forward boss **1006** may be located above the power interface **1004** in the lateral direction **156b**. All, or a portion, of the forward boss **1006** may be located forward of the power interface **1004** in the longitudinal direction **156a**. All, or a portion, of the forward boss **1006** may be aligned in the longitudinal direction **156a** with the power interface **1004** (i.e., vertically aligned). All, or a portion, of the forward boss **1006** may be aligned in the lateral direction **156b** with the power interface **1004** (i.e., horizontally aligned). The mounting aperture **1020** may be located above the power interface **1004**. All, or a portion, of the mounting aperture **1020** may be located forward of the power interface **1004** in the longitudinal direction **156a** (i.e., vertically aligned). All, or a portion, of the mounting aperture **1020** may be aligned in the lateral direction **156b** with the power interface **1004** (i.e., horizontally aligned).

(103) The aperture **1018** may be located in an upper portion **1036**, forward portion **1042**, lower portion **1040**, and/or a rearward portion **1038** of the boss **1014**. For example, the aperture **1018** may be located within one diameter of the aperture **1018** of an external upper face **1052** of the boss **1014**, within one diameter of the aperture **1018** of a rear face **1050** of the boss **1014**, and/or within one diameter of the aperture of a forward face **1054** of the boss **1014**. In some examples, the aperture **1018** may be within one diameter of the aperture **1018** of the upper surface **1052** of the housing **1002**.

(104) The housing **1002** of the motive power source **1000** may include one or more removable bosses. For example, the motive power source **1000** may include a protrusion **1024** configured to couple to one or more boss extensions **1030a/b**. The protrusion **1024** may have one or more apertures defined therethrough, such as the apertures **1032a/b**. When coupled to the protrusion **1024**, the protrusion **1024** and the boss extensions **1030a/b** may form a rearward boss **1014** similar in structure and function to the rearward boss **304**. The rearward boss **1014** may extend away and rearward from the aft portion **1010** of the housing **1002**.

(105) As shown for example in FIG. **11**, one or more boss extensions **1030** may be provided. The boss extension **1030a** and/or **1030b** may have a boss extension body **1016**. The boss extension body **1016** may have a mounting aperture **1018** defined therethrough. The mounting aperture **1018** may be similar in structure, location, and function to the mounting aperture **320** of the motive power source **300** previously described. The boss extension body **1016** may have a receptacle **1026** defined therein and adapted to receive a protrusion of the motive power source **1000**, such as the protrusion **1024**. The receptacle **1026** may include one or more mounting apertures such as the mounting apertures **1022a/b**. The mounting apertures **1022a/b** may be adapted to align with the respective apertures **1032a/b** of the protrusion **1024**. One or more fastener elements **1034** may secure the boss extension body **1016** to the housing **1002** via the respective mounting apertures

**1022a/b** and apertures **1032a/b**. The alignment of the mounting apertures **1022a/b** with the apertures **1032a/b** may position the boss extension body **1016** relative to the motive power source **1000**, the suspended body **102**, and/or the suspension linkage **114**. When assembled, the axle **170** of an axle assembly, such as the axle assemblies **168a/b** may extend through the suspended body aperture **158**, the second aperture **162** of the bottom link **106a/b**, and the mounting aperture **1018** to form a jointed connection. The IVC[**102**][**106**] **128** may be located within the jointed connection formed by the axle **170**, the suspended body aperture **158**, the second aperture **162**, and the mounting aperture **1018**. In some examples, the alignment of the mounting apertures **1022a/b** with the apertures **1032a/b** may position the mounting aperture **1018** to be concentric with the suspended body aperture **158** and/or the second aperture **162** of the bottom link **106a/b**.

(106) A benefit of providing a removable boss such as with the motive power source **1000** may include the ability to use a common motive power source **1000** with different suspended bodies **102** and/or suspension linkages **114**, or to change performance characteristics of the suspension linkage **114**. As shown for example, in FIGS. **12** and **13**, different boss extensions may provide for different locations of the mounting aperture **1018** relative to the motive power source **1000** or the suspended body **102**. Moving the location of the mounting aperture **1018** may move the location of the IVC[**102**][**106**] **128** relative to the other IVCs of the suspension linkage **114**. Some locations of the IVC[**102**][**106**] **128** may be suited for one type of suspended body **102** and/or suspension linkage **114**, while other locations of the IVC[**102**][**106**] **128** may be provided for another suspended body **102** and/or suspension linkage **114**, while using the same motive power source **1000**. In another example, the boss extensions **1030a/b** may provide for adjustment of suspension characteristics of the suspension linkage **114**, for example by moving the location of the IVC[**102**][**106**] **128** of a given suspension linkage **114** and/or suspended body **102**. For example, the boss extension **1030a** may be associated with one location of the IVC[**102**][**106**] **128** and a corresponding type of performance for the suspension linkage **114**, whereas another boss extension **1030b** and another location of the IVC[**102**][**106**] **128** may be associated with another type of performance for the suspension linkage **114**. For example, the boss extension **1030a** may be suited to configure the two-wheeled vehicle to climb a grade, whereas the boss extension **1030b** may be suited to configure the two-wheeled vehicle to descend a grade. In other examples, the locations of the IVC[**102**][**106**] **128** may change the anti-squat and/or anti-rise behavior of the suspension linkage **114**. In some cases, it may be economical for the same motive power source to be used on several different two-wheeled vehicles with varying designs. To accommodate these varying packaging constraints, while maintaining suspension linkage performance such as anti-squat and/or anti-rise, the motive power source may be rotated, as an example, about an axis parallel to transverse direction **156c**, or shifted in the lateral direction **156b**, the longitudinal direction **156a** or the transverse direction **156c**. The protrusion **1024** may be shifted accordingly. The boss extensions **1030a/b** may provide for adjustment of suspension characteristics of the suspension linkage **114**, for example by maintaining a similar relationship of the location of the IVC[**102**][**106**] **128** of a given suspension linkage **114** and/or suspended body **102**, and the driven wheel axis **118** despite the position change of the motive power source **1000**. Adjustability of mounting aperture **1018** may also provide for clearance to suspended bodies or two-wheel vehicle components.

(107) FIG. **15A**-FIG. **15C** show an example of the motive power source **1000** used with the axle assembly **168a** as previously described. The axle assembly **168a** may have a similar function and structure when used with the motive power source **1000** as when used with the motive power source **300**, which is not repeated, for brevity.

(108) FIGS. **16A**-**16C** show an example of the motive power source **1000** used with the axle assembly **168b** as previously described. The boss extensions **1030a/b** may include the locator bosses **196** such that inner race extenders **174b** are not used with the axle assembly **18b** and the motive power source **1000**. The axle assembly **168b** may have a similar function and structure when used with the motive power source **1000** as when used with the motive power source **300**,

which is not repeated, for brevity.

(109) FIG. 17A—FIG. 17D show views of an example of a bottom link **106b**. While the bottom link **106a** may have an H-like shape, the bottom link **106b** may have a Y-like shape. The bottom link **106b** has transversely opposing plates **161a/b**. Each plate **161a/b** being generally I shaped and each defining a first portion **140a/b** and a second portion **141a/b** in communication with the first portions **104a/b**. The transverse plates **161a/b** are attached to one another by a connecting portion **166** extending between the second portions **141a/b** and spacing the transverse plates **161a/b** apart. A lobe **140c** extends longitudinally from the connecting portion **166**. An aperture **164** is formed in the first lobe **140a/b** of each plate **161a/b**. The apertures **164** are aligned with each other. An aperture **162** is formed in the lobe **140c**. An aperture **160** is formed in the second portions **141a/b** of each plate **161a/b**. The apertures **160** are aligned with each other and run through the connection portion **166**. The bottom links **106a/b** may be adapted for use with different motive power sources. For example, the bottom link **106a** may be adapted for use with the motive power sources **300** and **1000** as previously described. The bottom link **106b** may be adapted for use with motive power sources **1800** and **1900** described herein. The bottom link **106b** has a body **142b**. The body **142b** includes a connecting portion **166** extending in a transverse direction **156c** between lobe **140a** and lobe **140b** disposed at opposite transverse ends of the connecting portion **166**. The lobes **140a** and **140b** extend in lateral direction **156b** from the connecting portion **166**. The bottom link **106b** includes a lobe **140c** extending in the longitudinal direction **156a** from a central part of the connecting portion **166**. The bottom link **106b** includes a first aperture **160** defined within, and extending through, the connecting portion **166**. The bottom link **106b** includes a second aperture **162** extending through the lobe **140c**. The bottom link **106b** includes a third aperture **164** that extends through both the lobe **140a** and the lobe **140b**. Any of the first aperture **160**, the second aperture **162**, and/or the third aperture **164** may form a joint with any portion of the suspended body **102** and/or the suspension linkage **114**. For example, the first aperture **160** may form a pivoted joint between the bottom link **106b** and another part of the suspension linkage **114**, such as the chain stay **108**. The second aperture **162** may form a pivoted joint between the bottom link **106b** and the suspended body **102**. The third aperture **164** may form a pivoted joint between the bottom link **106b** and the center link **112**. When assembled to the frame **100** with the balance of suspension linkage **114**, the IVC[**106**][**108**] **130** may be located within the first aperture **160**; the IVC[**102**][**106**] **128** may be located within the second aperture **162**; and the IVC[**106**][**112**] **134** may be located within the third aperture **164**. In some examples, the IVC[**106**][**108**] **130** is concentric with an axis of the first aperture **160**. In some examples, the IVC[**102**][**106**] **128** is concentric with an axis of the second aperture **162**. In some examples, the IVC[**106**][**112**] **134** is concentric with an axis of the third aperture **164**.

(110) FIGS. 18A-18C show an example of a motive power source **1800** used with the axle assembly **168b** as previously described. The motive power source **1800** is similar to the motive power source **300**. However, the rearward boss of the motive power source **1800** is bifurcated into two rearward bosses **1802a** and **1802b** spaced apart from one another in the transverse direction **156c**. A receptacle **1804** is defined between the rearward bosses **1802a** and **1802b**. As best seen in FIG. 18C, the receptacle may be adapted to receive the lobe **140c** of the bottom link **106b**. When used with the motive power source **1800**, the axle assembly **186b** is assembled as previously described. The axle **170** is passed through the mounting apertures **320** in the motive power source **1800**. The axle **170** may be passed through the second aperture **162** of the bottom link **106b**, and may be threaded into the cap **182** and secured with the fastener **148** and tapered collet **150** as previously described. When assembled with the motive power source **1800**, the axle assembly **168b** may pass through the IVC [ **102** ][ **106** ] **128**. In some examples the axle may be concentric with the IVC [ **102** ][ **106** ] **128**.

(111) FIGS. 19A-19C show an example of a motive power source **1900** used with the axle assembly **168b** as previously described. The motive power source **1900** is similar to the motive

power source **1000**. However, the motive power source **1900** includes two removable boss extensions **1902a** and **1902b** spaced apart in the transverse direction **156c**. The motive power source **1900** includes protrusions **1904a** and **1904b** similar to the protrusion **1024** of the motive power source **1000**. The boss extensions **1902a/b** are coupled to the respective protrusions **1904a/b** by one or more fasteners **1034** as previously described with respect to the motive power source **1000**. The boss extensions **1902a** and **1902b** may include the locator bosses **196** and may include mounting apertures **1018** therethrough, as previously described. The function, structure and benefits of the motive power source **1900** may be similar to those of the motive power sources **300**, **1000**, and **1800** described herein. A receptacle **1804** is defined between the rearward bosses **1802a** and **1802b**. As best seen in FIG. **18C**, the receptacle **1906** may be adapted to receive the lobe **140c** of the bottom link **106b**. When used with the motive power source **1900**, the axle assembly **186b** is assembled as previously described. The axle **170** is passed through the mounting apertures **1018** in the boss extensions **1902a/b** of the motive power source **1900**. The axle **170** may be passed through the second aperture **162** of the bottom link **106b**, and may be threaded into the cap **182** and secured with the fastener **148** and tapered collet **150** as previously described. When assembled with the motive power source **1900**, the axle assembly **168b** may pass through the IVC **[102][106]** **128**. In some examples the axle may be concentric with the IVC **[102][106]** **128**.

(112) Providing for the mounting of the motive power source **300**, **1000**, **1800**, and/or **1900** to the frame **100** and to the suspension linkage **114**, such as described herein may provide for a compact frame **100**, with fewer parts, joints, and a simpler construction than with traditional motor mounts. For example, by using a motor mounting aperture such as the mounting aperture **320** and/or **1018** to both mount the motor and act as a suspension joint, the need for separate motor mounts and suspension joints may be reduced or eliminated. Additionally, the forward portion **308** of the motive power source **300** may be received in the receptacle **144** formed in the suspended body **102**, thereby forming a more compact two-wheeled vehicle.

(113) The description of certain embodiments included herein is merely exemplary in nature and is in no way intended to limit the scope of the disclosure or its applications or uses. In the included detailed description of embodiments of the present systems and methods, reference is made to the accompanying drawings which form a part hereof, and which are shown by way of illustration specific to embodiments in which the described systems and methods may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice presently disclosed systems and methods, and it is to be understood that other embodiments may be utilized, and that structural and logical changes may be made without departing from the spirit and scope of the disclosure. Moreover, for the purpose of clarity, detailed descriptions of certain features will not be discussed when they would be apparent to those with skill in the art so as not to obscure the description of embodiments of the disclosure. The included detailed description is therefore not to be taken in a limiting sense, and the scope of the disclosure is defined only by the appended claims.

(114) From the foregoing it will be appreciated that, although specific embodiments of the invention have been described herein for purposes of illustration, various modifications may be made without deviating from the spirit and scope of the invention.

(115) The particulars shown herein are by way of example and for purposes of illustrative discussion of the preferred embodiments of the present invention only and are presented in the cause of providing what is believed to be the most useful and readily understood description of the principles and conceptual aspects of various embodiments of the invention. In this regard, no attempt is made to show structural details of the invention in more detail than is necessary for the fundamental understanding of the invention, the description taken with the drawings and/or examples making apparent to those skilled in the art how the several forms of the invention may be embodied in practice.

(116) As used herein and unless otherwise indicated, the terms “a” and “an” are taken to mean “one”, “at least one” or “one or more”. Unless otherwise required by context, singular terms used

herein shall include pluralities and plural terms shall include the singular.

(117) Unless the context clearly requires otherwise, throughout the description and the claims, the words ‘comprise’, ‘comprising’, and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in the sense of “including, but not limited to”.

Words using the singular or plural number also include the plural and singular number, respectively. Additionally, the words “herein,” “above,” and “below” and words of similar import, when used in this application, shall refer to this application as a whole and not to any particular portions of the application.

(118) Of course, it is to be appreciated that any one of the examples, embodiments or processes described herein may be combined with one or more other examples, embodiments and/or processes or be separated and/or performed amongst separate devices or device portions in accordance with the present systems, devices and methods.

(119) Finally, the above discussion is intended to be merely illustrative of the present system and should not be construed as limiting the appended claims to any particular embodiment or group of embodiments. Thus, while the present system has been described in particular detail with reference to exemplary embodiments, it should also be appreciated that numerous modifications and alternative embodiments may be devised by those having ordinary skill in the art without departing from the broader and intended spirit and scope of the present system as set forth in the claims that follow. Accordingly, the specification and drawings are to be regarded in an illustrative manner and are not intended to limit the scope of the appended claims.

## Claims

1. A two-wheeled vehicle comprising: a suspended body; a suspension linkage including a bottom link body pivotally coupled to the suspended body at a joint; and a motive power source coupled to both the suspended body and the bottom link body at the joint, the motive power source including a housing forming an exterior portion of thereof, wherein a removable first boss extends from the housing; a second boss is selectively removable from the housing, wherein: the removable first boss defines an IVC in a first location when coupled to the housing while the second boss is not coupled to the housing; and the second boss defines the IVC in a second location when coupled to the housing while the removable first boss is not coupled to the housing.
2. The two-wheeled vehicle of claim 1, further comprising: a first securement structure formed in the suspended body; a second securement structure formed in the bottom link body; the removable first boss having a third securement structure; and an axle coupled to the first, second, and third securement structures.
3. The two-wheeled vehicle of claim 2, wherein an instantaneous velocity center (IVC) of the suspension linkage is located within the first, second, and third securement structures.
4. The two-wheeled vehicle of claim 2, wherein the first securement structure, the second securement structure, and the third securement structure are concentric with one another at the joint.
5. The two-wheeled vehicle of claim 1, further comprising: an axle assembly including: an axle, wherein the axle includes an expandable portion at a first end of an elongate body and an internally threaded portion located proximate to the expandable portion; a tapered collet including an aperture therethrough; a fastener adapted to be received in the aperture and including an externally threaded portion adapted to mate with the internally threaded portion of the axle, wherein when the fastener is mated with the axle, the fastener causes the tapered collet to expand the expandable portion to secure the axle assembly to the suspended body.
6. The two-wheeled vehicle of claim 2, wherein the removable first boss is selectively removable from the housing.
7. The two-wheeled vehicle of claim 1, wherein the housing is a load bearing member of the



suspension linkage.

8. The two-wheeled vehicle of claim 1, wherein the suspension linkage includes: a plurality of linkage bodies including: the suspended body, a second body, the bottom link body, a fourth body, a fifth body, and a sixth body operatively connected defining at least seven primary instantaneous velocity centers (IVCs) wherein; the suspended body is a binary link; a shock assembly is configured to resist movement between two or more of the suspended body, the second body, the bottom link body, the fourth body, the fifth body, or the sixth body; and at least one primary IVC migration path reverses as the suspension linkage moves from an at least partially extended state to an at least partially compressed state.

9. The two-wheeled vehicle of claim 8, wherein the plurality of linkage bodies define a driven wheel-path.

10. The two-wheeled vehicle of claim 8, wherein: the suspended body (**102**) includes a jointed connection with the bottom link body (**106**) defining a primary IVC[**102**][**106**] (**128**), and a jointed connection with the fifth body (**110**) defining a primary IVC[**102**][**110**] (**124**); the bottom link body (**106**) includes a jointed connection with the fourth body (**108**) defining a primary IVC[**106**][**108**] (**130**), and a jointed connection with the sixth body (**112**) defining a primary IVC[**106**][**112**] (**134**); the fifth body (**110**) includes a jointed connection with the second body (**104**) defining a primary IVC[**104**][**110**] (**132**), and a jointed connection with the sixth body (**112**) defining a primary IVC[**110**][**112**] (**122**); and the second body (**104**) includes a jointed connection with the fourth body (**108**) defining a primary IVC[**104**][**108**] (**126**), wherein a migration path defined by the IVC[**106**][**112**] (**134**) reverses as the suspension linkage moves from the at least partially extended state to the at least partially compressed state.

11. The two-wheeled vehicle of claim 10, wherein a migration path defined by the IVC[**106**][**108**] (**130**) reverses as the suspension linkage moves from the at least partially extended state to the at least partially compressed state.

12. The two-wheeled vehicle of claim 10, wherein the second body (**104**) is a driven wheel carrier body or a brake carrier body.

13. The two-wheeled vehicle of claim 10, wherein the second body (**104**) is a driven wheel carrier body and a brake carrier body.

14. The two-wheeled vehicle of claim 10, wherein the fourth body (**108**) is a driven wheel carrier body or a brake carrier body.

15. The two-wheeled vehicle of claim 10, wherein the fourth body (**108**) is a driven wheel carrier body and a brake carrier body.

16. The two-wheeled vehicle of claim 10, wherein: a lower base line is defined by the primary IVC[**102**][**106**] (**128**) and the primary IVC[**106**][**108**] (**130**); an upper base line is defined by the primary IVC[**102**][**110**] (**124**) and the primary IVC[**104**][**110**] (**132**); and the primary IVC[**110**][**112**] (**122**) is located outside the upper and lower base lines.

17. The two-wheeled vehicle of claim 10, wherein a line defined by the primary IVC[**106**][**112**] (**134**) and the primary IVC[**110**][**112**] (**122**) is located outside the primary IVC[**102**][**106**] (**128**) and the primary IVC[**106**][**108**] (**130**).

18. The two-wheeled vehicle of claim 10, wherein the primary IVC[**106**][**112**] (**134**) and the primary IVC[**106**][**108**] (**130**) are on the same side of the primary IVC[**102**][**106**] (**128**).

19. A two-wheeled vehicle comprising: a suspended body; a suspension linkage including a bottom link body pivotally coupled to the suspended body at a joint; a motive power source coupled to both the suspended body and the bottom link body at the joint, the motive power source including a housing forming an exterior portion of thereof, wherein a removable first boss extends from the housing; and an axle assembly including: an axle, wherein the axle includes an expandable portion at a first end of an elongate body and an internally threaded portion located proximate to the expandable portion; a tapered collet including an aperture therethrough; a fastener adapted to be received in the aperture and including an externally threaded portion adapted to mate with the

internally threaded portion of the axle, wherein when the fastener is mated with the axle, the fastener causes the tapered collet to expand the expandable portion to secure the axle assembly to the suspended body.

---