

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250253600

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Dittus; Karl Klaus

COMBINATION OUTLET ASSEMBLY AND POWER DISTRIBUTION UNIT INCLUDING THE SAME

Abstract

An electrical outlet assembly includes a molded housing having side walls, end walls extending between the side walls, a bottom wall interconnecting the side walls and the end walls, and an outlet core extending upwardly from the bottom wall into a space defined between the side and end walls. In one example, a first end wall of the end walls includes a latch portion that is deflectable relative to the space to selectively secure an electrical plug that is engaged with the outlet core. In another example, a biasing element is attached to the molded housing to bias the latch portion toward the outlet core.

Inventors: Dittus; Karl Klaus (Raleigh, NC)

Applicant: CIS Global LLC (Tucson, AZ)

Family ID: 78179235

Appl. No.: 19/049680

Filed: February 10, 2025

Related U.S. Application Data

parent US continuation 18521614 20231128 parent-grant-document US 12224536 child US 19049680

parent US continuation 17694379 20220314 parent-grant-document US 11831112 child US 18521614

parent US continuation 17070336 20201014 parent-grant-document US 11276970 child US 17694379

Publication Classification

Int. Cl.: H01R24/78 (20110101); **H01R13/506** (20060101); **H01R13/514** (20060101);
H01R27/00 (20060101); **H01R105/00** (20060101)

U.S. Cl.:

CPC H01R24/78 (20130101); **H01R13/506** (20130101); **H01R13/514** (20130101);
H01R27/00 (20130101); **H01R2105/00** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application is a continuation of U.S. application Ser. No. 17/694,379, filed Mar. 14, 2022, which is a continuation of U.S. application Ser. No. 17/070,336, filed Oct. 14, 2020, each of which are hereby incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

[0002] The field of the invention relates generally to electrical outlets operable interchangeably with a combination of different types of mating plug connectors, and more specifically to a combination outlet assembly for an industrial power distribution unit.

[0003] Computer data center applications typically include a plurality of computer servers arranged in server racks or cabinets. Power distribution units (PDUs) are known to include a number of power outlets distributed along a chassis of the PDU for respective connection to components and equipment arranged on the server rack. The respective PDUs receive input power from the same power source or different power sources, and distribute output power to the power outlets provided. Power cords of equipment in the server racks or cabinets may be plugged in to the PDU. State of the art PDUs also intelligently facilitate remote management of power distribution to critical equipment, power metering and monitoring features both local and remote from the PDU, power outlet switching on/off and local and remote controls, alarm features detecting and alerting of certain operating conditions, and other sophisticated features allowing adaptation of the PDU for particular power system applications distributing power to specific electrical components and equipment.

[0004] A variety of different types of plug connectors for power cords are known for use with different devices in the server rack or cabinet that are desirably served by industrial power distribution units. As such, PDUs including so-called combination outlets have recently been introduced wherein the same power outlets in the PDU may be interchangeably used with different types of plug connectors in different arrangements. Conventional combination outlets for PDUs are disadvantaged in some aspects, however, and further improvements are desired to more completely meet the needs of the marketplace.

SUMMARY

[0005] Some embodiments of the invention provide an electrical outlet assembly. The electrical outlet assembly includes a molded housing having side walls, end walls extending between the side walls, a bottom wall interconnecting the side walls and the end walls, and an outlet core extending upwardly from the bottom wall into a space defined between the side and end walls. In one example, a first end wall of the end walls includes a latch portion that is deflectable relative to the space to selectively secure an electrical plug that is engaged with the outlet core. In another example, a biasing element is attached to the molded housing to bias the latch portion toward the outlet core.

[0006] Some embodiments of the invention provide an electrical outlet assembly. The electrical outlet assembly includes a monolithic housing that includes an outlet core, and walls that define a

space around the outlet core to receive an electrical plug. In one example, a first wall of the walls includes a cantilevered latch portion that is movable relative to the space and the outlet core to selectively retain an electrical plug. In another example, a biasing element is removably secured to the monolithic housing to contact an exterior side of the cantilevered latch portion, to bias the cantilevered latch portion toward the outlet core.

[0007] Some embodiments of the invention provide a method of manufacturing an electrical outlet assembly. The method includes molding a housing that includes an outlet core, and walls that define a space around the outlet core to receive an electrical plug, with a first wall of the walls including a cantilevered latch portion that is movable relative to the space and the outlet core to retain an electrical plug, and securing a biasing element to the molded housing to contact an exterior side of the cantilevered latch portion to bias the cantilevered latch portion toward the outlet core.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Non-limiting and non-exhaustive embodiments are described with reference to the following Figures, wherein like reference numerals refer to like parts throughout the various views unless otherwise specified.

[0009] FIG. 1 is a top perspective view of a combination outlet assembly according to an exemplary embodiment of the present invention.

[0010] FIG. 2 is a top view of the exemplary combination outlet assembly shown in FIG. 1.

[0011] FIG. 3 is a magnified view of a first exemplary outlet in the combination outlet assembly shown in FIGS. 1 and 2.

[0012] FIG. 4 is an exemplary perspective view of a first exemplary power cord and plug connector that may be connected to the first outlet and the second outlet shown in FIG. 3.

[0013] FIG. 5 is a magnified view of a second exemplary outlet in the combination outlet assembly shown in FIGS. 1 and 2.

[0014] FIG. 6 is an exemplary perspective view of a second exemplary power cord and plug connector that may be connected only to the second outlet shown in FIG. 5.

[0015] FIG. 7 is a bottom perspective view of the exemplary combination outlet assembly shown in FIG. 1.

[0016] FIG. 8 is an end view of the exemplary combination outlet assembly shown in FIGS. 1 and 7.

[0017] FIG. 9 is a side view of the exemplary combination outlet assembly shown in FIGS. 1 and 7.

[0018] FIG. 10 is a bottom view of the exemplary combination outlet assembly shown in FIGS. 1 and 7.

[0019] FIG. 11 is a first partial exploded view of the exemplary combination outlet assembly shown in FIG. 1.

[0020] FIG. 12 is a perspective view of an exemplary power cord latch element for the combination outlet assembly shown in FIG. 11.

[0021] FIG. 13 is a full exploded view of the exemplary combination outlet assembly shown FIG. 1.

[0022] FIG. 14 is a partial assembly view of a portion of an exemplary power distribution unit including combination outlet assemblies as shown in FIGS. 1-13.

[0023] FIG. 15 is an enlarged partial assembly view of the power distribution unit shown in FIG. 14.

[0024] FIG. 16 is a perspective view of the complete power distribution unit shown in partial view

in FIGS. 14 and 15.

[0025] FIG. 17 is a partial exploded view of an exemplary power cord locking latch assembly for the power distribution unit assemblies shown in FIGS. 14 through 16 and including the combination outlet assemblies shown in FIGS. 1-13.

[0026] FIG. 18 is a perspective assembly view of the power cord locking latch assembly shown in FIG. 17.

[0027] FIG. 19 is a perspective view of a portion of the power cord locking latch assembly shown in FIGS. 17 and 18.

DETAILED DESCRIPTION OF THE INVENTION

[0028] In order to understand the inventive concepts described below to their fullest extent, set forth below is a discussion of the state of the art and certain longstanding problems pertaining to industrial power distribution units (PDUs), followed by descriptions of exemplary inventive embodiments of PDU devices, systems and methods addressing longstanding problems in the art.

[0029] In general, an industrial PDU typically includes an elongated chassis with a large number of power outlets (e.g., 36 outlets) arranged along an axial length of the chassis, in combination with sophisticated power monitoring and power management components. The PDU may define a portion of a rather complex redundant power system in certain applications. For example, in a data center application, two power input paths may connect to respective sets of main power panels, transfer switches, backup generators, power panels, Maintenance Bypass Panels (MBP), uninterruptible power supplies, and branch protection circuit breakers feeding electrical power to the respective PDUs that in turn feed electrical power to information technology (IT) equipment and achieve multiple and redundant power supply operation of the IT equipment via the PDUs provided.

[0030] Each PDU in the data center application may be provided with “intelligent” features such as power metering, power control, environmental sensing, etc. of the PDU in use. A management module, sometimes referred to as a network management module, is therefore typically provided in the PDU that includes a simple computer or controller in communication with a network interface to realize bi-directional communication with a remote computer or computing network for purposes of monitoring and managing the power system in the data center. A number of different communication ports may be provided in a network interface including a Universal Serial Bus (USB) port, an Ethernet port, Rs485 ports, and sensor ports that may in turn interface with compatible cables and mating connectors in a known manner.

[0031] The management module in a conventional PDU may include a display that is local to the management module to show data and setup information at the PDU to the end user or installer, as well as responsible persons for overseeing the data center. The display in the management module may include a liquid crystal display (LCD) display screen, a light emitting diode (LED) display screen, and LCD/LED display screen, an organic light emitting diode (oLED) display screen, or another known type of display screen. The local display may be a single color display or multiple color display, may be provided with or without backlighting, and may be factory set to show critical power and setup information to the end user, installer or overseer as well as to display desired data and information after setup.

[0032] By virtue of the features described above, industrial PDUs are relatively large, sophisticated devices and therefore relatively expensive devices possessing vast functionality that so-called “power strip” devices cannot and will not provide. Power-strips are instead multi-outlet devices which, by design, are smaller, lighter, portable, and relatively inexpensive for powering non-critical electrical components for general business or residential use that do not require the power monitoring, power management, and data communication capabilities of an industrial PDU.

[0033] The various power outlets provided in a PDU may distribute electrical power from a common power supply input to a respective electrical component, electrical device, electrical appliance or electrical equipment via removable power cords. Each power cord has a plug

connector on one end that interfaces with one of the outlets on the PDU and a second end that connects to the electrical device, electrical appliance or electrical equipment. Such PDUs and power cords are prolifically used for respective power connection to IT components and equipment arranged on the server rack in a computer data center.

[0034] A number of different types of plug connectors exist for power cords in the computer data center equipment realm. The plug connectors typically include terminals located inside an open-ended housing that may in turn be received over an outlet in a PDU in a safe and effective manner. The terminals of the plug connector pass through apertures in the outlet of the PDU and are received in mating terminals of the outlet to establish the desired electrical connection to the PDU while the housing of the plug connector extends over and receives the exterior surface of the PDU outlet. As such, conventional plug connectors and PDU outlets each have mating housing features and mating terminal features.

[0035] In contrast to a PDU, a conventional power strip device is designed for use with a standard plug having terminals projecting from an exterior of the plug housing that are mated with plug-in connection to internal terminals of an outlet, without positive engagement of the plug connector housing to any housing feature of the socket. The outlets in the power strip receive the terminals of a plug but the plug connector housing itself is not received in the outlets to establish the desired electrical connection. The power strip device that is generally designed for residential or business use is designed to operate with respect to standard plugs having standard terminals that are in turn universally used with a standard wall outlet in a modern residence or commercial building.

[0036] For instance, in the United States the standard wall outlet is a NEMA 5-15R, 15A outlet. The standard plug in the United States is either a NEMA 1-15P plug or a NEMA 5-15P plug. NEMA 1-15P and NEMA 5-15P plugs each include parallel and straight terminal blades, while the NEMA 5-15 plug further includes a terminal ground pin. The NEMA 1-15P and NEMA 5-15P plugs are commonly referred to in layman terms as a “two prong” plug or a “three prong” plug that are prolifically found in power cords and extension cords of a typical consumer electrical device or appliance. In general, any power cord including the standard plug can be plugged into the standard wall outlet and can alternatively be plugged in to the power strip device, whereas the plug connectors of certain types of data center equipment are entirely incompatible with the standard wall outlet due to the terminals being interior to the plug housing and due to interfering features of the plug connector housing and the standard wall outlet, and for the same reasons are incompatible with the standard outlets in a power strip device. From this perspective, and unlike the power strip device, the industrial PDU requires special purpose outlets rather than standard outlets in order to make the needed connections to IT equipment or other devices via power cords having special purpose plug connectors with incompatible housing and terminal features to the standard outlet design.

[0037] Different types of special purpose plug connectors are likewise known that include different plug connector housing shapes and different orientations of terminals inside the plug connector housing. Accordingly, different types of special outlets are known for PDUs that are specifically configured to connect to different types of special purpose connector plugs via compatible outlet shapes and terminal apertures with one of the different types of plug connectors available. Such different types of special purpose outlets have been used in conventional PDUs to connect with specific plug connector types in a one-to-one correlation. That is, each of the different types of special purpose outlets is generally configured to specifically connect to a different one of the particular and different types of plug connectors available. In other words, a plurality of different outlets have conventionally been provided in a PDU to correspondingly mate with different types of plug connectors, wherein a first type of outlet is provided to mate with a first type of plug connector, a second type of outlet is provided to mate with a second type of plug connector, etc.

[0038] Providing such different types of special purpose outlets in a conventional PDU to mate with different plug connector types is undesirable from the manufacturing perspective. Increasing

the number of outlets in the PDU to provide a greater variety of power outlets having specific configuration to mate with power cords having different plug connector types requires a larger PDU and therefore increased material costs and assembly costs in the manufacturing of a PDU. While this may be acceptable to customers that can use the outlets provided in about the same number, in other cases such a PDU would be a poor fit for a customer that has no need for the number of combination outlets provided in the PDU. A possible solution would be to offer a number of stock keeping units (SKUs) of PDUs having different numbers of combination outlets, but increasing SKUs complicates the supply chain and requires additional costs to maintain an adequate inventory of PDUs to meet the needs of different customers.

[0039] Alternatively, customized PDU manufacturing is possible to meet the needs of customers specifically. Such customization of PDUs is undesirable in some aspects from each of the manufacturer's perspective and customer perspective. While customization of PDUs can be accommodated with some appeal to certain customers, it increases manufacturing costs and corresponding purchase prices. Different PDUs having the various different types of power outlets in different numbers for individual installations also entails a relatively complicated order process and opportunity for human error and mistake in the ordering and in the execution of the order by the manufacturer. Manufacturing delay and delivery delay for customized PDUs may also result in uneven timing of orders and inefficiencies of manufacturing customized PDUs.

[0040] From the purchaser's perspective, customization of PDUs can nonetheless undesirably result in a sub-optimal number of outlets for connection to the specific types of plug connectors for a particular end use either because the purchaser miscalculated the number of desired outlets of each type that is actually needed or because the needs changed due to unanticipated changes in the components being connected to the PDU or to unexpected types of power cords provided or on hand to make the desired connections. Considering that the connected plugs and IT equipment receiving power from the PDU may change over time in a data center, an otherwise acceptable PDU at the time of initial purchase and installation could suddenly become obsolete as the need to connect to different types of plug connectors changes.

[0041] Recently, PDUs have been introduced that include so-called combination outlets that are designed to facilitate electrical connections to different types of special purpose plug connectors in the same outlet. That is, by virtue of such combination outlets, different types of plug connectors having different plug housings and/or different terminal configurations can be interchangeably connected to the same outlet. This provides desired flexibility to make connections to various different types of plug connectors in a smaller number of outlets to reduce the size and expense of a PDU while affording greater flexibility from the installation perspective. Known combination outlets, however, can nonetheless be impractical in some aspects, undesirably limited in some aspects, undesirably complicated and expensive to manufacture, and/or subject to certain reliability issues in use. Improvements are accordingly desired.

[0042] Practical, simple, reliable and more economically manufactured combination outlet assemblies and power distribution units including combination outlet assemblies are described hereinbelow that address the shortcomings above. Method aspects will be in part apparent and in part explicitly discussed from the following description. While combination outlet assemblies and industrial PDUs including the same are described in the exemplary context of power distribution in computer data centers and data center equipment including IT equipment, such description is exemplary only and the embodiments of the invention are not necessarily limited thereto. Rather, the benefits of the inventive embodiments of combination outlet assemblies and PDUs accrue more generally to any end use or application presenting similar problems and in which at least some of the same benefits may be realized via the inventive concepts described herein.

[0043] Referring now to FIGS. 1-13, a combination outlet assembly **100** according to an exemplary embodiment of the present invention is shown in various views. The combination outlet assembly **100** has a compact package size including dual power outlets that are designed for interchangeable

use with different special purpose plug connectors in a reduced amount of space and at an economical manufacturing cost relative to more complicated conventional combination assemblies having more than two outlets (e.g. four, six, eight, etc.) in a larger package size. The dual outlets in the assembly **100** are different and distinguishable from one another to accept different plug connectors in a different manner as described in detail further below. The combination outlet assembly **100** may be ganged together with other combination outlet assemblies **100** for installation to a PDU as also described below to economically provide a PDU having any desired number of combination outlets using a small number of modular component parts.

[0044] The combination outlet assembly **100** includes a housing **102** that in an exemplary embodiment is a single piece integrally formed housing including the features shown and described below. Specifically, in a contemplated embodiment the housing **102** may be formed and fabricated in a single piece construction via a molded, heavy duty plastic material. As compared to combination outlets including multiple piece housings that must be separately manufactured and subsequently assembled to one another, the single piece housing is advantageous from the manufacturing perspective to lower costs, while also avoiding reliability issues of separately fabricated housing parts detaching from one another in use and handling when attached to a PDU.

[0045] In the example embodiment shown the single piece housing **102** is defined by a pair of longitudinal side walls **104**, **106** having respective first and second end edges, a pair of end walls **108**, **110** extending orthogonally to the pair of longitudinal side walls **104**, **106** and respectively interconnecting the first and second edges of the pair of longitudinal side walls **104**, **106**. A bottom wall **112** interconnects the pair of longitudinal side walls **104**, **106** and the pair of end walls **108**, **110**. The side walls **104**, **106**, end walls **108**, **110** and bottom wall **112** define a generally rectangular or box-like housing. As shown in FIG. 2, the longitudinal side walls **104**, **106** have an axial length dimension L extending in a direction perpendicular to the end walls **108**, **110** that is about twice as long as a width dimension W extending in direction perpendicular to the longitudinal side walls **104**, **106**.

[0046] As shown in FIGS. 1, 2, 7 and 8, at the respective end edges thereof the longitudinal wall **104** further includes integrally formed vertically extending projections **111** extending parallel to a height dimension H of the housing **102**. The longitudinal wall **106** includes integrally formed vertically extending grooves or slots **113** extending parallel to the height dimension H of the housing **102**. As shown in FIG. 2, the projections **111** include hooks at the distal ends thereof. The projections **111** and slots **113** serve as ganging features wherein when two housings **102** are arranged side-by-side they may be positively interlocked to one another with a dovetail engagement of the projections **111** and grooves **113** as shown in FIGS. 14 and 15. While exemplary locations, orientations and geometry of ganging features are shown in the form of the projections **111** and slots **113**, other locations, orientations and geometry is possible in alternative embodiments.

[0047] As shown in FIGS. 1, 2, 3, 5, 11 and 13 a first outlet core **114** is integrally formed in the housing **102** at an interior location to the walls **104**, **106**, **108** and **110** of the housing **102**. The first outlet core **114** extends upwardly from the bottom wall **112**. A second outlet core **116** is also integrally formed in the housing **102** at an interior location to the walls **104**, **106**, **108** and **110** of the housing **102**. The second outlet core **116** extends upwardly from the bottom wall **112** in spaced relation from the first outlet core **114** along the length dimension L of the housing **102**. An interior dividing wall **118** is formed in the housing **102** and extends between the outlet cores **114** and **116**. In the example shown, the dividing wall **118** extends perpendicularly to the pair of longitudinal side walls **104**, **106** and separates distinct regions on either side thereof wherein the core outlets **114**, **116** reside. In other contemplated embodiments, however, the dividing wall **118** could be considered optional and need not be included while still realizing at least some of the benefits of the present invention.

[0048] In the illustrated example, the dividing wall **118** is slightly off-centered in the lengthwise

dimension L of the single piece integrally formed housing **102**. That is, the dividing wall **118** is slightly closer to one of the pair of end walls **108**, **110** than to the other as shown in the top view of FIG. 2. Also, the outlet core **114** is slightly off-centered in the widthwise dimension W while the outlet core **116** is centered in the widthwise dimension W. That is, the outlet core **114** is positioned slightly closer to the longitudinal side wall **106** than to the side wall **104** of the housing **102** while the outlet core **116** is approximately equidistant from the longitudinal wall **104** and the longitudinal wall **106**. The off-centered outlet core **114** in the widthwise direction accommodates fastener openings **119** alongside the outlet core **114** and the longitudinal side wall **104**. The fastener openings **119** allow the housing **102** to be fastened to a support structure such as a chassis of a PDU using known fasteners such as screws that are received in the fastener openings **119** from above the housing **102**. Coupled with the interlocking ganging features described above, the fasteners securely fix the combination outlet assembly **100** in place. In another embodiment, fastener openings may be located at an alternative location and/or the outlet core **114** could be centered and aligned with the outlet core **116** if desired.

[0049] As shown in FIGS. 2, 3 and 5, the first and second outlet cores **114**, **116** respectively have a common outer shape and profile including a short end vertical wall **120** extending parallel to the dividing wall **118**, a pair of vertical walls **122**, **124** respectively extending at an obtuse but opposite angle to one another from the end wall **120** on either respective side of the vertical wall **120**. As such, the slope of the angled walls **122**, **124** is inverted on each side of the end wall **120**. The outer shape and profile also includes a pair of side vertical walls **126**, **128** extending parallel to the longitudinal side walls **104**, **106** from the end of each angled wall **122**, **124**, and a long end wall **130** extending parallel to the short end wall **120** and interconnecting the ends of the parallel side walls **126**, **128**. A rounded internal groove **132** is also integrally formed in the long wall **130** in a central portion thereof that extends with concave curvature toward the short end wall **120**. The vertical walls **120**, **122**, **124**, **126**, **128** and **130** of the outlet cores **114**, **116** arranged as shown and described may be recognized as having the shape and profile of an IEC C13 inlet/receptacle familiar to those in the art. In combination with the groove **132** the outlet cores **114**, **116** may be recognized as having the shape and profile of an IEC C15 inlet/receptacle also familiar to those in the art. While both the outlet cores **114**, **116** have the same outer shape and profile in the illustrated embodiment, in another embodiment the outlet cores **114**, **116** may be differently shaped and have a different profile from one another.

[0050] In the example shown, the outer shape and profile of the first and second outlet cores **114**, **116** further extend as mirror images of one another in the lengthwise dimension L. In other words, and as shown in top view in FIG. 2 the outer shape and profile of the outlet core **114** is oriented in an inverted or upside down position (i.e., in a 180° orientation relative to the core outlet core **116**) in the lengthwise dimension L. In the inverted arrangement, the short end wall **120** of each outlet core **114**, **116** respectively faces the dividing wall and the long end walls **130** face the respective end walls **108**, **110** of the housing **102**. The outlet cores **114**, **116** extend on opposing sides of the dividing wall **118** and the outlet core **114** extends slightly offset from the outlet core **116** in the widthwise dimension W. As a result, the outlet core **114** is shifted slightly to the left in FIG. 2 relative to the outlet core **116** and imparting an asymmetry in the housing **102** via slight staggering of the inverted outlet cores **114**, **116**. In other words, the inverted outlet cores **114**, **116** are slightly misaligned with respect to an axial centerline of the housing **102** in the lengthwise direction. In another embodiment, however, the outlet cores **114**, **116** need not necessarily be inverted or misaligned.

[0051] As shown in FIGS. 3 and 5, a respective receptacle space **134**, **136** surrounds each of the first and second outlet core **114**, **116** in the single piece integrally formed housing **102** via interior walls therein that are spaced from the outer shape and profile of each outlet core **114**, **116**. In the example shown, the space **134** that surrounds the outlet core **114** is shaped to complement the outer shape and profile of the outlet core **114**. That is, the internal walls of the housing **102** surrounding

the outlet core **114** include respective walls arranged complementary to but spaced from the outer walls **120, 122, 124, 126, 128** and **130** of the outlet core **114**. The space **134** is defined by an inner boundary corresponding to the outer perimeter of the outer walls **120, 122, 124, 126, 128** and **130** of the outlet core **114** and an outer boundary having a larger perimeter but matching the shape of the inner boundary. The peripheral space **134** extends between the inner and outer boundaries to surround the entire circumferential perimeter of the outlet core **114**.

[0052] Unlike the space **134**, the space **136** that surrounds the outlet core **116** does not match the outer shape and profile of the outlet core **116**. While the outlet core **116** has six walls **120, 122, 124, 126, 128** and **130** as shown, the housing internal walls surrounding the outlet core **116** include only four walls defining a generally rounded rectangular shape. As such, the space **136** has an inner boundary corresponding to the outer perimeter of the walls **120, 122, 124, 126, 128** and **130** of the outlet core **116** and an outer boundary that is nearly square. The outer boundary of the space **136** is therefore both larger than the inner boundary and differently shaped from the inner boundary. The area of the space **136** on the bottom wall **112** of the housing is considerably larger than the area of the space **134** as shown.

[0053] The receptacle space **134** surrounding the first outlet core **114** is compatible with a first power cord **200** (FIG. 4) having a first plug connector housing **202** that is complementary in outer shape and profile to the outlet core **114**. The first plug connector housing **202** may accordingly be received over the outlet core **114** within the space **134** provided. The first plug connector housing **202** also includes three terminal blades **204** that extend in spaced apart but parallel planes inside the plug connector housing **202**. The three terminal blades **204** correspond to a line terminal, a neutral terminal, and a ground terminal connecting to respective conductors in cable **206** of the power cord **200**. The terminal and housing configuration of the plug of the power cord **200** shown in FIG. 4 may be recognized as an IEC C14 plug connector. When engaged, the terminals **204** in the plug connector housing **202** pass through rectangular apertures **140** (FIG. 3) in the outlet core **114** where they engage respective terminals **150, 152, 154** (FIGS. 3 and 13) that are located inside the outlet core **114** beneath the apertures **140**.

[0054] As shown in FIG. 5, the space **136** surrounding the outlet core **116** in the housing **102**, being both larger and differently shaped than the space **134** surrounding the outlet core **114**, is compatible with the first plug connector housing **202** of the power cord **200** (FIG. 4) that is complementary in outer shape and profile to the outlet core **116**, and further is compatible with a second plug connector housing **222** of a second power cord **220** shown in FIG. 6. The plug connector housing **222** includes four walls arranged in a generally square shape and terminals **224** inside the four walls. The four walls of the plug connector housing **222** may be received over the outlet core **116** within the space **136** provided.

[0055] The second plug connector housing **222** also includes three terminal blades **224**, two of which extend in a generally coplanar relationship and third extending in a spaced apart but parallel plane to the other two of the terminal blades **224**. As such, each of the terminal blades **224** of the plug connector housing **222** inside the plug connector housing **222** extend at a 90° angle relative to the terminals **204** of the plug connector housing **202** of the power cord **200** (FIG. 4). Therefore, as shown in FIG. 4 the blade terminals **204** in the plug connector housing **202** extend at a common and generally vertical orientation, whereas the terminals **224** in the plug connector **222** as shown in FIG. 6 extend at a common and generally horizontal orientation. In alternative embodiments, one or more of the blade terminals in each plug connector housing may be oriented differently to another one of the blade terminals. By virtue of the different housing structure and/or the different terminal orientation such plug connectors are deemed to of different type in the context of the present invention.

[0056] The three terminal blades **224** in the plug connector housing **222** correspond to a line terminal, a neutral terminal, and a ground terminal connecting to respective conductors in cable **226** of the power cord **220**. The terminal and housing configuration of the power cord plug shown in

FIG. 6 may be recognized as an IEC C20 plug connector. When the power cord 220 is engaged to the outlet core 116, the terminals 224 in the plug connector housing 222 pass through respective horizontal portions of T-shaped apertures 160 (FIG. 5) in the outlet core 116 where they engage respective terminals 150, 152, 154 (FIGS. 5 and 13) that are located inside the outlet core 116 beneath the apertures 160. When the power cord 200 is engaged to the outlet core 116, the terminals 204 in the plug connector housing 202 pass through respective vertical portions of T-shaped apertures 160 in the outlet core 116 where they engage respective terminals 150, 152, 154 (FIGS. 5 and 13) that are located inside the outlet core 116. Therefore, by virtue of the outer shape and profile of the outlet core 216, the surrounding space 136, and the T-shaped apertures 160 in the core outlet core 116 both of the plug connector housing 202 and terminals 204 and the plug connector housing 222 and the terminals 224 may be interchangeably accepted by the outlet core 116 and engaged to the terminals 150, 152, 154 therein, whereas the outlet core 114 will accept the plug connector housing 202 and terminals 204 but reject the plug connector housing 222 and the terminals 224 due to interfering portions of the housing of the power cord 220.

[0057] In the illustrated embodiments, the outlet cores 114, 116 are respectively provided with the same sets of terminals 150, 152, 154. It is recognized, however, that the sets of terminals need not be the same in the outlet cores 114, 116 in another embodiment. Specifically, the outlet core 114 may be provided with simpler shaped terminals than those shown in FIG. 13 since the outlet core 114 includes the rectangular apertures 140 that would operate to reject a plug having incompatible terminals with the apertures 140. In other words, the terminals 150, 152, 154 that are configured to accept terminals of a plug in respectively different orientations are not required in the outlet core 114 because the apertures 140 will only accept plug terminals having a corresponding orientation. The benefits of the terminals 150, 152, 154 to accept different plug types in the outlet core 166 is only realized in the outlet core 116 having the T-shaped apertures 160. While exemplary terminals 150, 152, 154 are shown and described having capability to accept different plug types, other terminal configurations are possible and may be adopted in further and/or alternative embodiments.

[0058] It is also recognized that by virtue of the grooves 132 in each outlet core 114, 116, each of the outlet cores may also accept an IEC C16 plug that is similar to housing 202 of the power cord 200 and has similar terminals to the terminals 204, but further includes an internal protrusion that fits into the groove 132 in each outlet core. The outlet core 114 may therefore accept a C16 plug and a C14 plug but reject a C20 plug, while the outlet core 116 may accept a C14 plug, a C16 plug and a C20 plug. As such, the outlet core 114 may accept two different types of plugs while the outlet core 116 may accept three different types of plugs. The combination outlet assembly including only two outlet cores 114, 116 may therefore accept six combinations of mating plugs of different types. While exemplary plug types are described and illustrated having different housing structure and/or different terminal structure, such plug types are exemplary only and alternative types of plugs having plug connector housings of alternative geometry are possible having the same or different terminal structure of the IEC plug connectors described above in further and/or alternative embodiments.

[0059] As shown in FIG. 5, a pair of spaced apart projections 170, 172 extend upwardly from the bottom wall 112 of the housing 102 in the space 136 surrounding the outlet core. The pair of projections 170, 172 are located on the bottom wall 112 in spaced relation from the angled vertical walls 122, 124 of the outlet core 116 at a distance to respectively engage a portion of an exterior surface of the plug connector housing 202 (FIG. 4) when mated to the outlet core 116 or alternatively to engage an interior surface of the plug connector housing 222 (FIG. 6) when mated to the outlet core 116. In the example shown, the projection 170 is angularly oriented relative to the projection 172 on the bottom floor at about a 90° angle to contact and support adjacent portions of the plug connector housing 202 or 222 that is mated to the outlet core 116. The projections 170 and 172 that engage the plug connector housing 202 or 222 when received help to grip and hold the plug connector housing 202 or 222 in place and resist any tendency that otherwise may exist for the

plug connector housing to disengage from the outlet core **116**. The plug connector housing **202** in the complementary space **134** surrounding the outlet core **114** is less subject to being dislodged in a similar manner, although similar protrusions to the projections **170**, **172** could be employed in the space **134** as well if desired. The projections **170**, **172** are easily formed on the bottom wall **112** of the housing **102** with little additional material and negligible effect on the manufacturing cost of the housing **102**. The projections **170**, **172** are therefore more economical plug connector housings than much more elaborate housing features that utilize significantly greater amounts of housing material or require assembly of separately fabricated pieces to implement.

[0060] While an exemplary location and geometry has been described and illustrated for the projections **170**, **172** the projections may be located elsewhere and may have different geometry in another embodiment. Also, a greater or fewer number of projections of the same or different shape and geometry may be utilized for similar purposes to the projections **170**, **172** and to realize the benefits thereof to varying degrees.

[0061] As shown in FIGS. **1**, **2**, **5**, **7**, **8** and **11**, to further ensure that a mated plug reliably stays connected to the outlet core **116**, the end wall **108** of the single piece integrally formed housing **102** includes a deflectable latch portion **180**. The deflectable latch portion **180** is attached to the housing **102** at a lower end thereof, but otherwise is separated from the end wall **108** of the housing **102** on the vertical sides thereof, and an angled finger grip extends away from the space **136** on the distal upper end of the deflectable latch portion **180**. The latch portion **180** is formed with a latch opening **182** that accepts a latch protrusion (not shown) provided on a power cord in the plug connector housing **202** or **222**. The associated plug and latch protrusion can therefore be positively locked or latched in place in the desired orientation relative to the outlet core **116**.

[0062] A resilient spring element **184** (FIGS. **11** and **12**) is separately provided from the housing **102** and may be fabricated from metal in a contemplated embodiment. The spring element **184** in the example shown includes a relatively wide base portion **186** in the widthwise dimension of the housing **102** that is inserted in a slot in the housing end wall **108** beneath the deflectable latch portion **180**. The base portion **186** includes inwardly facing deflectable fingers in central portion thereof, and a relatively thin angled section **188** extending upwardly from an edge of the base portion **186**. The upstanding angled section **188** abuts the deflectable latch portion **180** when assembled to the housing **102**. The angled section **188** of the spring element **184** acts upon the deflectable latch portion **180** to apply an inwardly directed mechanical bias force to hold the deflectable latch portion **180** in a locked or latched position extending generally vertically and flush with the remainder of the end wall **108** of the housing **102**. As a mating plug is inserted into the outlet core **116** the latch protrusion thereof will deflect the latch portion **180** outwardly until the latch protrusion can be received in the latch opening **182**. When desired, a user may grasp or depress the upper end of the latch portion **180** and manually deflect it outwardly to release a latch protrusion and remove a connected plug from the outlet core **116** when desired. The lock protrusion in the power cord need not move relative to the power cord in order to engage or disengage the deflectable latch portion **180**.

[0063] A similar opening to the latch opening **182** is provided in the end wall **110** of the housing **102** in the example shown, but the end wall **110** in the illustrated embodiment does not include a deflectable latch portion to assist with locking and unlocking of a power cord. The end wall **110** can still interface with a lock protrusion of a power cord, but requires a lock protrusion in the power cord that can be selectively positioned relative to the power cord housing to secure and release the lock protrusion with the lock opening in the end wall **110**. The deflectable and non-deflectable latch openings in the housing **102** on the end walls **108**, **110** provides additional flexibility in the combination outlet assembly to be used with different types of latch protrusions on power cords.

[0064] Instead of providing different latching features on each side of the housing **102**, in further embodiments both of the housing end walls **108**, **110** may be provided with a deflectable latch

portion or a non-deflectable latch opening if desired. While the deflectable and non-deflectable latch features are illustrated on the end walls **106, 108** of the housing, in another embodiment the deflectable latch portion and the non-deflectable latch opening could be located on the longitudinal side walls **104, 106**. Of course, in some embodiments wherein latching of power cords is not desired or needed, the latch features described could be omitted in the housing construction.

[0065] The combination outlet assembly **100** further includes, as shown in FIGS. **7, 10** and **13**, conductor bus elements **190, 192, 194** interconnecting the respective terminals **150, 152, 154** associated with each of the outlet core **114** and the outlet core **116** on an exterior of the bottom wall **112**. Each of the three conductor bus elements **190, 192, 194** completes a circuit path of different axial length between respective pairs of the terminals **150, 152, 154**. The circuit path in each conductor bus element **190, 192, 194** connecting the terminals **150, 152, 154** is generally planar with a number of bends or angled transitions in each element **190, 192, 194**.

[0066] In the illustrated embodiment, the conductor bus element **190** is an asymmetrical J-shaped element having a long leg and a short leg extending parallel thereto and a perpendicular leg interconnecting ends of the long and short legs. The opposing ends of the conductor bus element **190** include sections of enlarged areas to complete mechanical and electrical connection to the terminals **154**. The conductor bus element **192** in the example shown is a generally symmetrical element having opposing parallel legs offset from one another with an angled section in between, and out of plane tabs at the distal ends thereof for connection to the terminals **152**. The conductor bus element **194** in the example shown is an asymmetrical element having an open rectangular shape with parallel distal ends for connection to the terminals **150**. Each conductor bus element **190, 192, 194** also includes out of plane fastener tabs to fix the elements **190, 192, 194** in the desired orientation in the assembly and to complete electrical connection to corresponding bus structure in the chassis of a PDU. The conductor bus elements **190, 192, 194** and sets of terminals in each outlet core **114, 116** are mechanically and electrically connected to corresponding bus conductors in the PDU to complete respective line connections, neutral connections, and ground connections for power distribution to the power outlets provided in the PDU.

[0067] As best shown in FIG. **10**, the conductor bus element **192** is nested partly between portions of the conductor bus element **194** and partly in the conductor bus element **190**. That is, portions of the conductor bus elements **190** and **194** surround the conductor bus element in a relatively compact arrangement. The bottom wall **112** of the housing **102** is formed with separating wall sections to prevent electrical shorting between the conductor bus elements **190, 192, 194**. The geometry and arrangement of the conductor bus elements **190, 192, 194** is exemplary only and alternative geometry and arrangement of conductor bus elements **190, 192, 194** may be employed in other embodiments.

[0068] In certain contemplated embodiments, the conductor bus elements **190, 192, 194** may be omitted in favor of connecting wires to establish electrical connections to external circuitry through the terminals **150, 152, 154** or in favor of a circuit board including circuitry to which the terminals **150, 152, 154** may be connected in a PDU. Variations and adaptations are possible in this regard to make the electrical connections in the combination outlet assembly **100** to line, neutral and ground circuits in a power system whether through a PDU or as a stand-alone outlet device mounted to another support structure (e.g., a wall, a cabinet, or other support structure).

[0069] Also in certain contemplated embodiments, less than the three conductor bus elements **190, 192, 194** shown may be provided. For example, only two the conductor bus elements shown may be provided to respectively interconnect the neutral terminal and the ground terminal of each outlet core **114, 116**, while the line connections may be made separately to each line terminal in the outlet cores **114, 116** to desirably facilitate switched outlet capability in the outlets provided. As such, and because the line terminals in each outlet core **114, 116** are not connected by a conductor bus in such an embodiment, they may be selectively turned on or off from via connection or disconnection to the same or different power inputs as desired. For example, the line terminals in each outlet core

114, 116 may be connected to a circuit board and controls to selectively energize or de-energize the outlets either independently or in combination in a known manner. Alternatively, switching elements may be provided that are not implemented through a circuit board if desired.

[0070] In the illustrated example wherein all three of the conductor bus elements **190, 192, 194** are provided, however, the outlets are connected to the same power input and desired power metering is facilitated in a simpler manner at reduced cost albeit with more basic functionality than the aforementioned switched power arrangement involving only two of the three conductor bus elements described.

[0071] As shown in FIGS. **14-16**, a number of combination outlet assemblies **100** may be attached to a PDU **300**. The PDU **300** includes an elongated chassis **302** having an opening **304** to receive the combination outlet assemblies **100** in a side-by-side manner with the housings **102** ganged together. In the example of FIG. **14** showing a small portion of the power distribution unit **300**, the opening **304** is large enough to receive three combination outlet assemblies **100** with the housings **102** ganged together. The end walls **108, 110** of the housings **102** when attached extend parallel to the longitudinal walls of the PDU **300** in the axial lengthwise dimension of the PDU **300** while the longitudinal side walls **104, 106** extend perpendicularly to the longitudinal axis of the PDU **300**. The inverted outlet cores **114, 116** in each housing **102** extend across the widthwise dimension of the PDU chassis.

[0072] Groups of three ganged combination outlet assemblies **100** are shown in FIG. **15** in spaced apart locations in the chassis **302** along the axial length of the PDU **300**. In FIG. **16** three groups of ganged combination outlet assemblies **100** are shown in the PDU **300** on opposing sides of a management module **306** and communication interface **308** including various different types of communication ports and sensor ports such as those described above. A power cord **310** is provided at one end of the PDU to establish an input power connection to the PDU **300**, with the outlets in the combination outlet assemblies **100** distributing power to electrical devices and equipment connected to the power outlets in the PDU **300**.

[0073] The six groups of three combination outlets **100** in the PDU **300** shown in FIG. **16** corresponds to a total of eighteen combination outlet assemblies **100** and thirty six total outlets (eighteen outlets having the outlet core **114** and eighteen outlets having the outlet core **116**) in the exemplary PDU **300**. Since each combination outlet assembly **100** can accommodate six combinations of different plug types, the PDU **300** having the eighteen outlets can collectively facilitate one hundred and eight combinations of different plug types (eighteen outlets times six combinations each) in a relatively compact package size. As such, the PDU **300** is less likely to disappoint purchasers that find the number of outlets to be too limited for the intended application, and also less likely to become obsolete due to changing needs over time. Further, the flexibility of the outlets provided to interchangeably connect to different power cord plug connectors accommodates changing needs or uncertainty in needs in particular PDU installations as well as more capably accommodates changing needs over time.

[0074] The management module **306** in the PDU **300** may include a display presenting power information and setup information to a PDU installer or data center overseer. The PDU **300** may include switches, sensors and other components to provide desired power management and metering functionality that can be accessed locally on the PDU via the management module **306** or communicated to or made accessible from the network interface **308**. While the PDU shows an exemplary arrangement of outlets via the combination outlet assemblies **100** provided relative to the management module **308**, other arrangements are possible in another embodiment. Also, while the PDU includes only combination outlets via the combination outlet assembly **100**, still other types of outlets could be provided in addition to the combination outlets in the combination outlet assembly **100**. Varying numbers of combination outlet assemblies **100** may be provided in different embodiments.

[0075] The combination outlet assembly **100** including the single piece housing **102** including the

features described avoids more complicated multi-piece housing components to provide a combination outlet. Specifically, separately provided adapter pieces fitted to the outlet cores to configure them to accept or reject certain types of plug connectors are obviated by the single piece construction described and illustrated herein. As such adapter pieces are eliminated, any possibility for them to be lost or mislaid, or inadvertently broken or detached is avoided together with reliability issues or negative experiences by purchasers and installers who are frustrated by such issues.

[0076] The combination outlet assembly **100** including single piece housings **102** can be provided in a modular form and easily be ganged together to scale a PDU to have as many combination outlets desired in an economical manner that generally avoids customization including custom fabricated housings and the like to provide different numbers of power outlets. Considerable variation in PDUs is therefore possible while using a small number of component parts to provide the combination outlet assembly **100**. Of course, while the single piece housing **102** in the combination outlet described has considerable benefits, in alternative embodiments the housing **102** may be fabricated from more than one housing piece if desired while still realizing some of the other benefits described. Additionally, combination outlets having more than two outlets are possible in alternative embodiments having single piece or multi-piece housing constructions. Variations and adaptations are possible in this regard.

[0077] FIGS. **17-19** illustrate an alternative power cord latch or locking assembly **400** that may be utilized with a combination outlet assembly **100** to reliably retain a power cord thereto. Unlike the lock or latching features described above in relation to deflectable and non-deflectable portions of the housing sidewalls in the combination outlet assembly **100**, the power cord latch or locking assembly **400** may be utilized with a power cord **402** that does not include a lock protrusion at all. The power cord **402** may include any of the plug connector types described above without a lock protrusion, and therefore may be a more economical power cord.

[0078] The latch or locking assembly **400** includes a receptacle insert **404** and a power cord clamp **406**. The insert **404** includes a planar rim **408** having a center opening therein with complementary shape to the outer shape and profile of the outlet cores **114**, **116** in the combination outlet assembly **100**. As such, the rim **408** may be inserted into the receptacle space **134** or **136** and be fitted around the outlet core **114** or **116** adjacent the bottom wall **112**. The rim **408** may abut the protrusions **170**, **172** in the bottom wall **112** of the housing **102** and therefore be gripped and retained in place in the housing **102** once installed.

[0079] A thin and rectangular locking tab **410** extends upwardly and generally perpendicularly from the rim **408**, and the locking tab **410** includes a lock protrusion **412** that may be received in the lock opening of the housing end wall **108** or **110** described above. The thin locking tab **410** extends along the interior wall of the outlet core **114** or **116** without obstructing a power cord plug connector in the receptacle space **134** or **136**. An elongated tether element **414** extends upwardly from the locking tab **410** and exterior to the receptacle space **134**, **136**. The tether element **414** includes a series of latch grooves **416** that may be gripped in an interlocking fashion to the power cord clamp **406**.

[0080] As shown in FIG. **19**, the power cord clamp **406** includes a rectangular collar **420** and a deflectable latch element **422** interior to the collar **420**. The collar **420** may receive the tether element **414** and the latch element **422** may be lockingly engaged to one of the latch grooves **416** at the desired elevation. The clamp **406** further includes a support **424** and a round power cord grip **426** having a central opening **428** through which a portion of the power cord **402** may be passed. The power cord grip **426** is deflectable to restrict the size of the opening **428**, and further includes a series of locking protrusions in the form of outwardly extending teeth **430** on a distal end thereof. When the distal end of the power cord grip **426** is deflected, it may be received in a latch housing **432** extending from the support **424** and lockingly engaged to a tooth **436** of a finger tab **438**.

[0081] In use, with the latch element **422** of the clamp **406** engaged to the tether element **414** and

with a portion of the power cord **402** in the clamp opening **428** the distal end of the power cord grip **426** can be deflected and received in the latch housing **432** by a desired amount to engage the tooth **436** of the finger tab **438** to one of the teeth **430** on the power cord grip **426**. As the power cord grip **426** is deflected, the opening **428** is decreased and clamps the portion of the power cord **402** therein. If desired the distal end of the power cord grip **426** can be passed entirely through the latch housing **432** via an opening **434** to restrict the opening **428** even further. The opening **434** can be adjusted in size as needed to be clamped around a portion of the power cord plug housing or around a portion of the power cord cable. The locking insert **404** and the clamp **406** when engaged therefore provide positive locking of a power cord that does not include a lock protrusion while still preventing the power cord from dislodging.

[0082] When desired, the finger tab **438** of the clamp **406** can be used to deflect the locking tooth **436** outwardly in order to release the distal end of the power cord grip **426** to enlarge the opening **428** to the degree required to remove the power cord **402**. The power cord **402** can therefore be removed while the power cord clamp **406** remains attached to the tether element **414** of the insert **404** and while the insert **404** remains in place in the housing **102**. The adjustable power cord clamp **406** can be universally used with power cord having plugs of different types. While exemplary shapes and geometries of locking insert **404** and power cord grip **426** are shown and described, alternative geometry could be utilized in other embodiments to realize otherwise similar locking features. The insert **404** and clamp **406** may be fabricated from plastic materials in contemplated embodiments at relatively low cost. The insert **404** and clamp **406** provide event further flexibility to the combination outlet assembly **100** to be used with power cords having integral locking features and power cords without integral locking features while ensuring that connections to the power outlets are reliably secured maintained.

[0083] While the latch or locking assembly **400** with the receptacle insert **404** and power cord clamp **406** is described in combination with the combination outlet assembly **100**, it is recognized that that latch or locking assembly **400** does not require the combination outlet assembly **100** and instead can be used apart from the combination outlet assembly **100** if desired. As such, the latch or locking assembly **400** may be used with power outlets other than those specifically described herein, whether or not configured as combination outlets that may be interchangeably connected to different power cords having different plug connector types. The rim **408** of the insert can be shaped to complement alternative outlet shapes to the outlet cores **114**, **116** and different versions of inserts having different rims **408** can be provided to provide similar locking benefits to various different types of outlets to provide power cord locking features to power cord features that do not have integral locking features.

[0084] The benefits of the inventive concepts herein are now believed to have been amply illustrated in relation to the exemplary embodiments disclosed.

[0085] An embodiment of a combination outlet assembly has been disclosed including a single piece integrally formed housing. The housing includes a pair of longitudinal side walls having respective first and second ends, a pair of end walls extending orthogonally to the pair of longitudinal side walls and respective interconnecting the first and second edges of the pair of longitudinal side walls, a bottom wall interconnecting the pair of longitudinal side walls and the pair of end walls, a first outlet core extending upwardly from the bottom wall, and a second outlet core extending upwardly from the bottom wall. The first and second outlet cores respectively have a similar outer shape and profile but differently shaped sets of three terminal apertures, and three terminals associated with each respective set of three terminal apertures in the first outlet core and the second outlet core.

[0086] Optionally, the single piece integrally formed housing may further include a dividing wall extending between the first and second outlet cores. The dividing wall may be off-centered in the single piece integrally formed housing. The outer shape and profile of the first and second outlet cores may respectively extend as mirror images of one another on opposing sides of the dividing

wall, and the first outlet core may be misaligned with the second outlet core.

[0087] As further options, at least two conductor bus elements may extend on an exterior of the bottom wall, the at least two conductor bus elements interconnecting respective first and second terminals associated with the first outlet core and the second outlet core. The at least two conductor bus elements may complete a circuit path of different axial length between respective ones of the first and second terminals associated with the first outlet core and the second outlet core. The at least two conductor bus elements may include three conductor bus elements, and a portion of one of the conductor bus elements may be nested between portions of the other conductor bus elements.

[0088] As additional options, a respective space surrounds each of the first and second outlet core in the single piece integrally formed housing, with the respective space that surrounds the first outlet core being shaped to complement the outer shape and profile and the respective space that surrounds the second outlet core being shaped to mismatch the outer shape and profile. The respective space surrounding the first outlet core may accept a first housing of a first plug connector type but reject a second housing of a second plug connector type, wherein the second housing of the second plug connector type is differently shaped from the first housing of the first plug connector type, and wherein the respective space surrounding the second outlet core may accept the first housing of the first connector type and also accept the second housing of the second connector type. The first plug connector type may include three terminal blades extending at a common first angular orientation inside the first housing, and the second plug connector type may include three terminal blades extending at a second angular orientation that is 90° from the first angular orientation. The shaped sets of three terminal apertures of the second outlet core may accept each of the three terminal blades of the first plug connector type and also may accept each of the three terminal blades of the second plug connector type. A pair of spaced apart projections may extend upwardly in the bottom wall in the space surrounding the second outlet core, with the pair of projections located on the bottom wall to engage an exterior surface of the first housing of the first plug connector type and also to engage an interior surface of the second housing of the second plug connector type. The first one of the pair of spaced apart projections may be angularly oriented relative to the second one of the pair of spaced apart projections on the bottom floor. The first one of the pair of spaced apart projections may be angularly oriented about 90° relative to the second one of the pair of spaced apart projections on the bottom floor.

[0089] Also optionally, one of the pair of end walls of the single piece integrally formed housing may include a deflectable latch portion including a latch opening. A spring may element acting upon the deflectable latch portion. Furthermore, one of the pair of end walls include may include a latch opening, and the combination outlet assembly may further include a separately fabricated latch insert having a latch protrusion configured to be received in the latch opening. The insert may further include an elongated a tether section including a series of latch grooves, and a power cord clamp may be attached to the tether section via one of the series of latch grooves, with the power cord clamp including a power cord grip including an opening being adjustably secured around a portion of a power cord.

[0090] The combination outlet assembly may optionally be provided in combination with a power distribution unit having a chassis and a management module, and the combination outlet assembly may be fastened to the chassis. A plurality of combination outlet assemblies may be ganged side-by-side in the power distribution unit.

[0091] This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include

equivalent structural elements with insubstantial differences from the literal languages of the claims.

Claims

- 1.** An electrical outlet assembly, comprising: a molded housing including: side walls; end walls extending between the side walls, a bottom wall interconnecting the side walls and the end walls; and an outlet core extending upwardly from the bottom wall into a space defined between the side and end walls, a first end wall of the end walls including a latch portion that is deflectable relative to the space to selectively secure an electrical plug that is engaged with the outlet core; and a biasing element attached to the molded housing to bias the latch portion toward the outlet core.
- 2.** The electrical outlet assembly of claim 1, wherein the latch portion includes a latch opening to selectively retain a latch protrusion of the electrical plug, to secure the electrical plug within the molded housing.
- 3.** The electrical outlet assembly of claim 1, wherein the biasing element is removably secured within a slot defined by the first end wall.
- 4.** The electrical outlet assembly of claim 3, wherein the biasing element has a base portion received within the slot and an angled portion extending away from the base portion toward the outlet core.
- 5.** The electrical outlet assembly of claim 4, wherein the base portion defines a width along the slot that is wider than a width of the angled portion.
- 6.** The electrical outlet assembly of claim 5, wherein the biasing element includes one or more fingers that extend from the base portion to secured the biasing element within the slot.
- 7.** The electrical outlet assembly of claim 1, wherein the latch portion is defined by a cantilevered portion of the first end wall; and wherein the biasing element includes a leaf spring body that extends along the latch portion.
- 8.** The electrical outlet assembly of claim 1, wherein the outlet core is a first outlet core and the molded housing includes a dividing wall extending between the first outlet core and a second outlet core; and wherein the dividing wall is off-centered in the molded housing.
- 9.** The electrical outlet assembly of claim 8, wherein the first outlet core is offset from the second outlet core with respect to an axial centerline of the molded housing.
- 10.** The electrical outlet assembly of claim 1, wherein the latch portion extends on a first side of the outlet core; and wherein the molded housing further includes projections extending from the bottom wall into the space, on a second side of the outlet core opposite the first side, to further secure the electrical plug.
- 11.** An electrical outlet assembly, comprising: a monolithic housing that includes an outlet core, and walls that define a space around the outlet core to receive an electrical plug, a first wall of the walls including a cantilevered latch portion that is movable relative to the space and the outlet core to selectively retain an electrical plug; and a biasing element removably secured to the monolithic housing to contact an exterior side of the cantilevered latch portion, to bias the cantilevered latch portion toward the outlet core.
- 12.** The electrical outlet assembly of claim 11, wherein the monolithic housing further includes projections extending into the space, on an opposite side of the outlet core from the cantilevered latch portion.
- 13.** The electrical outlet assembly of claim 12, wherein the projections and the outlet core extend monolithically from a bottom wall of the walls.
- 14.** The electrical outlet assembly of claim 11, wherein the biasing element has a base portion and an angled portion extending away from the base portion.
- 15.** The electrical outlet assembly of claim 14, wherein the base portion defines a width than is wider than a width of the angled portion; and wherein the base portion is secured within a slot

defined on the exterior of the single-piece housing.

16. The electrical outlet assembly of claim 14, wherein the angled portion abuts the cantilevered latch portion to bias the cantilevered latch portion towards the outlet core.

17. The electrical outlet assembly of claim 16, wherein the cantilevered latch portion includes a latch opening to selectively retain a latch protrusion of the electrical plug.

18. A method of manufacturing an electrical outlet assembly, the method comprising: molding a housing that includes an outlet core, and walls that define a space around the outlet core to receive an electrical plug, with a first wall of the walls including a cantilevered latch portion that is movable relative to the space and the outlet core to retain an electrical plug; and securing a biasing element to the molded housing to contact an exterior side of the cantilevered latch portion to bias the cantilevered latch portion toward the outlet core.

19. The method of claim 18, wherein the biasing element is secured within a slot defined in the molded housing to the outside of the space.

20. The method of claim 18, wherein the cantilevered latch portion extends to a first side of the outlet core; and wherein the molded housing further includes projections extending into the space, to a second side of the outlet core.
