

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250256065

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

BACICH; Steven R. et al.

APPARATUS AND METHOD FOR EVERTING CATHETER FOR UTERINE ACCESS FOR BIOPSY AND CYTOLOGY

Abstract

An everting balloon system is disclosed that can be used for biopsy within a body of a patient or animal. The everting balloon system can be used to access a bodily cavity or vessel for tissue specimen collection at specific bodily locations. The everting catheter system described simplifies the process of tissue biopsy.

Inventors: BACICH; Steven R. (Half Moon Bay, CA), YUREK; Matthew Thomas (San Diego, CA), VIDYARTHI; Piush (San Rafael, CA)

Applicant: CrossBay Medical, Inc. (San Diego, CA)

Family ID: 1000008560433

Assignee: CrossBay Medical, Inc. (San Diego, CA)

Appl. No.: 19/193726

Filed: April 29, 2025

Related U.S. Application Data

parent US continuation 17207239 20210319 parent-grant-document US 12311123 child US 19193726

parent US continuation 16791768 20200214 parent-grant-document US 10967149 child US 17207239

parent US continuation 16377161 20190406 parent-grant-document US 10576248 child US 16791768

us-provisional-application US 62702321 20180723

Publication Classification

Int. Cl.: A61M25/01 (20060101); **A61B10/02** (20060101); **A61B17/34** (20060101); **A61B17/42** (20060101); **A61M25/10** (20130101)

U.S. Cl.:

CPC A61M25/0119 (20130101); **A61B10/0291** (20130101); **A61M25/10** (20130101); A61B2010/0208 (20130101); A61B10/0275 (20130101); A61B2017/3435 (20130101); A61B2017/4225 (20130101); A61M2025/1068 (20130101); A61M2210/1433 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 17/207,239, filed Mar. 19, 2021, which is a continuation of U.S. patent application Ser. No. 16/791,768, filed Feb. 14, 2020, issued as U.S. Pat. No. 10,967,149, now abandoned, which is a continuation of U.S. patent application Ser. No. 16/377,161, filed Apr. 6, 2019, issued as U.S. Pat. No. 10,576,248, which claims priority to U.S. Provisional Application No. 62/702,321, filed Jul. 23, 2018, all of which are incorporated by reference herein in their entireties.

BACKGROUND

[0002] This application has particular utility for everting catheters that are characterized with an inner catheter, outer catheter, and everting membrane that is connected to both catheters. The inner catheter may contain an inner lumen to pass fluid or media, drugs or therapeutic agents, instruments or devices such as IUD's, endoscopes, and other catheters.

[0003] For physicians and medical professionals, accessing systems for vessels and bodily cavities in patients have typically used various guidewire and catheter technologies or everting catheters. Everting catheters utilize a traversing action in which a balloon is inverted and with the influence of hydraulic pressure created by a compressible or incompressible fluid or media, rolls inside out or everts with a propulsion force through the vessel. Everting balloons have been referred to as rolling or outrolling balloons, evaginating membranes, toposcopic catheters, or linear everting catheters such as those in U.S. Pat. Nos. 5,364,345; 5,372,247; 5,458,573; 5,472,419; 5,630,797; 5,902,286; 5,993,427; 6,039,721; 3,421,509; and 3,911,927; all of which are incorporated herein by reference in their entireties. These are categorized as everting balloons and are for traversing vessels, cavities, tubes, or ducts in a frictionless manner. In other words, an everting balloon can traverse a tube without imparting any shear forces on the wall being traversed. Because of this action and lack of shear forces, resultant trauma can be reduced and the risk of perforation reduced. In addition as a result of the mechanism of travel through a vessel, material and substances in the proximal portion of the tube or vessel are not pushed or advanced forward to a more distal portion of the tube or vessel.

[0004] In addition, as the everting catheter deploys inside out, uncontaminated or untouched balloon material is placed inside the vessel wall. In the inverted or undeployed state, the balloon is housed inside the catheter body and cannot come into contact with the patient or physician. As the balloon is pressurized and everted, the balloon material rolls inside out without contacting any element outside of the vessel. Another advantage of an everting balloon catheter is that the method of access is more comfortable for the patient since the hydraulic forces “pull” the balloon membrane through the vessel or duct as opposed to a standard catheter that needs to be “pushed” into and through the vessel or duct.

[0005] Everting catheters have been described as dilatation catheters. Representative examples of

dilating everting catheters include U.S. Pat. Nos. 5,364,345 and 4,863,440, both of which are incorporated by reference herein in their entireties.

[0006] Everting catheters have also been described with additional elements such as a handle for controlling instruments within an everting catheter. A representative example is U.S. Pat. No. 5,346,498 which is incorporated by reference herein in its entirety. Everting balloon catheters can be constructed with an inner catheter with an internal lumen or through-lumen (or thru-lumen). The through-lumen can be used for the passage of instruments, media, materials, therapeutic agents, endoscope, guidewires, or other instruments or devices. Representative samples of everting catheters with through-lumens are in U.S. Pat. Nos. 5,374,247 and 5,458,573. In addition, everting catheters have been described with waists or a narrowing of the balloon diameter, such as in U.S. Pat. No. 5,074,845, which is incorporated by reference herein in its entirety.

SUMMARY OF THE INVENTION

[0007] More specialized everting catheter systems have specific instruments or tools built within the catheter system. Examples of such tools or instruments are biopsy devices, cytology devices, drug delivery mechanisms, endoscopes, IUD's or other tools to be delivered into a bodily cavity, a bodily space, a potential bodily space that is created by the everting balloon mechanism, or a bodily vessel. There are several advantages to having the instrument built into the everting catheter system. The everting balloon can be used to pull the instrument into the bodily cavity without requiring the physician or operator to push the instrument into place. This is useful for tortuous or tight passageways or any pathways in which the everting balloon works to protect the body passageway from the distal end profile of the instrument while pulling the instrument into the desired location. The biopsy device is fixed to the everting catheter system and automatically extends beyond the distal end of the everting balloon by being pulled by the everting balloon into the bodily lumen, or for endometrial biopsy in the uterine cavity. During the eversion process, the biopsy device is shielded from the body tissue until it extends beyond the distal end of the everting balloon. This is particularly useful in uterine biopsy since vaginal, endocervical, or other more proximal tissue is not picked up or contaminated into biopsy device. Providing the biopsy device at a specific distance in the everting catheter system can provide the physician the ability to direct the biopsy to a specific location. Other embodiments described herein illustrate how a biopsy can be performed in a particular location in the bodily lumen or cavity. As an example, some embodiments can perform a biopsy specifically on the anterior portion of a lumen to provide the physician more directed information on the status of the patient. Other examples for locations include posterior, lateral, contralateral, multiple locations, or the progression of disease or diagnosis from the proximal portions of a bodily lumen versus more distal portions. The biopsy can be provided by an aspiration system, cytology, tissue shaving, tissue collection, bodily fluid or materials collection, or providing a diagnostic tool within the body to indicate pH, temperature, pressure, or the presence of certain chemicals, materials, bile, blood, or other bodily materials. Once the tissue or cell biopsy is performed in the body, the everting catheter system can be removed and the everting catheter can be re-everted to retrieve the collected tissue specimen.

[0008] One embodiment of an everting catheter for performing a biopsy procedure is an aspiration mechanism or additional derivations built into the distal end of the inner catheter. The additional derivations include configurations that perform specific tissue removal processes for a desired tissue specimen type.

[0009] Additional embodiments include aspiration mechanisms that circumscribe larger areas in the bodily cavity for more wide spread tissue collection. Another embodiment includes automatic rotation of the inner catheter during the eversion and inversion step for greater area of tissue collection.

[0010] Another improvement performs the aspiration step automatically upon complete eversion.

[0011] Further improvements include mechanisms for performing aspiration in a one-handed manner or by activating the aspiration source with one button.

[0012] Another example is an everting catheter for performing biopsy is a cytology or tissue brush built within the distal end of the inner catheter. One embodiment describes a cytology or tissue brush that works with the everting balloon to trap tissue within the bristles of the brush during the inversion process.

[0013] Both of the examples of biopsy above demonstrate an everting catheter system during the inversion or retraction process that can perform biopsy at a specific location within the body without exposing the biopsy mechanism to the proximal or non-desired portion of a bodily passageway. This can be advantageous in situations where a location-specific, directed, or non-contaminated tissue specimen is desired.

[0014] Another embodiment of an everting catheter for performing biopsy is an instrument that performs tissue shaving and removal. Another embodiment for shaving and collecting tissues includes a mechanism designed to sweep a larger area for tissue collection within the desired location in the body.

[0015] Another embodiment of an everting catheter includes an everting balloon membrane surface that is designed specifically to pick up and collect tissue or cells in a location in the body. The everting membrane contains an external surface that has protruding hooks, latches, barbs, or bristles that collect tissue or cells when the everting membrane is unrolled and exposed in a specific area. Another embodiment contains a material on the exterior surface of the everting membrane with micro-channels or pores that are pressed against tissue upon eversion and pick up cellular material. Upon inversion, the tissue collection area is rolled into the everting membrane where it is contained and protected from contamination from other areas in the bodily passageway. Once the everting catheter system is removed from the body, the everting catheter can be re-everted to expose the tissue collection area for tissue specimen retrieval. In one configuration, the tissue collection area can be in the distal end of the everting membrane at the full eversion position. Other configurations can have tissue collection area of the membrane near or more proximal to the distal end of the everting membrane. Another configuration can have multiple tissue collection areas by radial segments or stripes to biopsy different locations of a bodily passageway which may facilitate the extent or proliferation of a disease state. Yet further, the tissue collection areas can be placed in anterior and posterior locations of an everting membrane to define specific locations of studied cells or tissue.

[0016] Another embodiment for specifically collecting bodily fluid within a specific location in the body has an everting membrane lined on the exterior surface with a porous or fluid receptive membrane or material for fluid collection. Upon eversion, the fluid collecting areas of the everting membrane would be in contact with a specific bodily location within the passageway or body cavity.

[0017] Another embodiment has an everting balloon membrane with a diagnosing material on the external surface. The diagnosing material can be designed to determine pH, lactate, hormonal content, medication content, urine, fecal, blood, lymphatic fluid, bile, mucus, infection or pus, edema, or other detectable bodily fluid or by-product. The diagnosing material can be placed on the external surface of the everting membrane as a test strip. Other versions of a test strip can detect and report temperature exposure, amount of pressure exerted as in pressure-sensitive test strips, or interior surface morphology of tissue within a bodily vessel.

[0018] Another embodiment can include a through-lumen within the inner catheter for irrigation or lavage of tissue to facilitate cellular or specimen collection. Adding irrigation can facilitate the collection of cells such as obtaining endometrial cells for determining endometrial receptivity for in vitro fertilization procedures.

[0019] Another embodiment can include a tissue agitator on the everting membrane to facilitate tissue or cellular collection. Another embodiment has a tissue agitator on the inner catheter of the biopsy device that performs the function of agitation automatically upon eversion or inversion. The physician or operator can manually advance or retract, or rotate, the entire everting catheter system

to facilitate tissue agitation to increase the amount of tissue for specimen collection.

[0020] The device can be used for atrophic endometrium or post-menopausal women. The device can include a tissue shaver for removing and collecting thin layers of tissue within the uterine cavity.

[0021] The tissue shaver can have both external and internal collection apparatus with and without internal aspiration.

[0022] The tissue shaver can include an internal coring apparatus.

[0023] The tissue shaver can include a cellular collection and filtration system that can include an irrigation source for the uterine cavity.

[0024] A method for retrieving a tissue sample from a uterus is disclosed. The method can include inserting a distal end of an elongated element into the uterus, positioning the tissue sample in the elongated element, and closing the cover over the opening. The elongated element can have a receiving volume, such as a reservoir or a lumen of the elongated element, to receive the tissue sample. The receiving volume can have an opening and a cover closeable over the opening. The opening can have or be a port on a lateral side of the elongated element.

[0025] The method can include, after closing the cover, translating the receiving volume out of the uterus, through the cervix, and through the vagina. The cover can be kept or remain closed while the receiving volume passes out of the uterus, through the cervix, and through the vagina. The translating of the receiving volume can include translating the elongated element. The translating of the receiving volume can include translating the elongated element concurrently together with the receiving volume. The cover can have or be an everting member. The translating of the receiving volume can include inverting or everting the cover. Closing of the cover can include inverting or everting the cover (e.g., the everting member, such as a membrane) over the opening.

[0026] The method can include separating the tissue sample from tissue adjacent to the tissue sample in the uterus. The opening can have or be a port on a lateral side of the elongated element.

[0027] The method can include taking a biopsy of the uterus resulting in separating the tissue sample from the uterus. The taking of the biopsy can include the positioning of the tissue sample.

[0028] The method can include separating with a wire the tissue sample from surrounding tissue, wherein the wire is at least partially in the elongated element. The positioning of the tissue can include applying suction across the opening. The suction can pull the tissue sample into the lateral port and into the lumen of the elongated element.

[0029] A method for retrieving a tissue sample from a uterus is disclosed that can include inserting a distal end of an elongated element into the uterus. positioning the tissue sample in the elongated element, and covering the opening. The elongated element can have a closed distal terminal end and a receiving volume, such as the lumen or a reservoir, to receive the tissue sample. The receiving volume can have an opening, such as one or more lateral ports on the elongated element.

[0030] The everting member can be attached to the elongated element. The everting member can have a first retracted configuration and a second extended configuration. In the first configuration, the distal terminal end of the everting member can be proximal to the opening. In the second configuration, the distal terminal end of the everting member can be distal to the opening. The covering of the opening can include moving the everting member from the first configuration to the second configuration. The entire everting element can be radially outside of the elongated element in the first configuration and the second configuration

[0031] An apparatus for separation of a tissue from a remote position is disclosed. The apparatus can have an elongated element and an everting membrane. The elongated element can have a lumen and a distal tip. The distal tip can have a first lateral port in communication with the lumen. The distal terminal end of the elongated element, such as the distal facing surface, can be closed or otherwise have no ports or fenestrations.

[0032] The everting membrane can be radially outside of the elongated element. The everting membrane can have a first proximal configuration and a second distal configuration. In the first

configuration, the distal terminal end of the everting membrane can be proximal to the lateral port. In the second configuration, the everting membrane can create a fluid-tight seal, cover, obstruct or otherwise block the lateral port.

[0033] The apparatus can have a suction source in fluid communication with the lumen. The apparatus can have an irrigation source connected to the lumen. The lumen can have an irrigation channel. The irrigation source can be connected to the irrigation channel.

[0034] The apparatus can have a cutting wire extending through the lumen. The wire can have a longitudinal axis and a first protrusion at a distal end of the cutting wire. The first protrusion can extend laterally away from the longitudinal axis. The wire can have a first configuration where the first protrusion is fully inside of the lumen, and a second configuration where the first protrusion extends laterally out of the first lateral port. The cutting wire can be configured to rotate about the longitudinal axis. The cutting wire can change from the first configuration to the second configuration during the rotation about the longitudinal axis.

[0035] The apparatus can have an everting member radially outside of the elongated element.

[0036] The distal tip of the elongated element can have a second lateral port. The cutting wire can have a second protrusion. When the wire is in the first configuration, the second protrusion can be fully inside of the lumen. When the wire is in the second configuration, the second protrusion can extend laterally out of the second lateral port.

[0037] The wire can have a distal terminal tip. The distal terminal tip can be in contact with the inside surface of the lumen. Pressing the wire longitudinally can press the distal terminal tip against the inside surface of the lumen. The wire can then deform, bias, or translate (e.g., with or without deformation) into the second configuration.

[0038] The first and/or second protrusions can have V shapes.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0039] FIGS. 1A to 1F illustrate of an everting catheter for performing a biopsy procedure with an aspiration mechanism.

[0040] FIGS. 2A to 2F illustrate in both side views and top views additional derivations built into the distal end of the inner catheter.

[0041] FIGS. 3A and 3F illustrate in both side views and top views aspiration mechanisms that expand or circumscribe a larger area in the bodily cavity for more wide spread tissue collection once the biopsy device exits the distal end of the everting membrane.

[0042] FIG. 4 illustrates an automatic rotation of the inner catheter during the eversion and inversion step for greater area of tissue collection.

[0043] FIGS. 5A to 5C illustrate another improvement that performs the aspiration step automatically following eversion.

[0044] FIGS. 6A to 6C illustrate further improvements include mechanisms for performing aspiration in a one-handed manner.

[0045] FIGS. 7A and 7B illustrate other examples of an everting catheter for performing biopsy that contains a cytology brush built within the distal end of the inner catheter.

[0046] FIGS. 8A to 8D illustrate everting catheters for performing biopsy that contain a cytology brush built within the distal end of the inner catheter whereby the cytology brush works with the everting balloon as a system to trap tissue within the bristles of the brush during the inversion process.

[0047] FIGS. 9A to 9D illustrate everting catheters for performing biopsy with an instrument that performs tissue shaving and removal.

[0048] FIGS. 10A and 10B illustrate an everting catheter for performing biopsy with an instrument

that performs tissue shaving and removal and a mechanism designed to sweep a larger area for tissue collection within the desired location in the body.

[0049] FIGS. **11A** to **11D** illustrate in cross-sectional views an everting catheter with an everting balloon membrane surface with protruding hooks, latches, barbs, or bristles to pick up and collect tissue or cells in a location in the body.

[0050] FIG. **12** illustrates in a cross-sectional view an everting balloon catheter with a material on the exterior surface of the distal end of the everting membrane with micro-channels or pores that are pressed against tissue upon eversion to pick up cellular material.

[0051] FIG. **13** illustrates in a cross-sectional view an everting balloon catheter with a material on the exterior surface that is near or more proximal the distal end of the everting membrane with micro-channels or pores that are pressed against tissue upon eversion to pick up cellular material.

[0052] FIG. **14** illustrates in a cross-sectional view an everting balloon catheter with a material on the exterior surface of the everting membrane with multiple tissue collection areas by radial segments or stripes to biopsy different locations of a bodily passageway which may facilitate the extent or proliferation of a disease state.

[0053] FIGS. **15A** to **15E** illustrate an everting balloon catheter with a material on the exterior surface of the everting membrane with multiple tissue collection areas placed on anterior and posterior locations of an everting membrane to define specific locations of studied cells or tissue in a body passageway.

[0054] FIGS. **16A** and **16D** illustrate an everting balloon catheter with a material for collecting bodily fluid within a specific location in the body whereby the everting membrane lined on the exterior surface with a porous or fluid receptive membrane or material for fluid collection for bodily fluid collection at a specific bodily location within the passageway or body cavity.

[0055] FIGS. **17A** and **17B** illustrate an everting balloon catheter with an everting balloon membrane with a diagnosing material on the external surface for determining pH, lactate, hormonal content, medication content, urine, fecal, blood, lymphatic fluid, bile, mucus, infection or pus, edema, or other detectable bodily fluid or by-product.

[0056] FIG. **18** illustrates an everting balloon catheter with an everting balloon membrane with a diagnosing material on the external surface that can detect and report temperature exposure, amount of pressure exerted as in pressure-sensitive test strips, or interior surface morphology of tissue within a bodily vessel.

[0057] FIG. **19** illustrates a biopsy everting catheter system that includes a through-lumen within the inner catheter for irrigation or lavage of tissue to facilitate cellular or specimen collection.

[0058] FIG. **20** illustrates in a cross-sectional view a biopsy everting catheter system with a tissue agitator on the everting membrane to facilitate tissue or cellular collection.

[0059] FIG. **21** illustrates a biopsy everting catheter system with a tissue agitator on the inner catheter of the biopsy device that performs the function of agitation automatically upon eversion or inversion.

[0060] FIG. **22** illustrates a biopsy everting catheter system with a handle for the manual advancement or retraction, or rotation, the entire everting catheter system to facilitate tissue agitation to increase the amount of tissue for specimen collection.

[0061] FIGS. **23A** to **23C** illustrate a tissue shaver for removing and collecting thin layers of tissue within the uterine cavity that can be used for atrophic endometrium or post-menopausal women.

[0062] FIG. **24** illustrates in cross section a tissue shaver with internal cutting apparatus with internal aspiration.

[0063] FIG. **25** illustrates a tissue shaver that can include an internal coring apparatus.

[0064] FIGS. **26A** and **26B** illustrate in cross section a tissue collector that can include a mechanism for cellular collection and sampling.

DETAILED DESCRIPTION

[0065] An everting balloon system (also referred to as an everting catheter system) that can be used

to traverse a vessel, such as the cervical canal for performing a biopsy procedure is disclosed. The everting balloon system can be used to access the uterine cavity via the cervix. The cervical canal is a single lumen vessel that can stretch or dilate. The everting catheter system can also traverse other locations in the body of a patient or animal for the purposes of tissue collection.

[0066] FIGS. 1A to 1F illustrate of an everting catheter for performing a biopsy procedure with an aspiration mechanism. FIG. 1A shows a biopsy device contained in an everting catheter system **10** in the inverted membrane position. Everting membrane and biopsy device (not visible in this figure) is contained within outer catheter **18** with acorn tip **10** at the distal end. Acorn tip **19** has an opening at the distal end (not visible). On the proximal end of outer catheter **18** there is a t-fitting or y-fitting **17** which contains an x-ring gasket (not visible). Inflation tubing and stopcock **15** supplies hydraulic energy to the everting catheter system. Hydraulic energy can be supplied by saline, air, a combination of saline and air, or gases such as CO₂, contrast media, culture media, and other fluids. Inner catheter **16** is translatable within the outer tubing **18** to advance and retract the everting membrane (not visible). On the proximal end of the inner catheter **16** there is a proximal hub **20** that is designed to connect to an aspiration source such as syringe **21** with syringe plunger **22**. Other aspiration sources can be wall vacuum, a portable vacuum source, a syringe motor system, and other manually driven inflation devices that are driven by ratchets and screw plungers.

[0067] FIG. 1B shows the distal end of the biopsy device **30** in the fully everted position or when the everting membrane (not visible in this figure) is fully everted. Biopsy device **30** has rounded distal end **32** and side hole **31**. Additional side holes **31** are possible including an opening at the distal end of the device, or combinations of both side holes and distal end holes. In operation when biopsy device **30** is in a body cavity such as the uterine cavity, an aspiration source can pull tissue, media, cellular material, and other bodily fluids into side hole **31**. When used in conjunction with an irrigation source or lavage, side hole **31** can be used to collect both bodily materials and irrigation fluids. Side hole **31** can be used to deliver other fluids into a bodily cavity such as contrast media, echogenic fluids, and medications or therapeutic fluids.

[0068] FIG. 1C shows the proximal end of the biopsy device with everting catheter **10** with outer catheter **18** attached to y-fitting **17** and inflation tubing and stopcock **15**. The inner catheter (not visible) can be in the fully everted position and is contained within the outer tubing **18**. Proximal hub **20** can be connected to a syringe **21** with plunger **22** in the retracted position by the user to provide negative pressure or an aspiration source.

[0069] FIG. 1D shows the distal end of the outer catheter **18** and acorn tip **19** with everting membrane **25** in the initial stages of eversion advancing through the distal end opening in acorn tip **19**. The everting membrane **25** can respond to hydraulic energy to roll inside out. The advancement of the everting membrane **25** can be performed by the user translating the inner catheter (not visible) or automatically in response to the hydraulic energy.

[0070] FIG. 1E shows the continuation of the eversion process with everting membrane **25** advanced further beyond the acorn tip **19**. At this point in the eversion process, the distal end of the biopsy device **30** and distal rounded tip **32** can protrude from the end of the everting membrane **25**. During a uterine endometrial biopsy, the everting membrane **25** can advance 1 cm to 5 cm before the biopsy device **30** protrudes from the everting membrane **25** to approximate the length of the endocervical canal. Other biopsy devices can advance a distance of 2 cm to 4 cm, or 3 cm before the biopsy device protrudes from the distal end of the everting membrane. Other biopsy devices can be made with translatable or re-positionable outer tubing (not shown) to modulate the distance the everting membrane travels in the endocervical canal prior to the biopsy device protrudes from the distal end of the everting membrane.

[0071] FIG. 1F shows the everting membrane **25** in the fully everted state and extending beyond the acorn tip **19**. Biopsy device **30** is seen with side hole **31** and rounded distal end **32**. The biopsy device is flexible and dimensioned to 1 mm to 4 mm in diameter, or 2 mm to 3 mm, and is made from Pebax, polyurethane, polypropylene, Teflon, nylon, or other biocompatible material. The

everting membrane is dimensioned to be 1 mm to 5 mm in diameter for the endocervical canal, or 2 mm to 4 mm, or 3 mm, with a wall thickness of 0.001" to 0.004", or 0.0015". The everting membrane can be manufactured from irradiated polyolefin, polyurethane, Pebax, silicone, or other flexible membrane material. Side hole **31** has an elliptical opening of 0.5 mm in the minor axis and 2.5 mm in the major axis. Opening dimensions can also be circular with an opening internal diameter ranging from 0.5 mm to 4.0 mm, or 2.5 mm. In conjunction with side hole **31**, negative pressure is supplied by syringe **21** as an aspiration source. With the application of negative pressure, tissue or bodily materials are collected within side hole **31** of biopsy device **30**. Negative pressure is also attenuated by the pressurization of everting membrane **25** which contacts the bodily lumen or in the case of uterine biopsy, the endocervical canal to maintain an airtight seal within the uterine cavity. Also in conjunction with negative pressure, the physician can advance and retract the entire everting catheter system **10** to additionally pull tissue within side hole **31**. The movements to advance and retract everting catheter system **10** while in the uterine cavity range from 0.5 cm to 2.0 cm in a back and forth manner. Everting catheter system **10** can also be rotated while in the bodily lumen or uterine cavity. During the application of negative pressure, or in conjunction with the movements on the everting catheter system **10** by the physician, tissue is drawn into biopsy device **30** and inner catheter **16**. Biopsy device **30** and inner catheter **16** can be constructed from translucent or optically clear materials such as natural polypropylene, natural Pebax, Teflon, or other translucent or optically clear biocompatible materials that allow the physician to visualize the tissue being pulled into biopsy device **30**.

[0072] FIGS. 2A to 2F illustrate in both side views and top views additional derivations built in the distal end of the inner catheter. FIG. 2A shows in a side view the distal end of an elongated biopsy device **30** that can have a flexible cylindrical tube with a closed and rounded distal terminal end **32** and lateral port or side hole opening **31**. Additional side holes can be made on the biopsy device including an opening at the distal end of the biopsy device. Side hole opening **31** also includes an agitator member **35** that is designed to disrupt or agitate the surface of the tissue in the bodily cavity, passageway, or lumen to create more cellular matter for collection or disruption of the endometrium. In another application, it may be desirable to agitate the endometrium in a time period prior to performing an embryo transfer in vitro fertilization procedures. In operation with an aspiration source is applied to the biopsy device **30**, tissue, fluids, cells, or other bodily materials are pulled into biopsy device **30**.

[0073] FIG. 2B shows biopsy device **30** in a top view that illustrates the agitator member **35** at the distal end location of side hole opening **31**. The agitator member **35** can be configured as a bump, barb, hook, or roughened surface and it is designed to disrupt tissue when the biopsy device **30** is advanced, retracted, or rotated about its axis. FIGS. 2A and 2B depict the agitator member at the distal end of side hole **31** but the agitator member can be on the proximal end, both ends, or have the construction of a continuous or fenestrated bump throughout the entire circumference of the side hole.

[0074] FIGS. 2C and 2D show another type of biopsy device **30** with side hole opening **31** and rounded end **32**. Lateral surface of side hole opening **31** has an agitator member **36** at only one side location but both sides can contain the agitator member.

[0075] FIG. 2D illustrates in a top view further the location of agitator member **36** on the lateral side of side hole **31**. In this configuration, agitator member **36** is designed to disrupt tissue as biopsy device **30** is rotated about its center axis.

[0076] FIGS. 2e and 2F illustrate another format for a side hole opening **31** that is angled to the center axis of biopsy device **30**. Agitator member **37** is placed on both the lateral wall and distal end of side hole opening **31** and is designed to disrupt the tissue as biopsy device **30** is advanced, retracted, and rotated within the bodily cavity.

[0077] FIGS. 3A and 3F illustrate in both side views and top views aspiration mechanisms that expand or circumscribe a larger area in the bodily cavity for more wide spread tissue collection

once the biopsy device exits the distal end of the everting membrane. FIG. 3A shows the distal end of biopsy device **30** after it has exited the distal end of the everting membrane. Distal end of biopsy device **30** has an expanding portion **41** that is flexible, resilient, and opens to a larger diameter after it is not contained within the everting membrane. Expansion can be achieved with resilient inner materials such as nitinol struts (not shown) that allow flexure, and a flexible material such as silicone, polyurethane, or other biocompatible flexible material that responds to the flexure provided by the nitinol struts. Struts can be constructed from other materials such as spring steel, Elgiloy, or other polymers that can act as a living hinge.

[0078] FIG. 3B illustrates the effect of everting membrane **25** on the distal end of biopsy device **30** with expanding portion **41** which is compressed to a lower profile within the everting membrane.

[0079] FIG. 3C shows in a top view expanding portion **41** of biopsy device **30**, as well as the configuration of the side hole opening **31** which is fully open when the biopsy device is extended beyond the everting membrane (not visible).

[0080] FIG. 3D shows the effect of the everting membrane **25** on the configuration of the expanding portion **41** and the side hole opening **31**. Note that the side hole opening **31** is now mostly closed under the influence of everting membrane **25** on the expanding portion **41** which is now compressed.

[0081] FIGS. 3E and 3F show biopsy device **30** in the fully extended position beyond the everting membrane (not shown). In the extended position, biopsy device **30** has curvature **42** near the distal end of biopsy device **30** and side hole opening **31** with rounded tip **32**. In operation, curvature **42** is straightened within the everting membrane with a straight profile.

[0082] Once extended beyond the everting membrane, curvature **42** circumscribes a larger area as biopsy device **30** is advanced, retracted, or rotated within the body. Curvature **42** can be created by shape memory material as an inner support material or mandrel (not shown) such as nitinol, or forming curvature **42** within the polymer material of biopsy device **30** by thermal forming or molding.

[0083] FIG. 3F shows biopsy device **30** with curvature **42** in a top view to illustrate that the curvature can be multiple in configuration and represent three-dimensional curves in x, y, and z axis.

[0084] FIG. 4 illustrates in a top view an automatic rotation of the inner catheter during the eversion and inversion step for greater area of tissue collection. Biopsy device **30** is fully extended from the everting membrane (not shown) and is configured like a cork screw so that side hole **31** rotates about the center axis of the biopsy device **30** as it is advanced and retracted to provide greater area of tissue collection within the body.

[0085] FIGS. 5A to 5C illustrate another improvement that performs the aspiration step automatically following eversion. FIG. 5A shows a biopsy device with everting catheter **10** with biopsy device **30** extending beyond the everting membrane **25** in the fully everted position with inner catheter (not visible) contained within outer catheter **18**. Proximal hub **20** is adjacent to y-fitting **17** with inflation tubing and stopcock **15**. Connected to proximal hub **20** is syringe **21** with syringe plunger **22** and spring **54** in the compressed condition between flange **51** and proximal portion of syringe plunger **22**. Clip **52** keeps spring in the compressed condition by being constrained in flange **51** and connector **53**.

[0086] FIG. 5B shows a close view of syringe **21** with compressed spring **54** and clip **52** being held by flange **52**. Spring **52** can be made from stainless steel, spring steel, or polymers. Clip **52** can be made from a polymer or metal and can be configured as a latch, leash, or flap that mechanically keeps spring **54** compressed.

[0087] FIG. 5C shows spring **54** now extended with clip **52** detached from flange **51**. Upon detachment, spring **52** acts on syringe plunger **22** to provide an aspiration source with syringe **21** within the biopsy device. By moving, flipping, displacing, or manipulating clip **51** off flange **51** or mechanical detent on flange **51**, the physician or user can automatically provide an aspiration

source without requiring the use of two hands by displacing clip **51** from flange **51** since syringe plunger **22** will withdraw and pull back from syringe **21** under the influence of the spring action or force of spring **54** to provide an aspiration source. Other embodiments can include clip **52** being restrained on flange **51** by slide button, hook, notch, or depressible button or detent (all not shown). In operation, these embodiments for displacing clip **52** provide a one-handed operation for automatically supplying an aspiration source with negative pressure of withdrawing syringe plunger **22** by the spring action or force of spring **52**.

[0088] FIGS. **6A** to **6C** illustrate further improvements include mechanisms for performing aspiration in a one-handed manner. FIG. **6A** shows another biopsy device with everting catheter **10** in the fully everted position with biopsy device **30** extending beyond the everting membrane **25**. Aspiration bulb **70** with air check valve **71** is attached to the proximal hub **20**.

[0089] FIG. **6B** shows the user squeezing the aspiration bulb **70** which expels the air from the aspiration bulb through air check valve **71**.

[0090] FIG. **6C** shows the user releasing the compression on aspiration bulb **70** which creates an aspiration source through the biopsy device with everting catheter **10**. Repeated squeezes or compressions, and subsequent releases on aspiration bulb **70** continue to draw aspiration pressure within the system. Other embodiments for supplying one-handed aspiration sources include mechanical flywheels, ratchet controlled pumps, or battery-operated pumps.

[0091] FIGS. **7A** and **7B** illustrate other examples of an everting catheter for performing biopsy that contains a cytology brush built within the distal end of the inner catheter. FIG. **7A** shows a cytology brush within an everting catheter **11** with everting membrane **25**. Cytology brush **61** has a rounded distal end **65** with brushes, bristles, absorbent materials, hooks, barbs, or other projections designed for collecting tissue, cells, fluids, or other bodily materials. Cytology brush with everting catheter **11** has a knob **71** for rotating, advancing, or retracting the distal end of cytology brush **61**. T-fitting **70** has irrigation tubing **72** for supplying fluids, media, gas, or other materials through connector hub **73** through the device and out the everting membrane **25**. Y-fitting with stopcock **15** is for providing hydraulic pressure to the everting catheter system.

[0092] FIG. **7B** shows two different configurations of cytology brushes **61** and **62**. Sizes of cytology brushes can be 1 mm to 5 mm in outer diameter, and 0.5 cm to 3 cm in length for applications in the uterine cavity. Other sizes are possible for other locations in the body. Cytology brush can be configured in the straight condition, be malleable to take a curve (not shown), have a pre-set curvature (not shown), or shaped as a loop or noose (not shown).

[0093] FIGS. **8A** to **8D** illustrate everting catheters for performing biopsy that contain a cytology brush built within the distal end of the inner catheter whereby the cytology brush works with the everting balloon as a system to trap tissue within the bristles of the brush during the inversion process. FIG. **8A** shows cytology brush **80** with distal end **81** with segmented bristles **82**, **83**, and **84** with bare locations **90** and **91**. Cytology brush **80** is fully extended beyond everting membrane **25**. In operation in a bodily cavity or location, the full extension of cytology brush **80** allows for tissue contact of the segmented brushes **82**, **83**, and **84**. Please note that the number of segmented brushes can be 2 to a number that can fit on the cytology brush. For the uterine cavity application, 3 to 6 segmented brush locations in which each location was 3-4 mm in length with a diameter of 2 to 4 mm.

[0094] FIG. **8B** shows cytology brush **80** being retracted within everting membrane **25** in which proximal segmented brush location **82** is flattened under the influence of the everting membrane. As segmented brush location **82** is flattened, bare location **90** becomes a collection point for tissue, cells, fluid, and other bodily materials. Subsequently as cytology brush **80** continues to be retracted within everting membrane **25**, segmented brush location **83** will flatten and trap tissue and bodily materials in bare location **91**.

[0095] FIG. **8C** shows an alternative configuration of a cytology brush **100** with segmented brushes that are in a helical configuration with continuous helix brush **102** and bare locations **90**, **91**, and

92. Bare locations are in fact continuous but are labeled individually for clarity.

[0096] FIG. **8D** shows cytology brush being retracted within everting membrane **25** in which the proximal portion of helix brush **102** is being compressed or flattened and tissue or bodily materials being collected in bare location **90**.

[0097] FIGS. **9A** to **9D** illustrate everting catheters for performing biopsy with an instrument that performs tissue shaving and removal. Tissue shaver with everting catheter **90** is shown with open shaver **91** with shaver distal end **92**. Shaver **91** is open when extended from the everting membrane **25** and shaver **91** is closed or in a low profile condition (not shown) when shaver **91** is retracted within the everting membrane **25**. Proximal knob **99** allows for advancement, retraction, or rotation of shaver **91**. Shaver **91** can be made from metal, nitinol, or a polymer.

[0098] FIG. **9B** shows a close up view of shaver **91** and shaver end **92** extending beyond the distal end of everting membrane **25** with acorn tip **19**. Shaver **91** can also be constructed with a composite of materials on the shaver **91** with a silicone, polyurethane, or other coating on the shaver **91**. Coating is constructed with a roughened surface (not shown) or contains projections (not shown) to collect or trap tissue within the opening of the shaver **91**. In another embodiment, the coating can be placed on the distal portion or distal half of the shaver (not shown) to trap tissue upon the closure and retraction of the shaver.

[0099] FIG. **9C** shows another shaver with everting catheter **105** that opens and deploys into a larger area within the body with shaver **93** with distal end **94**. The shaver **93** is in the open position after exiting the everting membrane **15** is fully everted and beyond the acorn tip **19**. Everting catheter is fully everted when the inner catheter (not visible) is translated within the outer catheter **18** through the y-fitting **17** under the influence of the hydraulic pressure applied through inflation tubing and stopcock **15**. Connected to proximal hub **25** is knob **98** that can be used to advance, retract, and rotate shaver **93** at the distal end of the shaver with everting catheter **105**. On the proximal end of knob **98** is a luer connection **97** with through hole for connecting with a syringe (not shown) for injecting irrigation fluid, contrast media, saline, gas, air, or therapeutic agents during the procedure. Luer connection **97** can also be used to supply an aspiration source (not shown) for assisting in maintaining cells, fluids, or other bodily material during the tissue shaving and collection procedure, or when retracting the device from the body.

[0100] FIG. **9D** is a close up view of shaver **93** with distal end **94** extending beyond the distal end of the everting membrane **25**. Shaver **93** is made from stainless steel but other materials such as nitinol, Elgiloy, or polymeric materials such as polypropylene, polycarbonate, ABS, nylon, PEEK, or other biocompatible materials are possible.

[0101] FIGS. **10A** and **10B** illustrate an everting catheter for performing biopsy with an instrument that performs tissue shaving and removal and a mechanism designed to sweep a larger area for tissue collection within the desired location in the body. FIG. **10A** shows the distal end of everting membrane **25** with shaver **96** with distal end **95**.

[0102] FIG. **10B** shows shaver **96** opened and deployed beyond everting membrane **25** with shaving elements **95** constructed to remove tissue within the body. Shaver **96** can be advanced, retracted, and rotated by the physician or user. Upon retraction back into everting membrane **25**, shaver **96** collapses and returns to a small profile.

[0103] FIGS. **11A** to **11D** illustrate in cross-sectional views an everting catheter with an everting balloon membrane surface with protruding hooks, latches, barbs, or bristles to pick up and collect tissue or cells in a location in the body. In this embodiment, the everting membrane itself becomes the tissue or tissue collection instrument by the physical contact of the everting membrane with the bodily cavity, passageway, lumen, or potential space. FIG. **11A** shows in a cross-sectional view an everting membrane **125** that is fully everted from the everting catheter (not shown). Distal end of everting membrane **125** contains bristles **126** or a brush on the surface of the membrane. As the membrane everts and rolls out on the tissue surface, bristles **126** pick-up or collect tissue, cellular or bodily materials. As everting membrane **126** is retracts and inverts along the center axis of the

everting catheter system, bristles **126** roll into the everting membrane **125** and cellular materials are collected. Note that by definition, the tissue collection or tissue sampling area is limited to only that area the everting membrane **125** and tissue collecting elements or bristles **126** contact.

[0104] FIG. **11B** shows a close up cross-sectional view of just side of everting membrane **125** and bristles **126**.

[0105] FIG. **11C** shows in a cross-sectional view one side of everting membrane **125** with another embodiment of a tissue or cellular collection system made of hooks **127** or barbs. Once deployed, hooks **127** contact and collect tissue that will be trapped within the everting membrane **125** as the inversion process is done.

[0106] FIG. **11D** shows in a cross-sectional view on side of everting membrane **125** with an alternative form of tissue collecting elements constructed with latches **128** and **129** that open and close upon physical contact with the tissue. Upon inversion, latches **128** and **129** close and trap tissue or cellular materials.

[0107] FIG. **12** illustrates in a cross-sectional view an everting balloon catheter (not shown) with cellular collection material **136** on the exterior surface of the distal end of everting membrane **135** with micro-channels **137** or pores that are pressed against tissue upon eversion to pick up cellular material. In operation, everting membrane **135** unrolls within a bodily cavity until the portion with the cellular collection material **136** contacts tissue. Upon pressure being applied with everting membrane **135**, micro-channels **137** open and collect bodily materials. Upon inversion, micro-channels **137** and cellular collection material **136** portion of the device is retracted within everting membrane **135**.

[0108] FIG. **13** illustrates in a cross-sectional view an everting balloon catheter (not shown) with a cellular collection material **136** on the exterior surface that is near or more proximal the distal end of the everting membrane **1315** with micro-channels **137** or pores that are pressed against tissue upon eversion to pick up cellular material. This embodiment demonstrates that the cellular collection material **136** can be placed on specific locations on the everting membrane that are not on the distal end of the membrane or a particular side of the everting membrane including the anterior, posterior, lateral, or combinations of these locations.

[0109] FIG. **14** illustrates in a cross-sectional view an everting balloon catheter (not shown) with cellular collection materials **136** on multiple locations of the exterior surface of the everting membrane **135**. Multiple tissue collection material **136** areas can be defined by radial segments or stripes to biopsy different locations of a bodily passageway which may facilitate or determine the extent or proliferation of a disease state within a bodily lumen. As an example, using the eversion process of everting membrane **135**, assessing the cellular collection materials **136** in the more proximal portion of the device versus the more distal portion can provide the practitioner a rate of disease progression or treatment.

[0110] FIGS. **15A** to **15E** illustrate an everting balloon catheter with a tissue collection material **326** on the exterior surface of the everting membrane **325** with multiple tissue collection material **326** areas placed on anterior and posterior locations of an everting membrane to assess specific locations of studied cells or tissue in a body passageway. FIG. **15A** shows an initial stage of the eversion process with everting membrane **325** exiting the acorn tip **19** with the membrane rolling at a distal end **320** and tissue collection material **326** located within the everting membrane **325**.

[0111] FIG. **15B** demonstrates the eversion process proceeding with the everting membrane **325** having further exited the acorn tip **19** and tissue collecting material **326** rolling out of the distal end **320** of the everting membrane **325**.

[0112] FIG. **15C** further illustrates that the tissue collection material **326** is rolling out on two sides of the everting membrane **325** at the distal end **320**.

[0113] FIG. **15D** illustrates the completion of the eversion process with the everting membrane **325** fully everted and tissue collection material **326** visible on one lateral side of everting membrane **325**.

[0114] FIG. 15E shows tissue collection material 326 on both sides of everting membrane 325 to provide the ability to assess or diagnose two distinct areas, such as anterior portion and posterior portion, or lateral side and contra-lateral side, of a bodily lumen or passageway.

[0115] FIGS. 16A and 16D illustrate an everting balloon catheter with a material for collecting bodily fluid within a specific location in the body whereby the everting membrane lined on the exterior surface with a porous or fluid receptive membrane or material for fluid collection for bodily fluid collection at a specific bodily location within the passageway or body cavity. FIG. 16A shows the initial stages of the eversion process with everting membrane 325 exiting the distal end opening of acorn tip 19. Distal end 320 of everting membrane is visible and tissue collection material 327 is located and isolated within the everting membrane 325.

[0116] FIG. 16B shows a continuation of the eversion process with everting membrane 325 advanced further from acorn tip 19 and tissue collection material 327 just exiting the distal end of the everting membrane 325.

[0117] FIG. 16C shows the completion of the eversion process with tissue collection material 327 located on one side of everting membrane 325 and just proximal to the distal end 320.

[0118] FIG. 16D shows the same tissue collection material 327 in another view located on one specific side of the everting membrane 325. Providing the tissue collection material 327 at a specific distance and specific location on everting membrane 325 provides the ability to directly diagnose a particular or specific area in a bodily passageway or lumen. Since the everting membrane 325 operates in the eversion process without shear forces, or without sliding along the interior surfaces of the body, tissue collection material 327 will be exposed within the body to only that tissue that contacts the material.

[0119] FIGS. 17A and 17B illustrate an everting balloon catheter with an everting balloon membrane 325 with a diagnosing material 328 on the external surface for determining pH, lactate, hormonal content, medication content, urine, fecal, blood, lymphatic fluid, bile, mucus, infection or pus, edema, or other detectable bodily fluid or by-product. Diagnosing material 328 is seen just proximal to the distal end 320 of the everting membrane 325 that is extended beyond the acorn tip 19. FIGS. 17A and 17B illustrate that the diagnosing material 328 located in a specific location on the everting membrane 325, but multiple diagnosing materials (not shown), or diagnosing materials that encompass the entire circumference or exterior surface of the everting membrane (not shown) are possible.

[0120] In another embodiment, FIG. 18 illustrates an everting balloon catheter with an everting balloon membrane 325 with a diagnosing material 329 on the external surface of everting membrane 325 that can detect and report temperature exposure, amount of pressure exerted as in pressure-sensitive test strips, or interior surface morphology of tissue within a bodily vessel. As an example, pressure sensitive tape is used as diagnosing material 329 that is everted into a bodily passageway. Once everted, the hydraulic pressure within the everting catheter system can be increased to promote contact of the pressure sensitive tape to the tissue at a known pressure. The amount of internal hydraulic pressure can be reduced to then allow for inversion and removal from the body of the patient. After removal, the pressure sensitive tape or diagnosing material can be evaluated. Other types of evaluation include internal tissue morphology or temperature.

[0121] FIG. 19 illustrates a biopsy everting catheter system 12 that includes a through-lumen within the inner catheter (not visible) for irrigation or lavage of tissue through port 73 and tubing 72. Lavage or fluid exits everting membrane 25 at the distal end 62 near biopsy device 61 (illustrated here with a cytology brush but other biopsy instruments are possible) to facilitate cellular or specimen collection.

[0122] FIG. 20 illustrates in a cross-sectional view a biopsy everting catheter system with tissue agitators 201 and 202 on the everting membrane 200 to facilitate tissue or cellular collection. Tissue agitators 201 and 202 are exposed to the tissue once everted from everting membrane 200. Tissue agitators 201 and 202 can also be used in conjunction with physically advancing, retracting,

or rotating the entire everting catheter system

[0123] FIG. **21** illustrates a biopsy everting catheter system with a tissue agitator **210** on the inner catheter of the biopsy device **201** that performs the function of agitation automatically upon eversion or inversion. Tissue agitator **210** is designed to loosen or disrupt tissue to facilitate collection in side hole opening **215** of biopsy device **201**.

[0124] FIG. **22** illustrates a biopsy everting catheter system **700** with handle **705** for the manual advancement, retraction, or rotation, of the entire everting catheter system to facilitate tissue agitation to increase the amount of tissue for specimen collection. Handle button **706** can be used by the physician or operator to physically evert or invert the everting membrane (not visible in outer catheter **18**). Or handle button can be connected to biopsy device **701** for the one handed manual advancement, retraction, or rotation of the biopsy device.

[0125] FIGS. **23A-23C** illustrate in cross-section a tissue shaver **800** for removing and collecting thin layers of tissue within the uterine cavity that is particularly suited for atrophic endometrium or post-menopausal women. Tissue shaver **800** has a distal catheter **805** that can have side holes **808** and **809** with internal nitinol wire **810** within the lumen of distal catheter **805**.

[0126] FIG. **23A** illustrates a variation of the configuration of the internal nitinol wire **810** as the tissue shaver **800** can be placed within the uterine cavity or bodily lumen. FIG. **23B** illustrates that once placed within the uterine cavity or other bodily lumen, the internal nitinol wire **810** can be advanced within the lumen of distal catheter **805**. Upon advancement, nitinol wire projections **811** and **812** can exit side holes **808** and **809** for exposure within endometrium **900** or other tissue as defined by the bodily lumen. Nitinol wire projection **811** and **812** can be configured to cut or shave tissue when the distal catheter **805** is rotated within the tissue or endometrium **900**.

[0127] FIGS. **23A** and **23B** illustrate a distal catheter **805** with two side holes **808** and **809** but a singular side hole, as well as a higher number of side holes is possible. The side holes can be configured diametrically opposite to each other or co-linear on the surface of distal catheter **805** as shown in FIGS. **23A** and **23B**. In operation, the distal catheter **805** can exit an everting membrane (not shown) or be placed within the patient as a single cannula catheter.

[0128] FIG. **23C** illustrates the biasing force **813** on the internal nitinol wire **810** that can force nitinol wire projections **811** and **812** to exit side holes **808** and **809**. Biasing force **813** can act upon inner lumen surface **814** to force nitinol wire projections **811** and **812** out of side holes **808** and **809** when the internal nitinol wire **810** is advanced within the lumen of the distal catheter **805**.

[0129] FIG. **24** illustrates in cross section a tissue shaver **815** with internal cutting wire **820** that can be housed within the lumen of a distal catheter **816**. The lumen of the distal catheter **816** can be coupled with an internal aspiration source (not shown) that supplies vacuum pressure **822** that force endometrium or bodily lumen tissue (not shown) within side hole **817**. Cutting wire can be coupled to an actuator or motor on the proximal portion of the catheter (not shown) that rotates cutting wire **820** within the lumen of distal catheter **816**. Distal end of cutting wire **820** is shown with distal cutting wire ball tip **821** that can facilitate the movement of cutting wire **820** within the lumen of distal catheter **816**. In operation, once deployed in the uterine cavity or bodily lumen, suction or vacuum force **822** can be applied to force endometrium and bodily lumen tissue within side hole **817**. In combination, the rotation of cutting wire **820** can slice tissue that protrudes inside side hole **817**. Cutting wire **820** can be configured with a biasing force **824** and wire curvature **826** to force the cutting portion **828** to slice tissue at side hole **817**. Alternatively, tissue shaver **815** can be used without a vacuum force **822** or internal aspiration source.

[0130] FIG. **24** illustrates one side hole **817** but multiple side holes at different locations on the distal catheter **816** are possible. Cutting wire **820** can be configured as a coil or spring (not shown). The coil or spring can be made from round wire, flat wire, D-shaped wire, or a wire surface with multiple facets. As a coil or spring, this cutting wire mechanism can be rotated within the lumen of a distal catheter, or separately or in combination, advanced and retracted to provide a cutting surface at the side hole of a distal catheter. This cutting action can be performed with or without a

vacuum force.

[0131] FIG. 25 illustrates in cross section a tissue shaver **830** that can include an internal coring screw **835** within distal catheter **832** with side hole **834**. Lumen of distal catheter **832** can be coupled to an aspiration source (not shown) that supplies vacuum force **836**. In operation when distal catheter **832** is placed within the uterine cavity or bodily lumen, vacuum force **836** can be applied to force endometrium or bodily lumen tissue within side hole **834**. Optionally in combination, actuator or motor (not shown) at the proximal portion of the tissue shaver **830** can be coupled to the internal coring screw **835** to provide rotation **838** to the internal coring screw **835**, which can rotate with or independently of the distal catheter **832**. Internal coring screw **835** can contain a pitch in which screw threads **839** and **840** remove endometrium and bodily lumen tissue as the internal coring screw **835** is rotated. Endometrium and bodily lumen tissue as it is removed at side hole **834** can be driven towards the proximal portion of distal catheter **832** in combination with the rotation of the internal coring screw **835** and vacuum force **836** to a specimen collection area (not shown) in the proximal portion of tissue shaver **830**. Internal coring screw **835** and tissue shaver **830** can be used without a coupled aspiration source. Distal catheter **832** can have a plurality of side holes in various locations on the distal catheter. For specimen collection, after removal from the uterine cavity or bodily lumen, the actuator or motor can be applied in the opposite direction to push endometrium and bodily lumen tissue back towards side hole **834** for removal from the distal catheter **830**.

[0132] FIGS. 26A and 26B illustrate in cross section tissue collector **840** with distal catheter with irrigation lumen **846** that can be coupled to an irrigation source (not shown) operated by the user or physician that provides irrigation **847** through irrigation side hole **843**. Fluid media for irrigation **847** can include saline or culture media depending upon the application. Distal catheter **842** can have aspiration side hole **844** that can be coupled to aspiration lumen **848**. An aspiration source (not shown) at the proximal portion of the tissue collector can provide vacuum force **849**. Proximal to the aspiration side hole **844**, filtration membrane **850** can have a porosity for collecting certain sized cells or tissue. Filtration membranes can include a 0.2 micron to 15 micron filter, or other porosities, for example to drive a vacuum or pressure differential across filtration membrane **850** but leaving cellular or tissue contents on the distal side **851** of the filtration membrane. In operation once the distal catheter **842** is placed within the uterine cavity or bodily lumen, media **847** can be introduced through irrigation lumen **846** and out into the patient through irrigation side hole **843**. Vacuum force **849** can be applied within aspiration lumen **848** to drive contents from the uterine cavity or bodily lumen into aspiration side hole **844**. Filtration membrane **850** can trap tissue or cellular contents on the distal side **851** of the filtration membrane **850**. Distal catheter **842** can then be removed from the patient. To obtain the tissue or cellular specimen, distal catheter **842** can be configured with a perforation or preferential weakness **852** that allows the end user to snap off the filtration membrane **850** from distal catheter **842** for subsequent analysis of the collected tissue or cellular contents. Aspiration side hole **844** can be used a portal to retrieve collected tissue. Tissue collector **840** can be used without irrigation lumen **846** and irrigation media **847**. Multiple irrigation side holes could be employed. Multiple aspiration side holes could be used, or combinations and numbers of irrigation and aspirations side holes. Multiple filtration membranes could be employed in which different porosities are used. For example, the most distal or first filtration membrane can have a larger porosity with a second, more proximal filtration membrane having a smaller or finer porosity to collect a specific size of tissue or cells that would flow through the first filtration membrane. A portal can be between the first and second membranes, for example to retrieve collected tissue or cells between the two filtration membranes. A perforation or preferential weakness in the distal catheter can, for example, retrieve tissue or cells between the two filtration membranes. A plurality of filtration membranes can be used.

[0133] FIG. 26B illustrates in cross section a tissue collector **840** with tissue or cellular collection area **860** in the proximal portion of the tissue collector. Aspiration source **862** can provide vacuum

force **849** through the tissue or cellular collection area **860** through filtration membranes **871** and **870**, and ultimately through the aspiration lumen **848** to the distal catheter **842** and aspiration side hole **844**. Tissue or cellular collection area **860** can be removed by the user following the sampling procedure in which cap **864** can be removed to access the specimen in collection area **861**. Irrigation lumen **846** can provide media **847** through irrigation side hole **843**. and filtration system that includes an irrigation source for the uterine cavity. As described in FIG. **26A**, the tissue collector **840** illustrated in FIG. **26B** could be used without irrigation lumen **846** and irrigation media **847**. Multiple irrigation side holes could be employed. Multiple aspiration side holes can be used, or combinations and numbers of irrigation and aspirations side holes.

[0134] Any of the apparatus and/or method elements described herein can be used in combination with or substituted with any of the apparatus and/or method elements of U.S. Provisional Application Nos. 61/302,742, filed Nov. 11, 2013; 61/977,478, filed Apr. 9, 2014; 62/005,355, filed May 30, 2014; 62/528,422, filed Jul. 3, 2017; 62/553,057, filed Aug. 31, 2017; 62/007,339, filed Jun. 3, 2014; and 62/597,353, filed Dec. 11, 2017, all of which are incorporated by reference herein in their entireties.

[0135] Any elements described herein as singular can be pluralized (i.e., anything described as “one” can be more than one). Any species element of a genus element can have the characteristics or elements of any other species element of that genus. The media delivered herein can be any of the fluids (e.g., liquid, gas, or combinations thereof) described herein. The patents and patent applications cited herein are all incorporated by reference herein in their entireties. Some elements may be absent from individual figures for reasons of illustrative clarity. The above-described configurations, elements or complete assemblies and methods and their elements for carrying out the disclosure, and variations of aspects of the disclosure can be combined and modified with each other in any combination. All devices, apparatuses, systems, and methods described herein can be used for medical (e.g., diagnostic, therapeutic or rehabilitative) or non-medical purposes.

Claims

1. A method for delivering an IUD into a uterus in a body comprising: inflating an everting balloon; covering an opening on a tool with the everting balloon; unrolling the everting balloon through a cervix to the uterus; delivering the tool through the everting balloon through the cervix to the uterus, wherein the tool comprises the IUD; uncovering the opening on the tool by extending the opening past the distal end of the everting balloon; delivering the IUD into the uterus; and retracting the everting balloon.
2. The method of claim 1, further comprising delivering a fluid media to the uterus.
3. The method of claim 1, further comprising applying a vacuum force to the uterus.
4. The method of claim 1, further comprising lavaging the uterus.
5. The method of claim 4, wherein the lavaging the uterus comprises lavaging with at least an irrigation fluid through the opening.
6. The method of claim 1, further comprising delivering a drug into the uterus.
7. The method of claim 2, wherein the lavaging comprises cellular collection.
8. The method of claim 2, wherein the lavaging comprises specimen collection.
9. The method of claim 1, further comprising delivery of a cytology element into the uterus.
10. The method of claim 1, further comprising delivery of a biopsy element into the uterus.
11. The method of claim 1, further comprising delivering contrast media or echogenic fluid through the opening.
12. The method of claim 1, further comprising aspirating contrast media or echogenic fluid through the opening.
13. The method of claim 1, further comprising delivering a medication through the opening.
14. The method of claim 1, further comprising aspirating a medication through the opening.

15. A method for delivering an IUD into a uterus in a body comprising: inserting a distal end of an elongated element into the uterus, wherein the elongated element comprises the IUD, and wherein the elongated element has an opening and a cover closeable over the opening; closing the cover over the opening, wherein the closing of the cover comprises everting the cover over the opening; delivering the IUD to the uterus through the opening of the elongated element; and everting the cover over the opening.

16. The method of claim 15, wherein the elongated element has an inner catheter, and wherein the inner catheter has a through-lumen, and wherein the method further comprises lavaging comprising delivering an irrigation fluid through the through-lumen.

17. A device for delivering an IUD into a uterus in a body comprising: an inflatable everting balloon having a center axis; a deliverable device along the center axis of the everting balloon, wherein the deliverable device has a port and comprises a tool comprising an IUD; wherein the everting balloon is configured to cover the port when the everting balloon is in a first configuration, and wherein the everting balloon is configured to not cover the port when the everting balloon is in a second configuration.

18. The device of claim 17, wherein the first configuration of the everting balloon is everted more distally than the second configuration of the everting balloon.

19. The device of claim 17, further comprising a drug in a position on the device deliverable into the uterus.

20. The device of claim 17, further comprising a handle button for advancement of the IUD.
