

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384203
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Matsumoto; Kenichi

Tire

Abstract

A tire tread includes a pair of first circumferential main grooves in a first half-tread region on one side in a tire width direction, a pair of second circumferential main grooves in a second half-tread region, first sipes provided in a first region between the first circumferential main grooves, a circumferential narrow groove having a groove width smaller than a groove width of the first circumferential main groove and extending in the tire circumferential direction within the first region, and sipes in a second region between the second circumferential main grooves, extending in the tire width direction, and closing within the second region. The number of intervals of the second sipes mutually adjacent is larger than the number of intervals of the first sipes mutually adjacent.

Inventors:	Matsumoto; Kenichi (Kanagawa, JP)
Applicant:	The Yokohama Rubber Co., LTD. (Tokyo, JP)
Family ID:	1000008750873
Assignee:	The Yokohama Rubber Co., LTD. (Tokyo, JP)
Appl. No.:	17/757036
Filed (or PCT Filed):	December 07, 2020
PCT No.:	PCT/JP2020/045379
PCT Pub. No.:	WO2021/117653
PCT Pub. Date:	June 17, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220410634 A1	Dec. 29, 2022

Foreign Application Priority Data

Publication Classification

Int. Cl.: B60C11/12 (20060101); B60C11/03 (20060101)

U.S. Cl.:

CPC B60C11/1272 (20130101); B60C11/0304 (20130101); B60C11/1236 (20130101);
B60C11/1263 (20130101); B60C2011/0348 (20130101); B60C2011/1295 (20130101)

Field of Classification Search

CPC: B60C (11/1263); B60C (11/0304); B60C (11/1236); B60C (2011/1295); B60C
(2011/0348)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2272879	12/1941	Hargraves	D12/598	B60C 11/1263
2012/0118455	12/2011	Hada	N/A	N/A
2012/0247632	12/2011	Hayashi	N/A	N/A
2017/0210175	12/2016	Yoshimura	N/A	N/A
2019/0283505	12/2018	Kuriyama	N/A	B60C 11/00
2019/0366774	12/2018	Tanabe et al.	N/A	N/A
2019/0375246	12/2018	Kubo	N/A	B60C 11/1236
2020/0148008	12/2019	Nemoto	N/A	B60C 11/24

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2505387	12/2011	EP	N/A
3208111	12/2016	EP	N/A
3575111	12/2018	EP	N/A
61-159203	12/1985	JP	N/A
2007-168628	12/2006	JP	N/A
2012-228992	12/2011	JP	N/A
2014-76764	12/2013	JP	N/A
2017-81540	12/2016	JP	N/A
2017-226369	12/2016	JP	N/A
2019-43541	12/2018	JP	N/A
2019-182202	12/2018	JP	N/A
2019-209731	12/2018	JP	N/A
2019-209874	12/2018	JP	N/A
WO-2018-235400	12/2017	WO	N/A

OTHER PUBLICATIONS

Machine translation for Japan 2007-168628 (Year: 2024). cited by examiner

Machine translation for Japan 61-159203 (Year: 2024). cited by examiner

Primary Examiner: Maki; Steven D

Attorney, Agent or Firm: Thorpe North & Western

Background/Summary

TECHNICAL FIELD

(1) The present technology relates to a tire having a tread pattern in a tread portion.

BACKGROUND ART

(2) One known way to improve the wet performance of a tire is to provide, on a tread surface of the tire, a main groove extending in a tire circumferential direction and also a lug groove extending in a tire width direction for ensuring drainage properties. However, in a configuration in which the lug groove has a large groove volume, a loud popping sound is generated when kicking out, and performance to reduce tire noise (hereinafter referred to as noise performance) is degraded.

(3) In the related art, there is known a tire without a groove having a width of 2 mm or more provided in a crown land portion or a middle land portion in a tread portion (see Japan Unexamined Patent Publication No. 2017-226369).

(4) In a configuration of Japan Unexamined Patent Publication No. 2017-226369, to avoid degrading noise performance, a groove having a width of 2 mm or more is not provided in a crown land portion or a middle land portion on a tread surface including a main groove and a lug groove, groove volume decreases, and thus noise performance improves, but drainage properties cannot be ensured due to a decrease in the groove volume, degrading wet performance.

SUMMARY

(5) The present technology provides a tire that provides improved wet performance while suppressing degradation of noise performance.

(6) An aspect of the present technology is a tire including a tread pattern in a tread portion.

(7) The tread pattern includes: a pair of first circumferential main grooves provided in a first half-tread region on one side of a tire centerline in a tire width direction, extending in a tire circumferential direction, and disposed at intervals from each other in the tire width direction; a pair of second circumferential main grooves provided in a second half-tread region on an other side in the tire width direction, extending in the tire circumferential direction, and disposed at intervals from each other in the tire width direction; a plurality of first sipes provided in a first region between the first circumferential main grooves, communicating with one of the first circumferential main grooves, extending in the tire width direction, and closing within the first region; a circumferential narrow groove having a groove width smaller than a groove width of the first circumferential main groove and extending in the tire circumferential direction within the first region; and a plurality of second sipes provided in a second region between the second circumferential main grooves, communicating with one or an other of the second circumferential main grooves, extending in the tire width direction, and closing within the second region. The number of intervals of the second sipes adjacent in the tire circumferential direction is larger than the number of intervals of the first sipes adjacent in the tire circumferential direction.

(8) Preferably, the tread pattern does not include lug grooves that are provided in the first region, communicate with the first circumferential main groove, and extend in the tire width direction, or lug grooves that are provided in the second region, communicate with the second circumferential main groove, and extend in the tire width direction.

(9) Preferably, the second sipes include a second sipe A and a second sipe B, the second sipe A

communicating with one of the second circumferential main grooves and the second sipe B communicating with the other of the second circumferential main grooves at a location, in the tire circumferential direction, which is different from a location, in the tire circumferential direction, where the second sipe A communicates with the circumferential main groove.

(10) Preferably, a plurality of the second sipes A and a plurality of the second sipes B are disposed at intervals in the tire circumferential direction, and the second sipes B are disposed one by one between the second sipes A adjacent in the tire circumferential direction.

(11) Preferably, a direction connecting two ends of an extension direction of the second sipe A and a direction connecting two ends of an extension direction of the second sipe B are inclined, with respect to the tire width direction, to a same side in the tire circumferential direction.

(12) Preferably, lengths of the intervals of the second sipes differ between the intervals adjacent in the tire circumferential direction.

(13) Preferably, the first sipe communicates with the circumferential narrow groove.

(14) Preferably, a sipe depth of a narrow groove side connection portion of the first sipe is smaller than a groove depth of the circumferential narrow groove, the narrow groove side connection portion connecting to the circumferential narrow groove, and a sipe depth of an intermediate portion of the first sipe is deeper than the groove depth of the circumferential narrow groove, the intermediate portion being located between the first circumferential main groove, with which the first sipe communicates, and the narrow groove side connection portion.

(15) Preferably, a sipe depth of a main groove side communicating portion of the first sipe is smaller than a groove depth of the circumferential main groove, the main groove side communicating portion communicating with the first circumferential main groove.

(16) Preferably, the first sipe extends in a curved shape bulging to one side in the tire circumferential direction on a tread surface.

(17) Preferably, a length of the first sipe in an extension direction of the first sipe is greater than a length of the second sipe in an extension direction of the second sipe.

(18) Preferably, the second sipe extends in a straight line, and an inclination angle, with respect to the tire width direction, of a direction connecting two ends of an extension direction of the second sipe differs between the second sipes adjacent in the tire circumferential direction.

(19) Preferably, the tread pattern comprises a plurality of third sipes that are provided in a third region between the first circumferential main groove, of the first circumferential main grooves, closest to the tire centerline and the second circumferential main groove, of the second circumferential main grooves, closest to the tire centerline, communicate with either the first circumferential main groove or the second circumferential main groove, extend in the tire width direction, and close within the third region, and the number of the intervals of the second sipes is larger than a number of intervals of the third sipes adjacent in the tire circumferential direction.

(20) Preferably, a length of the second sipe in the tire width direction is half or less of a length of the second region in the tire width direction, and a length of the third sipe in the tire width direction is half or less of a length of the third region in the tire width direction.

(21) Preferably, the tread pattern has a vehicle mounting orientation designated such that the second half-tread region is disposed in a vehicle outer side of the first half-tread region.

(22) The tire of the aspect described above can suppress degradation of wet performance while improving noise performance.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a diagram illustrating an example of a profile cross-section of a pneumatic tire according to the present embodiment.

- (2) FIG. 2 is a diagram illustrating an example of a tread pattern of the tire of FIG. 1.
- (3) FIG. 3 is a diagram illustrating a cross-section of a portion of a first middle region.
- (4) FIG. 4 is a perspective view illustrating an embodiment of a chamfered portion.
- (5) FIG. 5 is a diagram explaining an extension line.

DETAILED DESCRIPTION

(6) Overall Description of Tire

(7) Hereinafter, a tire of the present embodiment is described. The tire of the present technology is preferably a pneumatic tire, and the tire of the present embodiment is a pneumatic tire. A pneumatic tire is a tire including a cavity region surrounded by a tire and a rim, the cavity region being filled with air. Note that in the tire of the present embodiment, the cavity region surrounded by a tire and a rim may be filled with an inert gas such as nitrogen or other gas instead of air. The present embodiment includes various embodiments described below.

(8) FIG. 1 is a tire cross-sectional view illustrating an example of a profile cross-section of a pneumatic tire (hereinafter referred to simply as “tire”) **10**.

(9) The tire **10** is, for example, a tire for a passenger vehicle. “Tire for a passenger vehicle” refers to a tire specified in Chapter A of the JATMA YEAR BOOK 2012 (standards of The Japan Automobile Tyre Manufacturers Association, Inc.). The tire **10** can also be applied to a tire for a light truck specified in Chapter B and a tire for a truck and a bus specified in Chapter C.

(10) Tire width direction is a direction parallel to a rotation axis of a tire. “Outer side in the tire width direction” is a side distant from a tire centerline CL (tire equator line) representing a tire equatorial plane in the tire width direction. Additionally, “inner side in the tire width direction” is a side closer to the tire centerline CL in the tire width direction. Tire circumferential direction is a direction of rotation about the rotation axis of a tire. “Tire radial direction” is a direction orthogonal to the rotation axis of a tire. “Outer side in the tire radial direction” refers to a side away from the rotation axis. Similarly, “inner side in the tire radial direction” refers to a side closer to the rotation axis.

(11) Tire Structure

(12) The tire **10** includes a tread portion **10T** including a tread pattern, a pair of bead portions **10B**, and a pair of side portions **10S** provided in two sides of the tread portion **10T** and connected to the pair of bead portions **10B** and the tread portion **10T**.

(13) The tire **10** includes a carcass ply **12**, a belt **14**, and a bead core **16** as framework members and mainly includes, around the framework members, a tread rubber member **18**, a side rubber member **20**, bead filler rubber members **22**, rim cushion rubber members **24**, and an innerliner rubber member **26**.

(14) The carcass ply **12** is formed of a carcass ply member that is made of organic fibers covered with rubber and wound between a pair of the bead cores **16** having an annular shape into a toroidal shape. The carcass ply **12** is wound around the bead cores **16** and extends to an outer side in the tire radial direction. The belt **14** is provided in an outer side of the carcass ply **12** in the tire radial direction and includes two belt members **14a**, **14b**. The belt **14** includes a member made of a steel cord that is covered with rubber and inclined at a predetermined angle, for example, at from 20 to 30 degrees, with respect to the tire circumferential direction. The belt member **14a** of an inner layer has a width in the tire width direction that is greater than a width in the tire width direction of the belt member **14b** of an outer layer. The steel cords of the two belt members **14a**, **14b** are inclined in opposite directions. As such, the belt members **14a**, **14b** are crossing layers serving to suppress expansion of the carcass ply **12** due to pressure of the air in the tire.

(15) The tread rubber member **18** is provided in an outer side of the belt **14** in the tire radial direction. The side rubber members **20** are connected to two end portions of the tread rubber member **18** and form the side portions **10S**. The rim cushion rubber members **24** are provided at ends in an inner side of the side rubber member **20** in the tire radial direction and come into contact with a rim on which the tire **10** is mountable. Each of the bead filler rubber members **22** is provided

in an outer side of each of the head cores **16** in the tire radial direction and is interposed between a portion of the carcass layer **12** prior to being wound around the bead core **16** and a portion of the carcass ply **12** wound around the bead core **16**. The innerliner rubber member **26** is provided on an inner surface of the tire **10** facing a tire cavity region that is filled with air and is surrounded by the tire **10** and the rim.

(16) Additionally, two belt covers **30** made of organic fiber covered with rubber are provided between the belt member **14b** and the tread rubber member **18**. The two belt covers **30** cover the belt **14** from the outer side of the belt **14** in the tire radial direction.

(17) Tread Pattern

(18) FIG. **2** is a diagram illustrating a portion developed into a plan view of an example of a tread pattern of the tire **10** of FIG. **1**.

(19) The tread pattern according to the example illustrated in FIG. **2** includes a first outer main groove **21**, a first inner main groove **23**, a second inner main groove **25**, and a second outer main groove **27** as circumferential main grooves extending in the tire circumferential direction.

(20) The first outer main groove **21** and the first inner main groove **23** are provided in a first half-tread region on one side (left side in FIG. **2**) of the tire centerline CL in the tire width direction and are disposed at intervals from each other in the tire width direction.

(21) The second inner main groove **25** and the second outer main groove **27** are provided in a second half-tread region on the other side (right side in FIG. **2**) in the tire width direction and are disposed at intervals from each other in the tire width direction.

(22) Herein, main groove means a groove having a groove depth of, for example, from 6.5 to 9.0 mm and a groove width of, for example, from 5.0 to 15.0 mm.

(23) The number of main grooves provided in the tread pattern is four in the example illustrated in FIG. **2**, but may be, for example, three or five. In a configuration including three main grooves, the first inner main groove **23** and the second inner main groove **25** are, in the example illustrated in FIG. **2**, substituted by one circumferential main groove passing over the tire centerline CL.

(24) The tread pattern according to the example illustrated in FIG. **2** further includes narrow grooves **31**, **33** as two circumferential narrow grooves extending in the tire circumferential direction. The narrow grooves **31**, **33** each have a smaller groove width than the main grooves **21**, **23**, **25**, **27**. The narrow grooves **31**, **33** each have a smaller groove depth than the main grooves **21**, **23**, **25**, **27**. The groove depths of the narrow grooves **31**, **33** are, for example, from 1.0 to 5.0 mm and the groove widths of the narrow grooves **31**, **33** are, for example, from 0.8 to 3.0 mm.

(25) The narrow groove **31** is provided in a shoulder region **77** of the tread pattern on an outer side of the first outer main groove **21** in the tire width direction.

(26) The narrow groove **33** is provided in a first middle region (first region) **71** between the first outer main groove **21** and the first inner main groove **23**. The narrow groove **33** is located, within the first middle region **71**, on a first inner main groove **23** side of the center in the tire width direction of the first middle region **71**.

(27) According to an embodiment, the circumferential narrow groove is preferably not provided in a second middle region **75** and a center region **73**, which are described below. In the tread pattern according to the example illustrated in FIG. **2**, the circumferential narrow groove is not provided in a shoulder region **79**, which is described below.

(28) The tread pattern according to the example illustrated in FIG. **2** further includes first sipes **51**, second sipes **55**, **57**, and third sipes **53**. The first sipes **51**, the second sipes **55**, **57**, and the third sipes **53** ensure edge components extending in the tire width direction, thus improving an edge effect against a force in a front-rear direction (direction parallel to the tire circumferential direction on a ground contact surface). Herein, sipe refers to a sipe having a sipe depth of, for example, from 2.0 to 7.5 mm and a sipe width of, for example, from 0.3 to 1.0 mm.

(29) A plurality of the first sipes **51** are provided at intervals in the tire circumferential direction in the first middle region **71**, communicate with the first outer main groove **21**, extend in the tire

width direction, and close within the first middle region **71**. According to an embodiment, the first sipes **51** may communicate with the first inner main groove **23** instead of with the first outer main groove **21**.

(30) A plurality of the second sipes **55** (second sipes A) are provided at intervals in the tire circumferential direction in the second middle region **75** between the second inner main groove **25** and the second outer main groove **27**, communicate with the second inner main groove **25**, extend in the tire width direction, and close within the second middle region **75**.

(31) A plurality of the second sipes **57** (second sipes B) are provided at intervals in the tire circumferential direction in the second middle region **75**, communicate with the second outer main groove **27**, extend in the tire width direction in the second middle region **75**, and close within the second middle region **75** without reaching the second inner main groove **25**.

(32) According to an embodiment, the second middle region **75** may include only either the second sipes **55** or the second sipes **57**.

(33) A plurality of the third sipes **53** are provided at intervals in the tire circumferential direction in the center region (third region) **73** between the first inner main groove **23** and the second inner main groove **25**, communicate with the first inner main groove **23**, extend in the tire width direction, and close within the center region **73**. According to an embodiment, the third sipes **53** may communicate with the second inner main groove **25** instead of with the first inner main groove **23**.

(34) In the present embodiment, the number of intervals **G2** of the second sipes **55**, **57** adjacent in the tire circumferential direction (hereinafter referred to as the interval **G2** of the second sipes **55**, **57**) is larger than the number of intervals **G1** of the first sipes **51** adjacent in the tire circumferential direction (hereinafter referred to as the interval **G1** of the first sipes **51**). The intervals of the sipes adjacent in the tire circumferential direction refers to intervals of positions where lines extending the sipes along the shape of the sipes extending on the tread surface intersect the groove wall of the main groove in communication with the sipes (hereinafter the communicating positions), the positions being adjacent in the tire circumferential direction. Two adjacent communicating positions may be located in the same main groove or in different main grooves. Thus, the intervals between second middle sipes having the communicating positions at the same positions in the tire circumferential direction in the region are not included in the “intervals of the sipes adjacent in the tire circumferential direction”.

(35) In the present embodiment, the first middle region **71** and the second middle region **75** include the sipes **51**, **55**, **57**, and this reduces groove volume and improves noise performance, compared to a configuration in which the same include lug grooves instead of the sipes **51**, **55**, **57**. On the other hand, the first middle region **71** including the narrow grooves **33** compensates for degradation of drainage properties, which is caused by the inclusion of the sipes **51** instead of the lug grooves, and suppresses degradation of steering stability on wet road surfaces (wet performance). Additionally, in the second middle region **75**, as described above, the number of intervals **G2** of the second sipes **55**, **57** is larger than the number of intervals **G1** of the first sipes **51**, and this reduces the rigidity of the land portion of the second middle region **75** and makes the same easily deformable and more likely to follow road surface. Thus, in the second middle region **75**, adhesion friction with road surface is large, and the effect of suppressing degradation of wet performance increases. That is, compared to a configuration including lug grooves in place of the sipes **51**, **55**, **57**, the present embodiment suppresses degradation of wet performance while improving noise performance. In the present embodiment, the two middle regions **71**, **75** differ in shape and exhibit different functions with respect to wet performance, and this yields the effect of suppressing degradation in wet performance. Thus, in the present embodiment, the tread pattern is asymmetric with respect to the tire centerline **CL**.

(36) Here, in a configuration in which the number of intervals **G2** of the second sipes **55**, **57** is equal to the number of intervals **G1** of the first sipes **51**, or is less than the number of intervals **G1**

of the first sipes **51**, the rigidity of the second middle region **75** is too high, the land portion is not easily deformed, and followability to road surface is not high. Thus, a force to grip road surface by variation in the force received from road surface is insufficient. According to an embodiment, the number of intervals **G2** of the second sipes **55**, **57** is preferably from 1.5 to 2.5 times the number of intervals **G1** of the first sipes **51**, and more preferably from 1.8 to 2.2 times. Further, according to an embodiment, the average of the intervals **G2** of the second sipes **55**, **57** in the second middle region **75** is preferably smaller than the average of the intervals **G1** of the first sipe **51** in the first middle region **71**.

(37) The tread pattern according to the example illustrated in FIG. 2 further includes shoulder lug grooves **58**, **59**.

(38) A plurality of the lug grooves **58** are disposed at intervals in the tire circumferential direction in the shoulder region **77** on an outer side in the tire width direction of the first outer main groove **21**, extend in the tire width direction from the outer side in the tire width direction toward the first outer main groove **21** within an outer region **77A**, in the shoulder region **77**, located on an outer side of the narrow groove **31** in the tire width direction, intersect the narrow groove **31**, and close within an inner region **77B** between the narrow groove **31** and the main groove **21** without reaching the first outer main groove **21**.

(39) A plurality of the lug grooves **59** are disposed at intervals in the tire circumferential direction in a shoulder region **79** on an outer side in the tire width direction of the second outer main groove **27**, extend in the tire width direction from the outer side in the tire width direction toward the main groove **27** within the shoulder region **79**, and close within the region **79** without reaching the main groove **27**.

(40) Note that the regions **77B**, **79** include ground contact edges **E** in the tire width direction. “Ground contact edges” refer to two ends in the tire width direction of a ground contact surface where the tire **10** mounted on a regular rim, inflated to a regular internal pressure, and loaded with 88% of a regular load is brought into contact with a horizontal surface. “Regular rim” refers to a “measurement rim” defined by the Japan Automobile Tyre Manufacturers Association Inc.

(JATMA), a “Design Rim” defined by the Tire and Rim Association, Inc. (TRA), or a “Measuring Rim” defined by the European Tyre and Rim Technical Organisation (ETRTO). “Regular internal pressure” refers to a “maximum air pressure” defined by JATMA, a maximum value in “TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES” defined by TRA, or “INFLATION PRESSURES” defined by ETRTO. “Regular load” refers to a “maximum load capacity” defined by JATMA, a maximum value in “TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES” defined by TRA, or a “LOAD CAPACITY” defined by ETRTO.

(41) The shoulder lug grooves **58**, **59** include closed ends **58a**, **59a** of the shoulder lug grooves **58**, **59**, and main groove side portions **58b**, **59b**, which are located on an outer main groove **21** side and an outer main groove **27** side, respectively, of the ground contact edges **E**, extend at an incline with respect to the tire width direction.

(42) According to an embodiment, the tread pattern preferably does not include lug grooves in the first middle region **71** that communicate with at least one of the first outer main groove **21** and the first inner main groove **23** and extend in the tire width direction, or lug grooves in the second middle region **75** that communicate with at least one of the second outer main groove **27** and the second inner main groove **25** and extend in the tire width direction. Accordingly, groove volume decreases and tire noise performance improves. According to a further embodiment, the tread pattern preferably does not include lug grooves in the center region **73** that communicate with at least one of the first inner main groove **23** and the second inner main groove **25** and extend in the tire width direction. Lug groove is a groove having a component extending in the tire width direction and having a groove width of 1.5 mm or more.

(43) According to an embodiment, the second sipes preferably include, as in the example illustrated in FIG. 2, the second sipes **55** (second sipes A) communicating with the second inner main groove

25 and the second sipes 57 (second sipes B) having communicating positions with the second outer main groove 27 in the tire circumferential direction that are different from communicating positions between the second sipes 55 and the second inner main groove 25. Thus, in a configuration in which the second middle region 75 includes both the sipes communicating with the second inner main groove 25 and the sipes communicating with the second outer main groove 27, the balance of the rigidity of the land portion in the second middle region 75 in the tire width direction improves, and the land portion can easily follow various changes in the force received from road surface. The percentage of the number of second sipes 55 and second sipes 57 to the total number of second sipes is preferably from 20 to 80%, and is more preferably from 30 to 70%.

(44) In this embodiment, according to a further embodiment, the second sipes 57 are disposed one by one between the second sipes 55 adjacent in the tire circumferential direction. Accordingly, the balance of the rigidity in the tire width direction of the land portion of the second middle region 75 particularly improves. The percentages described above are preferably 50% each.

(45) In an embodiment in which a length L1 is a length along the tire circumferential direction between two communicating positions at which two second sipes 55 adjacent in the tire circumferential direction each communicate with the second inner main groove 25, the communicating positions of the second sipes 57 with the second outer main groove 27, as illustrated in FIG. 2, are preferably within the range of from 50 to 97% of the length L1 from one of the two communicating positions (first side in FIG. 2), and more preferably within the range of from 70 to 95% thereof. This increases an effect of reducing tire noise. Note that the one of the two communicating positions refers to a communicating position of the second sipe 55 with the second inner main groove 25, the second sipe 55 including a closed end within the range in the tire circumferential direction between the two communicating positions.

(46) In these embodiments, according to a further embodiment, the direction connecting two ends of the second sipe 55 in the extension direction thereof and the direction connecting two ends of the second sipe 57 in the extension direction thereof are preferably inclined, as a direction from one end to the other in the tire width direction, toward the same side in the tire circumferential direction with respect to the tire width direction. This can suppress, in the second middle region 75, concentration of locations where the rigidity of the land portion is low. In the example illustrated in FIG. 2, the two directions are inclined to a first side (upper side in FIG. 2) in the tire circumferential direction with respect to the tire width direction. According to a further embodiment, the first sipe 51 and the second sipes 55, 57 preferably have the relationship, described above, of being inclined to the same side, and more preferably the first sipe 51, the third sipe 53, and the second sipes 55, 57 have the relationship, described above, of being inclined to the same side.

(47) According to an embodiment, the lengths of the intervals G2 of the second sipes 55, 57 are preferably different between the intervals adjacent in the tire circumferential direction. FIG. 2 illustrates a plurality of the intervals G2 having different lengths. This yields the effect of dispersing the frequency of pattern noise, contributing to improving noise performance.

(48) According to an embodiment, the first sipes 51 are preferably connected to the narrow groove 33. This increases the drainage properties in the first middle region 71.

(49) In this embodiment, according to a further embodiment, as illustrated in FIG. 3, a sipe depth D51c of a narrow groove side connection portion 51c of the first sipe 51, the narrow groove side connection portion connecting to the narrow groove 33, is smaller than a groove depth D33 of the narrow groove 33, and a sipe depth D51b of an intermediate portion 51b of the first sipe 51, the intermediate portion being located between the first outer main groove 21, which communicate with the first sipe 51, and the narrow groove side connection portion 51c, is greater than the groove depth D33 of the narrow groove 33. The narrow groove side connection portion 51c having a such raised bottom portion can suppress a decrease in rigidity at the connection position of the first sipe 51 with the narrow groove 33. Further, the intermediate portion 51b of the first sipe 51 is deeper

than the narrow groove **33**, and this improves the water absorbency of the first sipe **51** and contributes to improving wet performance. FIG. **3** is a diagram illustrating a cross-section of a region, in the tire width direction, of the first middle region **71**, which is along the extension direction of the first sipe **51**. FIG. **3** omits a third chamfered surface, which is described below.

(50) In these two embodiments, according to a further embodiment, a sipe depth **D51a** of a main groove side communicating portion **51a**, of the first sipe **51**, the main groove side communicating portion communicating with the first outer main groove **21**, is preferably smaller than the groove depth **D33** of the narrow groove **33**. The main groove side communicating portion **51a** having such a raised bottom portion can suppress a decrease in the rigidity in the communicating position of the first sipe **51** with the first outer main groove **21**.

(51) According to an embodiment, the sipe depth **D51c** of the narrow groove side connection portion **51c** and the sipe depth **D51a** of the main groove side communicating portion **51a** are preferably from 20 to 50% of the sipe depth **D51b** of the intermediate portion **51b**, and more preferably from 30 to 40% thereof.

(52) According to an embodiment, a groove depth **D21** of the first outer main groove **21**, the sipe depth **D51b** of the intermediate portion **51b**, the groove depth **D33** of the narrow groove **33**, and the sipe depths **D51c**, **D51a** of the narrow groove side connection portion **51c** and the main groove side communicating portion **51a** preferably become smaller in this order. That is, $D21 > D51b > D33 > D51c$, **D51a** is preferable. **D51c** and **D51a** may be different from each other, but are preferably equal.

(53) According to an embodiment, the first sipe **51** preferably extends in a curved shape so as to bulge roundly to one side in the tire circumferential direction in the tread surface. This suppresses movement, in the first middle region **71**, of portions on two sides of the first sipe **51** in the tire circumferential direction to be displaced from each other in the tire width direction when a lateral force is applied, and this contributes to improving wet performance. In the example illustrated in FIG. **2**, the first sipe **51** extends so as to form an arc shape that bulges, on the tread surface, to a first side in the tire circumferential direction. The radius of curvature of the arc shape of the first sipe **51** is preferably from 50 to 150 mm.

(54) On the other hand, according to an embodiment, the second sipes **55**, **57** and the third sipes **53** preferably extend in a straight line on the tread surface.

(55) In this case, according to a further embodiment, the length of the first sipe **51** in the extension direction thereof is preferably greater than the lengths of the second sipes **55**, **57** in the extension directions thereof. The number of first sipes **51** is smaller than the total number of second sipes **55**, **57**, and such an embodiment contributes to improving the balance of the rigidity of the first middle region **71** and the second middle region **75**. Also, this facilitates adjustment of the rigidity of the first middle region **71** to a level between the rigidity of the second middle region **75** and that of the center region **73**. Note that, according to an embodiment, the length of the first sipe **51** in the extension direction thereof is preferably greater than the length of the third sipe **53** in the extension direction thereof (for example, from 115 to 125% of the length of the third sipe **53** in the extension direction thereof).

(56) According to an embodiment, the second sipes **55**, **57** each extend in a straight line, and the inclination angle, with respect to the tire width direction, of the direction connecting two ends of the extension direction of the second sipe **55** is preferably different between the second sipes **55** adjacent in the tire circumferential direction and the inclination angle, with respect to the tire width direction, of the direction connecting two ends of the extension direction of the second sipe **57** is preferably different between the second sipes **57** adjacent in the tire circumferential direction.

(57) According to an embodiment, the number of intervals **G2** of the second sipes **55** and the number of intervals **G2** of the second sipes **57** is preferably larger than the number of intervals **G3** of the third sipes **53** adjacent in the tire circumferential direction (hereinafter referred to as the intervals **G3** of the third sipes **53**). That is, the number of intervals **G3** of the third sipes **53** is

preferably smaller than the number of intervals G2 of the second sipes 55, 57. The center region 73 has, in the tread portion, the longest ground contact length in the tire circumferential direction, and thus a ground contact area with the road surface is preferably ensured according to the embodiment described above. According to an embodiment, the number of intervals G2 of the second sipes 55, 57 is preferably from 1.5 to 2.5 times the number of intervals G3 of the third sipes 53, and more preferably from 1.8 to 2.2 times the number of same.

(58) In this case, according to a further embodiment, the length of the second sipe 55 and the length of the second sipe 57 in the tire width direction are preferably from 20 to 50% of the length of the second middle region 75 in the tire width direction, and more preferably from 30 to 40% of the same, and the length of the third sipe 53 in the tire width direction is from 20 to 50% of the length of the center region 73 in the tire width direction, and more preferably from 30 to 40% of the same. This can suppress an excessive decrease in the rigidity of the second middle region 75 and of the center region 73.

(59) According to an embodiment, the tread pattern preferably has a vehicle mounting orientation designated such that the second half-tread region is disposed on a vehicle outer side (“out” side illustrated in FIG. 2) of the first half-tread region. In an embodiment in which the second half-tread region, which has a smaller groove area ratio than the first half-tread region, is disposed on the vehicle outer side, noise performance improves.

(60) Chamfered Surface

(61) According to an embodiment, the tread pattern preferably includes any one of a first chamfered surface 81, second chamfered surfaces 85, 87, and a third chamfered surface 83, which correspond to the first sipe 51, the second sipes 55, 57, and the third sipe 53, respectively.

(62) An end portion in the tire width direction of the first sipe 51, which communicates with the first outer main groove 21, is adjacent in the tire circumferential direction to portions of a land portion. The first chamfered surface 81 is a surface having a tread surface of one of the portions of the land portion inclined toward the first outer main groove 21. A plurality of the first chamfered surfaces 81 are provided in the tire circumferential direction, and the first sipes 51 open thereto without reaching the groove wall of the first outer main groove 21.

(63) An end portion in the tire width direction of the second sipe 55, which communicates with the second inner main groove 25, is adjacent in the tire circumferential direction to portions of a land portion. The second chamfered surface 85 is a surface having a tread surface of one of the portions of the land portion inclined toward the second inner main groove 25. A plurality of the second chamfered surfaces 85 are provided in the tire circumferential direction, and the second sipes 55 open thereto without reaching the groove wall of the second inner main groove 25.

(64) An end portion in the tire width direction of the second sipe 57, which communicates with the second outer main groove 27, is adjacent in the tire circumferential direction to portions of a land portion. The second chamfered surface 87 is a surface having a tread surface of one of the portions of the land portion inclined toward the second outer main groove 27. A plurality of the second chamfered surfaces 87 are provided in the tire circumferential direction, and the second sipes 57 open thereto without reaching the groove wall of the second outer main groove 27.

(65) An end portion in the tire width direction of the third sipe 53, which communicates with the first inner main groove 23, is adjacent in the tire circumferential direction to portions of a land portion. The third chamfered surface 83 is a surface having a tread surface of one of the portions of the land portion inclined toward the first inner main groove 23. A plurality of the third chamfered surfaces 83 are provided in the tire circumferential direction, and the third sipes 53 open thereto without reaching the groove wall of the first inner main groove 23.

(66) According to an embodiment, the chamfered surfaces 81, 83, 85, 87 are preferably greater in length in the tire circumferential direction than in the tire width direction. This embodiment includes the sipes 51, 53, 55, 57 in the first middle region 71, the center region 73, and the second middle region 75 and thus has a smaller groove volume and a more excellent noise performance

than a configuration including lug grooves instead of the sipes **51, 53, 55, 57**. On the other hand, the embodiment includes any one of the chamfered surfaces **81, 83, 85, 87** in the first middle region **71**, the center region **73**, and the second middle region **75**, and thus has more edge components and a larger edge effect than a configuration not including the chamfered surface. This suppresses a decrease in wet performance due to a decrease in drainage properties, with the sipes **51, 53, 55, 57** provided instead of the lug grooves. Further, as described above, the sipes **51, 53, 55, 57** provided ensure edge components that exert an effect on the force in the front-rear direction (tire circumferential direction), and thus with the length in the tire circumferential direction of each of the chamfered surfaces **81, 83, 85, 87** being longer than the length in the tire width direction thereof, edge components that exhibit an effect on a force in a front-rear direction can be ensured, edge components that exhibit an effect on a lateral force can also be ensured, and the effect of improving wet performance with respect to the forces, in various directions, received from the road surface can be obtained. This increases the effect of suppressing a decrease in wet performance. That is, this embodiment, compared to an embodiment including the lug grooves instead of the sipes **51, 53, 55, 57**, suppresses a decrease in wet performance while improving noise performance. Note that this embodiment, which includes at least one of the chamfered surfaces **81, 83, 85, 87** in the first middle region **71**, the center region **73**, and the second middle region **75**, has a larger groove volume than an embodiment without the chamfered surfaces, and makes less of a difference in the groove volume and has less of an effect on noise performance than, for example, an embodiment including notches (the Length in the extension direction is relatively short).

(67) According to an embodiment, the sipes **51, 53, 55, 57** open to the chamfered surfaces **81, 83, 85, 87**, respectively, and the length of each of the chamfered surfaces **81, 83, 85, 87** in the tire circumferential direction is preferably from 5 to 50% of the length of the interval between a corresponding one of pairs of the sipes **51, 53, 55, 57**, each of the pairs being adjacent in the tire circumferential direction. The chamfered surfaces **81, 83, 85, 87** that are longer in the tire circumferential direction than this percentage are likely to degrade noise performance due to an increase in the groove volume, and may have an adverse effect on wet performance due to a decrease in the rigidity of the land portions. Further, the chamfered surfaces **81, 83, 85, 87** that are smaller in the tire circumferential direction than this percentage lessen the effect of improving wet performance.

(68) According to an embodiment, the ratio of the length of each of the chamfered surfaces **81, 83, 85, 87** in the tire width direction to the length thereof in the tire circumferential direction is preferably larger than 1, and 10 or less, and more preferably 1.5 or more and 8 or less.

(69) According to an embodiment, the length in the tire circumferential direction of the first chamfered surface **81** and the length in the tire circumferential direction of the third chamfered surface **83** are preferably mutually different. Further, according to an embodiment, the lengths of the second chamfered surfaces **87, 85** in the tire circumferential direction are preferably mutually different. These embodiments can yield the effect of improving wet performance by the chamfered surfaces **81, 87**, which are longer in the tire circumferential direction and have edge components having an effect on a lateral force, and the effect of improving noise performance by the chamfered surfaces **83, 85**, which are shorter in the tire circumferential direction and reduce groove volume. The length in the tire circumferential direction of the chamfered surface having the longest length in the tire circumferential direction, of the chamfered surfaces having different lengths in the tire circumferential direction, is preferably from 1.2 to 3 times, and more preferably from 1.5 to 2 times, the length in the tire circumferential direction of the chamfered surface having the shortest length in the tire circumferential direction.

(70) According to an embodiment, the length in the tire circumferential direction of the first chamfered surface **81**, which is farther from the tire centerline CL, than the third chamfered surface **83**, is preferably greater than the length in the tire circumferential direction of the third chamfered surface **83**, which is closer to the tire centerline CL than the first chamfered surface **81**. Further,

according to an embodiment, the length in the tire circumferential direction of the second chamfered surface **87**, which is farther from the tire centerline CL than the second chamfered surface **85**, is preferably greater than the length in the tire circumferential direction of the second chamfered surface **85**, which is closer to the tire centerline CL than the second chamfered surface **87**. In these embodiments, the effect of improving wet performance is larger in a region farther from the tire centerline CL, and the effect of improving noise performance is larger in a region at or near the tire centerline CL, and thus noise performance improves, and the effect of suppressing a decrease in wet performance can be effectively obtained.

(71) According to an embodiment, the ranges in the tire circumferential direction where the first chamfered surface **81** and the third chamfered surface **83** are located preferably do not overlap each other. According to another embodiment, the ranges in the tire circumferential direction where the second chamfered surfaces **85**, **87** are located preferably do not overlap each other. According to yet another embodiment, the ranges in the tire circumferential direction where the chamfered surfaces **81**, **83**, **85**, **87** are located preferably do not overlap each other. Thus, the chamfered surfaces **81**, **83**, **85**, **87** are dispersed in the tire circumferential direction, and the effects of each of the chamfered surfaces **81**, **83**, **85**, **87** on noise performance can be dispersed.

(72) According to an embodiment, the maximum depths of the chamfered surfaces **81**, **83**, **85**, **87** are preferably greater than the depths (maximum depths) of the Sipes **51**, **53**, **55**, **57**, respectively, which open to the chamfered surfaces **81**, **83**, **85**, **87**, respectively. The chamfered surfaces **81**, **83**, **85**, **87** are inclined toward the main grooves **21**, **23**, **25**, **27**, respectively, and are deepest at the groove walls of the main grooves **21**, **23**, **25**, **27**, respectively. FIG. 3 illustrates a maximum depth **D81** of the chamfered surface **81**. FIG. 3 is a diagram illustrating a cross-section of a region between the first outer main groove **21** and the narrow groove **33**. The maximum depths of the chamfered surfaces **81**, **83**, **85**, **87** are thus greater than the depths of the sipes **51**, **53**, **55**, **57**, respectively, and the sipes **51**, **53**, **55**, **57**, as illustrated in FIG. 4, do not reach the groove walls of the main grooves **21**, **23**, **25**, **27**, respectively, open to the chamfered surfaces **81**, **83**, **85**, **87**, respectively, and close within the chamfered surfaces **81**, **83**, **85**, **87**, respectively. That is, the sipes **51**, **53**, **55**, **57**, though not connected (directly open) to the main grooves **21**, **23**, **25**, **27**, respectively, are open to the chamfered surfaces **81**, **83**, **85**, **87**, respectively, as described above, and are thus in communication with the main grooves **21**, **23**, **25**, **27**, respectively, FIG. 4 illustrates an embodiment of the chamfered surfaces **81**, **83** as representing the chamfered surfaces **81**, **83**, **85**, **87**. In an embodiment in which the sipes **51**, **53**, **55**, **57** are not connected to the main grooves **21**, **23**, **25**, **27**, respectively, in contrast to an embodiment in which the sipes **51**, **53**, **55**, **57** are connected to the main grooves **21**, **23**, **25**, **27**, respectively, too much deformation of the land portion due to a decrease in rigidity is suppressed, and an appropriate rigidity of the land portions is obtained. Such an embodiment contributes to improving wet performance.

(73) According to an embodiment, the maximum depths of the chamfered surfaces **81**, **83**, **85**, **87** are preferably equal to each other.

(74) According to an embodiment, a tire circumferential direction side where the first chamfered surface **81** is located with respect to the first sipe **51** (second side in FIG. 2) is preferably the same side as a tire circumferential direction side where the third chamfered surface **83** is located with respect to the third sipe **53** (second side in FIG. 2). Further, according to an embodiment, a tire circumferential direction side where the second chamfered surface **85** is located with respect to the second sipe **55** (second side in FIG. 2) is preferably opposite a tire circumferential direction side where the second chamfered surface **87** is located with respect to the second sipe **57** (first side in FIG. 2).

(75) According to an embodiment, as illustrated in FIG. 4, the chamfered surfaces **81**, **83**, **85**, **87** preferably each have a substantially triangular shape that decreases in length in the tire width direction from one side in the tire circumferential direction to the other side. This can minimize the effect of the chamfered surfaces **81**, **83**, **85**, **87** on noise performance. The apexes of the triangle of

the substantially triangular shape are located in the groove wall of the main groove, on the ground contact surface of the land portion in contact with the groove wall, and at the boundary between the ground contact surface and the groove wall.

(76) According to an embodiment, each of the sipes **51, 53, 55, 57** preferably opens to a portion of a corresponding one of the chamfered surfaces **81, 83, 85, 87**, the portion being where the chamfered surface is longest in the tire width direction (a portion that forms an apex of a substantially triangular shape in FIG. 4).

(77) According to an embodiment, each of the sipes **51, 53, 55, 57** preferably has a raised bottom portion (main groove side communicating portion) at an opening end portion thereof that opens to a corresponding one of the chamfered surfaces **81, 83, 85, 87**, the raised bottom portion being shallower than the maximum depth of a corresponding one of the sipes **51, 53, 55, 57**. An embodiment in which the sipes **51, 53, 55, 57** are not connected to the main grooves **21, 23, 25, 27** increases the effect of obtaining the appropriate rigidity of the land portions.

(78) According to an embodiment, as illustrated in FIG. 4, the tread pattern includes, in the land portion of each of the first middle region **71**, the center region **73**, and the second middle region **75**, a wall surface of the land portion adjacent to a corresponding one of the chamfered surfaces **81, 83, 85, 87**. The wall surface of the land portion is provided from an opening end portion of a corresponding one of the sipes **51, 53, 55, 57**, to which the chamfered surfaces **81, 83, 85, 87** are inclined respectively, to the wall surface of a corresponding one of the main grooves **21, 23, 25, 27** and continuously extends from the wall surface of a corresponding one of the sipes **51, 53, 55, 57**. FIG. 4 illustrates wall surfaces **82, 84** as representing the wall surface. The wall surfaces preferably each extend without being inclined with respect to the tire radial direction. This reduces groove volume and contributes to improving noise performance, compared to an embodiment in which the wall surfaces are inclined with respect to the tire radial direction. This also improves the effect of cutting water film and contributes to improving wet performance, compared to an embodiment in which the wall surfaces are inclined with respect to the tire radial direction.

(79) According to an embodiment, the wall surface preferably extends along the extension direction of each of the sipes **51, 53, 55, 57**, which open to the chamfered surfaces **81, 83, 85, 87**, respectively. In an embodiment in which the wall surfaces extend away from the chamfered surfaces **81, 83, 85, 87** with respect to the extension directions of the sipes **51, 53, 55, 57**, respectively (such that the inclination angles with respect to the tire width direction increase), edge components that have an effect on a lateral force may decrease, and the effect of suppressing a decrease in wet performance may decrease.

(80) According to an embodiment, the inclination angles of the sipes **51, 53, 55, 57** with respect to the tire width direction are preferably 45 degrees or less. The edge components that have an effect on a lateral force are ensured by the chamfered surfaces **81, 83, 85, 87**, and the edge effect can be enhanced with respect to a force in a front-rear direction by reducing the inclination angles of the sipes **51, 53, 55, 57**. The inclination angles are preferably from 10 to 35 degrees.

(81) According to an embodiment, the tread pattern preferably further includes a chamfered surface **89** where the tread surface is inclined toward the narrow groove **33** at an end portion in the tire width direction on a narrow groove **33** side of the region **71A** including the first sipes **51**, the region **71A** being one of two regions divided by the narrow groove **33** in the tire width direction in the first middle region **71**. A plurality of the chamfered surfaces **89** are provided in the tire circumferential direction, and are each connected to the sipe wall surface of the first sipe **51** at a connection end portion with the narrow groove **33**. According to an embodiment, the maximum depth of the chamfered surface **89** is preferably smaller than the depth of the first sipe **51**.

(82) According to an embodiment, the length of the chamfered surface **89** in the tire circumferential direction is preferably shorter than the lengths of the chamfered surfaces **81, 83, 85, 87** in the tire circumferential direction.

(83) According to an embodiment, the chamfered surface **81** and the chamfered surface **89** are

preferably located on opposite sides of the first sipe **51** in the tire circumferential direction (second side and first side in FIG. 2).

(84) Extension Line

(85) According to an embodiment, as in the example illustrated in FIG. 5, the second sipes **55** preferably overlap each of a plurality of extension lines S. The second sipe **57** extends between two extension lines S adjacent in the tire circumferential direction, of the plurality of extension lines S, in a direction along the extension lines S. FIG. 5 is a diagram explaining the extension lines S. and illustrates two of the extension lines S in dashed lines.

(86) The extension lines S are imaginary lines extending a plurality of the shoulder lug grooves **59** from the closed ends **59a** of the plurality of the shoulder lug grooves **59** smoothly along an inclination direction of the main groove side portions **59h** toward closed ends **53a** of a plurality of the third sipes **53**. The main groove side portion **59b** is a portion of the shoulder lug groove **59** on a main groove **27** side, the portion including the closed end **59a**. The extension line S is a straight line, “Extending smoothly” means that, of angles formed at the closed end **59a** of the shoulder lug groove **59** between an inclination direction of the shoulder lug groove **59** with respect to the tire width direction and an extension direction of the extension line S, a smaller one is 10 degrees or less, and preferably 5 degrees or less, Of angles formed at the closed end **53a** of the third sipe **53** between an inclination direction of the third sipe **53** and an inclination direction of the extension line S, a smaller one is preferably 10 degrees or less, and more preferably 5 degrees or less. Still more preferably, the two directions are the same.

(87) That “second sipes **55** overlap the extension lines S” includes not only an embodiment in which the second sipes **55** each contact or intersect the extension line S but also an embodiment in which the second sipes **55** each contact or intersect a region twice as distant from the extension line S in a direction orthogonal to the extension line S as the groove width of the main groove side portion **59b** of the shoulder lug groove **59**. Further, that “second sipe **57** extends in a direction along the extension lines S” means that an inclination angle of the extension direction of the second sipe **57** with respect to the extension lines S is 10 degrees or less, preferably 5 degrees or less, and more preferably 0 degrees.

(88) Thus, the shoulder lug groove **59**, the second sipe **55**, and the third sipe **53** overlap the extension line S inclined with respect to the tire width direction, and so the shoulder lug groove **59**, the second chamfered surface **87**, and the second chamfered surface **85** are easily dispersed in the tire circumferential direction, contributing to improving noise performance.

(89) On the other hand, the second sipe **57** is disposed closer to the shoulder lug groove **59** than the third sipe **53** and the second sipe **55**. Accordingly, the second sipe **57** is disposed between two extension lines S adjacent in the tire circumferential direction, extending along the extension lines S, and thus does not overlap the extension lines S. Since the shoulder lug groove **59** has a large groove volume and generates a loud popping sound, the second sipe **57** and the shoulder lug groove **59** are preferably separated from each other in the tire circumferential direction.

(90) According to an embodiment, preferably, each of all the shoulder lug grooves **59** and the third sipes **53** forms an end in the extension direction of one of the plurality of extension lines S, and each of all the second sipes **55** overlaps one of the extension lines S, and each of all the second sipes **57** extends between one of pairs of the extension lines S adjacent in the tire circumferential direction. Accordingly, an effect of dispersing the second chamfered surface **85**, the second chamfered surface **87**, and the shoulder lug groove **59** at mutually different locations in the tire circumferential direction is obtained across an entire circumference in the tire circumferential direction, and an effect of improving noise performance increases.

(91) Further, according to an embodiment, the range of the second chamfered surface **85** along the tire circumferential direction preferably does not overlap the range of the shoulder lug groove **59** along the tire circumferential direction. The second chamfered surface **85** and the shoulder lug groove **59** being disposed at mutually different locations in the tire circumferential direction

contributes to improving noise performance.

(92) According to an embodiment, ranges in the tire circumferential direction of the extension lines S adjacent in the tire circumferential direction preferably do not overlap each other. An embodiment in which ranges of a couple of the extension lines S along the tire circumferential direction overlap each other is less likely to yield the effect of dispersing the chamfered surface **85**, the second chamfered surface **87**, and the shoulder lug groove **59** in the tire circumferential direction. Thus, the magnitude of the inclination angle of the extension line S with respect to the tire width direction is preferably from 10 to 30 degrees.

(93) Further, according to an embodiment, the third sipe **53**, the second sipe **55**, and the second sipe **57** preferably have substantially equal inclination angles with respect to the tire width direction. “Substantially equal” refers to a difference in the inclination angle between the sipes being up to 10 degrees, and preferably up to 5 degrees.

(94) According to an embodiment, the first sipe **51** preferably overlaps an imaginary straight line (second extension line) extending from a connection position of the third sipe **53** with the third inner main groove **23** to the outer side in the tire width direction (vehicle mounting inner side in FIG. 2) along the inclination direction of the third sipe **53** with respect to the tire width direction. That “first sipe **51** overlaps the second extension line” includes not only an embodiment in which the first sipe **51** contacts or intersects the second extension line but also an embodiment in which the first sipe **51** contacts or intersects a region located at a distance twice the groove width of the main groove side portion **58b** of the shoulder lug groove **58**, the distance being in a direction orthogonal to the second extension line from the second extension line.

(95) In the tread pattern according to the example illustrated in FIG. 2, no lug grooves and sipes communicating with or connected to the narrow groove **33** or the first inner main groove **23** are provided in the region **71B** between the narrow groove **33** and the first inner main groove **23**, and a rib extending continuously in the tire circumferential direction is formed therein. Additionally, no sipes connected to the narrow groove **31** or the main groove **21** are provided in the region **77B**, no lug grooves connected to the main groove **21** are provided in the region **77B**, and a rib extending continuously in the tire circumferential direction is formed therein. Thus, in a region, disposed on a vehicle inner side, of the tread pattern, two narrow grooves **31**, **33** form many edge components extending in the tire circumferential direction, and the rigidity of the two ribs is ensured. This increases steering stability by an inner ring during turning. Preferably, the length (width) of the region **77B** in the tire width direction is greater than the width of the region **71B**. The narrow groove **31** preferably has a wider groove width than the narrow groove **33**.

(96) The tread pattern of the present embodiment is not limited to the tread pattern according to the example illustrated in FIG. 2.

Comparative Examples and Examples

(97) To examine effects of a tire of the present embodiment, the tread pattern of the tire was varied, and wet performance and noise performance were examined. The prototype tires each had a size of 225/65R17, and except for specifications indicated in Table 1 and below, were based on the tread pattern illustrated in FIG. 2 and the cross-section profile illustrated in FIGS. 1 and 3, and based the chamfered surfaces and wall surfaces on the embodiment illustrated in FIG. 4.

(98) Table 1 indicates an embodiment related to the tread pattern of each of the tires and evaluation results thereof.

(99) “71=75” of “Number of sipe intervals of regions **71**, **75**” in Table 1 means that the number of intervals G1 in the first middle region **71** and the number of intervals G2 in the second middle region **75** are equal, whereas “71<75” means that the number of intervals G2 is larger than the number of intervals G1.

(100) In the “Arrangement configuration of second sipes **55**, **57**” row, “55 only” means that the second middle region **75** includes the second sipes **55** only and none of the second sipes **57**, whereas “alternate” means that the second sipes **55** and the second sipes **57** are disposed alternately

in the tire circumferential direction.

(101) “Displacement amount of second sipe **57** relative to second sipe **55**” indicates in percentage where the communicating position of the second sipe **57** with the second outer main groove is located in the interval L between the sipes **0.55** mutually adjacent, from the second sipe **55** adjacent to the second sipe **57** on the first side in the tire circumferential direction toward the second side.

(102) “Longitudinal/lateral lengths of chamfered surfaces **81, 83, 85, 87**” indicates a size relationship between the tire circumferential direction (longitudinal) length and the tire width direction (lateral) length of each of the chamfered surfaces **81, 83, 85, 87**.

(103) “Overlap of second sipe **55** and extension line” indicates whether the second sipe **55** overlaps the extension line S and the second sipe **57** extends between the extension lines S, with “overlapping” meaning an overlapping embodiment and “non-overlapping” meaning not such an embodiment.

(104) Examples including Example 5 in which “Overlap of second sipe **55** and extension line is “non-overlapping” have the same configuration as Example 6 in FIG. 2 except that the second middle region was displaced in the tire circumferential direction with respect to the center region and the shoulder region such that the second sipe **55** did not overlap the extension line S and the second sipe **57** overlapped the extension line S.

(105) Example 5 has the same configuration as Example 4 except that the chamfered surfaces **81, 83, 85, 87** are three times greater in length in the tire circumferential direction than in the tire width direction. Note that in examples including Example 4 in which in “Longitudinal/lateral lengths of chamfered surfaces **81, 83, 85, 87**”, “longitudinal=lateral”, the lengths of the chamfered surfaces **81, 83, 85, 87** in the tire circumferential direction and in the tire width direction were each set to a length of 5% of the interval between a corresponding one of pairs of the sipes **51, 53, 55, 57** adjacent in the tire circumferential direction, the sipes **51, 53, 55, 57** opening to the chamfered surfaces **81, 83, 85, 87**. In Comparative Examples and Examples, the maximum depths of the chamfered surfaces **81, 83, 85, 87** were deeper than the maximum depths of the sipes **51, 53, 55, 57** that opened to the chamfered surfaces **81, 83, 85, 87**, respectively.

(106) In Comparative Example 2 and Examples 1 to 3, the length of the first sipe **51** in the extension direction thereof was set to 80% of the length of the region **71A** in the width direction.

(107) Example 1 has the same configuration as Example 2 except that the second sipes **57** were omitted and that the same number of second sipes **55** as the number of second sipes **57** omitted were added.

(108) In Comparative Example 2, the number of second sipes **55** was set to half that in Example 1. In Examples 1 to 6, the number of intervals G2 was set to twice the number of intervals G1.

(109) Comparative Example 1 has the same configuration as Comparative Example 2 except that the sipes **51, 53, and 55** were replaced with lug grooves.

(110) In Comparative Examples and Examples, the inclination angles, with respect to the tire width direction, of the lug grooves and sipes in the first middle region **71**, the center region **73**, and the second middle region **75** were set to from 20 to 30 degrees. Further, the magnitude of the inclination angle of the extension line S with respect to the tire width direction was set to from 20 to 30 degrees.

(111) Each of these test tires was assembled on a vehicle such that the second half-tread region was disposed in a vehicle outer side of the first half-tread region, and evaluated for noise performance and wet performance as described below. The results of the evaluation are indicated in Tables 1 and 2. In the evaluation, each of the test tires was mounted on a wheel having a rim size of 17×7J, mounted on a front wheel drive vehicle of engine displacement of 2400 cc, and inflated to an air pressure of 230 kPa.

(112) Noise Performance

(113) Each test tire was measured for pass-by noise outside of a vehicle in accordance with the European noise regulation conditions (ECE R117). The evaluation results were expressed as index

values by using reciprocals of measurement values, with Comparative Example 1 being assigned as the reference **100**. Larger index values mean excellent noise performance.

(114) Wet Performance

(115) Running at a speed of from 40 to 100 km/hr was performed on a test course of an asphalt road surface sprayed with water having a depth of less than 1 mm, and a test driver performed sensory evaluation on steering characteristics when changing lanes and when cornering, and on stability when traveling straight. Wet performance is expressed as index values with Comparative Example 1 used as a tire according to the related art and assigned as the reference **100**. Larger index values indicate excellent wet performance.

(116) The allowable range of the index value of noise performance for each of the tires having the size of 225/65R17 was evaluated to be 103 or more, and that of the index value of wet performance for the same was evaluated to be 97 and more, and a case meeting these conditions was evaluated to have succeeded in suppressing a decrease in wet performance while improving noise performance.

(117) TABLE-US-00001

TABLE 1	Comparative Example 1	Example 2	Example 1
Lug groove or sipe	Lug groove	Sipe	Sipe
Number of sipe intervals of	—	71 = 75	71 < 75
71, 75 regions	71, 75	Arrangement configuration	—
55 only	55 only	Alternate of second sipes	55, 57
Displacement amount (%)	—	—	—
50 of second sipe	57 with respect to second sipe	55	Presence of connection of
Non-	Non-	Non-	first sipe
51 and narrow connected	connected	groove	33
Longitudinal/lateral lengths	Longitudinal =	Longitudinal =	Longitudinal =
Longitudinal =	of chamfered surfaces	81, lateral	lateral
lateral	lateral	lateral	lateral
83, 85, 87	Overlap of second sipe	55	—
—	—	Non-	and extension line overlapping
Noise performance	100	110	108
108	Wet performance	100	95
98	102	Example 3	Example 4
Example 5	Example 6	Lug groove or sipe	Sipe
Sipe	Sipe	Sipe	Number of sipe intervals of
71 < 75	71 < 75	71 < 75	71 < 75
regions	71, 75	Arrangement configuration	Alternate
Alternate	Alternate	Alternate	Alternate of second sipes
55, 57	Displacement amount (%)	95	95
95	95	95	95
of second sipe	57 with respect to second sipe	55	Presence of connection of
Non-	Connected	Connected	Connected
first sipe	51 and narrow connected	groove	33
Longitudinal/lateral lengths	Longitudinal =	Longitudinal =	Longitudinal >
Longitudinal >	of chamfered surfaces	81, lateral	lateral
lateral	lateral	lateral	lateral
83, 85, 87	Overlap of second sipe	55	Non-
Non-	Non-	Non-	Overlapping and extension line overlapping
overlapping	overlapping	overlapping	overlapping
Noise performance	110	110	108
110	Wet performance	103	105
107	109		

(118) A comparison between Comparative Example 1 and Example 1 reveals that a configuration including the first sipes and the second sipes, and more intervals of the first sipes than those of the second sipes can suppress a decrease in wet performance while improving noise performance.

(119) A comparison between Comparative Example 2 and Example 1 reveals that a configuration including more intervals of the second sipes than those of the first sipes improves wet performance.

(120) A comparison between Example 1 and Example 2 reveals that a configuration including the second sipes **55** and the second sipes **57** alternately in the tire circumferential direction improves wet performance.

(121) A comparison between Example 2 and Example 3 reveals that in a configuration in which “Displacement amount of second sipe **57** relative to second sipe **55**” is set to a value other than 50% and the intervals of the second sipes have a plurality of lengths, noise performance improves.

(122) A comparison between Example 3 and Example 4 reveals that a configuration including the first sipes connected to the narrow groove **33** improves wet performance.

(123) A comparison between Example 4 and Example 5 reveals that in a configuration in which the chamfered surfaces **81, 83, 85, 87** are greater in length in the tire circumferential direction than in the tire width direction, wet performance improves.

(124) A comparison between Example 5 and Example 6 reveals that in a configuration in which the second sipe **55** overlaps the extension line S and the second sipe **57** extends between the extension lines **5**, noise performance improves.

(125) Although the tire according to an embodiment of the present technology has been described above in detail, the tire according to an embodiment of the present technology is not limited to the embodiments or examples that have been described above, and may of course be enhanced or modified in various ways without departing from the scope of the present technology.

Claims

1. A tire comprising a tread pattern on a surface of a tread portion that contacts a road surface, the tread pattern comprising: a pair of first circumferential main grooves provided in a first half-tread region on one side of a tire centerline in a tire width direction, extending in a tire circumferential direction, and disposed at intervals from each other in the tire width direction; a pair of second circumferential main grooves provided in a second half-tread region on an other side in the tire width direction, extending in the tire circumferential direction, and disposed at intervals from each other in the tire width direction; a plurality of first sipes provided in a first region between the first circumferential main grooves, communicating with one of the first circumferential main grooves, extending in the tire width direction, and closing within the first region; a circumferential narrow groove having a groove width smaller than a groove width of the first circumferential main grooves and extending in the tire circumferential direction within the first region; and a plurality of second sipes provided in a second region between the second circumferential main grooves, communicating with one or an other of the second circumferential main grooves, extending in the tire width direction, and closing within the second region, and a number of intervals of the second sipes adjacent in the tire circumferential direction being larger than a number of intervals of the first sipes adjacent in the tire circumferential direction; wherein each sipe of the plurality of first sipes and the plurality of second sipes has a sipe width in a range of from 0.3 mm to 1.0 mm, and the second sipes comprise a second sipe A and a second sipe B, the second sipe A communicating with one of the second circumferential main grooves and the second sipe B communicating with an other of the second circumferential main grooves at a location, in the tire circumferential direction, which is different from a location, in the tire circumferential direction, where the second sipe A communicates with the one of the second circumferential main grooves.
2. The tire according to claim 1, wherein the tread pattern does not comprise lug grooves that are provided in the first region, communicate with either of the first circumferential main grooves, and extend in the tire width direction, or lug grooves that are provided in the second region, communicate with either of the second circumferential main grooves, and extend in the tire width direction.
3. The tire according to claim 1, wherein a plurality of the second sipes A and a plurality of the second sipes B are disposed at intervals in the tire circumferential direction, and the second sipes B are disposed one by one between the second sipes A adjacent in the tire circumferential direction.
4. The tire according to claim 1, wherein a direction connecting two ends of an extension direction of the second sipe A and a direction connecting two ends of an extension direction of the second sipe B are inclined, with respect to the tire width direction, to a same side in the tire circumferential direction.
5. The tire according to claim 1, wherein lengths of the intervals of the second sipes differ between intervals of the second sipes which are adjacent in the tire circumferential direction.
6. The tire according to claim 1, wherein the first sipes communicate with the circumferential narrow groove.
7. The tire according to claim 6, wherein a sipe depth of a narrow groove side connection portion of the first sipes is smaller than a groove depth of the circumferential narrow groove, the narrow groove side connection portion connecting to the circumferential narrow groove, and a sipe depth of an intermediate portion of the first sipes is deeper than the groove depth of the circumferential narrow groove, the intermediate portion being located between the one of the first circumferential

main grooves, with which the first sipes communicate, and the narrow groove side connection portion.

8. The tire according to claim 6, wherein a sipe depth of a main groove side communicating portion of the first sipes is smaller than a groove depth of the one of the first circumferential main grooves, the main groove side communicating portion communicating with the one of the first circumferential main grooves.

9. The tire according to claim 1, wherein the first sipes extend in a curved shape bulging to one side in the tire circumferential direction on a tread surface.

10. The tire according to claim 9, wherein a length of the first sipes in an extension direction of the first sipes is greater than a length of the second sipes in an extension direction of the second sipes.

11. The tire according to claim 1, wherein the second sipes extend in a straight line, and an inclination angle, with respect to the tire width direction, of a direction connecting two ends of an extension direction of the second sipes differs between adjacent second sipes which are adjacent in the tire circumferential direction.

12. The tire according to claim 1, wherein the tread pattern comprises a plurality of third sipes that are provided in a third region between a first inner main groove of the first circumferential main grooves, closest to the tire centerline and a second inner main groove of the second circumferential main grooves, closest to the tire centerline, communicate with either the first inner main groove or the second inner main groove, extend in the tire width direction, and close within the third region, and the number of the intervals of the second sipes is larger than a number of intervals of the third sipes adjacent in the tire circumferential direction.

13. The tire according to claim 12, wherein a length of the second sipes in the tire width direction is half or less of a length of the second region in the tire width direction, and a length of the third sipes in the tire width direction is half or less of a length of the third region in the tire width direction.

14. A tire comprising a tread pattern on a surface of a tread portion that contacts a road surface, the tread pattern comprising: a pair of first circumferential main grooves provided in a first half-tread region on one side of a tire centerline in a tire width direction, extending in a tire circumferential direction, and disposed at intervals from each other in the tire width direction; a pair of second circumferential main grooves provided in a second half-tread region on an other side in the tire width direction, extending in the tire circumferential direction, and disposed at intervals from each other in the tire width direction; a plurality of first sipes provided in a first region between the first circumferential main grooves, communicating with one of the first circumferential main grooves, extending in the tire width direction, and closing within the first region; a circumferential narrow groove having a groove width smaller than a groove width of either of the first circumferential main grooves and extending in the tire circumferential direction within the first region; and a plurality of second sipes provided in a second region between the second circumferential main grooves, communicating with one or an other of the second circumferential main grooves, extending in the tire width direction, and closing within the second region, and a number of intervals of the second sipes adjacent in the tire circumferential direction being larger than a number of intervals of the first sipes adjacent in the tire circumferential direction; wherein each sipe of the plurality of first sipes and the plurality of second sipes has a sipe width in a range of from 0.3 mm to 1.0 mm, and the first sipes communicate with the circumferential narrow groove.
