

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12387559
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Lucchetti; Matthew J. et al.

---

### Systems and methods for determining player participation at gaming tables

---

#### Abstract

A system includes a plurality of stationary gaming tables positioned at a plurality of respective locations, a moveable table game device, one or more processors, and a server. Each gaming table includes a table transceiver and a table controller. The table game device includes a device transceiver that sends and receives data signals including operational data from the table transceivers via a first communication network. The server collects the operational data via a second communication network and stores the operational data for analysis, in particular, to obtain player participation data. The system, via the device transceiver and the table transceiver, may configure the moveable table game device according to configuration data stored in the memories of the table controller or the server by a configured moveable table game device previously located at the gaming table.

---

**Inventors:** Lucchetti; Matthew J. (Las Vegas, NV), Vizzo; Michael (Las Vegas, NV)

**Applicant:** LNW Gaming, Inc. (Las Vegas, NV)

**Family ID:** 1000008749251

**Assignee:** LNW Gaming, Inc. (Las Vegas, NV)

**Appl. No.:** 18/313034

**Filed:** May 05, 2023

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240144776 A1	May. 02, 2024

#### Related U.S. Application Data

**Publication Classification****Int. Cl.:** G07F17/32 (20060101)**U.S. Cl.:****CPC** G07F17/3239 (20130101); G07F17/322 (20130101); G07F17/3234 (20130101);  
G07F17/3293 (20130101);**Field of Classification Search****CPC:** G07F (17/3239); G07F (17/322); G07F (17/3234); G07F (17/3293); G07F (17/3223);  
G07F (17/3225); G07F (17/3241)**USPC:** 463/11; 463/12; 463/13

---

**References Cited****U.S. PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Issued Date</b>	<b>Patentee Name</b>	<b>U.S. Cl.</b>	<b>CPC</b>
5722893	12/1997	Hill et al.	N/A	N/A
6886829	12/2004	Hessing et al.	N/A	N/A
7950663	12/2010	Schubert et al.	N/A	N/A
8100753	12/2011	Soltys	N/A	N/A
8702101	12/2013	Krenn et al.	N/A	N/A
9316597	12/2015	Blazevic	N/A	N/A
9474957	12/2015	Haushalter et al.	N/A	N/A
9776072	12/2016	Riordan et al.	N/A	N/A
10086260	12/2017	Grauzer et al.	N/A	N/A
10286291	12/2018	Wadds et al.	N/A	N/A
10343054	12/2018	Czyzewski et al.	N/A	N/A
10525328	12/2019	Riordan et al.	N/A	N/A
11386745	12/2021	Helgesen	N/A	G07F 17/3218
11915546	12/2023	Helgesen	N/A	H04W 4/029
11990000	12/2023	Lyons	N/A	G07F 17/3293
2007/0238502	12/2006	Pokorny et al.	N/A	N/A
2008/0051169	12/2007	Michaelson et al.	N/A	N/A
2015/0021272	12/2014	Ko et al.	N/A	N/A
2016/0203672	12/2015	Acres	N/A	N/A
2016/0354678	12/2015	Grauzer et al.	N/A	N/A
2020/0098223	12/2019	Lyons et al.	N/A	N/A
2020/0402342	12/2019	Kelly et al.	N/A	N/A
2022/0189241	12/2021	Helgesen	N/A	G07F 17/3218
2022/0301392	12/2021	Helgesen	N/A	G07F 17/3218

**FOREIGN PATENT DOCUMENTS**

Patent No.	Application Date	Country	CPC
2003026763	12/2002	WO	N/A
2015021272	12/2014	WO	N/A
2015051312	12/2014	WO	N/A

---

*Primary Examiner:* Elisca; Pierre E

---

## Background/Summary

RELATED APPLICATIONS (1) This application claims priority benefit to U.S. Provisional Patent Application No. 63/392,622, filed Jul. 27, 2022. This application also claims priority benefit to U.S. Provisional Patent Application No. 63/357,662 filed Jul. 1, 2022. Both of the above-referenced provisional patent applications are incorporated herein by reference in their entireties.

COPYRIGHT (2) A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent disclosure, as it appears in the Patent and Trademark Office patent files or records, but otherwise reserves all copyright rights whatsoever. Copyright 2020-2023, LNW Gaming, Inc.

### TECHNICAL FIELD

(1) This disclosure relates generally to networked gaming systems and, more specifically, to determining player participation at networked gaming devices within a gaming environment.

### BACKGROUND

(2) Gaming devices used in the gaming industry, such as electronic gaming machines (EGMs), card-handling devices, and the like, are used for increasing the efficiency, security, and game speed in games such as blackjack, baccarat, poker, and reel-based games. The gaming devices are deployed in a gaming environment (e.g., a casino). At least some gaming devices generate and/or collect data associated with gameplay, device diagnostics, and/or the like. The gaming devices may be communicatively coupled to a network to store and analyze the data from the gaming devices using a centralized data processing system. Casinos make money from a house edge on every bet. The higher the turnover of bets, the more profit from the edge. A full table at a low limit (especially blackjack) makes very little money and can actually lose money. A table with only one or two players has a much higher bet turnover. Often, a casino will raise the minimum wagers at a table to reduce the number of players at the table to one or two players. However, players at tables ebb and flow. Some dealers deal faster than others, affecting the need to make a change at a particular table. Some games have a more complex decision structure than others. Achieving a balance between entertainment value for players and profitability can be a daunting task. Estimating the average number of players and the number of hands per hour played at a variety of games with different rules and numbers of decks of cards can be overwhelming for gaming pit personnel responsible for a myriad of other tasks including general customer service, monitoring dealers and players for cheating, resolving payment disputes, and the like. Decisions to increase or decrease table limits, to open or close particular gaming tables, or to change the type of game played at each gaming table should be driven by analysis of player participation data that is as accurate and as timely as possible. Having real-time information on the number of players participating in rounds of play at the various gaming tables in a gaming establishment can help a casino fine-tune its advantage at any given moment. In some cases, table limits can be automatically adjusted, or tables may be automatically opened or closed based on such real time data.

### SUMMARY

(3) A system includes a plurality of stationary gaming tables positioned at a plurality of respective

locations, a moveable table game device, one or more processors, and a server. Each gaming table includes a table transceiver and a table controller. The table game device includes a device transceiver that sends and receives data signals including operational data from the table transceivers via a first communication network. The server collects the operational data via a second communication network and stores the operational data for analysis, including the determination of player participation data.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of an example networked gaming device system according to at least one embodiment.
- (2) FIG. 2 is a block diagram of an example gaming device according to at least one embodiment.
- (3) FIG. 3 is a block diagram of an example gaming table according to at least one embodiment;
- (4) FIG. 4 is a flow diagram of an example method for locating gaming devices using a networked gaming device system in accordance with at least one embodiment;
- (5) FIG. 5 is a data flow block diagram of the method shown in FIG. 4;
- (6) FIG. 6 is a data flow block diagram of data transmitted and generated by a networked gaming device system in accordance with at least one embodiment; and
- (7) FIG. 7 is a flow diagram of an example method for determining player participation in a blackjack game at a networked gaming device system in accordance with at least one embodiment.
- (8) The figures depict various embodiments for purposes of illustration only. One skilled in the art who also has the benefit of this disclosure may recognize from the following discussion that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles described herein.

### DETAILED DESCRIPTION

- (9) The present disclosure illustrates, in various embodiments, systems and methods of locating and communicating with networked, moveable gaming devices.
- (10) In the following description, circuits and functions may be shown in block diagram form in order not to obscure the descriptions in unnecessary detail. Conversely, specific circuit implementations shown and described are examples only and should not be construed as the only way to implement networked gaming devices unless specified otherwise herein. Additionally, block definitions and partitioning of logic between various blocks illustrates one possible embodiment. It may become apparent to one of skill in the art, who also has the benefit of this disclosure, that the embodiments disclosed may be practiced by various other partitioning solutions, all of which are contemplated herein.
- (11) Further, the term “module” is used herein in a non-limiting sense to indicate functionality of particular circuits and/or assemblies within embodiments of networked gaming device systems and is not to be construed as requiring a particular physical structure, or particular partitioning between elements for performing the indicated functions.
- (12) When executed as firmware or software, the instructions for performing the methods and processes described herein may be stored on a computer readable medium. A computer readable medium includes, but is not limited to, magnetic and optical storage devices such as disk drives, magnetic tape, CDs (compact discs), DVDs (digital versatile discs or digital video discs), and semiconductor devices such as RAM, DRAM, ROM, EPROM, and Flash memory.
- (13) The processors described herein process data signals and may comprise various computing architectures such as a complex instruction set computer (CISC) architecture, a reduced instruction set computer (RISC) architecture, or an architecture implementing a combination of instruction sets. Although only a single processor may be shown, multiple processors may be included. The

processors comprise an arithmetic logic unit, a microprocessor, a general-purpose computer, or some other information appliance equipped to transmit, receive, and process electronic data signals from an associated memory and/or one or more input/output devices

(14) The memory described herein stores instructions and/or data that may be executed and/or accessed by the associated processor. The instructions and/or data may comprise code for performing any and/or all of the techniques described herein. The memory may be a dynamic random-access memory (DRAM) device, a static random-access memory (SRAM) device, Flash RAM (non-volatile storage), combinations of the above, or some other memory device known in the art. While the memory may be shown within some devices, some of the memory can be remote, e.g., on a separate device connected to the device or via a WAN, e.g., a cloud-based storage device.

(15) As used herein, a “gaming device” or “game device” refers to an apparatus associated with one or more aspects of a gaming environment. For example, a gaming device may include card-handling devices (e.g., shufflers and shoes), electronic gaming machines (EGMs), and/or other devices that provide gameplay features for a game. Gaming devices may also include devices that are not directly involved in gameplay, such as information kiosks, displays, currency conversion devices, and the like. The foregoing examples of gaming devices are for exemplary purposes only and do not limit the gaming devices to the examples mentioned above.

(16) As used herein, a “gaming environment” or “casino environment” is a location or multiple locations in which one or more games (particularly, wagering games) are conducted. Although some gaming environments may not include any gaming devices, in the embodiments described herein, at least one gaming device is deployed at the gaming environment to facilitate play of the one or more games.

(17) The systems and methods described herein facilitate data communication with, and location tracking of, networked gaming devices. These gaming devices may be moveable within and outside of one or more gaming environments to enable operators of the gaming environments to customize the gaming environments and remove the gaming devices from the gaming environments for maintenance. In the systems and methods described herein, each gaming device includes a device transceiver for data communication over a first communication network. The gaming environment includes one or more stationary devices, such as stationary gaming tables, that have transceivers that communicatively couple to the device transceivers of the gaming devices to exchange gaming data via the first communication network. The transceivers are further communicatively coupled to a server via a second communication network to enable the server to collect the gaming data from the gaming devices and the stationary devices for analysis and historical storage.

(18) In the systems and methods described herein, the stationary devices have a known or predetermined location within the gaming environment. The device transceivers, the transceivers of the stationary devices, and/or other computing modules associated with the gaming devices or stationary devices monitor data signals transmitted between each gaming device and each stationary device to calculate a relative distance measurement between the gaming device and the stationary device. The distance data associated with a gaming device is collected and analyzed by the gaming device to determine its location relative to the stationary devices. The location data generated by the gaming devices may be collected by the server to facilitate centralized storage and analysis of the location data. Based on the location data, the server may automatically determine which gaming devices are active, what game that the gaming devices are being used for, which gaming environment the gaming devices are located in, and/or other data relevant to the device location.

(19) The technical problems addressed by the systems and methods described herein may include, for example: (i) data network congestion from transmitting gaming data over populated network channels; (ii) imprecise location determinations of gaming devices and users within gaming environments; (iii) manual configuration of game devices for a particular game; (iv) imprecise usage data collection for gaming devices; and (v) reactive maintenance of gaming device

malfunctions.

(20) The technical solutions that may be provided by the systems and methods described herein may include, for example: (i) reduced data network congestion by using network channels other than the populated network channels and frequency bands; (ii) improved precision of locating gaming devices and users within gaming environments; (iii) automated configuration of game devices for a particular game; (iv) improved usage data collection for gaming devices; (v) proactive maintenance of gaming devices to reduce the frequency of device malfunctions; and (vi) reduced cost and complexity of transceivers by consolidating data communication and location services using the same communication network.

(21) FIG. 1 is a block diagram of an example networked gaming device system **100** for use within one or more gaming environments **101**. The system **100** includes one or more gaming devices **102**, a plurality of stationary devices **104**, a first network **106**, one or more communication nodes **108**, a server system **110**, and a second communication network **112**. In other embodiments, the system **100** may include additional, fewer, or alternative subsystems, including those described elsewhere herein.

(22) The gaming devices **102** are moveable devices configured to facilitate play of games within the gaming environments **101**. In the example embodiment, the gaming devices **102** are deployed in two gaming environments, e.g., two casinos. In other embodiments, the gaming devices **102** may be deployed to a different number of gaming environments (including one).

(23) FIG. 2 is a block diagram of an example gaming device **200** that may be used with a networked gaming device system, such as the system **100**. The gaming device **200** includes a device controller **202**, a sensor system **204**, and a device transceiver **206**. In other embodiments, the gaming device **200** may include additional, fewer, or alternative components, including those described elsewhere herein.

(24) The device controller **202** is configured to monitor and/or control operation of the gaming device **200**. The device controller **202** includes one or more processors **208** and associated memory **210**. The memory **210** stores computer-readable instructions that, when executed by the processors **208**, cause the device controller **202** to function as described herein. For example, when the gaming device **200** is a card-handling device, the device controller **202** may be configured to cause the gaming device **200** to receive cards from a dealer, shuffle the cards, and output the shuffled cards to the dealer for use in a card-based game (e.g., poker or blackjack).

(25) The sensor system **204** includes one or more sensors **212** that are configured to collect sensor data associated with the gaming device **200**. For example, the sensor system **204** of a card-handling device may include one or more image sensors to capture images of each card passing through a portion of the card-handling device. In another example, the sensor system **204** may include one or more sensors to identify user input and/or credit inputs (e.g., bills, coins, tickets, etc.) from a player. The sensors **212** may be configured to collect any suitable sensor data associated with the gaming device **200** and/or the environment surrounding the gaming device **200**, such as motion data, image data, strain data, pressure data, temperature data, usage data, maintenance-related data, and the like. In the example embodiment, the sensor system **204** is communicatively coupled to the device controller **202** to transmit the sensor data. In certain embodiments, the sensor system **204** is communicatively coupled to the device transceiver **206** to transmit the sensor data. Alternatively, the gaming device **200** may not include the sensor system **204**.

(26) The device transceiver **206** is communicatively coupled to the device controller **202** and the first communication network **106** (shown in FIG. 1). Although the device transceiver **206** is shown within the gaming device **200**, in some embodiments, the device transceiver **206** may be positioned externally from the device **200**, such as an add-on or after-market device. In such embodiments, the device transceiver **206** may be communicatively coupled to the controller **202** via wired, contact and/or wireless communication. For example, the device **200** may include one or more data ports or antenna to connect to the device transceiver **206**. In the example embodiment, the device

transceiver **206** includes one or more transceiver processors **214**, associated memory **216**, an antenna **218**, and an analog interface **220**. In some embodiments, the device transceiver **206** includes additional, fewer, or alternative components, including those described elsewhere herein. For example, the device transceiver **206** may include a power storage device (e.g., a battery) to facilitate operation while the device controller **202** is inactive. Similarly, the device transceiver **206** may be configured to operate in a low-power mode to function as described herein while the device controller is inactive. In other embodiments, the device transceiver **206** is at least partially integrated with the device controller **202**. In one example, the transceiver processors **214** and/or the memory **216** are part of the processors **208** and the memory **210**, respectively. In such an example, the processes and functions of the transceiver processors **214** and the memory **216** may be implemented as dedicated modules or applications within the processors **208** and the memory **210**. In another example, each component of the device transceiver **206** is included within the device controller **202**.

(27) The device transceiver **206** is configured to communicate data associated with the gaming device **200** to and from the first communication network **106** and determine the relative location of the gaming device **200** as described in detail herein. In particular, the device transceiver **206** is configured to communicate data in accordance with the communication protocols of the first communication network **106**. In one example, the first communication network **106** is an ultra-wideband communication network. Ultra-wideband communication, unlike some common types of wireless communication (e.g., Wi-Fi and Bluetooth), is not restricted to heavily populated frequency bands (e.g., 2.4 GHz and 5 GHz). Rather, ultra-wideband communication may be performed at other, less-populated, frequency bands that still provide relatively high data speeds. In one example, the ultra-wideband network may be configured to facilitate communication at a plurality of frequency bands from 3.5 GHz to 6.5 GHz with data rates of 110 kbps, 850 kbps, or 6.8 Mbps. In addition, in comparison to wired communication networks, wireless communication using ultra-wideband facilitates improved portability of the gaming device **200** and increased flexibility for arranging the device **200** within a gaming environment without concern of wire access points and the like. In other embodiments, other suitable types of communication networks that avoid populated or saturated frequency bands may be used for the first communication network **106**.

(28) In the example embodiment, the first communication network **106** is a non-persistent communication network. That is, unlike Wi-Fi, which uses routers to maintain a persistent communication signal for connecting devices to the Wi-Fi network, each device communicatively coupled to the network **106** includes a transceiver (e.g., the device transceiver **206**) for discovering and establishing communication with other devices. In other embodiments, the first communication network **106** is a persistent network.

(29) The antenna **218** of the device transceiver **206** is configured to receive and transmit data signals with other devices via the first communication network **106**. In some embodiments, the device transceiver **206** may include more than one antenna **218**, such as one antenna **218** for receiving signals and another antenna **218** for transmitting signals. In the example embodiment, the data signals received and transmitted by the antenna **218** are analog signals. The analog interface **220** is communicatively coupled to the antenna **218** to convert received data signals to a digital format compatible with the transceiver processor **214** and to convert digital data signals from the processor **214** to an analog format for transmission via the first communication network **106**.

(30) In at least some embodiments, the device transceiver **206** includes other components that facilitate the operation of the transceiver processor **214**, the antenna **218**, and/or the analog interface **220**, such as, but not limited to, clock generators, phase-lock-loop circuitry, state controllers, power supplies, power management circuitry, filter circuitry, communication interfaces with the device controller **202**, and the like. In some embodiments, the device transceiver **206** is powered separately from the device controller **202** to enable communication even if the gaming

device **200** is in an inactive (i.e., powered-off) state. In such embodiments, the device transceiver **206** may enter a low-power mode while the gaming device is inactive to conserve power.

(31) With respect again to FIG. **1**, the stationary devices **104** are positioned around the gaming environment. Rather than being permanently fixed to a particular location (though some stationary devices **104** may be permanent fixtures), the stationary devices **104** are typically located at a single, predetermined location for a period of time (e.g., one hour, one day, one month, etc.). For example, the stationary devices **104** may include, but are not limited to, gaming tables, building structural components (e.g., walls, stairs, ceiling panels, etc.), and/or other similar devices. Likewise, although the gaming devices **102** may be moveable or portable, the gaming devices **102** may remain stationary for an extended period of time. In some cases, a gaming device **102** may be deployed at a stationary device **104** until maintenance is required, and some gaming devices **102** may be moved together with the corresponding stationary device **104**. As an example, a card-handling device coupled to a gaming table may remain coupled to the table other than during periods of maintenance and may be relocated within a gaming environment together with the table.

(32) For exemplary purposes herein, the stationary devices **104** are stationary gaming tables positioned within the gaming environment. However, the details described below with respect to the gaming tables **104** are not limited to gaming tables and may be applicable to other stationary devices. Moreover, in some embodiments, the stationary devices **104** may include a variety of different types of stationary devices.

(33) FIG. **3** illustrates an example stationary gaming table **300** that may be used with a networked gaming device system, such as the system **100**. The gaming table **300** includes a game interface **302**, a table controller **304**, and a table transceiver **306**. In other embodiments, the gaming table **300** may include additional, fewer, or alternative components, including those described elsewhere herein.

(34) The game interface **302** is an area of the gaming table **300** that is used for play of a game. For example, the upper felt surface including game symbols on a poker table is the game interface **302**. The game interface **302** may be configured to include one or more gaming devices (e.g., the gaming devices **102**, shown in FIG. **1**) and/or other devices that facilitate play of a game. In one example, the game interface **302** includes one or more displays, lights, and/or input devices for a game.

(35) The table controller **304**, similar to the device controller **202** shown in FIG. **2**, is configured to monitor and/or control operation of one or more devices associated with the gaming table **300**, including the table **300** itself in some embodiments. The table controller **304** includes one or more table processors **308** and associated memory **310** for executing computer-readable instructions to perform the functions of the table controller described herein. The table controller **304** may be configured to coordinate the various devices associated with the gaming table to provide consistent gameplay of the game. For example, if the gaming table **300** includes individual displays for each player, the table controller **304** may be configured to cause each display to display information relevant to the respective players.

(36) In the example embodiment, the table controller **304** includes one or more sensors **312** for collecting sensor data. The sensors **312** may include, but are not limited to, image sensors, pressure sensors, light sensors, audio sensors, and the like. The table controller **304** may analyze the sensor data to determine the state of the game, gaming devices, operators, and/or players associated with the gaming table **300**.

(37) The table transceiver **306** is physically coupled to the gaming table **300** and is configured to communicate with the first communication network **106** and the second communication network **112** (both shown in FIG. **1**). The table transceiver **306** is further communicatively coupled to the table controller **304** to facilitate communication between the table controller **304** and the first and/or second communication networks **106**, **112**. In other embodiments, the table controller **304** may be separate and independent from the table transceiver **306**. In the example embodiment, the



table transceiver **306** includes one or more processors **314**, associated memory **316**, a first antenna **318**, a second antenna **320**, and a communication interface **322**. The memory **316** stores instructions that, when executed by the processors **314**, cause the device transceiver to function as described herein. In other embodiments, the table transceiver **306** may include additional, fewer, or alternative components, including those described elsewhere herein.

(38) In some embodiments, the table controller **304** and the table transceiver **306** may be at least partially integrated with each other. For example, the table processors **308** and the memory **310** may be integrated with the processor **314** and the memory **316**, respectively. As another example, the sensors **312** may be incorporated with the table transceiver **306**. In other embodiments, the gaming table **300** does not include a table controller **304**, and the table transceiver **306** operates independently. In such embodiments, the gaming table **300** may not include devices controllable by the controller **304** or the devices are configured to operate without control from the table controller **304**.

(39) The first antenna **318** is configured to transmit and receive data signals via the first communication network **106**, whereas the second antenna **320** is configured to transmit and receive data signals via the second communication network **112**. The antennae **318**, **320** may include more than one antenna each to facilitate communication. In certain embodiments, a single antenna may be used to communicate with both the first and second communication networks **106**, **112**. The communication interface **322** is communicatively coupled to the antennae **318**, **320** to convert data signals between analog and digital formats and perform any other suitable functions to facilitate communication. In certain embodiments, the table transceiver **306** may be divided into separate modules for communication with the first communication network **106** and the second communication network **112**. That is, at least the antennae **318**, **320** may be separated into different physical modules. The processors **314**, the memory **316**, and/or the communication interface **322** may be divided between the separate modules. In at least some embodiments, the table transceiver **306** may include other components and subsystems to facilitate the functions described herein. For example, the table transceiver **306** may include circuitry for power supply, power management, signal filtration, state management, other network interfaces, and/or other suitable functionality.

(40) With respect to both FIGS. **1** and **3**, the second communication network **112** is configured to facilitate communication with a plurality of gaming tables **300** and other stationary devices using a reduced number of communication nodes **108**. That is, the second communication network **112** is configured for relatively long-range, low interference communication to enable one or more communication nodes **108** to communicate with a plurality of gaming tables **104** deployed throughout a gaming environment. In addition, similar to the first communication network **106**, the second communication network **112** is configured to facilitate communication outside of the commonly populated frequency bands to avoid signal interference. The second communication network **112** may be a different type of network and/or use a different frequency band in comparison to the first communication network **106**. In the example embodiment, the second communication network **112** is a Long Range (LoRa) communication network. LoRa networks communicate using radio signals having frequencies below 1 GHz to facilitate relatively long communication ranges, relatively low power consumption, and/or other network features, such as end-to-end encryption and relatively high communication bandwidth. The use of a wireless second communication network **112** facilitates increased flexibility in deploying the gaming tables throughout a gaming environment, and the use of a LoRa network with a relatively large communication range reduces the number of communication nodes **108** that need to be deployed to communicate with the gaming tables **300**. In other embodiments, other suitable types of networks may be used as the second communication network **112**. Alternatively, the second communication network **112** may be integrated with the first communication network **106**.

(41) The communication node **108** is a network interface communicatively coupled to the server system **110** and the second communication network **112** at a respective gaming environment **101**.

The communication node **108** facilitates communication between the gaming tables **104** and the server system **110** for data transmission, locating gaming devices **102** within the gaming environments **101**, and the like. The communication node **108** may include any suitable network components to communicate with both the second communication network **112** and the server system **110**. For example, the communication node **108** may include a transceiver configured to transmit data signals in accordance with the protocols of the second communication network **112**. In another example, the communication node **108** may be communicatively coupled with the server system **110** via any form of wireless or wired connections or any combination thereof. By way of example and not limitation, communication between the communication node **108** and the server system **110** may be comprised of serial data links, parallel data links, USB, Ethernet, a Wide Area Network (WAN), a Local Area Network (LAN), infrared communication, IEEE 802.16 (or WiMax), IEEE 802.11a/b/g/n/p, Wi-Fi, and any public cellular phone network including, but not limited to, GSM, CDMA, 3G, or 3GPP Long Term Evolution (LTE), communication, etc.

(42) In the example embodiment, each gaming environment **101** includes one communication node **108** for communicating with the gaming tables **104** at the respective gaming environment **101**. In other embodiments, a plurality of communication nodes **108** may be configured to communicate with the second communication network **112** at a single gaming environment **101**. Alternatively, a communication node **108** may be configured to communicate with the second communication network **112** over multiple gaming environments **101**. In certain embodiments, the communication node **108** may be configured to communicatively couple to the first communication network **106** in addition to or instead of the second communication network **112**. In such embodiments, the communication node **108** may communicate with the gaming devices **102** and/or the gaming tables **104** via the first communication network **106**. In one example, the communication node **108** is configured to communicate with relatively nearby devices **102** and/or tables **104** via the first communication network **106** (i.e., devices and tables within the effective communication range of the communication node **108** using the first communication network) and to communicate with other tables **104** via the second communication network **112** that has a greater effective communication range than the first communication network **106**.

(43) The server system **110** includes one or more server computing devices **114** and a server database **116**. The server system **110** may be centralized (i.e., the server computing device **114** and the server database **116** are integrated with each other) or distributed. The server system **110** is configured to collect data from the gaming devices **102** and the gaming tables **104** via the communication node **108** and the second communication network **112**, analyze the data, and/or store the data. In one example, the server system **110** monitors usage of the gaming devices **102** within the gaming environments **101**. In another example, the server system **110** determines a location of each deployed gaming device **102** as described herein.

(44) The server computing device **114** is configured to execute at least a portion of the tasks performed by the server system **110** as described herein, such as requesting data from the gaming tables **104**, analyzing the data from the gaming tables **104**, and storing data within the server database **116**. In the example embodiment, the server computing device **114** is configured to receive data indicating a relative location of each gaming device **102** for storage and analysis of the location data. In certain embodiments, the server computing device **114**

(45) The server database **116** is configured to store data generated by the server system **110** and/or data collected from the gaming tables **104**. In some embodiments, the server database **116** is formed by a plurality of distributed databases. In one example, the server database **116** is configured to store data collected from the gaming tables **104**, game settings associated with one or more games, usage data for each gaming device **102**, reports generated by the server computing device **114**, and/or a dynamic map indicating a location of each gaming device **102** within the gaming environments **101**.

(46) FIG. 4 is a flow diagram of an example method **400** of locating a gaming device **102** within a

gaming environment **101** using the networked gaming device system **100**. FIG. 5 is a data flow diagram **500** of the method **400** using the networked gaming device system **100**. The method **400** may be used to locate a plurality of gaming devices **102** within multiple gaming environments **101** to provide a dynamic map of where each device **102** is located, if the device **102** is active (i.e., in use), and/or what gaming table **104** is associated with each device **102**. In other embodiments, the method **400** may include additional, fewer, or alternative steps, including those described elsewhere herein. Moreover, at least some of the steps described herein performed by the gaming device **102**, the gaming tables **104**, the communication node **108**, and/or the server system **110** may be performed using one or more computing devices and/or processors, such as the computing devices and processors described above with respect to FIGS. 1-3.

(47) In the example embodiment, with respect to both FIGS. 4 and 5, the gaming tables **104** are deployed within a gaming environment **101** and establish communication with the communication node **108**. The gaming tables **104** have a predetermined location within the gaming environment **101**. The location may be provided as, for example, geographical coordinates, coordinates within a map of the gaming environment **101** (and any surrounding areas), and/or other suitable forms of specifying location. In one example, a map of the gaming environment is divided into a grid, where each cell of the grid can be filled with a gaming table **104**. In some embodiments, the predetermined location is identified and assigned to the gaming tables **104** manually. In other embodiments, the location of each gaming table **104** is determined automatically by the server system **110** and/or the respective gaming tables **104**. In one example in which a gaming table **104** is communicatively coupled to at least three communication nodes **108** via a LoRa second communication network **112**, the location of the gaming table **104** may be determined as a function of the timestamps of a data signal generated by the transceiver of the gaming table **104** (e.g., table transceiver **306**, shown in FIG. 3) and received by each communication node **108**. The server system **110** stores **402** the predetermined location of each stationary gaming table **104** for the location determination described herein. Each stationary gaming table **104** may also store its respective location. In certain embodiments, each gaming table **104** may be associated with one or more games to be played at the gaming table **104**. That is, a gaming table **104** is assigned one or more games and, in some embodiments, game settings may be stored by the gaming table **104** for the games.

(48) The gaming device **102** is then activated and deployed **404** within the gaming environment **101**. Although each gaming table **104** is assumed to be within communication range of the gaming device **102** for exemplary purposes, other gaming tables **104** may be deployed outside of the communication range of the gaming device **102**. When activated, the gaming device **102** is configured to receive **406** data signals **502** including identification data **504** from each gaming table **104** via the first communication network **106**. The identification data **504** identifies the gaming table **104** from which the respective data signal **502** originates. The identification data **504** may include, but is not limited to, a unique identifier, a type of game, supported game device and/or other suitable data associated with the gaming table **104** that may be used to locate and configure the gaming device **102**. The data signal **502** is received by the gaming device **102** and the identification data **504** is extracted to identify each gaming table **104**. In at least some embodiments, the device transceiver and/or the controller of the gaming device **102** (e.g., device controller **202** and device transceiver **206**, both shown in FIG. 2) automatically generates a timestamp **506** at the time that each data signal **502** was received. In at least some embodiments, the gaming device **102** is configured to generate the data signal **502** to be received by the gaming tables **104**. In such embodiments, the gaming tables **104** are configured to generate the timestamps **506** for each received data signal **502**. The data signal **502** may be generated by both the gaming device **102** and the gaming tables **104**. For example, one gaming device **102** may receive data signals **502** from the gaming tables **104** and/or other gaming devices **102**. In such embodiments, the gaming devices **102** may treat the data signals **502** from other gaming devices **102** similar to data

signals from gaming tables **104** for purposes of determining location as described herein. Likewise, in another example, one stationary gaming table may receive data signals **502** from gaming devices **102** and/or other stationary gaming tables **104**. In certain embodiments, the data signal **502** may be transmitted in response to a data signal received by the gaming device **102** or the gaming tables **104**.

(49) In the example embodiment, one or more characteristics of the data signal **502** may be used to calculate **408** a relative distance between the gaming device **102** and each of the gaming tables **104**. The characteristics may include, but are not limited to, amplitude, phase, frequency, phase, time-of-transmission, time-of-flight, time-of-arrival, and/or signal intensity. In one example, if the first communication network **106** is an ultra-wideband network, the characteristic may preferably be a time-of-flight characteristic or a time-difference-of-arrival characteristic. In at least one example, the relative distance between the gaming device **102** and one of the gaming tables **104** is at least partially a function of the frequency of the data signal **502**, the speed of light, and/or the time the data signal **502** was received (i.e., the timestamp **506**). In some embodiments, the gaming tables **104** generate a respective transmission timestamp **508** and include the transmission timestamps **508** with the respective data signals **502**. The internal clocks of the gaming tables **104** may be synchronized to improve the accuracy of the timestamps **508**. In such embodiments, the difference between the timestamp **506** at which the signal **502** was received and the transmission timestamp **508** indicates a relative distance between the gaming device **102** and the gaming table **104**.

(50) Unlike other types of communication networks, the use of the time-of-flight characteristic or the time-difference-of-arrival characteristic provides improved accuracy of the distance determination in comparison to methods relying upon signal strength, which may be impacted by various other factors beyond distance (especially in gaming environments populated with devices and structures that may impact signal strength). Synchronizing the internal clocks of the gaming device **102** and/or the gaming tables **104** facilitates increased precision in calculating the relative distances.

(51) The gaming device **102** and/or the gaming tables **104** generate **410** distance data **510** indicating the calculated relative distances between the gaming device **102** and each gaming table **104**. The distance data **510** may include, but is not limited to, a distance measurement, an identifier of the associated gaming table **104**, the timestamp **506**, the transmission timestamp **508**, and/or other data that facilitates determining the relative distances to the gaming device **102**. In some embodiments in which the gaming tables **104** generate the distance data **510**, each gaming table **104** generates its respective distance data **510**. Alternatively, the gaming device **102** may generate the distance data **510** for the gaming tables **104**. In such embodiments, the gaming device **102** may transmit the distance data **510** to each respective gaming table **104**.

(52) In the example embodiment, the gaming device **102** collects the distance data **510** for at least a portion of the calculated distances. That is, in some embodiments, the gaming device **102** may filter out distances exceed a threshold distance to reduce computational burden of the location determination analysis described herein. In addition, the gaming device **102** collects the predetermined locations of the gaming tables **104**. In certain embodiments, the locations are included within the identification data **504**. In other embodiments, the locations are collected via other data signals received by the gaming device **102**. The gaming device **102** is configured to determine its relative location within (or near) the gaming environment **101**.

(53) The gaming system **102** compares the timestamps and/or distances of the distance data **510** with the predetermined locations of the gaming tables **104**. Using trilateration or other suitable location-determination techniques, the location of the gaming device **102** is identified at least partially as a function of the distance data **510**. For example, if the relative distances are calculated between the gaming device **102** and at least three gaming tables **104** while accounting for the known locations of the gaming tables, the gaming device **102** can determine the location of the gaming device **102** relative to the gaming tables **104**. In comparison to location-determination

techniques that use satellites, signal towers, and the like that are remotely located from the gaming environment **101** and susceptible to interference from other devices and structures, determining location relative to the gaming tables **104** facilitates improved accuracy in the location determination of the gaming device **102**. Moreover, by performing the location determination locally at the gaming device **102**, the location can be determined even without reliance on external computing systems. In certain embodiments, rather than determining a specific location of the gaming device **102**, the gaming device **102** identifies a gaming table **104** associated with the gaming device **102** as described herein and assigns itself the predetermined location of the associated gaming table **104**.

(54) In response to determining its relative location, the gaming device **102** generates **412** location data **512** to be transmitted to the communication node **108**. The location data **512** indicates the relative location and may also include other suitable data, such as a game data, maintenance scheduling data, and/or the like. The gaming device **102** may transmit **414** the location data **512** to the communication node **108** via one or more gaming tables **104** and the second communication network **112**. The communication node **108** collects the location data **512** and transmits the data **512** to the server system **110** for storage and analysis. In some embodiments, the gaming tables **104** and/or the server system **110** may generate the distance data **510** and/or the location data **512** rather than the gaming device **102**. In such embodiments, the gaming tables **104** and/or the server system **110** may collect the corresponding data to generate the distance data **510** and/or the location data **512**. In one example, the gaming device **102** generates the distance data **510** and transmits the distance data **510** to the server system **110**. The server system **110** then generates the location data **512** as a function of the predetermined locations of the gaming tables and the distance data **510**.

(55) The method **400** may be repeated for a plurality of gaming devices **102** such that the server system **110** may identify and monitor the location of every gaming device **102** deployed within the gaming environment **101**. In at least some embodiments, gaming devices **102** that are not deployed within the gaming environment **101** may notify the server system **110** of its location. In one example, at least some gaming devices **102** may include power storage devices (e.g., batteries) and/or low-power modes to facilitate location determination while the gaming devices **102** are not deployed. In other embodiments, the absence of a location determination by a particular gaming device **102** may be inferred that the gaming device **102** is not deployed and inactive. These gaming devices **102** may be in storage, maintenance, at other gaming environments **101**, and the like. Monitoring the location of the devices **102** may provide increased awareness of the how the gaming devices **102** are being used.

(56) In at least some embodiments, the server system **110** is further configured to generate a dynamic map **514** of the gaming environment **101** that identifies the location of each gaming device **102** and each gaming table **104**. The dynamic map **514** may be presentable to an operator for analysis. The location of the gaming devices **102** may be updated over time to monitor the current and historical movements of the gaming devices **102**. The server system **110** may be configured to prompt the gaming devices **102** and/or the gaming tables **104** to generate the location data **512** periodically to update the dynamic map **514**. In other embodiments, the gaming devices **102** and/or the gaming tables **104** may generate location data **512** in response to the gaming devices **102** moving relative to the gaming tables **104** and may transmit the location data **512** to the server system **110** via the communication node **108** to update the dynamic map **514**. Alternatively, in embodiments in which the server system **110** generates the location data **512**, the gaming devices **102** and/or the gaming tables **104** transmit updated distance data **510** to the server system **110** to update the dynamic map **514**.

(57) The networked gaming device system **100** is not limited to locating gaming devices **102** within a gaming environment **101**. For example, the system **100** may also be used to generate and transmit gaming data, game settings, device data, usage data, and other suitable data associated with the system **100**. FIG. 6 is a data flow diagram of exemplary data transmitted within the system **100**

(shown in FIG. 1). In other embodiments, other data may be transmitted and/or generated by the system **100**, including data described elsewhere herein.

(58) In the example embodiment, a gaming device **102** may be associated with a particular stationary gaming table **104**. For example, a card-handling device may be deployed to a table for play of a card-based game, such as blackjack or poker. Associating the gaming device **102** with the gaming table **104** may facilitate certain and/or prevent certain functionalities of the gaming device **102** and the gaming table **104**. For example, other than data signals transmitted for location determination (e.g., the data signal **502**, shown in FIG. 5), the gaming device **102** or the gaming table **104** may block other data from being transmitted to and/or received from unassociated devices. The associated gaming device **102** and gaming table **104** may be configured to generate and communicate game data **602** associated with play of the game. In at least some embodiments, the gaming device **102** is associated with a gaming table **104** based at least partially on the relative distances between the gaming device **102** and one or more gaming tables **104**. For example, if the relative distance to the gaming table **104** is within a threshold predetermined distance (e.g., one meter or half of a meter) and no other gaming table **104** has a similar relative distance, the gaming device **102** may be associated with the relatively close gaming table **104**. The association may also be partially based on the type of gaming device **102** and what game is to be played at a particular gaming table **104**. For example, the gaming device **102** and/or the gaming tables **104** may broadcast game type, device type, and the like to each other. Based on the broadcasted data, the gaming device **102** and/or the gaming tables **104** determine whether or not the gaming device **102** is compatible. If a gaming device **102** is determined to be incompatible (e.g., a card-handling device for a dice-oriented table game), the gaming device **102** may ignore the incompatible gaming table **104** irrespective of its relative distance.

(59) The association may be determined by the gaming device **102**, the gaming tables **104**, and/or the server system **110**. In some embodiments, the gaming tables **104** and/or the server system **110** may store game settings **604** to configure the gaming device **102** for the game. The game settings **604** may include, but are not limited to, rules of the game, number of cards shuffled, number of available card decks, card information, artwork, animations, wagering thresholds, and/or other configurable aspects of the gaming device **102**. The game settings **604** may be transmitted to the gaming device **102** in response to associating with the gaming table **104**. The gaming device **102** may automatically be configured in accordance with the game settings to reduce necessary time to manually prepare the gaming device **102**.

(60) According to some embodiments, the gaming device **102** may be manually prepared with the game settings **604**, upon which the gaming table **104** and/or the server system **110** may store the game settings **604**. If the gaming device **102** should be removed from the gaming table **104**, for example, for repair or maintenance, a replacement gaming device **102** may then be automatically configured in accordance with the stored game settings of the gaming device previously at the gaming table **104** to reduce the preparation time for the replacement gaming device **102**. For example, table controller **304** may store the game settings **604** in its associated memory **310** until needed, at which time, the table controller **304** may transmit the game settings **604** to the gaming device **102** via the table transceiver **306**. As previously noted, a given gaming table **104** may have a number of processors with associated memories. In various embodiments, each of these may be capable of performing the operation of restoring game settings **604** in a replacement gaming device **102**. In a non-limiting example, in embodiments where the gaming table **104** does not include a table controller **304** and the table transceiver **306** operates independently, the table transceiver **306** may restore game settings **604** to the replacement gaming device **102**.

(61) In response to associating the gaming device **102** to a gaming table **104**, the gaming device **102** may transmit data to the gaming table **104** to be collected by the server system **110** via the communication node **108**. The data may also include data generated by the gaming table **104**. In some embodiments, the server system **110** is configured to periodically collect the data from the

gaming tables **104** (i.e., via polling). In other embodiments, the gaming tables **104** transmit the data asynchronously to the communication node **108** for storage and analysis by the server system **110**. At least some data may remain local to the associated gaming device **102** and gaming table **104** (i.e., the data is not transmitted to the communication node **108**). The data may include, but is not limited to, the game data **602**, device data **606**, and location data **608** (e.g., the location data **512**, shown in FIG. 5). The game data **602** includes data associated with the game played at the gaming table **104**. Examples of game data **602** may include, but are not limited to, wager amounts, wagered outcomes, payouts, game outcomes, progressive jackpot amounts, number of players, bonus game outcomes, number of cards or decks remaining, image data associated with the game, number of shuffles, game play events, game sessions, use in a period, and/or other suitable data associated with the game.

(62) The parameter of the number of shuffles can represent the number of full deck shuffles performed by the gaming device **102**. When multiple decks are shuffled, the parameters can reflect the total number of decks shuffled. The parameter of the number of cards shuffled can represent the number of cards shuffled by the gaming device **102**. In an embodiment when a particular card is shuffled multiple times over the course of a time period, the parameter is incremented each time the card is shuffled. In another embodiment, a card is shuffled once when the card is part of a shuffle process in which one or more decks of cards are completely shuffled.

(63) The parameter of a game play event can represent the number of completed games/hands at a table **104**. For example, one game play event for blackjack represents the dealing of cards between the placement of an initial bet and the final result of the hand. In one embodiment, if there are five players at a table, the completion of one hand for all players and the dealer represents five game plays, in some embodiments the dealer's hand is also counted so this represents six game plays, in another embodiment this represents one game play.

(64) The parameter of a game session can represent a series of game plays/deals for a particular type of game played such as blackjack, THREE CARD POKER®, etc., without a significant break in play. For example, if a gaming device **102** is used for THREE CARD POKER® and is in continuous use, e.g., shuffling and dealing cards with no more than a five-minute break (other break period criteria can be used), for six hours, then the gaming device **102** is used for blackjack, then the six hours of THREE CARD POKER® is one game play session.

(65) The parameter of use in a period can represent the total amount of usage of the gaming device **102** in a period. Examples of usage are number of shuffles, number of cards shuffled, number of game play events, and/or game sessions. The information can assist in identifying trends in the amount of game plays of particular games, e.g., THREE CARD POKER®.

(66) The device data **606** includes operating conditions, diagnostics, maintenance reminders, and/or other data associated with the gaming device **102**. At least some of the device data **606** is collected by sensors (e.g., the sensor system **204**, shown in FIG. 2) monitoring the gaming device **102**.

(67) In at least some embodiments, the server system **110** collects the game data **602**, the device data **606**, and/or the distance data **608** to generate usage data **610** associated with each gaming device **102**. In some embodiments, the data received by the server system **110** may be collectively referred to as “operational data.” The usage data **610** indicates how long the gaming device **102** has been active and in use, under what conditions, and/or other similar factors. The usage data **610** may be used to proactively identify gaming devices due for maintenance prior to device failure and/or to accurately monitor the use of rental or leased gaming devices within the gaming environments **101**. Moreover, because the server system **110** monitors multiple gaming environments **101**, the usage data **610** of gaming devices **102** that are deployed in multiple gaming environments over time may be captured by the system **100**. The server system **110** may be configured to generate and present reports including the operational data for one or more gaming devices **102** and/or other data associated with the system **100**. In certain embodiments, each gaming device **102** may be configured to generate its respective usage data **610** and transmit the usage data **610** to the server

system **110** for storage and analysis. In other embodiments, the usage data **610** is transmitted to the gaming table **104**, which stores and analyzes the usage data **610** locally, for example, by the memory and processor(s) of a table controller **304**.

(68) For example, if the game being played at a gaming table **104** is THREE CARD POKER®, in which the dealer and each player receive three cards delivered in a three-card packet by the gaming device **102** (e.g., shuffler), a dealer at the gaming table **104** may operate the gaming device **102** to shuffle the cards and press a button to indicate a start of the dealing process. The gaming device **102** then delivers a first packet of three cards, which goes to the dealer. The gaming device then continues to deliver packets of three cards each, which the dealer distributes to each of the players participating in the round, for example, two players. When dealing to all of the players is complete, the dealer presses the button again to signal the end of dealing to the gaming device **102**. One final packet, delivered in anticipation of being dealt to a third, non-existent, player, goes unused and the gaming device **102** dispenses all of the remaining shuffled cards. The number of packets dealt between the first button press and the second button press may be transmitted as game data **602** by the gaming device **102** to the gaming table **104** to be collected by the server system **110** via the communication node **108**. The server system **110** can then analyze the data and determine that, of the four packets dispensed, one packet went to the dealer, one packet went to each of two players and a final packet was dispensed by the gaming device **102** but not used (since there was no third player present to receive the packet). Thus, for a gaming table **104** with a gaming device **102** configured to deal THREE CARD POKER®, the server system **110** is able to determine from packet count data that two players participated in that round of play. This participation data may then be stored with the participation data for other rounds of play at that gaming table **104** for further analysis, discussed below. While the example of THREE CARD POKER® has been used, it should be clear that the disclosed embodiment applies equally to any other game that employs packets of cards of predetermined sizes. Not-limiting examples include Ultimate Texas Hold'Em®, Mississippi Stud®, and Let it Ride®.

(69) In another example, the game being played at a gaming table **104** may be blackjack. Unlike in THREE CARD POKER®, each blackjack player may receive a different number of cards during a round of play. Thus, a different approach must be used to determine player participation in a round when the game being played at gaming table **104** is blackjack. In this case, as each card is dealt, the gaming device **102** may transmit a timestamp corresponding to the dealing of the card as game data **602** to the gaming table **104** to be collected by the system server **110** via the communication node **108**. Periodically, the server system **110** may analyze all of the timestamps collected during multiple rounds of play to identify the rounds and their lengths and to estimate and store the number of wagering positions participating in each round.

(70) For example, consider the following hypothetical set of timestamps for cards dealt in a game of blackjack:

(71) Start of first round:

(72) 21:08:02.10—First card to player #1

(73) 21:08:02.30—First card to player #2

(74) 21:08:02.48—First card to player #3

(75) 21:08:02.59—First card to player #4

(76) 21:08:03.18—First card dealer (hole card, face down)

(77) 21:08:03.38—Second card to player #1

(78) 21:08:03.56—Second card to player #2

(79) 21:08:04.15—Second card to player #3

(80) 21:08:04.35—Second card to player #4

(81) 21:08:04.56—Second card to dealer (face up)

(82) Dealer peeks at the hole card and does not have blackjack

(83) 21:10:06.21—Player #1 takes one card (hits and stands)



(84) 21:10:09.12—Player #2 takes one card (hits)  
(85) 21:11:11.45—Player #2 takes a second card (busts)  
(86) Player #3 stands and takes no additional cards.  
(87) 21:11:14.75—Player #4 takes a card and stands.  
(88) 21:11:17.25—Player #4 takes one card (hits and stands).  
(89) 21:11:19.40—Dealer turns over the hole card, takes one additional card and stands.  
(90) Start of next round:  
(91) 21:11:26.02—First card to player 1  
(92) 21:11:26.24—First card to player 2 . . . .  
(93) In the first round of the above example, the timestamp data shows that ten cards were quickly dealt, generally within one second of each other. Additional cards were then dealt with longer pauses in between, followed by an even longer pause before multiple cards were drawn out again with less than one second between them.  
(94) Because each blackjack player and the dealer may take a number of additional cards (or none) during a round, the longer periods between timestamps of the intermediate cards are largely meaningless, except to show what they are not: cards dealt in a “burst” at the start of a round. Thus, the analysis algorithm can simply look for the rapid dealing of an even number of cards bracketed by two longer pauses. The first pause indicates the end of the previous round, wherein the dealer pays wins and removes cards from the table in preparation for the next round. The second pause occurs when the dealer examines the hole card in the new round) and then, if the dealer does not have blackjack, waits to deal a card to the first player wishing to take a hit. In this example, analysis may assume that the ten cards dealt in rapid fashion were the initial burst of a round, wherein each player and the dealer received two cards. Subtracting the two cards dealt to the dealer, it can be inferred that cards were dealt to four wagering spots at the gaming table **104** during this round. In other embodiments, the dealer may receive only a single card in the burst. In this scenario, the burst would have an odd number of cards. If the burst is an odd number, subtracting one card from the number of cards in the burst and dividing by two may be used to determine the number of positions in play.  
(95) The system server **110** can thus infer and store player participation data and game play data, for example, when each new round started, the average length of each round, and the number of wagers participating in each round. As with the THREE CARD POKER® data, this participation data may then be stored with the participation data for other rounds of play at that gaming table **104** for further analysis.  
(96) The example of blackjack and an opening burst of dealt cards is illustrative, it should be clear that the disclosed embodiment applies equally to any other game that includes a signature dealing pattern of cards identifiable by timestamps associated with each of the cards dealt during play of the card game to identify one or more rounds of play and wherein the number of cards in the signature dealing pattern of each round may be used to determine a number of players or active wagering spots within each of the rounds.  
(97) In accordance with some embodiments, the participation data may be combined with other data collected by the system server **110**. For example, to begin each round of play at a gaming table **104**, each player must make a standard wager, but may also place a separate progressive wager in order to try to win a large award for particular game outcomes. For example, in an optional progressive wager for blackjack, the progressive pay table considers a player's first two cards and the dealer's first two cards. Progressive payable payouts start when the dealer's up-card is an ace and continue with larger payouts when the dealer has a blackjack. Top payouts are awarded for a premium four-card poker hand between the four cards. The progressive wagers are typically placed on a progressive “coin sensor” at each player's respective betting position at gaming table **104**. These wagers are detected and transmitted to a progressive system, such as a GM Atlas System manufactured by LNW Gaming, Inc., to increment the value of one or more progressive pools

associated with the particular game being played at table **104**. The progressive coin sensor data from the progressive system may also be stored on a per hand basis in the system server **110**. While the coin sensor data reflects a raw count of the number of progressive wagers placed at each gaming table **104**, more useful information may be obtained when this data is combined with the above-described player participation data. For example, a percentage of players participating in the progressive game in each round at each gaming table **104** may be obtained by dividing the coin spot data for a particular round by the table headcount for that round (i.e., progressive participation percentage=coin spot data/table headcount data times **100**). Average overall progressive participation for each of a variety of progressive games being offered may then be derived from this information. Business decisions based on the relative popularity and profitability of each progressive game are then possible.

(98) FIG. **7** is a flow diagram of an example method **700** of collection participation data at a blackjack table with a gaming device **102** within the gaming environment **101** using the networked gaming device system **100**.

(99) At step **702**, data related to the time each card is dealt at the blackjack table is captured by the gaming device **102**. At step **704**, the gaming device **102** transmits the timestamp data to the gaming table **104**, which forwards it to the communication node **108** at step **706**. The timestamp data is then collected from the communication node **108** by the server system **110** at step **708**.

(100) At step **710**, the system server **110** analyzes the timestamp data to detect the start of round dealing pattern described above. Typically, this pattern will be an even number of timestamps within a second of one another that occur after the dealing of a card several seconds prior, the previous card being the last card dealt prior to the dealer reconciling any remaining bets in the previous round, removing cards from the table, etc. This pattern is followed by another delay between dealt cards of more than a second, which is caused by the dealer examining the hole card and the first player, if any, to take a hit card.

(101) At step **712**, once the start of a round has been identified, the system server **110** assigns a number of seats dealt to in the round based on the number of cards in the “burst.” The dealer's cards are subtracted. As described above, for example, if ten cards are dealt in the initial burst,  $(10-2)/2=4$  cards were dealt to four betting spots. This may or may not be the number of players, as some players may play multiple hands. The system server **110** stores player participation data and game play data, for example, when each new round started, the average length of each round, and the number of wagers participating in each round.

(102) At step **714**, the collection and analysis of game participation data may be further analyzed and compiled into reports used to make business decisions related to the operation of the gaming tables **104**, for example, how many gaming tables **104** to have in operation during particular hours or at various levels of participation, what mix of game types (blackjack, baccarat, THREE CARD POKER®, etc.) to deploy at those tables, what table wager limits to deploy at each table, the hours during which to raise or lower table wager limits, etc. In accordance with some embodiments, the system **100** may make real-time recommendations with respect to these decisions. In still other embodiments, the system **100** may automatically communicate changes to the gaming tables **104**, for example, the system may transmit commands to the table controller **304** at a particular gaming table **104** to modify minimum and maximum wager values (i.e., table wager limits) indicated on an electronic display connected to the table controller **304** or to indicate whether the gaming table **104** is open or closed on such a display. In accordance with other embodiments, participation data is processed locally at the gaming table **104**, for example, the timestamp data is stored and analyzed in the memory of the table controller

(103) In at least some embodiments, the system **100** may be used to facilitate leasing gaming devices **102** to operators of the gaming environments **101**. In particular, the system **100** may facilitate billing based on actual usage of the gaming devices **102**. In some embodiments, the system **100** permits the reporting period, and any associated billing period, to be of any duration

and based on any type of, or combination of, use. In other embodiments, billing amounts may include maintenance charges, fees, or other payable service events. Types of use for a card-handling gaming device include, but are not limited to, cards or decks inserted into the card device, cards dispensed, cards counted, cards sorted, cards or decks checked for completeness, individual hands dealt, type of game played, individual games played, game sessions played, directly or indirectly based on any amount of winnings detected during play including any progressive, individual hand reports and game reports generated, and/or request for a report from a past card usage, past game or past session data including individual hands previously generated (past data may help a casino with a patron dispute, may help with a billing dispute, etc.). This may be downloaded to a card-handling device from a central location (e.g., the server system **110**) where extended game data associated with each card-handling device may be stored, or, otherwise provided to a user (casino, operator) of the local card-handling device, if the device is unable to communicate or display the results of the request. Such data, billable events, and recallable events are based on the capabilities of each card-handling device. The level to which each card-handling device may record data in any form is reflected in the data kept at a central location for later recall, analysis, and use. Unsophisticated card-handling devices with limited reporting capabilities will have equally limited data available from any back-end system, while sophisticated card-handling devices will enable a back-end system to keep far more detailed records, respond to download requests for specific data and similar actions. The type of data available from a sophisticated card-handling device is limited only by its detectors and associated computer power. Any type of data related to card usage, deck usage or deck type (including, but not limited to, the deck's manufacturer and other data), deck or card count of any kind, ordering in a randomized deck or partial deck, data for each dealt or issued card for any event (including card counting or deck determinations, as well as game play events), and any other type of count or event based on cards in any manner used in a card-handling device is contemplated herein.

(104) The collected data may be organized, analyzed, and reported in any manner useful for either billing, meaning creating bills for payment eventually sent to the user of the device, or, maintenance of any type, including actual and predictive failure analysis and/or predictive required maintenance reports. Predictive reporting may be based in part, or in whole, on statistical analysis of the use data, error logs, interrupt events, fault reports, and any and all data, if available, from detectors or detection circuits, detection ICs, or any type of element that is configured to log or generate data regarding the condition of any element, either itself or another element. In at least some embodiments, the server system **110** and/or the gaming devices **102** may generate one or more alerts or notifications to notify a user of particular events based on analysis of the operational data.

(105) Examples of detector elements includes elements such as strain detectors or motion detectors located on, or associated with, mechanical components, and failure detection ICs measuring various electrical/electronic properties of components so that anomalous events can be reported or logged. Similarly, detection elements may be failure detection (or condition monitoring) circuits contained in larger circuits reporting/logging performance deviations or apparent out-of-spec behaviors, and/or any other detection elements that generate logs, interrupts, or other events. This further includes firmware or software that may use algorithms coupled with input from one or more components or elements of any type (mechanical elements using or interfacing to mechanical-electrical, mechanical-optical, or other elements, all electronic elements, etc.) to generate data or report on actual, possible, or predictive failure events. This is by way of example only, the concept covers collecting and/or using or evaluating any data from failure detection elements, as implemented in various models of card-handling devices now or in the future.

(106) In some embodiments, the server system **110** may be configured to at least partially control the operation of the gaming devices **102** by transmitting control data **612** to the gaming devices **102** via the gaming tables **104**. The control data **612** may automatically cause the gaming device **102** to

reconfigure and/or to perform one or more tasks. For example, if a gaming device **102** is identified as potentially malfunctioning based on the data received by the server system **110**, the server system **110** may transmit control data **612** to cause the gaming device **102** to shut down and/or perform a diagnostic operation to identify a cause of the malfunction. In some embodiments, the gaming device **102** is configured to apply the control data **612** in response to associating with the gaming table **104**. Otherwise, the gaming device **102** may ignore the control data **612**. In other embodiments, the gaming device **102** may apply at least some control data **612** (e.g., diagnostics functions, shut down functions etc.) irrespective of the gaming device **102** associating with the gaming table **104**.

(107) In certain embodiments, the system **100** may further include user transceivers **118** for tracking the location of users within the gaming environments **101**, such as employees and/or players. Each user transceiver **118** may be substantially similar to the device transceivers **206** shown in FIG. 2, though, in some embodiments, the user transceiver **118** may be different from the device transceivers. For example, the device transceiver **206** may be integrated with the device controller **202** (shown in FIG. 2), whereas the user transceiver may be a standalone apparatus. The user transceiver **118** is affixed to, coupled to, or held by a user **119** or the garments of the user **119**.

(108) The user transceiver **118** is configured to be incorporated within the method **400** (shown in FIG. 4) to determine the location of the user **119** similar to the determining the location of the gaming devices **102**. For example, the user transceiver **118** communicates with the gaming tables **104** via the first communication network **106** to determine a relative distance between the user **119** and each gaming table **104**. Based on the determined relative distances, the user transceiver generates location data indicating a relative location of the user. The location data is then transmitted to the server system **110** for storage with location data of other users and analysis. In certain embodiments, if the user **119** is an employee of the gaming environment, the user transceiver **118** may be configured to identify a role or position of the user **119**. For example, if the user **119** is a card dealer, the user transceiver **118** may transmit identification data indicating the user **119** is a card dealer to the gaming tables **104**. In some embodiments, the user transceiver **118** may be configured to collect and generate other suitable data, such as performance data, time spent at a particular gaming table **104**, and the like.

(109) Embodiments will vary as to what and where data collection, reporting, and analysis are done. In some embodiments, a gaming device may be fairly simple and relatively inexpensive, and its data collection and reporting capabilities will reflect these limitations. In one embodiment, such a gaming device will do no data analysis at all; it will all be done at a server location (or other computer that eventually receives or has access to the data). At the other end of the spectrum may be multi-functional gaming devices having the ability to perform multiple game functions as well as support multiple games, and further having their own displays, printers, and other components. Such sophisticated gaming devices may do some analysis of the data collected that enables them to generate, locally in a manner readable by humans. This may include output to a printer or on a screen. This enables a casino or other user of the device to track their usage, current amount owed, possible servicing requirements, and other parameters.

(110) It is expected that the most sophisticated data analysis regarding predictive failure analysis will be done centrally, at least in part because more sophisticated analysis uses data from many gaming devices. However, some or all of the results of such analysis may be downloaded to any individual gaming devices that are sophisticated enough to use them, typically in the form of what the gaming device may detect in terms of patterns in its own data. Examples of such patterns may include the occurrence of certain logged events during a specified time period from a component, or certain data entries, measurements, interrupts, or logs from a set of components that by themselves do not raise an alarm, but do raise an alarm when they occur together, etc. Any and all patterns determined by data analysis are conceptually included herein.

(111) Reference in the specification to “one embodiment” or to “an embodiment” means that a

particular feature, structure, or characteristic described in connection with the embodiments is included in at least one embodiment. The appearances of the phrase “in one embodiment” or “an embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

(112) Some portions of the detailed description are presented in terms of algorithms and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of steps (instructions) leading to a desired result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical, magnetic, or optical signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It is convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like. Furthermore, it is also convenient at times, to refer to certain arrangements of steps requiring physical manipulations or transformation of physical quantities or representations of physical quantities as modules or code devices, without loss of generality.

(113) However, all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the following discussion, it is appreciated that throughout the description, discussions utilizing terms such as “processing,” “computing,” “calculating,” “determining,” “displaying,” or “determining,” or the like, refer to the action and processes of a computer system, or similar electronic computing device (such as a specific computing machine), that manipulates and transforms data represented as physical (electronic) quantities within the computer system memories or registers or other such information storage, transmission or display devices.

(114) Certain aspects of the embodiments include process steps and instructions described herein in the form of an algorithm. It should be noted that the process steps and instructions of the embodiments can be embodied in software, firmware, or hardware, and when embodied in software, could be downloaded to reside on and be operated from different platforms used by a variety of operating systems. The embodiments can also be in a computer program product, which can be executed on a computing system.

(115) The embodiments also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the purposes, e.g., a specific computer, or it may comprise a general-purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a computer-readable storage medium, such as, but not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, application specific integrated circuits (ASICs), or any type of media suitable for storing electronic instructions, and each coupled to a computer system bus. Memory can include any of the above and/or other devices that can store information/data/programs and can be transient or non-transient medium, where a non-transient or non-transitory medium can include memory/storage that stores information for more than a minimal duration. Furthermore, the computers referred to in the specification may include a single processor or may be architectures employing multiple processor designs for increased computing capability.

(116) The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Various general-purpose systems may also be used with programs in accordance with the teachings herein, or it may prove convenient to construct more specialized apparatus to perform the method steps. The structure for a variety of these systems will appear

from the description herein. In addition, the embodiments are not described with reference to any particular programming language. It will be appreciated that a variety of programming languages may be used to implement the teachings of the embodiments as described herein, and any references herein to specific languages are provided for disclosure of enablement and best mode. (117) While particular embodiments and applications have been illustrated and described herein, it is to be understood that the embodiments are not limited to the precise construction and components disclosed herein and that various modifications, changes, and variations may be made in the arrangement, operation, and details of the methods and apparatuses of the embodiments without departing from the spirit and scope of the embodiments as defined in the appended claims.

## Claims

1. A system for monitoring player participation at moveable table game devices used in connection with stationary gaming tables in a gaming environment, the system comprising: a plurality of stationary gaming tables positioned at a plurality of respective locations, each gaming table equipped with a table transceiver and associated memory, each table transceiver in communication with a first communication network and a second communication network different from the first communication network; a moveable table game device equipped with a device transceiver and associated memory, the device transceiver configured to transmit and receive data signals including operational data via the first communication network with table transceivers of the plurality of stationary gaming tables; one or more processors, individually or in combination, being configured to generate operational data associated with the moveable table game device at least partially as a function of data associated with cards distributed by the moveable table game device during play of a card game; a communication node in communication with the second communication network, the communication node configured to collect the generated operational data from at least one of the table transceivers over the second communication network; and a server with associated memory, the server communicatively coupled to the communication node and configured to receive, store and analyze the collected operational data.
2. The system of claim 1, wherein the first communication network is an ultra-wideband network.
3. The system of claim 1, wherein the operational data comprises a number of packets of cards distributed by the moveable table game device between an occurrence of a first event and an occurrence of a second event.
4. The system of claim 3, wherein the card game is at least one of THREE CARD POKER®, Ultimate Texas Holdem®, Mississippi Stud®, or Let It Ride®.
5. The system of claim 1, wherein the operational data comprises timestamps associated with each card distributed by the moveable table game device.
6. The system of claim 5, wherein the server analyzes the timestamps to identify a timestamp-based signature pattern of cards dealt during a round of play of the card game.
7. The system of claim 6, wherein the server determines a player participation level based on the number of cards dealt in the signature pattern of cards.
8. The system of claim 7, wherein the card game is blackjack.
9. A method of determining player participation at one of a plurality of stationary gaming tables, the method comprising: distributing cards during a plurality of rounds of a card game played at the one of the plurality of stationary gaming tables via a moveable table game device equipped with one or more processors, a device transceiver and associated memories, the device transceiver configured to communicate data signals via a first communication network to and from a table transceiver and associated memory of the one of the plurality of stationary gaming tables, the table transceiver in communication with the first communication network and a second communication network different from the first communication network; generating, via the one or more processors, individually or in combination, timestamp data associated with the cards distributed by

the moveable table game device; transmitting, via the device transceiver and the table transceiver, the timestamp data to the stationary gaming table; transmitting, via the table transceiver, the timestamp data to a communication node in communication with the second communication network, the communication node configured to collect the generated timestamp data from the table transceiver over the second communication network; receiving the timestamp data at a server with associated memory, the server communicatively coupled to the communication node and configured to receive, store, and analyze the collected timestamp data; analyzing the timestamp data to identify a plurality of rounds of play of the card game according to a timestamp-based signature dealing pattern in each round; and based on the number of cards dealt in the signature dealing pattern in each round, determining and assigning a player participation level to each of the identified rounds.

10. The method of claim 9, wherein the card game is blackjack.

11. The method of claim 10, wherein the signature dealing pattern in each round comprises an initial burst of dealt cards.

12. The method of claim 9, wherein the number of cards in the signature dealing pattern is odd and wherein the participation level in each round is determined at least in part by dividing the number of cards in the signature dealing pattern by two.

13. The method of claim 12, wherein the number of cards in the signature dealing pattern is reduced by one prior to determination of each participation level to account for a card dealt to the dealer.

14. The method of claim 9, wherein the signature dealing pattern is identified by a block of contiguous timestamps of cards separated by an interval less than one second.

15. The method of claim 9, further comprising generating a recommendation for action based on analysis of the participation level assigned to one or more of the identified rounds of play.

16. The method of claim 15, wherein the analysis of the participation level assigned to the one or more identified rounds of play comprises progressive game data.

17. The method of claim 15, wherein the recommendation for action comprises adjusting wagering limits at the one of the plurality of gaming tables.

18. A method of determining player participation at one of a plurality of stationary gaming tables, the method comprising: distributing cards during a plurality of rounds of a card game played at the one of the plurality of stationary gaming tables via a moveable table game device equipped with one or more processors, a device transceiver and associated memories, the device transceiver configured to communicate data signals via a first communication network to and from a table transceiver and associated memory of the one of the plurality of stationary gaming tables; generating, via the one or more processors, individually or in combination, timestamp data associated with the cards distributed by the moveable table game device; transmitting, via the device transceiver and the table transceiver, the timestamp data to a table controller of the stationary gaming table; analyzing the timestamp data, via the table controller, to identify a plurality of rounds of play of the card game according to a timestamp-based signature dealing pattern in each round; and based on the number of cards dealt in the signature dealing pattern in each round, determining, and assigning a player participation level to each of the identified rounds.

19. The method of claim 18, wherein the signature dealing pattern in each round comprises an initial burst of dealt cards.

20. The method of claim 18, wherein the number of cards in the signature dealing pattern is odd and wherein the participation level in each round is determined at least in part by dividing the number of cards in the signature dealing pattern by two.

---