



US01238839B2

(12) **United States Patent**
Sankuratripati

(10) **Patent No.:** **US 12,388,839 B2**

(45) **Date of Patent:** ***Aug. 12, 2025**

(54) **DATA COMPRISING ENCRYPTION KEY**

(56) **References Cited**

(71) Applicant: **Snap Inc.**, Santa Monica, CA (US)

U.S. PATENT DOCUMENTS

(72) Inventor: **Subhash Sankuratripati**, Playa Vista, CA (US)

6,038,295 A 3/2000 Mattes
6,980,909 B2 12/2005 Root et al.
(Continued)

(73) Assignee: **Snap Inc.**, Santa Monica, CA (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

CA 2887596 A1 7/2015

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

“U.S. Appl. No. 15/099,719, Corrected Notice of Allowability mailed Nov. 5, 2018”, 4 pgs.

(Continued)

(21) Appl. No.: **18/209,567**

(22) Filed: **Jun. 14, 2023**

Primary Examiner — Jeffrey C Pwu

Assistant Examiner — Samuel Ambaye

(65) **Prior Publication Data**

US 2023/0328074 A1 Oct. 12, 2023

(74) *Attorney, Agent, or Firm* — Schwegman Lundberg & Woessner, P.A.

(57)

ABSTRACT

Systems and methods for end to end encryption are provided. In example embodiments, a computer accesses an image including a geometric shape. The computer determines that the accessed image includes a candidate shape inside the geometric shape. The computer determines, using the candidate shape, an orientation of the geometric shape. The computer determines a public key of a communication partner device by decoding, based on the determined orientation, data encoded within the geometric shape. The computer receives a message. The computer verifies, based on the public key of the communication partner device, whether the message is from the communication partner device. The computer provides an output including the message and an indication of the communication partner device if the message is verified to be from the communication partner device. The computer provides an output indicating an error if the message is not verified to be from the communication partner device.

Related U.S. Application Data

(63) Continuation of application No. 17/445,553, filed on Aug. 20, 2021, now Pat. No. 11,716,336, which is a (Continued)


(51) **Int. Cl.**
H04L 9/32 (2006.01)
H04L 9/08 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04L 63/123** (2013.01); **H04L 9/0838** (2013.01); **H04L 9/0891** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC . H04L 63/123; H04L 63/0442; H04L 63/061;
H04L 9/0828

(Continued)

20 Claims, 17 Drawing Sheets



Related U.S. Application Data

continuation of application No. 16/855,437, filed on Apr. 22, 2020, now Pat. No. 11,128,640, which is a continuation of application No. 16/256,639, filed on Jan. 24, 2019, now Pat. No. 10,659,474, which is a continuation of application No. 15/099,719, filed on Apr. 15, 2016, now Pat. No. 10,225,265.

- (51) **Int. Cl.**
H04L 9/40 (2022.01)
H04W 12/033 (2021.01)
- (52) **U.S. Cl.**
 CPC **H04L 63/0442** (2013.01); **H04L 63/061** (2013.01); **H04W 12/033** (2021.01)
- (58) **Field of Classification Search**
 USPC 713/171
 See application file for complete search history.

- (56) **References Cited**

U.S. PATENT DOCUMENTS

7,173,651	B1	2/2007	Knowles	
7,411,493	B2	8/2008	Smith	
7,535,890	B2	5/2009	Rojas	
8,131,597	B2	3/2012	Hudetz	
8,199,747	B2	6/2012	Rojas et al.	
8,332,475	B2	12/2012	Rosen et al.	
8,718,333	B2	5/2014	Wolf et al.	
8,724,622	B2	5/2014	Rojas	
8,874,677	B2	10/2014	Rosen et al.	
8,909,679	B2	12/2014	Root et al.	
8,995,433	B2	3/2015	Rojas	
9,040,574	B2	5/2015	Wang et al.	
9,055,416	B2	6/2015	Rosen et al.	
9,100,806	B2	8/2015	Rosen et al.	
9,100,807	B2	8/2015	Rosen et al.	
9,191,776	B2	11/2015	Root et al.	
9,204,252	B2	12/2015	Root	
9,443,227	B2	9/2016	Evans et al.	
9,489,661	B2	11/2016	Evans et al.	
9,491,134	B2	11/2016	Rosen et al.	
9,501,681	B1 *	11/2016	Wang	G06K 7/1417
10,225,265	B1	3/2019	Sankuratripati	
10,659,474	B1	5/2020	Sankuratripati et al.	
11,128,640	B2	9/2021	Sankuratripati	
11,716,336	B2	8/2023	Sankuratripati	
2003/0200450	A1	10/2003	England et al.	
2004/0068470	A1 *	4/2004	Klyne	G06Q 20/388 380/279
2005/0069196	A1 *	3/2005	Uchiyama	G06T 7/70 382/154
2008/0031446	A1 *	2/2008	Suga	H04N 21/4408 386/E5.069
2011/0202598	A1	8/2011	Evans et al.	
2012/0124150	A1	5/2012	Ge et al.	
2012/0209924	A1	8/2012	Evans et al.	
2016/0127326	A1 *	5/2016	Lin	H04W 12/04 713/171
2016/0373418	A1 *	12/2016	Stahl	G06F 21/44
2020/0389466	A1	12/2020	Sankuratripati	
2022/0046029	A1	2/2022	Sankuratripati	

OTHER PUBLICATIONS

"U.S. Appl. No. 15/099,719, Examiner Interview Summary mailed Mar. 16, 2018", 3 pgs.

"U.S. Appl. No. 15/099,719, Final Office Action mailed Aug. 10, 2018".

"U.S. Appl. No. 15/099,719, Non Final Office Action mailed Jan. 17, 2018", 17 pgs.

"U.S. Appl. No. 15/099,719, Notice of Allowance mailed Oct. 17, 2018", 8 pgs.

"U.S. Appl. No. 15/099,719, Response filed Apr. 17, 2018 to Non Final Office Action mailed Jan. 17, 2018", 14 pgs.

"U.S. Appl. No. 15/099,719, Response filed Sep. 14, 2018 to Final Office Action mailed Aug. 10, 2018", 10 pgs.

"U.S. Appl. No. 16/256,639, Corrected Notice of Allowability mailed Mar. 17, 2020".

"U.S. Appl. No. 16/256,639, Non Final Office Action mailed Jul. 11, 2019", 19 pgs.

"U.S. Appl. No. 16/256,639, Notice of Allowance mailed Jan. 15, 2020", 7 pgs.

"U.S. Appl. No. 16/256,639, Response filed Oct. 8, 2019 to Non-Final Office Action mailed Jul. 11, 2019", 9 pgs.

"U.S. Appl. No. 16/855,437, 312 Amendment filed Aug. 13, 2021", 8 pgs.

"U.S. Appl. No. 16/855,437, Corrected Notice of Allowability mailed May 25, 2021", 2 pgs.

"U.S. Appl. No. 16/855,437, Corrected Notice of Allowability mailed Jun. 3, 2021", 4 pgs.

"U.S. Appl. No. 16/855,437, Examiner Interview Summary mailed Apr. 7, 2021", 2 pgs.

"U.S. Appl. No. 16/855,437, Final Office Action mailed Mar. 4, 2021", 27 pgs.

"U.S. Appl. No. 16/855,437, Non Final Office Action mailed Oct. 16, 2020", 42 pgs.

"U.S. Appl. No. 16/855,437, Notice of Allowance mailed May 13, 2021", 7 pgs.

"U.S. Appl. No. 16/855,437, Preliminary Amendment filed Aug. 31, 2020", 8 pgs.

"U.S. Appl. No. 16/855,437, PTO Response to Rule 312 Communication mailed Aug. 23, 2021", 2 pgs.

"U.S. Appl. No. 16/855,437, Response filed Feb. 16, 2021 to Non Final Office Action mailed Oct. 16, 2020", 12 pgs.

"U.S. Appl. No. 16/855,437, Response filed May 4, 2021 to Final Office Action mailed Mar. 4, 2021", 10 pgs.

"U.S. Appl. No. 17/445,553, Final Office Action mailed Dec. 30, 2022", 20 pgs.

"U.S. Appl. No. 17/445,553, Non Final Office Action mailed Sep. 23, 2022", 22 pgs.

"U.S. Appl. No. 17/445,553, Notice of Allowance mailed Mar. 14, 2023", 7 pgs.

"U.S. Appl. No. 17/445,553, Preliminary Amendment filed Nov. 3, 2021", 6 pgs.

"U.S. Appl. No. 17/445,553, Response filed Feb. 23, 2023 to Final Office Action mailed Dec. 30, 2022", 8 pgs.

"U.S. Appl. No. 17/445,553, Response filed Dec. 13, 2022 to Non Final Office Action mailed Sep. 23, 2022", 9 pgs.

Leyden, John, "This SMS will self-destruct in 40 seconds", [Online] Retrieved from the Internet: <URL: <http://www.theregister.co.uk/2005/12/12/stealthtext/>>, (Dec. 12, 2005), 1 pg.

* cited by examiner




FIG. 1

200




FIG. 2




FIG. 3A





FIG. 3B








FIG. 5






FIG. 9




FIG. 8




FIG. 11




FIG. 10




FIG. 12B

FIG. 12A




FIG. 12C




FIG. 14




FIG. 13




FIG. 16




FIG. 15




FIG. 18




FIG. 17




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23

1

DATA COMPRISING ENCRYPTION KEY**CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 17/445,553, filed on Aug. 20, 2021, which is a continuation of U.S. patent application Ser. No. 16/855,437, filed on Apr. 22, 2020, which is a continuation of U.S. patent application Ser. No. 16/256,639, filed on Jan. 24, 2019, which is a continuation of U.S. patent application Ser. No. 15/099,719, filed on Apr. 15, 2016, each of which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

Embodiments of the present disclosure relate generally to computing technology and, more particularly, but not by way of limitation, to end to end encryption.

BACKGROUND

Users of computing devices send messages to one another via messaging applications. To get from a sender to a recipient, a message may travel over a network, where it may pass through various servers of the messaging application provider or be accessible to various eavesdroppers. However, the sender and the recipient may desire to keep their communications private. In other words, the sender and the recipient may desire to allow themselves to view the messages sent between them, but not to allow the messaging application provider or any eavesdroppers to view those messages. As the foregoing illustrates, a new approach for end to end encryption may be desirable.

BRIEF DESCRIPTION OF THE DRAWINGS

Various ones of the appended drawings merely illustrate example embodiments of the present disclosure and should not be considered as limiting its scope.

FIG. 1 is a block diagram illustrating a networked system, according to some example embodiments.

FIG. 2 is a block diagram illustrating an example embodiment of a custom pattern system, according to some example embodiments.

FIGS. 3A and 3B are diagrams illustrating examples of optical barcodes employing a custom functional pattern, according to some example embodiments.

FIG. 4 is a diagram illustrating an example of identifying and decoding an optical barcode employing a custom functional pattern, according to some example embodiments.

FIG. 5 is a flow diagram illustrating an example method for identifying and decoding an optical barcode using a custom functional pattern, according to some example embodiments.

FIG. 6 is a flow diagram illustrating further example operations identifying the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. 7 is a diagram illustrating an example of identifying the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. 8 is a flow diagram illustrating further example operations for identifying the optical barcode using the custom functional pattern, according to some example embodiments.

2

FIG. 9 is a diagram illustrating an example of identifying the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. 10 is a flow diagram illustrating further example operations for decoding the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. 11 is a diagram illustrating an example of decoding the optical barcode using the custom functional pattern, according to some example embodiments.

FIGS. 12A, 12B, and 12C are diagrams illustrating various image transformations used to facilitate decoding the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. 13 is a flow diagram illustrating further example operations for decoding the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. 14 is a diagram illustrating an example of decoding the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. 15 is a user interface diagram depicting an example user interface for identifying the optical barcode, according to some example embodiments.

FIG. 16 is a user interface diagram depicting an example user interface for performing an action associated with the optical barcode, according to some example embodiments.

FIG. 17 is a flow diagram illustrating further example operations for generating the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. 18 is a user interface diagram depicting an example user interface for generating the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. 19 is a user interface diagram depicting an example mobile device and mobile operating system interface, according to some example embodiments.

FIG. 20 is a block diagram illustrating an example of a software architecture that may be installed on a machine, according to some example embodiments.

FIG. 21 is a block diagram presenting a diagrammatic representation of a machine in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any of the methodologies discussed herein, according to an example embodiment.

FIG. 22 is a data flow diagram of an end to end encryption method, according to some example embodiments.

FIG. 23 is a flow chart of a method for verifying that a message is from a communication partner based on information stored in an image, according to some embodiments.

DETAILED DESCRIPTION

The description that follows includes systems, methods, techniques, instruction sequences, and computing machine program products that embody illustrative embodiments of the disclosure. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide an understanding of various embodiments of the inventive subject matter. It will be evident, however, to those skilled in the art, that embodiments of the inventive subject matter may be practiced without these specific details. In general, well-known instruction instances, protocols, structures, and techniques are not necessarily shown in detail.

QR codes, and other optical barcodes (e.g., Universal Product Code (UPC) barcodes, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code), are a convenient way to share small pieces of information with users of mobile devices, wearable devices, and other smart devices. For instance, QR codes are two-dimensional optical barcodes that encode information readable by a device (e.g., a smart phone) equipped with a camera sensor. Typically, a QR code includes one or more functional patterns such as a finder pattern used for identification and recognition of the QR code or an alignment pattern used to facilitate decoding. Conventional finder patterns comprise multiple markings that are generic in design such as square marks placed in all corners except the bottom right corner (as is the case with a QR code). These finder patterns are absent aesthetic elements such as curves, non-uniformities, and other stylistic elements and often conform to a particular standard to promote open use of the optical barcode.

In various example embodiments, an optical barcode that uses custom or non-standard functional patterns provides users with an aesthetically pleasing, branded barcode that allows for an exclusive experience associated with the optical barcode. For example, an entity logo (e.g., a logo of a company, organization, or individual) can be used as a finder pattern, and in some instances an alignment pattern, to create a branded and exclusive optical barcode that is machine-readable using software provided by the entity. In a specific example, a “snapcode” is an optical barcode that uses the SNAPCHAT® logo as a functional pattern.

In an example embodiment, a custom pattern system receives image data representing an image from a user device. For example, the custom pattern system receives the image data from an optical sensor (e.g., a camera sensor) of a smart phone of the user. In various embodiments, the image data from the user device is received in response to a user-initiated image capture, a periodic monitoring of image data being detected by the optical sensor of the user device, an access of stored image data, or a combination thereof. A portion of the image data can include data representing an optical barcode employing a custom graphic for a particular functional pattern (e.g., a finder pattern). In some scenarios, the image data includes extraneous or irrelevant data along with the data pertaining to the optical barcode (e.g., an image of an optical barcode includes a background that is not pertinent to decoding the optical barcode). In a specific example, the optical sensor of the user device captures an image of a promotional poster that includes a particular optical barcode. The image of the promotional poster can include the particular optical barcode along with irrelevant portions of the promotional poster or background that surrounds the particular optical barcode.

After the custom pattern system receives the image data, the custom pattern system searches the image data of the image for the custom graphic to determine whether the image includes the optical barcode. That is to say, the custom graphic is used as a finder pattern for recognition, identification, or detection of the optical barcode within the image. In an example embodiment, the custom pattern system searches for the custom graphic by extracting a candidate shape feature, or multiple candidate shape features, from the image data. For example, the custom pattern system performs an edge detection technique, or another image processing technique, to identify the candidate shape feature such as a contour line of the image. The custom pattern system then determines whether the candidate shape feature satisfies shape feature rules or criteria. For instance, if a particular candidate shape feature is a contour line, the

custom pattern system can determine whether the contour line is an enclosed line that encircles a portion of the image. Consistent with some embodiments, the shape feature rules filter out irrelevant or extraneous candidate shape features or candidate shape features with a low probability of being the custom graphic.

In response to the candidate shape feature satisfying the shape feature rules, the custom pattern system identifies the custom graphic by comparing the candidate shape feature with a reference shape feature of the custom graphic. For example, the custom pattern system can compare an area or size of the candidate shape feature with a reference area or size of the reference shape feature. In this example, the custom pattern system identifies the custom graphic based on a match or near match (e.g., a percentage match above a threshold) between the candidate shape feature and the reference shape feature. In this way, the custom pattern system uses the custom graphic as a finder pattern to identify the presence of the optical barcode within a portion of the image.

In further example embodiments, the custom graphic functions as an alignment pattern to facilitate the custom pattern system decoding the data encoded in the optical barcode. In an example embodiment, the custom pattern system extracts spatial attributes of the custom graphic in the image from the image data. For example, the custom pattern system extracts a position, scale, or orientation of the custom graphic from the image data. The custom pattern system decodes data encoded in the image from the image data using the spatial attributes of the custom graphic in the image. For instance, the custom pattern system can perform an image transform using the spatial attributes (e.g., a de-skew, a rotation, a scale, or another type of image transform) to improve detectability/readability of data encoded in a portion of the image. In this way, the custom pattern system uses the custom graphic as an alignment pattern to facilitate decoding the optical barcode.

Accordingly, the custom pattern system uses the custom graphic as a functional pattern of the optical barcode without utilizing conventional functional patterns. Using the custom graphic as a functional pattern allows for an aesthetically pleasing design and can provide exclusivity to a particular software application as the functional pattern does not necessarily conform to an open standard and thus is readable exclusively by the particular software application.

Some embodiments relate to verifying that a message is from a communication partner based on information stored in an image. A computing device accesses an image. The image includes a geometric shape, such as a square or rectangle with rounded corners. The image may be accessed from an application, such as a web browser, a social networking application, an email application, a messaging application, etc. The image may be accessed via a camera of the computing device, for example, by pointing the camera at the image, which may be printed on a signpost, billboard, bus stop, etc. The computing device determines that the accessed image includes a candidate shape (e.g., the SNAPCHAT® ghost logo or another candidate shape). The computing device determines, using the candidate shape, an orientation (e.g., an upward and downward direction) of the geometric shape. The computing device determines a public key of a communication partner device by decoding, based on the determined orientation, data encoded within the geometric shape. Later, the computing device receives a message. The computing device verifies, based on the public key of the communication partner device, whether the message is from the communication partner device. If the

message is verified to be from the communication partner device, the computing device outputs the message. Otherwise, the computing device outputs an error indicator.

According to one example implementation, a user may visit a coffee shop. On a wall of the coffee shop, the user may see a printed advertisement for a mathematics tutor that includes a square with rounded corners with a logo of a messaging application inside of it. The user may wish to communicate with the mathematics tutor to request tutoring. In order to establish this communication, the user may open the messaging application on a mobile phone and point a camera of the mobile phone to the square. In response, the messaging application may initiate an “add friend” process with the mathematics tutor, to allow the user to communicate with the mathematics tutor. During the “add friend” process, the user and the mathematics tutor exchange public keys. After completing the “add friend” process and exchanging the public keys, the user may securely communicate with the mathematics tutor. Messages between the user and the mathematics tutor may be encrypted, using the techniques described herein, to prevent the messages from being readable at a server of the messaging application or by any eavesdroppers, while allowing the messages to be read by both the user and the mathematics tutor.

As a result of some implementations of the subject technology, a user of a messaging service may dictate who can view messages he/she sends, and prevent access to the messages by eavesdroppers or engineers of the messaging service, who may have access to the server of the messaging service. In the event that the servers of the messaging service are compromised, messages stored thereat may be stored in a form that is not readable to eavesdroppers.

FIG. 1 is a network diagram depicting a network system 100 having a client-server architecture configured for exchanging data over a network, according to one embodiment. For example, the network system 100 may be a messaging system where clients communicate and exchange data within the network system 100. The data may pertain to various functions (e.g., sending and receiving text and media communication, determining geolocation, etc.) and aspects associated with the network system 100 and its users. Although illustrated herein as client-server architecture, other embodiments may include other network architectures, such as peer-to-peer or distributed network environments.

As shown in FIG. 1, the network system 100 includes a social messaging system 130. The social messaging system 130 is generally based on a three-tiered architecture, consisting of an interface layer 124, an application logic layer 126, and a data layer 128. As is understood by skilled artisans in the relevant computer and Internet-related arts, each module or engine shown in FIG. 1 represents a set of executable software instructions and the corresponding hardware (e.g., memory and processor) for executing the instructions. To avoid obscuring the inventive subject matter with unnecessary detail, various functional modules and engines that are not germane to conveying an understanding of the inventive subject matter have been omitted from FIG. 1. Of course, additional functional modules and engines may be used with a social messaging system, such as that illustrated in FIG. 1, to facilitate additional functionality that is not specifically described herein. Furthermore, the various functional modules and engines depicted in FIG. 1 may reside on a single server computer, or may be distributed across several server computers in various arrangements. Moreover, although the social messaging system 130 is

depicted in FIG. 1 as a three-tiered architecture, the inventive subject matter is by no means limited to such an architecture.

As shown in FIG. 1, the interface layer 124 consists of one or more interface modules (e.g., a web server) 140, which receive requests from various client-computing devices and servers, such as client device(s) 110 executing client application(s) 112, and third party server(s) 120 executing third party application(s) 122. In response to received requests, the interface module(s) 140 communicate appropriate responses to requesting devices via a network 104. For example, the interface modules 140 can receive requests such as Hypertext Transfer Protocol (HTTP) requests, or other web-based Application Programming Interface (API) requests.

The client device(s) 110 can execute conventional web browser applications or applications (also referred to as “apps”) that have been developed for a specific platform to include any of a wide variety of mobile computing devices and mobile-specific operating systems (e.g., IOS™, ANDROID™, WINDOWS® PHONE). In an example, the client device(s) 110 are executing the client application(s) 112. The client application(s) 112 can provide functionality to present information to a user 106 and communicate via the network 104 to exchange information with the social messaging system 130. Each client device 110 can comprise a computing device that includes at least a display and communication capabilities with the network 104 to access the social messaging system 130. The client device(s) 110 comprise, but are not limited to, remote devices, work stations, computers, general purpose computers, Internet appliances, hand-held devices, wireless devices, portable devices, wearable computers, cellular or mobile phones, personal digital assistants (PDAs), smart phones, tablets, ultrabooks, netbooks, laptops, desktops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, network PCs, mini-computers, and the like. Users 106 can include a person, a machine, or other means of interacting with the client devices 110. In some embodiments, the users 106 interact with the social messaging system 130 via the client device(s) 110.

As shown in FIG. 1, the data layer 128 has one or more database servers 132 that facilitate access to one or more information storage repositories or databases 134. The database(s) 134 are storage devices that store data such as member profile data, social graph data (e.g., relationships between members of the social messaging system 130), and other user data.

An individual can register with the social messaging system 130 to become a member of the social messaging system 130. Once registered, a member can form social network relationships (e.g., friends, followers, or contacts) on the social messaging system 130 and interact with a broad range of applications provided by the social messaging system 130.

The application logic layer 126 includes various application logic modules 150, which, in conjunction with the interface modules 140, generate various user interfaces with data retrieved from various data sources or data services in the data layer 128. Individual application logic modules 150 may be used to implement the functionality associated with various applications, services, and features of the social messaging system 130. For instance, a social messaging application can be implemented with one or more of the application logic modules 150. The social messaging application provides a messaging mechanism for users of the

client device(s) **110** to send and receive messages that include text and media content such as pictures and video. The client device(s) **110** may access and view the messages from the social messaging application for a specified period of time (e.g., limited or unlimited). In an example, a particular message is accessible to a message recipient for a predefined duration (e.g., specified by a message sender) that begins when the particular message is first accessed. After the predefined duration elapses, the message is deleted and is no longer accessible to the message recipient. Of course, other applications and services may be separately embodied in their own application logic module(s) **150**.

As illustrated in FIG. 1, the social messaging system **130** or the client application(s) **112** includes a custom pattern system **160** that provides functionality to identify and decode optical barcodes that employ custom functional patterns. In various embodiments, the custom pattern system **160** can be implemented as a standalone system and is not necessarily included in the social messaging system **130**. In some embodiments, the client device(s) **110** includes a portion of the custom pattern system **160** (e.g., a portion of the custom pattern system **160** may be included independently or in the client application(s) **112**). In embodiments where the client device(s) **110** includes a portion of the custom pattern system **160**, the client device(s) **110** can work alone or in conjunction with the portion of the custom pattern system **160** included in a particular application server or included in the social messaging system **130**.

FIG. 2 is a block diagram **200** of the custom pattern system **160**. The custom pattern system **160** is shown to include a communication module **210**, a presentation module **220**, a finder module **230**, an alignment module **240**, a decoder module **250**, an action module **260**, and an encoder module **270**. All, or some, of the modules **210-270** communicate with each other, for example, via a network coupling, shared memory, and the like. Each module of the modules **210-270** can be implemented as a single module, combined into other modules, or further subdivided into multiple modules. Other modules not pertinent to example embodiments can also be included, but are not shown.

The communication module **210** provides various communications functionality. For example, the communication module **210** receives, accesses, or otherwise obtains image data of an image from a user device. In a specific example, the communication module **210** receives substantially real-time image data from a camera sensor of a smart phone (e.g., a single frame of image data or a continuous stream of frames captured by a camera sensor of the smart phone). The communication module **210** exchanges network communications with the database server(s) **132**, the client device(s) **110**, and the third party server(s) **120**. The information retrieved by the communication module **210** includes data associated with the user (e.g., user **106**) (e.g., member profile data from an online account or social network service data) or other data to facilitate the functionality described herein.

The presentation module **220** provides various presentation and user interface functionality operable to interactively present and receive information to and from the user. For instance, the presentation module **220** is utilizable to present user interfaces generated in response to decoding the optical barcode. In other instances, the presentation module **220** generates user interfaces that include optical barcode(s). In various embodiments, the presentation module **220** presents or causes presentation of information (e.g., visually displaying information on a screen, acoustic output, haptic feedback). The process of interactively presenting information is

intended to include the exchange of information between a particular device and the user. The user may provide input to interact with the user interface in many possible manners, such as alphanumeric, point based (e.g., cursor), tactile, or other input (e.g., touch screen, tactile sensor, light sensor, infrared sensor, biometric sensor, microphone, gyroscope, accelerometer, or other sensors). The presentation module **220** provides many other user interfaces to facilitate functionality described herein. The term “presenting” as used herein is intended to include communicating information or instructions to a particular device that is operable to perform presentation based on the communicated information or instructions.

The finder module **230** provides image processing functionality to identify, recognize, or detect the custom graphic being employed as a finder pattern in the optical barcode. For example, the finder module **230** extracts and analyzes candidate shape features or candidate contour characteristics from image data of the image received from the user device (e.g., the client device(s) **110**). The finder module **230** determines satisfaction of various rules or criteria associated with the extracted candidate shape features. The finder module **230** compares the extracted candidate shape features with reference shape features of the custom graphic, or another reference image, to identify the custom graphic included in the image. The finder module **230** can employ a wide variety of schemes and techniques to extract the candidate shape features from the image data of the image and subsequently identify the custom graphic based on an analysis of the candidate shape features. Examples of those techniques are illustrated later with respect to FIGS. 5-14.

The alignment module **240** provides image processing functionality to determine an alignment of the optical barcode using the custom graphic. The custom pattern system **160** can use the alignment to facilitate decoding of data encoded in the optical barcode. In this way, the custom graphic functions as an alignment pattern for the optical barcode. For example, the alignment module **240** extracts spatial attributes of the custom graphic in the image from the image data. In various embodiments, the spatial attributes include at least one of position, orientation, scale, or another spatial aspect of the optical barcode. The alignment module **240** determines an alignment of the optical barcode based on the spatial attributes (e.g., a particular orientation of the optical barcode). In an example, the alignment module **240** can determine an alignment including position and orientation based on the spatial attributes and generate a transformed image according to the alignment. The custom pattern system **160** can then use the transformed image to decode data encoded in a portion of the transformed image.

The decoder module **250** provides functionality to decode data encoded in the image using the spatial attributes or the determined alignment of the custom graphic in the image. For instance, the decoder module **250** can decode the data encoded in the image from an image transformed according to the spatial attributes of the custom graphic extracted from image data. In an embodiment, the decoder module **250** detects markings (e.g., high contrast dots, squares, or other marks in the image) representing data encoded in a portion of the image from the image data. In a specific example, the decoder module **250** employs a Reed-Solomon error correction scheme (or any other error correction scheme) to decode data encoded in the image. The Reed-Solomon error correction scheme (or other error correction scheme) allows for a successful or valid decoding even when a certain percentage of data could not be decoded from the optical barcode (e.g., damaged bits or incorrectly decoded bits). In some

embodiments, the user or an administrator of the custom pattern system **160** configures a tolerance value for an amount of damaged or incorrectly decoded data acceptable when decoding the optical barcode. In some embodiments, the decoder module **250** also provides image processing functionality to improve decoding of the optical barcode. For instance, the decoder module **250**, as well as the alignment module **240**, can perform image transforms of the image (e.g., perform image sharpening, de-noise processing, other digital filtering, or other image processing techniques to improve decoding accuracy).

The action module **260** provides functionality to perform a variety of actions based on decoding the data encoded in the image. For example, the data encoded in a portion of the image can indicate a particular action or include information to be used in conjunction with a particular action. In a specific example, the data encoded in a portion of the image can comprise a user name, or other user identification, of a member of a social networking service, and based on decoding the user name, the action module **260** can perform an action on the social networking service corresponding to the user name (e.g., sending a message to the member associated with the user name). In some embodiments, the action module **260** performs an action specific to a particular app that scans the image (e.g., a function available to a user of the app but otherwise unavailable). In some instances, the action module **260** performs the action without communicating with an external server (e.g., an action locally performed on the user device that scanned the snapcode).

The encoder module **270** provides functionality to generate and encode data into an optical barcode that employs the custom graphic as one or more functional patterns (e.g., generating snapcodes). As discussed above in connection with the decoder module **250**, in a specific example the encoder module **270** can employ a technique such as Reed-Solomon error correction (or any other error correction) to encode data. In an example embodiment, the encoder module **270** renders a machine-readable arrangement of marks that represents the data to be encoded. The encoder module **270** can then generate the machine-readable optical barcode using the rendered arrangement of marks and the custom graphic to be used as a functional pattern.

FIGS. 3A and 3B are diagrams illustrating examples of optical barcodes employing the custom graphic for a finder pattern or an alignment pattern (e.g., snapcodes). Diagram **300** shows an example optical barcode that includes a custom graphic **310** (e.g., a company logo), and markings **320** that represent data encoded into the optical barcode. In this example, the custom graphic **310** is a company logo such as the SNAPCHAT® “ghost” logo. It will be appreciated that the SNAPCHAT® “ghost” logo is merely an example custom graphic, and other graphics, icons, or symbols can be employed as a finder pattern or alignment pattern using the techniques described herein. Other example custom graphics used as a functional pattern can include designs with multiple paths, multiple polygons, multiple aesthetic elements, or other design features.

As shown in the diagram **300**, the markings **320** are dots that are arranged in a pattern with a particular spacing or positioning readable by a machine. Although the diagram **300** shows the markings **320** as dots, other shapes and marks can be employed (e.g., squares or asymmetric shapes of various geometries). The markings **320** can be arranged in a uniform pattern or a non-uniform pattern. In some instances, the marks can be of different sizes or a uniform size. Additionally, the markings **320** can be in a predetermined arrangement or an arrangement that is dynamically deter-

minable when decoding data from the markings. In some embodiments, the custom graphic **310** and the markings **320** can be surrounded by a bounding shape, such as an outer box **325**. Although the outer box **325** of the diagram **300** is shown as a square with rounded corners, the outer box **325** can be in the form of a variety of other shapes with various geometries. Diagram **330** in FIG. 3B shows another example optical barcode that employs the custom graphic for a finder pattern or an alignment pattern. The diagram **330** shows the optical barcode with markings excluded from within the custom graphic. In these and other embodiments, the space internal to the custom graphic may be reserved for other uses. For example, a picture, graphic, animation, annotation, or image selected by a user may be inserted.

Turning now to FIG. **4**, a diagram **400** illustrating an example of identifying and decoding the optical barcode employing the custom graphic for a finder pattern or an alignment pattern is shown. FIG. **4** is an overview of a particular example embodiment of identifying and decoding the optical barcode using the custom graphic. Additional details and alternative implementations are discussed in connection with the figures to follow. In the diagram **400**, a scene **402** illustrates a poster **404** that includes an optical barcode **406** and a user **410**. It will be appreciated that the optical barcode **406** can be displayed in a variety of manners such as on a user device display, a computer display, woven or otherwise affixed to an article of clothing or another product, or included in a variety of printed items. Callout **412** portrays an enlarged view of a portion of the scene **402**. The callout **412** includes a user device **414** of the user **410** that includes an optical sensor (e.g., a camera sensor of a smart phone) operable to detect an optical signal **408** of the optical barcode **406**.

In an example embodiment, the user device **414** captures an image of the poster **404** that includes the optical barcode **406**. The custom pattern system **160** receives the image data representing the image from the user device **414**. In this example embodiment, the custom pattern system **160** is included in the user device **414** (e.g., an application executing on a smart phone of the user **410**), although in other example embodiments, the custom pattern system **160** can reside on a server (e.g., a server of the social messaging system **130**) that is communicatively coupled with the user device **414**. Callout **416** portrays example image processing the finder module **230** performs to identify the custom graphic in the image and use the custom graphic as an alignment pattern for decoding data included in the optical barcode **406**. In the callout **416**, the finder module **230** extracts candidate shape features from the image data of the image. Subsequently, the finder module **230** determines if the candidate features meet certain rules and criteria to filter out irrelevant shape features or shape features that have a low probability of being the custom graphic. The finder module **230** can then compare the candidate shape features that meet the shape feature criteria or rules with reference shape features of the custom graphic. In an example, the finder module **230** identifies the custom graphic based on a match between the candidate shape features and the reference shape feature (e.g., a match score that exceeds a threshold).

Subsequent to the finder module **230** identifying the custom graphic, the custom pattern system **160** can use the custom graphic as an alignment pattern for decoding. For instance, the alignment module **240** extracts spatial attributes of the custom graphic in the image and compares the extracted spatial attributes to reference spatial attributes to determine an alignment of the custom graphic. The align-

11

ment module 240 or the decoder module 250 may then generate a transformed image of the image according to the alignment (e.g., a rotation or de-skew) as shown in callout 418. After generating the transformed image, the decoder module 250 decodes the data encoded in a portion of the transformed image as shown in callout 420. In the callout 420, the dots of the optical barcode 406 are transformed into data shown as ones for dots and zeros for non-dots, although this is merely an illustrative example and other schemes can be employed. In this way, the custom pattern system 160 uses the custom graphic included in the optical barcode 406 as one or more functional patterns such as a finder pattern or an alignment pattern.

According to some implementations, after the user device 414 scans the optical barcode 406, the messaging application may initiate an “add friend” process between the user device 414 and a second device associated with the optical barcode 406. During the “add friend” process, the user device 414 and the second device may exchange public keys to initiate secure communication. According to some examples, the public key of the second device may be encoded within the optical barcode and decoded using the techniques described herein (e.g., read from the callout 420). After exchanging public keys, the user device 414 and the second device may communicate securely, preventing eavesdroppers and people having access to the messaging server from reading messages sent between the user device 414 and the second device.

FIG. 5 is a flow diagram illustrating an example method 500 for an optical barcode (e.g., the optical barcode 406 of FIG. 4) employing a custom functional pattern. The operations of the method 500 can be performed by components of the custom pattern system 160, and are so described below for the purposes of illustration.

At operation 510, the communication module 210 receives image data of an image from a user device. For example, the communication module 210 receives the image data from an optical sensor (e.g., a camera sensor) of a smart phone of the user. In various embodiments, the image data from the user device is received in response to a user-initiated image capture, a periodic monitoring of image data being detected by the optical sensor of the user device, or a combination thereof. In some embodiments, the image data represents an image or video being captured by the user device in substantially real time (e.g., a live image feed from a camera sensor of a smart phone). In other embodiments, the image data represents an image captured by the user device, or another device and stored on the user device, from a time in the past (e.g., a still image or video stored on the user device or downloaded from a social networking service). In embodiments where the image data comprises video image data, the custom pattern system 160 can analyze individual frames of the video or a combination of multiple frames of the video to detect and decode the optical barcode. A portion of the image data can include data representing an optical barcode employing a custom graphic, custom symbol, or specific graphic for a particular functional pattern (e.g., a finder pattern or alignment pattern).

In some scenarios, the image data includes extraneous or irrelevant data along with the data pertaining to the optical barcode (e.g., an image of an optical barcode includes a background that is not pertinent to decoding the optical barcode). In a specific example, the optical sensor of the user device captures an image of a movie poster that includes a particular optical barcode. The image of the movie poster can include the particular optical barcode along with irrel-

12

evant portions of the movie poster or background that surrounds the particular optical barcode.

At operation 520, the finder module 230 extracts a candidate shape feature or candidate characteristic of the image from the image data. The candidate shape feature can be indicative of an identification of the custom graphic (e.g., include certain traits or characteristics that indicate the custom graphic). For example, the finder module 230 performs an edge detection technique, or another image processing technique, to identify shape features such as contour lines or localized concentrations of color or shading of the image. In some embodiments, the finder module 230 extracts multiple candidate shape features from the image data. In some embodiments, the candidate shape feature includes various shape feature data such as a position of the candidate shape feature relative to a boundary of the image, a brightness of the candidate shape feature relative to the image, an average color of the candidate shape feature, and so forth.

In further example embodiments, the finder module 230 generates a low resolution copy of the image. The finder module 230 can perform various image processing on the low resolution copy of the image, such as a blur (e.g., a Gaussian blur function or another blur function) and a thresholding, to generate a modified low resolution image. The thresholding image process can include adjusting lighter colors (e.g., as determined by a threshold or threshold range) of the low resolution copy of the image to a white color and darker colors (e.g., as determined by a threshold or threshold range) of the low resolution copy of the image to a black color. The finder module 230 can then extract candidate shape features from the modified low resolution image to improve detection of the custom graphic in the image and improve computational efficiency of identifying the custom graphic in the image.

In still further example embodiments, the finder module 230 generates a high resolution copy of a portion of the image. For instance, the finder module 230 can generate the high resolution copy of a particular portion of the image corresponding to the extracted candidate shape feature. The finder module 230, the alignment module 240, or the decoder module 250 can use the high resolution copy for subsequent analysis, as described below, to improve detection, alignment, and decoding results.

At operation 530, the finder module 230 determines that the candidate shape feature satisfies one or more shape feature criteria or rules. For instance, if a particular shape feature is a contour line, the finder module 230 can determine whether the contour line is an enclosed line that encircles a portion of the image. Consistent with some embodiments, the shape feature rule filters out irrelevant or extraneous features. Particular shape feature rules can be directed to or purposed for various objectives. For example, a particular shape feature rule can be purposed to filter out candidate shape features with a low probability of being the custom graphic. In this example, the particular shape feature rule can be specific to the custom graphic. In other examples, some shape feature rules can be purposed to filter out candidate shape features that are unlikely to be associated with the optical barcode. In these examples, the shape feature rule is not necessarily specific to the custom graphic.

At operation 540, in response to the candidate shape feature satisfying the shape feature rule, the finder module 230 identifies the custom graphic or custom symbol in the image by comparing the candidate shape feature with a reference shape feature of the custom graphic or custom symbol. For example, the finder module 230 can compare an

13

area or size of the candidate shape feature with a reference area or size of the reference shape feature. In this example, the finder module **230** identifies the custom graphic based on a match or near match (e.g., a percentage match above a threshold) between the candidate shape feature and the reference shape feature. In this way, the finder module **230** uses the custom graphic, or at least a portion of the custom graphic, as a finder pattern to identify the presence of the optical barcode within a portion of the image.

In some embodiments, the finder module **230** extracts multiple candidate shape features from the image data. In these embodiments, the finder module **230** scores each candidate shape feature and ranks the multiple candidate shape features according to respective scores. For example, the finder module **230** determines a shape feature score for respective candidate shape features based on a count, or weighted count, of shape feature rules the respective candidate shape feature satisfies. The finder module **230** can iterate through the ranked candidate shape features starting with the highest scoring candidate shape feature and perform further analysis (e.g., comparing the candidate shape feature to a reference shape feature) to determine that the candidate shape feature is the custom graphic.

In some embodiments, the reference shape feature is predetermined, and in other embodiments, the reference shape feature is dynamically determined. For instance, the finder module **230** can dynamically determine the reference shape feature by analyzing a reference image of the custom graphic. For example, the finder module **230** can perform analysis techniques similar to those for analyzing the image data on the reference image such as calculating the reference area value for a particular feature or characteristic of the reference image. In these embodiments, the finder module **230** dynamically determining the reference shape feature allows for dynamic use of a particular custom graphic as a functional pattern in an optical barcode. For instance, the custom pattern system **160** can be provided (e.g., received at the communication module **210**) data representing the reference image or data representing the reference features when the method **500** is performed. In this way, the custom functional patterns do not necessarily have to be fixed prior to performing the method **500**.

In further example embodiments, the finder module **230** searches for multiple custom graphics in the image data of the image (e.g., where multiple versions or different custom graphics are employed as functional patterns). In a specific example, the custom graphic can comprise a first company logo and the company may change logos to a second company logo. The custom pattern system **160** can be operable to use the first company logo as a finder pattern and the second company logo as a finder pattern and the custom pattern system **160** can search for each logo when performing the method **500**.

In further example embodiments, the finder module **230** identifies the custom graphic in the image in conjunction with other candidate shape features extracted from the image data. For example, the finder module **230** can search for both the custom graphic (e.g., a logo) and an outer box (e.g., the outer box **325**) surrounding the custom graphic. In these embodiments, the finder module **230** identifies a combination of the custom graphic and one or more additional candidate shape features extracted from the image data.

At operation **550**, in response to identifying the custom graphic, the alignment module **240** extracts a spatial attribute, geometry attribute, or spatial property of the custom graphic or custom symbol in the image from the image data. For example, the alignment module **240** extracts a position,

14

scale, or orientation of the custom graphic from the image data. In various example embodiments, the spatial attribute is indicative of an orientation of the custom graphic in the image. The alignment module **240** or the decoder module **250** can use the spatial attribute to facilitate decoding the optical barcode.

In further embodiments, the alignment module **240** extracts a spatial attribute, geometry attribute, or spatial property of another candidate shape feature extracted from the image data of the image. For example, the alignment module **240** extracts a spatial attribute of the outer box (e.g., the outer box **325** of FIG. 3A) surrounding the custom graphic and the markings that encode data. It will be noted that throughout the discussion to follow, the alignment module **240** and the decoder module **250** can use the spatial attribute of the outer box in a same or similar way as the spatial attribute of the custom graphic to determine an alignment of the optical barcode used to facilitate decoding. For example, the alignment module **240** or the decoder module **250** can use the spatial attributes of the outer box to generate a transformed image of the image used to decode the data encoded in the image.

At operation **560**, the decoder module **250** decodes data encoded in a portion of the image from the image data using the spatial attribute of the custom graphic in the image. For instance, the decoder module **250** can perform an image transform using the spatial attributes (e.g., a de-skew, a rotation, a scale, or another type of image transform) to improve detectability or readability of data encoded in a portion of the image. In an example embodiment, the decoder module **250** decodes the data encoded in the portion of the image by detecting marking (e.g., dots, squares, or another marking) indicative of data included in the image. In this way, the decoder module **250** uses the custom graphic, or at least a portion of the custom graphic, as an alignment pattern to facilitate decoding the optical barcode. In various embodiments, the decoder module **250** employs a Reed-Solomon error correction scheme (or any other error correction scheme) to decode data encoded in the image. The Reed-Solomon error correction scheme (or other error correction scheme) allows for a successful decoding of the data encoded in the image with a certain percentage of data encoded in the image being corrupt, damaged, or incorrectly decoded. In further embodiments, the decoder module **250** uses a small checksum to verify that the value decoded from the image data is a value that includes real data rather than just random data (e.g., random bits).

In further example embodiments, the decoder module **250** rejects certain results of the decoded data (e.g., results of data decoded from the image data known to be invalid as specified by an administrator of the custom pattern system **160**). For example, the decoder module **250** can reject decoded data that includes all zeros, all ones, or another specified result even though the decoded data passed other data integrity tests (e.g., error correction and checksumming). For example, this can occur when the custom pattern system **160** scans the custom graphic without any associated markings that indicate data (e.g., where the custom graphic is a logo, simply scanning the logo may yield all zeros in the decoded data and may be rejected by the decoder module **250**). In a specific example, scanning the icon associated with social messaging app **1908**, shown below in FIG. 19, would likely yield data with all zeros and the decoder module **250** would reject the scan.

FIG. 6 is a flow diagram illustrating further example operations for identifying the optical barcode (e.g., the optical barcode **406**) using the custom functional pattern. At

15

operation **530**, the finder module **230** determines that the candidate shape feature satisfies the shape feature rule. In some embodiments, the operation **530** includes the operations of FIG. 6.

At operation **610**, the finder module **230** determines that the candidate shape feature comprises an enclosed line from the image data. That is to say, the shape feature rule comprises a path rule and the finder module **230** determines that the candidate shape feature satisfies the path rule. The finder module **230** can employ a variety of techniques to determine that the candidate shape feature satisfies the path rule.

At operation **630**, the finder module **230** determines whether the candidate shape feature is an enclosed line by determining that the candidate shape feature encircles a portion of the image by having a path that starts at a particular point and returns to the same particular point. In an example embodiment, if the candidate shape feature does not satisfy the path rule (indicated by “no” in FIG. 6), no further analysis of the candidate shape feature is performed and the finder module **230** analyzes another candidate shape feature or performs no further operations. Alternatively, at operation **640**, if the finder module **230** determines that the candidate shape feature satisfies the path rule (indicated by “yes” in FIG. 6), the subsequent operations of the method **500** are performed.

To illustrate the concepts of FIG. 6, FIG. 7 is a diagram **700** illustrating an example of identifying the optical barcode using the custom functional pattern. In the diagram **700**, the image **710** is an example image that is received or accessed from the user device. The image **720** is an example image portraying example candidate shape features **730**. For instance, the finder module **230** performs an edge detection image processing on the image **710** to derive the image **720**. From the image **720**, the finder module **230** identifies the candidate shape features **730**.

Callout **740** shows a particular candidate shape feature of the candidate shape features **730**. The callout **740** shows a contour line **750** (illustrated as a dotted line) of the particular candidate shape feature, a path **760**, and a point **770** of the particular candidate shape feature. In the callout **740**, the finder module **230** determines that the path rule is met if the path **760** that starts at the point **770** can follow the contour line **750** and return to the point **770**. In the diagram **700**, the particular candidate shape feature shown in the callout **740** does satisfy the path rule since the path **760** can follow the contour line **750** and return to the point **770**.

FIG. 8 is a flow diagram illustrating further example operations for identifying the optical barcode using the custom functional pattern. At operation **530**, the finder module **230** determines that the candidate shape feature satisfies the shape feature rule. In some embodiments, the operation **530** includes the operations of FIG. 8.

At operation **810**, the finder module **230** calculates an area value or size approximation of the candidate shape feature. For example, the finder module **230** uses a proxy shape such as a polygon (e.g., a square, a rectangle, or a quadrilateral) or a non-polygonal shape (e.g., an ellipse) to approximate the shape of the candidate shape feature. The finder module **230** fits or nearly fits the proxy shape to the outer edges or outer perimeter of the candidate shape feature so that the proxy shape is representative of an area of the candidate shape feature. Subsequently, the finder module **230** calculates the area value of the proxy shape to determine the area value or size approximation of the candidate shape feature. In some embodiments, the finder module **230** employs such a technique (e.g., polygonal area approximation) to avoid a

16

computationally expensive area calculation of the candidate shape feature in situations where the candidate shape feature is likely to be complex in shape (e.g., an area calculation for a non-uniform or irregular shaped feature is typically more computationally expensive). In some embodiments, other techniques such as pixel-based counting can be employed to determine the area value.

At operation **820**, the finder module **230** determines an area score or size score of the candidate shape feature. The finder module **230** determines the area score by comparing the area value of the candidate shape feature with a reference area value. In some embodiments, the reference area value comprises an area value of a corresponding proxy shape fitted to a reference image of the custom graphic (e.g., the area value of a proxy shape fitted to the ghost logo from a front view perspective). In other embodiments, the reference area value comprises the area value of the custom graphic (e.g., the area value of the ghost logo). The finder module **230** calculates the area score, for example, by determining a match percentage between the candidate shape feature area value and the reference area value. The finder module **230** can employ a wide variety of other schemes and techniques to calculate the area score.

At operation **830**, the finder module **230** determines whether the area score exceeds a threshold. The threshold can be predefined or dynamically determined (e.g., statistically determined based on a rolling historical average of scans).

At operation **840**, based on the area score exceeding the threshold (indicated by “yes” in FIG. 8), the finder module **230** determines that the candidate shape feature satisfies the area rule and proceeds to subsequent operations. In another example embodiment, the finder module **230** compares the area score to an area range to satisfy the area rule (e.g., greater than a particular value and less than a particular value). If the area score does not exceed the threshold (indicated by “no” in FIG. 8), then the finder module **230** analyzes another candidate shape feature or no further operations are performed, according to an example embodiment. In some example embodiments, the finder module **230** uses the determination of whether the candidate shape feature satisfies the shape feature rules as a filter (e.g., to remove or skip candidate shape features that are unlikely to be the custom graphic) to identify candidate shape features to be further analyzed in the process of identifying the custom graphic in the image.

To further illustrate the concepts of FIG. 8, FIG. 9 is a diagram **900** illustrating an example of identifying the optical barcode using the custom functional pattern. In the diagram **900**, image **902** is an example image that is received from the user device. Callout **904** shows the spatial orientation of the image **902**. In this example, the image **902** is portrayed and being seen from a front right perspective. The image **902** includes optical barcode **906**. In this example, the optical barcode **906** employs the custom graphic as a functional pattern.

Callout **908** shows an enlarged portion of the image **902** that includes the candidate shape feature being analyzed by the finder module **230** to identify the custom graphic. In the callout **908**, the polygon **910** (e.g., a quadrilateral) is shown fitted to a perimeter of the candidate shape feature. Area value **912** is the area of the polygon **910**.

Callout **914** shows a reference image of the custom graphic. Callout **916** shows the spatial orientation of the reference image. In this example, the reference image is shown from the front view perspective. Polygon **918** is shown fitted to a perimeter of the reference image. Refer-

17

ence area value **920** is the area of the polygon **918**. Although FIG. **9** shows polygons **910** and **918** as quadrilaterals, the finder module **230** can employ other shapes such as a square or a shape that follows or traces a contour of the candidate shape feature (e.g., an n-sided polygon or smooth fitted shape that follows contour points of the candidate shape feature).

The finder module **230** compares the area value **912** with the reference area value **920** to determine that the candidate shape feature satisfies the area rule. Another candidate shape feature of the image **902**, such as one of the musical notes of the image **902**, would not have an area value that is similar to the reference area value and therefore would not satisfy the area rule. In this way, the finder module **230** can quickly remove or skip certain candidate shape features that are unlikely to be identified as the custom graphic.

FIG. **10** is a flow diagram illustrating further example operations for decoding the optical barcode using the custom functional pattern. At the operation **540**, the finder module **230** identifies the custom graphic in the image by comparing the candidate shape feature with a reference shape feature of the custom graphic. Subsequent to the operation **540**, the operations of FIG. **10** are performed in some example embodiments.

At operation **1010**, the alignment module **240** extracts a distinctive feature of the custom graphic from the image data where the distinctive feature is indicative of an alignment of the custom graphic (e.g., a particular asymmetry of the custom graphic that can be used to determine an orientation of the custom graphic). For example, the distinctive feature can comprise a distinctive point of the custom graphic, a distinctive curve, a particular asymmetry, a particular non-uniformity, or another characteristic of the custom graphic.

At operation **1020**, the alignment module **240** determines an orientation of the custom graphic in the image by comparing the distinctive feature with a reference distinctive feature of the custom graphic. For example, the alignment module **240** maps the extracted distinctive feature of the custom graphic to a reference distinctive feature to determine spatial differences between the distinctive features. In this way, the alignment module **240** can determine an alignment of the custom graphic as compared to a reference image of the custom graphic based on the determined spatial differences.

At operation **1030**, the alignment module **240** generates a transformed image by transforming the image according to the orientation of the custom graphic. For instance, the alignment module **240** can rotate, de-skew, scale, or otherwise spatially transform the image to allow for a more accurate decoding of the data in the image.

At operation **1040**, the decoder module **250** decodes the data encoded in the image using the orientation and a position of the custom graphic in the image. For example, the decoder module **250** decodes the data encoded in the image from the transformed image. In a specific scenario, the image is transformed to a front view to increase visibility and uniformity of marks in the image that represent data encoded in the image.

To assist in understanding the disclosure of FIG. **10**, FIG. **11** is a diagram **1100** illustrating an example of decoding the optical barcode using the custom functional pattern. In the diagram **1100**, similar to the FIG. **9** described above, image **1102** is an example image that is received from the user device. In this example, the image **1102** is portrayed and being seen from a front right perspective. The image **1102**

18

includes optical barcode **1106**. In this example, the optical barcode **1106** employs the custom graphic as a functional pattern.

Callout **1108** shows an enlarged portion of the image **1102** that includes the candidate shape feature being analyzed by the alignment module **240**. Callout **1110** shows an enlarged portion of the callout **1108** showing a distinctive feature of the candidate shape feature.

Callout **1112** shows a reference image of the custom graphic. Callout **1114** shows the spatial orientation of the reference image. In this example, the reference image is shown from the front view perspective. Callout **1116** shows an enlarged portion of the callout **1112** showing a reference distinctive feature of the reference image.

The alignment module **240** compares the distinctive feature and the reference distinctive feature to determine an alignment including an orientation, scale, or position. For example, if the image that includes the custom graphic is shown from the front perspective, the distinctive feature of the custom graphic in the image should match the reference distinctive feature. The alignment module **240** can determine perspective changes based on a mismatch between the distinctive feature and the reference distinctive feature. The alignment module **240** uses the mismatch to infer or determine a perspective of the image or other spatial attributes of the image that can be utilized by the decoder module **250** to more accurately decode data from the image.

FIGS. **12A**, **12B**, and **12C** are diagrams illustrating various image transformations used to facilitate decoding the optical barcode using the custom functional pattern. In an example embodiment, the alignment module **240** or the decoder module **250** performs an image transformation such as a rotation as shown by a transition between example optical barcode **1200** and **1202**. In other embodiments, the alignment module **240** or the decoder module **250** performs a de-skewing, scale transformation, or another type of image transformation. In further example embodiments, the alignment module **240** or the decoder module **250** performs other image transformations such as a color inversion as shown by a transition between example optical barcode **1204** and **1206**. The alignment module **240** or the decoder module **250** can perform other image transformation not shown such as image sharpening, noise reduction, or other image processing.

FIG. **12C** illustrates an example of a technique to determine an alignment of the custom graphic. The example optical barcode **1208** is rotated slightly away from zero degrees. An ellipse **1210** can be fitted to the custom graphic to determine an alignment such as a rotation value of the optical barcode **1208**. The major axis **1212** of the ellipse **1210** provides an indication of a rotation value **1214** away from zero degrees (of course, the minor axis, or another axis, may similarly be used to determine a rotation value). The alignment module **240** or the decoder module **250** can perform an image transformation to adjust for the rotation value **1214** as shown by the example optical barcode **1216** being rotated from an original orientation **1218**. In this way, the alignment module **240** or the decoder module **250** can use the custom graphic to determine an alignment for the optical barcode included in the image to assist in decoding the data encoded in the image.

FIG. **13** is a flow diagram illustrating further example operations for decoding the optical barcode using the custom functional pattern. At operation **1040**, the decoder module **250** decodes the data encoded in a portion of the image from

the image data. Subsequent to the operation **1040**, the operations of FIG. **13** are performed in some example embodiments.

At operation **1310**, the decoder module **250** determines a failure to decode the data encoded in the portion of the image using the transformed image. For instance, if the data decoded from the image is corrupted, incomplete, or garbled, the decoder module **250** determines the failure to decode the data. In another instance, a portion of the data encoded in the image can be for the purposes of data validation. That is to say, a known or determinable value can be encoded into the data such that the data is valid if the value is decoded from the image. The decoder module **250** can employ a variety of other schemes and techniques to determine the failure to decode the data encoded in the portion of the image.

At operation **1320**, the alignment module **240** generates another transformed image by transforming the image according to a different orientation of the custom graphic. For example, the alignment module **240** generates a transformed image that is rotated 180 degrees, and the decoder module **250** attempts to decode the data a second time. The alignment module **240** can perform common transforms that may resolve the failure to decode such as 90 degree rotations or another transform that has frequently resolved the failure to decode in past scans. In some embodiments, the alignment module **240** performs another analysis of the image data of the image to determine another alignment to use to use when generating another transformed image. The alignment module **240** can perform other types of image transformations by applying different types of filters (e.g., orientation, color reduction, brightness manipulation, etc.) to the custom graphic.

At operation **1330**, the decoder module **250** decodes the data encoded in the portion of the image using another transformed image. The alignment module **240** and the decoder module **250** can attempt any number (e.g., a set number of attempts or an unlimited number of attempts) of iterations of alignments that ends when the data is successfully decoded from the image. In this way, the custom pattern system **160** can use the markings for self-alignment.

To further explain the discussion in connection with FIG. **13**, FIG. **14** is a diagram **1400** illustrating an example of decoding the optical barcode using the custom functional pattern. Example optical barcode **1410** shows positions for markings with empty circles. Each empty circle of optical barcode **1410** is a position for a marker. Example optical barcode **1420** shows a misalignment between marking positions and markings. Example optical barcode **1430** shows a matching alignment between the markings and the marking positions.

Turning now to FIGS. **15** and **16**, although user interfaces described herein (e.g., FIGS. **15**, **16**, and **18**) depict specific example user interfaces and user interface elements, these are merely non-limiting examples, and many other alternate user interfaces and user interface elements can be generated by the presentation module **220** and presented to the user. It will be noted that alternate presentations of the displays described herein include additional information, graphics, options, and so forth; other presentations include less information, or provide abridged information for easy use by the user.

FIG. **15** is a user interface diagram **1500** depicting an example user interface **1510** for identifying the optical barcode. In the user interface diagram **1500**, the user interface **1510** is showing a substantially real-time image captured from a camera sensor of the user device (e.g., the client

device(s) **110**, the user device **414**). The user interface **1510** can include graphics and user interface elements superimposed or overlaid over the substantially real-time image being displayed underneath. For instance, user interface element **1520** is a bracket that indicates identification of an optical barcode. The user interface **1510** can indicate to the user the successful, or unsuccessful, scan of a particular optical barcode.

FIG. **16** is a user interface diagram **1600** depicting an example user interface **1610** for performing an action associated with the optical barcode. In an example embodiment, the user interface **1610** is displayed after the user interface **1510** of FIG. **15** (e.g., after a successful scan, various action options associated with the scan are displayed). The user interface **1610** can include a variety of action options associated with detecting a particular optical barcode such as user interface elements **1620**. In some embodiments, a particular action is automatically performed by the custom pattern system **160** in response to detecting and decoding a particular optical barcode.

In further example embodiments, the action is exclusive to software that provides scanning functionality for the optical barcode that uses the custom functional pattern (e.g., a snapcode). In some embodiments, the software that scans the optical barcode can perform certain exclusive actions without communicating with a server. This is due to the exclusive, branded nature of the custom functional pattern that is not necessarily openly decodable by other third-party software applications. The snapcode can specify such actions since it is likely that the software (e.g., a mobile computing software such as an app) that scans the branded optical barcode is associated with the branded optical barcode.

FIG. **17** is a flow diagram illustrating example operations for generating the optical barcode using the custom functional pattern. The operations of the method **1700** can be performed by components of the custom pattern system **160**, and are so described below for the purposes of illustration.

At operation **1710**, the communication module **210** receives a request to generate a machine-readable image such as an optical barcode that uses custom functional patterns. In some embodiments, the request includes user specified data to encode into the image.

At operation **1720**, the encoder module **270** renders a machine-readable arrangement of marks that encodes the user-specified data. For instance, the marks can comprise dots, squares, or other markings that are arranged in a predetermined pattern. In an example embodiment, the presence of a mark at a particular location in the arrangement is indicative of data.

At operation **1730**, the encoder module **270** generates the machine-readable image by positioning the machine-readable arrangement of marks in the machine-readable image with respect to a position of the custom graphic included in the machine-readable image. For example, the custom graphic can be centered in the optical barcode or positioned elsewhere (e.g., the example optical barcodes of FIGS. **3A** and **3B**).

At operation **1740**, the communication module **210** stores or transmits the machine-readable image. For instance, the communication module **210** can store the machine-readable image on the user device, a server, or another storage repository (either locally or remotely stored). In other instances, the communication module **210** transmits the machine-readable image to the user device, a server, or one or more other devices.

FIG. 18 is a user interface diagram 1800 depicting an example user interface 1810 for generating an optical barcode 1820 using the custom graphic. User interface elements 1830 provide the user with options for generating, sharing, or saving the machine-readable image. In some embodiments, the user interface diagram 1800 includes a user interface configured to receive user-specified data to encode into the machine-readable image (e.g., a social networking service member identifier, a website address, or another piece of information).

FIG. 19 illustrates an example mobile device 1900 executing a mobile operating system (e.g., IOS™, ANDROID™, WINDOWS® Phone, or other mobile operating systems), consistent with some embodiments. In one embodiment, the mobile device 1900 includes a touch screen operable to receive tactile data from a user 1902. For instance, the user 1902 may physically touch 1904 the mobile device 1900, and in response to the touch 1904, the mobile device 1900 may determine tactile data such as touch location, touch force, or gesture motion. In various example embodiments, the mobile device 1900 displays a home screen 1906 (e.g., Springboard on IOS™) operable to launch applications or otherwise manage various aspects of the mobile device 1900. In some example embodiments, the home screen 1906 provides status information such as battery life, connectivity, or other hardware statuses. The user 1902 can activate user interface elements by touching an area occupied by a respective user interface element. In this manner, the user 1902 interacts with the applications of the mobile device 1900. For example, touching the area occupied by a particular icon included in the home screen 1906 causes launching of an application corresponding to the particular icon.

Many varieties of applications (also referred to as “apps”) can be executed on the mobile device 1900, such as native applications (e.g., applications programmed in Objective-C, Swift, or another suitable language running on IOS™ or applications programmed in Java running on ANDROID™), mobile web applications (e.g., applications written in Hypertext Markup Language-5 (HTML5)), or hybrid applications (e.g., a native shell application that launches an HTML5 session). For example, the mobile device 1900 includes a messaging app, an audio recording app, a camera app, a book reader app, a media app, a fitness app, a file management app, a location app, a browser app, a settings app, a contacts app, a telephone call app, or other apps (e.g., gaming apps, social networking apps, biometric monitoring apps). In another example, the mobile device 1900 includes a social messaging app 1908 such as SNAPCHAT® that, consistent with some embodiments, allows users to exchange ephemeral messages that include media content. In this example, the social messaging app 1908 can incorporate aspects of embodiments described herein.

Certain embodiments are described herein as including logic or a number of components, modules, or mechanisms. Modules can constitute either software modules (e.g., code embodied on a machine-readable medium) or hardware modules. A “hardware module” is a tangible unit capable of performing certain operations and can be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a stand-alone computer system, a client computer system, or a server computer system) or one or more hardware modules of a computer system (e.g., a processor or a group of processors) can be configured by software (e.g., an application or application portion) as a hardware module that operates to perform certain operations as described herein.

In some embodiments, a hardware module can be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware module can include dedicated circuitry or logic that is permanently configured to perform certain operations. For example, a hardware module can be a special-purpose processor, such as a Field-Programmable Gate Array (FPGA) or an Application Specific Integrated Circuit (ASIC). A hardware module may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware module can include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware modules become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware module mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) can be driven by cost and time considerations.

Accordingly, the phrase “hardware module” should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. As used herein, “hardware-implemented module” refers to a hardware module. Considering embodiments in which hardware modules are temporarily configured (e.g., programmed), each of the hardware modules need not be configured or instantiated at any one instance in time. For example, where a hardware module comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware modules) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware module at one instance of time and to constitute a different hardware module at a different instance of time.

Hardware modules can provide information to, and receive information from, other hardware modules. Accordingly, the described hardware modules can be regarded as being communicatively coupled. Where multiple hardware modules exist contemporaneously, communications can be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware modules. In embodiments in which multiple hardware modules are configured or instantiated at different times, communications between such hardware modules may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware modules have access. For example, one hardware module can perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware module can then, at a later time, access the memory device to retrieve and process the stored output. Hardware modules can also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information).

The various operations of example methods described herein can be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors constitute processor-implemented modules

23

that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented module” refers to a hardware module implemented using one or more processors.

Similarly, the methods described herein can be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method can be performed by one or more processors or processor-implemented modules. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an Application Program Interface (API)).

The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented modules can be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented modules are distributed across a number of geographic locations.

The modules, methods, applications and so forth described in conjunction with the figures above are implemented in some embodiments in the context of a machine and an associated software architecture. The sections below describe representative software architecture(s) and machine (e.g., hardware) architecture that are suitable for use with the disclosed embodiments.

Software architectures are used in conjunction with hardware architectures to create devices and machines tailored to particular purposes. For example, a particular hardware architecture coupled with a particular software architecture will create a mobile device, such as a mobile phone, tablet device, or so forth. A slightly different hardware and software architecture may yield a smart device for use in the “internet of things,” while yet another combination produces a server computer for use within a cloud computing architecture. Not all combinations of such software and hardware architectures are presented here as those of skill in the art can readily understand how to implement the subject technology in different contexts from the disclosure contained herein.

FIG. 20 is a block diagram of a system 2000 that includes a representative software architecture 2002, which may be used in conjunction with various hardware architectures herein described. FIG. 20 is merely a non-limiting example of a software architecture and it will be appreciated that many other architectures may be implemented to facilitate the functionality described herein. The software architecture 2002 may be executing on hardware such as machine 2100 of FIG. 21 that includes, among other things, processors 2110, memory/storage 2130, and I/O components 2150. A representative hardware layer 2004 is illustrated and can represent, for example, the machine 2100 of FIG. 21. The representative hardware layer 2004 comprises one or more processing units 2006 having associated executable instructions 2008. Executable instructions 2008 represent the executable instructions of the software architecture 2002, including implementation of the methods, modules and so forth in the figures and description above. Hardware layer 2004 also includes memory and storage modules 2010,

24

which also have executable instructions 2008. Hardware layer 2004 may also comprise other hardware 2012, which represents any other hardware of the hardware layer 2004, such as the other hardware illustrated as part of machine 2100.

In the example of FIG. 20, the software architecture 2002 may be conceptualized as a stack of layers where each layer provides particular functionality. For example, the software architecture 2002 may include layers such as an operating system 2014, libraries 2016, frameworks/middleware 2018, applications 2020 and presentation layer 2044. Operationally, the applications 2020 or other components within the layers may invoke application programming interface (API) calls 2024 through the software stack and receive a response, returned values, and so forth illustrated as messages 2026 in response to the API calls 2024. The layers illustrated are representative in nature and not all software architectures have all layers. For example, some mobile or special purpose operating systems may not provide the frameworks/middleware layer 2018, while others may provide such a layer. Other software architectures may include additional or different layers.

The operating system 2014 may manage hardware resources and provide common services. The operating system 2014 may include, for example, a kernel 2028, services 2030, and drivers 2032. The kernel 2028 may act as an abstraction layer between the hardware and the other software layers. For example, the kernel 2028 may be responsible for memory management, processor management (e.g., scheduling), component management, networking, security settings, and so on. The services 2030 may provide other common services for the other software layers. The drivers 2032 may be responsible for controlling or interfacing with the underlying hardware. For instance, the drivers 2032 may include display drivers, camera drivers, BLUETOOTH® drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth depending on the hardware configuration. In an example embodiment, the operating system 2014 includes an imaging service 2033 that can provide image processing services, such as hardware-accelerated image processing, or image capture services, such as low-level access to optical sensors or optical sensor data.

The libraries 2016 may provide a common infrastructure that may be utilized by the applications 2020 or other components or layers. The libraries 2016 typically provide functionality that allows other software modules to perform tasks in an easier fashion than to interface directly with the underlying operating system 2014 functionality (e.g., kernel 2028, services 2030 or drivers 2032). The libraries 2016 may include system libraries 2034 (e.g., C standard library) that may provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries 2016 may include API libraries 2036 such as media libraries (e.g., libraries to support presentation and manipulation of various media format such as MPREG4, H.264, MP3, AAC, AMR, JPG, or PNG), graphics libraries (e.g., an OpenGL framework that may be used to render 2D and 3D in a graphic content on a display), database libraries (e.g., SQLite that may provide various relational database functions), web libraries (e.g., WebKit that may provide web browsing functionality), and the like. The libraries 2016 may also include a wide variety of other libraries 2038 to provide many other APIs to the applications 2020 and other software components/modules. In an example embodiment, the libraries 2016 include

imaging libraries **2039** that provide image processing or image capture functionality that can be utilized by the custom pattern system **160**.

The frameworks **2018** (also sometimes referred to as middleware) may provide a higher-level common infrastructure that may be utilized by the applications **2020** or other software components/modules. For example, the frameworks **2018** may provide various graphic user interface (GUI) functions, high-level resource management, high-level location services, and so forth. The frameworks **2018** may provide a broad spectrum of other APIs that may be utilized by the applications **2020** or other software components/modules, some of which may be specific to a particular operating system or platform. In an example embodiment, the frameworks **2018** include an image processing framework **2022** and an image capture framework **2023**. The image processing framework **2022** can provide high-level support for image processing functions that can be used in aspects of the custom pattern system **160**. Similarly, the image capture framework **2023** can provide high-level support for capturing images and interfacing with optical sensors.

The applications **2020** include built-in applications **2040** or third party applications **2042**. Examples of representative built-in applications **2040** may include, but are not limited to, a contacts application, a browser application, a book reader application, a location application, a media application, a messaging application, or a game application. Third party applications **2042** may include any of the built-in applications **2040** as well as a broad assortment of other applications. In a specific example, the third party application **2042** (e.g., an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or other mobile operating systems. In this example, the third party application **2042** may invoke the API calls **2024** provided by the mobile operating system such as operating system **2014** to facilitate functionality described herein. In an example embodiment, the applications **2020** include a messaging application **2043** that includes the custom pattern system **160** as part of the application. In another embodiment, the applications **2020** include a stand-alone application **2045** that includes the custom pattern system **160**.

The applications **2020** may utilize built-in operating system functions (e.g., kernel **2028**, services **2030** or drivers **2032**), libraries (e.g., system libraries **2034**, API libraries **2036**, and other libraries **2038**), frameworks/middleware **2018** to create user interfaces to interact with users of the system **2000**. Alternatively, or additionally, in some systems, interactions with a user may occur through a presentation layer, such as presentation layer **2044**. In these systems, the application/module “logic” can be separated from the aspects of the application/module that interact with a user.

Some software architectures utilize virtual machines. In the example of FIG. **20**, this is illustrated by virtual machine **2048**. A virtual machine creates a software environment where applications/modules can execute as if they were executing on a hardware machine (such as the machine **2100** of FIG. **21**, for example). A virtual machine is hosted by a host operating system (operating system **2014** in FIG. **20**) and typically, although not always, has a virtual machine monitor **2046**, which manages the operation of the virtual machine **2048** as well as the interface with the host operating system (i.e., operating system **2014**). A software architecture executes within the virtual machine **2048** such as an oper-

ating system **2050**, libraries **2052**, frameworks/middleware **2054**, applications **2056** or presentation layer **2058**. These layers of software architecture executing within the virtual machine **2048** can be the same as corresponding layers previously described or may be different.

FIG. **21** is a block diagram illustrating components of a machine **2100**, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein. Specifically, FIG. **21** shows a diagrammatic representation of the machine **2100** in the example form of a computer system, within which instructions **2116** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **2100** to perform any one or more of the methodologies discussed herein can be executed. For example, the instructions **2116** can cause the machine **2100** to execute the flow diagrams of FIGS. **5**, **6**, **8**, **10**, **13**, and **17**. Additionally, or alternatively, the instructions **2116** can implement the communication module **210**, the presentation module **220**, the finder module **230**, the alignment module **240**, the decoder module **250**, the action module **260**, or the encoder module **270** of FIG. **2**, and so forth. The instructions **2116** transform the general, non-programmed machine into a particular machine programmed to carry out the described and illustrated functions in the manner described. In alternative embodiments, the machine **2100** operates as a standalone device or can be coupled (e.g., networked) to other machines. In a networked deployment, the machine **2100** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **2100** can comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **2116**, sequentially or otherwise, that specify actions to be taken by the machine **2100**. Further, while only a single machine **2100** is illustrated, the term “machine” shall also be taken to include a collection of machines **2100** that individually or jointly execute the instructions **2116** to perform any one or more of the methodologies discussed herein.

The machine **2100** can include processors **2110**, memory/storage **2130**, and I/O components **2150**, which can be configured to communicate with each other such as via a bus **2102**. In an example embodiment, the processors **2110** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) can include, for example, processor **2112** and processor **2114** that may execute instructions **2116**. The term “processor” is intended to include multi-core processor that may comprise two or more independent processors (sometimes referred to as “cores”) that can execute instructions contemporaneously. Although FIG. **21** shows multiple processors **2110**, the machine **2100** may include a single processor with a single core, a single processor with multiple cores (e.g., a multi-core processor),

multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

The memory/storage **2130** can include a memory **2132**, such as a main memory, or other memory storage, and a storage unit **2136**, both accessible to the processors **2110** such as via the bus **2102**. The storage unit **2136** and memory **2132** store the instructions **2116** embodying any one or more of the methodologies or functions described herein. The instructions **2116** can also reside, completely or partially, within the memory **2132**, within the storage unit **2136**, within at least one of the processors **2110** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **2100**. Accordingly, the memory **2132**, the storage unit **2136**, and the memory of the processors **2110** are examples of machine-readable media.

As used herein, the term "machine-readable medium" means a device able to store instructions and data temporarily or permanently and may include, but is not be limited to, random-access memory (RAM), read-only memory (ROM), buffer memory, flash memory, optical media, magnetic media, cache memory, other types of storage (e.g., Erasable Programmable Read-Only Memory (EEPROM)) or any suitable combination thereof. The term "machine-readable medium" should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store instructions **2116**. The term "machine-readable medium" shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., instructions **2116**) for execution by a machine (e.g., machine **2100**), such that the instructions, when executed by one or more processors of the machine **2100** (e.g., processors **2110**), cause the machine **2100** to perform any one or more of the methodologies described herein. Accordingly, a "machine-readable medium" refers to a single storage apparatus or device, as well as "cloud-based" storage systems or storage networks that include multiple storage apparatus or devices. The term "machine-readable medium" excludes signals per se.

The I/O components **2150** can include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **2150** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones will likely include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **2150** can include many other components that are not shown in FIG. 21. The I/O components **2150** are grouped according to functionality merely for simplifying the following discussion and the grouping is in no way limiting. In various example embodiments, the I/O components **2150** can include output components **2152** and input components **2154**. The output components **2152** can include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input components **2154** can include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point based input components (e.g., a mouse, a

touchpad, a trackball, a joystick, a motion sensor, or other pointing instruments), tactile input components (e.g., a physical button, a touch screen that provides location and force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

In further example embodiments, the I/O components **2150** can include biometric components **2156**, motion components **2158**, environmental components **2160**, or position components **2162** among a wide array of other components. For example, the biometric components **2156** can include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram based identification), and the like. The motion components **2158** can include acceleration sensor components (e.g., an accelerometer), gravitation sensor components, rotation sensor components (e.g., a gyroscope), and so forth. The environmental components **2160** can include, for example, illumination sensor components (e.g., a photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., a barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensor components (e.g., machine olfaction detection sensors, gas detection sensors to detect concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components **2162** can include location sensor components (e.g., a Global Positioning System (GPS) receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

Communication can be implemented using a wide variety of technologies. The I/O components **2150** may include communication components **2164** operable to couple the machine **2100** to a network **2180** or devices **2170** via a coupling **2182** and a coupling **2172**, respectively. For example, the communication components **2164** include a network interface component or other suitable device to interface with the network **2180**. In further examples, communication components **2164** include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, BLUETOOTH® components (e.g., BLUETOOTH® Low Energy), WI-FI® components, and other communication components to provide communication via other modalities. The devices **2170** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a Universal Serial Bus (USB)).

Moreover, the communication components **2164** can detect identifiers or include components operable to detect identifiers. For example, the communication components **2164** can include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as a Universal Product Code (UPC) bar code, multi-dimensional bar codes such as

a Quick Response (QR) code, Aztec Code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, Uniform Commercial Code Reduced Space Symbology (UCC RSS)-2D bar codes, and other optical codes), acoustic detection components (e.g., microphones to identify tagged audio signals), or any suitable combination thereof. In addition, a variety of information can be derived via the communication components 2164, such as location via Internet Protocol (IP) geo-location, location via WI-FI® signal triangulation, location via detecting a BLUETOOTH® or NFC beacon signal that may indicate a particular location, and so forth.

In various example embodiments, one or more portions of the network 2180 can be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a WI-FI® network, another type of network, or a combination of two or more such networks. For example, the network 2180 or a portion of the network 2180 may include a wireless or cellular network, and the coupling 2182 may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other type of cellular or wireless coupling. In this example, the coupling 2182 can implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1xRTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard setting organizations, other long range protocols, or other data transfer technology.

The instructions 2116 can be transmitted or received over the network 2180 using a transmission medium via a network interface device (e.g., a network interface component included in the communication components 2164) and utilizing any one of a number of well-known transfer protocols (e.g., Hypertext Transfer Protocol (HTTP)). Similarly, the instructions 2116 can be transmitted or received using a transmission medium via the coupling 2172 (e.g., a peer-to-peer coupling) to devices 2170. The term “transmission medium” shall be taken to include any intangible medium that is capable of storing, encoding, or carrying the instructions 2116 for execution by the machine 2100, and includes digital or analog communications signals or other intangible medium to facilitate communication of such software.

FIG. 22 is a data flow diagram of an end to end encryption method 2200. The method 2200 is implemented in conjunction with two client devices—the client device of Alice 2202 and Bob 2206. (The names “Alice” and “Bob” are used as examples for convenience only. Also, while Alice 2202 and Bob 2206 are illustrated as being laptop computers, either Alice 2202 or Bob 2206 may be any computing device, such as a mobile phone, tablet computer, personal digital assistant (PDA), digital music player, or desktop computer.) The client devices Alice 2202 and Bob 2206 communicate with one another via a server 2204. For example, the server 2204 is a messaging server and Alice 2202 and Bob 2206 are mobile devices that include a messaging application asso-

ciated with the server 2204. The client devices Alice 2202 and Bob 2206 may correspond to client devices 110 of FIG. 1. The server 2204 may correspond to the social messaging system 130 of FIG. 1.

The method 2200 may be implemented when Alice 2202 and Bob 2206 first begin communicating with one another, for example, when Alice 2202 and Bob 2206 add one another as friends in the messaging service or when Alice 2202 or Bob 2206 first join the messaging service.

The method 2200 begins at step 2210-S, where the server 2204, in order to allow for encrypted messaging between client devices, selects values of g and p . The value p is a large (e.g., greater than a threshold value, such as 10^7 or 10^9) prime number, and the value g is a primitive root modulo p that is less than p and greater than 1. In some cases, g is also a prime number.

As used herein, the phrase “primitive root modulo” encompasses its plain and ordinary meaning. According to some examples, a number g is a primitive root modulo p if every number coprime to p is congruent to a power of g modulo p . That is, for every integer k such that $\gcd(k, p) = 1$, there is an integer a such that $g^a \equiv k \pmod{p}$.

The server 2204 notifies Alice 2202 and Bob 2206 of the values of g and p , which may be accessible to the general public and to any devices that use the messaging application associated with the server 2204. In alternative embodiments, the server 2204 may select different values of g and p for different client devices, or the values g and p may be selected at one of the client devices Alice 2202 or Bob 2206.

At step 2220-A, Alice 2202 selects a private key a . The private key a is an integer greater than 1 and less than p . Alice 2202 may store the private key a in a secure part of local memory and may not share the value of a with any other machine.

Similarly, at step 2220-B, Bob 2206 selects a private key b . The private key b is an integer greater than 1 and less than p . Bob 2206 may store the private key b in a secure part of local memory and may not share the value of b with any other machine.

At step 2230-A, Alice 2202 computes its public key according to the equation: $A = g^a \pmod{p}$. Alice 2202 communicates its public key A to Bob 2206.

Similarly, at step 2230-B, Bob 2206 computes its public key according to the equation: $B = g^b \pmod{p}$. Bob 2206 communicates its public key B to Alice 2202.

At step 2240-A, Alice 2202 computes a shared secret according to the equation: $s = B^a \pmod{p}$. At step 2240-B, Bob 2206 computes the same shared secret s , but using a different equation: $s = A^b \pmod{p}$. The shared secret s is stored in the local memory of Alice 2202 and in the local area of Bob 2206, in some cases, in a secure part of the local memory. It should be noted that both Alice 2202 and Bob 2206 compute the same shared secret, using a combination of private and public values to reach the result.

As shown at blocks 2250-A, 2250-B, and 2250-S, after steps 2240-A and 2240-B, g , p , A , and B are public values known to Alice 2202, Bob 2206, and the server 2204. The private keys a and b are private values that are only known to Alice 2202 and Bob 2206, respectively. The shared secret s is a private value that is known only to Alice 2202 and to Bob 2206, but not to the server 2204.

After implementing the method 2200, Alice 2202 and Bob 2206 may communicate with one another by encrypting messages with the shared secret s before transmission and decrypting messages with the shared secret s after transmission. The encrypted messages can be decrypted by Alice

2202 and by Bob 2206, but not by any eavesdroppers who may have access to the server 2204. Furthermore, by verifying that a message was encrypted with s , Alice 2202 can verify that the message was sent by Bob 2206, and Bob 2206 can verify that the message was sent by Alice 2202, since only Alice 2202 and Bob 2206 know the value of the shared secret s . In some cases, the shared secrets is run through a key derivation function, and the output of the function is used to encrypt data.

According to one example implementation, at step 2210-S, the server 2204 selects $g=5$ and $p=23$. (In most implementations, larger values of g or p may be used. However, small numbers are used here for simplicity of explanation.)

At steps 2220-A and 2220-B, the values $a=6$ and $b=15$ are selected.

Thus, at steps 2230-A and 2230-B, Alice 2202 computes $A=g^a \bmod p=5^6 \bmod 23=8$. Bob 2206 computes $B=g^b \bmod p=5^{15} \bmod 23=19$.

At steps 2240-A and 2240-B, Alice 2202 computes the shared secret $s=B^a \bmod p=19^6 \bmod 23=2$. Bob 2206 computes, via a different equation, the shared secret $s=A^b \bmod p=8^{15} \bmod 23=2$. It should be noted that both Alice 2202 and Bob 2206 arrive at the same shared secret $s=2$, using different inputs to compute the shared secret s .

Alice 2202 may periodically modify a value of the private key a , for example, after a passage of a predetermined time period or after sending a predetermined number of messages. Upon modifying the private key a , Alice 2202 re-computes its public key A based on the modified value of its private key a . Alice 2202 notifies Bob 2206 of the re-computed value of the public key A . Alice 2202 re-computes the shared secrets of Alice 2202 and Bob 2206 based on the modified value of the private key a . Upon receiving a notification, from Alice 2202, that the public key A of Alice 2202 has changed, Bob 2206 re-computes the shared secret s of Alice 2202 and Bob 2206 based on the modified value of the public key A .

Similarly, Bob 2206 may periodically modify a value of the private key b , for example, after a passage of a predetermined time period or after sending a predetermined number of messages. Upon modifying the private key b , Bob 2206 re-computes its public key B based on the modified value of its private key b . Bob 2206 notifies Alice 2202 of the re-computed value of the public key B . Bob 2206 re-computes the shared secrets of Alice 2202 and Bob 2206 based on the modified value of the private key b . Upon receiving a notification, from Bob 2206, that the public key B of Bob 2206 has changed, Alice 2202 re-computes the shared secret s of Alice 2202 and Bob 2206 based on the modified value of the public key B .

According to some implementations, User-A may install a messaging application on a client device. Upon installation, the messaging application generates a long-term asymmetric signing key and N short-term asymmetric data encryption keys. In order to communicate with the client device of User-B, the client device of User-A needs to obtain the public encryption keys for User-B. In some examples, the public encryption keys are exchanged during the "Add friend" procedure, which is implemented when User-A and User-B indicate that they wish to communicate with one another in the messaging application. The public keys are stored at a server or a data repository associated with the messaging application (e.g., server 2204) and are obtained by the client devices of User-A and User-B, by accessing the server or the data repository over a network. Alternatively, the public encryption keys may be exchanged the first time User-A sends a message to User-B or User-B sends a

message to User-A. When the first message is sent or when the "add friend" procedure is implemented, the public keys can be obtained from the server (e.g., server 2204) or from the communication partner (e.g., Alice 2202 can obtain the public key of Bob 2206 from Bob 2206). The public keys are stored either in a server or data repository associated with the messaging application or on the devices of the users having the public keys (e.g., User-A's public key is stored on User-A's client device). As noted above, client devices may occasionally modify their public and private keys to increase security in the unlikely event that a key is accidentally compromised by "hacking" into the client device or by guessing the value of the key.

According to some implementations, the server verifies, by communicating with the client device, that a message is successfully decrypted at the client device. If the message is not successfully decrypted, the server checks whether the public key of the communication partner has changed and, if so, updates the public key provided to the client device. The server checks, by accessing the client device receiving the message, whether the public key of the client device receiving the message has changed and, if so, updates the public key stored at the communication partner device and instructs the communication partner device to attempt re-encoding (e.g., re-wrapping) and re-transmission of the message using the new public key of the client device by transmitting an instruction over the network. According to some implementations, the user may be able to view when his/her conversations are encrypted. For example, text or an image associated with encryption may be presented in a corner of the screen.

According to some implementations, a recipient who is logged out of the messaging application may have no available key material. In this case, the sender of the message may be notified that the recipient is logged out. The sender may be offered to wait to send the message until the recipient logs in, when the key material can be obtained from the recipient for encrypting the message. Alternatively, the sender may be offered to send the message to the recipient without using encryption. In some cases, when encryption is always required, an error message may be presented.

According to some implementations, a first client device implementing a messaging application generates a 128-bit manifestation of its signing public key. For example, the first client device extracts 128-bits from a secure hash algorithm-256 (SHA-256) hash or other cryptographic hash function. The user of the first client device can then display his/her public key on the screen of the first client device, in a printed paper, within a social networking service, or the like. A user of a second client device can indicate, to the second client device, that he/she wishes to communicate with the user of the first client device in a secure manner. The user can scan, into the second client device, data that possibly corresponds to the public key of the first client device. The second client device verifies that the signing key of the first client device matches the data that was scanned. If the signing key of the first client device matches the data that was scanned, the signing key is marked as trusted, and is used for secure communication between the first client device and the second client device. FIG. 22 describes one approach to encryption. However, in alternative implementations, different approaches to encryption can be used in place of the approach described in FIG. 22. For example, some implementations of the subject technology use the Elliptic Curve Diffie Hellman (ECDH) algorithm for encryption.

FIG. 23 is a flow chart of a method 2300 for verifying that a message is from a communication partner based on information stored in an image. The method 2300 may be implemented in conjunction with the end to end encryption method 2200 of FIG. 22. The method 2300 may be implemented at a client device, such as one of the client devices 110, Alice 2202, or Bob 2206.

The method 2300 begins at step 2310, where the client device accesses an image. The image includes a geometric shape, such as a square or rectangle with rounded circles. For example, the image may be the optical barcode 406 of FIG. 4. In some examples, the client device accesses the image by pointing a camera of the client device at the image. Alternatively, the client device may access the image via a web browser, a social networking application, a messaging service, etc., executing on the client device. For example, the image may be displayed, by the web browser or other application, on the screen of the client device.

At step 2320, the client device determines whether a candidate shape is inside the geometric shape. For example, the client device may detect a shape within the geometric shape. The client device may compare the detected shape with a set of reference shapes to determine a similarity score. The client device may determine whether the similarity score exceeds a threshold, and determine whether the candidate shape is inside the geometric shape based on the similarity score exceeding the threshold. If the candidate shape is inside the geometric shape, the method 2300 continues to step 2330. Otherwise, the method 2300 ends.

At step 2330, the client device determines, using the candidate shape, an orientation of the geometric shape. For example, if the geometric shape is a rectangle, determining the orientation of the geometric shape may include determining an upward direction of the candidate shape, and setting an upward direction of the geometric shape based on the upward direction of the candidate shape and based on a direction of a side of the rectangle. According to some examples, the set upward direction of the geometric shape is perpendicular or parallel to the side of the rectangle. According to some examples, a ray corresponding to the set upward direction of the geometric shape and a ray corresponding to the determined upward direction of the candidate shape make an angle of less than 45 degrees.

At step 2340, the client device determines a public key B of a communication partner device by decoding, based on the determined orientation, data encoded within the geometric shape. The decoding may be completed using any of the approaches described herein for decoding information from an image or any other known approaches. In some cases, the public key B is encoded in the geometric shape, for example, in binary code with dots representing the digit 1 and blank spaces representing the digit 0. Alternatively, a code encoded in the geometric shape is used to access a server or a data repository. The server or the data repository stores a data structure (e.g., hash table, matrix, list, etc.) that is used to look up the public key B with the code encoded in the geometric shape. As a result of the use of the server or the data repository, a short (e.g., 256 bit) code encoded in the geometric shape can be used to look up a longer (e.g., 2048 or 3072 bit) public key. In some cases, as described in greater detail below, the client device reads, from the scanned image, a transformation of the value of B, rather than the actual value. The client device then verifies that a locally stored value of B is correct based on the read transformation of B.

At step 2350, the client device receives a message purporting to be from the communication partner device.

At step 2360, the client device verifies, based on the public key B of the communication partner device, whether the message is from the communication partner device. For example, the client device attempts to decode the message using a shared secrets, which is computed using the public key B of the communication partner device using the techniques described herein in conjunction with FIG. 22.

At step 2370, the client device determines whether the message is verified to be from the communication partner device using the result of step 2360. If the message is verified to be from the communication partner device, the computing device outputs (e.g., via a display unit) the message at step 2380. In some cases, the output of the message includes the text of the message and an indication of (e.g., text or an image associated with) the communication partner device. If the message is not verified to be from the communication partner device, the computing device outputs an error indicator at step 2390. After step 2380 or step 2390, the method 2300 ends.

In some cases, the number of bits that can be encoded within the image may be limited. For example, the image may have space for 128 bits, while the public key B may be 255 bits long. In these cases, when generating the image, the server computes a hash SHA-256 (public key B) and truncates the output to 128 bits. The truncated 128 bits are then encoded within the image. To verify the image, the client device selects a communication partner and scans the image to get the communication partner's public key B. The client device then finds a local copy of the communication partner's public key B, computes the hash, and truncates to 128 bits. The client device then verifies that the two 128 bit values are the same. In summary, in some cases, the image that is scanned does not include the public key itself and instead includes a transformation of the public key B.

Throughout this specification, plural instances may implement components, operations, or structures described as a single instance. Although individual operations of one or more methods are illustrated and described as separate operations, one or more of the individual operations may be performed concurrently, and nothing requires that the operations be performed in the order illustrated. Structures and functionality presented as separate components in example configurations may be implemented as a combined structure or component. Similarly, structures and functionality presented as a single component may be implemented as separate components. These and other variations, modifications, additions, and improvements fall within the scope of the subject matter herein.

Although an overview of the inventive subject matter has been described with reference to specific example embodiments, various modifications and changes may be made to these embodiments without departing from the broader scope of embodiments of the present disclosure. Such embodiments of the inventive subject matter may be referred to herein, individually or collectively, by the term "invention" merely for convenience and without intending to voluntarily limit the scope of this application to any single disclosure or inventive concept if more than one is, in fact, disclosed.

The embodiments illustrated herein are described in sufficient detail to enable those skilled in the art to practice the teachings disclosed. Other embodiments may be used and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. The Detailed Description, therefore, is not to be taken in a limiting sense, and the scope of various

35

embodiments is defined only by the appended claims, along with the full range of equivalents to which such claims are entitled.

As used herein, the term “or” may be construed in either an inclusive or exclusive sense. Moreover, plural instances may be provided for resources, operations, or structures described herein as a single instance. Additionally, boundaries between various resources, operations, modules, engines, and data stores are somewhat arbitrary, and particular operations are illustrated in a context of specific illustrative configurations. Other allocations of functionality are envisioned and may fall within a scope of various embodiments of the present disclosure. In general, structures and functionality presented as separate resources in the example configurations may be implemented as a combined structure or resource. Similarly, structures and functionality presented as a single resource may be implemented as separate resources. These and other variations, modifications, additions, and improvements fall within a scope of embodiments of the present disclosure as represented by the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

What is claimed is:

1. An apparatus of a mobile device, the apparatus comprising:

one or more processors; and

one or more memories storing instructions that when executed, configure the one or more processors to perform operations comprising:

causing an image capturing device of the mobile device to capture an image;

determining a public key of a communication partner by decoding unencrypted data encoded within the image, the unencrypted data comprising the public key;

receiving a wireless communication comprising a message;

verifying, based on decrypting at least a portion of the message using the public key, that the message is from the communication partner;

in response to a verification that the message is from the communication partner,

causing an indication that the message is verified to be displayed on a screen of the mobile device;

determining a shared secret of the mobile device and the communication partner according to an equation: $s = B^a \text{ mod } p$, wherein B indicates the public key of the communication partner, p is a prime number that exceeds a threshold, and g is a primitive root modulo p ; and

encrypting, for transmission to the communication partner, a second message using the shared secret.

2. The apparatus of claim 1, wherein the verifying further comprises:

comparing the public key to a preexisting public key for the communication partner.

3. The apparatus of claim 1, wherein the image includes a geometric shape, and wherein the operations further comprises

determining that the image includes a candidate shape inside the geometric shape;

determining an orientation of the geometric shape; and wherein determining the public key comprises:

determining the public key by decoding, based on the determined orientation, data encoded within the geometric shape.

36

4. The apparatus of claim 3, wherein determining that the image includes the candidate shape inside the geometric shape comprises:

detecting a shape within the geometric shape;

comparing the detected shape with a set of reference shapes to determine a similarity score; and

determining that the similarity score transgresses a threshold.

5. The apparatus of claim 3, wherein the geometric shape comprises a rectangle with rounded corners, and wherein determining the orientation of the geometric shape comprises:

determining an upward direction of the candidate shape; and

determining an upward direction of the geometric shape based on the upward direction of the candidate shape and based on a direction of at least one side of the rectangle.

6. The apparatus of claim 5, wherein the determined upward direction of the geometric shape is perpendicular or parallel to the at least one side of the rectangle.

7. The apparatus of claim 5, wherein a ray corresponding to the determined upward direction of the geometric shape and a ray corresponding to the determined upward direction of the candidate shape make an angle of less than 45 degrees.

8. The apparatus of claim 1, wherein the mobile device is associated with a social messaging platform, and wherein verifying further comprises:

sending an indication of the public key and an indication of the communication partner to the social messaging platform; and

receiving from the social messaging platform an indication of whether the public key and a preexisting public key are equivalent.

9. The apparatus of claim 1, wherein the operations further comprise:

generating, at the mobile device, a private key (a) of the mobile device;

computing a public key (A) of the mobile device, the public key of the mobile device being computed according to an equation: $A = g^a \text{ mod } p$;

decrypting the received message using the shared secret.

10. The apparatus of claim 9, wherein p , g , A , and B are publicly accessible values, and wherein the private key (a) of the mobile device is a secret value stored securely at the mobile device.

11. The apparatus of claim 9, wherein the operations further comprise:

periodically modifying a value of the private key (a) of the mobile device after a passage of a predetermined time period or after sending a predetermined number of messages;

re-computing the public key (A) of the mobile device based on the modified value of the private key (a) of the mobile device;

notifying the communication partner of the re-computed value of the public key (A) of the mobile device; and re-computing the shared secret(s) of the mobile device and the communication partner based on the modified value of the private key (a) of the mobile device.

12. The apparatus of claim 1, wherein the image is a first image, and wherein the operations further comprise:

accessing a web browser, a social networking platform, or a messaging service, using information in the message.

37

13. A non-transitory computer readable medium comprising instructions that when executed configure hardware processing circuitry of a mobile device to perform operations comprising:

causing an image capturing device of the mobile device to capture an image;
 determining a public key of a communication partner by decoding unencrypted data encoded within the image, the unencrypted data comprising the public key;
 receiving a wireless communication comprising a message;
 verifying, based on decrypting at least of portion of the message using the public key, that the message is from the communication partner;
 in response to a verification that the message is from the communication partner,
 causing an indication that the message is verified to be displayed on a screen of the mobile device;
 determining a shared secret of the mobile device and the communication partner according to an equation: $s=B^a \text{ mod } p$, wherein B indicates the public key of the communication partner, p is a prime number that exceeds a threshold, and g is a primitive root modulo p;
 and
 encrypting, for transmission to the communication partner, a second message using the shared secret.

14. The non-transitory computer readable medium of claim 13, wherein the verifying further comprises:

comparing the public key to a preexisting public key for the communication partner.

15. The non-transitory computer readable medium of claim 13, wherein the image includes a geometric shape, and wherein the operations further comprises

determining that the image includes a candidate shape inside the geometric shape;
 determining an orientation of the geometric shape; and
 wherein determining the public key comprises:
 determining the public key by decoding, based on the determined orientation, data encoded within the geometric shape.

16. A method perform by an apparatus of a mobile device, the method comprising:

causing an image capturing device of the mobile device to capture an image;

38

determining a public key of a communication partner by decoding unencrypted data encoded within the image, the unencrypted data comprising the public key;
 receiving a wireless communication comprising a message;

verifying, based on decrypting at least of portion of the message using the public key, that the message is from the communication partner;

in response to a verification that the message is from the communication partner,

causing an indication that the message is verified to be displayed on a screen of the mobile device;

determining a shared secret of the mobile device and the communication partner according to an equation: $s=B^a \text{ mod } p$, wherein B indicates the public key of the communication partner, p is a prime number that exceeds a threshold, and g is a primitive root modulo p;
 and

encrypting, for transmission to the communication partner, a second message using the shared secret.

17. The method of claim 16, wherein the verifying further comprises:

comparing the public key to a preexisting public key for the communication partner.

18. The method of claim 16, wherein the image includes a geometric shape, and wherein the method further comprises:

determining that the image includes a candidate shape inside the geometric shape;
 determining an orientation of the geometric shape; and
 wherein determining the public key comprises:
 determining the public key by decoding, based on the determined orientation, data encoded within the geometric shape.

19. The method of claim 18, wherein determining that the image includes the candidate shape inside the geometric shape comprises:

detecting a shape within the geometric shape;
 comparing the detected shape with a set of reference shapes to determine a similarity score; and
 determining that the similarity score transgresses a threshold.

20. The method of claim 18, wherein the public key is a public signing key.

* * * * *