

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250249217

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

McEvoy; Francis Denis et al.

MEDICAL CATHETER

Abstract

In some examples, a catheter may include an elongate body and a push assembly. The elongate body may include an inner liner defining an entry port into a lumen defined by the elongate body, and an outer jacket. The push assembly may an anchor member positioned at a distal end of an elongate member. Distal to a proximal end of the elongate body, a first portion of the push assembly, comprising the anchor member, may be positioned between a portion of the inner liner and a portion of the outer jacket. The anchor member may extend only partially around an outer perimeter of the inner liner when the catheter is assembled. Proximal to the proximal end of the elongate body, a second portion of the push assembly, proximal to the first portion, may be positioned outside of the outer jacket and the inner liner.

Inventors: McEvoy; Francis Denis (Laois, IE), Connolly; Colm (Galway, IE), O'Connell; Barry (Galway, IE), Cooney; Shane (Galway, IE), Cunniffe; Joanna (Galway, IE), Hannon; James (Galway, IE), Larkin; Maria (Galway, IE)

Applicant: Medtronic Vascular, Inc. (Santa Rosa, CA)

Family ID: 67003697

Appl. No.: 19/188515

Filed: April 24, 2025

Related U.S. Application Data

parent US continuation 18146742 20221227 parent-grant-document US 12311129 child US 19188515

parent US continuation 16432679 20190605 parent-grant-document US 11541208 child US 18146742

us-provisional-application US 62680792 20180605

Publication Classification

Int. Cl.: **A61M25/06** (20060101); **A61F2/966** (20130101); **A61M25/00** (20060101); **A61M25/01** (20060101); **A61M25/09** (20060101)

U.S. Cl.:

CPC **A61M25/0662** (20130101); **A61F2/966** (20130101); **A61M25/005** (20130101); **A61M25/0108** (20130101); **A61M25/09** (20130101); A61M2025/0008 (20130101); A61M25/001 (20130101); A61M25/0012 (20130101); A61M2025/0681 (20130101); A61M2025/0687 (20130101)

Background/Summary

[0001] This application is a continuation of U.S. patent application Ser. No. 18/146,742, filed on Dec. 27, 2022, and entitled “MEDICAL CATHETER,” which is a continuation of U.S. patent application Ser. No. 16/432,679, filed on Jun. 5, 2019, now U.S. Pat. No. 11,541,208, and entitled, “MEDICAL CATHETER,” which claims the benefit of U.S. Provisional Application No. 62/680,792, filed Jun. 5, 2018, and entitled, “MEDICAL CATHETER,” the entire content of each of which is incorporated herein by reference.

TECHNICAL FIELD

[0002] This disclosure relates to a medical catheter.

BACKGROUND

[0003] A medical catheter defining at least one lumen has been proposed for use with various medical procedures. For example, in some cases, a medical catheter may be used to deliver a medical device and/or composition within vasculature of a patient.

SUMMARY

[0004] In some aspects, this disclosure describes example catheters that each include a push assembly and an elongate body including an inner liner defining an entry port into a lumen of the elongate body and an outer jacket. The push assembly may include an elongate member and an anchor member positioned at a distal end of the elongate member. The elongate member is relatively stiff such that the push assembly may be configured to facilitate introduction of the catheter in vasculature of a patient. When the push assembly is assembled with the elongate body, distal to the entry port, a portion of the push assembly including the anchor member may be positioned between adjacent portions of the inner liner and outer jacket. Proximal to the entry port, a portion of the push assembly may be positioned outside of adjacent portions of the inner liner and outer jacket. In some examples, a proximal portion of the push assembly may be positioned entirely outside of the inner liner and outer jacket. In some examples, the anchor member may have a partial-ring shape and a beveled distal edge and may extend partially around an outer perimeter of the inner liner.

[0005] In some examples, a catheter system includes an outer catheter, and the catheter including the push assembly may be an inner catheter that may be introduced into vasculature of a patient through a lumen of the outer catheter. The elongate body may be configured to extend out of a distal opening of the outer catheter to extend through heavy tortuosity or calcification within a body vessel. The elongate body may have a smaller radial profile and may be more flexible than the outer catheter such that it may more easily navigate through heavy tortuosity or calcification within a body vessel than the outer catheter. In some examples, the elongate body may include an atraumatic tip to minimize adverse interactions with patient tissue during advancement of the

elongate body within a body vessel.

[0006] Clause 1: In some examples, a catheter comprises an elongate body and a push assembly, the elongate body comprising an outer jacket and an inner liner defining an entry port into a lumen defined by the elongate body, the push assembly including an elongate member and an anchor member, the anchor member positioned at a distal end of the elongate member, wherein distal to a proximal end of the elongate body, a first portion of the push assembly is positioned between a portion of the inner liner and a portion of the outer jacket, and proximal to the proximal end of the elongate body, a second portion of the push assembly is positioned outside of the outer jacket and the inner liner, wherein the first portion of the push assembly comprises the anchor member, the anchor member extending only partially around an outer perimeter of the inner liner, and wherein the second portion of the push assembly is proximal to the first portion.

[0007] Clause 2: In some examples of the catheter of clause 1, the anchor member defines a beveled distal edge.

[0008] Clause 3: In some examples of the catheter of clause 1 or clause 2, the anchor member comprises a radiopaque marker.

[0009] Clause 4: In some examples of the catheter of any of clauses 1-3, the anchor member extends about 140 degrees to about 160 degrees around an outer perimeter of the inner liner.

[0010] Clause 5: In some examples of the catheter of any of clauses 1-4, the anchor member extends about 160 degrees around the outer perimeter of the inner liner.

[0011] Clause 6: In some examples of the catheter of any of clauses 1-5, the anchor member extends from a proximal end to a distal end, the anchor member defining a slot extending from the proximal end towards the distal end, and wherein the distal end of the elongate member is positioned at least partially within the slot.

[0012] Clause 7: In some examples of the catheter of clause 6, the slot has a length from about 25 percent to about 75 percent of a length of the anchor member, the length of the anchor member being measured from the proximal end to the distal end of the anchor member.

[0013] Clause 8: In some examples of the catheter of clause 7, the length of the slot is about 40 percent to about 60 percent of the length of the anchor member.

[0014] Clause 9: In some examples of the catheter of any of clauses 1-8, the anchor member is welded to the elongate member.

[0015] Clause 10: In some examples of the catheter of clause 9, the catheter further comprises welding material between the anchor member and the elongate member.

[0016] Clause 11: In some examples of the catheter of any of clauses 1-10, the anchor member is 50 to 100 micrometers thick, a thickness of the anchor member being measured in a direction perpendicular to a longitudinal axis defined by the elongate body when the anchor member is mechanically connected to the elongate member.

[0017] Clause 12: In some examples of the catheter of any of clauses 1-11, the anchor member defines a partial-ring shape.

[0018] Clause 13: In some examples of the catheter of any of clauses 1-12, the outer jacket comprises a first outer jacket section and a second outer jacket section distal to the first outer jacket section, and wherein the first and second outer jacket sections have different stiffnesses.

[0019] Clause 14: In some examples of the catheter of any of clauses 1-13, the inner liner comprises a first inner liner section and a second inner liner section distal to the first inner liner section, and wherein the first inner liner section defines the entry port.

[0020] Clause 15: In some examples of the catheter of clause 14, a proximal end of the anchor member is aligned with a proximal end of the entry port.

[0021] Clause 16: In some examples of the catheter of any of clauses 1-15, the entry port extends along a length of the elongate body.

[0022] Clause 17: In some examples of the catheter of any of clauses 1-16, the portion of the inner liner comprises a first portion of the inner liner and the portion of the outer jacket comprises a first

portion of the outer jacket, the catheter further comprising a reinforcement member positioned between at least a portion of the inner liner and at least a second portion of the outer jacket.

[0023] Clause 18: In some examples of the catheter of clause 17, a distal end of the anchor member is positioned proximal to the reinforcement member.

[0024] Clause 19: In some examples of the catheter of clause 17 or clause 18, the distal end of the anchor member abuts a proximal end of the reinforcement member.

[0025] Clause 20: In some examples of the catheter of clause 17 or clause 18, the distal end of the anchor member is spaced from a proximal end of the reinforcement member.

[0026] Clause 21: In some examples of the catheter of any of clauses 1-20, the anchor member defines an inner surface and an outer surface wherein at least one of the inner surface or the outer surface defines a non-semicircular surface.

[0027] Clause 22: In some examples of the catheter of clause 21, the non-semicircular surface defines a plurality of notches.

[0028] Clause 23: In some examples of the catheter of clause 21 or clause 22, the non-semicircular surface defines a plurality of waves.

[0029] Clause 24: In some examples of the catheter of any of clauses 1-23, the catheter further comprises a sleeve surrounding at least a portion of the elongate member external to the lumen defined by elongate body.

[0030] Clause 25: In some examples of the catheter of clause 24, an outer surface of the sleeve is textured.

[0031] Clause 26: In some examples of the catheter of clause 25, the textured outer surface is etched.

[0032] Clause 27: In some examples of the catheter of any of clauses 24-26, the sleeve is a different color than at least one of: the elongate member, the inner liner, or the outer jacket.

[0033] Clause 28: In some examples of the catheter of clauses 24-27, the sleeve comprises a partial cut around a perimeter of the sleeve, the partial cut extending only partially through a radial thickness of the sleeve.

[0034] Clause 29: In some examples of the catheter of clause 28, the partial cut extends 360 degrees around a cross section of the sleeve.

[0035] Clause 30: In some examples of the catheter of any of clauses 24-29, the sleeve comprises a visible marker.

[0036] Clause 31: In some examples of the catheter of clause 30, the sleeve comprises a double-stripe mark.

[0037] Clause 32: In some examples of the catheter of any of clauses 1-31, the elongate member tapers in a distal direction.

[0038] Clause 33: In some examples of the catheter of clause 32, a cross section of the elongate member is circular at a first portion and D-shaped at a second portion, the first portion being proximal to the second portion.

[0039] Clause 34: In some examples of the catheter of clause 32, a cross section of the elongate member is circular at a first portion and flat at a second portion, the first portion being proximal to the second portion.

[0040] Clause 35: In some examples of the catheter of any of clauses 1-34, the outer jacket comprises a tubular distal portion and a tapered proximal portion, wherein the tapered proximal portion comprises the portion of the outer jacket.

[0041] Clause 36: In some examples of the catheter of any of clauses 1-35, a proximal end of the inner liner is proximal to the entry port.

[0042] Clause 37: In some examples, a method of forming a catheter comprises inserting an anchor member of a push assembly between an inner liner and an outer jacket, wherein the anchor member, when inserted, extends only partially around an outer perimeter of the inner liner, and wherein the anchor member is positioned at a distal end of an elongate member of the push

assembly. The method further comprises heating at least one of the inner liner or the outer jacket to reflow material around the anchor member, wherein the elongate body comprises the inner liner and the outer jacket, wherein the inner liner defines an entry port into a lumen defined by the elongate body, wherein, after insertion and advancement of the anchor member, distal to a proximal end of the elongate body, a first portion of the push assembly is positioned between a portion of the inner liner and a portion of the outer jacket, and proximal to the proximal end of the elongate body, a second portion of the push assembly is positioned outside of the outer jacket and the inner liner, wherein the first portion of the push assembly comprises the anchor member, and wherein the second portion of the push assembly is proximal to the first portion.

[0043] Clause 38: In some examples of the method of clause 37, the method further comprises coupling the anchor member to the elongate member.

[0044] Clause 39: In some examples of the method of clause 38, coupling the anchor member to the elongate member comprises welding the anchor member to the elongate member.

[0045] Clause 40: In some examples of the method of clause 39, welding the anchor member to the elongate member comprises placing welding material between the anchor member and the elongate member.

[0046] Clause 41: In some examples of the method of any of clauses 38-40, the anchor member extends from a proximal end to a distal end, the anchor member defining a slot extending from the proximal end towards the distal end, wherein coupling the anchor member to the elongate member comprises positioning the distal end of the elongate member at least partially within the slot.

[0047] Clause 42: In some examples of the method of clause 41, the slot has a length from about 25 percent to about 75 percent of a length of the anchor member, the length of the anchor member being measured from the proximal end to the distal end of the anchor member.

[0048] Clause 43: In some examples of the method of clause 42, the length of the slot is about 40 percent to about 60 percent of the length of the anchor member.

[0049] Clause 44: In some examples of the method of any of clauses 37-43, the anchor member defines a beveled distal edge.

[0050] Clause 45: In some examples of the method of any of clauses 37-44, the anchor member comprises a radiopaque marker.

[0051] Clause 46: In some examples of the method of any of clauses 37-45, the anchor member extends about 140 degrees to about 160 degrees around the outer perimeter of the inner liner.

[0052] Clause 47: In some examples of the method of clause 46, the anchor member extends about 160 degrees around the outer perimeter of the inner liner.

[0053] Clause 48: In some examples of the method of any of clauses 37-47, the anchor member is about 50 micrometers to about 100 micrometers thick, a thickness of the anchor member being measured in a direction perpendicular to a longitudinal axis defined by the elongate body when the anchor member is mechanically connected to the elongate member.

[0054] Clause 49: In some examples of the method of any of clauses 37-48, the anchor member defines a partial-ring shape.

[0055] Clause 50: In some examples of the method of any of clauses 37-49, the outer jacket comprises a first outer jacket section and a second outer jacket section distal to the first outer jacket section, and wherein the first and second outer jacket sections have different stiffnesses.

[0056] Clause 51: In some examples of the method of any of clauses 37-50, the outer jacket comprises a first outer jacket section and a second outer jacket section distal to the first outer jacket section, and wherein the first outer jacket section and the inner liner define the entry port.

[0057] Clause 52: In some examples of the method of any of clauses 37-51, advancing the anchor member between the inner liner and the outer jacket in the distal direction comprises aligning a proximal end of the anchor member with a proximal end of the entry port.

[0058] Clause 53: In some examples of the method of any of clauses 37-52, the portion of the inner liner comprises a first portion of the inner liner and the portion of the outer jacket comprises a first

portion of the outer jacket, the catheter further comprising positioning a reinforcement member between at least a second portion of the inner liner and at least a second portion of the outer jacket.

[0059] Clause 54: In some examples of the method of clause 53, advancing the anchor member between the inner liner and the outer jacket in the distal direction comprises positioning a distal end of the anchor member proximal to the reinforcement member.

[0060] Clause 55: In some examples of the method of clause 53 or clause 54, advancing the anchor member between the inner liner and the outer jacket in the distal direction comprises positioning the distal end of the anchor member such that it abuts a proximal end of the reinforcement member.

[0061] Clause 56: In some examples of the method of clause 53 or clause 54, after heating the at least one of the inner liner or the outer jacket to reflow material around the anchor member, there is a space between the distal end of the anchor member and a proximal end of the reinforcement member.

[0062] Clause 57: In some examples of the method of any of clauses 37-56, the anchor member defines an inner surface and an outer surface wherein at least one of the inner surface or the outer surface defines a non-semicircular surface.

[0063] Clause 58: In some examples of the method of clause 57, the non-semicircular surface defines a plurality of notches.

[0064] Clause 59: In some examples of the method of clause 57 or clause 58, the non-semicircular surface defines a plurality of waves.

[0065] Clause 60: In some examples of the method of any of clauses 37-59, the method further comprises positioning a sleeve around at least a portion of the elongate member external to a lumen defined by the elongate body.

[0066] Clause 61: In some examples of the method of clause 60, an outer surface of the sleeve is textured.

[0067] Clause 62: In some examples of the method of clause 61, the textured outer surface is etched.

[0068] Clause 63: In some examples of the method of any of clauses 60-62, the sleeve is a different color than at least one of: the elongate member, the inner liner, or the outer jacket.

[0069] Clause 64: In some examples of the method of any of clauses 60-63, the sleeve comprises a partial cut around a perimeter of the sleeve, the partial cut extending only partially through a radial thickness of the sleeve.

[0070] Clause 65: In some examples of the method of clause 64, the partial cut extends 360 degrees around a cross section of the sleeve.

[0071] Clause 66: In some examples of the method of any of clauses 60-65, the sleeve comprises a visible marker.

[0072] Clause 67: In some examples of the method of clause 66, the sleeve comprises a double-stripe mark.

[0073] Clause 68: In some examples of the method of any of clauses 37-67, the elongate member tapers in a distal direction.

[0074] Clause 69: In some examples of the method of clause 68, a cross section of the elongate member is circular at a first portion and D-shaped at a second portion, the first portion being proximal to the second portion.

[0075] Clause 70: In some examples of the method of clause 68, a cross section of the elongate member is circular at a first portion and flat at a second portion, the first portion being proximal to the second portion.

[0076] Clause 71: In some examples of the method of any of clauses 37-70, the outer jacket comprises a tubular distal portion and a tapered proximal portion, wherein the tapered proximal portion comprises the portion of the outer jacket.

[0077] Clause 72: In some examples of the method of any of clauses 37-71, a proximal end of the inner liner is proximal to the entry port.

[0078] Clause 73: In some examples, a catheter comprises an elongate body and a push assembly, the elongate body comprising an inner liner and an outer jacket, the inner liner defining an outer perimeter and defining an entry port into a lumen defined by the elongate body. The push assembly includes an anchor member positioned at a distal end of an elongate member, the anchor member defining a beveled distal edge, wherein distal to a proximal end of the elongate body, a distal portion of the push assembly is positioned between a portion of the inner liner and a portion of the outer jacket, and proximal to the proximal end of the elongate body, a proximal portion of the push assembly is positioned entirely outside of the outer jacket and the inner liner, wherein the distal portion of the push assembly comprises the anchor member, the anchor member having an inner perimeter that is less than the outer perimeter of the inner liner.

[0079] Clause 74: In some examples of the catheter of clause 73, the anchor member comprises a radiopaque marker.

[0080] Clause 75: In some examples of the catheter of clause 73 or clause 74, the anchor member extends about 140 degrees to about 160 degrees around an outer perimeter of the inner liner.

[0081] Clause 76: In some examples of the catheter of clause 75, the anchor member extends about 160 degrees around the outer perimeter of the inner liner.

[0082] Clause 77: In some examples of the catheter of any of clauses 73-76, the anchor member extends from a proximal end to a distal end, the anchor member defining a slot extending from the proximal end towards the distal end, and wherein the distal end of the elongate member is positioned at least partially within the slot.

[0083] Clause 78: In some examples of the catheter of clause 77, the slot has a length from about 25 percent to about 75 percent of a length of the anchor member, the length of the anchor member being measured from the proximal end to the distal end of the anchor member.

[0084] Clause 79: In some examples of the catheter of clause 78, the length of the slot is about 40 percent to about 60 percent of the length of the anchor member.

[0085] Clause 80: In some examples of the catheter of any of clauses 73-79, the anchor member is welded to the elongate member.

[0086] Clause 81: In some examples of the catheter of clause 80, the catheter further comprises welding material between the anchor member and the elongate member.

[0087] Clause 82: In some examples of the catheter of any of clauses 73-81, the anchor member is about 50 micrometers thick to about 100 micrometers thick, a thickness of the anchor member being measured in a direction perpendicular to a longitudinal axis defined by the elongate body when the anchor member is mechanically connected to the elongate member.

[0088] Clause 83: In some examples of the catheter of any of clauses 73-82, the anchor member defines a partial-ring shape.

[0089] Clause 84: In some examples of the catheter of any of clauses 73-83, the outer jacket comprises a first outer jacket section and a second outer jacket section distal to the first outer jacket section, and the first and second outer jacket sections have different stiffnesses.

[0090] Clause 85: In some examples of the catheter of any of clauses 73-84, the inner liner comprises a first inner liner section and a second inner liner section distal to the first inner liner section, and the first inner liner section defines the entry port.

[0091] Clause 86: In some examples of the catheter of clause 85, a proximal end of the anchor member is aligned with a proximal end of the entry port.

[0092] Clause 87: In some examples of the catheter of any of clauses 73-86, the portion of the inner liner comprises a first portion of the inner liner and the portion of the outer jacket comprises a first portion of the outer jacket, and the catheter further comprises a reinforcement member positioned between at least a second portion of the inner liner and at least a second portion of the outer jacket.

[0093] Clause 88: In some examples of the catheter of clause 87, a distal end of the anchor member is positioned proximal to the reinforcement member.

[0094] Clause 89: In some examples of the catheter of clause 88, the distal end of the anchor

member abuts a proximal end of the reinforcement member.

[0095] Clause 90: In some examples of the catheter of any of clauses 73-89, the anchor member defines an inner surface and an outer surface wherein at least one of the inner surface or the outer surface defines a non-semicircular surface.

[0096] Clause 91: In some examples of the catheter of clause 90, the non-semicircular surface defines a plurality of notches.

[0097] Clause 92: In some examples of the catheter of clause 90 or clause 91, the non-semicircular surface defines a plurality of waves.

[0098] Clause 93: In some examples of the catheter of any of clauses 73-92, the catheter further comprises a sleeve surrounding at least a portion of the elongate member external to the lumen defined by the elongate body.

[0099] Clause 94: In some examples of the catheter of clause 93, an outer surface of the sleeve is textured.

[0100] Clause 95: In some examples of the catheter of clause 94, the textured outer surface is etched.

[0101] Clause 96: In some examples of the catheter of any of clauses 93-95, the sleeve is a different color than at least one of: the elongate member, the inner liner, or the outer jacket. Clause

97: In some examples of the catheter of any of clauses 93-96, the sleeve

[0102] comprises a partial cut around a perimeter of the sleeve, and the partial cut extends only partially through a radial thickness of the sleeve.

[0103] Clause 98: In some examples of the catheter of clause 97, the partial cut extends 360 degrees around a cross section of the sleeve.

[0104] Clause 99: In some examples of the catheter of any of clauses 93-98, the sleeve comprises a visible marker.

[0105] Clause 100: In some examples of the catheter of any of clauses 93-99, the sleeve comprises a double-stripe mark.

[0106] Clause 101: In some examples of the catheter of clause 73, the elongate member tapers in a distal direction.

[0107] Clause 102: In some examples of the catheter of clause 101, a cross section of the elongate member is circular at a first portion and D-shaped at a second portion, the first portion being proximal to the second portion.

[0108] Clause 103: In some examples of the catheter of clause 101, a cross section of the elongate member is circular at a first portion and flat at a second portion, the first portion being proximal to the second portion.

[0109] Clause 104: In some examples of the catheter of any of clauses 73-103, the outer jacket comprises a tubular distal portion and a tapered proximal portion, wherein the tapered proximal portion comprises the portion of the outer jacket.

[0110] Clause 105: In some examples of the catheter of any of clauses 73-104, a proximal end of the inner liner is proximal to the entry port.

[0111] The details of one or more aspects of the disclosure are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the techniques described in this disclosure will be apparent from the description and drawings, and from the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0112] FIG. 1 is a conceptual side view of an example catheter, which includes an elongate body, a push assembly, and a handle.

[0113] FIG. 2 is a conceptual cross-sectional view of a portion of the example catheter of FIG. 1 and an outer catheter.

[0114] FIG. 3 is a conceptual cross-sectional view of an example elongate member of the push assembly of the catheter of FIGS. 1 and 2 taken along line 3-3 in FIG. 2.

[0115] FIG. 4 is a conceptual cross-sectional view of an example elongate member of the push assembly of the catheter of FIGS. 1 and 2 taken along line 4-4 in FIG. 2.

[0116] FIG. 5 is a conceptual cross-sectional view of an example elongate member of the push assembly of the catheter of FIGS. 1 and 2 taken along line 5-5 in FIG. 2.

[0117] FIG. 6 is a conceptual cross-sectional view of the catheter of FIGS. 1 and 2 taken along line 6-6 in FIG. 2.

[0118] FIGS. 7A and 7B are conceptual cross-sectional views of examples of the catheter of FIGS. 1 and 2 taken along line 7-7 in FIG. 2.

[0119] FIGS. 8A and 8B are conceptual cross-sectional views of examples of the catheter of FIGS. 1 and 2 taken along line 8-8 in FIG. 2.

[0120] FIG. 9 is a conceptual perspective view of the anchor member of FIGS. 1, 2, 6, 7A, 7B, 8A, and 8B.

[0121] FIGS. 10A and 10B are conceptual perspective views of the push assembly of FIGS. 1, 2, 6, 7A, and 7B.

[0122] FIG. 11 is a conceptual perspective view of an example push assembly, such as the push assembly of FIGS. 1, 2, 10A and 10B, further including a radiopaque band.

[0123] FIGS. 12 and 13 are conceptual cross-sectional views of example anchor members, such as the anchor member of FIGS. 1 and 2, with an inner surface and/or an outer surface defining a non-semicircular surface.

[0124] FIG. 14 is a conceptual side view of an example of the anchor member of the push assembly of FIGS. 2, 10A, and 10B and a distal portion of the elongate member of the push assembly of FIGS. 2, 10A, and 10B, before the anchor member and the elongate member are mechanically connected together to form the push assembly.

[0125] FIG. 15 is a conceptual side view of the push assembly of FIG. 14 after the anchor member and the elongate member are mechanically connected together to form the push assembly.

[0126] FIG. 16 is a conceptual perspective view of a portion of an example of the elongate member of FIGS. 1, 2, 10A, 10B, and 11.

[0127] FIG. 17 is a flowchart illustrating an example method of assembling the example catheter shown in FIGS. 1 and 2.

DETAILED DESCRIPTION

[0128] In some examples, a medical catheter (“catheter”) described herein includes a push assembly and an elongate body including an inner liner and an outer jacket. The push assembly includes an elongate member (also referred to herein as a shaft) and an anchor member at a distal end of the push assembly. In some examples, the push assembly includes only one anchor member at the distal end of the push assembly, while in other examples, the push assembly includes a plurality of anchor members. The anchor member is configured to facilitate attachment of the elongate member to the inner liner and outer jacket of the elongate body. The anchor member may be positioned at a distal end of the elongate member.

[0129] The outer jacket and the inner liner, alone or in combination with other elements, may form the elongate body, may be a distal portion of the catheter. The elongate body defines at least one lumen through which a medical device (e.g., a catheter, guidewire, filter, stent delivery system, and the like), therapeutic agent, or other element can be introduced into vasculature or other tissue sites of a patient. The inner liner may define an entry port into the lumen. At least a portion of the elongate member of the push assembly may extend proximal of the outer jacket and the inner liner. In examples in which the catheter is part of an intravascular catheter system and is used in conjunction with an outer catheter, the elongate body of the catheter may be used to effectively

extend the reach of the outer catheter. For example, the elongate body of the catheter may be fully or partially pushed through a lumen of the outer catheter until the entire or part of the elongate body extends past a distal end of the outer catheter, while the push assembly remains fully or partially within the lumen of the outer catheter. The push assembly has a lower profile than the elongate body, and, as a result, may occupy less space within the outer catheter lumen than the elongate body of the catheter. Thus, the push assembly may both facilitate pushability of the catheter through the outer catheter and/or through vasculature of a patient, while still enabling relatively large medical devices to be introduced through the outer catheter lumen to reach the lumen of the catheter.

[0130] In some examples, the catheter described herein may also help delivery to or past a diseased region or the body. For example, a diseased region may include heavy tortuosity and/or calcification and the catheter may be better suited for navigation through such heavy tortuosity and/or calcification than the outer catheter due to its flexibility and lower profile. In some examples, a clinician may push the catheter out of a distal end of the outer catheter upon the approach of the outer catheter to such a region that would be difficult or impossible for the outer catheter to extend through. In some examples, the catheter may be said to “telescope” out of the outer catheter when it is pushed out of a distal end of the outer catheter.

[0131] The elongate body, including the inner liner and outer jacket, may define a proximal end. Distal to the proximal end, a portion of the push assembly including the anchor member may be positioned between the inner liner and outer jacket. The anchor member may extend only partially around an outer perimeter of the inner liner. Proximal to the proximal end of the elongate body, a portion of the push assembly proximal to the portion including the anchor member may be positioned outside of the outer jacket.

[0132] In some examples, the anchor member may be configured to facilitate manufacture of a catheter. For example, the anchor may define a beveled distal edge to assist with placement of the anchor member, including insertion and advancement of the anchor member between the outer jacket and the inner liner. As another example, the anchor member may define a slot extending from a proximal end of the anchor member and towards a distal end of the anchor member. The slot may facilitate attachment of the elongate member to the anchor member as the slot may be configured such that a distal end of the elongate member may be positioned at least partially within the slot and may be welded to the anchor. The slot may be configured such that welding material may be placed between the anchor member and the elongate member, such as in a gap within the slot between the anchor member and the elongate member when the distal end of the elongate member is positioned at least partially within the slot, such that the welding material may not add to the profile of the push assembly.

[0133] In some examples, an inner surface and/or an outer surface of the anchor member may be a non-semicircular surface such as, for example, a surface defining a plurality of notches or waves and/or a textured and/or etched surface. Such a non-circular surface may aid in securing the anchor member between the inner liner and the outer jacket by providing greater surface area that may be bonded to the inner liner and/or outer jacket including, for example, by reflow of material of the inner liner and/or outer jacket.

[0134] In some examples, the catheter may include one or more radiopaque markers to facilitate visualization of the catheter during a medical procedure. The one or more radiopaque markers can be located, for example, on the anchor member, on the elongate member, or in any suitable place or combination of places, to assist with visualization and placement of the catheter, with respect to, for example, an outer catheter and/or a target tissue site. In some examples, the anchor is at least partially radiopaque and/or a radiopaque marker is positioned at or near the entry port into the elongate body of the catheter. This radiopaque marker placement may enable a clinician to relatively quickly ascertain the location of the entry port of the lumen of the catheter.

[0135] In some examples, the catheter may be configured to facilitate maneuverability. For

example, the outer jacket may vary in stiffness along its length, which may help aid maneuverability of the catheter within vasculature of a patient. As another example, a reinforcement member may be positioned between the inner liner and the outer jacket, may be distal to and/or abutting the anchor member, and may aid in the strength and/or maneuverability of the catheter within vasculature of a patient.

[0136] In some examples, the elongate member of the push assembly may taper in a distal direction to enable the distal portion of the elongate member to better approximate a profile of the anchor member. By tapering the elongate member instead of forming the entire elongate member to have the lower profile, the proximal portion of the elongate member may still have a size and strength sufficient for pushing the catheter within the vasculature and/or sufficient size for gripping by a user. In some of these examples, as well as some other examples, the elongate member may be a solid member having a round (e.g., circular) cross-section. That is, the elongate member may not define a central lumen or other opening in its cross-section.

[0137] In some examples, the catheter may facilitate differentiation from other devices used in conjunction with the catheter and/or between elements of the catheter. For example, a sleeve may surround at least a portion of the elongate member, such as a portion proximal to the anchor member. In some examples, the sleeve may be a different color than the elongate member, the elongate body, a guidewire, and/or other devices used with the catheter in order to help visually distinguish the sleeve. The sleeve can also include other features to help facilitate usage of the sleeve. For example, the sleeve may include one or more bands including one or more partial cuts extending partially through a radial thickness of the sleeve and/or one or more markers. In some examples, the sleeve may include a textured surface. In some examples, partial cuts and/or a textured surface may aid in tactile differentiation of the sleeve from other components. In some examples, one or more bands including one or more partial cuts and/or markers may aid in visual differentiation of the sleeve. Visual and/or tactile differentiation of the sleeve may enable the elongate member to be discerned from other elements including, for example, an outer catheter, a guidewire, or other delivery devices or components in use with the catheter described herein.

[0138] FIG. 1 is a conceptual side view of an example catheter **100**, which includes an elongate body **102**, a push assembly **108**, and a handle **101**. FIG. 2 is a conceptual cross-sectional view of a portion of catheter **100** of FIG. 1 and an outer catheter **110**. Catheter **100** defines a longitudinal axis X. Elongate body **102** includes an inner liner **104** and an outer jacket **106**. As shown in FIG. 1, elongate body **102** may define a proximal end **10** and a distal end **12**.

[0139] In some examples, catheter **100** may be part of an assembly that includes an outer catheter **110** defining a lumen **111**, through which catheter **100** may be introduced in order to access, for example, a distal target site within vasculature of a patient. Thus, at least a portion of outer catheter **110** may be configured to surround catheter **100**. Outer catheter **110** may further define distal opening **113** and, in some examples, at least a portion of catheter **100** may be configured to extend through distal opening **113** and distally of outer catheter **110**, as shown in FIG. 2. For example, catheter **100** may be configured to extend out of distal opening **113** of outer catheter **110** to extend through heavy tortuosity or calcification within a body vessel. Catheter **100** may have a smaller radial profile and may be more flexible than outer catheter **110** such that it may more easily navigate through heavy tortuosity or calcification within a body vessel than outer catheter **110**.

[0140] In some examples, an outer radial profile of elongate body **102** of catheter **100** may be similar in a radial shape and/or size of at least a distal portion of lumen **111** of outer catheter **110** such that catheter **100** may fit relatively snugly inside of outer catheter **110** when elongate body is at least partially within outer catheter **110**. This may help to define a relatively smooth transition between elongate body **102** and outer catheter **110** when only a portion of elongate body **102** extends distally of distal opening **113** of outer catheter **110** and another portion remains within lumen **111** of outer catheter **110** and/or when a proximal end of elongate body **102** abuts a distal end of outer catheter **110**. This relatively smooth transition and/or snug fit may provide certain

advantages. For example, fluids may be easier to deliver through the lumen **111** of outer catheter **110** and the lumen **105** of elongate body **102** without leakage. As an additional example, devices and/or other elements may be easier to advance from lumen **111** of outer catheter **110** to lumen **105** of elongate body **102** because the transition between lumen **111** and lumen **105** may be relatively smooth such that components being delivered may not get caught at a transition from lumen **111** to lumen **105**.

[0141] Although catheter **100** is shown as extending out distal opening **113** of outer catheter **100** such that proximal end **10** of elongate body **102** is distal to distal opening **113**, in some medical procedures, catheter **100** may be positioned relative to outer catheter **110** such that proximal end **10** of elongate body **102** is proximate to distal opening **113**. For example, entry port **109** of elongate body **102**, described in further detail below, may be positioned within lumen **111** of outer catheter **110**, such that an interventional medical device or another medical device can be introduced from lumen **111** of outer catheter **110** into lumen **105** of elongate body **102** without exiting lumen **111**.

[0142] In some examples, as shown in FIG. **1**, catheter **100** may include an atraumatic tip **14** to minimize adverse interactions with patient tissue during advancement of catheter **100** within a body vessel.

[0143] Elongate body **102** is configured to provide a delivery vessel on catheter **100** that may extend distally of outer catheter **110** to telescope out of a distal end of outer catheter **110** and effectively extend a reach of a catheter within vasculature of a patient and enable delivery of devices, agents, and/or any other suitable elements to target sites that may be difficult for outer catheter **110** to reach. In some examples, elongate body **102** may include an inner liner **104** and outer jacket **106** that may provide multiple layers between which push assembly **108** may be inserted to attach push assembly **108** to elongate body **102**. This may provide for a relatively strong attachment between push assembly **108** and elongate body **102**, as well as maintain relatively smooth outer and inner surfaces of elongate body **102** at the portion of elongate body **102** attached to push assembly **108**.

[0144] Inner liner **104** of elongate body **102** defines lumen **105** and outer jacket **106** defines lumen **107**. In some examples, at least a portion of inner liner **104** may be positioned within lumen **107** of outer jacket **106**. In some examples, inner liner **104** may extend within the full length of lumen **107** of outer jacket **106**. In other examples, however, inner liner **104** may terminate prior to a distal end of outer jacket **106** or may extend past a distal end of outer jacket **106**. Although elongate body **102** is shown as a tubular body in FIG. **1**, elongate body **102** may have any suitable configuration.

[0145] Inner liner **104**, alone or in combination with outer jacket **106**, may define entry port **109** into lumen **105**. Entry port **109** may extend from a proximal end **138** to a distal end **140** along a length of elongate body **102**. In some examples, entry port **109** may be angled from distal end **140** to proximal end **138** due to the tapered shape of the elongate body **102**. Entry port **109** may be formed by skiving at least part of portion **120** of elongate body **102**. In some examples, entry port **109** may have a length, measured from proximal end **138** to distal end **140** along longitudinal axis **X**, of about 2 centimeters (cm) to about 10 cm (e.g., 2 cm to 10 cm or nearly 2 cm to 10 cm, to the extent permitted by manufacturing tolerances), such as about 3.5 cm to about 4.5 cm or about 4 cm. It is believed that a tapered entry port **109** having a relatively longer length and being angled from distal end **140** to proximal end **138** may help contribute to smooth delivery of a medical device (e.g., an interventional medical device) into inner lumen **105** of elongate body **102** via entry port **109** by guiding the medical device into inner lumen **105**.

[0146] Push assembly **108** may be configured to enable a clinician to position elongate body **102** with respect to outer catheter **110** and/or with respect to patient vasculature. For example, a proximal portion of push assembly **108** may be configured to be gripped and moved by the clinician to position (e.g., advance distally or proximally, and/or rotate) elongate body **102** within vasculature of a patient. In some examples, push assembly **108** may be used to advance elongate body **102** with respect to outer catheter **110** to advance elongate body **102** within outer catheter **110**

and/or extend all or a portion of elongate body **102** distal of outer catheter **110** to access vasculature distal to outer catheter **110**. Push assembly **108** may include any suitable length. In some examples, a length of push assembly **108** may be approximately 100 cm to approximately 150 cm, such as about 125 cm, measured along longitudinal axis X and from a distal end of handle **101** to a distal end **128** of anchor or measured from a distal end of handle **101** to a distal end of elongated member **114**. In some examples, push assembly **108** includes an elongate member **114** and an anchor member **116**. For clarity, a portion of anchor member **116**, which is positioned behind inner liner **104** in the illustrated view, is shown in phantom. In some examples, elongate member **114** may include a distal end **118** and anchor member **116** may be positioned at distal end **118** of elongate member **114**. In some examples, push assembly **108** may not include any other anchor member at distal end **118** other than anchor member **116**.

[0147] In some examples, at least a portion of push assembly **108** is positioned between at least adjacent portions (e.g., radially adjacent portions) of inner liner **104** and outer jacket **106**. For example, at least a portion of push assembly **108** may be positioned radially inward of outer jacket **106** and radially outward of inner liner **104** such that the portion of push assembly **108** is between outer jacket **106** and inner liner **104**. In some examples, the portion of push assembly **108** between inner liner **104** and outer jacket **106** may have a length of approximately 4 cm. Positioning at least a portion of push assembly **108** between portions of inner liner **104** and outer jacket **106** may aid in mechanically connecting push assembly **108** and elongate body **102** in a manner that enables push assembly **108** to transmit pushing forces and, in some examples, rotational forces, to elongate body **102**. In addition, positioning at least a portion of push assembly **108** between inner liner **104** and outer jacket **106** may enable elongate body **102** to have relatively smooth inner and outer surfaces at the portion of elongate body **102** attached to push assembly **108**.

[0148] In some examples, elongate body **102** may include a tapered portion **120**. For example, portions of inner liner **104** and outer jacket **106**, as shown in FIG. 2, corresponding to tapered portion **120** of elongate body **102** may be tapered in a proximal direction. The tapering of elongate body **102** at tapered portion **120** may enable elongate body **102** to more easily be retracted into outer catheter **110**. For example, during or after use of catheter **100**, a clinician may desire to retract at least a portion of elongate body **102** within outer catheter **110** by retracting push assembly **108** proximally with respect to outer catheter **110**. Tapered portion **120** may allow for smoother entry of elongate body **102** into outer catheter **110**.

[0149] Additionally, the tapered shape of tapered portion **120** may be configured facilitate attachment of push assembly **108** to elongate body **102**. For example, the tapered shape may allow for anchor member **116** to support entry port **109** while also allowing a portion of elongate member **114** proximal to anchor member **116** to be positioned between inner liner **104** and outer jacket **106**, which may increase bond tensile strength between the push assembly **108** and the elongate body **102**. The bond tensile strength between push assembly **108** and elongate body **102** may decrease with a shorter length of elongate member **114** positioned between inner liner **104** and outer jacket **106**. Thus, if only anchor member **116** (and not elongate member **114**) was positioned between inner liner **104** and outer jacket **106**, then the bond tensile strength between push assembly **108** and elongate body **102** may decrease. The decreased bond tensile strength may adversely affect the ability for push assembly **108** to transfer pushing and/or rotational forces to elongate body **102** without compromising the mechanical connection between push assembly **108** and elongate body **102**.

[0150] Further, because a distal portion of elongate member **114** may be relatively flexible (compared to a more proximal portion of elongate member **114**), as described in further detail below, positioning the distal portion of elongate member **114** between inner liner **104** and outer jacket **106** may help prevent the junction of push assembly **108** and elongate body **102** from being undesirably stiff.

[0151] In some examples, distal to proximal end **10** of elongate body **102**, a portion of push

assembly **108** is positioned between adjacent portions of inner liner **104** and outer jacket **106**. Proximal to proximal end **10** of elongate body **102**, a portion of push assembly **108** is positioned outside of outer jacket **106** and inner liner **104**. The portion of push assembly **108** positioned between adjacent portions of inner liner **104** and outer jacket **106** may comprise anchor member **116**. The portion of push assembly **108** positioned outside of outer jacket **106** and inner liner **104** may be proximal to the portion positioned between adjacent portions of inner liner **104** and outer jacket **106**.

[0152] Anchor member **116** may have any suitable shape and size. In some examples, at least an outer surface of anchor member **116** may define a partial-ring shape as shown in further detail below with reference to FIGS. **6-9**. In other examples, however, anchor member **116** may define other shapes. The partial-ring shape of anchor member **116** may provide one or more advantages. For example, the partial-ring shape may provide support to inner liner **104** and outer jacket **106** to prevent collapse of proximal ends of inner liner **104** and outer jacket **106** and thus help maintain the open state of entry port **109** into lumen **105** defined by inner liner **104** such that other catheters or devices may be inserted into lumen **105**.

[0153] In some examples, and as described in further detail below with respect to FIG. **6**, anchor member **116** may have an inner perimeter that is less than the outer perimeter of inner liner **104** and anchor member **116** may extend only partially around an outer perimeter of inner liner **104**. For example, anchor member **116** may extend about 140 degrees to about 160 degrees around an outer perimeter of inner liner **104**. More particularly, in some examples, anchor member **116** may extend about 160 degrees around the outer perimeter of inner liner **104**. In some examples, anchor member **116** is radiopaque, and extending only partially about the outer perimeter of inner liner **104** may enable anchor member **116** to indicate a rotational orientation (e.g., rotational position about longitudinal axis X) of elongate body **102** (e.g., entry port **109**) within vasculature of a patient. This may enable a clinician to better position catheter **100** relative to outer catheter **110**.

[0154] In addition, extending only partially about the outer perimeter of inner liner **104** may enable anchor member **116** to be positioned within tapered portion **120** of elongate body **102**. This may enable anchor member **116** to be positioned at entry port **109** to indicate the location thereof, and may also enable anchor member **116** to provide structural support to tapered portions of the inner liner **104** and outer jacket **106**. A full-ring shape would not be able to be located within the tapered portion **120** of elongate body **102** but instead would need to be located distal to the tapered portion **120** and thus distal to the entry port **109** in order to fit between inner liner **104** and outer jacket **106** without being exposed and would thus not be able to include a marker to indicate a location of the entry port **109**.

[0155] In some examples, however, as shown in FIG. **2**, a proximal end of anchor member **116** is positioned proximate to the distal end **140** of entry port **109**. For example, a proximal end of anchor member **116** may be aligned with distal end **140** of entry port **109**, such that anchor member **116** is fully positioned within the portion of elongate body **102** defining a circular outer perimeter in cross-section. As another example, a proximal end of anchor member **116** may not be exactly aligned with distal end **140** of entry port **109**, but within 4 millimeters (mm), such as within 2 mm or less, of distal end **140** of entry port **109** in a proximal or a distal direction. In these examples, a substantial length of that anchor member **116** is positioned within the portion of elongate body **102** defining a circular outer perimeter in cross-section.

[0156] This partial-ring shape of anchor member **116** may also be advantageous over a full-ring shape because it may be less likely to cause inner liner **104** to bunch during insertion of anchor member **116** between outer jacket **106** and inner liner **104** because anchor member **116** does not extend fully about an outer perimeter of inner liner **104**.

[0157] In some examples anchor member **116** may define a beveled distal edge **124**. Beveled distal edge **124** may allow anchor member **116** to more easily be inserted and advanced between inner liner **104** and outer jacket **106** than examples in which an anchor member has a straight edge. For

example, beveled distal edge **124** may enable anchor member **116** to be more easily inserted between inner liner **104** and outer jacket **106** by providing a narrow profile of anchor member **116** at distal end **128**, which leads anchor member **116** into the space between inner liner **104** and outer jacket **106**. Additionally, beveled distal edge **124** may provide a smooth distal profile of anchor member **116** that enables less resistance to advancement of anchor member **116** between and with respect to inner liner **104** and outer jacket **106** than a profile including a straight edge and/or sharp corners which may be more likely to catch on inner liner **104** and/or outer jacket **106**.

[0158] Inner liner **104** may be formed from any suitable material, such as, but not limited to polytetrafluorethylene (PTFE). In some examples, outer jacket **106** may comprise one or more polymers. In some examples, outer jacket **106** may have a hydrophilic coating. For example, the hydrophilic coating may be positioned over the entire outer surface of outer jacket **106** or only along a portion of outer jacket, such as only along a distal-most portion of outer jacket **106**. In some examples, a hydrophilic coating is positioned over the distal-most approximately 15 cm to approximately 25 cm of outer jacket **106** (e.g., the distal-most 15 cm to 25 cm to the extent permitted by manufacturing tolerances), such as the distal-most approximately 20 cm to approximately 22 cm of outer jacket **106**, or the distal-most approximately 21 cm of outer jacket **106**, the distances being measured from distal end of outer jacket **106**, which may correspond to distal end **12** of elongate body **102** in some examples.

[0159] In some examples, outer jacket **106** may include multiple sections having different stiffnesses. For example, outer jacket **106** may include a proximal section, corresponding with portion **136** of catheter **100**, and a distal section, corresponding with portion **129** of catheter **100** (shown in FIG. 1), that is distal to the proximal section. In some examples, the proximal section may be approximately 1 cm to approximately 4 cm long, such as approximately 2.5 cm long or approximately 1.25 cm long. In some examples, the distal section may be approximately 15 cm to approximately 27 cm long, such as approximately 24 cm long to approximately 26 cm long, or approximately 25 cm long. The lengths may be measured along longitudinal axis X.

[0160] The distal section of outer jacket **106** may have a different stiffness than the proximal section. For example, the distal section may have a stiffness that is greater than a stiffness of the proximal section. In other examples, the distal section may have a stiffness that is less than the proximal section. Outer jacket **106** having a more stiff proximal section (relative to a distal outer jacket section) may help maintain the integrity of the proximal portion of inner lumen **105** of elongate body **102**, which may aid in introduction of medical devices into lumen **105** from entry port **109** without adversely impact the navigability of catheter **100** through vasculature of a patient. For example, outer jacket **106** having a more stiff proximal section may help distal end **140** of entry port **109** and a proximal-most portion of elongate body **102** resist deformation to help maintain luminal integrity.

[0161] Outer jacket **106** may include any suitable number of sections having any suitable stiffnesses according to particular needs. In some examples, sections of outer jacket **106** may include different types of polymers, with a stiffer section comprising a stiffer polymer than a more flexible section comprising a softer polymer. In some examples, outer jacket **106** having multiple sections with different stiffnesses may provide improved functionality of outer jacket **106** including, for example, improved maneuverability of outer jacket **106** through the vasculature. For example, the distal section may have a stiffness that is less than a stiffness of the proximal section, which may allow the distal section improved flexibility for navigation through the vasculature.

[0162] In some examples, catheter **100** may further include a reinforcement member **126** positioned between a portion of inner liner **104** and a portion of outer jacket **106**. For clarity, a portion of reinforcement member **126**, which is positioned behind inner liner **104** in the illustrated view, is shown in phantom. Reinforcement member **126** may be any suitable structure configured to provide structural support to elongate body **102** and, in some examples, increase the structural integrity of elongate body **102**. For example, reinforcement member **126** may comprise a metal

coil, a metal braid, or a combination thereof. In some examples, a distal end **128** of anchor member **116** may be positioned proximal to and spaced from reinforcement member **126**, such that there is a gap between distal end **128** of anchor member **116** and a proximal end **130** of reinforcement member **126**. Example gaps include, for example, gaps less than or equal to 4 mm, such as about 2 mm or less than 2 mm, measured along longitudinal axis X. In other examples, anchor member **116** may contact (e.g., abut) reinforcement member **126**, e.g., distal end **128** of anchor member **116** may contact proximal end **130** of reinforcement member **126**. In yet other examples, anchor member **116** and reinforcement member **126** may overlap in the longitudinal direction, e.g., by a length of about 2 mm or less, such as about 1 mm or less.

[0163] Anchor member **116** at distal end **118** of elongate member **114** may increase a surface area of a distal portion of push assembly **108** relative to examples of push assemblies including only elongate member **114** without anchor member **116**, which may provide certain advantages. For example, the increased surface area at the distal portion of push assembly **108** provided by anchor member **116** may improve tensile strength of catheter **100** by strengthening the bond between push assembly **108** and elongate body **102**. Additionally, the increased surface area at the distal portion of push assembly **108** provided by anchor member **116** may help prevent protrusion of elongate member **114** through outer jacket **106** when elongate member **114** is under compression, i.e., when a pushing force is applied to a proximal portion of elongate member **114** as catheter **100** is advanced through vasculature of a patient. For example, in examples without anchor member **116**, distal end **118** of elongate member **114** may pierce outer jacket **106** due to the relatively small surface area of distal end **118** of elongate member **114**. Anchor member **116**, however, helps distribute the pushing force and minimize any pressure points at the distal end of push assembly **108**. Additionally, anchor member **116** may help avoid bending of distal end **118** of elongate member **114** under outer jacket **106** by providing reinforcement to distal end **118** of elongate member **114**.

[0164] FIGS. 3, 4, and 5 are conceptual cross-sectional views of an example elongate member **114** of push assembly **108** of catheter **100** of FIGS. 1 and 2 taken along lines 3-3, 4-4, and 5-5, respectively, in FIG. 2. Although lines 3-3, 4-4, and 5-5 are shown as intersecting multiple elements of catheter **100** in FIG. 1, for clarity, FIGS. 3, 4, and 5 show only the cross-section of elongate member **114**. As shown, elongate member **114** may taper in a distal direction. For example, in some examples and as shown in the illustrated example, a greatest cross-sectional dimension of elongate member **114** along line 5-5 may be smaller than a greatest cross-sectional dimension of elongate member **114** along line 3-3 and a greatest cross-sectional dimension of elongate member **114** along line 4-4. In some examples and as shown in the illustrated example, a greatest cross-sectional dimension of elongate member **114** along line 4-4 may be smaller than a greatest cross-sectional dimension of elongate member **114** along line 3-3. A transition between the cross-sections illustrated in FIGS. 3, 4, and 5 may be stepwise, defined by a discrete tapered section, or defined by a substantially constant tapered section.

[0165] In some examples, a cross-section of a proximal portion of elongate member **114**, such as the cross-section along line 3-3, may be round (e.g., circular). In some examples, this proximal portion of elongate member **114** having the round cross-section may include a proximal-most portion of elongate member **114** including a proximal end of elongate member **114**. In addition, in some examples, the proximal portion of elongate member **114**, the configuration of which may be represented by the cross-section along line 3-3, may be both round in cross-section and solid (e.g., not hollow or defining any lumens). Elongate member **114** having a proximal portion that is solid and round in cross-section may exhibit a better push force transmission along catheter **110**, e.g., relative to an elongate body that has a proximal portion that is a hollow in cross-section and/or non-round (e.g., rectangular) in cross-section.

[0166] In some examples, a greatest cross-sectional dimension of the proximal portion of elongate member **114**, e.g., as shown at line 3-3, is approximately 0.3 mm to approximately 1 mm, such as

approximately 0.4 mm to approximately 0.5 mm. However, other cross-sectional dimensions of elongate member **114** may be used in other examples.

[0167] In some examples, as in the illustrated example, a portion of elongate member **114** having a circular cross section may be proximal to a portion of elongate member **114** having a D-shaped cross-section. The portions of elongate member **114** having the D-shaped cross-sections may define a smaller profile than the proximal portion of elongate member **114** defining the round (e.g., circular) cross-section, such that the portions of elongate member **114** defining the D-shaped cross-sections may define the “tapered” portions of elongate member **114**. For example, a cross-section of an intermediate and/or a distal portion of elongate member **114**, such as the cross-section along line **4-4** or line **5-5**, may be D-shaped. In these examples, one half of elongate member **114** in cross-section may be substantially flat (e.g., planar to extent permitted by manufacturing tolerances) and the other longitudinal half of elongate member **114** in cross-section may be round (e.g., semi-circular).

[0168] In examples in which a distal portion of elongate member **114** tapers in a distal direction, a first section of the distal portion may define a first D-shaped cross section having a first cross-sectional area, e.g., as shown in FIG. **4**, and a second section of the distal portion distal to the first section may define a second D-shaped cross section having a second cross-sectional area, where the second cross-sectional area is less than the first cross-sectional area.

[0169] The difference in cross-sectional area may be due to, for example, a profile height of elongate member **114** in the first and second sections of the distal portion. In some examples, a D-shaped cross-section along line **4-4** may include profile height (e.g., from the flat surface of the “D” to the crest of the curved surface of the “D”) of approximately 0.1 mm to about 0.5 mm, such as approximately 0.2 mm to approximately 0.3 mm. In some examples, a D-shaped cross-section along line **5-5** is less than the profile height along line **4-4**, and may include profile height of approximately 0.05 mm and 0.2 mm. Other profile heights may be used in other examples and may depend on various factors, such as a size of lumen **105** or anchor member **116**. The profile height at the distal-most section of the distal portion of elongate member **114** may be selected such that when elongate member **114** is mechanically connected to anchor member **116**, elongate member **114** does not protrude from anchor member **116** in the cross-sectional dimension (orthogonal to longitudinal axis X) or protrudes a relatively minimal amount from anchor member **116** to reduce occupying space that limits the cross-sectional size of lumen **105**.

[0170] In some examples, a length of a proximal portion elongate member **114** having a circular cross section as illustrated in FIG. **3** may be approximately 100 cm to approximately 130 cm, such as approximately 110 cm to approximately 120 cm, or approximately 115 cm or approximately 117.5 cm. In some examples, the tapered portion of elongate member **114** adjacent to the proximal portion and extending to a distal end of elongate member **114** may have a length between approximately 2 cm to approximately 20 cm, such as approximately 10 cm.

[0171] In some examples, a length of elongate member **114** having a cross section substantially as illustrated along line **4-4** may be between approximately 20 mm to approximately 60 mm, such as approximately 40 mm. The cross-section along line **4-4** may be selected to enable elongate member **114** to be positioned between at least adjacent portions of inner liner **104** and outer jacket **106** and provide structural support to entry port **109**.

[0172] In addition, in some examples (which may be combined with the foregoing dimensions), a length of elongate member **114** having a cross-section substantially as illustrated along line **5-5** may be between approximately 5 mm to approximately 15 mm, such as approximately 10 mm. The cross-section along line **5-5** may be selected to enable elongate member **114** to be positioned between at least adjacent portions of inner liner **104** and outer jacket **106** without obstructing inner lumen **105** of elongate body **102**. In some examples, the distal-most section of elongate member **114** including a distal end of elongate member **114**, e.g., represented by the cross-section shown in FIG. **5**, may be selected to enable the distal portion of elongate member **114** to be flexible enough

to be moved out of the way of a medical device that is being introduced into lumen **105** of elongated body **102** via entry port **109**. As the medical device is pushed into lumen **105**, elongate member **114** may inadvertently wrap around the medical device due to the manner in which it extends through outer catheter **110**. This can be referred to as “wire wrap.” The relatively flexible distal portion of elongate member **114** may enable the medical device to push past any wrapped sections of elongate member **114** and avoid adverse impacts to medical device delivery attributable to wire wrap.

[0173] In some examples, the cross-section along line 5-5 may be selected to substantially match a thickness of anchor member **116**. This provide a smoother profile at the juncture of elongate member **114** and anchor member **116**, which may result in a smoother profile of entry port **109** and lumen **105**.

[0174] In some examples, a cross-section of elongate member **114** may be flat or substantially flat on one side (such as D-shaped) or on both sides at a portion that is distal to a portion having a circular cross section. A cross-section of elongate member **114** may have any suitable size and/or shape according to particular needs. In addition, elongate member **114** may be tapered using any suitable technique. In some examples, the tapered cross-section of elongate member **114** may be defined by an abrasive processing, such as grinding, sanding, or grit blasting. In some examples, the abrasive processing to form the taper of elongate member **114** may form at least one rough surface on elongate member. The at least one rough surface may increase the surface area of elongate member **114**. The increased surface area may improve adhesion of a polymeric material, such as PTFE, and decrease delamination of the polymeric material, for example, during use of catheter **100**. The polymeric material may be, for example, the material used to form inner liner **104** and/or outer jacket **106**.

[0175] Elongate member **114** being tapered in a distal direction may provide particular advantages in some cases. For example, a proximal portion of elongate member **114** having a solid round profile may have greater cross sectional area and mechanical integrity compared to an elongate member having a different profile, such as a rectangular profile or a hollow profile. In this way, the proximal portion of elongate member **114** may better resist kinking in response to a push force better than an elongate member having a different profile, such as a rectangular cross-section and/or a hollow cross-section. For example, a solid 0.45 mm diameter round profile stainless steel elongate member **114** may transfer at least **400** gram-force.

[0176] Additionally, or alternatively, due to its D-shaped tapered portions (e.g., along lines **4-4** and **5-5**), elongate member **114** may have greater flexibility at a distal portion (relative to non-D-shaped profiles, such as circular profiles), which may help facilitate navigability of catheter **100** through vasculature of a patient. The D-shaped profile may also enable elongate member **114** to have a similar profile to anchor member **116** at a portion of elongate member **114** bonded to anchor member **116** which may allow push assembly **108** to maintain a smoother profile at the juncture of elongate member **114** and anchor member **116**. This smoother profile at the juncture of elongate member **114** and anchor member **116** may result in a smoother profile of entry port **109** and lumen **105**, which may facilitate easier introduction of medical devices into lumen **105** via entry port **109**.

[0177] FIG. **6** is a conceptual cross-sectional view of catheter **100** of FIGS. **1** and **2** taken along line **6-6** in FIG. **2**. FIG. **6** illustrates a cross-section of inner liner **104**, outer jacket **106**, and elongate member **114** within the section of catheter **100** defining entry port **109**. Inner liner **104** and outer jacket **106** do not define circular cross-sections in the portion of catheter **100** shown in FIG. **6** because they are configured (e.g., by skiving) to define entry port **109**. In addition, anchor body **116** is not present in the portion of catheter **100** shown in FIG. **6**.

[0178] FIGS. **7A** and **7B** are conceptual cross-sectional views of examples of catheter **100** of FIGS. **1** and **2** taken along line **7-7** in FIG. **2**, and FIGS. **8A** and **8B** are conceptual cross-sectional views of examples of catheter **100** of FIGS. **1** and **2** taken along line **8-8** in FIG. **2**. FIGS. **7A** and **8A** are conceptual cross-sectional views of catheter **100** during assembly of elongate body **102**, after

anchor member **116** has been inserted and advanced between inner liner **104** and outer jacket **106**. FIGS. **7B** and **8B** are a conceptual cross-sectional view of catheter **100** after assembly of catheter **100**, after anchor member **116** has been inserted and advanced between inner liner **104** and outer jacket **106**, as shown in FIGS. **7A** and **8A**, respectively, and after heat has been applied to inner liner **104** and outer jacket **106** to reflow material of inner liner **104** and outer jacket **106** around anchor member **116**.

[0179] As shown in FIGS. **7A-8B**, anchor member **116** may be positioned between outer jacket **106** and inner liner **104** such that anchor member **116** is positioned within outer jacket **106** and at least partially around an outer perimeter of inner liner **104**. In some examples, anchor member **116** may extend about 140 degrees to about 160 degrees around the outer perimeter of inner liner **104**. For example, a widest portion of anchor member **116**, as shown in FIGS. **7A** and **7B** may extend about 140 degrees to about 160 degrees around the widest portion of inner liner **104**. For example, in some examples, anchor member **116** may extend about 160 degrees around the outer perimeter of inner liner **104**.

[0180] Anchor member **116** defines an inner surface **142** and an outer surface **144**, and, in some examples, one or more of inner surface **142** and outer surface **144** may define a substantially semicircular surface but may, in some examples, include surface irregularities (e.g., waves, bumps, or other texturing). Anchor member **116** may have a thickness $t_{sub}AM$ measured in a direction perpendicular to longitudinal axis **X** of catheter **100**. In some examples, thickness $t_{sub}AM$ may be about 50 micrometers thick to about 100 micrometers thick, such as about 76.2 micrometers thick or any other size suitable to fit between inner liner **104** and outer jacket **106** while also having suitable strength to secure push assembly **108** to elongate body **102**. As shown in FIG. **6**, welding material **146** may join elongate member **114** to anchor member **116**, as describe in further detail below with respect to FIG. **15**.

[0181] As shown in FIG. **7B** and **8B**, in some examples, heat may be applied to inner liner **104** and/or outer jacket **106** to reflow material from inner liner **104** and/or outer jacket **106** around anchor member **116** to bond anchor member **116** between inner liner **104** and outer jacket **106**. Although FIG. **7B** shows reflow of material from both inner liner **104** and outer jacket **106**, in some examples, heat may be applied to only one of inner liner **104** and outer jacket **106** and/or material from only one of inner liner **104** and outer jacket **106** may be reflowed around anchor member **116**. Alternatively, or in addition to reflow, other methods may be used to bond anchor member **116** between inner liner **104** and outer jacket **106**. For example, adhesives may be used. Bonding inner liner **104** and/or outer jacket **106** to anchor member **116** may improve the bond between elongate body **102** and push assembly **108** over methods wherein elongate member **114** is bonded directly to inner liner **104** and/or outer jacket **106**, and may thus improve tensile strength, by providing greater surface area for bonding.

[0182] FIG. **9** is a conceptual perspective view of anchor member **116** of FIGS. **1**, **2**, **6**, **7A**, **7B**, **8A**, and **8B**. FIGS. **10A** and **10B** are conceptual perspective views of push assembly **108** of FIGS. **1**, **2**, and **6**. As shown in FIGS. **9**, **10A**, and **10B**, anchor member **116** may define a partial-ring shape. As shown in FIGS. **10A** and **10B**, anchor member **116** may be secured to elongate member **114** to form push assembly **108**. For example, anchor member **116** may be welded to distal end **118** of elongate member **114** as described in further detail below with reference to FIGS. **14** and **15**. As another example, anchor member **116** may be adhered or otherwise mechanically connected to distal end **118** of elongate member **114**.

[0183] In some examples, anchor member **116** may be formed of a radiopaque material such that anchor member **116** may serve as a radiopaque marker to indicate a location of entry port **109** to lumen **105** of elongate body **102**. In other cases, a band may be added to anchor member **116** to serve as a marker. As discussed above, because anchor member **116** is not circular in cross-section, a radiopaque anchor member **116** may help indicate a rotational orientation of catheter **100** (e.g., a rotational orientation of entry port **109**) within vasculature of a patient. In contrast, an anchor

member having a circular cross-section would not indicate the rotational position of entry port **109** of catheter **100**, as the rotational position of the anchor member within a medical image would not appear to change based on the rotational orientation of entry port **109** about longitudinal axis X. [0184] FIG. **11** is a conceptual perspective view of an example push assembly **152**, such as push assembly **108** of FIGS. **1**, **2**, **10A** and **10B**, further including a radiopaque band **154**. [0185] Push assembly **152** may include anchor member **156** and elongate member **158**. In some examples, anchor member **156** may include one or more radiopaque bands **154** to facilitate visualization of anchor member **156**.

[0186] Band **154** may be formed from a radiopaque material and can include, for example, a radiopaque marker band (e.g., one or more partial rings) attached to anchor member **158**, e.g., by an adhesive or weld. In some examples, band **154** may include any suitable radiopaque material. In addition to, or instead of a radiopaque marker band, band **154** may include one or more grooves protruding from an outer surface **160** of anchor member **158** or defined by and recessed within outer surface **160** of anchor member **158**. Although band **154** is shown along an outer diameter of anchor member **158**, band **154** may include grooves including, for example, a series of tangential arcs along an inner diameter of anchor member **158** and may be formed from a radiopaque material, or may be filled with a radiopaque material in the case of recessed grooves, which may be visible within the patient with the aid of suitable medical imaging equipment. Band **154** may help a clinician determine an orientation and/or location of anchor member **158** and/or any suitable component of the device described herein.

[0187] FIGS. **12** and **13** are conceptual cross-sectional views of example anchor members, such as anchor member **116** of FIGS. **1** and **2**, with an inner and/or outer surface defining a non-semicircular surface. For example, as shown in FIG. **12**, anchor member **172** may define inner surface **174** and outer surface **176**, and one or more of inner surface **174** and outer surface **176** may define a non-semicircular surface. For example, outer surface **176** may define a plurality of notches **178a-178n**. As another example, as shown in FIG. **13**, anchor member **182** may define inner surface **184** and outer surface **186** and one or more of inner surface **184** and outer surface **186** may define a plurality of waves **188a-188n**. In some examples, as in FIG. **12**, both inner surface **174** and outer surface **176** may define a non-semicircular surface. In other examples, as in FIG. **12**, only one of inner surface **174** and outer surface **176** may define a substantially non-semicircular surface.

[0188] Although FIGS. **12** and **13** show particular example anchor members **172** and **182** with non-semicircular and substantially semicircular surfaces, any suitable surfaces may be used according to particular needs. For example, an anchor member may define inner and outer surfaces both defining a plurality of waves. As another example, only one of an inner surface and an outer surface of an example anchor member may define a plurality of notches. In some examples, an anchor member may include one of an inner surface and an outer surface defining a plurality of notches and another of the inner surface and outer surface defining a plurality of waves. An anchor member may have any suitable combination of inner and outer surfaces according to particular needs.

[0189] In some examples, an anchor member with inner and/or outer surfaces defining non-semicircular surfaces may provide particular advantages. For example, such non-semicircular advantages may increase surface area of the surface(s) and thus improve bond between the anchor member and the inner liner, and/or the outer jacket. For example, reflow of inner liner and/or outer jacket material may bond with a greater surface area of the anchor member and may thus improve the bond between the inner liner and/or outer jacket and the anchor member.

[0190] Anchor member **116** may be mechanically connected to elongate member **114** using any suitable technique, such as, but not limited to, welding, an adhesive, or mechanical fixation mechanism, such as a strap, or the like. FIG. **14** is a conceptual side view of an example of anchor member **116** of push assembly **108** of FIGS. **2**, **10A**, and **10B** and a distal portion of elongate member **114** of the push assembly **108** of FIGS. **2**, **10A**, and **10B**, before anchor member **116** and

elongate member **114** are mechanically connected together to form push assembly **108**. FIG. **15** is a conceptual side view of push assembly **108** of FIG. **14** after anchor member **116** and elongate member **114** are mechanically connected together to form push assembly **108**.

[0191] As shown in FIG. **14**, anchor member **116** may extend from a proximal end **192** to a distal end **128**. Length $L_{sub.AM}$ of anchor member **116** may be measured along axis X (where orthogonal x-y axes are shown in FIGS. **14** and **15** for ease of description only) from proximal end **192** to distal end **128** of anchor member **116**. In some examples, length $L_{sub.AM}$ of anchor member **116** is about 2 mm to about 5 mm, such as about 3 mm. Anchor **116** may have other lengths in other examples. Anchor member **116** may define a slot **194** extending from proximal end **192** towards distal end **128**. In some examples, distal end **128** of elongate member **114** may be positioned at least partially within slot **194**. In some examples, slot **194** has a length $L_{sub.S}$ from about 25 percent to about 75 percent of a length $L_{sub.AM}$ of anchor member **116**. In some examples, length $L_{sub.S}$ of slot **194** may be about 40 percent to about 60 percent of length $L_{sub.AM}$ of anchor member **116**. In some examples, anchor member **116** may be welded to elongate member **114**. For example, as shown in FIG. **15**, welding material **146** may be placed within slot **194** and between anchor member **116** and elongate member **114**. In some examples, slot **194** may extend through the entire thickness $t_{sub.AM}$ of anchor member **116**. In other examples, slot **194** may extend only partially through thickness $t_{sub.AM}$ of anchor member **116**. Slot **194** may extend a thickness sufficient to receive distal end **118** of elongate member **114** and welding material **146**.

[0192] Anchor member **116** defining a slot **194** within which distal end **118** of elongate member **114** and welding material **146** may be placed in order to bond distal end **118** of elongate member **114** to anchor member **116** may provide one or more advantages. For example, slot **194** may increase the surface area of the portions of elongate member **114** and anchor member **116** that are mechanically connected to each other, which may increase the strength of the mechanical connection between elongate member **114** and anchor member **116**. As another example, slot **194** may provide for a lower radial profile of push assembly **108** compared to examples in which an anchor member does not include a slot or in which a slot is not wide enough for both distal end **118** of elongate member **114** and welding material **146** because distal end **118** and/or welding material **146** need not increase a radial profile of elongate body **102** and/or push assembly **108** by extending radially, inwardly or outwardly, from anchor member **116**. This may also provide improved assembly of catheter **100** by providing a less bulky push assembly **108** that may be more easily inserted and advanced between inner liner **104** and outer jacket **106**.

[0193] FIG. **16** is a conceptual perspective view of a portion of an example elongate member **114** of FIGS. **1**, **2**, **10A**, **10B**, and **11**. In some examples, a sleeve **202** may surround at least a portion of elongate member **114**. In some examples, a sleeve **202** may surround at least a portion of elongate member **114** external to lumen **105** defined by elongate body. Sleeve **202** may include one or more layers of material configured to surround at least a portion of elongate member **114** and to distinguish elongate member **114** from other medical devices and/or to enable easier grip of elongate member **114**.

[0194] In some examples, sleeve **202** may be textured such that it defines at least one textured surface, which may help a clinician grip sleeve **202** and/or sleeve **202** grip elongate member **114**. For example, in some examples, sleeve **202** may be etched such that it defines at least one etched surface. As another example, sleeve **202** may define ridges, grooves, or the like on the surface facing outward (the surface that a clinician would grip when engaging sleeve **202**), and/or on the surface facing elongate member **114**.

[0195] In addition to, or instead of, aiding a clinician's handling of elongate member **114**, in some examples, sleeve **202** may provide one or more visible indicia that help differentiate elongate member **114** from other medical devices. For example, sleeve **202** may be a different color than at least one of elongate member **114**, inner liner **104**, and outer jacket **106**. In addition, or instead,

sleeve **202** may include one or more visible and/or tactile bands **204**. In some examples, bands **204** may include a partial cut around a perimeter of sleeve **202**. In some examples, the partial cut may extend only partially through a radial thickness $t_{sub.S}$ of sleeve **202**. In some examples, the partial cut may extend 360 degrees around a perimeter of sleeve **202**. Bands **204** may include a double-stripe mark. Bands **204** may include a marker with any suitable visual characteristics, such as, but not limited to, a particular color(s), visible pattern(s), and/or texture(s).

[0196] Sleeve **202** may provide particular advantages. For example, sleeve **202** including a textured surface, having a distinct color, having bands **204** and/or or other visually distinct indicium or indicia may help to tactilely and/or visually distinguish elongate member **114** from other components including, for example, a guidewire or other catheters or devices used with catheter **100** such that a user may more easily distinguish it from other components. For example, without sleeve **202**, elongate member **114** may look and/or feel like a guidewire and may be difficult to identify as being a part of push assembly **108**.

[0197] FIG. **17** is a flowchart illustrating an example method including the various stages of assembly of example catheter **100** shown in FIGS. **1** and **2**. In accordance with this method of assembly, anchor member **116** of push assembly **108** is inserted between inner liner **104** and outer jacket **106** of catheter **100** such that, after insertion, anchor member **116** extends only partially around an outer perimeter of inner liner **104** (**212**). In some examples, anchor member **116** is advanced between inner liner **104** and outer jacket **106** in a distal direction (**214**). In some examples, anchor member **116** may be advanced between inner liner **104** and outer jacket **106** in a distal direction until proximal end **192** of anchor member **116** is aligned with proximal end **138** of entry port **109**. In other examples, anchor member **116** may be advanced between inner liner **104** and outer jacket **106** in a distal direction until distal end **128** of anchor member **116** is aligned with distal end **140** of entry port **109**. Anchor member **116** may be advanced to any suitable position between inner liner **104** and outer jacket **106** according to particular needs.

[0198] After insertion and advancement of anchor member **116**, distal to proximal end **10** of elongate body **102**, a portion of push assembly **108**, including anchor member **116**, is positioned between adjacent portions inner liner **104** and outer jacket **106** and, proximal end **10** of elongate body **102**, a portion of push assembly **108** is positioned outside of outer jacket **106** and inner liner **104**.

[0199] In some examples, heat may be applied to inner liner **104** and/or outer jacket **106** to reflow material around anchor member **116** (**214**).

[0200] In some examples, a method of assembly may further include abrasive processing of elongate member **114** to form a taper, such as the D-shaped taper illustrated in FIGS. **4** and **5**. The abrasive processing may include, for example, grinding, sanding, or grit blasting at least a portion of elongate member **114** to remove material.

[0201] In some examples, a method of assembly may further include coupling anchor member **116** to elongate member **114**. For example, anchor member **116** may be coupled to elongate member **114** before insertion of anchor member **116** between inner liner **104** and outer jacket **106** of catheter **100**. In some examples, coupling anchor member **116** to elongate member **114** may include positioning distal end **118** of elongate member **114** at least partially within slot **194** of anchor member **116**. In some examples, coupling anchor member **116** to elongate member **114** may include welding anchor member **116** to elongate member **114**. In some examples, welding anchor member **116** to elongate member **114** may include placing welding material **146** within slot **194** and between anchor member **116** and elongate member **114**.

[0202] In some examples, the method may further include positioning reinforcement member **126** between at least a portion of inner liner **104** and at least a portion of outer jacket **106**. In some examples, the method may include positioning distal end **128** of anchor member **116** proximal to reinforcement member **126**. In some examples, the method may include positioning distal end **128** of anchor member **116** such that it abuts proximal end **130** of reinforcement member **126**. In some

examples, the method may include positioning sleeve 202 around at least a portion of elongate member 114.

[0203] Various examples have been described. These and other examples are within the scope of the following claims.

Claims

1. A catheter comprising: an elongate body comprising: an inner liner; and an outer jacket positioned radially outward of the inner liner, the inner liner and the outer jacket together defining an entry port into a lumen of the elongate body; and a push assembly comprising: an elongate member; and an anchor member positioned at a distal portion of the elongate member, a widest portion of the anchor member being wider than the distal portion of the elongate member, wherein the anchor member and a first portion of the elongate member are coextensive with the inner liner and the outer jacket, the anchor member having an inner perimeter that extends less than fully around an outer perimeter of the inner liner, and wherein a second portion of the elongate member is not coextensive with either of the outer jacket or the inner liner.
2. The catheter of claim 1, wherein the anchor member defines an inner surface and an outer surface, and wherein at least one of the inner surface or the outer surface defines a semicircular surface.
3. The catheter of claim 1, wherein the elongate member includes a first material, and wherein the anchor member includes a second material, the second material being different than the first material.
4. The catheter of claim 3, wherein the first material is stainless steel.
5. The catheter of claim 3, wherein the second material is a radiopaque material.
6. The catheter of claim 1, wherein the second portion of the elongate member is positioned proximal to the outer jacket and the inner liner.
7. The catheter of claim 1, wherein the outer jacket comprises a first outer jacket section and a second outer jacket section distal to the first outer jacket section, the first and second outer jacket sections having different stiffnesses, and wherein the inner liner comprises a first inner liner section and a second inner liner section distal to the first inner liner section, the first inner liner section being less flexible than the second inner liner section.
8. The catheter of claim 1, wherein the elongate member does not define any lumens.
9. The catheter of claim 1, wherein the anchor member defines a length of 2 mm to 5 mm.
10. The catheter of claim 1, wherein the entry port tapers between a distal end of the entry port and a proximal end of the entry port.
11. The catheter of claim 10, wherein a proximal end of the anchor member is within 4 mm of the distal end of the entry port.
12. A catheter comprising: an elongate body comprising: an inner liner; and an outer jacket positioned radially outward of the inner liner, the inner liner and the outer jacket together defining an entry port into a lumen of the elongate body; and a push assembly comprising: an elongate member that does not define any lumens; and an anchor member positioned at a distal portion of the elongate member, a widest portion of the anchor member being wider than the distal portion of the elongate member, wherein the anchor member and a first portion of the elongate member are coextensive with the inner liner and the outer jacket, and wherein a second portion of the elongate member is not coextensive with either of the outer jacket or the inner liner.
13. The catheter of claim 12, wherein the anchor member defines an inner surface and an outer surface, and wherein at least one of the inner surface or the outer surface defines a semicircular surface.
14. The catheter of claim 12, wherein the elongate member includes a first material, and wherein the anchor member includes a second material, the second material being different than the first

material.

15. The catheter of claim 12, wherein the second portion of the elongate member is positioned proximal to the outer jacket and the inner liner.

16. The catheter of claim 12, wherein the entry port tapers between a distal end of the entry port and a proximal end of the entry port.

17. The catheter of claim 16, wherein a proximal end of the anchor member is within **4** mm of the distal end of the entry port.

18. A catheter comprising: an elongate body comprising: an inner liner; and an outer jacket positioned radially outward of the inner liner, the inner liner and the outer jacket together defining an entry port into a lumen of the elongate body; and a push assembly comprising: an elongate member; and a radiopaque anchor member positioned at a distal portion of the elongate member, a widest portion of the radiopaque anchor member being wider than the distal portion of the elongate member, wherein the radiopaque anchor member and a first portion of the elongate member are coextensive with the inner liner and the outer jacket, the radiopaque anchor member having an inner perimeter that extends less than fully around an outer perimeter of the inner liner, and wherein a second portion of the elongate member is not coextensive with either of the outer jacket or the inner liner.

19. The catheter of claim 18, wherein the radiopaque anchor member defines an inner surface and an outer surface, and wherein at least one of the inner surface or the outer surface defines a semicircular surface.

20. The catheter of claim 18, wherein the elongate member does not define any lumens.
