



US 20250256166A1

(19) **United States**(12) **Patent Application Publication**
Woodward et al.(10) **Pub. No.: US 2025/0256166 A1**(43) **Pub. Date: Aug. 14, 2025**(54) **GOLF CLUB HEADS WITH HOSEL INSERTS
AND RELATED METHODS**(71) Applicant: **KARSTEN MANUFACTURING
CORPORATION**, Phoenix, AZ (US)(72) Inventors: **Alex G. Woodward**, Phoenix, AZ (US);
Jacob T. Clarke, Apex, NC (US); **Eric
J. Morales**, Laveen, AZ (US); **Ryan M.
Stokke**, Anthem, AZ (US); **Evan R.
Greer**, Peoria, AZ (US); **Eric V. Cole**,
Phoenix, AZ (US); **David S. Kultala**,
Phoenix, AZ (US)(73) Assignee: **Karsten Manufacturing Corporation**,
Phoenix, AZ (US)(21) Appl. No.: **19/169,946**(22) Filed: **Apr. 3, 2025****Related U.S. Application Data**


(63) Continuation of application No. 18/186,763, filed on Mar. 20, 2023, which is a continuation of application No. 17/304,836, filed on Jun. 25, 2021, now Pat. No. 11,607,590, which is a continuation-in-part of application No. 17/330,309, filed on May 25, 2021, now Pat. No. 12,070,660, which is a continuation of application No. 16/523,839, filed on Jul. 26, 2019, now Pat. No. 11,013,964, which is a continuation of application No. 15/831,515, filed on Dec. 5, 2017, now Pat. No. 10,398,946, which is a continuation of application No. 15/003,494, filed on Jan. 21, 2016, now Pat. No. 9,868,035, which is a continuation-in-part of application No. 14/282,786, filed on May 20, 2014, now Pat. No. 9,327,170, which is a continuation-in-part of application No. 13/795,653, filed on Mar. 12, 2013, now Pat. No. 9,168,426, which is a continuation-in-part of application No. 13/429,319, filed on Mar. 24, 2012, now Pat. No. 8,790,191, which is a continuation-in-part of application No. 13/468,663,



filed on May 10, 2012, now Pat. No. 8,926,447, which is a continuation-in-part of application No. 13/468,675, filed on May 10, 2012, now Pat. No. 8,932,147, which is a continuation-in-part of application No. 13/735,123, filed on Jan. 7, 2013, now Pat. No. 9,192,823, said application No. 13/468,663 is a continuation-in-part of application No. 13/429,319, filed on Mar. 24, 2012, now Pat. No. 8,790,191, said application No. 13/468,675 is a continuation-in-part of application No. 13/429,319, filed on Mar. 24, 2012, now Pat. No. 8,790,191, said application No. 13/735,123 is a continuation-in-part of application No. 13/468,663, filed on May 10, 2012, now Pat. No. 8,926,447, which is a continuation-in-part of application No. 13/468,675, filed on May 10, 2012, now Pat. No. 8,932,147, which is a continuation-in-part of application No. 13/468,677, filed on May 10, 2012, now Pat. No. 8,419,567, which is a continuation of application No. 13/429,319, filed on Mar. 24, 2012, now Pat. No. 8,790,191.


(60) Provisional application No. 62/107,240, filed on Jan. 23, 2015, provisional application No. 62/254,081, filed on Nov. 11, 2015, provisional application No. 61/590,232, filed on Jan. 24, 2012, provisional application No. 61/529,880, filed on Aug. 31, 2011.

Publication Classification(51) **Int. Cl.**
A63B 53/02 (2015.01)
A63B 53/04 (2015.01)
(52) **U.S. Cl.**
CPC **A63B 53/02** (2013.01); **A63B 53/0466**
(2013.01); **A63B 53/023** (2020.08); **Y10T**
29/49826 (2015.01)(57) **ABSTRACT**

Embodiments of golf coupling mechanisms are presented herein. Other examples and related methods are also disclosed herein.










Fig. 4




Fig. 5




Fig. 6





Fig. 8






Fig. 9




Fig. 11

Fig. 10




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16





Fig. 17

Fig. 18






Fig. 19




Fig. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 22A




FIG. 22B




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33A




FIG. 33B




FIG. 34




FIG. 35A




FIG. 35B




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40

GOLF CLUB HEADS WITH HOSEL INSERTS AND RELATED METHODS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This is a continuation of U.S. patent application Ser. No. 18/186,763 filed Mar. 20, 2023, which is a continuation of U.S. patent application Ser. No. 17/304,836, filed Jun. 25, 2021, now U.S. Pat. No. 11,607,590, which is a continuation-in-part of U.S. patent application Ser. No. 17/330,309, filed May 25, 2021, now U.S. Pat. No. 11,013,964, which is a continuation of U.S. patent application Ser. No. 16/523,839, filed on Jul. 26, 2019, now U.S. Pat. No. 11,013,964, which is a continuation of U.S. patent application Ser. No. 15/831,515, filed on Dec. 5, 2017, now U.S. Pat. No. 10,398,946, which is a continuation of U.S. patent application Ser. No. 15/003,494, filed on Jan. 21, 2016, now U.S. Pat. No. 9,868,035, which is a continuation in part of U.S. patent application Ser. No. 14/282,786, filed May 20, 2014 which is a continuation in part of: (i) U.S. patent application Ser. No. 13/795,653, filed on Mar. 12, 2013, now U.S. Pat. No. 9,327,170; (ii) U.S. patent application Ser. No. 13/429,319, filed on Mar. 24, 2012, now U.S. Pat. No. 8,790,191; (iii) U.S. patent application Ser. No. 13/468,663, filed on May 10, 2012, now U.S. Pat. No. 8,926,447; (iv) U.S. patent application Ser. No. 13/468,675, filed on May 10, 2012, now U.S. Pat. No. 8,932,147; and (v) U.S. patent application Ser. No. 13/735,123, filed on Jan. 7, 2013, now U.S. Pat. No. 9,192,823, all of which are fully incorporated herein by references.

[0002] U.S. patent application Ser. No. 15/003,494, filed Jan. 21, 2016 claims the benefit of U.S. Prov. Patent Application No. 62/107,240, filed Jan. 23, 2015, and U.S. Prov. Patent Application No. 62/254,081 filed Nov. 11, 2015.

[0003] U.S. patent application Ser. No. 13/429,319 claims the benefit of U.S. Provisional Patent Application No. 61/590,232, filed on Jan. 24, 2012, and of U.S. Provisional Patent Application No. 61/529,880, filed on Aug. 31, 2011.

[0004] U.S. patent application Ser. No. 13/468,663 and U.S. patent application Ser. No. 13/468,675 each are a continuation in part of U.S. patent application Ser. No. 13/429,319. U.S. patent application Ser. No. 13/468,677 is a continuation of U.S. patent application Ser. No. 13/429,319.

[0005] U.S. patent application Ser. No. 13/735,123 is a continuation in part of U.S. patent application Ser. No. 13/468,663, filed on May 10, 2012, U.S. patent application Ser. No. 13/468,675, filed on May 10, 2012, and U.S. patent application Ser. No. 13/468,677, filed on May 10, 2015.

[0006] U.S. patent application Ser. No. 13/468,677 is a continuation of U.S. patent application Ser. No. 13/429,319 filed Mar. 20, 2021, now U.S. Pat. No. 8,790,191.

[0007] U.S. Prov. Patent Application No. 62/107,240, U.S. Prov. Patent Application No. 62/254,081, U.S. patent application Ser. No. 14/282,786, U.S. patent application Ser. No. 13/795,653, U.S. patent application Ser. No. 13/429,319, U.S. patent application Ser. No. 13/468,663, U.S. patent application Ser. No. 13/468,675, U.S. patent application Ser. No. 13/735,123, U.S. patent application Ser. No. 13/468,677, U.S. Prov. Patent Application No. 61/590,232, and U.S. Prov. Patent Application No. 61/529,880 all of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

[0008] The present disclosure relates generally to sports equipment, and relates, more particularly, to golf coupling mechanisms and related methods.

BACKGROUND

[0009] Several sports, like golf, require equipment with features that can be selected or custom-fit to an individual's characteristics or preferences. For example, the recommended type of club shaft, type of club head, and/or the loft or lie angle of the club head may vary based on the individual's characteristics, such as skill, age or height. Once assembled, however, golf clubs normally have fixed, unchangeable coupling mechanisms between their golf club shafts and golf club heads. Accordingly, when determining suitable equipment for the individual, an unnecessarily large number of golf clubs with such fixed coupling mechanisms must be available to test different combinations of club shafts, club heads, loft angles, and/or lie angles. In addition, if the individual's characteristics or preferences were to change, his golf equipment would not be adjustable to account for such changes. Adjustable coupling mechanisms can be configured to provide such flexibility in changeably setting different features of golf clubs, but may introduce instabilities leading to lack of cohesion or concentrations of stress at the golf club head and golf club shaft coupling. Considering the above, further developments in golf coupling mechanisms and related methods will enhance utilities and adjustability features for golf clubs.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The present disclosure may be better understood from a reading of the following detailed description of examples of embodiments, taken in conjunction with the accompanying figures.

[0011] FIG. 1 illustrates a front perspective view of a golf club head with a golf coupling mechanism according to one example of the present disclosure.

[0012] FIG. 2 illustrates a top perspective view of the golf club head with the golf coupling mechanism of FIG. 1.

[0013] FIG. 3 illustrates a cross-sectional view of the golf club head along cross-sectional line III-III of FIG. 2, showing the golf coupling mechanism with a shaft sleeve inserted into a shaft receiver.

[0014] FIG. 4 illustrates a cross-sectional view of the golf club head and the golf coupling mechanism along cross-sectional line IV-IV of FIG. 2.

[0015] FIG. 5 illustrates a side view of the shaft sleeve decoupled from the golf club head.

[0016] FIG. 6 illustrates a cross sectional view of the shaft sleeve along cross-sectional line VI-VI of FIG. 5.

[0017] FIG. 7 illustrates a cross-sectional view of the shaft sleeve along cross-sectional line VII-VII of FIG. 5.

[0018] FIG. 8 illustrates a top view of the golf club head of FIG. 1, with the shaft sleeve removed therefrom, showing the shaft receiver from above.

[0019] FIG. 9 illustrates a side cross-sectional side view of the golf club head of FIG. 1 along cross-sectional line III-III of FIG. 2, with the shaft sleeve removed therefrom.

[0020] FIG. 10 illustrates a side view of a portion of a sleeve coupler set of the shaft sleeve.

[0021] FIG. 11 illustrates a side x-ray view of a portion of a receiver coupler set of the shaft receiver.

[0022] FIG. 12 illustrates a side view of a portion of a sleeve coupler set of a shaft sleeve similar to the shaft sleeve of FIGS. 1-7, and 10.

[0023] FIG. 13 illustrates a side x-ray view of a portion a receiver coupler set of a shaft receiver similar to the shaft receiver of FIGS. 1-4, 8-9, and 11.

[0024] FIG. 14 illustrates a top cross-sectional view of the golf coupling mechanism in a first configuration, with respect to the viewpoint of cross-sectional line XIV-XIV of FIG. 4.

[0025] FIG. 15 illustrates a top cross-sectional view of the golf coupling mechanism in a second configuration, with respect to the viewpoint of cross-sectional line XIV-XIV of FIG. 4.

[0026] FIG. 16 illustrates a top cross-sectional view of the golf coupling mechanism in a third configuration, with respect to the viewpoint of with the shaft sleeve removed therefrom line XIV-XIV of FIG. 4.

[0027] FIG. 17 illustrates a top cross-sectional view of the golf coupling mechanism in a fourth configuration, with respect to the viewpoint of with the shaft sleeve removed therefrom line XIV-XIV of FIG. 4.

[0028] FIG. 18 illustrates a flowchart for a method that can be used to provide, form, and/or manufacture a golf coupler mechanism in accordance with the present disclosure.

[0029] FIG. 19 illustrates a comparison of stagnant drag wake areas for respective hosels of different golf club heads 1910 and 1920.

[0030] FIG. 20 illustrates a chart of drag as a function of open face angle with respect to the hosel diameters the golf club heads of FIG. 19.

[0031] FIG. 21 illustrates a front perspective view of a golf club head with a golf coupling mechanism, according to an embodiment.

[0032] FIG. 22 illustrates a side view of a shaft sleeve of the golf coupling mechanism of the golf club head decoupled from the golf club head, according to the embodiment of FIG. 21.

[0033] FIG. 22A illustrates a side cross-sectional view of the golf club head of FIG. 21 along cross-sectional line III-III of FIG. 2, with the shaft sleeve removed therefrom.

[0034] FIG. 22B illustrates a side x-ray view of a portion of a receiver coupler set of the shaft receiver.

[0035] FIG. 23 illustrates a cross sectional view of the shaft sleeve along line XXIII-XXIII of FIG. 22, according to the embodiment of FIG. 21.

[0036] FIG. 24 illustrates a side view of a shaft sleeve body of the shaft sleeve decoupled from a shaft sleeve cap of the shaft sleeve, according to the embodiment of FIG. 21.

[0037] FIG. 25 illustrates a side view of the shaft sleeve cap decoupled from shaft sleeve body, according to the embodiment of FIG. 21.

[0038] FIG. 26 illustrates an elevational view of the shaft sleeve cap decoupled from the shaft sleeve body, according to the embodiment of FIG. 21.

[0039] FIG. 27 illustrates a flowchart for a method, according to an embodiment.

[0040] FIG. 28 illustrates an exemplary activity of providing a shaft sleeve, according to the embodiment of FIG. 27.

[0041] FIG. 29 illustrates a front perspective view of a golf club head with a golf coupling mechanism, according to an embodiment.

[0042] FIG. 30 illustrates a side view of a shaft sleeve of the golf coupling mechanism of the golf club head decoupled from the golf club head, according to the embodiment of FIG. 29.

[0043] FIG. 31 illustrates a cross sectional view of the shaft sleeve along line XXXIII-XXXIII of FIG. 30, according to the embodiment of FIG. 29.

[0044] FIG. 32 illustrates a side view of a shaft sleeve body of the shaft sleeve decoupled from a shaft sleeve cap of the shaft sleeve, according to the embodiment of FIG. 29.

[0045] FIG. 33A illustrates a side view of the shaft sleeve cap decoupled from shaft sleeve body, according to the embodiment of FIG. 29. FIG. 33B illustrates a top angled view of the shaft sleeve cap decoupled from shaft sleeve body, according to the embodiment of FIG. 29.

[0046] FIG. 34 illustrates a cross sectional view of the shaft sleeve cap along line XLVV-XLVV of FIG. 33B, according to the embodiment of FIG. 29.

[0047] FIG. 35A illustrates a top view of the shaft sleeve cap decoupled from the shaft sleeve body, according to the embodiment of FIG. 29. FIG. 35B illustrates a top view of the shaft sleeve body decoupled from the golf head, according to the embodiment of FIG. 29.

[0048] FIG. 36 illustrates a flowchart for a method, according to an embodiment.

[0049] FIG. 37 illustrates an exemplary activity of providing a shaft sleeve, according to the embodiment of FIG. 35.

[0050] FIG. 38 illustrates a side view of a shaft sleeve of a golf coupling mechanism decoupled from a golf club head, according to an embodiment.

[0051] FIG. 39 illustrates a cross sectional view of the shaft sleeve alone IVIII-IVIII of FIG. 38, according to the embodiment of FIG. 38.

[0052] FIG. 40 illustrates a side view of a shaft sleeve body of the shaft sleeve decoupled from the shaft sleeve cap of the shaft sleeve, according to the embodiment of FIG. 38.

[0053] For simplicity and clarity of illustration, the drawing figures illustrate the general manner of construction, and descriptions and details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the present disclosure. Additionally, elements in the drawing figures are not necessarily drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of embodiments of the present disclosure. The same reference numerals in different figures denote the same elements.

[0054] The terms “first,” “second,” “third,” “fourth,” and the like in the description and in the claims, if any, are used for distinguishing between similar elements and not necessarily for describing a particular sequential or chronological order. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments described herein are, for example, capable of operation in sequences other than those illustrated or otherwise described herein. Furthermore, the terms “include,” and “have,” and any variations thereof, are intended to cover a non-exclusive inclusion, such that a process, method, system, article, device, or apparatus that comprises a list of elements is not necessarily limited to those elements, but may include other elements not expressly listed or inherent to such process, method, system, article, device, or apparatus.

[0055] The terms “left,” “right,” “front,” “back,” “top,” “bottom,” “over,” “under,” and the like in the description and in the claims, if any, are used for descriptive purposes and not necessarily for describing permanent relative positions. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of the apparatus, methods, and/or articles of manufacture described herein are, for example, capable of operation in other orientations than those illustrated or otherwise described herein.

[0056] The terms “couple,” “coupled,” “couples,” “coupling,” and the like should be broadly understood and refer to connecting two or more elements, mechanically or otherwise. Coupling (whether mechanical or otherwise) may be for any length of time, e.g., permanent or semi-permanent or only for an instant.

[0057] The absence of the word “removably,” “removable,” and the like near the word “coupled,” and the like does not mean that the coupling, etc. in question is or is not removable.

[0058] As defined herein, two or more elements are “integral” if they are comprised of the same piece of material. As defined herein, two or more elements are “non-integral” if each is comprised of a different piece of material.

DETAILED DESCRIPTION

[0059] Some embodiments include a golf club head. The golf club head comprises a club head body, and the golf club head body comprises a sole comprising a sole bottom end, a top portion opposite the sole portion, a heel portion, a toe portion opposite the heel portion, a rear portion, a front portion opposite the rear portion, and a hosel. Further, the front portion comprises a strike face. The golf club head also comprises a shaft sleeve insertable into the hosel and configured to couple a golf club shaft with the hosel. The hosel can comprise a hosel bore configured to receive the shaft sleeve. Meanwhile, the shaft sleeve comprises (i) a shaft bore configured to receive an end of the golf club shaft, (ii) a shaft sleeve body comprising a sleeve body outer wall, and at least one coupler at the sleeve body outer wall, and (iii) a shaft sleeve cap configured to be coupled with the shaft sleeve body. When the golf club head is at an address position, with the shaft sleeve secured in the hosel, the shaft sleeve center of gravity can be located at a shaft sleeve CG vertical distance less than or equal to approximately 46 millimeters relative to the sole bottom end.

[0060] In these or other embodiments, the shaft sleeve body can comprise an intermediate region, the shaft sleeve body can comprise a sleeve body wall, and the sleeve body wall can comprise an intermediate region thickness of approximately 0.020 inch at the intermediate region.

[0061] In these or other embodiments, the shaft sleeve body can comprise a coupler region, the shaft sleeve body can comprise the sleeve body wall, the sleeve body wall can comprise a coupler region thickness that varies at the coupler region from a greatest thickness of the sleeve body wall to a least thickness of the sleeve body wall, the greatest thickness of the sleeve body wall can be less than or equal to approximately 0.75 inch, and the least thickness of the sleeve body wall can be greater than or equal to approximately 0.020 inch.

[0062] In these or other embodiments, the hosel bore can comprise at least one receiver configured to engage the at least one coupler, and when the hosel bore receives the shaft

sleeve, the at least one coupler can engage the at least one receiver to restrict a rotation of the shaft sleeve relative to the hosel.

[0063] In these or other embodiments, the shaft sleeve cap can be removably coupled with the shaft sleeve body.

[0064] In these or other embodiments, the at least one coupler can comprise multiple couplers, the multiple couplers can comprise a first coupler and a second coupler, and a coupler length of the first coupler can be different than a coupler length of the second coupler.

[0065] In these or other embodiments, the at least one coupler can comprise a coupler length, and the coupler length can be greater than or equal to approximately 0.260 inch and less than or equal to approximately 0.38 inch.

[0066] In these or other embodiments, the shaft sleeve body can comprise a receiving groove, the shaft sleeve cap can comprise an extrusion portion, and the receiving groove can be configured to receive the extrusion portion when the shaft sleeve body is coupled with the shaft sleeve cap.

[0067] In these or other embodiments, the shaft sleeve cap comprises at least one slit and a cap wall, and the at least one slit is configured to permit the cap wall to compress axially.

[0068] In these or other embodiments, the shaft sleeve cap can comprise a cap bore and one or more ribs extending into the cap bore, and when the shaft bore receives the end of the golf club shaft, the one or more ribs can center the golf club shaft within the shaft bore.

[0069] In these or other embodiments, the shaft sleeve can comprise a shaft sleeve mass of approximately 4.5 grams, the shaft sleeve body can comprise a shaft sleeve body mass less than or equal to approximately 4.1 grams, and/or the shaft sleeve cap can comprise a shaft sleeve cap mass greater than or equal to approximately 0.3 grams less than or equal to approximately 1.0 grams.

[0070] In these or other embodiments, the golf club head can comprise a fastener configured to couple the shaft sleeve to the hosel, when the shaft sleeve cap is coupled with the shaft sleeve body, and when the fastener is securing the shaft sleeve to the hosel, the golf club head can comprise an assembled club head mass, and the assembled club head mass can be less than or equal to approximately 199 grams.

[0071] In these or other embodiments, the golf club head can comprise a fastener configured to couple the shaft sleeve to the hosel, when the shaft sleeve cap is coupled with the shaft sleeve body, and when the fastener is securing the shaft sleeve to the hosel, the golf club head can comprise an assembled club head mass, the shaft sleeve can comprise a shaft sleeve mass, and a ratio of the shaft sleeve mass to the assembled club head mass can be less than or equal to approximately 2.2%.

[0072] In these or other embodiments, the golf club head can comprise a disassembled club head mass, the shaft sleeve can comprise a shaft sleeve mass, and a ratio of the shaft sleeve mass to the disassembled club head mass can be less than or equal to approximately 2.2%.

[0073] In these or other embodiments, the shaft sleeve CG vertical distance can be greater than or equal to approximately 45.3 millimeters relative to the sole bottom end.

[0074] In these or other embodiments, when the shaft sleeve body is coupled to the shaft sleeve cap, the shaft sleeve comprises a shaft sleeve height, and the shaft sleeve height can be greater than or equal to approximately 1.78 inches and less than or equal to approximately 1.82 inches; when the shaft sleeve body is coupled to the shaft sleeve cap,

the shaft sleeve comprises a shaft sleeve body height, and the shaft sleeve body height can be greater than or equal to approximately 1.529 inches and less than or equal to approximately 1.569 inches; and/or when the shaft sleeve body is coupled to the shaft sleeve cap, the shaft sleeve comprises a shaft sleeve cap height, and the shaft sleeve cap height can be greater than or equal to approximately 0.46 inches and less than or equal to approximately 0.50 inches.

[0075] Further embodiments include a golf club head. The golf club head comprises a club head body, and the golf club head body comprises a sole comprising a sole bottom end, a top portion opposite the sole portion, a heel portion, a toe portion opposite the heel portion, a rear portion, a front portion opposite the rear portion, and a hosel. Further, the front portion comprises a strike face. The golf club head also comprises a shaft sleeve insertable into the hosel and configured to couple a golf club shaft with the hosel. Meanwhile, the hosel can comprise a hosel bore configured to receive the shaft sleeve. Further, the shaft sleeve can comprise (i) a shaft bore configured to receive an end of the golf club shaft, (ii) a shaft sleeve body comprising a sleeve body outer wall, and at least one coupler on the sleeve body outer wall, and (iii) a shaft sleeve cap configured to be coupled with the shaft sleeve body. The shaft sleeve body can further comprise an intermediate region and a sleeve body wall. Also, the shaft sleeve can comprise a shaft sleeve mass of approximately 4.3 grams. In these embodiments, the shaft sleeve body can comprise a shaft sleeve body mass less than or equal to approximately 3.8 grams. Further, the shaft sleeve cap can comprise a cap bore and one or more ribs into the cap bore, and when the shaft bore receives the end of the golf club shaft, the one or more ribs can center the golf club shaft within the shaft bore. In various embodiments, the shaft sleeve cap can be removably coupled with the shaft sleeve body. Further still, when the golf club head is at an address position, with the shaft sleeve secured in the hosel: the shaft sleeve center of gravity can be located at a shaft sleeve CG vertical distance greater than or equal to approximately 43.5 millimeters and less than or equal to approximately 47 millimeters relative to the sole bottom end.

[0076] Other embodiments include a method. The method can comprise providing a shaft sleeve.

[0077] Meanwhile, providing the shaft sleeve can comprise: providing a shaft sleeve body; and providing a shaft sleeve cap. Further, the shaft sleeve can be configured to be insertable into a hosel of a golf club head and configured to couple a golf club shaft with the hosel. Likewise, the golf club head can comprise a golf club head body and the hosel, and the golf club head body can comprise a sole comprising a sole bottom end, a top portion opposite the sole portion, a heel portion, a toe portion opposite the heel portion, a rear portion, a front portion opposite the rear portion. The front portion can comprise a strike face. Further still, the hosel can comprise a hosel bore configured to receive the shaft sleeve. Also, the shaft sleeve can comprise (i) a shaft bore configured to receive an end of the golf club shaft, (ii) a shaft sleeve body comprising a sleeve body outer wall, and at least one coupler on the sleeve body outer wall, and a shaft sleeve cap configured to be coupled with the shaft sleeve body. When the golf club head is at an address position, with the shaft sleeve secured in the hosel, the shaft sleeve center of gravity can be located at a shaft sleeve CG vertical distance less than or equal to approximately 46 millimeters relative to the sole bottom end.

[0078] Other examples and embodiments are further disclosed herein. Such examples and embodiments may be found in the figures, in the claims, and/or in the present description.

[0079] Turning to the drawings, FIG. 1 illustrates a front perspective view of golf club head 101 with golf coupling mechanism 1000 according to one example of the present disclosure. FIG. 2 illustrates a top perspective view of golf club head 101 with golf coupling mechanism 1000. FIG. 3 illustrates a cross-sectional view of golf club head 101 along line III-III of FIG. 2, showing golf coupling mechanism 1000 with shaft sleeve 1100 inserted into shaft receiver 3200. FIG. 4 illustrates a cross-sectional view of golf club head 101 and golf coupling mechanism 1000 along line IV-IV of FIG. 2.

[0080] In the present embodiment, golf coupling mechanism 1000 comprises shaft sleeve 1100 configured be coupled to an end of a golf club shaft, such as golf club shaft 102 (FIG. 1). FIG. 5 illustrates a side view of shaft sleeve 1100 decoupled from golf club head 101 (FIG. 1). FIG. 6 illustrates a cross sectional view of shaft sleeve 1100 along line VI-VI of FIG. 5. In the present example, shaft sleeve 1100 comprises shaft bore 3120 configured to receive the end of golf club shaft 102. Shaft sleeve 1100 also comprises sleeve axis 5150 extending along a longitudinal centerline of shaft sleeve 1100, from sleeve top end 1191 to sleeve bottom end 3192. Sleeve outer wall 3130 is a right angle cylinder such that at least portions of sleeve outer wall 3130 are substantially parallel to sleeve axis 5150 in the present example, and bound shaft bore 3120 therewithin. In other words, sleeve axis 5150 is the center of sleeve outer wall 3130 in this embodiment. In the present example, shaft bore 3120 extends coaxially to shaft bore axis 6150, and is angled with respect to sleeve axis 5150, thus being non-coaxial thereto. Shaft bore axis 6150 is angled at approximately 0.5 degrees from sleeve axis 5150 in the present example, but there can be examples where such angle can be of approximately 0.2 degrees to approximately 4 degrees relative to sleeve axis 5150. Accordingly, shaft bore 3120 and sleeve outer wall 3130 are not concentric in this embodiment. There can be other embodiments, however, where shaft bore axis 6150 can be substantially collinear with sleeve axis 5150, such that sleeve outer wall 3130 and shaft bore 3120 can be substantially concentric.

[0081] Shaft sleeve 1100 comprises sleeve coupler set 3110 with one or more couplers protruding from sleeve outer wall 3130. FIG. 7 illustrates a cross-section view of shaft sleeve 1100 along line VII-VII of FIG. 5 across sleeve coupler set 3110. FIGS. 3-7 illustrate different views of sleeve coupler set 3110 protruding from sleeve outer wall 3130. In the present example, sleeve coupler set 3110 comprises sleeve couplers 3111, 3112, 5116, and 7115 protruding from sleeve outer wall 3130, where sleeve coupler 3112 lies opposite sleeve coupler 3111 and sleeve coupler 7115 lies opposite sleeve coupler 5116 along perimeter 7191 of sleeve outer wall 3130. As can be seen from FIG. 7, sleeve coupler set 3110 forms alternating concave and convex surfaces about perimeter 7191 in the present embodiment.

[0082] The sleeve couplers of sleeve coupler set 3110 comprise arcuate surfaces configured to restrict rotation of shaft sleeve 1100 relative golf club head 101 when shaft sleeve 1100 is inserted and secured in shaft receiver 3200. For example, as seen in FIGS. 3, 5, and 7: (a) sleeve coupler

3111 comprises arcuate surface **3151** curved throughout the outer area of sleeve coupler **3111**, (b) sleeve coupler **3112** comprises arcuate surface **3152** curved throughout the outer area of sleeve coupler **3112**, (c) sleeve coupler **5116** comprises arcuate surface **5156** curved throughout the outer area of sleeve coupler **5116**, and (d) sleeve coupler **7115** comprises arcuate surface **7155** curved throughout the outer area of sleeve coupler **7115**.

[0083] Golf coupling mechanism **1000** also comprises shaft receiver **3200**, configured to receive shaft sleeve **1100** as seen in FIGS. 3-4. FIG. 8 illustrates a top view of golf club head **101** with shaft sleeve **1100** removed therefrom, showing shaft receiver **3200** from above. FIG. 9 illustrates a cross-sectional side view of golf club head **101** with shaft sleeve **1100** removed therefrom and along line III-III of FIG. 2, showing a side cross section of shaft receiver **3200**.

[0084] In the present example, shaft receiver **3200** is integral with hosel **1015** of club head **101**, but there can be embodiments where shaft receiver **3200** can be distinct from hosel **1015** and coupled thereto via one or more fastening methods, such as via adhesives, via a screw thread mechanism, and/or via a bolt or rivet. In the same or other embodiments, the terms hosel and shaft receiver may be used interchangeably. There can also be embodiments where golf club head **101** may comprise a head bore into its crown or top portion, rather than hosel **1015**. In such embodiments, the shaft receiver **3200** may also be part of, or coupled to, such head bore.

[0085] Shaft sleeve **1100** is configured to be inserted into shaft receiver **3200**, and can be subdivided in several portions. For example, shaft sleeve **1100** comprises sleeve insertion portion **3160** bounded by sleeve outer wall **3130** and configured to be internal to shaft receiver **3200** when shaft sleeve **1100** is secured in shaft receiver **3200**. In the present example, shaft sleeve **1100** also comprises sleeve top portion **3170**, configured to remain external to shaft receiver **3200** when shaft sleeve **1100** is secured in shaft receiver **3200**. There can be other examples, however, that are devoid of sleeve top portion **3170** and/or with a shaft sleeve similar to shaft sleeve **1100** but configured to be inserted in its entirety into shaft receiver **3200**.

[0086] Shaft receiver **3200** comprises hosel outer wall **3240**, with receiver inner wall **3230** configured to bound sleeve insertion portion **3160** and sleeve outer wall **3130** of shaft sleeve **1100** when inserted therein. Shaft receiver **3200** also comprises receiver coupler set **3210** configured to engage coupler set **3110** of shaft sleeve **1100** to restrict a rotation of shaft sleeve **1100** relative to shaft receiver **3200**. In the present embodiment, as can be seen in FIG. 8, receiver coupler set **3210** comprises receiver couplers **3213**, **3214**, **8217**, and **8218** indented into receiver inner wall **3230**, with receiver coupler **3213** opposite receiver coupler **3214** and with receiver coupler **8218** opposite receiver coupler **8217**.

[0087] The receiver couplers of receiver coupler set **3210** in shaft receiver **3200** comprise arcuate surfaces complementary with the arcuate surfaces of sleeve coupler set **3110** of shaft sleeve **1100**. For example: (a) receiver coupler **3213** comprises arcuate surface **3253** curved throughout the inner area of receiver coupler **3213** (FIG. 8), where arcuate surface **3253** of receiver coupler **3213** is complementary with arcuate surface **3151** of sleeve coupler **3111** (FIG. 7), (b) receiver coupler **3214** comprises arcuate surface **3254** curved throughout the inner area of receiver coupler **3214** (FIG. 8), where arcuate surface **3254** of receiver coupler **3214** is

complementary with arcuate surface **3152** of sleeve coupler **3112** (FIG. 7), (c) receiver coupler **8217** comprises arcuate surface **8257** curved throughout the inner area of receiver coupler **8217** (FIG. 8), where arcuate surface **8257** of receiver coupler **8217** is complementary with arcuate surface **7155** of sleeve coupler **7115** (FIG. 7), and (d) receiver coupler **8218** comprises arcuate surface **8258** curved throughout the inner area of receiver coupler **8218** (FIG. 8), where arcuate surface **8258** of receiver coupler **8218** is complementary with arcuate surface **5156** of sleeve coupler **5116** (FIG. 7).

[0088] In the present embodiment, the arcuate surfaces of sleeve coupler set **3110** and of receiver coupler set **3210** are curved throughout their respective sleeve couplers and receiver couplers. FIG. 10 illustrates a side view of a portion of shaft sleeve **1100** and sleeve coupler set **3110**. FIG. 11 illustrates a side x-ray view of a portion of shaft receiver **3200** and receiver coupler set **3210**. As seen in FIGS. 7 and 10, arcuate surface **5156** of sleeve coupler **5116** comprises horizontal radius of curvature **7176**, arcuate surface **3151** of sleeve coupler **3111** comprises horizontal radius of curvature **7171**, arcuate surface **3152** of sleeve coupler **3112** comprises horizontal radius of curvature **7172**, and arcuate surface **7155** of sleeve coupler **7115** comprises horizontal radius of curvature **7175** in the present example. Also in the present example, the arcuate surfaces of sleeve coupler set **3110** comprise vertical taperings that decrease in thickness towards sleeve bottom end **3192** of shaft sleeve **1100** and towards sleeve axis **5150** (FIGS. 5-6). For example, as seen in FIG. 10, arcuate surface **5156** of sleeve coupler **5116** comprises vertical tapering **10186**, arcuate surface **3151** of sleeve coupler **3111** comprises vertical tapering **10181**, and arcuate surface **3152** of sleeve coupler **3112** comprises vertical tapering **10182**. Although not shown in FIG. 10, arcuate surface **7155** of sleeve coupler **7115** also comprises a vertical tapering similar to vertical tapering **10186** of sleeve coupler **5116**.

[0089] With respect to receiver coupler set **3210** of shaft receiver **3200**, as seen in FIGS. 8 and 11, arcuate surface **8258** of receiver coupler **8218** comprises horizontal radius of curvature **8278** complementary with horizontal radius of curvature **7176** of sleeve coupler **5116** (FIGS. 7, 10), arcuate surface **3253** of receiver coupler **3213** comprises horizontal radius of curvature **8273** complementary with horizontal radius of curvature **7171** of sleeve coupler **3111** (FIG. 7), arcuate surface **3254** of receiver coupler **3214** comprises horizontal radius of curvature **8274** complementary with horizontal radius of curvature **7172** of sleeve coupler **3112** (FIG. 7), and arcuate surface **8257** of receiver coupler **8217** comprises horizontal radius of curvature **8277** complementary with horizontal radius of curvature **7175** of sleeve coupler **7115** (FIG. 7) in the present example.

[0090] Also in the present example, the arcuate surfaces of receiver coupler set **3210** comprise vertical taperings complementary to the vertical taperings of the arcuate surfaces of sleeve coupler set **3110**. For example, as seen in FIG. 11, arcuate surface **8258** of receiver coupler **8218** comprises vertical tapering **11288** complementary with vertical tapering **10186** of sleeve coupler **5116** (FIG. 10), arcuate surface **3253** of receiver coupler **3213** comprises vertical tapering **11283** complementary with vertical tapering **10181** of sleeve coupler **3111** (FIG. 10), and arcuate surface **3254** of receiver coupler **3214** comprises vertical tapering **11284** complementary with vertical tapering **10182**

of sleeve coupler **3112** (FIG. 10). Although not shown in FIG. 11, arcuate surface **8257** of receiver coupler **8217** also comprises a vertical tapering similar to vertical tapering **11288** of receiver coupler **8218** and complementary to the vertical tapering of sleeve coupler **7115**.

[0091] In the present embodiment, the vertical taperings of the arcuate surfaces of sleeve coupler set **3110** are substantially linear, decreasing in a substantially straight line as can be seen in the profile view of vertical taperings **10181** and **10182** for sleeve couplers **3111** and **3112** in FIG. 10. Similarly, the vertical taperings of the arcuate surfaces of receiver coupler set **3210** are substantially linear, as can be seen in the profile view of vertical taperings **11283** and **11284** for receiver couplers **3213** and **3214** in FIG. 11. In the same or other examples, the substantially linear vertical taperings of the arcuate surfaces of sleeve coupler set **3110** and of receiver coupler set **3210** may be considered to comprise a large or infinite vertical radius of curvature yielding a substantially straight line.

[0092] There can be other embodiments, however, where the vertical taperings of the sleeve couplers and/or the receiver couplers need not be linear. FIG. 12 illustrates a side view of a portion of shaft sleeve **12100** with sleeve coupler set **12110**. FIG. 13 illustrates a side x-ray cross-sectional view of shaft receiver **13200** with receiver coupler set **13210**.

[0093] Shaft sleeve **12100** can be similar to shaft sleeve **1100** (FIGS. 1-7, 10), and shaft receiver **13200** can be similar to shaft receiver **3200** (FIGS. 3-4, 8, 10). Sleeve coupler set **12110** differs from sleeve coupler set **3110**, however, by comprising vertical taperings that are not linear. For example, sleeve coupler set **12110** comprises vertical taperings **12186**, **12181**, and **12182** that are curved rather than linear, and can comprise respective vertical radii of curvature. Similarly, receiver coupler set **13210** comprises vertical taperings **13288**, **13283**, and **13284** that are curved rather than linear, and comprise respective vertical radii of curvature complementary with the radii of curvature of sleeve coupler set **12110**. Accordingly, the sleeve couplers of sleeve coupler set **12110** and the receiver couplers of receiver coupler set **13210** are each curved horizontally and vertically throughout their respective surface areas. For example, any horizontal line tangential to any point of a total surface of sleeve coupler **12116** is non-tangential to any other point of the total surface of sleeve coupler **12116**. In the same or other embodiments, the total surface of each sleeve coupler of sleeve coupler set **12110**, and the total surface of each receiver coupler of receiver coupler set **13210** is each curved throughout and in all directions.

[0094] The different sleeve couplers and receiver couplers of the present disclosure may comprise respective curvatures within certain ranges. For example, with respect to FIGS. 7 and 10, horizontal radii of curvature **7171**, **7172**, **7175**, and **7176** of sleeve coupler set **3110** are each of approximately 0.175 inches (4.45 millimeters (mm)), but there can be embodiments where they could range from approximately 0.1 inches (2.54 mm) to approximately 0.225 inches (5.715 mm). With respect to FIGS. 8 and 11, horizontal radii of curvature **8273**, **8274**, **8277**, and **8278** of receiver coupler set **3210** can be complementarily the same or similar to horizontal radii of curvature **7171**, **7172**, **7175**, and **7176** (FIGS. 7, 10), respectively. In addition, the horizontal radii of curvature for sleeve coupler set **12110** and for receiver coupler set **13210** in the embodiment of FIGS. 12-13 can

also be similar to those described above with respect to the embodiment of FIGS. 1-11 for sleeve coupler set **3110** and/or receiver coupler set **3210**.

[0095] As previously described, in the embodiment of FIGS. 1-11, the vertical taperings of sleeve coupler set **3110** (FIG. 10) and of receiver coupler set **3210** (FIG. 11) can comprise vertical radii of curvature approximating infinity, thereby yielding substantially straight lines. In the embodiment of FIGS. 12-13, the vertical taperings of sleeve coupler set **12110** (FIG. 12) and of receiver coupler set **13210** (FIG. 13) comprise more pronounced vertical radii of curvature. As an example the vertical radius of curvature for vertical tapering **12186** of sleeve coupler **12116** (FIG. 12) is of approximately 0.8 inches (20.32 mm), but there can be embodiments where it could range from approximately 0.4 inches (10.16 mm) to 2 inches (50.8 mm). The vertical radii of curvature for other similar portions of sleeve coupler set **12110** can also be in the same range described for vertical tapering **12186**. In addition, the vertical radii of curvature for receiver coupler set **13210** (FIG. 13) can be complementarily the same or similar to the vertical radii of curvature described for sleeve coupler set **12110** (FIG. 12).

[0096] In some examples, the arcuate surfaces of the sleeve couplers and/or of the receiver couplers may comprise portions of geometric structures. For instance, the arcuate surface of sleeve coupler **12116** (FIG. 12) can comprise a quadric surface, and the arcuate surface of receiver coupler **13218** (FIG. 13) can comprise a quadric surface complementary to the arcuate surface of sleeve coupler **12116**. In such examples, the quadric surface of sleeve coupler **12116** and of receiver coupler **13218** can comprise, for example, a portion of a paraboloid surface or a portion of a hyperboloid surface. There can also be examples with sleeve couplers and receiver couplers whose quadric arcuate surfaces can comprise a portion of a degenerate quadric surface, such as a portion of a conical surface. Such examples can be similar to those of FIGS. 10-11 with respect to sleeve coupler set **3110** and receiver coupler set **3200**.

[0097] In the embodiments of FIGS. 10-11 and of FIGS. 12-13, the arcuate surfaces of the sleeve couplers of sleeve coupler set **3110** (FIG. 10) and/or **12110** (FIG. 12), and the arcuate surfaces of the receiver couplers of receiver coupler set **3210** (FIG. 11) and/or **13210** (FIG. 13), can be configured to be devoid of any inflection point, such as to be continuously curved. In the same or other embodiments, such arcuate surfaces can also be configured to be edgeless (except for their respective perimeter). For example, the total surface area of sleeve coupler **5116** (FIG. 10) is edgeless with respect to any portion of its total surface area within its perimeter. In addition, the total surface area of receiver coupler **8218** (FIG. 11) also is edgeless with respect to any portion of its total surface area within its perimeter. Similar edgeless attributes are also shared by sleeve coupler **12110** (FIG. 12) and receiver coupler **13218** (FIG. 13). The characteristics described above can permit the contact area to be maximized when sleeve couplers seat against receiver couplers to restrict rotation of their shaft sleeves relative to their respective shaft receivers.

[0098] As can be seen in FIGS. 3-7 and 10, sleeve coupler set **3110** protrudes from a top section of sleeve outer wall **3130**. Similarly, as can be seen in FIGS. 3-4, 8-9, and 11, receiver coupler set **3210** is indented into a top section of receiver inner wall **3230**. There can be other embodiments,

however, where sleeve coupler set **3110** and receiver coupler set **3210** may be located elsewhere. For instance, sleeve coupler set **3110** and receiver coupler set **3210** may be located at or towards bottom sections or mid sections of shaft sleeve **1100** and shaft receiver **3200**, respectively. In the same or other embodiments, the shape of sleeve coupler set **3110** and receiver coupler set **3210** could be reversed such that sleeve coupler set **3110** is recessed into sleeve outer wall **3130** and receiver coupler set **3210** protrudes from receiver inner wall **3230**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

[0099] As can be seen in the cross section presented in FIG. 3, golf coupling mechanism **1000** also comprises securing fastener **3400** configured to secure shaft sleeve **1100** to shaft receiver **3200**. In the present example, securing fastener **3400** comprises a bolt configured to couple, via a passageway at a bottom of shaft receiver **3200**, with sleeve bottom end **3192** of shaft sleeve **1100**. Securing fastener **3400** is configured to couple with sleeve bottom end **3192** via a screw thread mechanism. As the screw thread mechanism is tightened, securing fastener **3400** is configured to pull shaft sleeve **1100** towards the bottom end of shaft receiver **3200**, thereby causing the arcuate surfaces of sleeve coupler set **3110** to seat against the arcuate surfaces of receiver coupler set **3210**.

[0100] In examples such as the present one, the combined total masses of the body of golf club head **101**, shaft sleeve **1100**, and securing fastener **3400** may be referred to as an assembled club head mass, while the mass of the body of golf club head **101**, without shaft sleeve **1100** and securing fastener **3400**, may be referred to as a disassembled club head mass.

[0101] In the present embodiment, securing fastener **3400** comprises retainer element **3450** coupled thereto to restrict or at least inhibit securing fastener **3400** from being fully removed from shaft receiver **3200** when decoupled from shaft sleeve **1100**. Retainer element **3450** comprises a washer located within shaft receiver **3200** and coupled around the threads of securing fastener **3400**. Retainer element **3450** can be configured to flexibly engage the threads of securing fastener **3400** in the present embodiment, such as to permit positioning thereof along the threads of securing fastener **3400** by ramming securing fastener **3400** through retainer element **3450**, and such as to remain substantially in place once positioned along the threads of securing fastener **3400**. Retainer element **3450** can thus retain an end of securing fastener **3400** within shaft receiver **3200** after shaft sleeve **1100** is removed therefrom, and can permit insertion of the end of securing fastener **3400** into sleeve bottom end **3192**. In some examples, retainer element **3450** can comprise a material such as a nylon material or other plastic material more flexible than the material of securing fastener **3400**.

[0102] In other examples, the bore through which securing fastener **3400** enters shaft receiver **3200** may comprise threading corresponding to that of securing fastener **3400**, where such threading can thereby serve as the retainer element. In these other examples, retainer element **3450** can be omitted.

[0103] Sleeve coupler set **3110** and receiver coupler set **3210** are configured such that at least a majority of their respective arcuate surfaces seat against each other when shaft sleeve **1110** is secured in shaft receiver **3200** by

securing fastener **3400**. For example, in the embodiment of FIGS. 10-11, when seated against each other, at least a majority of a total surface of sleeve coupler **5116** and a majority of a total surface of receiver coupler **8218** contact each other and restrict rotation of shaft sleeve **1100** relative to shaft receiver **3200**. As another example, in the embodiment of FIGS. 11-12, when seated against each other, a majority of a total surface of sleeve coupler **12116** and a majority of a total surface of receiver coupler **13218** also contact each other to restrict rotation. In the same or other examples, the contact area defined by the interface between an individual sleeve coupler of sleeve coupler set **3110** (FIG. 10) or **12110** (FIG. 12) and an individual receiver coupler of receiver coupler set **3210** (FIG. 11) or **13210** (FIG. 13) may be of approximately 51% to approximately 95% of a total surface of the individual receiver coupler or the individual sleeve coupler. Such contact area may be even greater in some embodiments, such as to substantially approach or equal the total surface of the individual receiver coupler and/or of the individual sleeve coupler. There can also be examples where, when the arcuate surfaces of the sleeve couplers of sleeve coupler set **3110** (FIG. 10) or **12110** (FIG. 12) seat against the arcuate surfaces of the receiver couplers of receiver coupler set **3200** (FIG. 11) or **13210** (FIG. 13), normal forces are exerted against each other across the respective contact areas.

[0104] In the present example, when securing fastener **3400** secures shaft sleeve **1100** in shaft receiver **3200**, sleeve top portion **3170** remains external to shaft receiver **3200**, with bottom end **3171** of sleeve top portion **3170** spaced away from a top end of shaft receiver **3200** by the seating of sleeve coupler set **3110** against receiver coupler set **3210**. Such built-in spacing cases manufacturing tolerances, ensuring that sleeve coupler set **3110** can properly seat against receiver coupler set **3210**.

[0105] In the same or other examples, a portion of one or more of the sleeve couplers of sleeve coupler set **3110** may protrude past the top end of shaft receiver **3200**. There can also be examples where one or more of the sleeve couplers of sleeve coupler set **3110** may extend past the bottom end of one or more of the receiver couplers of receiver coupler set **3210**. In other examples, one or more of the receiver couplers of receiver coupler set may extend past the bottom end of one or more of the sleeve couplers of sleeve coupler set **3110**. Some of the features described above may be designed into golf coupling mechanism **1000** to ease the required manufacturing tolerances while still permitting proper seating of sleeve coupler set **3110** against receiver coupler set **3210**.

[0106] FIG. 14 illustrates a top cross-sectional view of golf coupling mechanism **1000** in configuration **1400**, with respect to the viewpoint of line XIV-XIV of FIG. 4. Golf coupling mechanism **1000** is shown in FIGS. 3-4 and 14 in configuration **1400**, where sleeve couplers **3111**, **7115**, **3112**, and **5116** (FIG. 7) of sleeve coupler set **3110** are respectively coupled to receiver couplers **3213**, **8217**, **3214**, and **8218** (FIG. 8) of receiver coupler set **3210**. Because shaft bore axis **6150** (FIG. 6) is non-coaxial with sleeve axis **5150** of shaft sleeve **1100** as described above, configuration **1400** in FIG. 14 can comprise a first lie angle and a first loft angle between shaft bore axis **6150** (FIG. 6) and shaft receiver **3200** (FIGS. 3-4, 8-9) and/or between shaft **102** (FIG. 1) and golf club head **101** (FIG. 1).

[0107] FIG. 15 illustrates a top cross-sectional view of golf coupling mechanism 1000 in configuration 1500, with respect to the viewpoint of line XIV-XIV of FIG. 4. In configuration 1500, sleeve couplers 3112, 5116, 3111, and 7115 (FIG. 7) of sleeve coupler set 3110 are respectively coupled to receiver couplers 3213, 8217, 3214, and 8218 (FIG. 8) of receiver coupler set 3210. Because shaft bore axis 6150 (FIG. 6) is non-coaxial with sleeve axis 5150 of shaft sleeve 1100 as described above, configuration 1500 in FIG. 15 can comprise a second lie angle and a second loft angle between shaft bore axis 6150 (FIG. 6) and shaft receiver 3200 (FIGS. 3-4, 8-9) and/or between shaft 102 (FIG. 1) and golf club head 101 (FIG. 1).

[0108] FIG. 16 illustrates a top cross-sectional view of golf coupling mechanism 1000 in configuration 1600, with respect to the viewpoint of line XIV-XIV of FIG. 4. In configuration 1600, sleeve couplers 7115, 3112, 5116, and 3111 (FIG. 7) of sleeve coupler set 3110 are respectively coupled to receiver couplers 3213, 8217, 3214, and 8218 (FIG. 8) of receiver coupler set 3210. Because shaft bore axis 6150 (FIG. 6) is non-coaxial with sleeve axis 5150 of shaft sleeve 1100 as described above, configuration 1600 in FIG. 16 will comprise a third lie angle and a third loft angle between shaft bore axis 6150 (FIG. 6) and shaft receiver 3200 (FIGS. 3-4, 8-9) and/or between shaft 102 (FIG. 1) and golf club head 101 (FIG. 1).

[0109] FIG. 17 illustrates a top cross-sectional view of golf coupling mechanism 1000 in configuration 1700, with respect to the viewpoint of line XIV-XIV of FIG. 4. In configuration 1700, sleeve couplers 5116, 3111, 7115, and 3112 (FIG. 7) of sleeve coupler set 3110 are respectively coupled to receiver couplers 3213, 8217, 3214, and 8218 (FIG. 8) of receiver coupler set 3210. Because shaft bore axis 6150 (FIG. 6) is non-coaxial with sleeve axis 5150 of shaft sleeve 1100 as described above, configuration 1700 in FIG. 17 will comprise a fourth lie angle and a fourth loft angle between shaft bore axis 6150 (FIG. 6) and shaft receiver 3200 (FIGS. 3-4, 8-9) and/or between shaft 102 (FIG. 1) and golf club head 101 (FIG. 1).

[0110] Depending on the angle of shaft bore axis 6150 with respect to sleeve axis 5150 and sleeve coupler set 3110, different lie and loft angle alignments may be attained via the configurations shown in FIGS. 14-17. For example, in the present embodiment, as can be seen in FIG. 6, the angle between shaft bore axis 6150 and sleeve axis 5150 causes the bottom of shaft bore 3120 to point towards sleeve coupler 3111, such that shaft 102 (FIG. 1) will lean towards sleeve coupler 3112 when inserted into shaft sleeve 1100.

[0111] Accordingly, in configuration 1400 (FIG. 14), the first lie angle may comprise a lower lie angle, and the first loft angle may comprise a neutral or middle loft angle. As an example, the first lie angle can be set to tilt the grip end of shaft 102 towards the heel of golf club head 101 (FIG. 1) by approximately 0.2 degrees to approximately 4 degrees, thereby decreasing the lie angle of the golf club in configuration 1400. The first loft angle, being neutral in the present example, does not affect the tilt of shaft 102 in configuration 1400.

[0112] In configuration 1500 (FIG. 15), the second lie angle may comprise a higher lie angle, and the second loft angle may comprise a neutral or middle loft angle, which may be similar or equal to the first loft angle of configuration 1400 (FIG. 14). As an example, second lie angle can be set to tilt the grip end of shaft 102 towards the toe of golf club

head 101 (FIG. 1) by approximately 0.2 degrees to approximately 4 degrees, thereby increasing the lie angle of the golf club in configuration 1500. The second loft angle, being neutral in the present example, does not affect the tilt of shaft 102 in configuration 1500.

[0113] In configuration 1600 (FIG. 16), the third loft angle may comprise a lower loft angle, and the third lie angle may comprise a neutral or middle lie angle. As an example, the third loft angle can be set to tilt the grip end of shaft 102 towards the rear of golf club head 101 (FIG. 1) by approximately 0.2 degrees to approximately 4 degrees, thereby decreasing the loft angle of the golf club in configuration 1600. The third lie angle, being neutral in the present example, does not affect the tilt of shaft 102 in configuration 1600.

[0114] In configuration 1700 (FIG. 17), the fourth loft angle may comprise a higher loft angle, and the fourth lie angle may comprise a neutral or middle lie angle, which may be similar or equal to the third lie angle of configuration 1600 (FIG. 16). As an example, the fourth loft angle can be set to tilt the grip end of shaft 102 towards the front or strike face of golf club head 101 (FIG. 1) by approximately 0.2 degrees to approximately 4 degrees, thereby increasing the loft angle of the golf club in configuration 1700. The fourth lie angle, being neutral in the present example, does not affect the tilt of shaft 102 in configuration 1700.

[0115] Other lie and loft angle relationships may be configured in other embodiments by altering the angle and/or orientation of shaft bore axis 6150 (FIG. 6) with respect to sleeve axis 5150 (FIG. 6) of shaft sleeve 1100. Furthermore, as seen from FIGS. 14-17, sleeve couplers 3111, 3112, 5116, and 7115 are symmetric with each other, and receiver couplers 3213, 3214, 8217, and 8218 are also symmetric with each other. In a different embodiment, only opposite ones of the sleeve couplers and the receiver couplers may be symmetric with each other such that only two (and not four) different lie and loft angle combinations are permitted.

[0116] The different features described above for the golf coupler mechanisms of FIGS. 1-17 can also impart several performance benefits to the golf clubs on which they are used, when compared to other golf club heads with adjustable shaft coupling mechanisms. For example, because of the small number of parts required, and/or because receiver coupler set 3210 is located only towards the top end of shaft receiver 3200 (FIG. 3), hosel diameter 1031 of hosel 1015 (FIG. 1) can be maintained to a minimum and/or relatively unchanged from a hosel diameter of a corresponding regular golf club head. In some examples, as can be seen in FIG. 8, hosel diameter 1031 can be of less than approximately 20 mm, such as of approximately 0.55 inches (approximately 14 mm), or such as of approximately 0.53 inches (approximately 13.46 mm) at receiver top end 1032. In addition, top wall thickness 9250 (FIGS. 8-9) of shaft receiver 3200 can be minimized as shown at receiver top end 1032 of shaft receiver 3200. For instance, top wall thickness 9250 can be of approximately 0.035 inches (approximately 0.9 mm) or less, such as of approximately 0.024 inches (approximately 0.61 mm).

[0117] As can be seen in FIG. 8, top wall thickness 9250 varies in thickness along receiver top end 1032 in the present embodiment, and comprises at least one hosel top wall narrow section 8252 and at least one hosel top wall thick section 8251 at receiver top end 1032. Hosel top wall thick section 8251 can have a thickness less than or equal to

approximately 2.3 mm at receiver top end **1032**, when measured radially relative to a centerpoint of hosel diameter **1031**. Hosel top wall narrow section **8252** can have a thickness less than or equal to approximately 0.9 mm at receiver top end **1032**, when measured radially relative to the centerpoint of hosel diameter **1031**. In the present example, when measured radially relative to the centerpoint of hosel diameter **1031**, hosel top wall thick section **8251** can be less than or equal to approximately 1.27 mm, and hosel top wall narrow section **8252** can be less than or equal to 0.64 mm.

[0118] Because hosel diameter **1031** can be minimized as described above, the aerodynamic characteristics of golf club head **101** can be improved as a result of the reduced aerodynamic drag from hosel **1015**. FIG. 19 illustrates a comparison of stagnant drag wake areas **1911** and **1921** for respective hosels of golf club heads **1910** and **1920**, where golf club head **1910** comprises a hosel diameter of approximately 0.5 inches, and where golf club head **1920** comprises a larger hosel diameter of approximately 0.62 inches. In some examples, golf club head **1910** can be similar to golf club head **101** (FIGS. 1-4, 8-9). As seen in FIG. 19, the larger hosel diameter of club head **1920** creates larger stagnant drag wake area **1921** downstream of its hosel, leading to higher values of aerodynamic drag when compared to the smaller stagnant drag wake area **1911** of club head **1910**. FIG. 20 illustrates a chart of drag as a function of open face angle with respect to the hosel diameters golf club heads **1910** and **1920**. In some examples, club head **1910** can also comprise a golf club shaft of reduced shaft thickness, such as a shaft thickness of approximately 0.335 inches (approximately 8.5 mm). In the same or other examples, for open-faced orientations of up to 50 degrees, such difference in hosel diameter can amount for up to approximately 0.1 pounds less drag resistance for golf club head **1910** when compared to the larger drag of golf club head **1920**. In the same or other examples, the drag of golf club head **1910** can range from approximately 1.2 pounds at an approximately square orientation, to approximately 0.2 pounds at an open-faced orientation of approximately 50 degrees.

[0119] In the same or other embodiments, the mass and/or mass ratio of the golf coupler mechanisms of FIGS. 1-17 can be minimized with respect to their respective golf club heads when compared to other golf club heads with adjustable shaft coupling mechanisms. For instance, in examples where golf club head **101** (FIGS. 1-4, 8-9) comprises a driver-type

golf club head, the different elements of club head **101** can comprise mass characteristics similar to those summarized below in Table 1.

TABLE 1

Sample Mass Characteristics for Driver-Type Golf Club Head		
	Exemplary Driver Head	Ranges for Driver Heads
Mass of Club Head 101 (Disassembled)	≤192 grams (approx.)	185-205 grams (approx.)
Mass of Sleeve 1100	≤5.2 grams (approx.)	≤6 grams (approx.)
Mass of Sleeve 1100 + Securing Fastener 3400	≤6.8 grams (approx.)	≤7.5 grams (approx.)
Total Assembled Club Head Mass	≤198.8 grams (approx.)	188-213 grams (approx.)

[0120] In such examples, the mass ratios for the golf coupler mechanism **1000** relative to assembled club head **101** can be very low, as summarized below in Table 2.

TABLE 2

Sample Mass Ratios for Driver-Type Golf Club Head		
	Exemplary Driver Head	Ranges for Driver Heads
Mass of Sleeve	≤2.7% (approx.)	≤3% (approx.)
Mass of Disassembled Club Head		
Mass of Sleeve	≤2.6% (approx.)	≤3% (approx.)
Mass of Assembled Club Head		
Mass of (Sleeve + Securing Fastener)	≤3.5% (approx.)	≤4% (approx.)
Mass of Disassembled Club Head		
Mass of (Sleeve + Securing Fastener)	≤3.4% (approx.)	≤4% (approx.)
Mass of Assembled Club Head		

[0121] In other examples, such as where golf club head **101** (FIGS. 1-4, 8-9) comprises a fairway-wood-type golf club head, the different elements of club head **101** can comprise mass characteristics similar to those summarized below in Table 3.

TABLE 3

Sample Mass Characteristics for Fairway-Wood-Type Golf Club Head				
	Exemplary 3-FW Head	Exemplary 5-FW Head	Exemplary 7-FW Head	Ranges for FW Heads
Mass of Club Head 101 (Disassembled)	≤205 grams (approx.)	≤209 grams (approx.)	≤213 grams (approx.)	200-225 grams (approx.)
Mass of Sleeve 1100	≤5.2 grams (approx.)	≤5.2 grams (approx.)	≤5.2 grams (approx.)	≤6 grams (approx.)
Mass of Sleeve 1100 + Securing Fastener 3400	≤6.8 grams (approx.)	≤6.8 grams (approx.)	≤6.8 grams (approx.)	≤7.5 grams (approx.)
Total Assembled Club Head Mass	≤211.8 (approx.)	≤215.8 (approx.)	≤219.8 (approx.)	203-233 grams (approx.)

[0122] In such examples, the mass ratios for the golf coupler mechanism **1000** relative to assembled club head **101** can be very low, as summarized below in Table 4.

TABLE 4

Sample Mass Ratios for Fairway-Wood-Type Golf Club Head				
	Exemplary 3-FW Head	Exemplary 5-FW Head	Exemplary 7-FW Head	Ranges for FW Heads
Mass of Sleeve	≤2.54%	≤2.48%	≤2.44%	≤2.8%
Mass of Disassembled Club Head	(approx.)	(approx.)	(approx.)	(approx.)
Mass of Sleeve	≤2.46%	≤2.41%	≤2.36%	≤2.8%
Mass of Assembled Club Head	(approx.)	(approx.)	(approx.)	(approx.)
Mass of (Sleeve + Securing Fastener)	≤3.32%	≤3.25%	≤3.19%	≤3.5%
Mass of Disassembled Club Head	(approx.)	(approx.)	(approx.)	(approx.)
Mass of (Sleeve + Securing Fastener)	≤3.21%	≤3.16%	≤3.10%	≤3.5%
Mass of Assembled Club Head	(approx.)	(approx.)	(approx.)	(approx.)

[0123] There can be examples where the mass, dimension, and/or location characteristics described above can provide benefits and/or flexibility with respect to the mass distribution and/or location of the center of gravity (CG) for the golf club head. For example, shaft sleeve center of gravity **1150** (FIG. 1) of shaft sleeve **1100** can be configured to be located at shaft sleeve CG vertical distance **1159** (FIG. 1).

[0124] In some examples, such as in embodiments where club head **101** (FIGS. 1-4, 8-9) comprises a driver-type golf club head, shaft sleeve center of gravity **1150** (FIG. 1) of shaft sleeve **1100** can be configured to be located at shaft sleeve CG vertical distance **1159** can be of less than approximately 50 mm above the exterior sole bottom end **10141** of sole **1014** of driver-type club head **101**. In the same or other examples, shaft sleeve CG vertical distance **1159** can be less than approximately 46.2 mm above exterior sole bottom end **10141**. In the same or other examples, shaft sleeve CG vertical distance **1159** can be less than approximately 43.7 mm above the exterior sole bottom end **10141**. Shaft sleeve center of gravity **1150** of shaft sleeve **1100** also can be configured to be located at shaft sleeve CG vertical distance **1059** (FIG. 1) of less than approximately 0.59 inches (approximately 15 mm) above assembled club head center of gravity **1050** (FIG. 1) of driver-type assembled golf club head **101** in some embodiments. In the same or other embodiments, shaft sleeve CG vertical distance **1159** can be at least approximately 7.6 mm greater than assembled club head CG vertical distance **1058** of driver-type club head **101**.

[0125] In other examples, such as in embodiments where club head **101** (FIGS. 1-4, 8-9) comprises a fairway-wood-type golf club head, shaft sleeve center of gravity **1150** (FIG. 1) of shaft sleeve **1100** can be configured to be located at shaft sleeve CG vertical distance **1159** of less than approximately 35.6 mm above exterior sole bottom end of sole **1014** of fairway-wood-type club head **101**. In the same or other examples, shaft sleeve CG vertical distance **1159** can be less than approximately 1.35 inches (approximately 34.3 mm) above exterior sole bottom end **10141** of sole **1014** of fairway-wood-type club head **101**. Shaft sleeve center of gravity **1150** of shaft sleeve **1100** also can be configured to be located at shaft sleeve CG vertical distance **1059** (FIG. 1) of less than approximately 19 mm above assembled club head center of gravity **1050** (FIG. 1) of fairway-wood-type assembled golf club head **101** in some embodiments. In the same or other embodiments, shaft sleeve CG vertical dis-

tance **1159** can be at least approximately 16.5 mm greater than assembled club head CG vertical distance **1058** of fairway-wood-type club head **101**.

[0126] In the present example, as seen in FIG. 1, hosel **1015** comprises hosel axis **1016** extending along a longitudinal centerline of hosel **1015**. Hosel axis **1016** defines hosel lie angle **1018** relative to bottom horizontal axis **1019**, where bottom horizontal axis **1019** is horizontally tangent to sole bottom end **10141**. In some embodiments, hosel lie angle **1018** can be of, for example, approximately 58 degrees. In the present embodiment, shaft sleeve CG vertical distance **1159** and assembled club head CG vertical distance **1058** extend vertically from bottom horizontal axis **1019**.

[0127] Club head **101** also comprises crown height vertical distance **1018** extending vertically to the top end of crown **1017** relative to sole bottom end **10141**. In some embodiments, such as where club head **101** comprises a driver-type golf club head, crown height vertical distance **1018** can be of at least approximately 59.7 mm relative to sole bottom end **10141**. In the same or other embodiments, assembled club head CG vertical distance can be less than approximately 33 mm relative to sole bottom end **10141**.

[0128] There can also be examples, such as seen in FIG. 1, where receiver top end **1032** is at the top of hosel **1015** and is configured to remain below the top end of crown **1017** of golf club head **101**. Hosel **1015** can be devoid of a cylindrical external top section in the same or other embodiments, where crown **1017** can transition to the substantially circular external perimeter at receiver top end **1032** of hosel **1015** without defining a cylindrical external shape for hosel **1015**. Such features can permit location of the center of gravity of shaft sleeve **1100** closer to the center of gravity of assembled golf club head **101**.

[0129] Backtracking though the figures, FIG. 18 illustrates a flowchart for a method **18000**, which can be used to provide, form, and/or manufacture a golf coupler mechanism in accordance with the present disclosure. In some examples, the golf coupler mechanism can be similar to golf coupler mechanism **1000** of FIGS. 1-11 and 14-16, or the golf coupler mechanism of FIGS. 12-13.

[0130] Method **18000** comprises block **18100** for providing a shaft sleeve to couple with an end of a golf club shaft and comprising a sleeve arcuate coupler set. In some examples, the shaft sleeve can be similar to shaft sleeve **1100** (FIGS. 1-7, 10, 14-16) and/or to shaft sleeve **12100** (FIG. 12), and the golf club shaft can be similar to golf club shaft **102** (FIGS. 1, 5). In the same or other examples, the sleeve

arcuate coupler set can be similar to sleeve coupler set **3110** (FIGS. 3-7, **10**, **14-17**) and/or to sleeve coupler set **12110** (FIG. **12**).

[0131] Block **18200** of method **18000** comprises providing a shaft receiver of a golf club head, comprising a receiver arcuate coupler set configured to couple with the sleeve arcuate coupler set of the shaft sleeve. In some examples, the shaft receiver can be similar to shaft receiver **3200** (FIGS. 3-4, 8-9, **11**, **14-17**) and/or to shaft receiver **13200** (FIG. **13**). The receiver arcuate coupler set can be similar to receiver coupler set **3210** (FIGS. 3-4, 8-9, **11**, **14-17**) and/or to receiver coupler set **13210** (FIG. **13**).

[0132] Block **18300** of method **18000** comprises providing a securing fastener configured to secure the shaft sleeve to the shaft receiver. In some examples, the securing fastener can be similar to securing fastener **3400** (FIGS. 3-4). The securing fastener can be configured to pull the shaft sleeve towards the shaft receiver to seat the sleeve arcuate coupler set against the receiver arcuate coupler set.

[0133] In some examples, one or more of the different blocks of method **18000** can be combined into a single block or performed simultaneously, and/or the sequence of such blocks can be changed. For example, in some embodiments, blocks **18200** and **18300** may be combined if desired. In the same or other examples, some of the blocks of method **18000** can be subdivided into several sub-blocks. As an example, block **18100** may comprise a sub-block for forming horizontal radii of curvature for the arcuate surfaces of the sleeve couplers of the sleeve arcuate coupler set, and a sub-block for forming vertical taperings for the arcuate surfaces of the sleeve couplers of the sleeve arcuate coupler set. There can also be examples where method **18000** can comprise further or different blocks. As an example, method **18000** may comprise another block for providing the golf club head for the shaft receiver of block **18200**, and/or another block for providing the shaft for the shaft sleeve of block **18100**. In addition, there may be examples where method **18000** can comprise only part of the steps described above. For instance, block **18300** may be optional in some implementations. Other variations can be implemented for method **18000** without departing from the scope of the present disclosure.

Slot Cap Golf Coupling Mechanism

[0134] Turning ahead in the drawings, FIG. **21** illustrates a front perspective view of golf club head **21101** with golf coupling mechanism **211000**, according to an embodiment. In many embodiments, golf coupling mechanism **211000** can comprise shaft sleeve **211100** configured to be coupled to an end of a golf club shaft, such as golf club shaft **21102**. In various embodiments, golf club head **21101** can be similar to golf club head **101** (FIG. **1**); golf coupling mechanism **211000** can be similar to golf coupling mechanism **1000** (FIG. **1**); and/or golf club shaft **21102** can be similar or identical to golf club shaft **102** (FIG. **1**). Accordingly, golf coupling mechanism **211000** can comprise shaft sleeve **211100** and shaft receiver **213200**. Meanwhile, shaft sleeve **211100** can be similar to shaft sleeve **1100** (FIG. **1**), and/or shaft receiver **213200** can be similar to shaft receiver **3200** (FIG. **3**).

[0135] Turning ahead again in the drawings, FIG. **22** illustrates a side view of shaft sleeve **211100** decoupled from golf club head **21101** (FIG. **21**), according to the embodiment of FIG. **21**. FIG. **22A** illustrates a cross-sectional side

view of golf club head **21101** with shaft sleeve **211100** removed, showing a side cross section of shaft receiver **213200** with asymmetric lobes. FIG. **22B** illustrates a side cross-sectional view of a portion of a receiver coupler set of the shaft receiver, wherein the asymmetric lobes comprise different vertical taperings resulting in different lobe lengths. Meanwhile, FIG. **23** illustrates a cross sectional view of shaft sleeve **211100** along line XXIII-XXIII of FIG. **22**, according to the embodiment of FIG. **21**.

[0136] Referring to FIG. **22**, shaft sleeve **211100** comprises shaft sleeve body **22103** and shaft sleeve cap **22104**. Further, in many embodiments, shaft sleeve body **22103** can comprise sleeve coupler set **223110** with one or more couplers protruding from sleeve body outer wall **223130**, and shaft receiver **213200** (FIG. **21**) can comprise a receiver coupler **213210** (FIG. **22B**) set configured to engage sleeve coupler set **223110** of shaft sleeve **211100** to restrict a rotation of shaft sleeve **211100** relative to shaft receiver **213200**. In these or other embodiments, sleeve coupler set **213110** can be similar to sleeve coupler set **3110** (FIG. **3**); sleeve body outer wall **223130** can be similar to sleeve outer wall **3130** (FIG. **3**); and/or the receiver coupler set can be similar to receiver coupler set **3210** (FIG. **3**). Shaft sleeve **211100** is configured to be inserted into shaft receiver **223200**, such that receiver couplers **213213**, **218217**, and **213214**, shown in FIG. **22A**, comprise arcuate surfaces **213253**, **213257**, and **213254**, shown in FIG. **22B**, that correspond to the arcuate surfaces sleeve coupler set **223110**. For example, as shown in FIG. **22B**, arcuate surfaces **213253**, **213257**, and **213254** of receiver couplers **213213**, **218217**, and **213214** comprise vertical taperings **211283**, **211287**, and **211284**, which are complementary with vertical taperings of the sleeve couplers of sleeve coupler set **223110**. As explained in greater detail below, in many embodiments, shaft sleeve cap **22104** can comprise a ferrule and can be operable to couple shaft sleeve body **22103** with golf club shaft **21102** (FIG. **21**).

[0137] Meanwhile, turning now to FIG. **23**, shaft sleeve **211100** can comprise: (i) shaft bore **233120** configured to receive an end of golf club shaft **21102** (FIG. **21**), (ii) securing fastener bore **23105** at sleeve body bottom end **233192**, (iii) bore bottom surface **23111**; and/or (iv) shaft sleeve top end **231191**. Securing fastener bore **23105** can be configured to receive a securing fastener (not shown) in order to secure shaft sleeve **211100** to shaft receiver **213200** (FIG. **21**). Further, bore bottom surface **23111** can comprise a bottom surface (e.g., deepest surface) of shaft bore **232120**. In many embodiments, shaft bore **233120** can be similar to shaft bore **3120** (FIG. **3**); securing fastener bore **23105** can be similar or identical to the bore configured to receive securing fastener **3400** (FIG. **3**); sleeve body bottom end **233192** can be similar or identical to sleeve bottom end **3192** (FIG. **3**); the securing fastener can be similar or identical to securing fastener **3400** (FIG. **3**); and/or shaft sleeve top end **231191** can be similar or identical to sleeve top end **1191** (FIG. **3**).

[0138] Further, when shaft sleeve body **22103** is coupled to shaft sleeve cap **22104**, shaft sleeve **211100** can comprise shaft sleeve height **23119**, shaft sleeve body height **23210**, shaft sleeve cap height **23121**, and shaft sleeve cap top height **23122**. Shaft sleeve height **23119** can refer to a distance from sleeve body bottom end **233192** to shaft sleeve top end **231191** measured approximately perpendicular to sleeve body bottom end **233192**. Meanwhile, shaft

sleeve body height **23120** can refer to a distance from sleeve body bottom end **233192** to a top end of shaft sleeve body **22103** measured parallel to shaft sleeve height **23119**, and shaft sleeve cap height **23121** can refer to a distance from a bottom of shaft sleeve cap **22104** to shaft sleeve top end **231191** measured parallel to shaft sleeve height **23119**. Further, shaft sleeve cap top height **23122** can refer to a difference between shaft sleeve height **23119** and shaft sleeve body height **23120**.

[0139] For example, shaft sleeve height **23119** can be greater than or equal to approximately 1.78 inches and less than or equal to approximately 1.82 inches. In specific examples, shaft sleeve height **23119** can be approximately 1.8 inches.

[0140] Further, shaft sleeve body height **23120** can be greater than or equal to approximately 1.527 inches and less than or equal to approximately 1.567 inches. In specific examples, shaft sleeve body height **23120** can be approximately 1.547 inches.

[0141] Further still, shaft sleeve cap height **23121** can be greater than or equal to approximately 0.43 inches and less than or equal to approximately 0.47 inches. In specific examples, shaft sleeve cap height **23121** can be approximately 0.45 inches.

[0142] Meanwhile, for example, shaft sleeve cap top height **23122** can be greater than or equal to approximately 0.23 inches and less than or equal to approximately 0.27 inches. In specific examples, shaft sleeve body height **23122** can be approximately 0.25 inches.

[0143] In some embodiments, the securing fastener (not shown) for insertion into securing fastener bore **23105** can comprise titanium over steel. Further, the securing fastener can comprise a securing fastener mass. The securing fastener mass can be greater than or equal to approximately 2.7 grams.

[0144] Turning to the next drawing, FIG. 24 illustrates a side view of shaft sleeve body **22103** decoupled from shaft sleeve cap **22104** (FIG. 22), according to the embodiment of FIG. 21. Shaft sleeve body **22103** can be associated with one or more regions **24106**. For example, regions **24106** can comprise fastener region **24107**, intermediate region **24108**, coupler region **24109**, and cap interface region **24110**.

[0145] Fastener region **24107** can refer to a portion of shaft sleeve body **22103** located between sleeve body bottom end **233192** and bore bottom surface **23111** (FIG. 23). Meanwhile, coupler region **24109** can refer to a portion of shaft sleeve body located from a lowest point of sleeve coupler set **223110** (e.g., a point of sleeve coupler set **223110** closest to sleeve body bottom end **233192** (FIG. 23)) to a highest point of sleeve coupler set **223110** (e.g., a point of sleeve coupler set **223110** farthest from sleeve body bottom end **233192**). Meanwhile, intermediate region **24108** can refer to a portion of shaft sleeve body **22103** between fastener region **24107** and coupler region **24109**, and cap interface region **24110** can refer to a portion of shaft sleeve body **22103** opposite coupler region **24109** with respect to intermediate region **24108**.

[0146] When golf club head **21101** (FIG. 21) is being swung and/or operated to hit a golf ball, fastener region **24107** and coupler region **24109** can experience high stresses. Meanwhile, intermediate region **24108** and/or cap interface region **24110** can experience stresses lower than the high stresses experienced by fastener region **24107** and coupler region **24109**.

[0147] Securing shaft sleeve **211100** (FIG. 21) to shaft receiver **213200** (FIG. 21) with the securing fastener can help to offset the high stresses at fastener region **24107**. Further, because of the high stresses that can be experienced at coupler region **24109**, the coupler(s) of sleeve coupler set **223110** can comprise solid lobes configured to provide additional thickness to a sleeve body wall of shaft sleeve body **22103**. Accordingly, the coupler(s) can reinforce the sleeve body wall at coupler region **24109** to offset these the high stresses at coupler region **24109**. The coupler(s) of sleeve coupler set **223110** can slope (e.g., linearly or curvilinearly) with a greatest thickness at an end of coupler region **24109** farthest from sleeve body bottom end **233192** (e.g., where coupler region **24109** interfaces with cap interface region **24110**) and with a least thickness at an end of coupler region **24109** nearest sleeve body bottom end **233192** (FIG. 23) (e.g., where coupler region **24109** interfaces with intermediate region **24108**). For example, the greatest thickness can be approximately 0.75 inch thick, and the least thickness can be approximately 0.020 inch thick. In many embodiments, sloping the coupler(s) of sleeve coupler set **223110** (FIG. 22) can provide continuity (e.g., smooth transitioning in thickness) between intermediate region **24108** and cap interface region **24110**.

[0148] In some embodiment, the coupler(s) of sleeve couple set **223110** can be symmetric in profile. A length of the coupler(s) of sleeve coupler set **223110** can be less than or equal to approximately 0.38 inch (e.g., at part of the sleeve body outer wall **223130** of shaft sleeve body **22103**) and can be greater than or equal to approximately 0.26 inch (e.g., at another part of the sleeve body outer wall **223130** of shaft sleeve body **22103**).

[0149] In some embodiments, the coupler(s) of sleeve coupler set **223110** can be asymmetric in profile such that the coupler(s) are longer at a first part of sleeve body outer wall **223130** of shaft sleeve body **22103** than at another part (e.g., a part directly or 180 degrees opposite the first part). A length of the coupler(s) of sleeve coupler set **223110** can be less than or equal to approximately 0.38 inch (e.g., at part of the sleeve body outer wall **223130** of shaft sleeve body **22103**) and can be greater than or equal to approximately 0.260 inch (e.g., at another part of the sleeve body outer wall **223130** of shaft sleeve body **22103**). In many embodiments, the coupler(s) of sleeve coupler set **223110** (FIG. 22) can be longest at a part of the sleeve body outer wall **223130** of shaft sleeve body **22103** closest to a sleeve axis of shaft sleeve body **22103** at an end of coupler region **24109** farthest from sleeve body bottom end **233192** (e.g., where coupler region **24109** interfaces with cap interface region **24110**). The sleeve axis can be similar or identical to sleeve axis **5150** (FIG. 5). Said another way, the coupler(s) of sleeve coupler set **223110** (FIG. 22) can be longest at a part of the sleeve body outer wall **223130** of shaft sleeve body **22103** that intersects a plane including the sleeve axis and extending approximately perpendicular to sleeve body bottom end **233192**.

[0150] Meanwhile, because intermediate region **24108** experiences lower stresses when golf club head **21101** is being swung and/or operated to hit a golf ball, a sleeve body wall of shaft sleeve body can be thinner at intermediate region **24108** than at part or all of coupler region **24109**, and/or intermediate region **24108** can have holes or recesses to reduce the weight of intermediate region **24108**. For example, the sleeve body wall of shaft sleeve body **22103** at

intermediate region **24108** can comprise a thickness (e.g., an average thickness) of approximately 0.020 inch.

[0151] Turning now back to FIG. 23, in some embodiments, shaft bore **233120** can comprise a width (e.g., diameter) of approximately 0.346 inches. In these embodiments, the width can comprise an average width and/or can be approximately constant throughout shaft bore **233120**.

[0152] In various embodiments, shaft sleeve body **22103** can comprise etching channels **23112** at shaft bore **233120** to provide a better surface area for epoxy bonding golf club shaft **21102** (FIG. 21) to shaft sleeve body **22103**. Etching channels **23112** can be located at coupler region **24109** (FIG. 24) and/or at part or all of intermediate region **24108** (FIG. 24), such as, for example, at a half of intermediate region **24108** (FIG. 24) closer to coupler region **24109** (FIG. 24).

[0153] In these or other embodiments, shaft sleeve body **22103** can comprise receiving groove **23113** (e.g., an undercut notch). As explained in greater detail below, receiving groove **23113** can communicate and interlock with extrusion portion **25114** (FIG. 25) of shaft sleeve cap **22104** to secure shaft sleeve cap **22104** to shaft sleeve body **22103**. Thus, in many embodiments, receiving groove **23113** can complement extrusion portion **25114** (FIG. 25). In some embodiments, receiving groove **23113** can be located at cap interface region **24110** (FIG. 24). In many embodiments, receiving groove **23113** can be located at an interface of cap interface region **24110** (FIG. 24) and coupler region **24109** (FIG. 24).

[0154] Turning ahead now in the drawings, FIG. 25 illustrates a side view of shaft sleeve cap **22104** decoupled from shaft sleeve body **22103** (FIG. 22), according to the embodiment of FIG. 21.

[0155] In some embodiments, shaft sleeve cap **22104** can comprise cap wall **25115**. Further, cap wall **25115** can comprise extrusion portion **25114** and one or more slits **25116**.

[0156] Extrusion portion **25114** can comprise a lip extending out from cap wall **25115**, such as, for example, at an end of cap wall **25115**. Accordingly, extrusion portion **25114** can comprise a width (e.g., diameter) greater than a width (e.g., diameter) of a remainder of cap wall **25115** and/or of shaft bore **233120**.

[0157] Meanwhile, slit(s) **25116** can permit cap wall **25115** (e.g., extrusion portion **25114**) to elastically (e.g., temporarily) compress (e.g., axially) and draw toward itself when shaft sleeve cap **22104** is being coupled to and being decoupled from shaft sleeve body **22103** (FIG. 22). Accordingly, extrusion portion **25114** can be situated in and out of receiving groove **23113** (FIG. 23) to couple and decouple shaft sleeve cap **22104** to and from shaft sleeve body **22103** (FIG. 22). In these embodiments, extrusion portion **25114** can be operable as a locking feature to lock or snap into position the shaft sleeve cap **22104**.

[0158] Shaft sleeve cap **22104** can be further operable to provide damping (e.g., vibration and/or stress reduction) between golf club shaft **21102** (FIG. 21) and shaft sleeve body **22103** (FIG. 22). For example, shaft sleeve cap **22104** can act as a “shaft pillow” by increasing a concentricity of golf club shaft **21102** (FIG. 21) within shaft sleeve body **22103** (FIG. 22). In many embodiments, the concentricity of golf club shaft **21102** (FIG. 21) within shaft sleeve body **22103** (FIG. 22) can be strongly correlated with a durability of golf club shaft **21102** (FIG. 21). Accordingly, shaft sleeve

cap **22104** can prevent breakage of golf club shaft **21102** (FIG. 21) and increase an overall life of golf club head **21101** (FIG. 21).

[0159] Turning ahead in the drawings, FIG. 26 illustrates an elevational view of shaft sleeve cap **22104** decoupled from shaft sleeve body **22103** (FIG. 22), according to the embodiment of FIG. 21. In many embodiments, shaft sleeve cap **22104** can comprise cap bore **26116**, cap bore width **26117**, and one or more centering features **26118**. In some embodiments, shaft bore **233120** (FIG. 23) also can comprise cap bore width **26117**. Cap bore width **26117** can refer to a width (e.g., diameter) of cap bore **26116**. In these embodiments, the width can comprise an average width (e.g., average diameter).

[0160] Cap bore width **26117** can be greater than a width (e.g., diameter) of golf club shaft **21102** (FIG. 21). Dissimilarity in cap bore width **26117** and the width of golf club shaft **21102** (FIG. 21) can result in shaft orientation inconsistencies. Accordingly, to prevent misalignment of golf club shaft **21102** (FIG. 21), centering feature(s) **26118** can be extruded from an interior surface of cap bore **26116**. A distance that centering feature(s) **26118** extends from the interior surface of cap bore **26116** can be at least enough so that a collective magnitude will provide an effective width (e.g., diameter) within cap bore **26116** that is approximately less than or equal to the width of golf club shaft **21102** (FIG. 21). Cap bore width **26117** is greater than the effective width of cap bore **26116** resulting from centering feature(s) **26118**. Further, cap bore width **26117** can be similar or identical to the width of shaft bore **233120** (FIG. 23). Therefore, when golf club shaft **21102** (FIG. 21) is introduced to shaft sleeve cap **22104** and shaft sleeve body **22103** (FIG. 23), centering feature(s) **26118** are operable to approximately center golf club shaft **21102** (FIG. 21) in cap bore **26116** and about the sleeve axis described above.

[0161] Turning back to FIG. 22, shaft sleeve body **22103** can comprise any suitable material. For example, in some embodiments, shaft sleeve body **22103** can comprise a metal or metal alloy (e.g., an aluminum alloy). In these examples, the aluminum alloy can comprise greater than or equal to approximately 70% aluminum and less than or equal to approximately 75% aluminum. In more specific examples, the aluminum alloy can comprise approximately 70%, 71%, 72%, 73%, 74%, or 75% aluminum. Likewise, shaft sleeve cap **22104** can comprise any suitable material configured to permit cap wall **25115** (FIG. 25) to elastically compress as described above. For example, shaft sleeve cap **22104** can comprise a polymer material.

[0162] In many embodiments, shaft sleeve body **22103** can comprise a shaft sleeve body mass, and shaft sleeve cap **22104** can comprise a shaft sleeve cap mass. Further, shaft sleeve **211100** can comprise a shaft sleeve mass comprising the shaft sleeve body mass and the shaft sleeve cap mass. The shaft sleeve mass can be similar to the mass of the sleeve described above with respect to sleeve **1100** (FIG. 1).

[0163] In these or other embodiments, the shaft sleeve mass can be greater than or equal to approximately 4.3 grams. Further, the shaft sleeve body mass can be greater than or equal to approximately 3.3 grams and less than or equal to approximately 3.8 grams. Further still, the shaft sleeve cap mass can be greater than or equal to approximately 0.5 grams and less than or equal to approximately 1.0 grams. In various embodiments, the shaft sleeve mass can be approximately 0.5 grams less than the mass of sleeve **1100**

(FIG. 1). Further, the shaft sleeve mass combined with the securing fastener mass can be greater than or equal to approximately 7 grams. According, in various embodiments, shaft sleeve **211100** can offer weight advantages over shaft sleeve **1100** (FIG. 1).

[0164] Turning to FIG. 21, golf club head **21101** can comprise a disassembled club head mass and an assembled club head mass. The disassembled club head mass can be similar to the disassembled club head mass described above with respect to golf club head **101** (FIG. 1), and the assembled club head mass can be similar to the assembled club head mass described above with respect to golf club head **101** (FIG. 1).

[0165] In some embodiments, the disassembled club head mass can be greater than or equal to approximately 185 grams and less than or equal to approximately 205 grams. In these or other embodiments, the disassembled club head mass can be greater than or equal to approximately 192 grams.

[0166] In some embodiments, the assembled club head mass can be greater than or equal to approximately 188 grams and less than or equal to approximately 213 grams. In these or other embodiments, the assembled club head mass can be greater than or equal to approximately 199 grams.

[0167] Further, a ratio of the shaft sleeve mass to the disassembled club head mass can be less than or equal to approximately 2.0%, 2.2%, or 2.4%; a ratio of the shaft sleeve mass to the assembled club head mass can be less than or equal to approximately 1.95%, 2.16%, or 2.35%; a ratio of the shaft sleeve mass and the securing fastener mass to the disassembled club head mass can be less than or equal to approximately 3.4%, 3.6%, or 3.8%; and/or a ratio of the shaft sleeve mass and the securing fastener mass to the assembled club head mass can be less than or equal to approximately 3.3%, 3.5%, or 3.7%.

[0168] Meanwhile, golf club head **21101** can comprise an assembled club head CG associated with assembled club head CG vertical distance, and shaft sleeve **211100** can comprise a shaft sleeve CG associated with a shaft sleeve CG vertical distance. In these embodiments, assembled club head CG can be similar or identical to assembled club head CG **1050** (FIG. 1); the assembled club head CG vertical distance can be similar or identical to assembled club head CG vertical distance **1058** (FIG. 1); the shaft sleeve CG can be similar or identical to shaft sleeve CG **1032** (FIG. 1); and/or the shaft sleeve CG vertical distance can be similar or identical to shaft sleeve CG vertical distance **1159** (FIG. 1). In many embodiments, the shaft sleeve CG vertical distance can be greater than or equal to approximately 0.010 inch (approximately 0.254 millimeter) and less than or equal to approximately 0.050 inch (approximately 1.27 millimeter) less than shaft sleeve CG vertical distance **1159** (FIG. 1). For example, the shaft sleeve CG vertical distance can be greater than or equal to approximately 44.9 millimeters from a sole bottom end of golf club head **21101** and less than or equal to approximately 46 millimeters from the sole bottom end of golf club head **21101**. In specific examples, the shaft sleeve CG vertical distance can be greater than or equal to approximately 44.9 millimeters, 45.0 millimeters, 45.1 millimeters, 45.2 millimeters, 45.3 millimeters, 45.4 millimeters, 45.5 millimeters, 45.6 millimeters, 45.7 millimeters, 45.8 millimeters, 45.9 millimeters, 46.0 millimeters from the sole bottom end of golf club head **21101**. In some embodiments, the shaft sleeve CG vertical distance of the golf coupling

mechanism **211000** can be less than or equal to approximately 44.9 millimeters, 45.0 millimeters, 45.1 millimeters, 45.2 millimeters, 45.3 millimeters, 45.4 millimeters, 45.5 millimeters, 45.6 millimeters, 45.7 millimeters, 45.8 millimeters, 45.9 millimeters, or 46.0 millimeters from the sole bottom end of golf club head **41101**. The shaft sleeve CG vertical distance of the golf coupling mechanism **411000** can be 44.9 millimeters from the sole bottom end of golf club head **41101**. The sole bottom end can be similar or identical to sole bottom end **10141** (FIG. 1).

[0169] Turning ahead in the drawings, FIG. 27 illustrates a flowchart for a method **27000**, according to an embodiment. In many embodiments, method **27000** can comprise a method of manufacturing a golf club head of one or more parts of the golf club head. The golf club head can be similar or identical to golf club head **21101** (FIG. 21).

[0170] Method **27000** can comprise activity **27001** of providing a shaft sleeve. The shaft sleeve can be similar or identical to shaft sleeve **211100** (FIG. 21). FIG. 28 illustrates an exemplary activity **27001**, according to the embodiment of FIG. 27.

[0171] For example, in FIG. 28, activity **27001** can comprise activity **28001** of providing (e.g., manufacturing) a shaft sleeve body. The shaft sleeve body can be similar or identical to shaft sleeve body **22103** (FIG. 22).

[0172] Further, activity **27002** can comprise activity **28002** of providing (e.g., manufacturing) a shaft sleeve cap. The shaft sleeve cap can be similar or identical to shaft sleeve cap **22104** (FIG. 22).

[0173] Referring now back to FIG. 27, method **27000** can comprise activity **27002** of providing (e.g., manufacturing) a golf club head. The golf club head can be similar or identical to golf club head **21101** (FIG. 21). In some embodiments, activity **27001** can be performed before activity **27002**, and vice versa. In other embodiments, activity **27001** and **27002** can be performed approximately simultaneously. [0174] Further, method **27000** can comprise activity **27003** of inserting the shaft sleeve into a hosel bore of the golf club head. The hosel bore can be similar or identical to the hosel bore described above with respect to golf club head **21101** (FIG. 21).

[0175] Also, method **2700** can comprise activity **27004** of inserting a golf club shaft into a shaft bore. The golf club shaft can be similar or identical to golf club shaft **21102** (FIG. 21), and the shaft bore can be similar or identical to shaft bore **233120** (FIG. 23).

[0176] Meanwhile, method **2700** can comprise activity **27005** of inserting the shaft sleeve cap into the shaft bore. In some embodiments, activity **27004** can be performed before activity **27005**, or vice versa.

[0177] In other embodiments, activity **27004** and **27005** can be performed approximately simultaneously. In further embodiments, activity **27003** can be performed before activity **27004** and/or activity **27005**, and vice versa. In many embodiments, one or more of activities **27001-27003** can be performed before one or more of activities **27004-27005**, or vice versa.

[0178] Further still, method **27000** can comprise activity **27006** of securing the shaft sleeve to a hosel of the golf club head with a fastener. The hosel can be similar or identical to the hosel described above with respect to golf club head **21101** (FIG. 21), and the fastener can be similar or identical to the fastener described above with respect to golf club head **21101** (FIG. 21).

Solid Ribbed Cap Coupling Mechanism

[0179] Turning ahead in the drawings, FIG. 29 illustrates a front perspective view of golf club head 41101 with golf coupling mechanism 411000, according to an embodiment. In many embodiments, golf coupling mechanism 411000 can comprise shaft sleeve 411100 configured to be coupled to an end of a golf club shaft, such as golf club shaft 41102. In various embodiments, golf club head 41101 can be similar to golf club head 101 (FIG. 1); golf coupling mechanism 411000 can be similar to golf coupling mechanism 1000 (FIG. 1); and/or golf club shaft 41102 can be similar or identical to golf club shaft 102 (FIG. 1). Accordingly, golf coupling mechanism 411000 can comprise shaft sleeve 411100 and shaft receiver 413200. Meanwhile, shaft sleeve 411100 can be similar to shaft sleeve 1100 (FIG. 1), and/or shaft receiver 413200 can be similar to shaft receiver 3200 (FIG. 3).

[0180] Turning ahead again in the drawings, FIG. 30 illustrates a side view of shaft sleeve 411100 decoupled from golf club head 21101 (FIG. 29), according to the embodiment of FIG. 29. Meanwhile, FIG. 31 illustrates a cross sectional view of shaft sleeve 411100 along line XXXIII-XXXIII of FIG. 30, according to the embodiment of FIG. 29.

[0181] Referring to FIG. 30, shaft sleeve 411100 comprises shaft sleeve body 42103 and shaft sleeve cap 42104. Further, in many embodiments, shaft sleeve body 22103 can comprise sleeve coupler set 423110 with one or more couplers protruding from sleeve body outer wall 423130, and shaft receiver 413200 (FIG. 29) can comprise a receiver coupler set configured to engage sleeve coupler set 423110 of shaft sleeve 411100 to restrict a rotation of shaft sleeve 411100 relative to shaft receiver 413200. In these or other embodiments, sleeve coupler set 413110 can be similar to sleeve coupler set 3110 (FIG. 3); sleeve body outer wall 423130 can be similar to sleeve outer wall 3130 (FIG. 3); and/or the receiver coupler set can be similar to receiver coupler set 3210 (FIG. 3). As explained in greater detail below, in many embodiments, shaft sleeve cap 42104 can comprise a ferrule and can be operable to couple shaft sleeve body 42103 with golf club shaft 41102 (FIG. 29).

[0182] Meanwhile, turning now to FIG. 31, shaft sleeve 411100 can comprise: (i) shaft bore 433120 configured to receive an end of golf club shaft 41102 (FIG. 29), (ii) securing fastener bore 43105 at sleeve body bottom end 433192, (iii) bore bottom surface 43111; (iv) a cap bore 42110 configured to receive an end of the golf club shaft 41102 and couple to the shaft bore 433120 and/or (v) shaft sleeve top end 431191. Securing fastener bore 43105 can be configured to receive a securing fastener (not shown) in order to secure shaft sleeve 411100 to shaft receiver 413200 (FIG. 29). Further, bore bottom surface 43111 can comprise a bottom surface (e.g., deepest surface) of shaft bore 432120. In many embodiments, shaft bore 433120 can be similar to shaft bore 3120 (FIG. 3); securing fastener bore 43105 can be similar or identical to the bore configured to receive securing fastener 3400 (FIG. 3); sleeve body bottom end 433192 can be similar or identical to sleeve bottom end 3192 (FIG. 3); the securing fastener can be similar or identical to securing fastener 3400 (FIG. 3); and/or shaft sleeve top end 431191 can be similar or identical to sleeve top end 1191 (FIG. 3).

[0183] Further, when shaft sleeve body 42103 is coupled to shaft sleeve cap 42104, shaft sleeve 411100 can comprise shaft sleeve height 43119, shaft sleeve body height 43120,

shaft sleeve cap height 43121, and shaft sleeve cap top height 23122. Shaft sleeve height 43119 can refer to a distance from sleeve body bottom end 433192 to shaft sleeve top end 431191 measured approximately perpendicular to sleeve body bottom end 433192. Meanwhile, shaft sleeve body height 43120 can refer to a distance from sleeve body bottom end 433192 to a top end of shaft sleeve body 42103 measured parallel to shaft sleeve height 43119, and shaft sleeve cap height 43121 can refer to a distance from a bottom of shaft sleeve cap 42104 to shaft sleeve top end 431191 measured parallel to shaft sleeve height 43119. Further, shaft sleeve cap top height 43122 can refer to a difference between shaft sleeve height 43119 and shaft sleeve body height 43120.

[0184] For example, shaft sleeve height 43119 can be greater than or equal to approximately 1.78 inches and less than or equal to approximately 1.82 inches. In specific examples, shaft sleeve height 43119 can be approximately 1.8 inches.

[0185] Further, shaft sleeve body height 43120 can be greater than or equal to approximately 1.529 inches and less than or equal to approximately 1.569 inches. In specific examples, shaft sleeve body height 43120 can be approximately 1.549 inches.

[0186] Further still, shaft sleeve cap height 43121 can be greater than or equal to approximately 0.46 inches and less than or equal to approximately 0.50 inches. In specific examples, shaft sleeve cap height 43121 can be approximately 0.48 inches.

[0187] Meanwhile, for example, shaft sleeve cap top height 43122 can be greater than or equal to approximately 0.23 inches and less than or equal to approximately 0.27 inches. In specific examples, shaft sleeve body height 23122 can be approximately 0.25 inches.

[0188] In some embodiments, the securing fastener (not shown) for insertion into securing fastener bore 23105 can comprise titanium over steel. Further, the securing fastener can comprise a securing fastener mass. The securing fastener mass can be greater than or equal to approximately 2.7 grams.

[0189] Turning to the next drawing, FIG. 32 illustrates a side view of shaft sleeve body 42103 decoupled from shaft sleeve cap 42104 (FIG. 30), according to the embodiment of FIG. 29. Shaft sleeve body 42103 can be associated with one or more regions 44106. For example, regions 44106 can comprise fastener region 44107, intermediate region 44108, coupler region 44109, and cap interface region 44110.

[0190] Fastener region 44107 can refer to a portion of shaft sleeve body 42103 located between sleeve body bottom end 433192 and bore bottom surface 43111 (FIG. 31). Meanwhile, coupler region 44109 can refer to a portion of shaft sleeve body located from a lowest point of sleeve coupler set 423110 (e.g., a point of sleeve coupler set 423110 closest to sleeve body bottom end 433192 (FIG. 31)) to a highest point of sleeve coupler set 423110 (e.g., a point of sleeve coupler set 423110 farthest from sleeve body bottom end 433192). Meanwhile, intermediate region 44108 can refer to a portion of shaft sleeve body 42103 between fastener region 44107 and coupler region 44109, and cap interface region 44110 can refer to a portion of shaft sleeve body 42103 opposite coupler region 44109 with respect to intermediate region 44108. Further referring to FIG. 32, the cap interface region 44110 (FIG. 32) can further comprise a top ring 44115 (FIG. 32).

[0191] When golf club head **41101** (FIG. 29) is being swung and/or operated to hit a golf ball, fastener region **44107** and coupler region **44109** can experience high stresses. Meanwhile, intermediate region **44108** and/or cap interface region **44110** can experience stresses lower than the high stresses experienced by fastener region **44107** and coupler region **44109**.

[0192] Securing shaft sleeve **411100** (FIG. 29) to shaft receiver **413200** (FIG. 29) with the securing fastener can help to offset the high stresses at fastener region **44107**. Further, because of the high stresses that can be experienced at coupler region **44109**, the coupler(s) of sleeve coupler set **423110** can comprise solid lobes configured to provide additional thickness to a sleeve body wall of shaft sleeve body **42103**. Accordingly, the coupler(s) can reinforce the sleeve body wall at coupler region **44109** to offset these high stresses at coupler region **44109**. The coupler(s) of sleeve coupler set **423110** can slope (e.g., linearly or curvedly) with a greatest thickness at an end of coupler region **44109** farthest from sleeve body bottom end **433192** (e.g., where coupler region **44109** interfaces with cap interface region **44110**) and with a least thickness at an end of coupler region **44109** nearest sleeve body bottom end **433192** (FIG. 31) (e.g., where coupler region **44109** interfaces with intermediate region **44108**). For example, the greatest thickness can be approximately 0.75 inch thick, and the least thickness can be approximately 0.020 inch thick. In many embodiments, sloping the coupler(s) of sleeve coupler set **423110** (FIG. 30) can provide continuity (e.g., smooth transitioning in thickness) between intermediate region **44108** and cap interface region **44110**.

[0193] In some embodiment, the coupler(s) of sleeve coupler set **423110** can be symmetric in profile. A length of the coupler(s) of sleeve coupler set **423110** can be less than or equal to approximately 0.38 inch (e.g., at part of the sleeve body outer wall **423130** of shaft sleeve body **42103**) and can be greater than or equal to approximately 0.26 inch (e.g., at another part of the sleeve body outer wall **423130** of shaft sleeve body **42103**).

[0194] In some embodiments, the coupler(s) of sleeve coupler set **423110** can be asymmetric in profile such that the coupler(s) are longer at a first part of sleeve body outer wall **423130** of shaft sleeve body **42103** than at another part (e.g., a part directly or 180 degrees opposite the first part). A length of the coupler(s) of sleeve coupler set **423110** can be less than or equal to approximately 0.38 inch (e.g., at part of the sleeve body outer wall **423130** of shaft sleeve body **42103**) and can be greater than or equal to approximately 0.260 inch (e.g., at another part of the sleeve body outer wall **423130** of shaft sleeve body **42103**). In many embodiments, the coupler(s) of sleeve coupler set **423110** (FIG. 30) can be longest at a part of the sleeve body outer wall **423130** of shaft sleeve body **42103** closest to a sleeve axis of shaft sleeve body **42103** at an end of coupler region **44109** (FIG. 32) farthest from sleeve body bottom end **433192** (e.g., where coupler region **44109** interfaces with cap interface region **44110**). The sleeve axis can be similar or identical to sleeve axis **5150** (FIG. 5). Said another way, the coupler(s) of sleeve coupler set **423110** (FIG. 30) can be longest at a part of the sleeve body outer wall **423130** of shaft sleeve body **42103** that intersects a plane including the sleeve axis and extending approximately perpendicular to sleeve body bottom end **433192**.

[0195] Meanwhile, because intermediate region **44108** experiences lower stresses when golf club head **41101** is being swung and/or operated to hit a golf ball, a sleeve body wall of shaft sleeve body can be thinner at intermediate region **44108** than at part or all of coupler region **44109**, and/or intermediate region **44108** can have holes or recesses to reduce the weight of intermediate region **44108**. For example, the sleeve body wall of shaft sleeve body **42103** at intermediate region **44108** can comprise a thickness (e.g., an average thickness) of approximately 0.020 inch.

[0196] Turning now back to FIG. 31, in some embodiments, shaft sleeve body **42103** can comprise a width (e.g., outer diameter). The outer diameter of the shaft sleeve body **42103** can be greater than or equal to approximately 0.405 inches, and less than or equal to approximately 0.445 inches. In specific examples, the outer diameter of the shaft sleeve body can be 0.425 inches.

[0197] In some embodiments, the shaft bore can comprise a width (e.g., diameter) (FIG. 31). The diameter of the shaft sleeve body. The diameter of the shaft bore **433120** can decrease from the middle of the shaft bore to the bore bottom surface **43111**. The diameter of bore cap can be similar or the same as the diameter of the middle shaft bore **433130**. The diameter of the bore bottom **43150** can be greater than or equal to approximately 0.320 inches, and less than or equal to approximately 0.360 inches. In specific examples, the diameter of the bore bottom can be 0.340 inches. The diameter of the middle shaft bore **433130** can be greater than or equal to approximately 0.326 inches, and less than or equal to 0.366 inches. In specific examples, the diameter of the middle shaft bore **433130** can be 0.346 inches. The diameter of the cap bore **42115** can be greater than or equal to approximately 0.326 inches, and less than or equal to 0.366 inches. In specific examples, the diameter of the cap bore **42115** can be 0.346 inches.

[0198] In various embodiments, shaft sleeve body **42103** can comprise etching channels **43112** at shaft bore **433120** to provide a better surface area for epoxy bonding golf club shaft **41102** (FIG. 29) to shaft sleeve body **42103**. Etching channels **43112** can be located at coupler region **44109** (FIG. 32) and/or at part or all of intermediate region **44108** (FIG. 32), such as, for example, at a half of intermediate region **44108** (FIG. 32) closer to coupler region **44109** (FIG. 32).

[0199] In these or other embodiments, shaft sleeve body **42103** can comprise receiving groove **43113** (e.g., an undercut notch). As explained in greater detail below, receiving groove **43113** (FIG. 31) can communicate and interlock with extrusion portion **45114** (FIG. 33) of a shaft sleeve cap **42104** to secure shaft sleeve cap **42104** to shaft sleeve body **42103**. Thus, in many embodiments, receiving groove **43113** (FIG. 34) of the shaft sleeve body **42103** can complement extrusion portion **45114** (FIG. 33). In some embodiments, receiving groove **43113** can be located at cap interface region **44110** (FIG. 32). In many embodiments, receiving groove **43113** (FIG. 35B) can be located at an interface of cap interface region **44110** (FIG. 32) and coupler region **44109** (FIG. 32) (see also FIG. 31).

[0200] Turning ahead now in the drawings, FIG. 33A illustrates an upright side view of shaft sleeve cap **42104** decoupled from shaft sleeve body **42103** (FIG. 30), according to the embodiment of FIG. 29. FIG. 33B illustrates angled top view of shaft sleeve cap **42104** decoupled from shaft sleeve body **42103** (FIG. 30), according to the embodiment of FIG. 29. FIG. 34 illustrates a cross sectional view

of shaft sleeve cap **42104** along line XLV-XLV of FIG. 33A, according to the embodiment of FIG. 29. The shaft sleeve cap **42104** can further comprise a cap wall **45040** (FIG. 33A). The cap wall can comprise an outer cap wall **45115** on one end of the cap wall and an inner cap wall **45120** opposite the outer cap wall.

[0201] Referring to FIG. 33A, shaft sleeve cap **42104** can comprise an upper cap region **45050** and a lower cap region **45060**. The upper cap region **45050** can comprise a top ring **45045** at the top of the upper cap region **45050**, and a lower edge shelf **45055** at the lower end of the upper cap region **45050**. The upper cap region **45050** increases in diameter from top to bottom to the lower edge shelf **45055**. The lower cap region **45060** has a smaller outer diameter than the upper cap region **45050**.

[0202] The lower cap region **45060** can comprise an extrusion portion **45114** protruding from the outer cap wall **45115**. Extrusion portion **45114** can comprise a lip extending out from the outer cap wall **45115** (FIG. 34). Accordingly, extrusion portion **45114** can comprise a width (e.g. diameter) **45300** greater than a width **45200** of the remainder of cap wall of the lower cap region **45060** and/or the diameter of the shaft bore **43120** (FIG. 33A and FIG. 34). The width **45400** of the lower end shelf **45055** of the upper cap region **45050** is greater than the width **45300** of the extrusion portion **45114** of the lower cap region **45060** (FIG. 34).

[0203] The lower cap region **45060** of the shaft sleeve cap **42104** fits within the cap interface region **44110** and coupler region **44109** of the shaft sleeve body **42103** (FIG. 32). In one embodiment, the extrusion portion **45114** of the lower cap region **45060** of the shaft sleeve cap **42104** can be situated in and out of the receiving groove **43113** (FIG. 34) to couple and decouple shaft sleeve cap **42104** to and from shaft sleeve body **42103**. The receiving groove **43113** (FIG. 34) can complement the extrusion portion **45114** (FIG. 33) of the lower cap region **45060**. In these embodiments, the extrusion portion **45115** can be operable as a locking feature or snaps into position between the receiving groove **43113** (FIG. 34) of the shaft sleeve body **42103** (FIG. 32). In some embodiments, the extrusion portion **45115** can extend out at an upward angle to allow bending as the shaft sleeve cap **42104** is fitted into the shaft sleeve body **42103** (FIG. 32). Further referring to FIG. 32, when fitting the shaft sleeve cap **42104** into the shaft sleeve body **42103**, the lower end shelf **45055** of the shaft sleeve cap **42104** fits on top of the top ring of the cap interface region **44115** of the shaft sleeve body **42103** (FIG. 32).

[0204] The shaft sleeve cap **42104** can comprise a shaft bore **43120** (FIG. 33B). The shaft bore diameter **43130** is consistent throughout both the upper cap region **45050** and lower cap region **45060** (FIG. 34). The combination of the shaft sleeve cap **42104** (upper and lower region), and the cap interface region **44110** and coupler region **44109** of the shaft sleeve body **42103** prevents epoxy seepage during the assembly process.

[0205] The shaft sleeve cap **42104** can comprise one or more ribs **45202** protruding or extending into the shaft bore **43120** of the shaft sleeve cap **42104** parallel to each other along the inner cap wall **45120** from the upper cap region **45050** to the lower cap region **45060** (FIG. 33B). The ribs **45202** can provide additional sealing and securely couple the shaft sleeve cap **42104** into the shaft sleeve body **42103**.

The ribs **45202** can further provide securely centering the shaft of the golf club **41102** within the shaft sleeve **411100**.

[0206] The shaft sleeve cap **42104** provides stability compared to a shaft sleeve body **42103** without a shaft sleeve cap **42104**. The combination of the (1) overall design of the shaft sleeve cap **42104**, (2) ribs **45202** on the inner cap wall **45120** of the shaft sleeve cap **42104**, (3) the extrusion portion **45115** on the outer cap wall **45115** of the same, (4) the receiving groove **43113** of the shaft sleeve body **42103**, and (5) decreasing bore diameter from the middle of the shaft bore to the bore bottom surface **43111** of the shaft sleeve body **42103** can individually or in any combination thereof center the shaft of the golf club **41102** within both the top and bottom of the shaft sleeve **411100**, and provide greater stability to the shaft **41102** of FIG. 29. Centering increases the concentricity of the golf club shaft and reduces stresses upon the shaft during swinging of the golf club head and upon impact with a golf ball.

[0207] These factors, alone or in combination thereof, also provide damping (e.g., vibration) and stress reduction between golf club shaft **41102** (FIG. 29) and shaft sleeve body **42103** (FIG. 29). For example, shaft sleeve cap **42104** can act as a “shaft pillow” by increasing a concentricity of golf club shaft **41102** (FIG. 30) within shaft sleeve body **42103** (FIG. 31). In many embodiments, the concentricity of golf club shaft **41102** (FIG. 29) within shaft sleeve body **42103** (FIG. 30) can be strongly correlated with a durability of golf club shaft **41102** (FIG. 31). Accordingly, the ribs **45202** on the inner cap wall **45120** of the shaft sleeve cap **42104**, (2) the extrusion portion **45115** on the outer cap wall **45115** of the same, (3) the receiving groove **43113** of the shaft sleeve body **42103**, and (4) decreasing bore diameter from the middle of the shaft bore to the bore bottom surface **43111** of the shaft sleeve body **42103** can individually or in any combination thereof shaft sleeve cap **42104** can prevent breakage of golf club shaft **41102** (FIG. 29) and increase an overall life of golf club head **41101** (FIG. 29).

[0208] Turning back to FIG. 30, shaft sleeve body **42103** can comprise any suitable material. For example, in some embodiments, shaft sleeve body **22103** can comprise a metal or metal alloy (e.g., an aluminum alloy). In these examples, the aluminum alloy can comprise greater than or equal to approximately 70% aluminum and less than or equal to approximately 75% aluminum. In more specific examples, the aluminum alloy can comprise approximately 70%, 71%, 72%, 73%, 74%, or 75% aluminum.

[0209] The shaft sleeve cap **42104** can comprise any suitable material configured to permit cap wall **25115** (FIG. 25) to elastically compress as described above. For example, a shaft sleeve cap **22104** can comprise a polymer plastic material wherein the polymer plastic material can be a thermoplastic material, or a soft polymer plastic according to the Shore D durometer scale. The soft polymer plastic can be no greater than a **40**, **45**, **50**, **55** or **60** on the Shore D durometer scale. The soft polymer plastic can be no greater than 55 on the Shore D durometer scale. The polymer plastic material can be comprised of polystyrene, polyvinyl chloride, nylon, polymethacrylate, rubber, polycarbonate, synthetic rubber or co-polymers thereof.

[0210] In many embodiments, shaft sleeve body **42103** can comprise a shaft sleeve body mass, and shaft sleeve cap **42104** can comprise a shaft sleeve cap mass. Further, shaft sleeve **411100** can comprise a shaft sleeve mass comprising the shaft sleeve body mass and the shaft sleeve cap mass.

The shaft sleeve mass can be similar to the mass of the sleeve described above with respect to sleeve **1100** (FIG. 1).

[0211] In these or other embodiments, the shaft sleeve mass can be greater than or equal to approximately 4.0 grams, 4.1 grams, 4.2 grams, 4.3 grams, 4.4 grams, 4.5 grams, 4.6 grams, 4.7 grams, 4.8 grams, 4.9 grams or 5.0 grams. Further, the shaft sleeve body mass can be greater than or equal to approximately 4.2 grams and less than or equal to approximately 4.8 grams. The shaft sleeve body mass can be 4.5 grams. Further still, the shaft sleeve cap mass can be greater than or equal to approximately 3.8 grams, 3.9 grams, 4.0 grams, 4.1 grams, 4.2 grams, 4.3 grams or 4.4 grams. The shaft sleeve cap mass can be greater than or equal to approximately 0.1 grams and less than or equal to approximately 0.7 grams. In various embodiments, the shaft sleeve mass can be approximately 0.4 grams less than the mass of sleeve **1100** (FIG. 1). Further, the shaft sleeve mass combined with the securing fastener mass can be greater than or equal to approximately 7.2 grams. According, in various embodiments, shaft sleeve **411100** can offer weight advantages over shaft sleeve **1100** (FIG. 1).

[0212] Turning to FIG. 29, golf club head **41101** can comprise a disassembled club head mass and an assembled club head mass. The disassembled club head mass can be similar to the disassembled club head mass described above with respect to golf club head **101** (FIG. 1), and the assembled club head mass can be similar to the assembled club head mass described above with respect to golf club head **101** (FIG. 1).

[0213] In some embodiments, the disassembled club head mass can be greater than or equal to approximately 185 grams and less than or equal to approximately 205 grams. In these or other embodiments, the disassembled club head mass can be greater than or equal to approximately 192 grams.

[0214] In some embodiments, the assembled club head mass can be greater than or equal to approximately 188 grams and less than or equal to approximately 213 grams. In these or other embodiments, the assembled club head mass can be greater than or equal to approximately 199 grams.

[0215] Further, a ratio of the shaft sleeve mass to the disassembled club head mass can be less than or equal to approximately 2.0%, 2.2%, or 2.4%; a ratio of the shaft sleeve mass to the assembled club head mass can be less than or equal to approximately 1.95%, 2.16%, or 2.35%; a ratio of the shaft sleeve mass and the securing fastener mass to the disassembled club head mass can be less than or equal to approximately 3.4%, 3.6%, or 3.8%; and/or a ratio of the shaft sleeve mass and the securing fastener mass to the assembled club head mass can be less than or equal to approximately 3.3%, 3.5%, or 3.7%.

[0216] Meanwhile, golf club head **41101** can comprise an assembled club head CG associated with assembled club head CG vertical distance, and shaft sleeve **411100** can comprise a shaft sleeve CG associated with a shaft sleeve CG vertical distance. In these embodiments, assembled club head CG can be similar or identical to assembled club head CG **1050** (FIG. 1); the assembled club head CG vertical distance can be similar or identical to assembled club head CG vertical distance **1058** (FIG. 1); the shaft sleeve CG can be similar or identical to shaft sleeve CG **1032** (FIG. 1); and/or the shaft sleeve CG vertical distance can be similar or identical to shaft sleeve CG vertical distance **1159** measured either from the bottom of the club head (FIG. 1).

[0217] In many embodiments, the shaft sleeve CG vertical distance of the shaft sleeve **411100** (FIG. 31) can be greater than or equal to approximately 0.052 inches (approximately 1.32 millimeters), and less than or equal to 0.092 inches (approximately 2.34 millimeters) than shaft sleeve CG vertical distance of the shaft sleeve **211100** (FIG. 23). The shaft sleeve CG vertical distance of the shaft sleeve **411100** (FIG. 31) can be greater than or equal to approximately 0.042 inches (approximately 1.07 millimeters), and less than or equal to 0.062 inches (approximately 1.58 millimeters) than shaft sleeve CG vertical distance **1159** (FIG. 1). The shaft sleeve CG vertical distance of the golf coupling mechanism **411000** can be greater than or equal to approximately 43.5 millimeters from a sole bottom end of golf club head **41101** and less than or equal to approximately 47.0 millimeters from the sole bottom end of golf club head **41101**. In some embodiments, the shaft sleeve CG vertical distance of the golf coupling mechanism **411000** can be greater than or equal to approximately 43.5 millimeters, 43.6 millimeters, 43.7 millimeters, 43.8 millimeters, 43.9 millimeters, 44.0 millimeters, 44.1 millimeters, 44.2 millimeters, 44.3 millimeters, 44.4 millimeters, 44.5 millimeters, 44.6 millimeters, 44.7 millimeters, 44.8 millimeters, 44.9 millimeters, 45.0 millimeters, 45.1 millimeters, 45.2 millimeters, 45.3 millimeters, 45.4 millimeters, 45.5 millimeters, 45.6 millimeters, 45.7 millimeters, 45.8 millimeters, 45.9 millimeters, 46.0 millimeters, 46.1 millimeters, 46.2 millimeters, 46.3 millimeters, 46.4 millimeters, 46.5 millimeters, 46.6 millimeters, 46.7 millimeters, 46.8 millimeters, 46.9 millimeters, or 47.0 millimeters from the sole bottom end of golf club head **41101**. In some embodiments, the shaft sleeve CG vertical distance of the golf coupling mechanism **411000** can be less than or equal to approximately 43.5 millimeters, 43.6 millimeters, 43.7 millimeters, 43.8 millimeters, 43.9 millimeters, 44.0 millimeters, 44.1 millimeters, 44.2 millimeters, 44.3 millimeters, 44.4 millimeters, 44.5 millimeters, 44.6 millimeters, 44.7 millimeters, 44.8 millimeters, 44.9 millimeters, 45.0 millimeters, 45.1 millimeters, 45.2 millimeters, 45.3 millimeters, 45.4 millimeters, 45.5 millimeters, 45.6 millimeters, 45.7 millimeters, 45.8 millimeters, 45.9 millimeters, 46.0 millimeters, 46.1 millimeters, 46.2 millimeters, 46.3 millimeters, 46.4 millimeters, 46.5 millimeters, 46.6 millimeters, 46.7 millimeters, 46.8 millimeters, 46.9 millimeters, or 47.0 millimeters from the sole bottom end of golf club head **41101**. The shaft sleeve CG vertical distance of the golf coupling mechanism **411000** can be 45.3 millimeters from the sole bottom end of golf club head **41101**. The sole bottom end can be similar or identical to sole bottom end **10141** (FIG. 1).

[0218] In some embodiments, the shaft sleeve CG vertical distance of the golf coupling mechanism **411000** can be greater than or equal to approximately 32.0 millimeters, 32.1 millimeters, 32.3 millimeters, 32.4 millimeters, 32.5 millimeters, 32.6 millimeters, 32.7 millimeters, 32.8 millimeters, 32.9 millimeters, 33.0 millimeters, 33.1 millimeters, 33.2 millimeters, 33.3 millimeters, 33.4 millimeters, 33.5 millimeters, 33.6 millimeters, 33.7 millimeters, 33.8 millimeters, 33.9 millimeters, 34.0 millimeters, 34.1 millimeters, 34.2 millimeters, 34.3 millimeters, 34.4 millimeters, or 34.5 millimeters from the sole bottom end of golf club head **41101**. The shaft sleeve CG vertical distance of the golf coupling mechanism **411000** can be less than or equal to approximately 32.0 millimeters, 32.1 millimeters, 32.3 millimeters, 32.4 millimeters, 32.5 millimeters, 32.6 millime-

ters, 32.7 millimeters, 32.8 millimeters, 32.9 millimeters, 33.0 millimeters, 33.1 millimeters, 33.2 millimeters, 33.3 millimeters, 33.4 millimeters, 33.5 millimeters, 33.6 millimeters, 33.7 millimeters, 33.8 millimeters, 33.9 millimeters, 34.0 millimeters, 34.1 millimeters, 34.2 millimeters, 34.3 millimeters, 34.4 millimeters, or 34.5 millimeters from the sole bottom end of golf club head **41101**. The shaft sleeve CG vertical distance of the golf coupling mechanism can be 33.6 millimeters from the sole bottom end of golf club head **41101**.

[0219] Turning ahead in the drawings, FIG. **36** illustrates a flowchart for a method **47000**, according to an embodiment. In many embodiments, method **47000** can comprise a method of manufacturing a golf club head of one or more parts of the golf club head. The golf club head can be similar or identical to golf club head **41101** (FIG. **29**).

[0220] Method **47000** can comprise activity **47001** of providing a shaft sleeve. The shaft sleeve can be similar or identical to shaft sleeve **411100** (FIG. **30**). FIG. **36** illustrates an exemplary activity **47001**, according to the embodiment of FIG. **36**.

[0221] For example, in FIG. **36**, activity **47001** can comprise activity **48001** of providing (e.g., manufacturing) a shaft sleeve body. The shaft sleeve body can be similar or identical to shaft sleeve body **42103** (FIG. **37**).

[0222] Further, activity **47002** can comprise activity **48002** of providing (e.g., manufacturing) a shaft sleeve cap. The shaft sleeve cap can be similar or identical to shaft sleeve cap **42104** (FIG. **28**).

[0223] Referring now back to FIG. **36**, method **47000** can comprise activity **47002** of providing (e.g., manufacturing) a golf club head. The golf club head can be similar or identical to golf club head **41101** (FIG. **29**). In some embodiments, activity **47001** can be performed before activity **47002**, and vice versa. In other embodiments, activity **47001** and **47002** can be performed approximately simultaneously.

[0224] Further, method **47000** can comprise activity **47003** of inserting the shaft sleeve into a hosel bore of the golf club head. The hosel bore can be similar or identical to the hosel bore described above with respect to golf club head **41101** (FIG. **29**).

[0225] Also, method **4700** can comprise activity **47004** of inserting a golf club shaft into a shaft bore. The golf club shaft can be similar or identical to golf club shaft **41102** (FIG. **29**), and the shaft bore can be similar or identical to shaft bore **433120** (FIG. **31**).

[0226] Meanwhile, method **47000** can comprise activity **47005** of inserting the shaft sleeve cap into the shaft bore. In some embodiments, activity **47004** can be performed before activity **47005**, or vice versa. In other embodiments, activity **47004** and **47005** can be performed approximately simultaneously. In further embodiments, activity **47003** can be performed before activity **47004** and/or activity **47005**, and vice versa. In many embodiments, one or more of activities **47001-47003** can be performed before one or more of activities **47004-47005**, or vice versa (FIG. **37**).

[0227] Further still, method **47000** can comprise activity **47006** of securing the shaft sleeve to a hosel of the golf club head with a fastener. The hosel can be similar or identical to the hosel described above with respect to golf club head **41101** (FIG. **31**), and the fastener can be similar or identical to the fastener described above with respect to golf club head **21101** (FIG. **31**).

[0228] Although the golf coupling mechanisms and related methods herein have been described with reference to specific embodiments, various changes may be made without departing from the spirit or scope of the present disclosure. As an example, there may be embodiments where sleeve coupler set **3110** (FIGS. **3-7, 10, 14-17**), sleeve coupler set **12110** (FIG. **12**), sleeve coupler set **223110** (FIG. **22**), and/or sleeve coupler set **411100** can comprise only two sleeve couplers, and where receiver coupler set **3210** (FIGS. **3-4, 8-9, 11, 14-17**), receiver coupler set **13210** (FIG. **13**), the receiver coupler set of shaft receiver **213200** (FIG. **21**) and/or the receiver coupler set of shaft receiver **413200** (FIG. **29**) can comprise only two receiver couplers. In such embodiments, only two configurations may be possible between the shaft sleeve and the shaft receiver, and the golf coupler set may permit adjustment between two lie angles or two loft angles. Of course, there can also be embodiments with sleeve coupler sets having three, five, six, seven, eight, or more sleeve couplers, and receiver coupler sets having three, five, six, seven eight, or more receiver couplers, with corresponding increases in the number of possible lie and loft angle combinations.

[0229] Turning ahead in the drawings, FIG. **38** illustrates a side view of another embodiment of a shaft sleeve **511100** decoupled from golf club head **51101** (not shown). Golf club head **51101** (not shown) is substantially similar to golf club head **41101**, shown in FIG. **29**. FIG. **39** illustrates a cross sectional view of shaft sleeve **511100** along line IVIII-IVIII of FIG. **38**, according to the embodiment of FIG. **38** comprising tip weight **56000**. In many embodiments, golf coupling mechanism **511000** can comprise shaft sleeve **511100** configured to be coupled to an end of a golf club shaft (not shown), such as golf club shaft **41102**. In various embodiments, golf club head **51101** can be similar to golf club head **101** (FIG. **1**); golf coupling mechanism **511000** can be similar to golf coupling mechanism **1000** (FIG. **1**); and/or golf club shaft can be similar or identical to golf club shaft **102** (FIG. **1**). Accordingly, golf coupling mechanism **511000** can comprise shaft sleeve **511100** and shaft receiver **513200**. Meanwhile, shaft sleeve **511100** can be similar to shaft sleeve **1100** (FIG. **1**) and configured to receive a tip weight **56000**, and shaft receiver **513200** can be similar to shaft receiver **3200** (FIG. **3**) or shaft receiver **213200** (FIG. **22A**).

[0230] Referring to FIG. **38**, shaft sleeve **511100** comprises shaft sleeve body **52103** and shaft sleeve cap **52104**. In many embodiments, shaft sleeve body **52103** can comprise a sleeve coupler set **5231100** with one or more couplers protruding from a sleeve body outer wall **523130**. Likewise, shaft receiver **513200** can comprise a receiver coupler set configured to engage sleeve coupler set **523110** of shaft sleeve **511100**, such that rotation of shaft sleeve **511100** relative to shaft receiver **513200**. In these or other embodiments, sleeve coupler set **513110** can be similar to sleeve coupler set **3110** (FIG. **3**); sleeve body outer wall **523130** can be similar to sleeve outer wall **3130** (FIG. **3**); and/or the receiver coupler set can be similar to receiver coupler set **3210** (FIG. **3**). In these examples, the one or more couplers of sleeve coupler set **523110** can have substantially similar lengths. The length can be measured from a top end of the one or more couplers to a bottom end of the one or more couplers. In other examples, the one or more couplers of sleeve coupler set **523110** can have coupler lengths that vary.

The shaft sleeve cap **52104** can comprise a ferrule and can be operable to couple shaft sleeve body **52103** with golf club shaft (not shown).

[0231] Moving to the cross-sectional view of FIG. 39, shaft sleeve **511100** can comprise: (i) shaft bore **533120** configured to receive an end of golf club shaft (not shown), (ii) securing fastener bore **53105** at sleeve body bottom end **533192**, (iii) bore bottom surface **53111**; (iv) a tip weight **56000**; (v) a cap bore **52110** configured to receive an end of the golf club shaft and couple to the shaft bore **533120** and/or (vi) shaft sleeve top end **531191**. Securing fastener bore **53105** can be configured to receive a securing fastener (not shown) in order to secure shaft sleeve **511100** to shaft receiver **513200** (FIG. 29). Further, bore bottom surface **53111** can comprise a bottom surface (e.g., deepest surface) of shaft bore **532120** configured to abut a bottom surface **56100** of the tip weight **56000**. In many embodiments, shaft bore **533120** can be similar to shaft bore **3120** (FIG. 3); securing fastener bore **53105** can be similar or identical to the bore configured to receive securing fastener **3400** (FIG. 3); sleeve body bottom end **533192** can be similar or identical to sleeve bottom end **3192** (FIG. 3); the securing fastener can be similar or identical to securing fastener **3400** (FIG. 3); and/or shaft sleeve top end **531191** can be similar or identical to sleeve top end **1191** (FIG. 3).

[0232] FIG. 40 illustrates a side view of shaft sleeve **511100** with sleeve cap **52104** decoupled from shaft sleeve body **52103**, according to the embodiment of FIG. 38. Shaft sleeve body **52103** can be associated with one or more regions **54106**. For example, regions **54106** can comprise fastener region **54107**, intermediate region **54108**, coupler region **54109**, and cap interface region **54110**.

[0233] Further, when shaft sleeve cap **52104** is coupled to shaft sleeve body **52103**, shaft sleeve **511100** can comprise shaft sleeve height **53119**, shaft sleeve body height **53120**, shaft sleeve cap height **53121**, and shaft sleeve cap top height **53122**. Shaft sleeve height **53119** can refer to a distance from sleeve body bottom end **533192** to shaft sleeve top end **531191** measured approximately perpendicular to sleeve body bottom end **533192**. Meanwhile, shaft sleeve body height **53120** can refer to a distance from sleeve body bottom end **533192** to a top end of shaft sleeve body **52103** measured parallel to shaft sleeve height **53119**, and shaft sleeve cap height **53121** can refer to a distance from a bottom of shaft sleeve cap **52104** to shaft sleeve top end **531191** measured parallel to shaft sleeve height **53119**. Further, shaft sleeve cap top height **53122** can refer to a difference between shaft sleeve height **53119** and shaft sleeve body height **53120**.

[0234] Shaft sleeve height **53119** can be greater than previous embodiments in order to accommodate tip weight **56000**. For example, shaft sleeve height can be greater than or equal to 2.00 inches and less than or equal to 2.20 inches. In some examples, shaft sleeve height **53119** is 2.00 inches, 2.01 inches, 2.02 inch, 2.03 inches, 2.04 inches, 2.05 inches, 2.06 inches, 2.07 inches, 2.08 inches, 2.09 inches, 2.10 inches, 2.11 inches, 2.12 inches, 2.13 inches, 2.14 inches, 2.15 inches, 2.16 inches, 2.17 inches, 2.18 inches, 2.19 inches, or 2.20 inches. In a specific example, the shaft sleeve height **53119** is 2.10 inch.

[0235] Likewise, shaft sleeve body height **53120** can be extended, as compared to previous embodiments, to accommodate tip weight **56000**. Specifically, the shaft sleeve **52103** can be extended from the top end **531191**, rather than

the bottom end **531192**, such that the shaft bore **533120** is extended in a vertical direction. In some examples, shaft sleeve body height **53120** can be greater than or equal to approximately 1.78 inches and less than or equal to approximately 1.90 inches. For example, the shaft sleeve height **53119** can be 1.78 inches, 1.79 inches, 1.80 inches, 1.81 inches, 1.82 inches, 1.83 inches, 1.84 inches, 1.85 inches, 1.86 inches, 1.87 inches, 1.88 inches, 1.89 inches, or 1.90 inches. In specific examples, the shaft sleeve body height can be between 1.85 inches and 1.86 inches. Extending the shaft bore **533120** by way of the shaft sleeve body height **53120** ensures sufficient contact area between shaft bore **533120** and the golf club shaft for a secure fit between components. The increase in shaft sleeve body height **53120**, therefore, can be directly associated with the dimensions of the tip weight **56000**, such that the height increase is greater than or equal to a height of the tip weight **56600**.

[0236] Further, shaft sleeve cap height **53121** can be greater than or equal to approximately 0.46 inches and less than or equal to approximately 0.50 inches. In specific examples, shaft sleeve cap height **53121** can be approximately 0.48 inches.

[0237] Further still, shaft sleeve cap top height **53122** can be greater than or equal to approximately 0.23 inches and less than or equal to approximately 0.27 inches. In specific examples, shaft sleeve cap top height **53122** can be approximately 0.25 inches.

[0238] As mentioned above, weight receiving region **53124** is configured to retain a tip weight **56000**. The addition of tip weight **56000** within shaft bore **533120** allows a golf club head swing weight to be modified according to golfer specifications, independent of CG position. In other words, tip weight **56000** allows swing weight to be increased without moving the CG from the desired position. Tip weight **56000** can be secured within shaft bore **533120** via an epoxy or adhesive. Positioning the tip weight **56000** within the shaft sleeve **511100** can increase mass very far into the heel and toward the sole **10141**. This allows for improved CG modulation and the potential to maintain CG position or move the CG downward and toward the heel as desired.

[0239] Tip weight **56000** comprises a mass added to shaft sleeve **511100**. In some embodiments, tip weight **56000** comprises a mass ranging from 3 grams to 7 grams. For example, the tip weight **56000** can comprise a mass of 3 grams, 4 grams, 5 grams, 6 grams, or 7 grams. In a specific example, the tip weight **56000** comprises a mass of 5 grams.

[0240] Turning back to FIG. 38, shaft sleeve body **52103** comprises a width, or outer diameter. The outer diameter of shaft sleeve body can be greater than or equal to approximately 0.405 inch and less than or equal to 0.475 inch. For example, the outer diameter can be 0.405 inch, 0.410 inch, 0.415 inch, 0.420 inch, 0.425 inch, 0.430 inch, 0.435 inch, 0.440 inch, 0.445 inch, 0.450 inch, 0.455 inch, 0.460 inch, 0.465, 0.470 inch, or 0.475 inch. In specific examples, the shaft sleeve outer diameter can be 0.460 inch.

[0241] According to FIG. 39, shaft bore **533120** also comprises a width, or diameter. The diameter of shaft bore **533120** can decrease from the middle of the shaft bore to the bore bottom surface **53111**. The diameter of cap bore **52110** to the middle of shaft bore **533120** can be greater than approximately 0.400 inch and less than approximately 0.450 inch. In specific examples, the diameter of the middle of shaft bore **533120** can be approximately 0.430 inch. The

diameter of the bore bottom surface **53111** can be greater than or equal to approximately 0.320 inch and less than or equal to approximately 0.365 inch. In specific examples, the diameter of the bore bottom surface can be approximately 0.360 inch. The tip weight **56000** can comprise a cylindrical body having a body geometry corresponding shaft bore **53120**. Tip weight **56000** comprises a height **56150** defined as the perpendicular distance between weight bottom surface **56100** and weight top surface **56200**. The weight height ranges from 0.200 inch to 0.500 inch. For example, the weight height can be 0.200 inch, 0.220 inch, 0.240 inch, 0.260 inch, 0.280 inch, 0.300 inch, 0.320 inch, 0.340 inch, 0.360 inch, 0.380 inch, 0.400 inch, 0.420 inch, 0.440 inch, 0.460 inch, 0.480 inch, or 0.500 inch. In a specific example, the tip weight height **56150** of 0.260 inch. As mentioned above, the shaft sleeve body height **53120** can be extended by 0.200 inch to 0.500 inch to accommodate the tip weight height.

[0242] The tip weight **56000** can have a cylindrical shape so as to complement the interior shape of the shaft sleeve **511100**. In many embodiments, the tip weight **56000** can have a diameter that is equal to the diameter of the interior portion of the shaft sleeve **511100** that houses the tip weight **56000**. In other embodiments, the tip weight **56000** diameter can be slightly smaller than that of the interior shaft sleeve **511100** diameter. The tip weight **56000** fits into the shaft sleeve **511100** in a snug and secure manner, without substantial gaps, to prevent substantial lateral movement, twisting, or sliding of the weight **56000** during a swing.

[0243] In embodiments in which the tip weight **56000** is not fastened or secured with adhesive into the club head or shaft sleeve **511100**, it can be quickly and easily installed and removed. In these embodiments, the tip weight **56000** can be dropped into the shaft sleeve **511100** prior to the shaft sleeve **511100** receiving the shaft. To remove, the user can remove the shaft **51102** from the shaft sleeve **511100** and tip the shaft sleeve **511100** upside down, allowing the tip weight **56000** to fall out. This makes it simple for a golfer to change the weight **56000** as desired. In a fitting session, a fitter can easily interchange tip weights **56000** of various masses to optimize the feel and performance of the golf club for any given golfer.

[0244] Additional examples of such changes and others have been given in the foregoing description. Other permutations of the different embodiments having one or more of the features of the various figures are likewise contemplated. Accordingly, the specification, claims, and drawings herein are intended to be illustrative of the scope of the disclosure and is not intended to be limiting. It is intended that the scope of this application shall be limited only to the extent required by the appended claims.

[0245] The golf coupling mechanisms and related methods discussed herein may be implemented in a variety of embodiments, and the foregoing discussion of certain of these embodiments does not necessarily represent a complete description of all possible embodiments. Rather, the detailed description of the drawings, and the drawings themselves, disclose at least one preferred embodiment, and may disclose alternative embodiments.

[0246] Additionally, benefits, other advantages, and solutions to problems have been described with regard to specific embodiments. The benefits, advantages, solutions to problems, and any element or elements that may cause any benefit, advantage, or solution to occur or become more

pronounced, however, are not to be construed as critical, required, or essential features or elements of any or all of the claims, unless such benefits, advantages, solutions, or elements are expressly stated in such claims.

[0247] As the rules to golf may change from time to time (e.g., new regulations may be adopted or old rules may be eliminated or modified by golf standard organizations and/or governing bodies such as the United States Golf Association (USGA), the Royal and Ancient Golf Club of St. Andrews (R&A), etc.), golf equipment related to the apparatus, methods, and articles of manufacture described herein may be conforming or non-conforming to the rules of golf at any particular time. Accordingly, golf equipment related to the apparatus, methods, and articles of manufacture described herein may be advertised, offered for sale, and/or sold as conforming or non-conforming golf equipment. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

[0248] While the above examples may be described in connection with a driver-type golf club, the apparatus, methods, and articles of manufacture described herein may be applicable to other types of golf club such as a fairway wood-type golf club, a hybrid-type golf club, an iron-type golf club, a wedge-type golf club, or a putter-type golf club. Alternatively, the apparatus, methods, and articles of manufacture described herein may be applicable other type of sports equipment such as a hockey stick, a tennis racket, a fishing pole, a ski pole, etc.

[0249] Moreover, embodiments and limitations disclosed herein are not dedicated to the public under the doctrine of dedication if the embodiments and/or limitations: (1) are not expressly claimed in the claims; and (2) are or are potentially equivalents of express elements and/or limitations in the claims under the doctrine of equivalents.

What is claimed is:

1. A golf coupling mechanism between a golf club head and a golf club shaft;

the golf club head comprising:

a sole comprising a sole bottom end, a top portion opposite the sole portion, a heel portion, a toe portion opposite the heel portion, a rear portion, a front portion opposite the rear portion, the front portion comprising a strike face; and

a hosel;

the golf coupling mechanism comprising:

a shaft sleeve having a shaft sleeve height, measured perpendicularly from a shaft sleeve bottom end to a shaft sleeve top end, configured to be coupled to an end of the golf club shaft and a hosel;

wherein:

the shaft sleeve having a fastener region, an intermediate region, a coupler region, and a cap interface region comprises:

a shaft bore open at a shaft sleeve top end and comprising a bore bottom surface, such that the shaft bore is configured to receive the end of the golf club shaft;

a shaft sleeve body having a shaft sleeve body mass and comprising a sleeve outer wall;

wherein the shaft sleeve body further comprises a shaft sleeve body height measured perpendicularly between a shaft sleeve bottom end to a shaft sleeve top end;

a shaft sleeve cap having a shaft sleeve cap mass and configured to be coupled with the shaft sleeve;
 wherein the shaft sleeve cap further comprises a shaft sleeve cap total height, measured parallel to a shaft sleeve height between a shaft sleeve cap top end and a shaft sleeve cap bottom, and a shaft sleeve cap top height;
 a coupler set comprising:
 a first coupler protruding from the sleeve outer wall;
 a second coupler protruding from the sleeve outer wall;
 a third coupler protruding from the sleeve outer wall; and
 a fourth coupler protruding from the sleeve outer wall;
 the first coupler comprises a first arcuate surface curved throughout the first coupler;
 the second coupler comprises a second arcuate surface curved throughout the second coupler;
 the third coupler comprises a third arcuate surface curved throughout the third coupler;
 the fourth coupler comprises a fourth arcuate surface curved throughout the fourth coupler;
 a shaft sleeve mass, consisting of the shaft sleeve body mass, and the shaft sleeve cap mass defining a shaft sleeve center of gravity with a vertical distance of less than 50 mm above an exterior of the sole bottom end;
 wherein the first arcuate surface, second arcuate surface, third arcuate surface, and fourth arcuate surface are symmetric in profile;
 wherein the shaft bore is further configured to receive and retain a tip weight; and
 wherein the tip weight is disposed between the bore bottom surface and the end of the golf club shaft.

2. The golf coupling mechanism of claim 1, wherein:
 the shaft sleeve height ranges between 2.00 inches and 2.20 inches;
 the shaft sleeve body height ranges between 1.78 inches and 1.90 inches;
 the shaft sleeve cap total height ranges between 0.46 inch and 0.50 inch; and
 the shaft sleeve cap top height ranges between 0.23 inch and 0.27 inch.

3. The golf coupling mechanism of claim 1, wherein:
 the first arcuate surface, the second arcuate surface, the third arcuate surface, and the fourth arcuate surfaces are configured to restrict rotation of the shaft sleeve relative to the golf club head.

4. The golf coupling mechanism of claim 1, wherein:
 the shaft bore comprises a shaft bore diameter and the maximum shaft bore diameter is greater than 0.400 inch and less than 0.450 inch.

5. The golf coupling mechanism of claim 4, wherein:
 the shaft bore diameter at the bore bottom surface is in a range between 0.320 inch and 0.365 inch inclusive.

6. The golf coupling mechanism of claim 1, wherein:
 the first coupler, the second coupler, the third coupler, and the fourth coupler each comprise a coupler length; and
 the coupler length is greater than or equal to approximately 0.260 inch and less than or equal to approximately 0.38 inch.

7. The golf coupling mechanism of claim 1, wherein:
 the tip weight comprises a tip weight mass ranging from 3 grams to 7 grams and a tip weight height between 0.200 inch and 0.500 inch.

8. A golf coupling mechanism for a golf club head and a golf club shaft;

the golf club head comprising:

a sole comprising a sole bottom end, a top portion opposite the sole portion, a heel portion, a toe portion opposite the heel portion, a rear portion, a front portion opposite the rear portion, the front portion comprising a strike face; and

a hosel;

the golf coupling mechanism comprising:

a shaft sleeve having a shaft sleeve height, measured perpendicularly from a shaft sleeve bottom end to a shaft sleeve top end, configured to be coupled to an end of the golf club shaft and a hosel;

wherein:

the shaft sleeve having a fastener region, an intermediate region, a coupler region, and a cap interface region comprises:

a shaft bore open at a shaft sleeve top end and comprising a bore bottom surface, such that the shaft bore is configured to receive the end of the golf club shaft;

a shaft sleeve body having a shaft sleeve body mass and comprising a sleeve outer wall;

wherein the shaft sleeve body further comprises a shaft sleeve body height, measured perpendicularly between a shaft sleeve bottom end to a shaft sleeve top end;

a shaft sleeve cap having a shaft sleeve cap mass and configured to be coupled with the shaft sleeve;

wherein the shaft sleeve cap further comprises a shaft sleeve cap total height, measured parallel to a shaft sleeve height between a shaft sleeve cap top end and a shaft sleeve cap bottom, and a shaft sleeve cap top height;

a coupler set comprising:

a first coupler protruding from the sleeve outer wall;
 a second coupler protruding from the sleeve outer wall;

a third coupler protruding from the sleeve outer wall; and

a fourth coupler protruding from the sleeve outer wall;

the first coupler comprises a first arcuate surface curved throughout the first coupler;

the second coupler comprises a second arcuate surface curved throughout the second coupler;

the third coupler comprises a third arcuate surface curved throughout the third coupler;

the fourth coupler comprises a fourth arcuate surface curved throughout the fourth coupler; and

the shaft receiver comprises:

a fifth coupler indented into a receiver inner wall;
 a sixth coupler indented into the receiver inner wall;

a seventh coupler indented into the receiver inner wall; and

an eighth coupler indented into the receiver inner wall;

the fifth coupler comprises a fifth arcuate surface curved throughout the fifth coupler;

the sixth coupler comprises a sixth arcuate surface curved throughout the sixth coupler;
 the seventh coupler comprises a seventh arcuate surface curved throughout the seventh coupler;
 the eighth coupler comprises an eighth arcuate surface curved throughout the eighth coupler;
 wherein the coupler set is asymmetric in profile such that the first coupler is longer at a first part of a sleeve body outer wall of the shaft sleeve than the second, third, and fourth couplers;
 wherein the shaft bore is further configured to receive and retain a tip weight; and
 wherein the tip weight is disposed between a bottom surface of the shaft bore and the end of the golf club shaft.

9. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 the second coupler, third coupler, and fourth coupler are symmetrical in profile.

10. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 the fifth coupler is longer at a first part of the receiver inner wall than the sixth coupler, the seventh coupler, and the eighth coupler.

11. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 the sixth coupler, seventh coupler, and eighth coupler are symmetrical in profile.

12. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 the receiver coupler set of the shaft receiver is configured to engage the coupler set of the shaft sleeve and restrict rotation of the shaft sleeve relative to the golf club head.

13. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 the coupler set protrudes from a top section of the sleeve outer wall towards the sleeve top end.

14. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 the receiver coupler set is indented into a top section of the receiver inner wall.

15. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 a portion of one or more of the first coupler, second coupler, third coupler, and fourth coupler, of the sleeve coupler set, protrudes past a top end of the shaft receiver.

16. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 a portion of one or more of the fifth coupler, sixth coupler, seventh coupler, and eighth coupler, of the sleeve coupler set, may protrude past a bottom end of one or more couplers of the coupler set.

17. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 a contact area defined by the interface between the first coupler and one of the sixth coupler, seventh coupler, and eighth coupler is approximately 51% to approximately 79%.

18. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 a contact area defined by the interface between the first coupler and the fifth coupler is approximately 90% to approximately 95%.

19. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 a contact area defined by the interface between one of the second coupler, third coupler, and fourth coupler, and one of the sixth coupler, seventh coupler, and eighth coupler is approximately 90% to approximately 95%.

20. The golf coupling mechanism for a golf club head and a golf club shaft of claim **8**, wherein:
 the shaft sleeve height ranges between 2.00 inches and 2.20 inches;
 the shaft sleeve body height ranges between 1.78 inches and 1.90 inches;
 the shaft sleeve cap total height ranges between 0.46 inch and 0.50 inch; and
 the shaft sleeve cap top height ranges between 0.23 inch and 0.27 inch.

* * * * *